

Easy Factor Graph: the flexible and efficient tool for managing undirected graphical models

Casalino Andrea
andrecasa91@gmail.com

1 What is EFG	1
2 Theoretical background on factor graphs	3
2.1 Preliminaries	3
2.2 Message Passing	7
2.2.1 Belief propagation	8
2.2.2 Message Passing	9
2.3 Maximum a posteriori estimation	13
2.4 Gibbs sampling	14
2.5 Sub graphs	15
2.6 Learning	15
2.6.1 Learning of unconditioned model	17
2.6.1.1 Gradient of α	17
2.6.1.2 Gradient of β	18
2.6.2 Learning of conditioned model	19
2.6.2.1 Gradient of β	20
2.6.3 Learning of modular structure	21
2.6.3.1 Gradient of α	21
2.6.3.2 Gradient of β	21
3 Files representing factor graphs	23
4 Samples	27
4.1 Sample 01: Potential handling	27
4.1.1 part 01	27
4.1.2 part 02	27
4.2 Sample 02: Belief propagation, part A	28
4.2.1 part 01	29
4.2.2 part 02	29
4.2.3 part 03	31
4.3 Sample 03: Belief propagation, part B	31
4.3.1 part 01	34
4.3.2 part 02	34
4.3.3 part 03	35
4.3.4 part 04	35
4.4 Sample 04: Hidden Markov model like structure	35
4.5 Sample 05: Matricial structure	36
4.6 Sample 06: Learning, part A	37
4.6.1 part 01	37
4.6.2 part 02	37
4.6.3 part 03	38
4.6.4 part 04	38
4.7 Sample 07: Learning, part B	39

4.8 Sample 08: Sub-graphing	39
4.8.1 part 01	39
4.8.2 part 02	40
5 Namespace Index	43
5.1 Namespace List	43
6 Hierarchical Index	45
6.1 Class Hierarchy	45
7 Class Index	49
7.1 Class List	49
8 Namespace Documentation	51
8.1 EFG Namespace Reference	51
8.1.1 Detailed Description	51
8.2 EFG::categoric Namespace Reference	51
8.2.1 Detailed Description	52
8.2.2 Function Documentation	52
8.2.2.1 getComplementary()	52
8.3 EFG::distribution Namespace Reference	52
8.3.1 Detailed Description	53
8.4 EFG::distribution::factor Namespace Reference	53
8.4.1 Detailed Description	53
8.5 EFG::distribution::factor::cns Namespace Reference	54
8.5.1 Detailed Description	54
8.6 EFG::distribution::factor::modif Namespace Reference	54
8.6.1 Detailed Description	54
8.7 EFG::io Namespace Reference	54
8.7.1 Detailed Description	55
8.8 EFG::io::json Namespace Reference	55
8.8.1 Detailed Description	55
8.9 EFG::io::xml Namespace Reference	55
8.9.1 Detailed Description	55
8.10 EFG::iterator Namespace Reference	55
8.10.1 Detailed Description	56
8.10.2 Function Documentation	56
8.10.2.1 forEach()	56
8.10.2.2 forEachConditioned()	56
8.11 EFG::model Namespace Reference	57
8.11.1 Detailed Description	57
8.12 EFG::nodes Namespace Reference	57
8.12.1 Detailed Description	58
8.13 EFG::train Namespace Reference	58

8.13.1 Detailed Description	58
8.14 EFG::train::handler Namespace Reference	58
8.14.1 Detailed Description	58
9 Class Documentation	59
9.1 EFG::nodes::Base Class Reference	59
9.2 EFG::train::handler::BaseHandler Class Reference	59
9.3 EFG::train::BasicExtractor Class Reference	60
9.4 EFG::nodes::BeliefAware Class Reference	60
9.5 EFG::nodes::BeliefPropagator Class Reference	61
9.6 EFG::iterator::Bidirectional Class Reference	62
9.6.1 Detailed Description	62
9.7 EFG::train::handler::BinaryHandler Class Reference	62
9.8 EFG::categoric::Combination Class Reference	63
9.8.1 Detailed Description	63
9.8.2 Constructor & Destructor Documentation	63
9.8.2.1 Combination() [1/2]	63
9.8.2.2 Combination() [2/2]	64
9.8.3 Member Function Documentation	64
9.8.3.1 operator<()	64
9.8.3.2 operator=()	64
9.9 EFG::train::handler::CompositeHandler Class Reference	65
9.10 EFG::model::ConditionalRandomField Class Reference	65
9.10.1 Constructor & Destructor Documentation	66
9.10.1.1 ConditionalRandomField() [1/2]	66
9.10.1.2 ConditionalRandomField() [2/2]	66
9.10.2 Member Function Documentation	66
9.10.2.1 insertTunable()	66
9.11 EFG::nodes::Connection Struct Reference	67
9.12 EFG::distribution::Distribution Class Reference	67
9.12.1 Detailed Description	68
9.12.2 Member Function Documentation	68
9.12.2.1 find()	68
9.12.2.2 findRaw()	69
9.12.2.3 getFinder()	69
9.12.2.4 getIterator()	69
9.12.2.5 getProbabilities()	69
9.13 EFG::distribution::DistributionFinder Class Reference	70
9.13.1 Detailed Description	70
9.13.2 Constructor & Destructor Documentation	70
9.13.2.1 DistributionFinder()	70
9.13.3 Member Function Documentation	71

9.13.3.1 find()	71
9.14 EFG::distribution::DistributionInstantiable Class Reference	71
9.15 EFG::distribution::DistributionIterator Class Reference	72
9.15.1 Detailed Description	72
9.15.2 Constructor & Destructor Documentation	72
9.15.2.1 DistributionIterator()	72
9.15.3 Member Function Documentation	73
9.15.3.1 getCombination()	73
9.15.3.2 getImage()	73
9.15.3.3 getImageRaw()	73
9.15.3.4 getNumberOfValues()	73
9.16 EFG::distribution::DistributionSetter Class Reference	74
9.16.1 Member Function Documentation	74
9.16.1.1 setAllImagesRaw()	74
9.16.1.2 setImageRaw()	74
9.17 EFG::Error Class Reference	75
9.17.1 Detailed Description	75
9.18 EFG::distribution::Evaluator Class Reference	76
9.18.1 Member Function Documentation	76
9.18.1.1 evaluate()	76
9.19 EFG::distribution::factor::EvaluatorBasic Class Reference	76
9.19.1 Detailed Description	77
9.19.2 Member Function Documentation	77
9.19.2.1 evaluate()	77
9.20 EFG::distribution::factor::EvaluatorExponential Class Reference	78
9.20.1 Detailed Description	78
9.20.2 Member Function Documentation	78
9.20.2.1 evaluate()	78
9.21 EFG::nodes::EvidenceAware Class Reference	79
9.22 EFG::nodes::EvidencesChanger Class Reference	79
9.22.1 Member Function Documentation	80
9.22.1.1 addEvidence()	80
9.22.1.2 resetEvidences()	80
9.23 EFG::nodes::EvidencesSetter Class Reference	81
9.23.1 Member Function Documentation	81
9.23.1.1 setEvidences()	81
9.24 EFG::io::Exporter Class Reference	82
9.25 EFG::io::xml::Exporter Class Reference	82
9.25.1 Member Function Documentation	83
9.25.1.1 exportToXml()	83
9.26 EFG::io::json::Exporter Class Reference	83
9.26.1 Member Function Documentation	83

9.26.1.1 exportToJson()	84
9.27 EFG::distribution::factor::modif::Factor Class Reference	84
9.28 EFG::distribution::factor::cnst::Factor Class Reference	85
9.28.1 Detailed Description	86
9.28.2 Constructor & Destructor Documentation	86
9.28.2.1 Factor() [1/3]	86
9.28.2.2 Factor() [2/3]	87
9.28.2.3 Factor() [3/3]	87
9.29 EFG::distribution::factor::modif::FactorExponential Class Reference	87
9.30 EFG::distribution::factor::cnst::FactorExponential Class Reference	88
9.30.1 Detailed Description	89
9.30.2 Constructor & Destructor Documentation	89
9.30.2.1 FactorExponential()	89
9.30.3 Member Function Documentation	89
9.30.3.1 getWeight()	89
9.31 EFG::iterator::Forward Class Reference	89
9.31.1 Detailed Description	90
9.31.2 Member Function Documentation	90
9.31.2.1 operator==()	90
9.32 EFG::nodes::GibbsSampler Class Reference	90
9.32.1 Member Function Documentation	91
9.32.1.1 getHiddenSetSamples()	91
9.33 EFG::train::GradientDescend< Extractor > Class Template Reference	91
9.33.1 Member Function Documentation	91
9.33.1.1 train()	92
9.34 EFG::model::Graph Class Reference	92
9.34.1 Detailed Description	92
9.35 EFG::categoric::Group Class Reference	93
9.35.1 Detailed Description	93
9.35.2 Constructor & Destructor Documentation	93
9.35.2.1 Group() [1/4]	93
9.35.2.2 Group() [2/4]	94
9.35.2.3 Group() [3/4]	94
9.35.2.4 Group() [4/4]	94
9.35.3 Member Function Documentation	95
9.35.3.1 add()	95
9.35.3.2 operator=()	95
9.35.3.3 replace() [1/2]	95
9.35.3.4 replace() [2/2]	96
9.35.3.5 size()	96
9.36 EFG::nodes::HiddenClusters Struct Reference	96
9.37 EFG::io::xml::Importer Class Reference	97

9.37.1 Member Function Documentation	97
9.37.1.1 importFromXml()	97
9.38 EFG::io::Importer Class Reference	98
9.39 EFG::distribution::factor::cnst::IndicatorFactor Class Reference	98
9.39.1 Detailed Description	99
9.39.2 Constructor & Destructor Documentation	99
9.39.2.1 IndicatorFactor()	99
9.40 EFG::nodes::InsertCapable Class Reference	99
9.40.1 Member Function Documentation	100
9.40.1.1 absorbModel()	100
9.40.1.2 insert() [1/2]	101
9.40.1.3 insert() [2/2]	101
9.40.1.4 insertCopy() [1/2]	101
9.40.1.5 insertCopy() [2/2]	102
9.41 EFG::nodes::InsertTunableCapable Class Reference	102
9.41.1 Member Function Documentation	102
9.41.1.1 insertTunableCopy() [1/2]	103
9.41.1.2 insertTunableCopy() [2/2]	103
9.42 EFG::nodes::Node Struct Reference	103
9.43 EFG::nodes::NodesAware Class Reference	104
9.43.1 Member Function Documentation	104
9.43.1.1 getVariables()	104
9.44 EFG::nodes::PropagationResult Struct Reference	105
9.45 EFG::nodes::QueryHandler Class Reference	105
9.45.1 Member Function Documentation	105
9.45.1.1 getHiddenSetMAP()	105
9.45.1.2 getJointMarginalDistribution()	105
9.45.1.3 getMAP()	106
9.45.1.4 getMarginalDistribution()	106
9.46 EFG::model::RandomField Class Reference	106
9.46.1 Member Function Documentation	107
9.46.1.1 getGradient()	107
9.46.1.2 insertTunable()	107
9.47 EFG::categoric::Range Class Reference	108
9.47.1 Detailed Description	108
9.47.2 Constructor & Destructor Documentation	108
9.47.2.1 Range()	108
9.47.3 Member Function Documentation	109
9.47.3.1 get()	109
9.47.3.2 operator++()	109
9.47.3.3 operator==()	109
9.48 EFG::iterator::StlBidirectional< IteratorStl > Class Template Reference	110

9.48.1 Detailed Description	110
9.48.2 Member Function Documentation	110
9.48.2.1 operator==()	111
9.49 EFG::train::StochasticExtractor Class Reference	111
9.50 EFG::nodes::StructureAware Class Reference	111
9.50.1 Member Data Documentation	112
9.50.1.1 factors	112
9.50.1.2 factorsExp	112
9.51 EFG::nodes::StructureTunableAware Class Reference	112
9.51.1 Member Function Documentation	113
9.51.1.1 getFactorsTunable()	113
9.51.1.2 getWeights()	113
9.51.2 Member Data Documentation	113
9.51.2.1 factorsTunable	113
9.52 EFG::train::Trainable Class Reference	114
9.52.1 Detailed Description	114
9.52.2 Member Function Documentation	114
9.52.2.1 getGradient()	114
9.52.2.2 setOnes()	115
9.52.2.3 setWeights()	115
9.53 EFG::train::Trainer Class Reference	115
9.53.1 Member Function Documentation	116
9.53.1.1 train()	116
9.54 EFG::train::TrainHandler Class Reference	116
9.55 EFG::train::TrainSet Class Reference	117
9.55.1 Constructor & Destructor Documentation	117
9.55.1.1 TrainSet() [1 / 2]	117
9.55.1.2 TrainSet() [2 / 2]	117
9.55.2 Member Function Documentation	118
9.55.2.1 getRandomSubSet()	118
9.56 EFG::train::TrainSetExtractor Class Reference	118
9.57 EFG::train::handler::UnaryHandler Class Reference	119
9.58 EFG::categoric::Variable Class Reference	119
9.58.1 Detailed Description	120
9.58.2 Constructor & Destructor Documentation	120
9.58.2.1 Variable()	120

Chapter 1

What is EFG

Easy Factor Graph (EFG), is a simple and efficient C++ library for managing undirected graphical models.

EFG allows you to build step by step a graphical model made of unary or binary potentials, i.e. factors involving one or two variables. It contains several tools for exporting and importing graphs from textual file. EFG allows you to perform all the probabilistic queries described in Chapter 2, from marginal probabilities computation to learning the tunable parameters of a graph. All the work is internally done by EFG: you just have to focus on what you need to compute.

A nice Graphic User Interface application, described in ??, can be exploited to handle small and medium size structure.

The rest of this guide is structured as follows. Chapter 2 will introduce the main theoretical concepts about factor graphs, with the aim of explaining the capabilities of EFG. Chapter 3 will explain the format of the xml files adopted to represent factor graphs, exploited when importing or exporting the models to or from textual files. Chapter 4 will present the examples adopted for showing how EFG works. All the remaining Chapters, will describe the structure of the classes constituting EFG ¹.

¹A similar guide, but in a html format, is also available at http://www.andreacasalino.altervista.org/__EFG_doxy_guide/index.html.

Chapter 2

Theoretical background on factor graphs

This Section will provide a background about the basic concepts in probabilistic graphical models. Moreover, a precise notation will be introduced and used for the rest of this guide.

2.1 Preliminaries

This library is intended for managing network of categorical variables. Formally, the generic categorical variable V has a discrete domain Dom :

$$Dom(V) = \{v_0, \dots, v_n\} \quad (2.1)$$

Essentially, $Dom(V)$ contains all the possible realizations of V . The above notation will be adopted for the rest of the guide: capital letters will refer to variable names, while non capital refer to their realizations. Group of categorical variables can be considered categorical variables too, having a domain that is the Cartesian product of the domains of the variables constituting the group. Suppose X is obtained as the union of variables $V_{1,2,3,4}$, i.e. $X = \bigcup_{i=1}^4 V_i$, then:

$$Dom(X) = Dom(V_1) \times Dom(V_2) \times Dom(V_3) \times Dom(V_4) \quad (2.2)$$

The generic realization x of X is a set of realizations of the variables $V_{1,2,3,4}$, i.e. $x = \{v_1, v_2, v_3, v_4\}$. Suppose $V_{1,2,3}$ have the domains reported in the tables 2.1. The union $X = \bigcup_{i=1}^3 V_i$ is a categoric variable whose domain is made by the combinations reported in table 2.2.

The entire population of variables contained in a model is a set denoted as $\mathcal{V} = \{V_1, \dots, V_m\}$. As will be exposed in the following, the probability of $\bigcup_{V_i \in \mathcal{V}} V_i$ ¹ is computed as the product of a certain number of components called factors.

Knowing the joint probability of $V_{1,\dots,m}$, the probability distribution of a subset $S \subset \{V_1, \dots, V_m\}$ can be in general (not only for graphical models) obtained through marginalization. Assume C is the complement of S : $C \cup S = \bigcup_{i=1}^m V_i$ and $C \cap S = \emptyset$, then:

$$\mathbb{P}(S = s) = \sum_{\forall \hat{c} \in Dom(C)} \mathbb{P}(S = s, C = \hat{c}) \quad (2.3)$$

¹Which is the joint probability distribution of all the variables in a model

$Dom(V_1)$	$Dom(V_2)$	$Dom(V_3)$
v_{10}	v_{20}	v_{30}
v_{11}	v_{21}	v_{31}
	v_{22}	

Table 2.1 Example of domains for the group of variables $V_{1,2,3}$.

$Dom(X) = Dom(V_1 \cup V_2 \cup V_3)$
$x_0 = \{v_{10}, v_{20}, v_{30}\}$
$x_1 = \{v_{10}, v_{20}, v_{31}\}$
$x_2 = \{v_{11}, v_{20}, v_{30}\}$
$x_3 = \{v_{11}, v_{20}, v_{31}\}$
$x_4 = \{v_{10}, v_{21}, v_{30}\}$
$x_5 = \{v_{10}, v_{21}, v_{31}\}$
$x_6 = \{v_{11}, v_{21}, v_{30}\}$
$x_7 = \{v_{11}, v_{21}, v_{31}\}$
$x_8 = \{v_{10}, v_{22}, v_{30}\}$
$x_9 = \{v_{10}, v_{22}, v_{31}\}$
$x_{10} = \{v_{11}, v_{22}, v_{30}\}$
$x_{11} = \{v_{11}, v_{22}, v_{31}\}$

Table 2.2 Example of domains for the group of variables $V_{1,2,3}$.

In the above computation, variables in C were marginalized. Indeed they were in a certain sense eliminated, since the probability of the sub set S was of interest, no matter the realizations of all the variables in C .

A factor, sometimes also called a potential, is a positive real function describing the correlation existing among a subset of variables $D^i \subset \mathcal{V}$. Suppose factor Φ_i involves $\{X, Y, Z\}$, i.e. $D^i = \{X, Y, Z\}$. Then, $\Phi_i(X, Y, Z)$ is a function defined over $Dom(D^i)$. More formally:

$$\Phi_i(D^i) = \Phi_i(X, Y, Z) : \text{DOMAIN}(X) \times \text{DOMAIN}(Y) \times \text{DOMAIN}(Z) \longrightarrow \mathbb{R}^+ \quad (2.4)$$

The aim of Φ_i is to assume 'high' values for those combinations $d^i = \{x, y, z\}$ that are probable and low values (at least a null) for those being improbable. The entire population of factors $\{\Phi_1, \dots, \Phi_p\}$ is considered for computing $\mathbb{P}(V_{1,\dots,m})$, i.e. the joint probability distribution of all the variables in the model. The energy function E of a graph is defined as the product of the factors:

$$E(V_{1,\dots,m}) = \Phi_1(D^1) \cdot \dots \cdot \Phi_p(D^p) = \prod_{i=1}^p \Phi_i(D^i) \quad (2.5)$$

E is addressed for computing the joint probability distribution of the variables in \mathcal{V} :

$$\mathbb{P}(V_{1,\dots,m}) = \frac{E(V_{1,\dots,m})}{\mathcal{Z}} \quad (2.6)$$

where \mathcal{Z} is a normalization coefficient defined as follows:

$$\mathcal{Z} = \sum_{\forall \tilde{V}_{1,\dots,m} \in Dom(\bigcup_{i=1,\dots,m} V_i)} E(\tilde{V}_{1,\dots,m}) \quad (2.7)$$

Although the general theory behind graphical models supports the existence of generic multivaried factors, this library will address only two possible types:

- Binary potentials: they involve a pair of variables.
- Unary potentials: they involve a single variable.

We can store the values in the image of a Binary potential in a two dimensional table. For instance, suppose Φ_b involves variables A and B , whose domains contains 3 and 5 possible values respectively:

$$\begin{aligned} \text{DOM}(A) &= \{a_1, a_2, a_3\} \\ \text{DOM}(B) &= \{b_1, b_2, b_3, b_4, b_5\} \end{aligned} \quad (2.8)$$

The values assumed by $\Phi_b(A, B)$ are described by table 2.3. Essentially, $\Phi_b(A, B)$ tells us that the combinations $\{a_0, b_1\}$, $\{a_2, b_2\}$ are highly probable; while $\{a_0, b_0\}$, $\{a_1, b_1\}$ and $\{a_2, b_4\}$ are moderately probable. Let be

	b_0	b_1	b_2	b_3	b_4
a_0	1	4	0	0	0
a_1	0	1	0	0	0
a_2	0	0	5	0	1

Table 2.3 The values in the image of $\Phi_b(A, B)$.

a_0	a_1	a_2
0	2	0.5

Table 2.4 The values in the image of $\Phi_u(A)$.

$\Phi_u(A)$ a Unary potential involving variable A . The values characterizing Φ_u can be stored in a simple vector, see table 2.4. If $\Phi_b(A, B)$ would be the only potential in the model, the joint probability density of A and B will assume the following values ²:

$$\mathbb{P}(a_0, b_1) = \frac{\Phi_b(a_0, b_1)}{\mathcal{Z}} = \frac{4}{\mathcal{Z}} = 0.3333 \quad (2.9)$$

$$\mathbb{P}(a_2, b_2) = \frac{\Phi_b(a_2, b_2)}{\mathcal{Z}} = \frac{5}{\mathcal{Z}} = 0.4167 \quad (2.10)$$

$$\mathbb{P}(a_0, b_0) = \frac{\Phi_b(a_0, b_0)}{\mathcal{Z}} = \mathbb{P}(a_1, b_1) = \mathbb{P}(a_2, b_4) = \frac{1}{\mathcal{Z}} = 0.0833 \quad (2.11)$$

since \mathcal{Z} is equal to:

$$\mathcal{Z} = \sum_{\forall i=\{0,1,2\}, \forall j=\{0,1,2,3,4\}} \Phi_b(A = a_i, B = b_j) = 12 \quad (2.12)$$

Both Unary and Binary potentials, can be of two possible classes:

- Simple shape. The potential is simply described by a set of values characterizing the image of the factor. $\Phi_b(A, B)$ and $\Phi_u(A)$ of the previous example are both Simple shapes. Class Potential_Shape handles this kind of factors.
- Exponential shape. They are indicated with Ψ_i and their image set is defined as follows:

$$\Psi_i(X) = \exp(w \cdot \Phi_i(X)) \quad (2.13)$$

where Φ_i is a Simple shape. Class Potential_Exp_Shape handles this kind of factors. The weight w , can be tunable or not. In the first case, w is a free parameter whose value is decided after training the model (see Section 2.6), otherwise is a constant. Exponential shapes with fixed weight will be denoted with $\bar{\Psi}_i$.

Figure 2.1 resumes all the possible categories of factors that can be present in the models handled by this library.

Figure 2.2 reports an example of undirected graph. Set \mathcal{V} is made of 4 variables: A, B, C, D . There are 5 Binary potentials and 2 Unary ones. The graphical notation adopted for Fig. 2.2 will be adopted for the rest of this guide. Weights α, β, γ and δ are assumed for respectively $\Psi_{AC}, \Psi_{AB}, \Psi_{CD}, \Psi_B$. For the sake of clarity, the joint probability of the variables in Fig. 2.2 is computable as follows:

$$\begin{aligned} \mathbb{P}(A, B, C, D) &= \frac{E(A, B, C, D)}{\mathcal{Z}(\alpha, \beta, \gamma, \delta)} = \frac{E(A, B, C, D)}{\sum_{\tilde{A}, \tilde{B}, \tilde{C}, \tilde{D}} E(\tilde{A}, \tilde{B}, \tilde{C}, \tilde{D})} \\ E(A, B, C, D) &= \Phi_A(A) \cdot \exp(\alpha \Phi_{AC}(A, C)) \cdot \exp(\beta \Phi_{AB}(A, B)) \cdot \dots \\ &\dots \Phi_{BC}(B, C) \cdot \exp(\gamma \Phi_{CD}(C, D)) \cdot \Phi_{BD}(B, D) \cdot \exp(\delta \Phi_B(B)) \end{aligned} \quad (2.14)$$

Graphical models are mainly used for performing belief propagation. Subset $\mathcal{O} = \{O_1, \dots, O_f\} \subset \mathcal{V}$ is adopted for denoting the set of evidences: those variables in the net whose value become known. \mathcal{O} can be dynamical or

²combinations having a null probability were omitted




Figure 2.1 All the possible categories of factors, with the corresponding notation.




Figure 2.2 Example of graph: the legend of the right applies.

not. The hidden variables are contained in the complementary set $\mathcal{H} = \{H_1, \dots, H_t\}$. Clearly $\mathcal{O} \cup \mathcal{H} = \mathcal{V}$ and $\mathcal{O} \cap \mathcal{H} = \emptyset$. H will be used for referring to the union of all the variables in the hidden set:

$$H = \bigcup_{i=1}^t H_i \quad (2.15)$$

while O is used for indicating the evidences:

$$O = \bigcup_{i=1}^f O_i \quad (2.16)$$

Knowing the joint probability distribution of variables in \mathcal{V} (equation (2.6)) the conditional distribution of H w.r.t. O can be determined as follows:

$$\begin{aligned} \mathbb{P}(H = h | O = o) &= \frac{\mathbb{P}(H = h, O = o)}{\sum_{\hat{h} \in \text{Dom}(H)} \mathbb{P}(H = \hat{h}, O = o)} \\ &= \frac{E(h, o)}{\sum_{\hat{h} \in \text{Dom}(H)} E(\hat{h}, o)} = \frac{E(h, o)}{\mathcal{Z}(o)} \end{aligned} \quad (2.17)$$

The above computations are not actually done, since the number of combinations in the domain of \mathcal{H} is huge also when considering a low-medium size graph. On the opposite, the marginal probability $\mathbb{P}(H_i = h_i | O = 0)$ of a single variable in $H_i \in \mathcal{H}$ is computationally tractable. Formally $\mathbb{P}(H_i = h_i | O = 0)$ is defined as follows:

$$\mathbb{P}(H_i = h_i | O = o) = \sum_{\tilde{h} \in \{\mathcal{H} \setminus H_i\}} \mathbb{P}(H_i = h_i, \tilde{h} | O = o) \quad (2.18)$$

The above marginal distribution is essentially the conditional distribution of H_i w.r.t. O , no matter the other variables in \mathcal{H} .

A generic Random Field is a graphical model for which set \mathcal{O} (and consequently \mathcal{H}) is dynamical: the set of observations as well the values assumed by the evidences may change during time. Random field are handled by class `Random_Field`. Conditional Random Field are Random Field for which set \mathcal{O} must be decided once and cannot change after. Only the values of the evidences during time may change. Class `Conditional_Random_Field` is in charge of handling Conditional Random Field. Both Random Fields and Conditional Random Fields can be learnt knowing a training set, see Section 2.6. On the opposite, class `Graph` handles constant graphs: they are conceptually similar to Random Fields but learning is not possible. Indeed, all the Exponential Shape involved must be constant.

The rest of this Chapter is structured as follows. Section 2.2.2 will introduce the message passing algorithm, which is the pillar for performing belief propagation. Section 2.3 will expose the concept of maximum a posteriori estimation, useful when querying a graph, while Section 2.4 will address Gibbs sampling for producing a training set of a known model. Section 2.5 will present the concept of subgraph which is a useful way for computing the marginal probabilities of a sub group of variables in \mathcal{H} . Finally, 2.6 will discuss how the learning of a graphical model is done, with the aim of computing the weights of the Exponential shapes that are tunable.

2.2 Message Passing

Message passing is a powerful but conceptually simple algorithm adopted for propagating the belief across a net. Such a propagation is the starting point for performing many important operations, like computing the marginal distributions of single variables or obtaining sub graphs. Before detailing the steps involved in the message passing algorithm, let's start from an example of belief propagation. Without loss of generality we assume all the factors as Simple shapes.




Figure 2.3 Example of graph adopted for explaining the message passing algorithm. Below are reported the messages to compute for obtaining the marginal probability of variable x_1

2.2.1 Belief propagation

Consider the graph reported in Figure 2.3. Supposing for the sake of simplicity that no evidences are available (i.e. $\mathcal{O} = \emptyset$). We are interested in computing $\mathbb{P}(X_1)$, i.e. the marginal probability of X_1 . Recalling the definition introduced in the previous Section, the marginal probability is obtained by the following computation:

$$\mathbb{P}(x_1) = \sum_{\forall \tilde{x}_{2,3,4,5} \in \cup_{i=2}^5 X_i} \mathbb{P}(x_1, \tilde{x}_{2,3,4,5}) \quad (2.19)$$

Simplifying the notation and getting rid of the normalization coefficient \mathcal{Z} we can state the following:

$$\mathbb{P}(x_1) \propto \sum_{\tilde{x}_{2,3,4,5}} E(x_1, \tilde{x}_{2,3,4,5}) \quad (2.20)$$

Adopting the algebraic properties of the sums-products we can distribute the computations as follows:

$$\mathbb{P}(x_1) \propto \Phi_1(x_1) \sum_{\tilde{x}_5} \Phi_{15}(x_1, \tilde{x}_5) \sum_{\tilde{x}_4} \Phi_{14}(x_1, \tilde{x}_4) \Phi_4(\tilde{x}_4) \sum_{\tilde{x}_2} \Phi_{24}(\tilde{x}_2, \tilde{x}_4) \sum_{\tilde{x}_3} \Phi_{34}(\tilde{x}_3, \tilde{x}_4) \quad (2.21)$$

The first variable to marginalize can be \tilde{x}_2 or \tilde{x}_3 , since they are involved in the last terms of the sums products. The 'messages' $M_{2 \rightarrow 4}$, $M_{3 \rightarrow 4}$ are defined as follows:

$$\begin{aligned} M_{2 \rightarrow 4}(\tilde{x}_4) &= \sum_{\tilde{x}_2} \Phi_{24}(\tilde{x}_2, \tilde{x}_4) \\ M_{3 \rightarrow 4}(\tilde{x}_4) &= \sum_{\tilde{x}_3} \Phi_{34}(\tilde{x}_3, \tilde{x}_4) \end{aligned} \quad (2.22)$$

Inserting $M_{2 \rightarrow 4}$ and $M_{3 \rightarrow 4}$ into equation (2.21) leads to:

$$\mathbb{P}(x_1) \propto \Phi_1(x_1) \sum_{\tilde{x}_5} \Phi_{15}(x_1, \tilde{x}_5) \sum_{\tilde{x}_4} \Phi_{14}(x_1, \tilde{x}_4) \Phi_4(\tilde{x}_4) M_{2 \rightarrow 4}(\tilde{x}_4) M_{3 \rightarrow 4}(\tilde{x}_4) \quad (2.23)$$

At this point the messages $M_{4 \rightarrow 1}$ and $M_{5 \rightarrow 1}$ can be computed in the following way:

$$\begin{aligned} M_{4 \rightarrow 1}(x_1) &= \sum_{\tilde{x}_4} \Phi_{14}(x_1, \tilde{x}_4) \Phi_4(\tilde{x}_4) M_{2 \rightarrow 4}(\tilde{x}_4) M_{3 \rightarrow 4}(\tilde{x}_4) \\ M_{5 \rightarrow 1}(x_1) &= \sum_{\tilde{x}_5} \Phi_{15}(x_1, \tilde{x}_5) \end{aligned} \quad (2.24)$$

After inserting $M_{4 \rightarrow 1}$ and $M_{5 \rightarrow 1}$ into equation (2.23) we obtain:

$$\begin{aligned} \mathbb{P}(x_1) &\propto \Phi_1(x_1) M_{4 \rightarrow 1}(x_1) M_{5 \rightarrow 1}(x_1) \\ \mathbb{P}(x_1) &= \frac{\Phi_1(x_1) M_{4 \rightarrow 1}(x_1) M_{5 \rightarrow 1}(x_1)}{\sum_{\tilde{x}_1} \Phi_1(\tilde{x}_1) M_{4 \rightarrow 1}(\tilde{x}_1) M_{5 \rightarrow 1}(\tilde{x}_1)} \end{aligned} \quad (2.25)$$

which ends the computations. Messages are, in a certain sense, able to simplify the graph sending some information from an area of the graph to another one. Indeed, variables can be replaced by messages, which can be treated as additional factors. Figure 2.3 resumes the computations exposed. Notice that the computation of $M_{4 \rightarrow 1}$ must be done after computing the messages $M_{2 \rightarrow 4}$ and $M_{3 \rightarrow 4}$, while $M_{5 \rightarrow 1}$ can be computed independently from all the others.

2.2.2 Message Passing

The aforementioned considerations can be extended to a general structured graph. Look at Figure 2.4: the computation of Message $M_{B \rightarrow A}$ can be performed only after having computed all the messages $M_{V_1, \dots, m \rightarrow B}$, i.e. the messages incoming from all the neighbours of B a part from A . Clearly $M_{B \rightarrow A}$ is computed as follows:

$$\begin{aligned} M_{B \rightarrow A}(a) &= \sum_{\tilde{b}} \Phi_{AB}(a, \tilde{b}) M_{V_1 \rightarrow B}(\tilde{b}) \cdots M_{V_m \rightarrow B}(\tilde{b}) \\ &= \sum_{\tilde{b}} \Phi_{AB}(a, \tilde{b}) \prod_{i=1}^m M_{V_i \rightarrow B}(\tilde{b}) \end{aligned} \quad (2.26)$$

Essentially, it's like having simplified the graph: we can append to A the message $M_{B \rightarrow A}(a)$ as it's a Simple shape, deleting factor Φ_{AB} and all the other portions of the graph, see Figure 2.4. In turn, $M_{B \rightarrow A}(a)$ will be adopted for computing the message outgoing from A .

The above elimination is not actually done: all messages incoming to all nodes of a graph are computed by a derivation of the interface class `I_belief_propagation_strategy` and are stored to be used for subsequent queries. This is partially not true when considering the evidences. Indeed, when the values of the evidences are retrieved, variables in \mathcal{O} are temporarily deleted and replaced with messages, see Figure 2.5. Suppose variable C is connected to a variable A through a binary potential $\Phi_{AC}(A, C)$ and to variable B through Φ_{BC} . Suppose also that variable C is an evidence assuming a value equal to \hat{c} , then the messages sent to A and B can be computed independently as follows:


$$\begin{aligned} M_{C \rightarrow A}(a) &= \Phi_{AC}(a, \hat{c}) \\ M_{C \rightarrow B}(b) &= \Phi_{BC}(b, \hat{c}) \end{aligned} \quad (2.27)$$

Therefore all the variables that become evidences can be considered as leaves of the graph, sending messages to all the neighbouring nodes, possibly splitting an initial compact graph into many subgraphs, refer to Figure 2.5. Such computations are automatically handled by the library.

All the above considerations are valid when considering politree, i.e. graph without loops. Indeed, for these kind of graphs the message passing algorithm is able in a finite number of iterations to compute all the messages, see Figure 2.6. The same is not true when having loopy graphs (see Figure 2.7), since deadlocking situations arise: no further messages can be computed since for every nodes some incoming ones are missing. In such cases a variant of the message passing called loopy belief propagation can be adopted. Loopy belief propagation initializes all the messages to basic shapes having the values of the image all equal to 1 and then recomputes all the messages of all the variables till convergence.

You don't have to handle the latter aspect: when a belief propagation is performed, the library automatically chooses to deploy class `Message_Passing` or `Loopy_belief_propagation`, according to the structure of the graph for which the propagation is asked.

Remaining structure of the graph



Remaining structure of the graph




Figure 2.4 On the top the general mechanism involved in the message computation; on the bottom the simplification of the graph considering the computed message.




Figure 2.5 When variable C becomes an evidence, is temporary deleted from the graph, replaced by messages.




Figure 2.6 Steps involved for computing the messages of the polytree represented at the top. The leaves are the first nodes for which the outgoing messages can be computed.




Figure 2.7 Steps involved for computing the messages on a loopy graph: after computing the messages outgoing from the leaves, a deadlock is reached since no further messages are computable.

2.3 Maximum a posteriori estimation

Suppose we are not interested in determining the marginal probability of a specific variable, but rather we want the combination in the hidden set \mathcal{H} that maximises the probability $\mathbb{P}(H_{1,\dots,n}|O)$. Clearly, we could try to compute the entire distribution $\mathbb{P}(H_{1,\dots,n}|O)$ and then take the value of H maximising that distribution. However, this is not computationally possible since even for low medium size graphs the size of $\text{Dom}(\cup_{H_i \in \mathcal{H}} H_i)$ can be huge. Maximum a posteriori estimations solve this problem: the value maximising $\mathbb{P}(H_{1,\dots,n}|O)$ is computed, without explicitly building the entire distribution $\mathbb{P}(H_{1,\dots,n}|O)$. This is achieved by performing belief propagation with a slightly different version of the message passing algorithm presented in Section 2.2.2. Referring to Figure 2.4, the message to A is computed as follows when performing a maximum a posteriori estimation:

$$M_{B \rightarrow A}(a) = \max_{\tilde{b}} \{ \Phi_{AB}(a, \tilde{b}) \prod_{i=1}^m M_{V_i \rightarrow B}(\tilde{b}) \} \quad (2.28)$$

Essentially, the summation in equation (2.26) is replaced with the max operator. After all messages are computed, the estimation $h_{MAP} = \{h_{1MAP}, h_{2MAP}, \dots\}$ is obtained by considering for every variable in \mathcal{H} the value maximising:

$$h_{iMAP} = \operatorname{argmax} \{ \Phi_{H_i}(h_{iMAP}) \prod_{k=1}^L M_k(h_{iMAP}) \} \quad (2.29)$$

where M_1, \dots, M_L refer to all the messages incoming to H_i . To be precise, this procedure is not guaranteed to return the value actually maximising $\mathbb{P}(H_{1,\dots,n}|O)$, but at least a strong local maximum is obtained.

At this point it is worthy to clarify that the combination $h_{MAP} = \{h_{1MAP}, h_{2MAP}, \dots\}$ could not be obtained by simply assuming for every H_i the realization maximising the marginal distribution:

$$h_{MAP} \neq \{ \operatorname{argmax}(\mathbb{P}(h_1)), \dots, \operatorname{argmax}(\mathbb{P}(h_n)) \} \quad (2.30)$$

This is due to the fact that $\mathbb{P}(H_{1,\dots,n}|O)$ is a joint probability distribution, while the marginals $\mathbb{P}(H_i)$ are not. For better understanding this aspect consider the graph reported in Figure 2.8, with the potentials Φ_{XA} , Φ_{AB} and Φ_{YB} having the images defined in table 2.5. Suppose discovering that $X = 0$ and $Y = 1$. Then, performing the standard message passing algorithm explained in the previous Section we obtain the messages reported in Figure

	b_0	b_1		x_0	x_1		y_0	y_1
a_0	2	0	a_0	1	0.1	b_0	1	0.1
a_1	0	2	a_1	0.1	1	b_1	0.1	1

Table 2.5 Factors involved in the graph of Figure 2.8.

A	B	$E(A, B, X = 0, Y = 1)$
0	0	0.2
0	1	0
1	0	0
1	1	0.2

Table 2.6 Factors involved in the graph of Figure 2.8.

2.8. Clearly individual marginals for A and B would be equal to:

$$\begin{aligned}\mathbb{P}(A) &= \begin{pmatrix} \mathbb{P}(A = 0) \\ \mathbb{P}(A = 1) \end{pmatrix} = \begin{pmatrix} 0.5 \\ 0.5 \end{pmatrix} \\ \mathbb{P}(B) &= \begin{pmatrix} \mathbb{P}(B = 0) \\ \mathbb{P}(B = 1) \end{pmatrix} = \begin{pmatrix} 0.5 \\ 0.5 \end{pmatrix}\end{aligned}\quad (2.31)$$

Therefore, all the combinations $\{A = 0, B = 0\}$, $\{A = 0, B = 1\}$, $\{A = 1, B = 0\}$, $\{A = 1, B = 1\}$ maximise $\mathbb{P}(A, B|O)$. However, it easy to prove that $E(A, B, X, Y)$ assumes the values reported in table 2.6. Therefore, the combinations actually maximising the joint distribution $\mathbb{P}(A, B|O)$ are $\{A = 0, B = 0\}$ and $\{A = 1, B = 1\}$, leading to a different result.

Maximum a posteriori estimation can be performing invoking MAP_on_Hidden_set ?? on a particular derivation of class Node_factory.

2.4 Gibbs sampling

Gibbs sampling is a Monte Carlo method for obtaining samples from a joint distribution of variables X_1, \dots, m , without explicitly compute that distribution. Indeed, Gibbs sampling is an iterative method which requires every time to determine the conditional distribution of a single variable X_i w.r.t to all the others in the group.

More formally the algorithm starts with an initial combination of values $\{x_1^1, \dots, m\}$ for the variable $\cup_{i=\{1, \dots, m\}} X_i$. At every iteration, all the values of that combination are recomputed. At the j^{th} iteration the value of x_k^{j+1} for the subsequent iteration is obtaining by sampling from the following marginal distribution:

$$x_k^{j+1} \sim \mathbb{P}(x_k | x_{\{1, \dots, m\} \setminus k}^j) \quad (2.32)$$

After an initial transient, the samples cumulated during the iterations can be considered as drawn from the joint distribution involving group X_1, \dots, m .

This algorithm can be easily applied to graphical model. Indeed the methodologies exposed in Section 2.2.2 can be applied for determining the conditional distribution of a single variable $H_i \in \mathcal{H}$ w.r.t all the others (as well the evidences in \mathcal{O}), assuming all variables in $\mathcal{H} \setminus H_i$ as additional observations and computing the marginal probability of H_i . Gibbs_Sampling_on_Hidden_set ?? is in charge of performing Gibbs sampling on a generic graph.




Figure 2.8 Example of graph adopted. When the evidences are retrieved, the messages computed by making use of the message passing algorithm are reported below.

2.5 Sub graphs

As explained in Section 2.2.2, the marginal probability of a variable $H_i \in \mathcal{H}$ can be efficiently computed by considering the messages produced by the message passing algorithm. The same messages can be also used for performing graph reduction, with the aim to model the joint probability distribution of a subset of variables $\{H_1, H_2, H_3\} \subset \mathcal{H}$, i.e. $\mathbb{P}(H_{1,2,3}|O)$. The latter quantity is the marginal probability of the subset of variables of interest.

The aim of message passing is essentially to simplify the graph, condensing all the belief information into the messages. Such property is exploited for computing sub graphs. Without loss of generality assume from now on $\mathcal{O} = \emptyset$. Consider the graph in Figure 2.9 and suppose we are interested in modelling $\mathbb{P}(A, B, C)$, no matter the values of the other variables. After computing all the messages exploiting message passing, the sub graph reported in Figure 2.9 is the one modelling $\mathbb{P}(A, B, C)$. Actually, that sub graph is a graphical model itself, for which all the properties exposed so far hold. For example the energy function E is computable as follows:

$$E(A = a, B = b, C = c) = \Phi_{AB}(a, b)\Phi_{BC}(b, c)\Phi_{AC}(a, c)M_{X \rightarrow A}(a)M_{Y \rightarrow B}(b) \quad (2.33)$$

while the joint probability of A, B and C can be computed in this way:

$$\mathbb{P}(A = a, B = b, C = c) = \frac{E(a, b, c)}{\sum_{\forall \tilde{a}, \tilde{b}, \tilde{c}} E(\tilde{a}, \tilde{b}, \tilde{c})} \quad (2.34)$$

Notice that in this case the graph is significantly smaller than the originating one, implying that the above computations can be performed in an acceptable time.

Also Gibbs sampling can be applied to a reduced graph, producing samples drawn from the marginal probability $\mathbb{P}(A, B, C)$.

The reduction described so far is always possible when considering a subset of variables forming a connected sub-portion of the original graph, i.e. after reduction there must be a unique sub structure. For instance, variables X and Y of the graph in Figure 2.10 do not respect the latter specification, meaning that it is not possible to build a sub graph involving X and Y .

The class in charge of handling graph reduction is `Node_factory::SubGraph`.

2.6 Learning


The aim of learning is to determine the optimal values for the w (equation (2.13)) of all the tunable potentials (see Section 2.1) Ψ . To this aim two cases must be distinguished:

- Learning must be performed for a `Graph` or a `Random_Field`: see Section 2.6.1
- Learning must be performed for a `Conditional_Random_Field`: see Section 2.6.2

No matter the case, the population of tunable weights will be indicated with W :

$$W = \{w_1, \dots, w_D\} \quad (2.35)$$

w_i will refer to the i^{th} free parameter of the model. Learning is internally handled by EFG, exploiting class `I_Trainer`.



Sub graph involving A, B, C




Figure 2.9 Example of graph reduction.




Figure 2.10 Example of a subset of variables for which the graph reduction is not possible.

2.6.1 Learning of unconditioned model

For the purpose of learning, we assume $\mathcal{O} = \emptyset$. Learning considers a training set $T = \{t_1, \dots, t_N\}$ made of realizations of the joint distribution correlating all the variables in \mathcal{V} , no matter the fact that they are involved in tunable or non tunable potentials. As exposed in Section 2.1, if W is known, the probability of a combination t_j can be evaluated as follows:

$$\mathbb{P}(t_j) = \frac{E(t_j, W)}{\mathcal{Z}(W)} \quad (2.36)$$

At this point we can observe that the energy function is the product of two main factors: one depending from t_j and W and the other depending only upon t_j representing the contribution of all the non tunable potentials (Simple shapes and fixed Exponential shapes, see Section 2.1):

$$\begin{aligned} E(t_j, W) &= \exp(w_1 \Phi_1(t_j)) \cdots \exp(w_D \Phi_D(t_j)) \cdot E_0(t_j) \\ &= \exp\left(\sum_{i=1}^D w_i \Phi_i(t_j)\right) \cdot E_0(t_j) \end{aligned} \quad (2.37)$$

The likelihood function L can be defined as follows:

$$L = \prod_{t_j \in T} \mathbb{P}(t_j) \quad (2.38)$$

passing to the logarithmic likelihood and dividing by the training set size N we obtain:

$$\begin{aligned} J = \frac{\log(L)}{N} &= \sum_{t_j \in T} \frac{\log(\mathbb{P}(t_j))}{N} \\ &= \sum_{t_j \in T} \frac{\log(E(t_j, W)) - \log(\mathcal{Z}(W))}{N} \\ &= \frac{1}{N} \sum_{t_j \in T} \log(E(t_j, W)) - \log(\mathcal{Z}(W)) \\ &= \frac{1}{N} \sum_{t_j \in T} \left(\sum_{i=1}^D w_i \Phi_i(t_j) \right) - \log(\mathcal{Z}(W)) + \cdots \\ &+ \frac{1}{N} \sum_{t_j \in T} \log(E_0(t_j)) \end{aligned} \quad (2.39)$$

The aim of learning is to find the value of W maximising J . This is done iteratively, exploiting a gradient descend approach. The computations to perform for evaluating the gradient $\frac{\partial J}{\partial W}$ will be exposed in the following part of this Section. Notice that in equation (2.39), term $\sum_{t_j \in T} \log(E_0(t_j))$ is constant and consequently will be not considered for computing the gradient of J . Equation (2.39) can be rewritten as follows:

$$\begin{aligned} J &= \alpha(T, W) - \beta(W) \\ \alpha &= \frac{1}{N} \sum_{t_j \in T} \left(\sum_{i=1}^D w_i \Phi_i(t_j) \right) \end{aligned} \quad (2.40)$$

$$\beta = \log(\mathcal{Z}(W)) \quad (2.41)$$

α is influenced by T , while the same is not valid for β .

2.6.1.1 Gradient of α

By the analysis of the equation (2.40) it is clear that:

$$\frac{\partial \alpha}{\partial w_i} = \frac{1}{N} \sum_{t_j \in T} \Phi_i(t_j) \quad (2.42)$$

2.6.1.2 Gradient of β

The computation of $\frac{\partial \beta}{\partial w_i}$ requires to manipulate a little bit equation (2.41). Firstly the derivative of the logarithm must be computed:

$$\frac{\partial \beta}{\partial w_i} = \frac{1}{\mathcal{Z}} \frac{\partial \mathcal{Z}}{\partial w_i} \quad (2.43)$$

The normalizing coefficient \mathcal{Z} is made of the following terms (see also equation (2.6)):

$$\mathcal{Z}(W) = \sum_{\tilde{V} \in \bigcup_{i=1}^p V_i} \left(\exp\left(\sum_{i=1}^D w_i \Phi_i(\tilde{V})\right) \cdot E_0(\tilde{V}) \right) \quad (2.44)$$

Introducing equation (2.44) into (2.43) leads to:

$$\begin{aligned} \frac{\partial \beta}{\partial w_i} &= \frac{1}{\mathcal{Z}} \frac{\partial}{\partial w_i} \left(\sum_{\tilde{V}} \exp\left(\sum_{i=1}^D w_i \Phi_i(\tilde{V})\right) E_0(\tilde{V}) \right) \\ &= \frac{1}{\mathcal{Z}} \sum_{\tilde{V}} \frac{\partial}{\partial w_i} \left(\exp\left(\sum_{i=1}^D w_i \Phi_i(\tilde{V})\right) \right) E_0(\tilde{V}) \\ &= \frac{1}{\mathcal{Z}} \sum_{\tilde{V}} \exp\left(\sum_{i=1}^D w_i \Phi_i(\tilde{V})\right) E_0(\tilde{V}) \Phi_i(\tilde{V}) \\ &= \sum_{\tilde{V}} \frac{\exp\left(\sum_{i=1}^D w_i \Phi_i(\tilde{V})\right) E_0(\tilde{V})}{\mathcal{Z}} \Phi_i(\tilde{V}) \\ &= \sum_{\tilde{V}} \frac{E(\tilde{V})}{\mathcal{Z}} \Phi_i(\tilde{V}) \\ &= \sum_{\tilde{V}} \mathbb{P}(\tilde{V}) \Phi_i(\tilde{V}) \end{aligned} \quad (2.45)$$

Last term in the above equations can be further elaborated. Assume that the variables involved in potential Φ_j are $V_{1,2}$, then:

$$\begin{aligned} \frac{\partial \beta}{\partial w_i} &= \sum_{\tilde{V}} \mathbb{P}(\tilde{V}) \Phi_i(\tilde{V}) \\ &= \sum_{\tilde{V}_{1,2}} \Phi_i(\tilde{V}_{1,2}) \sum_{\tilde{V}_{3,4,\dots}} \mathbb{P}(\tilde{V}_{1,2,3,4,\dots}) \\ &= \sum_{\tilde{V}_{1,2}} \Phi_i(\tilde{V}_{1,2}) \mathbb{P}(\tilde{V}_{1,2}) \end{aligned} \quad (2.46)$$

where $\mathbb{P}(\tilde{V}_{1,2})$ is the marginal probability (see the initial part of Section 2.1) of the variables involved in the potential Φ_i , which can be easily computable by considering the sub graph containing only V_1 and V_2 as variables (see Section 2.5). Notice that in case Φ_i is a unary potential the same holds, considering the marginal distribution of the single variable involved by Φ_i :

$$\frac{\partial \beta}{\partial w_i} = \sum_{\forall \tilde{V}_1} \Phi_i(\tilde{V}_1) \mathbb{P}(\tilde{V}_1) \quad (2.47)$$

which can be easily obtained through the message passing algorithm (Section 2.2.2).

After all the manipulations performed, the gradient $\frac{\partial J}{\partial w_i}$ has the following compact expression:

$$\frac{\partial J}{\partial w_i} = \frac{1}{N} \sum_{j=1}^N \Phi_i(D_j^i) - \sum_{\tilde{D}^i} \mathbb{P}(\tilde{D}^i) \Phi_i(\tilde{D}^i) \quad (2.48)$$

2.6.2 Learning of conditioned model

For such models learning is more demanding as will be exposed. Recalling the definition provided in the final part of Section 2.1, Conditional Random Fields are graphs for which the set of observations \mathcal{O} is fixed. The training set T is made of realizations of both \mathcal{H} and \mathcal{O} :

$$\begin{aligned} T &= \{t_1, \dots, t_N\} \\ &= \{\{h_1, o_1\}, \dots, \{h_N, o_N\}\} \end{aligned} \quad (2.49)$$

We recall, equation (2.17), that the conditional probability of the hidden variables w.r.t. the observed ones is defined as follows:

$$\begin{aligned} \mathbb{P}(h_j, o_j) &= \frac{E(h_j, o_j, W)}{\mathcal{Z}(o_j, W)} \\ E(h_j, o_j, W) &= \exp\left(\sum_{i=1}^D w_i \Phi_i(h_j, o_j)\right) E_0(h_j, o_j) \\ \mathcal{Z}(o_j, W) &= \sum_{\tilde{h}} E(\tilde{h}, o_j, W) \end{aligned} \quad (2.50)$$

The aim of learning is to maximise a likelihood uncton L defined in this case as follows:

$$L = \prod_{h_j \in T} \mathbb{P}(h_j | o_j) \quad (2.51)$$

Passing to the logarithms and dividing by the training set size we obtain the following objective function J :

$$\begin{aligned} J &= \frac{\log(L)}{N} \\ &= \frac{1}{N} \sum_{h_j, o_j \in T} \log(E(h_j, o_j, W)) - \frac{1}{N} \sum_{h_j, o_j \in T} \log(\mathcal{Z}(o_j, W)) \\ &= \frac{1}{N} \sum_{h_j, o_j \in T} \left(\sum_{i=1}^D w_i \Phi_i(h_j, o_j) \right) - \frac{1}{N} \sum_{h_j, o_j \in T} \log(\mathcal{Z}(o_j, W)) \\ &\quad + \frac{1}{N} \sum_{h_j, o_j \in T} \log(E_0(h_j, o_j)) \end{aligned} \quad (2.52)$$

Neglecting E_0 which not depends upon W , equation (2.52) can be rewritten as follows:

$$\begin{aligned} J &= \alpha(T, W) - \beta(T, W) \\ \alpha(T, W) &= \frac{1}{N} \sum_{h_j, o_j} \left(\sum_{i=1}^D w_i \Phi_i(h_j, o_j) \right) \\ \beta(T, W) &= \frac{1}{N} \sum_{o_j} \log(\mathcal{Z}(o_j, W)) \end{aligned} \quad (2.53)$$

At this point, an important remark must be done: differently from the β defined in equation (2.41), $\beta(T, W)$ of conditioned model is a function of the training set. The latter observation has an important consequence: when performing learning of unconditioned model, belief propagation (i.e. the computation of the messages through message passing with the aim of computing the marginal probabilities of the groups of variables involved in the factor of the model) must be performed once for every iteration of the gradient descend; on the opposite when considering conditioned model, belief propagation must be performed at every iteration for every element of the training set, see equation (2.57). This makes the learning of conditioned models much more computationally demanding. This price is paid in order to not model the correlation among the observations³, which can be interesting for many applications. The computation of $\frac{\partial \alpha}{\partial w_i}$ is analogous to the one of non conditioned model, equation (2.42).

³that can be highly correlated

2.6.2.1 Gradient of β

Following the same approach in Section 2.6.1.2, the gradient of β can be computed as follows:

$$\begin{aligned}
\frac{\partial \beta}{\partial w_i} &= \frac{1}{N} \sum_{j=1}^N \frac{\partial \log(\mathcal{Z}(o_j, W))}{\partial w_i} \\
&= \frac{1}{N} \sum_{j=1}^N \frac{1}{\mathcal{Z}(o_j)} \frac{\partial \mathcal{Z}(o_j, W)}{\partial w_i} \\
&= \frac{1}{N} \sum_{j=1}^N \frac{\partial}{\partial w_i} \left(\sum_{\tilde{h}} \exp\left(\sum_{i=1}^D w_i \Phi_i(\tilde{h}, o_j)\right) E_0(\tilde{h}, o_j) \right) \\
&= \frac{1}{N} \sum_{j=1}^N \sum_{\tilde{h}} \left(\exp\left(\sum_{i=1}^D w_i \Phi_i(\tilde{h}, o_j)\right) E_0(\tilde{h}, o_j) \Phi_i(\tilde{h}, o_j) \right) \\
&= \frac{1}{N} \sum_{j=1}^N \sum_{\tilde{h}} \frac{E(\tilde{h}, o_j, W)}{\mathcal{Z}(o_j)} \Phi_i(\tilde{h}, o_j) \\
&= \frac{1}{N} \sum_{j=1}^N \sum_{\tilde{h}} \mathbb{P}(\tilde{h}|o_j) \Phi_i(\tilde{h}, o_j)
\end{aligned} \tag{2.54}$$

Suppose the variables involved in the factor Φ_j are $\tilde{h}_{1,2}$, then:

$$\begin{aligned}
\frac{\partial \beta}{\partial w_i} &= \frac{1}{N} \sum_{j=1}^N \sum_{\tilde{h}} \mathbb{P}(\tilde{h}|o_j) \Phi_i(\tilde{h}, o_j) \\
&= \frac{1}{N} \sum_{j=1}^N \sum_{\tilde{h}_{1,2}} \Phi_i(\tilde{h}_{1,2}) \sum_{\tilde{h}_{3,4}, \dots} \mathbb{P}(\tilde{h}_{1,2,3,4}, \dots | o_j) \\
&= \frac{1}{N} \sum_{j=1}^N \sum_{\tilde{h}_{1,2}} \Phi_i(\tilde{h}_{1,2}) \mathbb{P}(\tilde{h}_{1,2} | o_j)
\end{aligned} \tag{2.55}$$

where $\mathbb{P}(\tilde{h}_{1,2} | o_j)$ is the conditioned marginal probability of group $\tilde{h}_{1,2}$ w.r.t. the observations o_j .

Grouping all the simplifications we obtain:

$$\frac{\partial J}{\partial w_i} = \frac{1}{N} \sum_{j=1}^N \Phi_i(h_j, o_j) - \frac{1}{N} \sum_{j=1}^N \left(\sum_{\tilde{h}_{1,2}} \mathbb{P}(\tilde{h}_{1,2} | o_j) \Phi_i(\tilde{h}_{1,2}) \right) \tag{2.56}$$

Generalizing:

$$\frac{\partial J}{\partial w_i} = \frac{1}{N} \sum_{j=1}^N \Phi_i(D_j^i, o_j) - \frac{1}{N} \sum_{j=1}^N \left(\sum_{\tilde{D}^i} \mathbb{P}(\tilde{D}^i | o_j) \Phi_i(\tilde{D}^i, o_j) \right) \tag{2.57}$$

2.6.3 Learning of modular structure

Suppose to have a modular structure made of repeating units as for example the graph in Figure 2.11. Every single unit has the same population of potentials and we would like to enforce this fact when performing learning. In particular we'll have some sets of Exponential shape sharing the same weight w_1 (see Figure 2.11). Motivated by this example, we included in the library the possibility to specify that a potential must share its weight with another one. Then, learning is done consistently with the aforementioned specification.

2.6.3.1 Gradient of α

Considering the model in Figure 2.11, the α part of J (equation (2.40)) can be computed as follows:

$$\alpha = \frac{1}{N} \sum_{t_j} (w_1 \Phi_1(a_{1j}, b_{1j}) + w_1 \Phi_2(a_{2j}, b_{2j}) + w_1 \Phi_3(a_{3j}, b_{3j}) + \dots + \dots + \sum_{i=2}^D w_i \Phi_i(t_j)) \quad (2.58)$$

which leads to:

$$\frac{\partial \alpha}{\partial w_1} = \frac{1}{N} \sum_{t_j} (\Phi_1(a_{1j}, b_{1j}) + \Phi_2(a_{2j}, b_{2j}) + \Phi_3(a_{3j}, b_{3j})) \quad (2.59)$$

2.6.3.2 Gradient of β

Regarding the β part of J we can write what follows:

$$\begin{aligned} \frac{\partial \beta}{\partial w_1} &= \frac{1}{Z} \frac{\partial Z}{\partial w_1} \\ &= \frac{1}{Z} \frac{\partial}{\partial w_1} \left(\sum_{\tilde{V}} \left(\exp(w_1(\Psi_1(a_{1j}, b_{1j}) + \dots \right. \right. \\ &\quad \left. \left. \dots + \Psi_2(a_{2j}, b_{2j}) + \Psi_3(a_{3j}, b_{3j})) + \sum_{i=2}^D w_i \Phi_i(\tilde{V})) E_0(\tilde{V})) \right) \right) \\ &= \sum_{\tilde{V}} \mathbb{P}(\tilde{V}) (\Phi_1(\tilde{a}_1, \tilde{b}_1) + \Phi_2(\tilde{a}_2, \tilde{b}_2) + \Phi_3(\tilde{a}_3, \tilde{b}_3)) \\ &= \sum_{\tilde{V}} \mathbb{P}(\tilde{V}) \Phi_1(\tilde{a}_1, \tilde{b}_1) + \sum_{\tilde{V}} \mathbb{P}(\tilde{V}) \Phi_2(\tilde{a}_2, \tilde{b}_2) + \sum_{\tilde{V}} \mathbb{P}(\tilde{V}) \Phi_3(\tilde{a}_3, \tilde{b}_3) \\ &= \sum_{\tilde{A}_1, \tilde{B}_1} \mathbb{P}(\tilde{A}_1, \tilde{B}_1) \Phi_1(\tilde{A}_1, \tilde{B}_1) + \sum_{\tilde{A}_2, \tilde{B}_2} \mathbb{P}(\tilde{A}_2, \tilde{B}_2) \Phi_2(\tilde{A}_2, \tilde{B}_2) + \dots \\ &\quad \dots + \sum_{\tilde{A}_3, \tilde{B}_3} \mathbb{P}(\tilde{A}_3, \tilde{B}_3) \Phi_3(\tilde{A}_3, \tilde{B}_3) \end{aligned} \quad (2.60)$$

Notice that the gradient $\frac{\partial J}{\partial w_1}$ is the summation of three terms: the ones that would have been obtained considering separately the three potentials in which w_1 is involved (equation (2.48)):

$$\begin{aligned} \frac{\partial J}{\partial w_1} &= \frac{1}{N} \sum_{j=1}^N \Phi_1(a_i^1, b_i^1) - \sum_{\tilde{a}^1, \tilde{b}^1} \mathbb{P}(\tilde{a}^1, \tilde{b}^1) \Phi_1(\tilde{a}^1, \tilde{b}^1) + \dots \\ &\quad + \frac{1}{N} \sum_{j=1}^N \Phi_2(a_i^2, b_i^2) - \sum_{\tilde{a}^2, \tilde{b}^2} \mathbb{P}(\tilde{a}^2, \tilde{b}^2) \Phi_2(\tilde{a}^2, \tilde{b}^2) + \dots \\ &\quad + \frac{1}{N} \sum_{j=1}^N \Phi_3(a_i^3, b_i^3) - \sum_{\tilde{a}^3, \tilde{b}^3} \mathbb{P}(\tilde{a}^3, \tilde{b}^3) \Phi_3(\tilde{a}^3, \tilde{b}^3) + \dots \end{aligned} \quad (2.61)$$

The above result has a general validity, also considering conditioned graphs.




Figure 2.11 Example of modular structure: weight w_1 is simultaneously involved into potentials Φ_1, Φ_2 and Φ_3 .

Chapter 3

Files representing factor graphs

The aim of this Section is to expose how to build graphical models from XML files describing their structures. In particular, the syntax of such an XML will be clarified. XML files can be passed as input for the constructor of Graph `??`, Random_Field `??` and Conditional_Random_Field `??`. Figure 3.1 visually explains the structure of a valid XML. Essentially two kind of tags must be incorporated:

- Variable: describes the information related to a variable present in the graph. There must a tag of this kind for every variable constituting the model. Fields description:
 - name: is a string indicating the name of this variable.
 - Size: is the size of the variable, i.e. the size of Dom , see Section 2.1.
 - flag[optional] : is a flag that can assume two possible values, 'O' or 'H' according to the fact that this variable is in set \mathcal{O} (Section 2.1) or not respectively. When non specifying this flag 'H' is assumed.
- Potential: describes the information related to a unary or a binary potential present in the graph (see Section 2.1). Fields description:
 - var: the name of the first variable involved.
 - var[optional]: the name of the second variable involved. Is omitted when considering unary potentials, while is mandatory when a binary potentials is described by this tag.
 - weight[optional]: when specifying an Exponential shape (Section 2.1) it must be present for indicating the value of the weight w (equation (2.13)). When omitting, the potential is assumed as a Simple shape one.
 - tunability[optional]: it is a flag for specifying whether the weight of this Exponential shape is tunable or not (see Section 2.1). Is ignored in case weight is omitted. It can assumes two possible values, 'Y' or 'N' according to the fact that the weight involved is tunable or not respectively. When weight is specified and tunability is omitted, a value equal to 'Y' is assumed.
- Share[optional]: you must specify this sub tag when the containing Exponential shape shares its weight with another potential in the model. Sub fields var are exploited for specifying the variables involved by the potential whose weight is to share. If weight is omitted in the containing Potential tag, this sub tag is ignored, even though the value assigned to weight is ignored since it is shared with another potential. The potential sharing its weight must be clearly an Exponential shape, otherwise the sharing directive is ignored.

The following components are exclusive: only one of them can be specified in a Potential tag and at the same time at least one must be present.

- Correlation: it can assume two possible values, 'T' or 'F'. When 'T' is passed, this potential is assumed to be a simple shape correlating shape (see `??`), otherwise when passing 'F' a simple anti correlating shape is assumed (see `??`). It is invalid in case this Potential is a unary one. In case weight was specified, an Exponential shape is built, wrapping a simple correlating or anti-correlating shape.




Figure 3.1 The structure of the XML describing a graphical model.

- Source: it is the location of a textual file describing the values of the distribution characterizing this potential. Rows of this file contain the values characterizing the image of the potential. Combinations not specified are assumed to have an image value equal to 0. Clearly the number of values characterizing the distribution must be consistent with the number of specified var fields. In case weight was specified, an Exponential shape is built, wrapping the Simple shape whose values are specified in the aforementioned file. For instance, the potential Φ_b of Section 2.1 would have been described by a file containing the following rows:

```
0 0 1
0 1 4
1 1 1
2 2 5
2 4 1
```

(3.1)

- Set of sub tags Distr_val: is a set of nested tags describing the distribution of the this potential. Similarly to Source, every element use fields v for describing the combination, while D is used for specifying the value assumed by the distribution. For example the potential Φ_b of Section 2.1 would have been described by the syntax reported in Figure 3.2. In case weight was specified, an Exponential shape is built, wrapping the Simple shape whose distribution is specified by the aforementioned sub tags.

```
<Potential . . . >  
  <Distr_val "v"=0 "v"=0 "D"=1>  
  <Distr_val "v"=0 "v"=1 "D"=4>  
  <Distr_val "v"=1 "v"=1 "D"=1>  
  <Distr_val "v"=2 "v"=2 "D"=5>  
  <Distr_val "v"=2 "v"=4 "D"=1>  
</Potential>
```

Figure 3.2 Syntax to adopt for describing the potential Φ_b of Section 2.1, using a population of Distr_val sub tags.

Chapter 4

Samples

4.1 Sample 01: Potential handling

The aim of this series of examples is mainly to show how to handle the creation of variables and factors.

4.1.1 part 01

Part 01 creates a shape factor Φ_{AB} , involving the pair of variables A and B . Both that variables have a domain size equal to 4, i.e. $Dom(A) = \{a_0 = 0, a_1 = 1, a_2 = 2, a_3 = 3\}$ and $Dom(B) = \{b_0 = 0, b_1 = 1, b_2 = 2, b_3 = 3\}$. The generic value in the image Φ_{AB} is equal to:

$$\Phi_{AB}(A = a, B = b) = a + 2 \cdot b \quad (4.1)$$

Table 4.1 reports the entire image of Φ_{AB} .

4.1.2 part 02

Part 02 considers a ternary correlating factor $\Phi_{C \ V123}$, involving variables V_1 , V_2 and V_3 , each having a domain size equal to 3. Ternary factors cannot be part of a graph, but it is anyway possible to build them using class `Potential_Shape`. The values in the image of $\Phi_{C \ V123}$ are all 0, except for those combination for which V_1 , V_2 and V_3 assume the same value (0, 1 or 2) and in such cases, the image is equal to 1.

The same example builds at a second stage a ternary anti-correlating factor $\Phi_{A \ V123}$. The values in the image of $\Phi_{A \ V123}$ are all 1, except for those combination for which V_1 , V_2 and V_3 assume the same value (0, 1 or 2) and in such cases the image is equal to 0.

When considering a graph having only $\Psi_{C, V123}(\Phi_{C \ V123} \cdot w)$ as a factor, the ripartition function Z is equal to:

$$Z = (4^3 - 4) + 4 \cdot \exp(w) \quad (4.2)$$

	$b_0 = 0$	$b_1 = 1$	$b_2 = 2$	$b_3 = 3$
$a_0 = 0$	0	2	4	6
$a_1 = 1$	1	3	5	7
$a_2 = 2$	2	4	6	8
$a_3 = 3$	3	5	7	9

Table 4.1 The values in the image of Φ_{AB} .




Figure 4.1 The probability $\mathbb{P}(V_1 = v, V_2 = v, V_3 = v|w)$ and its complement, when considering a ternary correlating factor, on the left, and an anti-correlating one, on the right.

The probability to have as a realization a combination with the same values is equal to:

$$\mathbb{P}(V_1 = v, V_2 = v, V_3 = v) = \sum_{i=0}^3 \mathbb{P}(V_1 = i, V_2 = i, V_3 = i) \quad (4.3)$$

$$= \sum_{i=0}^3 \frac{\Psi_{C,V123}(i, i, i)}{Z} \quad (4.4)$$

$$= 4 \cdot \frac{\Psi_{C,V123}(0, 0, 0)}{Z} \quad (4.5)$$

$$= \frac{4 \cdot \exp(w)}{(4^3 - 4) + 4 \cdot \exp(w)} \quad (4.6)$$

The value assumed by $\mathbb{P}(V_1 = v, V_2 = v, V_3 = v|w)$ is reported in Figure 4.1, together with the complementary probability $1 - \mathbb{P}(V_1 = v, V_2 = v, V_3 = v|w)$.

When considering a graph having only $\Psi_{A,V123} = w \exp(\Phi_{A,V123})$ as factor, the ripartition function Z is equal to:

$$Z = (4^3 - 4) \cdot \exp(w) + 4 \quad (4.7)$$

The probability to have as a realization a combination with the same values is equal to:

$$\mathbb{P}(V_1 = v, V_2 = v, V_3 = v) = \sum_{i=0}^3 \mathbb{P}(V_1 = i, V_2 = i, V_3 = i) \quad (4.8)$$

$$= \sum_{i=0}^3 \frac{\Psi_{A,V123}(i, i, i)}{Z} \quad (4.9)$$

$$= 4 \cdot \frac{\Psi_{A,V123}(0, 0, 0)}{Z} \quad (4.10)$$

$$= \frac{4}{(4^3 - 4) \cdot \exp(w) + 4} \quad (4.11)$$

The value assumed by $\mathbb{P}(V_1 = v, V_2 = v, V_3 = v|w)$ is reported in Figure 4.1, together with its complement $1 - \mathbb{P}(V_1 = v, V_2 = v, V_3 = v|w)$. Indeed, when the variables are correlated, i.e. they share $\Psi_{C,V123}$, the probability $\mathbb{P}(V_1 = v, V_2 = v, V_3 = v|w)$ is big. Moreover, the more w is high (i.e. the more the variables are correlated), the more the latter probability is big. On the opposite, when the variables are anti-correlated, the opposite situation arises.

4.2 Sample 02: Belief propagation, part A

The aim of this series of examples is to show how to perform probabilistic queries on factor graphs.




Figure 4.2 On the left the graph considered in this example, while on the right the image of factor Ψ_{AB} . Since that potential is the only one present in the graph, the values in the image of Ψ_{AB} are also the ones assume by the energy function E .




Figure 4.3 On the left the graph considered in this example, while on the right the images of factor Ψ_{AB} and Ψ_{BC} having, respectively, a weight equal to β and α .

4.2.1 part 01

This example creates a graph having a single binary exponential shape Ψ_{AB} , see Figure 4.2, with a A and B having a Dom size equal to 2. $\Psi_{AB} = \exp(w\Phi_{AB})$, where Φ_{AB} is a simple correlating factor. The image of Ψ_{AB} is reported in the right part of Figure 4.2.

Variable B is considered as an evidence, whose value is equal, for the first part of the example, to 0, while a value of 1 is assumed in the second part. The probability of A conditioned to B , is equal to (see equation (2.17)):

$$\mathbb{P}(A = a|B = 0) = \frac{E(A = a, B = 0)}{E(A = 0, B = 0) + E(A = 1, B = 0)} \Rightarrow \begin{bmatrix} \mathbb{P}(A = 0|B = 0) = \frac{\exp(w)}{1 + \exp(w)} \\ \mathbb{P}(A = 1|B = 0) = \frac{1}{1 + \exp(w)} \end{bmatrix} \quad (4.12)$$

$$\mathbb{P}(A = a|B = 1) = \frac{E(A = a, B = 1)}{E(A = 0, B = 1) + E(A = 1, B = 1)} \Rightarrow \begin{bmatrix} \mathbb{P}(A = 0|B = 1) = \frac{1}{1 + \exp(w)} \\ \mathbb{P}(A = 1|B = 1) = \frac{\exp(w)}{1 + \exp(w)} \end{bmatrix} \quad (4.13)$$

4.2.2 part 02

A slightly more complex graph, made of two exponential correlating factors Ψ_{BC} and Ψ_{AB} , is built in this sample. The considered graph is reported in Figure 4.3. The two involved factors have two different weights, α and β : the resulting image sets are reported in the right part of Figure 4.3.

In the first part, $C = 1$ is assumed as evidence and the marginal probabilities of A and B conditioned to C are computed. They are compared with the theoretical results, obtained by applying the message passing algorithm




Figure 4.4 Belief propagation steps when C is assumed as evidence.





Figure 4.5 The marginals of variables B and A , when having a $C = 1$ as evidence of the graph reported in Figure 4.4.

Figure 4.6 Belief propagation steps when B is assumed as evidence.

(Section 2.2.2), whose steps are here detailed ¹. The message passing steps are summarized in Figure 4.4. After having computed all the messages, it is clear that the marginal probabilities are equal to:

$$\mathbb{P}(A|C=1) = \frac{1}{Z} M_{B \rightarrow A}(A) = \frac{1}{Z} \begin{bmatrix} \exp(\alpha) + \exp(\beta) \\ 1 + \exp(\alpha) \cdot \exp(\beta) \end{bmatrix} \quad (4.14)$$

$$\mathbb{P}(B|C=1) = \frac{1}{Z} \Phi_B(B) \cdot M_{A \rightarrow B}(B) = \frac{1}{Z} \Phi_B(B) = \frac{1}{Z} \begin{bmatrix} 1 \\ \exp(\alpha) \end{bmatrix} \quad (4.15)$$

Figure 4.5 shows the values assumed by the marginals when varying the coefficients α and β . As can be seen, the more A , B and C are correlated (i.e. the more α and β are big) the more $\mathbb{P}(B=1|C=1)$ and $\mathbb{P}(A=1|C=1)$ are big. Notice also that when assuming $\alpha = \beta$, $\mathbb{P}(B=1|C=1)$ is always bigger than $\mathbb{P}(A=1|C=1)$. This is intuitively explained by the fact that C is directly connected to B , while A is indirectly connected to C , through B . In the second part, $B=1$ is assumed as evidence and the marginal probabilities of A and C conditioned to B are computed. The theoretical results can be computed again considering the message passing, whose steps are reported in Figure 4.6. The marginal probabilities are in this case equal to:

$$\mathbb{P}(A|B=1) = \frac{1}{Z} \Phi_A(A) = \frac{1}{Z} \begin{bmatrix} 1 \\ \exp(\beta) \end{bmatrix} \quad (4.16)$$

$$\mathbb{P}(C|B=1) = \frac{1}{Z} \Phi_C(C) = \frac{1}{Z} \begin{bmatrix} 1 \\ \exp(\alpha) \end{bmatrix} \quad (4.17)$$


4.2.3 part 03

In this sample, a linear chain of variables $Y_{0,1,2,\dots,n}$ is considered. All variables in the chain have the same *Dom* size and all the factors $\Psi_{1,\dots,n}$, Figure 4.7, are simple exponential correlating factors. The image of the generic factor Ψ_i is reported in the right part of Figure 4.7.

The evidence $Y_0 = 0$ is assumed and the marginals of the last variable in the chain Y_n , i.e. the one furthest to Y_0 , are computed. Figure 4.8 reports the probability $\mathbb{P}(Y_n = 0|Y_0 = 0)$, when varying the chain size, as well the domain size of the variables. As can be seen, the more the chain is longer, the lower is the aforementioned probability, as Y_n is more and more indirectly correlated to Y_0 . Similar considerations hold for the domain size.

4.3 Sample 03: Belief propagation, part B

The aim of this series of examples is to show how to perform probabilistic queries on articulated complex graphs.



$\Psi_i(Y_{i-1}, Y_i)$	$Y_i = 0$	$Y_i = 1$	\dots	$Y_i = m$
$Y_{i-1} = 0$	$\exp(w)$	1	\dots	1
$Y_{i-1} = 1$	1	$\exp(w)$	\dots	1
\vdots	\vdots	\vdots	\ddots	\vdots
$Y_{i-1} = m$	1	1	\dots	$\exp(w)$

Figure 4.7 On the top the chain considered in this example, while on the bottom the image of the generic factor $\Psi_i(Y_{i-1}, Y_i)$.




Figure 4.8 Marginal probability of Y_n when varying the chain size of the structure presented in Figure 4.7. w is assumed equal to 3.5.






Figure 4.9 The factor graph considered by part 01.

Figure 4.10 Belief propagation steps when $E = 1$ is assumed as evidence.Figure 4.11 Belief propagation steps when $D = 1$ is assumed as evidence.




Figure 4.12 The factor graph considered by part 02.

4.3.1 part 01

Part 01 considers a graph made of 5 variables with a Dom size equal to 2 and some simple exponential correlating factors, having different weights. The graph is reported in Figure 4.9, together with the weights of factor $\alpha, \beta, \gamma, \varepsilon$. At first stage, the evidence $E = 1$ is assumed and the marginal probabilities of the other variables are computed with the message passing, whose steps are summarized in Figure 4.10. After the convergence of the message passing, the marginals of the variables are computed as similarly done for the previous examples. In a second phase, the evidence $E = 0$ is assumed. The computation of the marginals is omitted since it is specular to the previous case.

Finally, $D = 1$ is assumed and a new belief propagation is done, whose computations are reported in Figure 4.11.

4.3.2 part 02

Part 02 considers the graph reported in Figure 4.12. All the variables in Figure 4.12 have a domain size equal to 2, and all the factors are simply correlating exponential shape, having a unitary weight. Variables v_1, v_2 and v_3 are treated as evidences and the belief is propagated across the other ones, leading to the computation of the individual marginal probabilities. Since, the addressed structure is a politree (refer to Figure 2.6), the message passing algorithm converges within a finite number of steps.

In principle, the same approach followed in the previous examples can be followed to compute some theoretical results, with the aim of performing the comparisons. Anyway, for this kind of graph such an approach would be too complex. For this reason, results are compared with a Gibbs sampling approach: a series of samples $\mathcal{T} = \{T_1, \dots, T_N\}$ are taken from the joint conditioned distribution $\mathbb{P}(T = v_{4,5,6,7,8,9,10,11,12,13} | v_{1,2,3})$. Then, to evaluate the marginal probability $\mathbb{P}(v_i | v_{1,2,3})$ of a generic hidden variable v_i , the following empirical frequency is computed:

$$\mathbb{P}(v_i = v | v_{1,2,3}) = \frac{\sum_{T_j \in \mathcal{T}} L_{Ti}(T_j, v)}{N} \quad (4.18)$$

where $L_{Ti}(T_j, v)$ is an indicator function equal to 1 only for those samples for which v_i assumed a value equal to v .




Figure 4.13 The factor graph considered by part 03.




Figure 4.14 The factor graph considered by part 04.

4.3.3 part 03

Part 03 considers the graph reported in Figure 4.13. As for the example in the previous part, all variables are binary, and the potentials are simply exponential correlating with a unitary weight. However, this structure is loopy. E is treated as an evidence and the belief propagation is performed considering the loopy version of the message passing discussed in Section 2.2.2.

4.3.4 part 04

The last example in this series, considers a complex loopy graph, represented in Figure 4.14. As for other examples, all the variables are binary and the factors are exponential simply correlating with unitary weights. v_1 is assumed as evidence and the belief is propagated with the loopy version of message passing. Results are compared to the empirical frequencies obtained with a Gibbs sampler, as similarly done for the example of part 02.

4.4 Sample 04: Hidden Markov model like structure

The structure reported in Figure 4.15 is considered in this example. The reported chain is similar to those considered in Hidden Markov models, for which the chain of hidden variables $Y_{1,2,\dots}$ are connected to the chain of evidences $X_{1,2,\dots}$. The potential Φ_{YY_0} , represents an a-priori knowledge about variable Y_1 . All the variables are binary and the potentials are simply correlating exponential potentials. In particular, the ones connecting the hidden variables have a weight equal to w_{YY} , while the ones connecting the evidences to the hidden set share a weight equal to w_{XY} . The evidences are set as indicated in Figure 4.15, i.e. 0 and 1 are alternated in the chain represented by $X_{1,2,\dots}$. The MAP estimation² of the hidden set (Section 2.3) is computed into two different situations:

- case a): $w_{XY} \gg w_{YY}$

¹The same steps are internally execute by Node_factory.

²The Node_factory class is in charge of invoking the proper version of the message passing algorithm that leads to the MAP estimation computation.




Figure 4.15 The chain structure considered by Sample 04.




Figure 4.16 The matricial structure considered by Sample 05.

- case b): $w_{XY} \ll w_{YY}$

Here the point is that when considering case a), the information about the evidences and the correlations between $Y_{1,2,\dots}$ and $X_{1,2,\dots}$ is predominant. On the opposite, when dealing with case b), the correlations among the hidden variables as well as the prior knowledge about Y_0 is predominant. For this reason, for case a) the MAP estimation of the hidden variables is equal to $h_{MAP}^a = \{0, 1, 0, 1, \dots\}$, while for case b) the MAP estimation is equal to $h_{MAP}^b = \{0, 0, 0, 0, \dots\}$.

4.5 Sample 05: Matricial structure

The matrix-like structure reported in Figure 4.16 is considered in this example. The variables in the matrix have all the same domain size and they are correlated by the potentials populating the matrix, which are all simple exponential correlating factors sharing the same weight. The example builds the matrix and then assumes $Y_{0,0} = 0$ as an evidence. Then, the marginals of the variables along the diagonal of the matrix, i.e. $Y_{i,i}$, are evaluated. As can be seen, the marginal probability $\mathbb{P}(Y_{i,i} = 0 | Y_{0,0})$ decreases descending the diagonal. Figure 4.17 reports the results obtained when varying the weight of the correlating factors, on a matrix made of 10×10 variables having a *Dom* size equal to 3.




Figure 4.17 The marginals of variables $Y_{i,i}$, conditioned to $Y_{0,0} = 0$ as evidence of the graph reported in Figure 4.16, when varying the weight of the correlating exponential factors involved in the structure.




Figure 4.18 The graph considered by part 01.

4.6 Sample 06: Learning, part A

The aim of this series of examples is to show how to perform the learning of factor graphs. In all the examples contained in this Section, learning is done with the following methodology. A Gibbs sampler is used to take samples from the joint distribution correlating all the variables in a model A. Model A is actually the model to learn. The training set obtained from model A, is used to train a model B. Model B has the same variables and factors of model A, but with different values for the free parameters $w_{1,2,\dots}$ (Section 2.6). In this way, after having performed the learning, the value of the free parameters in model B will assume similar values to the ones in model A, showing the effectiveness of the functionalities contained in EFG. Clearly, this is not the approach followed in real applications, where the real coefficient of the model are unknown and only a training set of examples are available.

4.6.1 part 01

Part 01 considers the loopy graph reported in Figure 4.18. A , B and C are all binary variables, while Ψ_{AB} , Ψ_{AC} and Ψ_{BC} are simple correlating exponential distributions having as weights, respectively, α , β and γ .

In the initial part of this example, a Gibbs sampler draw samples from the joint distribution of A , B and C , with the aim of validating the Gibbs sampler. Indeed, some empirical frequencies of some specific combinations are compared with the theoretical probabilities. The theoretical results are computed considering the energy function $E(A, B, C)$ of the graph, reported in table 4.2 (for instance $\mathbb{P}(A = 0, B = 0, C = 1) = \frac{E(0,0,1)}{Z}$).

At a second stage, the samples obtained by the Gibbs sampler are exploited for performing learning on model B (see the initial part of this Section).

4.6.2 part 02

Part 02 considers a structure made of both tunable and non-tunable factors. The considered structure is reported in Figure 4.19. Weights β and γ must be tuned through learning, while α and γ are constant and known (refer also to the formalism described in Figure 2.2).

A	B	C	Ψ_{AB}	Ψ_{BC}	Ψ_{AC}	$E(A, B, C) = \Psi_{AB} \cdot \Psi_{BC} \cdot \Psi_{AC}$
0	0	0	$\exp(\alpha)$	$\exp(\gamma)$	$\exp(\beta)$	$\exp(\alpha)\exp(\beta)\exp(\gamma)$
1	0	0	1	$\exp(\gamma)$	1	$\exp(\gamma)$
0	1	0	1	1	$\exp(\beta)$	$\exp(\beta)$
1	1	0	$\exp(\alpha)$	1	1	$\exp(\alpha)$
0	0	1	$\exp(\alpha)$	1	1	$\exp(\alpha)$
1	0	1	1	1	$\exp(\beta)$	$\exp(\beta)$
0	1	1	1	$\exp(\gamma)$	1	$\exp(\gamma)$
1	1	1	$\exp(\alpha)$	$\exp(\gamma)$	$\exp(\beta)$	$\exp(\alpha)\exp(\beta)\exp(\gamma)$

Table 4.2 Factors involved in the graph of Figure 2.8. Summing all the possible values of E , the ripartition function results equal to $Z = \sum E(A, B, C) = 2 \left(\exp(\alpha) + \exp(\beta) + \exp(\gamma) + \exp(\alpha)\exp(\beta)\exp(\gamma) \right)$.




Figure 4.19 The graph considered by part 02.

4.6.3 part 03

Part 03 considers the loopy structure reported in Section 4.3.4. However, here instead of having constant exponential shapes, all the factors are made of tunable exponentials. The value assumed by the weight of model A (see the introduction of this Section) are showed in Figure 4.20.

4.6.4 part 04

Part 04 considers the structure reported in Figure 4.21, for which all the potentials connecting pairs Y_{i-1}, Y_i share the same weight α , while the factors connecting pairs X_i, Y_i share the weight β . The approach described in Section 2.6.3 is internally followed by EFG to learn such a structure.




Figure 4.20 The graph considered by part 03.




Figure 4.21 The graph considered by part 04.




Figure 4.22 The conditional random field considered in Sample 07.

4.7 Sample 07: Learning, part B

The aim of this example is to show how the learning process can be done when dealing with Conditional random fields. In particular, the structure reported in Figure 4.22 is considered (values of the free parameters are not indicated, since the reader may refer to the sources provided).

The approach adopted is similar to the one followed in the previous series of example, considering a couple of model A and B (see the initial part of the previous Section). However, in this case we cannot simply draw samples from the joint distribution correlating the variables in the model, since such a distribution does not exist. Indeed, the conditional random field of Figure 4.22, models the conditional distribution of variables $Y_{1,2,\dots}$ w.r.t the evidences $X_{1,2,\dots}$. For this reason, all the possible combination of evidences are determined, considering all $x \in \{Dom(X_1) \cup Dom(X_2) \cup \dots\}$. For each x , samples from the conditioned distribution $\mathbb{P}(Y_{1,2,\dots}|x)$ are taken with a Gibbs sampler. The entire population of samples determined is actually the training set adopted for training the conditional random field in Figure 4.22.

4.8 Sample 08: Sub-graphing

4.8.1 part 01

The chain structure described in Figure 4.23 is addressed in this example. The sub-graphs containing variables A, B, C and A, B are built, in order to compute the joint marginal probability distributions of that two groups of variables.

The values are compared to the real ones, obtained by considering the joint distribution³ of all the variables in the

³Which is significantly time consuming to compute. For this reason, the SubGraph class is able to compute the marginals without explicitly compute the entire joint distribution of the variables in the model. Here we want just to compare the theoretical result with the one obtained by the SubGraph class.




Figure 4.23 The chain considered in the example. All the underlying simple shapes are simple correlating.

A	B	$\mathbb{P}(A, B)$
0	0	$\frac{\exp(\alpha)}{1+\exp(\alpha)}$
0	1	$\frac{1}{1+\exp(\alpha)}$
1	0	$\frac{1}{1+\exp(\alpha)}$
1	1	$\frac{\exp(\alpha)}{1+\exp(\alpha)}$

A	B	C	$\mathbb{P}(A, B, C)$
0	0	0	$\frac{1}{Z_{ABC}} \cdot \exp(\alpha)\exp(\beta)$
0	1	0	$\frac{1}{Z_{ABC}}$
1	0	0	$\frac{1}{Z_{ABC}} \cdot \exp(\beta)$
1	1	0	$\frac{1}{Z_{ABC}} \cdot \exp(\alpha)$
0	0	1	$\frac{1}{Z_{ABC}} \cdot \exp(\alpha)$
0	1	1	$\frac{1}{Z_{ABC}} \cdot \exp(\beta)$
1	0	1	$\frac{1}{Z_{ABC}}$
1	1	1	$\frac{1}{Z_{ABC}} \cdot \exp(\alpha)\exp(\beta)$

Figure 4.24 Marginal probabilities of the sub-groups $\{A, B, C\}$ and $\{A, B\}$. The normalization coefficient

$$Z_{ABC} \text{ is equal to } Z_{ABC} = 2 \left(1 + \exp(\alpha) + \exp(\beta) + \exp(\alpha)\exp(\beta) \right).$$

chain, which can be obtained by computing the energy function E , equation (2.5) (computations are here omitted for brevity). Knowing the joint distribution of a group of variables, the marginal distribution of a sub-group can be obtained by marginalization, equation (2.3):

$$\begin{aligned} \mathbb{P}(A = a, B = b, C = c) &= \sum_{\tilde{d} \in \text{Dom}(D)} \mathbb{P}(A = a, B = b, C = c, D = \tilde{d}) \\ \mathbb{P}(A = a, B = b) &= \sum_{\tilde{c} \in \text{Dom}(C), \tilde{d} \in \text{Dom}(D)} \mathbb{P}(A = a, B = b, C = \tilde{c}, D = \tilde{d}) \end{aligned} \quad (4.19)$$

Applying the above rules to the chain of Figure 4.23 leads to obtain the theoretical marginal distributions indicated in Figure 4.24.

4.8.2 part 02

The aim of this example is to show how sub-graphs (see Section 2.5) can be computed using SubGraph. The example starts building the structure described in Figure 4.25 (refer to the sources for the details regarding the variables and factors involved in the structure) and assumes the following evidences: $X_1 = 0$ and $X_2 = 0$. Then, the two sub-graphs considering the sub-group of variables $A_{1,2,3,4}$ and $B_{1,2,3}$ are computed, refer to Figure 4.25. The marginal probabilities of some combinations for $A_{1,2,3,4}$ conditioned to the evidences $X_{1,2}$ are computed and compared with the empirical frequencies computed considering a samples set produced by a Gibb sampler on the entire graph: samples for $t = A_{1,2,3,4}, B_{1,2,3}$ are drawn and the empirical frequencies of specific combinations of $A_{1,2,3,4}$ are computed as similarly done in 4.3.2. The same thing is done for the sub-graph $B_{1,2,3}$. At a second stage, the evidences $X_{1,2}$ are changed and the sub-graphs, as well as the marginal probabilities, are consequently recomputed.




Figure 4.25 On the top, the graph considered by Sample 08, while on the bottom the sub-structures of the two groups $A_{1,2,3,4}$ and $B_{1,2,3}$.

Chapter 5

Namespace Index

5.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

EFG	51
EFG::categoric	51
EFG::distribution	52
EFG::distribution::factor	53
EFG::distribution::factor::cnst	54
EFG::distribution::factor::modif	54
EFG::io	54
EFG::io::json	55
EFG::io::xml	55
EFG::iterator	55
EFG::model	57
EFG::nodes	57
EFG::train	58
EFG::train::handler	58

Chapter 6

Hierarchical Index

6.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

EFG::nodes::Base	59
EFG::nodes::BeliefAware	60
EFG::nodes::BeliefPropagator	61
EFG::model::ConditionalRandomField	65
EFG::model::Graph	92
EFG::model::RandomField	106
EFG::nodes::EvidencesChanger	79
EFG::model::ConditionalRandomField	65
EFG::model::Graph	92
EFG::model::RandomField	106
EFG::nodes::EvidencesSetter	81
EFG::model::ConditionalRandomField	65
EFG::model::Graph	92
EFG::model::RandomField	106
EFG::nodes::InsertCapable	99
EFG::model::Graph	92
EFG::nodes::InsertTunableCapable	102
EFG::model::ConditionalRandomField	65
EFG::model::RandomField	106
EFG::nodes::QueryHandler	105
EFG::model::ConditionalRandomField	65
EFG::model::Graph	92
EFG::model::RandomField	106
EFG::train::Trainable	114
EFG::model::ConditionalRandomField	65
EFG::model::RandomField	106
EFG::nodes::EvidenceAware	79
EFG::nodes::BeliefPropagator	61
EFG::nodes::EvidencesChanger	79
EFG::nodes::EvidencesSetter	81
EFG::nodes::GibbsSampler	90
EFG::model::ConditionalRandomField	65
EFG::model::Graph	92
EFG::model::RandomField	106

EFG::nodes::InsertCapable	99
EFG::nodes::QueryHandler	105
EFG::nodes::NodesAware	104
EFG::nodes::EvidencesChanger	79
EFG::nodes::EvidencesSetter	81
EFG::nodes::InsertCapable	99
EFG::nodes::QueryHandler	105
EFG::train::Trainable	114
EFG::nodes::StructureAware	111
EFG::nodes::InsertCapable	99
EFG::nodes::StructureTunableAware	112
EFG::nodes::InsertTunableCapable	102
EFG::train::Trainable	114
EFG::categoric::Combination	63
EFG::nodes::Connection	67
EFG::distribution::Distribution	67
EFG::distribution::DistributionInstantiable	71
EFG::distribution::factor::cnst::Factor	85
EFG::distribution::factor::cnst::IndicatorFactor	98
EFG::distribution::factor::modif::Factor	84
EFG::distribution::factor::cnst::FactorExponential	88
EFG::distribution::factor::modif::FactorExponential	87
EFG::distribution::DistributionSetter	74
EFG::distribution::factor::cnst::FactorExponential	88
EFG::distribution::factor::modif::Factor	84
EFG::distribution::factor::modif::FactorExponential	87
EFG::distribution::DistributionFinder	70
EFG::distribution::Evaluator	76
EFG::distribution::factor::EvaluatorBasic	76
EFG::distribution::factor::EvaluatorExponential	78
EFG::io::Exporter	82
EFG::io::json::Exporter	83
EFG::io::xml::Exporter	82
EFG::iterator::Forward	89
EFG::categoric::Range	108
EFG::iterator::Bidirectional	62
EFG::iterator::StlBidirectional< IteratorStl >	110
EFG::iterator::StlBidirectional< std::map< categoric::Combination, float >::const_iterator >	110
EFG::distribution::DistributionIterator	72
EFG::categoric::Group	93
EFG::nodes::HiddenClusters	96
EFG::io::Importer	98
EFG::io::xml::Importer	97
EFG::nodes::Node	103
EFG::nodes::PropagationResult	105
runtime_error	
EFG::Error	75
EFG::train::Trainer	115
EFG::train::GradientDescend< Extractor >	91
EFG::train::TrainHandler	116
EFG::train::handler::BaseHandler	59
EFG::train::handler::BinaryHandler	62
EFG::train::handler::UnaryHandler	119
EFG::train::handler::CompositeHandler	65
EFG::train::TrainSet	117

EFG::train::TrainSetExtractor	118
EFG::train::BasicExtractor	60
EFG::train::GradientDescend< Extractor >	91
EFG::train::StochasticExtractor	111
EFG::categoric::Variable	119

Chapter 7

Class Index

7.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

EFG::nodes::Base	59
EFG::train::handler::BaseHandler	59
EFG::train::BasicExtractor	60
EFG::nodes::BeliefAware	60
EFG::nodes::BeliefPropagator	61
EFG::iterator::Bidirectional	
A Bidirectional iterable object, both incrementable and decrementable	62
EFG::train::handler::BinaryHandler	62
EFG::categoric::Combination	
An immutable combination of discrete values	63
EFG::train::handler::CompositeHandler	65
EFG::model::ConditionalRandomField	65
EFG::nodes::Connection	67
EFG::distribution::Distribution	
Base object for any kind of categoric distribution. Any kind of categoric distribution has:	67
EFG::distribution::DistributionFinder	
An object used to search for big combinations inside a Distribution	70
EFG::distribution::DistributionInstantiable	71
EFG::distribution::DistributionIterator	
An object able to iterate the domain/images of a distribution	72
EFG::distribution::DistributionSetter	74
EFG::Error	
A runtime error that can be raised when using any object in EFG::	75
EFG::distribution::Evaluator	76
EFG::distribution::factor::EvaluatorBasic	
Image = $\exp(w * \text{rowImage})$	76
EFG::distribution::factor::EvaluatorExponential	
An exponential function with weight w is used to obtain the image, i.e. image = $\exp(w * \text{row} \leftrightarrow \text{Image})$	78
EFG::nodes::EvidenceAware	79
EFG::nodes::EvidencesChanger	79
EFG::nodes::EvidencesSetter	81
EFG::io::Exporter	82
EFG::io::xml::Exporter	82
EFG::io::json::Exporter	83

EFG::distribution::factor::modif::Factor	84
EFG::distribution::factor::cnst::Factor	
A factor using the EvaluatorBasic object to convert the raw images into images	85
EFG::distribution::factor::modif::FactorExponential	87
EFG::distribution::factor::cnst::FactorExponential	
A factor using the EvaluatorExponential object to convert the raw images into images	88
EFG::iterator::Forward	
A Forward iterable object	89
EFG::nodes::GibbsSampler	90
EFG::train::GradientDescend< Extractor >	91
EFG::model::Graph	
A simple graph object, that can't store tunable factors	92
EFG::categoric::Group	
An ensemble of categoric variables. Each variable in the ensemble should have its own unique name	93
EFG::nodes::HiddenClusters	96
EFG::io::xml::Importer	97
EFG::io::Importer	98
EFG::distribution::factor::cnst::IndicatorFactor	
An indicator distribution having only one combination explicitly stated, whose image is equal to 1	98
EFG::nodes::InsertCapable	99
EFG::nodes::InsertTunableCapable	102
EFG::nodes::Node	103
EFG::nodes::NodesAware	104
EFG::nodes::PropagationResult	105
EFG::nodes::QueryHandler	105
EFG::model::RandomField	106
EFG::categoric::Range	
This object allows you to iterate all the elements in the joint domain of a group of variables, without precomputing all the elements in such domain. For example when having a domain made by variables = { A (size = 2), B (size = 3), C (size = 2) }, the elements in the joint domain that will be iterated are: <0,0,0> <0,0,1> <0,1,0> <0,1,1> <0,2,0> <0,2,1> <1,0,0> <1,0,1> <1,1,0> <1,1,1> <1,2,0> <1,2,1> After construction, the Range object starts to point to the first element in the joint domain <0,0,...>. Then, when incrementing the object, the following element is pointed. When calling get() the current pointed element can be accessed	108
EFG::iterator::StdBidirectional< IteratorStd >	
A bidirectional iterator built on top of an std iterator type	110
EFG::train::StochasticExtractor	111
EFG::nodes::StructureAware	111
EFG::nodes::StructureTunableAware	112
EFG::train::Trainable	
An object storing tunable factors, whose weights can be tuned with training	114
EFG::train::Trainer	115
EFG::train::TrainHandler	116
EFG::train::TrainSet	117
EFG::train::TrainSetExtractor	118
EFG::train::handler::UnaryHandler	119
EFG::categoric::Variable	
An object representing an immutable categoric variable	119

Chapter 8

Namespace Documentation

8.1 EFG Namespace Reference

Namespaces

- [categorical](#)
- [distribution](#)
- [io](#)
- [iterator](#)
- [model](#)
- [nodes](#)
- [train](#)

Classes

- class [Error](#)

A runtime error that can be raised when using any object in [EFG::](#)

8.1.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.2 EFG::categorical Namespace Reference

Classes

- class [Combination](#)

An immutable combination of discrete values.

- class [Group](#)

An ensemble of categorical variables. Each variable in the ensemble should have its own unique name.

- class [Range](#)

This object allows you to iterate all the elements in the joint domain of a group of variables, without precomputing all the elements in such domain. For example when having a domain made by variables = { A (size = 2), B (size = 3), C (size = 2) }, the elements in the joint domain that will be iterated are: <0,0,0> <0,0,1> <0,1,0> <0,1,1> <0,2,0> <0,2,1> <1,0,0> <1,0,1> <1,1,0> <1,1,1> <1,2,0> <1,2,1> After construction, the [Range](#) object starts to point to the first element in the joint domain <0,0,...>. Then, when incrementing the object, the following element is pointed. When calling [get\(\)](#) the current pointed element can be accessed.

- class [Variable](#)

An object representing an immutable categorical variable.

Typedefs

- typedef std::shared_ptr< [Variable](#) > **VariablePtr**

Functions

- bool **operator**< (const VariablePtr &a, const VariablePtr &b)
- bool **operator**== (const VariablePtr &a, const VariablePtr &b)
- std::set< VariablePtr > [getComplementary](#) (const std::set< VariablePtr > &set, const std::set< VariablePtr > &subset)
get the complementary group of the subset w.r.t a certain set. For instance the complementary of <A,C> w.r.t. <A,B,C,D,E> is <B,D,E>
- VariablePtr **makeVariable** (const std::size_t &size, const std::string &name)

8.2.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.2.2 Function Documentation

8.2.2.1 getComplementary()

```
std::set<VariablePtr> EFG::categoric::getComplementary (
    const std::set< VariablePtr > & set,
    const std::set< VariablePtr > & subset )
```

get the complementary group of the subset w.r.t a certain set. For instance the complementary of <A,C> w.r.t. <A,B,C,D,E> is <B,D,E>

Exceptions

<i>when</i>	not all variables in subset are present in set
<i>when</i>	the complementary is an empty set

8.3 EFG::distribution Namespace Reference

Namespaces

- [factor](#)

Classes

- class [Distribution](#)
Base object for any kind of categoric distribution. Any kind of categoric distribution has:
- class [DistributionFinder](#)
An object used to search for big combinations inside a [Distribution](#).
- class [DistributionInstantiable](#)
- class [DistributionIterator](#)
An object able to iterate the domain/images of a distribution.
- class [DistributionSetter](#)
- class [Evaluator](#)

Typedefs

- typedef std::shared_ptr< [Distribution](#) > **DistributionPtr**
- typedef std::shared_ptr< [Evaluator](#) > **EvaluatorPtr**

8.3.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.4 EFG::distribution::factor Namespace Reference

Namespaces

- [cnst](#)
- [modif](#)

Classes

- class [EvaluatorBasic](#)
 $image = exp(w * rowImage)$
- class [EvaluatorExponential](#)
*An exponential function with weight w is used to obtain the image, i.e. $image = exp(w * rowImage)$*

8.4.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.5 EFG::distribution::factor::cnst Namespace Reference

Classes

- class [Factor](#)
A factor using the [EvaluatorBasic](#) object to convert the raw images into images.
- class [FactorExponential](#)
A factor using the [EvaluatorExponential](#) object to convert the raw images into images.
- class [IndicatorFactor](#)
An indicator distribution having only one combination explicitly stated, whose image is equal to 1.

8.5.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.6 EFG::distribution::factor::modif Namespace Reference

Classes

- class [Factor](#)
- class [FactorExponential](#)

8.6.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.7 EFG::io Namespace Reference

Namespaces

- [json](#)
- [xml](#)

Classes

- class [Exporter](#)
- class [Importer](#)

8.7.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.8 EFG::io::json Namespace Reference

Classes

- class [Exporter](#)

8.8.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.9 EFG::io::xml Namespace Reference

Classes

- class [Exporter](#)
- class [Importer](#)

8.9.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.10 EFG::iterator Namespace Reference

Classes

- class [Bidirectional](#)
A [Bidirectional](#) iterable object, both incrementable and decrementable.
- class [Forward](#)
A [Forward](#) iterable object.
- class [StlBidirectional](#)
A bidirectional iterator built on top of an std iterator type.

Functions

- `template<typename Iter , typename Action >`
`void forEach (Iter &iter, Action action)`
takes an iterator to increment till the end, calling at every iteration the passed action.
- `template<typename Iter , typename ActionCondition >`
`void forEachConditioned (Iter &iter, ActionCondition action)`
similar to forEach(...), but in this case the action should be a predicate, taking as input the iterator and returning true when the loop should be terminated before reaching the end of the iterator.

8.10.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.10.2 Function Documentation

8.10.2.1 forEach()

```
template<typename Iter , typename Action >
void EFG::iterator::forEach (
    Iter & iter,
    Action action )
```

takes an iterator to increment till the end, calling at every iteration the passed action.

Parameters

<i>the</i>	iterator to increment
<i>an</i>	action taking as input the iterator for every iteration

8.10.2.2 forEachConditioned()

```
template<typename Iter , typename ActionCondition >
void EFG::iterator::forEachConditioned (
    Iter & iter,
    ActionCondition action )
```

similar to forEach(...), but in this case the action should be a predicate, taking as input the iterator and returning true when the loop should be terminated before reaching the end of the iterator.

Parameters

<i>the</i>	iterator to increment
<i>an</i>	action taking as input the iterator for every iteration and returning true when the loop should break

8.11 EFG::model Namespace Reference

Classes

- class [ConditionalRandomField](#)
- class [Graph](#)
A simple graph object, that can't store tunable factors.
- class [RandomField](#)

8.11.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andreca91@gmail.com.

8.12 EFG::nodes Namespace Reference

Classes

- class [Base](#)
- class [BeliefAware](#)
- class [BeliefPropagator](#)
- struct [Connection](#)
- class [EvidenceAware](#)
- class [EvidencesChanger](#)
- class [EvidencesSetter](#)
- class [GibbsSampler](#)
- struct [HiddenClusters](#)
- class [InsertCapable](#)
- class [InsertTunableCapable](#)
- struct [Node](#)
- class [NodesAware](#)
- struct [PropagationResult](#)
- class [QueryHandler](#)
- class [StructureAware](#)
- class [StructureTunableAware](#)

Enumerations

- enum **PropagationKind** { **Sum**, **MAP** }

Functions

- void **copyCluster** (std::set< [Node](#) * > &recipient, const std::set< [Node](#) * > &toAdd)

8.12.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andrecasa91@gmail.com.

8.13 EFG::train Namespace Reference

Namespaces

- [handler](#)

Classes

- class [BasicExtractor](#)
- class [GradientDescend](#)
- class [StochasticExtractor](#)
- class [Trainable](#)

An object storing tunable factors, whose weights can be tuned with training.

- class [Trainer](#)
- class [TrainHandler](#)
- class [TrainSet](#)
- class [TrainSetExtractor](#)

Typedefs

- typedef std::unique_ptr< [TrainHandler](#) > **TrainHandlerPtr**
- typedef std::shared_ptr< [categoric::Combination](#) > **CombinationPtr**
- typedef std::shared_ptr< [TrainSet](#) > **TrainSetPtr**

Functions

- void **printTrainSet** (const [TrainSet](#) &trainSet, const std::string &fileName)

8.13.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021

report any bug to andrecasa91@gmail.com.

8.14 EFG::train::handler Namespace Reference

Classes

- class [BaseHandler](#)
- class [BinaryHandler](#)
- class [CompositeHandler](#)
- class [UnaryHandler](#)

8.14.1 Detailed Description

Author: Andrea Casalino Created: 01.01.2021


report any bug to andrecasa91@gmail.com.

Chapter 9

Class Documentation

9.1 EFG::nodes::Base Class Reference

Inheritance diagram for EFG::nodes::Base:



Public Member Functions


- **Base** (const **Base** &)=delete
- **Base** & **operator=** (const **Base** &)=delete

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/bases/Base.h

9.2 EFG::train::handler::BaseHandler Class Reference

Inheritance diagram for EFG::train::handler::BaseHandler:



Public Member Functions

- void **setTrainSet** (TrainSetPtr newSet, const std::set< categoric::VariablePtr > &modelVariables) final
- float **getGradientAlpha** () final
- void **setWeight** (const float &w) final

Protected Member Functions

- **BaseHandler** (std::shared_ptr< [distribution::factor::modif::FactorExponential](#) > factor)
- float **dotProduct** (const std::vector< float > &prob) const

Protected Attributes


- std::shared_ptr< [distribution::factor::modif::FactorExponential](#) > **factor**
- float **gradientAlpha** = 0.f

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/handlers/BaseHandler.h

9.3 EFG::train::BasicExtractor Class Reference

Inheritance diagram for EFG::train::BasicExtractor:



Protected Member Functions


- TrainSetPtr **getTrainSet** () override

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/trainers/TrainSetExtractor.h

9.4 EFG::nodes::BeliefAware Class Reference

Inheritance diagram for EFG::nodes::BeliefAware:



Public Member Functions

- void **setMaxIterationsLoopyPropagation** (std::size_t iterations)
- std::size_t **getMaxIterationsLoopyPropagation** () const
- [PropagationResult](#) **getLastPropagationResult** () const

Protected Member Functions

- virtual void **propagateBelief** (const PropagationKind &kind)=0

Protected Attributes


- std::size_t [maxIterationsLoopyPropagation](#) = 100
maximum number of iterations considered when doing loopy propagation
- std::unique_ptr< [PropagationResult](#) > [lastPropagation](#)
results about the last belief propagation done. It is a nullptr until the first propagation is triggered

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/bases/BeliefAware.h

9.5 EFG::nodes::BeliefPropagator Class Reference

Inheritance diagram for EFG::nodes::BeliefPropagator:



Protected Member Functions

- void **propagateBelief** (const PropagationKind &kind) override

Additional Inherited Members

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/BeliefPropagator.h

9.6 EFG::iterator::Bidirectional Class Reference

A [Bidirectional](#) iterable object, both incrementable and decrementable.

```
#include <Bidirectional.h>
```

Inheritance diagram for EFG::iterator::Bidirectional:



Public Member Functions

- virtual void **operator--** ()=0

9.6.1 Detailed Description


A [Bidirectional](#) iterable object, both incrementable and decrementable.

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/iterator/Bidirectional.h

9.7 EFG::train::handler::BinaryHandler Class Reference

Inheritance diagram for EFG::train::handler::BinaryHandler:



Public Member Functions

- **BinaryHandler** ([nodes::Node](#) &nodeA, [nodes::Node](#) &nodeB, std::shared_ptr< [distribution::factor::modif::FactorExponential](#) > factor)
- float **getGradientBeta** () final

Protected Attributes

- `nodes::Node * nodeA`
- `nodes::Node * nodeB`

Additional Inherited Members

The documentation for this class was generated from the following file:

- `C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/handlers/BinaryHandler.h`

9.8 EFG::categoric::Combination Class Reference

An immutable combination of discrete values.

```
#include <Combination.h>
```

Public Member Functions

- `Combination (std::size_t bufferSize)`
A buffer of zeros with the passed size is created.
- `Combination (const std::size_t *buffer, std::size_t bufferSize)`
The passed buffer is copied to create this one.
- `Combination (const Combination &o)`
- `Combination & operator= (const Combination &o)`
- `bool operator< (const Combination &o) const`
compare two equally sized combination. Examples of ordering: <0,0,0> < <0,1,0> <0,1> < <1,0>
- `std::size_t size () const`
- `const std::size_t * data () const`
- `std::size_t * data ()`

9.8.1 Detailed Description

An immutable combination of discrete values.

9.8.2 Constructor & Destructor Documentation

9.8.2.1 Combination() [1/2]

```
EFG::categoric::Combination::Combination (
    std::size_t bufferSize )
```

A buffer of zeros with the passed size is created.

Exceptions

<i>if</i>	bufferSize is 0
-----------	-----------------

9.8.2.2 Combination() [2/2]

```
EFG::categoric::Combination::Combination (
    const std::size_t * buffer,
    std::size_t bufferSize )
```

The passed buffer is copied to create this one.

Parameters

<i>the</i>	buffer to clone
<i>the</i>	buffer size

9.8.3 Member Function Documentation

9.8.3.1 operator<()

```
bool EFG::categoric::Combination::operator< (
    const Combination & o ) const
```

compare two equally sized combination. Examples of ordering: <0,0,0> < <0,1,0> <0,1> < <1,0>

Exceptions

<i>when</i>	<i>o</i> has a different size
-------------	-------------------------------

9.8.3.2 operator=()

```
Combination& EFG::categoric::Combination::operator= (
    const Combination & o )
```

Exceptions


<i>when</i>	<i>o</i> has a different size
-------------	-------------------------------

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/categoric/Combination.h

9.9 EFG::train::handler::CompositeHandler Class Reference

Inheritance diagram for EFG::train::handler::CompositeHandler:



Public Member Functions

- **CompositeHandler** (TrainHandlerPtr elementA, TrainHandlerPtr elementB)
- void **setTrainSet** (TrainSetPtr newSet, const std::set< categoric::VariablePtr > &modelVariables) final
- float **getGradientAlpha** () final
- float **getGradientBeta** () final
- void **setWeight** (const float &w) final
- void **addElement** (TrainHandlerPtr element)

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/handlers/CompositeHandler.h

9.10 EFG::model::ConditionalRandomField Class Reference

Inheritance diagram for EFG::model::ConditionalRandomField:



Public Member Functions

- `template<typename Model >`
`ConditionalRandomField` (const Model &o)
- **ConditionalRandomField** (const `ConditionalRandomField` &o)
- `ConditionalRandomField` (const std::string &filePath, const std::string &fileName)
import the model from an xml file
- void `insertTunable` (std::shared_ptr< `distribution::factor::modif::FactorExponential` > toInsert) override
insert the passed tunable factor.
- void `insertTunable` (std::shared_ptr< `distribution::factor::modif::FactorExponential` > toInsert, const std::set< `categoric::VariablePtr` > &potentialSharingWeight) override
insert the passed tunable factor, sharing the weight with an already inserted one.

Additional Inherited Members

9.10.1 Constructor & Destructor Documentation

9.10.1.1 ConditionalRandomField() [1/2]

```
template<typename Model >
EFG::model::ConditionalRandomField::ConditionalRandomField (
    const Model & o ) [inline], [explicit]
```

Exceptions

<i>in</i>	case no evidences are present in the passed model
-----------	---

9.10.1.2 ConditionalRandomField() [2/2]

```
EFG::model::ConditionalRandomField::ConditionalRandomField (
    const std::string & filePath,
    const std::string & fileName )
```

import the model from an xml file

Parameters

<i>the</i>	folder storing the xml to read
<i>the</i>	name of the xml to read

Exceptions

<i>in</i>	case no evidences are set in the file
-----------	---------------------------------------

9.10.2 Member Function Documentation

9.10.2.1 insertTunable()

```
void EFG::model::ConditionalRandomField::insertTunable (
    std::shared_ptr< distribution::factor::modif::FactorExponential > toInsert,
    const std::set< categoric::VariablePtr > & potentialSharingWeight ) [override],
[virtual]
```

insert the passed tunable factor, sharing the weight with an already inserted one.

Parameters

<i>the</i>	factor to insert
<i>the</i>	set of variables identifying the potential whose weight is to share

Reimplemented from [EFG::nodes::InsertTunableCapable](#).

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/model/ConditionalRandomField.h

9.11 EFG::nodes::Connection Struct Reference

Public Member Functions

- **Connection** (distribution::DistributionPtr factor, std::unique_ptr< [distribution::Distribution](#) > message=nullptr)
- **Connection** ([Connection](#) &&o)

Public Attributes

- distribution::DistributionPtr **factor**
- std::unique_ptr< [distribution::Distribution](#) > **message2This**

The documentation for this struct was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/Node.h

9.12 EFG::distribution::Distribution Class Reference

Base object for any kind of categoric distribution. Any kind of categoric distribution has:

```
#include <Distribution.h>
```

Inheritance diagram for EFG::distribution::Distribution:



Public Member Functions

- const [categoric::Group](#) & **getGroup** () const
- [DistributionIterator](#) **getIterator** () const
- float **find** (const [categoric::Combination](#) &comb) const
searches for the image associated to an element in the domain
- float **findRaw** (const [categoric::Combination](#) &comb) const
searches for the raw image associated to an element in the domain
- [DistributionFinder](#) **getFinder** (const std::set< categoric::VariablePtr > &containingGroup) const
- std::vector< float > **getProbabilities** () const

Protected Member Functions

- void **checkCombination** (const [categoric::Combination](#) &comb, const float &value) const

Protected Attributes

- std::unique_ptr< [categoric::Group](#) > **group**
- std::shared_ptr< std::map< [categoric::Combination](#), float > > **values**
the ordered pairs of <domain combination, raw image value>
- EvaluatorPtr **evaluator**
the function used to convert raw images into images

Friends

- class **DistributionIterator**
- class **DistributionFinder**

9.12.1 Detailed Description

Base object for any kind of categoric distribution. Any kind of categoric distribution has:

- A domain, represented by the combinations in the joint domain of the Group associated to this distribution
- Raw images set, which are positive values associated to each element in the domain
- Images set, which are the image values associated to each element in the domain. They can be obtained by applying a certain function $f(x)$ to the raw images. In order to save memory, the combinations having an image equal to 0 are not explicitly saved even if they are accounted for the operations involving this distribution.

9.12.2 Member Function Documentation

9.12.2.1 find()

```
float EFG::distribution::Distribution::find (
    const categoric::Combination & comb ) const
```

searches for the image associated to an element in the domain

Returns

the value of the image.

9.12.2.2 findRaw()

```
float EFG::distribution::Distribution::findRaw (
    const categoric::Combination & comb ) const
```

searches for the raw image associated to an element in the domain

Returns

the value of the raw image.

9.12.2.3 getFinder()

```
DistributionFinder EFG::distribution::Distribution::getFinder (
    const std::set< categoric::VariablePtr > & containingGroup ) const
```

Returns

a [DistributionFinder](#) referring to this object

9.12.2.4 getIterator()

```
DistributionIterator EFG::distribution::Distribution::getIterator ( ) const
```

Returns

a [DistributionIterator](#) referring to this object

9.12.2.5 getProbabilities()

```
std::vector<float> EFG::distribution::Distribution::getProbabilities ( ) const
```

Returns

the probabilities associated to each combination in the domain, when assuming only the existence of this distribution. Such probabilities are the normalized images. The order of returned values, refer to the combination order obtained by iterating with the [categoric::Range](#) object.

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/Distribution.h

9.13 EFG::distribution::DistributionFinder Class Reference

An object used to search for big combinations inside a [Distribution](#).

```
#include <DistributionFinder.h>
```

Public Member Functions

- [DistributionFinder](#) (const [Distribution](#) &distribution, const std::set< [categoric::VariablePtr](#) > &containingGroup)
- **DistributionFinder** (const [DistributionFinder](#) &)=default
- [DistributionFinder](#) & **operator=** (const [DistributionFinder](#) &)=default
- std::pair< const [categoric::Combination](#) *, float > **find** (const [categoric::Combination](#) &comb) const
searches for matches. For example assume having built this object with a containingGroup equal to <A,B,C,D> and the variables describing the domain of the reference distribution equal to <B,D>. When passing comb ad <0,1,2,0>, it searches for the <combination,image> pertaining to this combination combination <B,D> = <1,0>.
- std::pair< const [categoric::Combination](#) *, float > **findRaw** (const [categoric::Combination](#) &comb) const
similar to DistributionFinder::find(...), but returning the raw image value.

9.13.1 Detailed Description

An object used to search for big combinations inside a [Distribution](#).

9.13.2 Constructor & Destructor Documentation

9.13.2.1 DistributionFinder()

```
EFG::distribution::DistributionFinder::DistributionFinder (
    const Distribution & distribution,
    const std::set< categoric::VariablePtr > & containingGroup )
```

Parameters

<i>the</i>	reference distribution
<i>the</i>	variables referring to the combinations to search. This kind of set should contain the subset of variables describing the domain of distribution

Exceptions

<i>if</i>	some of the variables describing the distribution domain are not contained in containingGroup
-----------	---

9.13.3 Member Function Documentation

9.13.3.1 find()

```
std::pair<const categoric::Combination*, float> EFG::distribution::DistributionFinder::find (
    const categoric::Combination & comb ) const
```

searches for matches. For example assume having built this object with a containingGroup equal to <A,B,C,D> and the variables describing the domain of the reference distribution equal to <B,D>. When passing comb ad <0,1,2,0>, it searches for the <combination,image> pertaining to this combination combination <B,D> = <1,0>.

Parameters

<i>the</i>	combination to search, referring to the set of variables passed when building this object.
------------	--

Returns


the pair <combination,image> of the the matching combination. <nullptr,0> is returned in case such a combination was not explicitly put in the distribution.

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/DistributionFinder.h

9.14 EFG::distribution::DistributionInstantiable Class Reference

Inheritance diagram for EFG::distribution::DistributionInstantiable:



Protected Member Functions

- **DistributionInstantiable** (const std::set< categoric::VariablePtr > &group, EvaluatorPtr [evaluator](#))
- **DistributionInstantiable** (const [DistributionInstantiable](#) &o)
- [DistributionInstantiable](#) & **operator=** (const [DistributionInstantiable](#) &o)
- **DistributionInstantiable** ([DistributionInstantiable](#) &&o)
- [DistributionInstantiable](#) & **operator=** ([DistributionInstantiable](#) &&o)

Additional Inherited Members

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/DistributionInstantiable.h

9.15 EFG::distribution::DistributionIterator Class Reference

An object able to iterate the domain/images of a distribution.

```
#include <DistributionIterator.h>
```

Inheritance diagram for EFG::distribution::DistributionIterator:



Public Member Functions

- [DistributionIterator](#) (const [Distribution](#) &distribution)
- **DistributionIterator** (const [DistributionIterator](#) &)=default
- [DistributionIterator](#) & **operator=** (const [DistributionIterator](#) &)=default
- const [categoric::Combination](#) & [getCombination](#) () const
- float [getImage](#) () const
- float [getImageRaw](#) () const
- std::size_t [getNumberOfValues](#) () const

Additional Inherited Members

9.15.1 Detailed Description

An object able to iterate the domain/images of a distribution.

9.15.2 Constructor & Destructor Documentation

9.15.2.1 DistributionIterator()

```
EFG::distribution::DistributionIterator::DistributionIterator (
    const Distribution & distribution ) [explicit]
```

Parameters

<i>the</i>	distribution to iterate
------------	-------------------------

9.15.3 Member Function Documentation

9.15.3.1 getCombination()

```
const categoric::Combination& EFG::distribution::DistributionIterator::getCombination ( )  
const [inline]
```

Returns

the combination currently pointed by the iterator

9.15.3.2 getImage()

```
float EFG::distribution::DistributionIterator::getImage ( ) const [inline]
```

Returns

the image of the combination currently pointed by the iterator

9.15.3.3 getImageRaw()

```
float EFG::distribution::DistributionIterator::getImageRaw ( ) const [inline]
```

Returns

the raw image of the combination currently pointed by the iterator

9.15.3.4 getNumberOfValues()

```
std::size_t EFG::distribution::DistributionIterator::getNumberOfValues ( ) const [inline]
```

Returns


the number of combinations having a non 0 image value.

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/DistributionIterator.h

9.16 EFG::distribution::DistributionSetter Class Reference

Inheritance diagram for EFG::distribution::DistributionSetter:



Public Member Functions

- void [replaceGroup](#) (const [categoric::Group](#) &newGroup)
replace the variables describing the domain of this distribution
- void [setImageRaw](#) (const [categoric::Combination](#) &comb, const float &value)
sets the image of the passed combination. In case the combination is currently not part of the distribution, it is added with the passe raw image value.
- void [fillDomain](#) ()
creates all the non explicitly set combinations and assumed for them a 0 raw image value.
- void [setAllImagesRaw](#) (const float &value)
sets the raw images of all the combinations equal to the passed value

Additional Inherited Members

9.16.1 Member Function Documentation

9.16.1.1 setAllImagesRaw()

```
void EFG::distribution::DistributionSetter::setAllImagesRaw (
    const float & value )
```

sets the raw images of all the combinations equal to the passed value

Exceptions

<i>passing</i>	a negative number for value
----------------	-----------------------------

9.16.1.2 setImageRaw()

```
void EFG::distribution::DistributionSetter::setImageRaw (
    const categoric::Combination & comb,
    const float & value )
```

sets the image of the passed combination. In case the combination is currently not part of the distribution, it is added with the passed raw image value.

Parameters

<i>the</i>	combination whose raw image must be set
<i>the</i>	raw image value to assume

Exceptions

<i>passing</i>	a negative number for value
----------------	-----------------------------

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/DistributionSetter.h

9.17 EFG::Error Class Reference

A runtime error that can be raised when using any object in [EFG::](#)

```
#include <Error.h>
```

Inheritance diagram for EFG::Error:



Public Member Functions

- **Error** (const std::string &what)

9.17.1 Detailed Description


A runtime error that can be raised when using any object in [EFG::](#)

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/Error.h

9.18 EFG::distribution::Evaluator Class Reference

Inheritance diagram for EFG::distribution::Evaluator:



Public Member Functions

- virtual float [evaluate](#) (const float &toConvert) const =0
applies a specific function to obtain the image from a the raw image value
- virtual std::shared_ptr< [Evaluator](#) > **copy** () const =0

9.18.1 Member Function Documentation

9.18.1.1 [evaluate\(\)](#)

```
virtual float EFG::distribution::Evaluator::evaluate (
    const float & toConvert ) const [pure virtual]
```

applies a specific function to obtain the image from a the raw image value

Parameters

<i>the</i>	raw value to convert
------------	----------------------

Returns

the converted image

Implemented in [EFG::distribution::factor::EvaluatorBasic](#), and [EFG::distribution::factor::EvaluatorExponential](#).

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/Evaluator.h

9.19 EFG::distribution::factor::EvaluatorBasic Class Reference

image = exp(w * rowImage)

```
#include <EvaluatorBasic.h>
```

Inheritance diagram for EFG::distribution::factor::EvaluatorBasic:



Public Member Functions

- float [evaluate](#) (const float &toConvert) const override
applies a specific function to obtain the image from a the raw image value
- std::shared_ptr< [Evaluator](#) > **copy** () const override

9.19.1 Detailed Description

image = exp(w * rowImage)

9.19.2 Member Function Documentation

9.19.2.1 evaluate()

```
float EFG::distribution::factor::EvaluatorBasic::evaluate (
    const float & toConvert ) const [inline], [override], [virtual]
```

applies a specific function to obtain the image from a the raw image value

Parameters

<i>the</i>	raw value to convert
------------	----------------------

Returns

the converted image

Implements [EFG::distribution::Evaluator](#).

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/factor/EvaluatorBasic.h

9.20 EFG::distribution::factor::EvaluatorExponential Class Reference

An exponential function with weight w is used to obtain the image, i.e. $\text{image} = \exp(w * \text{rowImage})$

```
#include <EvaluatorExponential.h>
```

Inheritance diagram for EFG::distribution::factor::EvaluatorExponential:



Public Member Functions

- **EvaluatorExponential** (const float &weight)
- float **getWeight** () const
- void **setWeight** (float w)
- float **evaluate** (const float &toConvert) const
applies a specific function to obtain the image from a the raw image value
- std::shared_ptr< [Evaluator](#) > **copy** () const override

9.20.1 Detailed Description

An exponential function with weight w is used to obtain the image, i.e. $\text{image} = \exp(w * \text{rowImage})$

9.20.2 Member Function Documentation

9.20.2.1 evaluate()

```
float EFG::distribution::factor::EvaluatorExponential::evaluate (
    const float & toConvert ) const [inline], [virtual]
```

applies a specific function to obtain the image from a the raw image value

Parameters

<i>the</i>	raw value to convert
------------	----------------------

Returns

the converted image


Implements [EFG::distribution::Evaluator](#).

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/factor/EvaluatorExponential.h

9.21 EFG::nodes::EvidenceAware Class Reference

Inheritance diagram for EFG::nodes::EvidenceAware:



Public Member Functions

- `std::set< categoric::VariablePtr > getHiddenVariables () const`
- `std::set< categoric::VariablePtr > getObservedVariables () const`
- `const std::map< categoric::VariablePtr, const std::size_t > & getEvidences () const`

Protected Attributes


- [HiddenClusters](#) `hidden`
Clusters of hidden node. Each cluster is a group of connected hidden nodes. Nodes in different clusters are not currently connected (due to the model structure or the kind of evidences currently set)
- `std::map< categoric::VariablePtr, const std::size_t > evidences`

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/bases/EvidenceAware.h

9.22 EFG::nodes::EvidencesChanger Class Reference

Inheritance diagram for EFG::nodes::EvidencesChanger:



Public Member Functions

- void `addEvidence` (const std::string &name, std::size_t value)
add a new evidence to the model
- void `resetEvidences` (const std::map< std::string, std::size_t > &evidences)
reset the evidences, deleting the previous ones.

Additional Inherited Members

9.22.1 Member Function Documentation

9.22.1.1 `addEvidence()`

```
void EFG::nodes::EvidencesChanger::addEvidence (
    const std::string & name,
    std::size_t value )
```

add a new evidence to the model

Parameters

<i>the</i>	name of the variable observed
<i>the</i>	value of the evidence

Exceptions

<i>when</i>	the passed variable name is not found
<i>when</i>	the passed variable name corresponds to an already set evidence
<i>when</i>	the passed evidence value is inconsistent

9.22.1.2 `resetEvidences()`

```
void EFG::nodes::EvidencesChanger::resetEvidences (
    const std::map< std::string, std::size_t > & evidences )
```

reset the evidences, deleting the previous ones.

Parameters

<i>the</i>	new evidences to assume: <variable name, evidence value>
------------	--

Exceptions


<i>when</i>	one of the passed variable name is not found
<i>when</i>	one of the passed evidence value is inconsistent

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/EvidenceChanger.h

9.23 EFG::nodes::EvidencesSetter Class Reference

Inheritance diagram for EFG::nodes::EvidencesSetter:



Public Member Functions

- void [setEvidences](#) (const std::vector< std::size_t > &observations)
reset evidence values. The group of observed variables is left unchanged, but the evidence values are updated.

Additional Inherited Members

9.23.1 Member Function Documentation

9.23.1.1 setEvidences()

```
void EFG::nodes::EvidencesSetter::setEvidences (
    const std::vector< std::size_t > & observations )
```

reset evidence values. The group of observed variables is left unchanged, but the evidence values are updated.

Exceptions


<i>when</i>	the number of evidences is inconsistent
<i>when</i>	one of the evidence value is inconsistent

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/EvidenceSetter.h

9.24 EFG::io::Exporter Class Reference

Inheritance diagram for EFG::io::Exporter:



Protected Member Functions

- virtual void **exportComponents** (const std::string &filePath, const std::string &modelName, const std::tuple< const [nodes::EvidenceAware](#) *, const [nodes::StructureAware](#) *, const [nodes::StructureTunableAware](#) * > &components)=0

Static Protected Member Functions


- template<typename Model >
static std::tuple< const [nodes::EvidenceAware](#) *, const [nodes::StructureAware](#) *, const [nodes::StructureTunableAware](#) * > **getComponents** (const Model &model)

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/io/Exporter.h

9.25 EFG::io::xml::Exporter Class Reference

Inheritance diagram for EFG::io::xml::Exporter:



Static Public Member Functions

- template<typename Model >
static void **exportToXml** (const Model &model, const std::string &filePath, const std::string &modelName="")
exports the model (variables and factors) into an xml file

Additional Inherited Members

9.25.1 Member Function Documentation

9.25.1.1 exportToXml()

```
template<typename Model >
static void EFG::io::xml::Exporter::exportToXml (
    const Model & model,
    const std::string & filePath,
    const std::string & modelName = "" ) [inline], [static]
```

exports the model (variables and factors) into an xml file

Parameters


<i>the</i>	model to export
<i>the</i>	folder that will store the xml
<i>the</i>	xml file name

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/io/xml/Exporter.h

9.26 EFG::io::json::Exporter Class Reference

Inheritance diagram for EFG::io::json::Exporter:



Static Public Member Functions

- template<typename Model >
static void [exportToJson](#) (const Model &model, const std::string &filePath, const std::string &modelName="")
exports the model (variables and factors) into a json file

Additional Inherited Members

9.26.1 Member Function Documentation

9.26.1.1 exportToJson()

```
template<typename Model >
static void EFG::io::json::Exporter::exportToJson (
    const Model & model,
    const std::string & filePath,
    const std::string & modelName = "" ) [inline], [static]
```

exports the model (variables and factors) into a json file

Parameters


<i>the</i>	model to export
<i>the</i>	folder that will store the json
<i>the</i>	json file name

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/io/json/Exporter.h

9.27 EFG::distribution::factor::modif::Factor Class Reference

Inheritance diagram for EFG::distribution::factor::modif::Factor:



Public Member Functions

- template<typename ... Args>
Factor (Args &&... args)
- **Factor** (const std::set< categoric::VariablePtr > &group)
- **Factor** (const [Factor](#) &o)
- **Factor** ([Factor](#) &&o)
- [Factor](#) & **operator=** (const [Factor](#) &o)
- [Factor](#) & **operator=** ([Factor](#) &&o)
- void **clear** ()

sets all raw images equal to 0 and deallocate all combinations

Additional Inherited Members

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/factor/modifiable/Factor.h

9.28 EFG::distribution::factor::cnst::Factor Class Reference

A factor using the [EvaluatorBasic](#) object to convert the raw images into images.

```
#include <Factor.h>
```

Inheritance diagram for EFG::distribution::factor::cnst::Factor:



Public Member Functions

- [Factor](#) (const std::set< categoric::VariablePtr > &group, bool corrOrAnti)
Builds a simple correlating or anticorrelating factor.
- [Factor](#) (const [Factor](#) &o)
- [Factor](#) ([Factor](#) &&o)
- [Factor](#) (const [Distribution](#) &o)
Copies all the images (not raw) of the passed distribution to build a generic factor.
- template<typename ... Distributions>
[Factor](#) (const [Distribution](#) *first, const [Distribution](#) *second, Distributions ... distr)
Merges all the passed distribution into a single [Factor](#). The domain of the [Factor](#) is obtained merging the domains of the distributions, while the image are obtained multiplying the images of the passed distributions.
- [Factor](#) (const std::set< const [Distribution](#) * > &distr)
Merges all the passed distribution into a single [Factor](#). The domain of the [Factor](#) is obtained merging the domains of the distributions, while the image are obtained multiplying the images of the passed distributions.
- [Factor](#) (const [Distribution](#) &toMarginalize, const categoric::Combination &comb, const std::set< categoric::VariablePtr > &evidences)
Builds the factor by taking only the combinations of the passed distribution matching with the passed combination. Suppose toMarginalize has a domain of variables equal to <A,B,C,D> and the passed comb is <0,1> and evidences is <B,C>. The built factor will have a domain of variables equal to <A,D>, with the combinations, raw images of toMarginalize (taking only the part referring to A,D) that have B=0 and C=1.
- [Factor](#) (const std::set< categoric::VariablePtr > &group, const std::string &fileName)
Build the [Factor](#) by importing the information from the file.

Protected Member Functions

- **Factor** (const std::set< categoric::VariablePtr > &group)

Static Protected Member Functions

- template<typename ... Distributions>
static std::set< const [Distribution](#) * > **pack** (const [Distribution](#) *first, const [Distribution](#) *second, Distributions ... distr)
- template<typename ... Distributions>
static void **pack** (std::set< const [Distribution](#) * > &packed, const [Distribution](#) *first, Distributions ... distr)
- static void **pack** (std::set< const [Distribution](#) * > &packed, const [Distribution](#) *first)

Additional Inherited Members

9.28.1 Detailed Description

A factor using the [EvaluatorBasic](#) object to convert the raw images into images.

9.28.2 Constructor & Destructor Documentation

9.28.2.1 Factor() [1/3]

```
EFG::distribution::factor::cnst::Factor::Factor (
    const std::set< categoric::VariablePtr > & group,
    bool corrOrAnti )
```

Builds a simple correlating or anticorrelating factor.

Parameters

<i>the</i>	variables representing the domain of this distribution
<i>when</i>	passing: <ul style="list-style-type: none"> • true, a simple correlating potential is built. Such a distribution has the images equal to 1 only for those combinations for which the variables have all the same values (<1,1,1>, <2,2,2>, <0,0>, etc...) and 0 for all the others • false, a simple anticorrelating potential is built. Such a distribution has the images equal to 0 for those combinations for which the variables have all the same values (<1,1,1>, <2,2,2>, <0,0>, etc...) and 1 for all the others

Exceptions

<i>when</i>	the passed group is made by less than 2 elements
<i>when</i>	not all the elements in the passed group have the same sizes

9.28.2.2 Factor() [2/3]

```
EFG::distribution::factor::cnst::Factor::Factor (
    const std::set< const Distribution * > & distr ) [explicit]
```

Merges all the passed distribution into a single [Factor](#). The domain of the [Factor](#) is obtained merging the domains of the distributions, while the image are obtained multiplying the images of the passed distributions.

Exceptions

<i>when</i>	the set contains less than 2 elements
<i>when</i>	the some of the distr groups contain common variable names, but with different sizes

9.28.2.3 Factor() [3/3]

```
EFG::distribution::factor::cnst::Factor::Factor (
    const std::set< categoric::VariablePtr > & group,
    const std::string & fileName )
```

Build the [Factor](#) by importing the information from the file.

Parameters

<i>the</i>	group of variables describing the domain
<i>the</i>	location of a file storing the combinations and the raw images in a matrix of numbers: each row has the combination values and at the end the raw image

Exceptions


<i>when</i>	a row in the file contains an inconsistent number of elements
-------------	---

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/factor/cnst/Factor.h

9.29 EFG::distribution::factor::modif::FactorExponential Class Reference

Inheritance diagram for EFG::distribution::factor::modif::FactorExponential:



Public Member Functions

- **FactorExponential** (const [cnst::Factor](#) &factor, float weight)
- **FactorExponential** (const [cnst::FactorExponential](#) &o)
- **FactorExponential** (const [FactorExponential](#) &o)
- [FactorExponential](#) & **operator=** (const [FactorExponential](#) &o)
- void [setWeight](#) (float w)
sets the weight used by teh exponential function converting the raw images

Additional Inherited Members

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/factor/modifiable/FactorExponential.h

9.30 EFG::distribution::factor::cnst::FactorExponential Class Reference

A factor using the [EvaluatorExponential](#) object to convert the raw images into images.

```
#include <FactorExponential.h>
```

Inheritance diagram for EFG::distribution::factor::cnst::FactorExponential:



Public Member Functions

- [FactorExponential](#) (const [Factor](#) &factor, float weight)
- **FactorExponential** (const [FactorExponential](#) &o)
- float [getWeight](#) () const

Additional Inherited Members

9.30.1 Detailed Description

A factor using the [EvaluatorExponential](#) object to convert the raw images into images.

9.30.2 Constructor & Destructor Documentation

9.30.2.1 FactorExponential()

```
EFG::distribution::factor::cnst::FactorExponential::FactorExponential (
    const Factor & factor,
    float weight )
```

Parameters

<i>the</i>	factor whose raw images are copied
<i>the</i>	weight to pass to the EvaluatorExponential

9.30.3 Member Function Documentation

9.30.3.1 getWeight()

```
float EFG::distribution::factor::cnst::FactorExponential::getWeight ( ) const
```

Returns

the weight of the [EvaluatorExponential](#)

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/factor/cnst/FactorExponential.h

9.31 EFG::iterator::Forward Class Reference

A [Forward](#) iterable object.

```
#include <Forward.h>
```

Inheritance diagram for EFG::iterator::Forward:



Public Member Functions

- virtual void **operator++** ()=0
- virtual bool **operator==** (std::nullptr_t) const =0
- bool **operator!=** (std::nullptr_t) const

9.31.1 Detailed Description

A [Forward](#) iterable object.

9.31.2 Member Function Documentation

9.31.2.1 operator==()

```
virtual bool EFG::iterator::Forward::operator== (
    std::nullptr_t ) const [pure virtual]
```

Returns

true when the iterator is at the end, i.e. can't be incremented further.


Implemented in [EFG::categoric::Range](#), [EFG::iterator::StlBidirectional< IteratorStl >](#), and [EFG::iterator::StlBidirectional< std::map<](#)

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/iterator/Forward.h

9.32 EFG::nodes::GibbsSampler Class Reference

Inheritance diagram for EFG::nodes::GibbsSampler:



Public Member Functions

- std::vector< [categoric::Combination](#) > [getHiddenSetSamples](#) (std::size_t numberOfSamples, std::size_t deltaIteration=100) const
Use Gibbs sampling to draw samples for the hidden variables, conditioned to the current evidences.

Additional Inherited Members

9.32.1 Member Function Documentation

9.32.1.1 getHiddenSetSamples()

```
std::vector<catgoric::Combination> EFG::nodes::GibbsSampler::getHiddenSetSamples (
    std::size_t numberOfSamples,
    std::size_t deltaIteration = 100 ) const
```

Use Gibbs sampling to draw samples for the hidden variables, conditioned to the current evidences.

Parameters


<i>number</i>	of samples to draw
<i>number</i>	of iterations used to evolve the model between the drawing of one sample and another

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/GibbsSampler.h

9.33 EFG::train::GradientDescend< Extractor > Class Template Reference

Inheritance diagram for EFG::train::GradientDescend< Extractor >:



Public Member Functions

- void `train` (`Trainable` &model, `TrainSetPtr` trainSet) override
trains the passed model, using the passed training set
- float `getAdvancement` () const
- void `setAdvancement` (float adv)

Additional Inherited Members

9.33.1 Member Function Documentation

9.35 EFG::categoric::Group Class Reference

An ensemble of categoric variables. Each variable in the ensemble should have its own unique name.

```
#include <Group.h>
```

Public Member Functions

- [Group](#) (const std::set< VariablePtr > &group)
- [Group](#) (VariablePtr var)
- [Group](#) (VariablePtr varA, VariablePtr varB)
- template<typename ... Vars>
[Group](#) (VariablePtr varA, VariablePtr varB, Vars ... vars)
- **Group** (const [Group](#) &)=default
- [Group](#) & [operator=](#) (const [Group](#) &o)
- bool [operator==](#) (const [Group](#) &o) const
- void [add](#) (VariablePtr var)
- void [replace](#) (const std::set< VariablePtr > &newGroup)
replaces the group of variables.
- template<typename ... Vars>
void [replace](#) (VariablePtr varA, VariablePtr varB, Vars ... vars)
replaces the group of variables.
- std::size_t [size](#) () const
- const std::set< VariablePtr > & [getVariables](#) () const

Protected Member Functions

- template<typename ... Vars>
void [add](#) (VariablePtr var, Vars ... vars)

Protected Attributes

- std::set< VariablePtr > **group**

9.35.1 Detailed Description

An ensemble of categoric variables. Each variable in the ensemble should have its own unique name.

9.35.2 Constructor & Destructor Documentation

9.35.2.1 Group() [1/4]

```
EFG::categoric::Group::Group (  
    const std::set< VariablePtr > & group ) [explicit]
```

Parameters

<i>the</i>	initial variables of the group
------------	--------------------------------

9.35.2.2 Group() [2/4]

```
EFG::categoric::Group::Group (
    VariablePtr var ) [explicit]
```

Parameters

<i>the</i>	initial variable to put in the group
------------	--------------------------------------

9.35.2.3 Group() [3/4]

```
EFG::categoric::Group::Group (
    VariablePtr varA,
    VariablePtr varB )
```

Parameters

<i>the</i>	first initial variable to put in the group
<i>the</i>	second initial variable to put in the group

Exceptions

<i>when</i>	the 2 variables have the same names
-------------	-------------------------------------

9.35.2.4 Group() [4/4]

```
template<typename ... Vars>
EFG::categoric::Group::Group (
    VariablePtr varA,
    VariablePtr varB,
    Vars ... vars ) [inline]
```

Parameters

<i>the</i>	first initial variable to put in the group
<i>the</i>	second initial variable to put in the group
<i>all</i>	the other initial variables

9.35.3 Member Function Documentation

9.35.3.1 add()

```
void EFG::categoric::Group::add (
    VariablePtr var )
```

Parameters

<i>the</i>	variable to add in the group
------------	------------------------------

Exceptions

<i>in</i>	case a variable with the same name is already part of the group
-----------	---

9.35.3.2 operator=()

```
Group& EFG::categoric::Group::operator= (
    const Group & o )
```

Exceptions

<i>In</i>	case of size mismatch with the previous variables set: the sizes of the 2 groups should be the same and the elements in the same positions must have the same domain size.
-----------	--

9.35.3.3 replace() [1/2]

```
void EFG::categoric::Group::replace (
    const std::set< VariablePtr > & newGroup ) [inline]
```

replaces the group of variables.

Exceptions

<i>In</i>	case of size mismatch with the previous variables set: the sizes of the 2 groups should be the same and the elements in the same positions must have the same domain size
-----------	---

9.35.3.4 replace() [2/2]

```
template<typename ... Vars>
void EFG::categorical::Group::replace (
    VariablePtr varA,
    VariablePtr varB,
    Vars ... vars ) [inline]
```

replaces the group of variables.

Exceptions

<i>In</i>	case of size mismatch with the previous variables set: the sizes of the 2 groups should be the same and the elements in the same positions must have the same domain size
-----------	---

9.35.3.5 size()

```
std::size_t EFG::categorical::Group::size ( ) const
```

Returns

the size of the joint domain of the group. For example the group <A,B,C> with sizes <2,4,3> will have a joint domain of size $2 \times 4 \times 3 = 24$

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/categorical/Group.h

9.36 EFG::nodes::HiddenClusters Struct Reference

Public Member Functions

- **HiddenClusters** (const std::set< [Node](#) * > &toSplit)
- void **add** (const std::list< std::set< [Node](#) * > > &toAdd)
- std::list< std::set< [Node](#) * > >::iterator **find** ([Node](#) &node)

Public Attributes


- std::list< std::set< [Node](#) * > > **clusters**

The documentation for this struct was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/bases/EvidenceAware.h

9.37 EFG::io::xml::Importer Class Reference

Inheritance diagram for EFG::io::xml::Importer:



Static Public Member Functions

- `template<typename Model >`
`static std::map< std::string, std::size_t > importFromXml (Model &model, const std::string &filePath, const std::string &fileName)`
imports the structure (variables and factors) described in an xml file and add it to the passed model

Additional Inherited Members

9.37.1 Member Function Documentation

9.37.1.1 importFromXml()

```

template<typename Model >
static std::map<std::string, std::size_t> EFG::io::xml::Importer::importFromXml (
    Model & model,
    const std::string & filePath,
    const std::string & fileName ) [inline], [static]
  
```

imports the structure (variables and factors) described in an xml file and add it to the passed model

Parameters

<i>the</i>	model receiving the parsed data
<i>the</i>	folder storing the xml
<i>the</i>	xml file name

Returns


the set of evidences read from the file. Attention! this quantities are returned to allow the user to set such evidence, since this is not automatically done when importing

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/io/xml/Importer.h

9.38 EFG::io::Importer Class Reference

Inheritance diagram for EFG::io::Importer:



Protected Member Functions

- virtual std::map< std::string, std::size_t > **importComponents** (const std::string &filePath, const std::string &fileName, const std::pair< [nodes::InsertCapable](#) *, [nodes::InsertTunableCapable](#) * > &components)=0

Static Protected Member Functions

- template<typename Model >
static std::pair< [nodes::InsertCapable](#) *, [nodes::InsertTunableCapable](#) * > **getComponents** (Model &model)

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/io/Importer.h

9.39 EFG::distribution::factor::cnst::IndicatorFactor Class Reference

An indicator distribution having only one combination explicitly stated, whose image is equal to 1.

```
#include <Indicator.h>
```

Inheritance diagram for EFG::distribution::factor::cnst::IndicatorFactor:



Public Member Functions

- [IndicatorFactor](#) (categoric::VariablePtr var, std::size_t evidence)

Additional Inherited Members

9.39.1 Detailed Description

An indicator distribution having only one combination explicitly stated, whose image is equal to 1.

9.39.2 Constructor & Destructor Documentation

9.39.2.1 IndicatorFactor()

```
EFG::distribution::factor::cnst::IndicatorFactor::IndicatorFactor (
    categoric::VariablePtr var,
    std::size_t evidence )
```

Parameters

<i>the</i>	variable this indicator function must refer to
<i>the</i>	only combination to consider for the indicator distribution

Exceptions


<i>when</i>	evidence is inconsistent for the passed variable
-------------	--

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/distribution/factor/const/Indicator.h

9.40 EFG::nodes::InsertCapable Class Reference

Inheritance diagram for EFG::nodes::InsertCapable:



Public Member Functions

- void **insert** (std::shared_ptr< [distribution::factor::cnst::Factor](#) > factor)
insert the passed factor.
- void **insertCopy** (const [distribution::Distribution](#) &factor)
insert a copy of the passed factor.
- void **insert** (std::shared_ptr< [distribution::factor::cnst::FactorExponential](#) > factor)
insert the passed exponential factor.
- void **insertCopy** (const [distribution::factor::cnst::FactorExponential](#) &factor)
insert a copy of the passed exponential factor.
- template<typename Model >
void **absorbModel** (const Model &model, const bool &useCopyInsertion=false)
insert all the factors contained in the passed model

Protected Member Functions

- std::set< [categoric::VariablePtr](#) > **convertUsingLocals** (const std::set< [categoric::VariablePtr](#) > &to↔
Convert)
- void **absorb** (const [StructureAware](#) &toAbsorb, const bool &useCopyInsertion)
- virtual void **absorb** (const [StructureTunableAware](#) &toAbsorb, const bool &useCopyInsertion)

Additional Inherited Members

9.40.1 Member Function Documentation

9.40.1.1 absorbModel()

```
template<typename Model >
void EFG::nodes::InsertCapable::absorbModel (
    const Model & model,
    const bool & useCopyInsertion = false ) [inline]
```

insert all the factors contained in the passed model

Parameters

<i>the</i>	model to absorb
<i>when</i>	passing true the factors from the passed model are copied, otherwise the shared pointers are copied

Exceptions

<i>if</i>	the passed model does not expose a StructureAware interface
-----------	---

9.40.1.2 insert() [1/2]

```
void EFG::nodes::InsertCapable::insert (
    std::shared_ptr< distribution::factor::cnst::Factor > factor )
```

insert the passed factor.

Exceptions

<i>if</i>	the factor is neither unary or binary
<i>in</i>	case the factor is binary and connects some already connected variables
<i>when</i>	there is already a variable in the model with the same name of a one into the factor domain, but not represented by the same object

9.40.1.3 insert() [2/2]

```
void EFG::nodes::InsertCapable::insert (
    std::shared_ptr< distribution::factor::cnst::FactorExponential > factor )
```

insert the passed exponential factor.

Exceptions

<i>if</i>	the factor is neither unary or binary
<i>in</i>	case the factor is binary and connects some already connected variables
<i>when</i>	there is already a variable in the model with the same name of a one into the factor domain, but not represented by the same object

9.40.1.4 insertCopy() [1/2]

```
void EFG::nodes::InsertCapable::insertCopy (
    const distribution::Distribution & factor )
```

insert a copy of the passed factor.

Exceptions

<i>if</i>	the factor is neither unary or binary
<i>in</i>	case the factor is binary and connects some already connected variables
<i>when</i>	there is already a variable in the model with the same name of a one into the factor domain, but with a different size

9.40.1.5 insertCopy() [2/2]

```
void EFG::nodes::InsertCapable::insertCopy (
    const distribution::factor::cnst::FactorExponential & factor )
```

insert a copy of the passed exponential factor.

Exceptions


<i>if</i>	the factor is neither unary or binary
<i>in</i>	case the factor is binary and connects some already connected variables
<i>when</i>	there is already a variable in the model with the same name of a one into the factor domain, but with a different size

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/InsertCapable.h

9.41 EFG::nodes::InsertTunableCapable Class Reference

Inheritance diagram for EFG::nodes::InsertTunableCapable:



Public Member Functions

- void [insertTunableCopy](#) (const [distribution::factor::modif::FactorExponential](#) &factor)
insert a copy of the passed tunable factor. A new tunable cluster is created containing only the passed factor.
- void [insertTunableCopy](#) (const [distribution::factor::modif::FactorExponential](#) &factor, const std::set< categoric::VariablePtr > &potentialSharingWeight)
insert a copy of the passed tunable factor, sharing the weight with an already inserted one.

Protected Member Functions

- virtual void **insertTunable** (std::shared_ptr< [distribution::factor::modif::FactorExponential](#) > toInsert)
- virtual void **insertTunable** (std::shared_ptr< [distribution::factor::modif::FactorExponential](#) > toInsert, const std::set< categoric::VariablePtr > &potentialSharingWeight)
- void **absorb** (const [StructureTunableAware](#) &toAbsorb, const bool &useCopyInsertion) override

Additional Inherited Members

9.41.1 Member Function Documentation

9.41.1.1 insertTunableCopy() [1/2]

```
void EFG::nodes::InsertTunableCapable::insertTunableCopy (
    const distribution::factor::modif::FactorExponential & factor )
```

insert a copy of the passed tunable factor. A new tunable cluster is created containing only the passed factor.

Exceptions

<i>if</i>	the factor is neither unary or binary
<i>in</i>	case the factor is binary and connects some already connected variables
<i>when</i>	there is already a variable in the model with the same name of a one into the factor domain, but not represented by the same object

9.41.1.2 insertTunableCopy() [2/2]

```
void EFG::nodes::InsertTunableCapable::insertTunableCopy (
    const distribution::factor::modif::FactorExponential & factor,
    const std::set< categoric::VariablePtr > & potentialSharingWeight )
```

insert a copy of the passed tunable factor, sharing the weight with an already inserted one.

Parameters

<i>the</i>	factor to insert
<i>the</i>	set of variables identifying the potential whose weight is to share

Exceptions

<i>when</i>	the potential whose weight must be shared is not found
<i>if</i>	the factor is neither unary or binary
<i>in</i>	case the factor is binary and connects some already connected variables
<i>when</i>	there is already a variable in the model with the same name of a one into the factor domain, but with a different size

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/InsertTunableCapable.h

9.42 EFG::nodes::Node Struct Reference**Public Member Functions**

- **Node** (categoric::VariablePtr var)

Public Attributes


- `categoric::VariablePtr` **variable**
- `std::list< distribution::DistributionPtr >` **unaryFactors**
- `std::map< Node *, Connection >` **activeConnections**
- `std::map< Node *, Connection >` **disabledConnections**

The documentation for this struct was generated from the following file:

- `C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/Node.h`

9.43 EFG::nodes::NodesAware Class Reference

Inheritance diagram for EFG::nodes::NodesAware:



Public Member Functions

- `std::set< categoric::VariablePtr >` **getVariables** () const
- `categoric::VariablePtr` **findVariable** (const std::string &name) const

Protected Attributes

- `std::map< categoric::VariablePtr, Node >` **nodes**
The set of variables part of the model, with the connectivity information.

9.43.1 Member Function Documentation

9.43.1.1 getVariables()

```
std::set<categoric::VariablePtr> EFG::nodes::NodesAware::getVariables ( ) const
```

Returns

all the variables (hidden or observed) in the model

The documentation for this class was generated from the following file:

- `C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/bases/NodesAware.h`

9.44 EFG::nodes::PropagationResult Struct Reference

Public Attributes


- PropagationKind **kindDone**
- bool **wasTerminated**

The documentation for this struct was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/bases/BeliefAware.h

9.45 EFG::nodes::QueryHandler Class Reference

Inheritance diagram for EFG::nodes::QueryHandler:



Public Member Functions

- `std::vector< float > getMarginalDistribution (const std::string &var)`
- `distribution::factor::cnst::Factor getJointMarginalDistribution (const std::set< std::string > &subgroup)`
- `std::size_t getMAP (const std::string &var)`
- `std::vector< size_t > getHiddenSetMAP ()`

Additional Inherited Members

9.45.1 Member Function Documentation

9.45.1.1 getHiddenSetMAP()

```
std::vector<size_t> EFG::nodes::QueryHandler::getHiddenSetMAP ( )
```

Returns

the Maximum a Posteriori estimation of the hidden variables, conditioned to the last set evidences. values are ordered in the same way the variables in the hidden set can be ordered (alfabetic order)

9.45.1.2 getJointMarginalDistribution()

```
distribution::factor::cnst::Factor EFG::nodes::QueryHandler::getJointMarginalDistribution (
    const std::set< std::string > & subgroup )
```

Returns

a factor representing the joint distribution of the subgraph described by the passed variables.

Exceptions

<i>when</i>	some of the passed variable names is not found
-------------	--

9.45.1.3 getMAP()

```
std::size_t EFG::nodes::QueryHandler::getMAP (
    const std::string & var )
```

Returns

the Maximum a Posteriori estimation of a specific variable in the model, conditioned to the last set evidences.

Exceptions

<i>when</i>	the passed variable name is not found
-------------	---------------------------------------

9.45.1.4 getMarginalDistribution()

```
std::vector<float> EFG::nodes::QueryHandler::getMarginalDistribution (
    const std::string & var )
```

Returns

the marginal probability of the passed variable, i.e. $P(\text{var}|\text{model}, \text{observations})$, conditioned to the last set evidences.

Exceptions

<i>when</i>	the passed variable name is not found
-------------	---------------------------------------

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/QueryHandler.h

9.46 EFG::model::RandomField Class Reference

Inheritance diagram for EFG::model::RandomField:



Public Member Functions

- `template<typename Model >`
RandomField (const Model &o)
- **RandomField** (const [RandomField](#) &o)
- `void insertTunable (std::shared_ptr< distribution::factor::modif::FactorExponential > toInsert)` override
insert the passed tunable factor.
- `void insertTunable (std::shared_ptr< distribution::factor::modif::FactorExponential > toInsert, const std::set< categoric::VariablePtr > &potentialSharingWeight)` override
insert the passed tunable factor, sharing the weight with an already inserted one.
- `std::vector< float > getGradient (train::TrainSetPtr trainSet)` override

Additional Inherited Members

9.46.1 Member Function Documentation

9.46.1.1 getGradient()

```
std::vector<float> EFG::model::RandomField::getGradient (
    train::TrainSetPtr trainSet ) [override], [virtual]
```

Returns

the gradient of the weights of the tunable clusters w.r.t. the passed training set

Exceptions

<i>when</i>	the trainSet is inconsistent because have a wrong combinations size
-------------	---

Implements [EFG::train::Trainable](#).

9.46.1.2 insertTunable()

```
void EFG::model::RandomField::insertTunable (
    std::shared_ptr< distribution::factor::modif::FactorExponential > toInsert,
    const std::set< categoric::VariablePtr > & potentialSharingWeight ) [override],
[virtual]
```

insert the passed tunable factor, sharing the weight with an already inserted one.

Parameters

<i>the</i>	factor to insert
<i>the</i>	set of variables identifying the potential whose weight is to share

Reimplemented from [EFG::nodes::InsertTunableCapable](#).

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/model/RandomField.h

9.47 EFG::categoric::Range Class Reference

This object allows you to iterate all the elements in the joint domain of a group of variables, without precomputing all the elements in such domain. For example when having a domain made by variables = { A (size = 2), B (size = 3), C (size = 2) }, the elements in the joint domain that will be iterated are: <0,0,0> <0,0,1> <0,1,0> <0,1,1> <0,2,0> <0,2,1> <1,0,0> <1,0,1> <1,1,0> <1,1,1> <1,2,0> <1,2,1> After construction, the [Range](#) object starts to point to the first element in the joint domain <0,0,...>. Then, when incrementing the object, the following element is pointed. When calling [get\(\)](#) the current pointed element can be accessed.

```
#include <Range.h>
```

Inheritance diagram for EFG::categoric::Range:



Public Member Functions

- [Range](#) (const std::set< VariablePtr > &group)
- [Range](#) (const [Range](#) &)=default
- [Range](#) & [operator=](#) (const [Range](#) &)=default
- const [Combination](#) & [get](#) () const
- void [operator++](#) () final

Make the object to point to the next element in the joint domain.

- bool [operator==](#) (std::nullptr_t) const final
- void [reset](#) ()

Make the object to point to the first element of the joint domain <0,0,...>, i.e. reset the status as it is after construction.

9.47.1 Detailed Description

This object allows you to iterate all the elements in the joint domain of a group of variables, without precomputing all the elements in such domain. For example when having a domain made by variables = { A (size = 2), B (size = 3), C (size = 2) }, the elements in the joint domain that will be iterated are: <0,0,0> <0,0,1> <0,1,0> <0,1,1> <0,2,0> <0,2,1> <1,0,0> <1,0,1> <1,1,0> <1,1,1> <1,2,0> <1,2,1> After construction, the [Range](#) object starts to point to the first element in the joint domain <0,0,...>. Then, when incrementing the object, the following element is pointed. When calling [get\(\)](#) the current pointed element can be accessed.

9.47.2 Constructor & Destructor Documentation

9.47.2.1 Range()

```
EFG::categoric::Range::Range (
    const std::set< VariablePtr > & group ) [explicit]
```

Parameters

<i>the</i>	group of variables whose joint domain must be iterated
------------	--

9.47.3 Member Function Documentation

9.47.3.1 get()

```
const Combination& EFG::categoric::Range::get ( ) const [inline]
```

Returns

the current pointed combination

9.47.3.2 operator++()

```
void EFG::categoric::Range::operator++ ( ) [final], [virtual]
```

Make the object to point to the next element in the joint domain.

Exceptions

<i>if</i>	the current pointed element is the last one.
-----------	--

Implements [EFG::iterator::Forward](#).

9.47.3.3 operator==()

```
bool EFG::categoric::Range::operator== (
    std::nullptr_t ) const [inline], [final], [virtual]
```

Returns

true when the iterator is at the end, i.e. can't be incremented further.

Implements [EFG::iterator::Forward](#).

The documentation for this class was generated from the following file:


- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/categoric/Range.h

9.48 EFG::iterator::StlBidirectional< IteratorStl > Class Template Reference

A bidirectional iterator built on top of an std iterator type.

```
#include <StlBidirectional.h>
```

Inheritance diagram for EFG::iterator::StlBidirectional< IteratorStl >:



Public Member Functions

- **StlBidirectional** (const IteratorStl &begin, const IteratorStl &end)
- **StlBidirectional** (const [StlBidirectional](#) &)=default
- [StlBidirectional](#) & **operator=** (const [StlBidirectional](#) &)=default
- void **operator++** () final
- void **operator--** () final
- bool [operator==](#) (std::nullptr_t) const final

Protected Attributes

- IteratorStl **cursor**
- const IteratorStl **end**

9.48.1 Detailed Description

```
template<typename IteratorStl>
class EFG::iterator::StlBidirectional< IteratorStl >
```

A bidirectional iterator built on top of an std iterator type.

9.48.2 Member Function Documentation

9.48.2.1 operator==()

```
template<typename IteratorStl >
bool EFG::iterator::StlBidirectional< IteratorStl >::operator== (
    std::nullptr_t ) const [inline], [final], [virtual]
```

Returns

true when the iterator is at the end, i.e. can't be incremented further.


Implements [EFG::iterator::Forward](#).

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/iterator/StlBidirectional.h

9.49 EFG::train::StochasticExtractor Class Reference

Inheritance diagram for EFG::train::StochasticExtractor:



Public Member Functions

- void **setPercentage** (const float &percentage)

Protected Member Functions


- TrainSetPtr **getTrainSet** () override

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/trainers/TrainSetExtractor.h

9.50 EFG::nodes::StructureAware Class Reference

Inheritance diagram for EFG::nodes::StructureAware:



Public Member Functions

- `const std::set< std::shared_ptr< distribution::factor::cnst::Factor > > & getFactors () const`
- `const std::set< std::shared_ptr< distribution::factor::cnst::FactorExponential > > & getFactorsExp () const`

Protected Attributes

- `std::set< std::shared_ptr< distribution::factor::cnst::Factor > > factors`
- `std::set< std::shared_ptr< distribution::factor::cnst::FactorExponential > > factorsExp`

9.50.1 Member Data Documentation

9.50.1.1 factors

```
std::set<std::shared_ptr<distribution::factor::cnst::Factor> > EFG::nodes::StructureAware↔  
::factors [protected]
```

Returns

the constant factors stored in the model

9.50.1.2 factorsExp

```
std::set<std::shared_ptr<distribution::factor::cnst::FactorExponential> > EFG::nodes::↔  
StructureAware::factorsExp [protected]
```

Returns


the constant exponential factors stored in the model

The documentation for this class was generated from the following file:

- `C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/bases/StructureAware.h`

9.51 EFG::nodes::StructureTunableAware Class Reference

Inheritance diagram for EFG::nodes::StructureTunableAware:



Public Member Functions

- `std::vector< std::vector< std::shared_ptr< distribution::factor::modif::FactorExponential > > > getFactorsTunable () const`
- `std::vector< float > getWeights () const`

Protected Attributes

- `std::size_t numberOfClusters = 0`
- `std::map< std::shared_ptr< distribution::factor::modif::FactorExponential >, std::size_t > factorsTunable`

9.51.1 Member Function Documentation

9.51.1.1 getFactorsTunable()

```
std::vector<std::vector<std::shared_ptr<distribution::factor::modif::FactorExponential> > >
EFG::nodes::StructureTunableAware::getFactorsTunable ( ) const
```

Returns

the clusters of tunable exponential factors. Each element in the returned vector, is a cluster of exponential factors sharing the same weight value.

9.51.1.2 getWeights()

```
std::vector<float> EFG::nodes::StructureTunableAware::getWeights ( ) const
```

Returns

the weights of the tunable clusters. For each cluster only 1 value is returned, since it is shared among the elements in the same cluster.

9.51.2 Member Data Documentation

9.51.2.1 factorsTunable

```
std::map<std::shared_ptr<distribution::factor::modif::FactorExponential>, std::size_t> EFG↔
::nodes::StructureTunableAware::factorsTunable [protected]
```

Returns

collection of tunable exponential factors. Each element is <exp factor, cluster id>

The documentation for this class was generated from the following file:


- `C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/nodes/bases/StructureTunableAware.h`

9.52 EFG::train::Trainable Class Reference

An object storing tunable factors, whose weights can be tuned with training.

```
#include <Trainable.h>
```

Inheritance diagram for EFG::train::Trainable:



Public Member Functions

- void [setWeights](#) (const std::vector< float > &w)
- void [setOnes](#) ()
- virtual std::vector< float > [getGradient](#) (TrainSetPtr trainSet)=0

Protected Member Functions

- virtual TrainHandlerPtr **makeHandler** (std::shared_ptr< [distribution::factor::modif::FactorExponential](#) > factor)
- void **insertHandler** (std::shared_ptr< [distribution::factor::modif::FactorExponential](#) > factor)
- void **setTrainSet** (TrainSetPtr newSet)
- TrainSetPtr **getLastTrainSet** () const

Protected Attributes

- std::list< TrainHandlerPtr > **handlers**

9.52.1 Detailed Description

An object storing tunable factors, whose weights can be tuned with training.

9.52.2 Member Function Documentation

9.52.2.1 getGradient()

```
virtual std::vector<float> EFG::train::Trainable::getGradient (
    TrainSetPtr trainSet ) [pure virtual]
```

Returns

the gradient of the weights of the tunable clusters w.r.t. the passed training set

Exceptions

<i>when</i>	the trainSet is inconsistent because have a wrong combinations size
-------------	---

Implemented in [EFG::model::RandomField](#).

9.52.2.2 setOnes()

```
void EFG::train::Trainable::setOnes ( )
```

Parameters

<i>sets</i>	equal to 1 the weight of all the tunable clusters
-------------	---

9.52.2.3 setWeights()

```
void EFG::train::Trainable::setWeights (
    const std::vector< float > & w )
```

Parameters

<i>the</i>	new set of weights to assume for the tunable clusters
------------	---

Exceptions


<i>when</i>	the number of passed weights is inconsistent
-------------	--

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/Trainable.h

9.53 EFG::train::Trainer Class Reference

Inheritance diagram for EFG::train::Trainer:



Public Member Functions

- virtual void [train](#) ([Trainable](#) &model, TrainSetPtr trainSet)=0
trains the passed model, using the passed training set
- std::size_t **getMaxIterations** () const
- void **setMaxIterations** (std::size_t iter)

Protected Attributes

- std::size_t **maxIterations** = 100

9.53.1 Member Function Documentation

9.53.1.1 train()

```
virtual void EFG::train::Trainer::train (
    Trainable & model,
    TrainSetPtr trainSet ) [pure virtual]
```

trains the passed model, using the passed training set

Parameters

<i>the</i>	model to train
<i>the</i>	training set to use


Implemented in [EFG::train::GradientDescend< Extractor >](#).

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/Trainer.h

9.54 EFG::train::TrainHandler Class Reference

Inheritance diagram for EFG::train::TrainHandler:



Public Member Functions

- virtual void **setTrainSet** (TrainSetPtr trainSet, const std::set< categoric::VariablePtr > &modelVariables)=0
- virtual float **getGradientAlpha** ()=0
- virtual float **getGradientBeta** ()=0
- virtual void **setWeight** (const float &w)=0

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/Trainable.h

9.55 EFG::train::TrainSet Class Reference

Public Member Functions

- [TrainSet](#) (const std::vector< [categoric::Combination](#) > &combinations)
- [TrainSet](#) (const std::string &fileName)
- [TrainSet](#) [getRandomSubSet](#) (const float &percentage) const
- const std::vector< CombinationPtr > & [getSet](#) () const

9.55.1 Constructor & Destructor Documentation

9.55.1.1 TrainSet() [1/2]

```
EFG::train::TrainSet::TrainSet (
    const std::vector< categoric::Combination > & combinations ) [explicit]
```

Parameters

<i>the</i>	set of combinations that will be part of the train set.
------------	---

Exceptions

<i>if</i>	the combinations don't have all the same size
<i>if</i>	the combinations container is empty

9.55.1.2 TrainSet() [2/2]

```
EFG::train::TrainSet::TrainSet (
    const std::string & fileName ) [explicit]
```

Parameters

<i>import</i>	the combinations from a textual file where each row represent a combination
---------------	---

Exceptions

<i>if</i>	the file is not readable
<i>if</i>	the parsed combinations don't have all the same size
<i>if</i>	the file is empty

9.55.2 Member Function Documentation

9.55.2.1 getRandomSubSet()

```
TrainSet EFG::train::TrainSet::getRandomSubSet (
    const float & percentage ) const
```

Returns

a [TrainSet](#) containing some of the combinations stored into this object. The combination to take are randomly decided.

Parameters


<i>the</i>	percentage of combinations to extract from this object.
------------	---

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/TrainSet.h

9.56 EFG::train::TrainSetExtractor Class Reference

Inheritance diagram for EFG::train::TrainSetExtractor:



Protected Member Functions


- virtual TrainSetPtr **getTrainSet** ()=0
- void **setCompleteTrainSet** (TrainSetPtr trainSet)
- TrainSetPtr **getCompleteTrainSet** ()

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/trainers/TrainSetExtractor.h

9.57 EFG::train::handler::UnaryHandler Class Reference

Inheritance diagram for EFG::train::handler::UnaryHandler:



Public Member Functions

- **UnaryHandler** (nodes::Node &node, std::shared_ptr< distribution::factor::modif::FactorExponential > factor)
- float **getGradientBeta** () final

Protected Attributes

- nodes::Node * node

Additional Inherited Members

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/train/handlers/UnaryHandler.h

9.58 EFG::categoric::Variable Class Reference

An object representing an immutable categoric variable.

```
#include <Variable.h>
```

Public Member Functions

- [Variable](#) (const std::size_t &size, const std::string &name)
- **Variable** (const [Variable](#) &)=default
- [Variable](#) & **operator=** (const [Variable](#) &)=delete
- bool **operator==** (const [Variable](#) &o) const
- std::size_t **size** () const
- const std::string & **name** () const

Protected Attributes

- const size_t **Size**
- const std::string **Name**

9.58.1 Detailed Description

An object representing an immutable categoric variable.

9.58.2 Constructor & Destructor Documentation

9.58.2.1 Variable()

```
EFG::categoric::Variable::Variable (
    const std::size_t & size,
    const std::string & name )
```

Parameters

<i>domain</i>	size of this variable
<i>name</i>	used to label this varaible.

Exceptions

<i>passing</i>	0 as size
<i>passing</i>	an empty string as name

The documentation for this class was generated from the following file:

- C:/Users/andre/Desktop/Easy-Factor-Graph/Lib/EFG/Header/categoric/Variable.h

Index

- absorbModel
 - EFG::nodes::InsertCapable, [100](#)
- add
 - EFG::categoric::Group, [95](#)
- addEvidence
 - EFG::nodes::EvidencesChanger, [80](#)
- Combination
 - EFG::categoric::Combination, [63](#), [64](#)
- ConditionalRandomField
 - EFG::model::ConditionalRandomField, [66](#)
- DistributionFinder
 - EFG::distribution::DistributionFinder, [70](#)
- DistributionIterator
 - EFG::distribution::DistributionIterator, [72](#)
- EFG, [51](#)
- EFG::categoric, [51](#)
 - getComplementary, [52](#)
- EFG::categoric::Combination, [63](#)
 - Combination, [63](#), [64](#)
 - operator<, [64](#)
 - operator=, [64](#)
- EFG::categoric::Group, [93](#)
 - add, [95](#)
 - Group, [93](#), [94](#)
 - operator=, [95](#)
 - replace, [95](#)
 - size, [96](#)
- EFG::categoric::Range, [108](#)
 - get, [109](#)
 - operator++, [109](#)
 - operator==, [109](#)
 - Range, [108](#)
- EFG::categoric::Variable, [119](#)
 - Variable, [120](#)
- EFG::distribution, [52](#)
- EFG::distribution::Distribution, [67](#)
 - find, [68](#)
 - findRaw, [68](#)
 - getFinder, [69](#)
 - getIterator, [69](#)
 - getProbabilities, [69](#)
- EFG::distribution::DistributionFinder, [70](#)
 - DistributionFinder, [70](#)
 - find, [71](#)
- EFG::distribution::DistributionInstantiable, [71](#)
- EFG::distribution::DistributionIterator, [72](#)
 - DistributionIterator, [72](#)
 - getCombination, [73](#)
 - getImage, [73](#)
 - getImageRaw, [73](#)
 - getNumberOfValues, [73](#)
- EFG::distribution::DistributionSetter, [74](#)
 - setAllImagesRaw, [74](#)
 - setImageRaw, [74](#)
- EFG::distribution::Evaluator, [76](#)
 - evaluate, [76](#)
- EFG::distribution::factor, [53](#)
- EFG::distribution::factor::cnst, [54](#)
- EFG::distribution::factor::cnst::Factor, [85](#)
 - Factor, [86](#), [87](#)
- EFG::distribution::factor::cnst::FactorExponential, [88](#)
 - FactorExponential, [89](#)
 - getWeight, [89](#)
- EFG::distribution::factor::cnst::IndicatorFactor, [98](#)
 - IndicatorFactor, [99](#)
- EFG::distribution::factor::EvaluatorBasic, [76](#)
 - evaluate, [77](#)
- EFG::distribution::factor::EvaluatorExponential, [78](#)
 - evaluate, [78](#)
- EFG::distribution::factor::modif, [54](#)
- EFG::distribution::factor::modif::Factor, [84](#)
- EFG::distribution::factor::modif::FactorExponential, [87](#)
- EFG::Error, [75](#)
- EFG::io, [54](#)
- EFG::io::Exporter, [82](#)
- EFG::io::Importer, [98](#)
- EFG::io::json, [55](#)
- EFG::io::json::Exporter, [83](#)
 - exportToJson, [83](#)
- EFG::io::xml, [55](#)
- EFG::io::xml::Exporter, [82](#)
 - exportToXml, [83](#)
- EFG::io::xml::Importer, [97](#)
 - importFromXml, [97](#)
- EFG::iterator, [55](#)
 - forEach, [56](#)
 - forEachConditioned, [56](#)
- EFG::iterator::Bidirectional, [62](#)
- EFG::iterator::Forward, [89](#)
 - operator==, [90](#)
- EFG::iterator::StlBidirectional< IteratorStl >, [110](#)
 - operator==, [110](#)
- EFG::model, [57](#)
- EFG::model::ConditionalRandomField, [65](#)
 - ConditionalRandomField, [66](#)
 - insertTunable, [66](#)

- EFG::model::Graph, 92
- EFG::model::RandomField, 106
 - getGradient, 107
 - insertTunable, 107
- EFG::nodes, 57
- EFG::nodes::Base, 59
- EFG::nodes::BeliefAware, 60
- EFG::nodes::BeliefPropagator, 61
- EFG::nodes::Connection, 67
- EFG::nodes::EvidenceAware, 79
- EFG::nodes::EvidencesChanger, 79
 - addEvidence, 80
 - resetEvidences, 80
- EFG::nodes::EvidencesSetter, 81
 - setEvidences, 81
- EFG::nodes::GibbsSampler, 90
 - getHiddenSetSamples, 91
- EFG::nodes::HiddenClusters, 96
- EFG::nodes::InsertCapable, 99
 - absorbModel, 100
 - insert, 100, 101
 - insertCopy, 101
- EFG::nodes::InsertTunableCapable, 102
 - insertTunableCopy, 102, 103
- EFG::nodes::Node, 103
- EFG::nodes::NodesAware, 104
 - getVariables, 104
- EFG::nodes::PropagationResult, 105
- EFG::nodes::QueryHandler, 105
 - getHiddenSetMAP, 105
 - getJointMarginalDistribution, 105
 - getMAP, 106
 - getMarginalDistribution, 106
- EFG::nodes::StructureAware, 111
 - factors, 112
 - factorsExp, 112
- EFG::nodes::StructureTunableAware, 112
 - factorsTunable, 113
 - getFactorsTunable, 113
 - getWeights, 113
- EFG::train, 58
- EFG::train::BasicExtractor, 60
- EFG::train::GradientDescend< Extractor >, 91
 - train, 91
- EFG::train::handler, 58
- EFG::train::handler::BaseHandler, 59
- EFG::train::handler::BinaryHandler, 62
- EFG::train::handler::CompositeHandler, 65
- EFG::train::handler::UnaryHandler, 119
- EFG::train::StochasticExtractor, 111
- EFG::train::Trainable, 114
 - getGradient, 114
 - setOnes, 115
 - setWeights, 115
- EFG::train::Trainer, 115
 - train, 116
- EFG::train::TrainHandler, 116
- EFG::train::TrainSet, 117
 - getRandomSubSet, 118
 - TrainSet, 117
- EFG::train::TrainSetExtractor, 118
- evaluate
 - EFG::distribution::Evaluator, 76
 - EFG::distribution::factor::EvaluatorBasic, 77
 - EFG::distribution::factor::EvaluatorExponential, 78
- exportToJson
 - EFG::io::json::Exporter, 83
- exportToXml
 - EFG::io::xml::Exporter, 83
- Factor
 - EFG::distribution::factor::cnst::Factor, 86, 87
- FactorExponential
 - EFG::distribution::factor::cnst::FactorExponential, 89
- factors
 - EFG::nodes::StructureAware, 112
- factorsExp
 - EFG::nodes::StructureAware, 112
- factorsTunable
 - EFG::nodes::StructureTunableAware, 113
- find
 - EFG::distribution::Distribution, 68
 - EFG::distribution::DistributionFinder, 71
- findRaw
 - EFG::distribution::Distribution, 68
- forEach
 - EFG::iterator, 56
- forEachConditioned
 - EFG::iterator, 56
- get
 - EFG::categoric::Range, 109
- getCombination
 - EFG::distribution::DistributionIterator, 73
- getComplementary
 - EFG::categoric, 52
- getFactorsTunable
 - EFG::nodes::StructureTunableAware, 113
- getFinder
 - EFG::distribution::Distribution, 69
- getGradient
 - EFG::model::RandomField, 107
 - EFG::train::Trainable, 114
- getHiddenSetMAP
 - EFG::nodes::QueryHandler, 105
- getHiddenSetSamples
 - EFG::nodes::GibbsSampler, 91
- getImage
 - EFG::distribution::DistributionIterator, 73
- getImageRaw
 - EFG::distribution::DistributionIterator, 73
- getIterator
 - EFG::distribution::Distribution, 69
- getJointMarginalDistribution
 - EFG::nodes::QueryHandler, 105
- getMAP

- EFG::nodes::QueryHandler, 106
- getMarginalDistribution
 - EFG::nodes::QueryHandler, 106
- getNumberOfValues
 - EFG::distribution::DistributionIterator, 73
- getProbabilities
 - EFG::distribution::Distribution, 69
- getRandomSubSet
 - EFG::train::TrainSet, 118
- getVariables
 - EFG::nodes::NodesAware, 104
- getWeight
 - EFG::distribution::factor::cnst::FactorExponential, 89
- getWeights
 - EFG::nodes::StructureTunableAware, 113
- Group
 - EFG::categoric::Group, 93, 94
- importFromXml
 - EFG::io::xml::Importer, 97
- IndicatorFactor
 - EFG::distribution::factor::cnst::IndicatorFactor, 99
- insert
 - EFG::nodes::InsertCapable, 100, 101
- insertCopy
 - EFG::nodes::InsertCapable, 101
- insertTunable
 - EFG::model::ConditionalRandomField, 66
 - EFG::model::RandomField, 107
- insertTunableCopy
 - EFG::nodes::InsertTunableCapable, 102, 103
- operator<
 - EFG::categoric::Combination, 64
- operator++
 - EFG::categoric::Range, 109
- operator=
 - EFG::categoric::Combination, 64
 - EFG::categoric::Group, 95
- operator==
 - EFG::categoric::Range, 109
 - EFG::iterator::Forward, 90
 - EFG::iterator::StlBidirectional< IteratorStl >, 110
- Range
 - EFG::categoric::Range, 108
- replace
 - EFG::categoric::Group, 95
- resetEvidences
 - EFG::nodes::EvidencesChanger, 80
- setAllImagesRaw
 - EFG::distribution::DistributionSetter, 74
- setEvidences
 - EFG::nodes::EvidencesSetter, 81
- setImageRaw
 - EFG::distribution::DistributionSetter, 74
- setOnes
 - EFG::train::Trainable, 115
- setWeights
 - EFG::train::Trainable, 115
- size
 - EFG::categoric::Group, 96
- train
 - EFG::train::GradientDescend< Extractor >, 91
 - EFG::train::Trainer, 116
- TrainSet
 - EFG::train::TrainSet, 117
- Variable
 - EFG::categoric::Variable, 120