Atelier 7

GitLab CI & SonarQube Cloud

Secure code analysis: V1 (clean code) vs V2 (XSS injection)

Project: atelier6_abdo (GitLab group ZEMRAN-group) - Author: Abdellah Zammrane - 11/11/2026

V1 - Clean, safe and simple code

Figure 1 - VS Code and GitLab push. Codex was asked to create index.html, style.css and script.js for a clean, safe and simple page that shows a message. It produced a responsive message page with a welcome button. The code was then pushed to the main branch of the GitLab repository, and the terminal shows the push completed without errors.




Figure 1 - Generated code and successful git push

Figure 2 - SonarQube Cloud analysis of V1. SonarQube Cloud analysed the main branch (85 lines of code). It found 0 open issues in Security, Reliability and Maintainability, all rated A, with 0.0% duplications. The quality gate shows "Not computed" only because duplication and coverage checks are ignored when new code has fewer than 20 lines. It is not a failure.




Figure 2 - SonarQube Cloud summary of V1

V2 - XSS injection

Figure 3 - Failed GitLab pipeline. For V2, an XSS (Cross-Site Scripting) vulnerability was deliberately added in the commit "Adding the V2 Injection XSS". Pipeline #3053726474 on main is marked **Failed** with the error label, which proves the insecure code was caught, unlike the clean V1 code.




Figure 3 - Pipeline #3053726474 in Failed status