



ATLAS Note

4th May 2018



Users guide to the ATLAS L^AT_EX package

Ian C. Brock

University of Bonn

The usage of the ATLAS L^AT_EX templates and style files is documented here. The options that are available are given, as well as the packages that can be loaded using these files. Information on the setups used to test the packages is given and some help with the conversion of the document to the L^AT_EX format needed for journal submission is included.

This document was generated using version 05-05-00 of the ATLAS L^AT_EX package. The T_EX Live version is set to 2016. It uses the option `atlasstyle`, which implies that the standard ATLAS preprint style is used.

Contents

1	Introduction	4
2	Getting started	4
3	ATLAS L^AT_EX and the Physics Office GitLab project	5
4	Title, author and document numbers	6
4.1	Authors and Contributors	6
4.2	Special author lists	7
4.3	Metadata commands	7
5	The atlasdoc class	9
5.1	Dependencies and atlaspackage	11
5.2	Cover pages	13
6	The ATLAS preprint style	14
7	CERN preprints and arXiv	15
8	ATLAS TDR and LOI documents	16
9	ATLAS notes	16
10	Auxiliary and HEPData material	16
11	Symbols in atlasphysics.sty	17
12	atlaslatex directories and Git or SVN	17
13	Language editor commands	17
14	Installation of atlaslatex in texmf tree	18
15	Platforms and L^AT_EX versions	18
16	Miscellaneous L^AT_EX tips	19
16.1	Line numbers	19
16.2	Definitions	19
16.3	Useful packages	20
16.4	Figures	20
16.5	Subfigures	21
16.6	Positions of figures and tables	22
16.7	p_T or E_T – that is the question	22
17	Remarks on units and symbols	23
A	Makefile	24

B	Journal templates	24
C	From atlasnote to atlasdoc	25
D	History	26
D.1	Changes in atlaslatex-05-00-00	26
D.2	Changes in atlaslatex-04-00-00	27
D.3	Changes in atlaslatex-02-00-00	27
D.4	Changes in atlascover-01-00-00	27

1 Introduction

This collection of ATLAS \LaTeX templates, style files and documentation can be used for papers, pre-prints and notes, both public and internal. All necessary files are collected in a single package called `atlaslatex`. The package is available from the web pages of the Publication Committee [1] and from Git [2].

The collection replaces and improves on the previous packages. In particular it supersedes:

- `atlasnote-00-04-05`
- `atlascover-00-00-11`
- `atlaspreprint-00-00-05`
- `atlasbib-00-00-04`

Section C summarises the changes that have been made and how you can adapt your documents to use the new package. Section D.4 summarises the changes to the cover macros.

The package includes the `atlasdoc` class, useful style files and documentation of the package. The package also defines a standard ATLAS style for papers. This style should be used for paper drafts and for submission to the arXiv and the journal. This option is the default. Add the option `atlasstyle=false` to the `atlasdoc` class if you do not want to use this style. The documentation is provided as both PDF files and \LaTeX documents that should provide examples of how to use the package and how to write good \LaTeX .

The design principle is that you have a main document and the style files and `atlasdoc` class are in a subdirectory `latex`. The logos that are needed are kept in a `logos` directory. This subdirectories can of course be links to a centrally maintained `latex` directory. See below and Section 14 for how to proceed if you want to use and/or install the package in a central place.

The usual procedure is that for each document that you create, you first unpack the latest version of `atlaslatex` and then create your main document in the top-level directory. This structure means that it is easier to update the style files if a new version of `atlaslatex` is released. Each document can then be independent of the `atlaslatex` release.

2 Getting started

To create a new document you can issue one of the commands:

```
make newspaper [BASENAME=mydocument] [TEXLIVE=YYYY]
make newnote [BASENAME=mydocument] [TEXLIVE=YYYY]
```

depending on whether you want to write a paper/CONF Note/Pub Note draft or an ATLAS not draft. The command copies `atlas-document.tex` and `atlas-paper-metadata.tex` or `atlas-note-metadata.tex` to `mydocument.tex` and `mydocument-metadata.tex`.¹ The selected \TeX Live version is set with the `TEXLIVE` option. The default is 2016. The `make newspaper|newnote` command also creates empty files `mydocument-defs.sty` and `mydocument.bib`. By default the document will be an ATLAS note draft.

¹ The Makefile should work for regular Linux and MacOSX distributions. For Windows, you probably have to execute the tasks in the Makefile by hand.

Use `make newspaper` for an ATLAS paper draft (including CONF and PUB notes). Replace the option PAPER with CONF or as appropriate.

In the Makefile you should change the BASENAME to the name of your document. You can then compile your document with the command: `make`. You can try the command `make run_latexmk` instead, which invokes `latexmk`, a Perl script that is cleverer than the Makefile. You can also make this command the default. Have a look at Makefile for other things you can adjust.

If you install `atlaslatex` in a central directory such as `${HOME}/texmf` the basic command is one of:

```
make newpapertexmf [BASENAME=mydocument] [TEXLIVE=YYYY]
make newnotetexmf [BASENAME=mydocument] [TEXLIVE=YYYY]
```

See Section 14 for more details.

In order to make a new document of book form like a TDR, use one of the commands:

```
make newbook [BASENAME=mydocument] [TEXLIVE=YYYY]
make newbooktexmf [BASENAME=mydocument] [TEXLIVE=YYYY]
```

By default, this will pass the option BOOK to `atlasdoc`. Use `make newbooktexmf` for a book with `atlaslatex` in a central directory.

Note that you have to specify the language of your document as an option in the `\documentclass` command. Typical settings are

- UKenglish (or british);
- USenglish (or american).

As mentioned above the default \TeX Live version is currently set to 2016. This should be the only option you have to adjust if you use different versions of \LaTeX . You should be able to always set a version lower than the one you have installed to maintain compatibility with older versions. To test compatibility with arXiv, try a setting of 2016.

As of Version 01-07-00 of `atlaslatex` you should include the command `\maketitle` after your `\begin{document}` if you want the document title to be printed.

Add the option `atlasstyle=false` to the `\documentclass` if you do not want to typeset your document in the ATLAS preprint style.

3 ATLAS \LaTeX and the Physics Office GitLab project

With the move of ATLAS software and documents to Git, new opportunities are available to streamline the production of documents and smooth the process of submitting them to arXiv and journals. This project is called PO-GitLab in the following [3].

In order for the new tools to work smoothly some file-naming conventions should be followed. If the Physics Office set up the Git repository, the files should already have the correct names. The conventions are documented on <https://gitlab.cern.ch/atlas-physics-office/gitlab-integration/wikis/newproject>. For paper drafts, in short:

- the main file should have the name GROUP-YEAR-NUM-PAPER.tex;
- the metadata file should have the name GROUP-YEAR-NUM-PAPER-metadata.tex
- the auxiliary material should be included in a file with the name GROUP-YEAR-NUM-PAPER-auxmat.tex

In addition:

- figures must be included using the `\includegraphics` command;

4 Title, author and document numbers

An ATLAS document usually collects a series of labels over time. These include the reference code of the analysis, e.g. BPHY-2013-04, the ATLAS note number and the CERN preprint number. In addition the abstract and title are needed on the front page of the document and also on various cover pages. The editors of the document, the editorial board members and the contributors to the analysis also need to be specified at some point.

While all this information can be collected in the main file of the document, it is probably better to put it all in a separate document. By default this file is called `mydocument-metadata.tex`.

As the metadata needed for ATLAS notes and ATLAS papers are somewhat different, separate templates are used as of Version 04-00-00.

4.1 Authors and Contributors

The supporting documentation for an ATLAS note (not the paper draft) should contain a list of the contributors to the analysis. A style file `atlascontribute.sty` has been written to help with the creation of such a list. The macros in the style file can also build the author list at the same time. Two basic macros are used to add names to the author list and list of contributions: `\AtlasContributor` and `\AtlasAuthorContributor`. The first macro adds a person to the list of contributors, while the second one also adds the person to the author list. I assume that in almost all cases you will want to use `\AtlasAuthorContributor`. Typical commands are:

```
\AtlasAuthorContributor{Joe Student}{a}{fake background estimate.}
\AtlasAuthorContributor{Jane Student}{b}{top background estimate.}
\AtlasAuthorContributor{John Postdoc}{a}{editor of internal note.}
\AtlasContributor{Jo Helper}{useful contributions in a few places.}
\affil[a]{University of Nowhere}
\affil[b]{University of Somewhere}
```

If a person should be added to the author list, you also need to add an appropriate affiliation using the macro `\affil`. The optional argument is a letter or number that should also be given as the second argument to `\AtlasAuthorContributor`.

You can keep the list of authors and contributors separate by using `\author` for the authors and `\AtlasContributor` for the contributors. You print the list of contributors by giving the command

`\PrintAtlasContribute`. Note that `\PrintAtlasContribute` has an argument that gives the fraction of the line width to be used for the name of the person. The list should either be printed before the table of contents or after the conclusions (i.e. where the Acknowledgements appear in a paper).

Note that `authblk` assumes that you will also have affiliations for each author. You can avoid them by using the syntax `\author{[]{Author Name}}`. Note that a space is needed in the optional argument. This means that a space appears between the author name and the comma after it, which is not so nice. Alternatively you can make the author list using the syntax:

`\author{Joe Student \and Jane Student \and John Postdoc}` and avoid the use of the `authblk` package by giving the option `authblk=false` to `atlascontribute`.

Note that the `atlascontribute` package requires that the packages `array` and `booktabs` be installed. If the list of contributors is very long, it may spread over more than one page. The `tabular` environment does not like this. Add the option `xtab` to use `xtab` instead. This option of course also requires that the package `xtab` is installed.

4.2 Special author lists

Sometimes a PUB note has a special author list. Hence a link to this list should be added to the front page. This can be achieved with the following code snippet that should be used for the author:

```
% \usepackage[marginal,hang]{footmisc}
% \setlength{\footnotemargin}{0.5em}
\usepackage{authblk}
\author{The ATLAS Collaboration%
\thanks{The full author list can be found at:\\
\url{https://atlas.web.cern.ch/Atlas/PUBNOTES/ATL-PHYS-PUB-2014-YYY/authorlist.pdf}}
}
```

The first two lines are needed if you do not use the standard ATLAS preprint style. Note that `atlasdoc` has to be loaded with the option `maketitle=false` and `\maketitle` should be added after `\begin{document}`. This is the default as of Version 01-07-00 of `atlaslatex`.

4.3 Metadata commands

The standard list of metadata commands are given below. More are available for the draft cover page when a paper, CONF note or PUB note draft is circulated to the collaboration. See `template/atlas-document-metadata.tex` for more details.

- `\AtlasTitle{<Title>}` typesets the paper title. If not given, you get either an error or a dummy title will be produced.
- `\author{<Author>}` typesets the paper author. If not explicitly given, ‘The ATLAS Collaboration’ will be used by default. Note that the `\author{}` command is pretty limited in case you want to display multiple author names and multiple affiliations. For this use case the `authblk.sty` package is provided; this is a typical example of its use:

```

\usepackage{authblk}
\renewcommand\Authands{, } % avoid ‘‘. and’’ for last author
\renewcommand\Affilfont{\itshape\small} % affiliation formatting

\author[a]{First Author}
\author[a]{Second Author}
\author[b]{Third Author}

\affil[a]{One Institution}
\affil[b]{Another Institution}

```

See also Section 4.1 if you want to combine the creation of a list of authors and contributors.

- `\AtlasAbstract{<The abstract text>}` typesets the abstract on the front page and cover page.
- `\date{<Date>}` typesets the paper date. If not explicitly given, the current date (`\today`) will be used.
- `\AtlasVersion{<Draft Version>}` displays the draft version on the front page, a DRAFT banner on all the other page headings, and adds line numbers to all text to easy commenting and reviewing. Should be included when paper draft is circulated to ATLAS. Highly recommended for all documents in the draft stage. In the future, the steering of whether the document is a draft or not will be done using the option `atlasdraft`. At present (`atlaslatex 04-03-00` onwards), if `atlasdraft=true` or `\AtlasVersion` is not empty, the document is declared as a draft.
- `\AtlasJournal{<Journal Name>}` displays the phrase *to be submitted to Journal Name* at the bottom of the front page and on the cover page. Should be included when a paper draft is circulated to ATLAS.
- `\AtlasRefCode{<Reference code>}` displays the ATLAS standard reference code, e.g. BPHY-2014-03, on the front page and the cover page. Not shown on the front page if the note number is given.
- `\AtlasNote{<Note number>}` displays the note number for a CONF, PUB, INT or COM note, e.g. ATLAS-CONF-2014-23, on the front page and cover page. If the note number is given, the reference code is not shown.
- `\PreprintIdNumber{<CERN preprint number>}` displays the CERN preprint number on the front page.
- `\AtlasDate{<Date>}` set by the Physics Office as the date of submission of a paper.
- `\AtlasJournalRef{<Journal reference>}` displays the journal reference on the preprint front page. This should be used for the arXiv update after the paper has been published.
- `\AtlasDOI{<Journal reference>}` displays the DOI on the preprint front page. This should be used for the arXiv update after the paper has been published.
- `\arXivId{<arXiv identifier>}` displays the arXiv reference on the front page.

template/atlas-document.tex contains a basic skeleton that can be used to start typing a new note using the atlasdoc class. Many of the custom commands described above are used in this example file, in order to demonstrate their use.

Links to supporting documentation should also be included on the cover page of draft papers circulated to ATLAS. They can be included using \AtlasCoverSupportingNote{Short title}{CDS link}. It is also possible to give a TWiki page instead, but this is deprecated.

As mentioned above, see template/atlas-document-metadata.tex for more details.

5 The atlasdoc class

This document has been typeset using the atlasdoc.cls class.

The atlasdoc class can use either the standard L^AT_EX article class as its basis or the KOMA-Script sctartcl class. All the usual commands and options you usually use with article or scrartcl should work with it. You turn on the use of KOMA-Script with the option koma. For instance, this document has been produced using this very simple preamble:

```
\documentclass[UKenglish]{latex/atlasdoc}
\usepackage{latex/atlaspackage}
\usepackage{latex/atlasphysics}
\graphicspath{{../../logos/}}{{figures/}}
```

Note that the document language must be specified, otherwise babel will complain.

The L^AT_EX packages that are used in the document are mostly specified in latex/atlaspackage.sty.

The style file latex/atlasphysics.sty defines a lot of useful macros for particles and more. See the separate document atlas_physics.pdf [4] for details.

If you do not want to use biblatex you need to add the option biblatex=false when you include atlaspackage. Have a look at the latex/atlaspackage.sty to see how biblatex is included. In your main document you use \addbibresource in the preamble to include your .bib files. Note that the backend biber returns with an error if it finds an empty .bib file. A style file latex/atlasbiblatex.sty is available that adjusts the format of the references to the usual ATLAS conventions.

As mentioned above, you have to specify the document language as an option to atlasdoc. Several more options can be set. In the following the default option is in boldface.

atlasstyle=true|false turn on (default) or off the use of the ATLAS style for the document;

atlasdraft=true|false this is a draft version of the document;

coverpage include an ATLAS draft cover page;

cernpreprint make the front page for a CERN preprint. The option preprint works as well, but is deprecated;

NOTE the document is an ATLAS note (default);

PAPER the document is an ATLAS paper (draft);

CONF the document is a CONF note;

PUB the document is an PUB note;

BOOK the document is book form like an LOI or TDR;

HEPDATA a separate document with detailed tables etc. for HEPData;

texlive=2016 adjust if you use an older version of T_EX Live like 2011. A value less than 2013 adjusts a few bibl_{at}ex options. A value less than 2012 uses t_xfont_s.

paper=a4|letter set the paper size;

titlesize=normal|small use normal or reduced size fonts for the title page;

floatopt=true|false adjust the options (default) governing number and placement of floats on a page;

texmf use the syntax `\usepackage{package}` instead of `\usepackage{latex/package}` to include packages. This is needed if you install atlas_{lat}ex centrally, rather than in a latex subdirectory;

newtx use the newtx_{text} and newtx_{math} packages for fonts (default for T_EXLive > 2012);

txfont_s use the txfont_s package for fonts instead of the default (default for older T_EXLive versions);

mhchem=true|false include mhchem before xpatch to avoid an error with T_EX Live 2014;

abstract=true|false the document contains an abstract. This option is only needed together with the BOOK option, if the book does not have an abstract;

datetop=true|false put the date at the top of the title page;

showframe=true|false load the showframe package, to display frames showing the boxes for text body, header, footer and margin;

titleextraheight=0em extra height that could be needed for the title, if it is very long;

copyrightoffset=0em adjust the position of the copyright, if it is not completely correct.

The option atlas_{draft} was introduced with atlas_{lat}ex 04-03-00. It is intended to replace to replace using the definition of `\AtlasVersion` to decide if this a final version of a document. In a later version the default value will be set to false, so that this option simply has to be removed when a document is final.

The following options were removed in atlas_{doc} in atlas_{lat}ex 02-00-00. They are mostly still available in atlas_{doc}1.

maketitle=true|false turn on or off the creation of a title page within `\AtBeginDocument`. If the option is false, but you still want a title, give the command `\maketitle` after `\begin{document}`. This is the recommended way of proceeding;

nomaketitle do not create a title page; equivalent to maketitle=false. This option has no effect as of atlas_{lat}ex 01-07-00 of atlas_{lat}ex;

koma=true|false use the KOMA-Script base class scrartcl instead of article;

letterpaper set the paper size to letter.

a4paper set the paper size to A4; *This option was removed in atlaslatex 02-00-00 – use paper=a4 instead;*

letter set the paper size to letter. *This option was removed in atlaslatex 02-00-00 – use paper=letter instead;*

Note that the options CONF and PUB get passed to atlascover.sty as they only influence the cover pages.

The [UK List of FAQ](#) recommends changing several default L^AT_EX options so that there are fewer problems with figure and table placement. It is certainly worth reading that page for further advice. As it is very hard to really test how well these options work they can be turned on or off in atlasdoc via the option floatopt=true|false. The default value is set to true.

As of atlasdoc Version 02-00-00, the KOMA-Script elements are used to create the title pages. In particular, \publishers is used for the abstract and copyright. The space and position for this may need to be adjusted, if you have a very long title. Use the options titleextraheight and copyrightoffset to make adjustments. It is very helpful to turn on the showframe option when doing this.

5.1 Dependencies and atlaspackage

The atlasdoc class depends on these packages, whose presence in your system is required:

- babel: become language aware;
- scrpage2: defines the header for draft mode and for auxiliary material documents.
- fontenc: output font encoding;
- hyperref: add hyperlinks and ability to click on cross-references;
- graphicx: include graphics in the document;
- lineno: add line numbers to documents;
- newtxtext and newtxmath: the standard ATLAS document font. If this is not available, you can fall back to txfonts;
- xcolor: add colours to L^AT_EX;
- ifthen: improved handling of conditionals.

These should be installed in any modern L^AT_EX installation. See [\[5\]](#) for details on which collections are needed to get these packages for your operating system.

Note that under Ubuntu versions 12.04 and 14.04, lineno can be found in the texlive-humanities package! If you cannot find it, it is also included in latex/other. Copy it to your main directory, or to $\${HOME}/texmf/tex/latex$ in order to make it centrally available.

Both the class atlasdoc and all style files: atlasbiblatex, atlascontribute, atlascover, atlaspackage and atlasphysics, need the package kvoptions so that they can process options where a value for an option should be set.

atlasdoc and atlascover both need hyperref. Have a look at one of these packages to see how to include it by hand. You can also simply use atlaspackage.sty

The style file atlaspackage.sty includes further packages. You can steer how many by using the option minimal, default or full. The minimal set is:

- **amsmath**: extra useful maths environments;
- **inputenc**: allow ä, ö, ø, ß, etc. to be input directly;
- **hyperref**: add hyperlinks and ability to click on cross-references;
- **placeins**: adds commands to force figure and table output before a certain position in the text.

The default set adds in addition:

- **booktabs**: nicer tables. Use `\toprule`, `\midrule` and `\bottomrule` instead of `\hline`;
- **csquotes**: smart quotes that incorporate language dependence;
- **siunitx**: units package with extra functionality for tables;
- **subfig**: more than one plot in a figure;
- **tocloft**: extra options for typesetting table of contents etc.

Finally the full set includes further packages that may be useful:

- **mhchem**: chemical elements and molecules;
- **rotating** rotate figures, tables, etc.;
- **xfrac** nicer fractions;
- **xtab** newer version of **supertabular**, which allows tabular environments to go over more than one page.

The full list of options is:

biblatex=true|false turn on/off use of **biblatex** and **biber/bibtex**;

backend=bibtex|biber specify the backend to use with **biblatex**. Specify **backend=bibtex** to use **bibtex** instead;

hyperref=true|false turn on/off use of **hyperref**;

siunitx=true|false do not include the **siunitx** package;

eVkern=true|false apply a kern of -0.1em to eV in order to move ‘e’ and ‘V’ closer together. This option is set by default if you use the **txfonts** fonts;

percentspace=true|false include or not the default space between a number and the % sign;

subcaption=true|false use **subcaption** instead of **subfig**; **subcaption** is supposed to be a newer, better and more general package than **subfig** or **subfigure**. It is probably best to only use it with **T_EX Live 2012** or later;

subfigure=true|false use the deprecated package **subfigure** instead of **subfig**;

subfig=true|false use the somewhat deprecated package **subfig**;

texlive=2016 set if you use an older version of **T_EX Live** like 2011. A value less than 2013 adjusts a few **biblatex** options. A value less than 2012 uses **txfonts** and the old (Version 1) option names for **siunitx**. A value less than 2010 uses the old option names for **csquotes**. Use **texlive=2016** to test options for arXiv submissions;

txfonts=true|false load the **txfonts** package and adjust loading of **amsmath** for duplicate symbols;

lineno=true|false load the **lineno** package.

lineno.sty and **authblk.sty** are also provided in **obsolete**, just in case they are not in your standard **L^AT_EX** installation and for some reason you cannot download them from CTAN (<https://ctan.org>).

Depending on the font you use, you may find that the ‘e’ and ‘V’ in eV, MeV etc. are too far apart. You can pass the option **eVkern** to **atlaspackage** in order to move them 0.1em closer together.² This is the amount used in the **atlasunit.sty** for `\gev` etc. which is included by passing the option **unit=true** to

² This option has no effect for **T_EX Live 2011** and older, as **siunitx** adjusted the spacing internally using the parameter **eVcorra**.

`atlasphysics`. If you use `siunitx`, I recommend setting `unit=false`, so that you use one consistent set of definitions throughout your document.

The `siunitx` [6] package puts a (non-breaking) space between a number and the % sign, as for any other unit. It says that this is as required by the SI system of units [7]. However, conventions between publishers appear to differ [8]. Many people are used to there being no space. Pass the option `percentspace=false` to suppress the space. This option only works for T_EX Live versions 2011 and later.

There used to be a problem using the `tikz` package with `atlasnote`. With `atlasdoc` this problem seems to have gone away. `tikz` is not included in `atlaspackage`. If you want to use it, just add the usual `\usepackage{tikz}` to your preamble.

Other packages that have been used at some point include:

- `savesym`: needed to avoid errors if `txfonts` is used, as `txfonts` and `amsmath` define the same symbols;
- `footmisc`: extra footnote options. These mess up the `atlasstyle` settings.

5.2 Cover pages

The package also provides cover pages for the circulations of ATLAS drafts and for the front page for the CERN preprint version of an ATLAS paper. A further cover page is provided for a document containing detailed tables associated with a preprint/paper. The style file can be found in `latex/atlascover.sty`.

If you wish to use the `atlascover` package with the `atlasdoc` class, you should usually use the `coverpage` option of the class:

```
\documentclass[coverpage,UKenglish]{latex/atlasdoc}
```

instead of the the usual `usepackage` command: this will ensure that the cover page is produced before the title page of the document.

You can include `atlascover` with `\usepackage` if you prefer. In this case you need the option `maketitle=false` (which is the default as of Version 01-07-00 of `atlaslatex`) in the `atlasdoc` class (if you are using it) and you include the `\maketitle` command after `\begin{document}`.

The following options can be passed on to the `atlascover` package:

coverpage outputs the standard ATLAS paper draft cover page;

CONF the document is a CONF note;

PUB the document is an PUB note;

LANGEDIT prints the language editor's name and email address;

coverfontsize the base font size used for the cover (default is 11pt). Adjust this for long abstracts;

twocolumn use this option if your document is formatted in two columns;

atlasdoc this option is set by `atlasdoc` and is not usually needed by the user.

If you use `atlascover` standalone, use the option `coverpage=true` to actually output a cover page. This is necessary as of Version 01-04-00 of `atlaslatex` to make the use of options more consistent. As of Version 02-00-00, the options `cernpreprint`, `preprint` and `auxmat` are no longer available in `atlascover`. You should pass these to `atlasdoc` instead, as the title pages are now part of the main class.

Some papers have a very long abstract, such that it does not fit on the cover page. You can reduce the font size used on the cover by setting the option `coverfontsize`. The default value is 11pt. Try 10.5pt or 10pt instead to get the abstract onto the page.

It used to be the case that some journal styles, especially JHEP, produced an ATLAS draft cover page that was offset. You could use the options `hoffset` and `voffset` to move the text around.

JHEP needed `hoffset=1in`, `voffset=1in`.

revtex (APS journals) looked better with `hoffset=-0.25in`, `voffset=-0.25in`.

These offsets are ignored, as of Version 01-04-00 of `atlaslatex`, as the problems with spurious offsets have been eliminated.

The option `clearpage`, which used to exist, has no effect.

6 The ATLAS preprint style

This style should be used for the preparation of paper drafts, as well as for the submission of papers to the arXiv and journals. The journals will then convert the documents to the style appropriate for the journal.

Documents are typeset by default in the standard ATLAS preprint style. The use of this style can be turned off by using the option `atlasstyle=false`. This style uses KOMA-Script as the base class. Further settings include:

Layout: DIV=14 and an extra 5 mm for the binding;

Paragraph: the paragraph indentation is set to zero and there is a half-line separation between paragraphs;

Figures and tables: a small font size is used for the captions. Captions are not indented. They should be below both figures and tables;

Font: the default fonts are from the `newtx` package. These are very similar to `txfonts` that have been used up to now, but have a better spacing in a few cases;

Section headers: the standard serif font is used.

The default fonts for ATLAS documents are `newtxtext` and `newtxmath`. These are more modern variants of the package `txfonts` that has been used in ATLAS documents in the past.

In general, if you have problems with the `newtx` fonts, you can switch to `txfonts` by including the option `txfonts` with `atlasdoc`.

7 CERN preprints and arXiv

If you are writing an ATLAS paper and it has been approved by the collaboration, you have to make a version with the CERN preprint title page and prepare the paper for submission to arXiv.

If your paper draft is within the PO-GitLab project, the following steps will be performed by the Physics Office using the GitLab Continuous Integration tools. Before asking the Physics Office to do this, you should check that your paper draft follows the ATLAS conventions.

In order to turn the paper into a CERN preprint, you should replace the option `PAPER` by `cernpreprint` in `atlasdoc`. The CERN preprint number is given via the macro `\PreprintIdNumber`. At the same time you should pass the option `texlive=2016` to `atlasdoc`. This is because arXiv contains a 2016 \TeX Live installation. Summarising, a typical `\documentclass` command would be:

```
\documentclass[cernpreprint, texlive=2016, UKenglish]{latex/atlasdoc}
\pdfoutput=1
```

The `\pdfoutput` command tells arXiv that a PDF file should be produced directly. You should also turn off ATLAS draft cover page – remove the option `coverpage=true`. If you move the class and style files to the same directory as the main file, you need to add the option `texmf` to the `\documentclass`.

You can test whether your document compiles with \TeX Live 2016 by setting your `PATH` on `lxplus` to

```
export PATH=/afs/cern.ch/sw/XML/TL2016/bin/x86_64-linux:$PATH
```

Note that you should submit the `bb1` file and not the `bib` to arXiv. Depending on which journal you submit to, you should turn on or off the printing of the titles in the bibliography. Further details on how to proceed can be found on the Physics Office TWiki [9] – see the Section on ‘Guidelines for paper submission’. APS journals have special requirements on the directory structure and the filenames for figures. Neither `biblatex` nor `siunitx` are available and KOMA-Script does not contain the `\KOMAOPTIONS` command. See the Physics Office TWiki [9] for more information.

It also makes sense to clean up the metadata file at this point. You get rid of line numbering by making sure that neither `\AtlasVersion` nor `\draftversion` are defined. I recommend moving the relevant definitions into the main \TeX file so that the metadata file is no longer needed. If you clean things up, the `atlascover` package is no longer needed. The metadata commands that are needed in addition to the title, author and abstract are:

- `\AtlasJournal{<Journal Name>}`
- `\PreprintIdNumber{<CERN preprint number>}`
- `\AtlasDate{<Date>}` set by the Physics Office
- `\AtlasJournalRef{<Journal reference>}` once it exists
- `\AtlasDOI{<Journal reference>}` once it exists
- `\arXivId{<arXiv identifier>}` once it exists

More details on arXiv recommendations can be found at https://arxiv.org/help/submit_tex.

8 ATLAS TDR and LOI documents

If you include the option `BOOK`, `atlasdoc` uses the `scrbook` as the document class. This option is geared to long documents such as TDRs and LOIs. Such a document has various numbers which can be set as follows:

- `\AtlasRefCode`: ATLAS reference code, e.g. ATLAS-TDR-099.
- `\PreprintIdCode`: LHCC reference code, e.g. CERN-LHCC-2017-099.
- `\AtlasDate`: Official date of the document.

The title will be typeset flushleft, rather than the usual centering. A typical title would be:

```
\AtlasTitle{Technical Design Report\\  
for the ATLAS Detector Upgrade}
```

If you want to add images to the front and back covers, the template contains commented out commands that allow you to do this. The `pdfpages` package seems to work very well for such things. The images can be in `pdf`, `png` or `jpg` format. Unlike `\includegraphics` you should include the filename extension.

Note that the title page will only be correctly formatted if you use \TeX Live 2013 or newer. If you are using an older version add `\flushleft` to `\AtlasTitle`.

9 ATLAS notes

If you include the macro `\AtlasNote` in your preamble, the note number will be printed under ‘ATLAS NOTE’ at the top of your document. This can be used for any sort of ATLAS note, including CONF, PUB and INT notes.

10 Auxiliary and HEPData material

Many papers have extra plots and tables that should be made public, but are not submitted to arXiv and the journal. These should be collected in a file `mydocument-auxmat.tex`, which is included in the draft document during its circulation within ATLAS. This is transparent for editors if they use the PO-GitLab system, but has to be done manually for other papers.

Some papers have many pages of extra tables and plots that are mainly of use to theorists who need extra information. Such material should usually be included in the paper draft until it is ready for submission to arXiv and to the journal. The default name for the file containing the information is `mydocument-hepdata.tex`. At the submission stage it should be moved into a separate document. A skeleton document created using the command `make newdata BASENAME=...`. The front page for this document is formatted using the `HEPDATA` option. If you use this option you should specify the arXiv preprint identifier using the macro `\arXivId` and the HEPData record using the macro `\HepDataRecord`. This information is then included on the cover page in the form of clickable links.

Use of this option also adds the arXiv preprint identifier to the top of every page of the document.

If you want to create an HEPData document with an older T_EX Live version such as 2009, use the command `make newdata TEXLIVE=2009`.

11 Symbols in `atlasphysics.sty`

Many useful symbols are defined in `atlasphysics.sty`. While this used to be a very long file, it has now been split into several smaller files, which can be included or not using options. The definitions can be found in a separate document `atlas_physics.pdf`.

12 `atlaslatex` directories and Git or SVN

There is some flexibility in how you set up your directory structure for using `atlaslatex`. By default the `atlaslatex` style files are in the `latex` subdirectory and the logos are in `logos`. This structure assumes that you will make a separate directory tree for each document that you create. If you want to include these files in Git or SVN, note that you only need to add the `latex`, `logos` and `bib` directories of the `atlaslatex` package to Git or SVN. In order to create a new document, you also need the `template` directory.

If you want use a centrally installed `atlaslatex` package, then you would usually unpack the `atlaslatex-XX-YY-ZZ.tds.zip` file into your `texmf` tree – see Section 14.

If you want to use another setup, you should set the variable `\ATLASLATEXPATH` appropriately at the beginning of your document. This would enable you to maintain a single copy of each `atlaslatex` version and easily switch between versions. For example, you give the command `\newcommand*\ATLASLATEXPATH{../atlaslatex-01-08-00/}` to use version 01-08-00 of the `atlaslatex` package, which you have unpacked into the directory tree `../atlaslatex-01-08-00`. Such a structure makes it very easy to switch between `atlaslatex` versions without breaking anything!

13 Language editor commands

The `todonotes` has been used to add a few macros that should be of use for language editors. The commands are in the `atlascomment` style file. This file is included if the `LANGEDIT` is passed to `atlasdoc`. The commands added are:

`\LEecomment` adds a comment about a change, or suggested change.

The commands takes two arguments: the relevant text and the explanation/suggestion.

Such comments are probably also useful for paper editors. Have a look at this style file and the `todonotes` documentation on how you can set up your own macros.

14 Installation of atlaslatex in texmf tree

As discussed above, the atlasdoc class and the style files can all be found in the latex subdirectory. The template documents are usually set up to pick up the style files from there. If you want to use the centrally installed version, you should first copy Makefile and the template directory from `${HOME}/texmf/source/atlaslatex` to the directory where you want to create your document. For the main document, you can then use the command `make newspapertexmf` or `make newnotetexmf` to get a template which uses the centrally installed style files.

If you want to install the package in a central area, use the `atlaslatex-XX-YY-ZZ.tds.zip` file. Change your directory to `${HOME}/texmf` and unzip the file there. To do it by hand you can do:

- unpack the tarball;
- copy the latex directory to `${HOME}/texmf/tex/latex/atlaslatex`;
- copy the contents of the bib directories to `${HOME}/texmf/bib`.

It is more complicated to checkout part of a Git repository. Hence the method described above is the recommended way of installing atlaslatex in your texmf tree.

In the template files, you have to use the command `make newspapertexmf` or `make newnotetexmf` or simply change

From	To
<code>\newcommand*{\ATLASLATEXPATH}{latex/}</code>	<code>\newcommand*{\ATLASLATEXPATH}{}</code>

If you are using traditional BibTeX you also have to change
`\bibliographystyle{bib/bst/atlasBibStyleWoTitle}` to
`\bibliographystyle{atlasBibStyleWoTitle}`

The texmf option in atlasphysics is not strictly necessary if you use the class atlasdoc, but it does not do any harm.

15 Platforms and L^AT_EX versions

The atlasdoc class works both with L^AT_EX and pdfL^AT_EX. I recommend to use pdfL^AT_EX and this is the default.

I would expect everything to work with T_EX Live 2009 or later. You should just set the option `texlive` appropriately. This is best done in the document class, as the option is then passed to all other packages. Examples of changes include some option names for `siunitx`.

If for example you have T_EX Live 2009, add the option `texlive=2009` to the document class. This will then include `siunitx` with the correct options for Version 1. It will also switch to `unit=false` to `atlasphysics` and use option `txfonts` in `atlasdoc`.

If you use the `biblatex` package, the default is to use the `biber` backend. This was changed as of Version 04-00-00 of `atlaslatex`. For \TeX Live versions earlier than 2013, it may be better to use `bibtex`. To do this, pass the option `backend=bibtex` to `atlaspackage`.

The `atlaslatex` package should work under Linux, MacOS(X) and Windows. Details on the installations that I use for testing things and how you should set up your system can be found on the PubCom \LaTeX FAQ [5].

16 Miscellaneous \LaTeX tips

16.1 Line numbers

Line numbers can be printed using the `lineno` package, which is included by default. Line numbers are automatically turned on if you set `\AtlasVersion` (or `\draftversion`) or you pass the option `atlasdraft=true` to `atlasdoc`. In general, you can turn them on and off in a document by using the `\linenumbers` or `\nolinenumbers` commands. Note that if `\AtlasVersion` or option `atlasdraft=true` are set, you will always get line numbers on the standard title page. Hence, for papers, CONF and PUB notes it is important to comment out `\AtlasVersion` in order to suppress the line numbers for the final version.

In order to avoid line numbers going slightly wrong around figures and tables, separate the `figure` and `table` environment from the rest of the text using blank lines.

If you use AMS Math \LaTeX environments such as `align` line numbering may be interrupted around the environment. Enclose the environment in a `linenomath` environment to fix this problem:

```
\begin{linenomath}
\begin{equation*}
  E = m c^2
\end{equation*}
\end{linenomath}
```

16.2 Definitions

You can use `\ensuremath` in definitions, so that they will work in both text mode and math mode, e.g. `\newcommand{\UoneS}{\ensuremath{\Upsilon(\text{1S})}\xspace}` to get $\Upsilon(1S)$ in either mode (`\UoneS{}` or `\$UoneS$`).

I highly recommend that you also terminate every definition with `\xspace`, as then you can use the definitions without having to terminate them with ‘`_`’ or ‘`{ }`’.

16.3 Useful packages

A vast number of \LaTeX packages are available. In this section I collect a few useful packages that are not loaded by `atlaspackage`, but are well worth considering.

cleveref Means that constructs like `Fig.\ref{fig:one}` or `\Fig{\ref{fig:one}}` are no longer necessary. Instead just use `\cref{fig:one}`. The package decides if it is a figure, table or equation and adds the appropriate text. At the beginning of sentences use `\Cref`. Use `\usepackage{cleveref}` to get ‘fig.’ etc. Use `\usepackage[capitalize]{cleveref}` to get ‘Fig.’ etc.

todonotes Very nice package for adding notes. See `atlscomment.sty` for an example.

heppennames A package that defines most elementary particle, mesons and baryons in a consistent way. Optionally the symbols can be upright or italic. The package is included if you pass the option `hepparticle` to `atlasphysics`. You can use the package `hepnice` instead, which uses more intuitive names for the particles, but is not as systematic.

physics A useful package for differentials, matrices and more. As the name suggests it is geared to physics usage. The `commath` is an alternative, but I find `physics` to be more reliable, when different fonts are used.

16.4 Figures

Use the `graphicx` package to include your plots and figures. The use of older packages like `espsfig` is deprecated. Since the `graphicx` package is required by the `atlasdoc` class, it is automatically loaded when using it, and there is no need to explicitly include it in the document preamble.

Always include your graphics file without giving the file extension. For instance, if you want to include the `figure.eps` file, you should use a syntax like this:

```
\includegraphics[width=\textwidth]{figure}
```

This will allow you to compile your document using either \LaTeX or pdf\LaTeX without changing your source file: you can in fact have both `figure.eps` and `figure.pdf` in your working directory, and the proper one will be picked up according to the processing method you choose.

Figures should be in general be made available in either `eps` (or `pdf`) format. `png` format can be used for event displays.

It is a good habit to keep your graphics files in a separate sub-directory (e.g. in `figures/`). In this case you can include them by mentioning it explicitly every time:

```
\includegraphics[width=\textwidth]{figures/figure}
```

or by telling the `graphicx` package where to look for them, by using this command:

```
\graphicspath{{figures/}}
```

If you use a modern version of \TeX Live, it creates PDF files automatically from EPS files (if they do not exist) when you use `pdflatex`. An EPS file with the name `picture1.eps` will lead to a PDF file with the name `picture1-eps-converted-to.pdf`. If you have a lot of figures in many different directories, you may want to clean up the PDF files every so often. You can use the command `make cleanepstopdf` to achieve this. You should adjust the top-level figures directory in the `Makefile` accordingly.

16.5 Subfigures

An example figure can be seen in Figure 1. The standard options to use for the positioning are `htbp`. If you get a couple of lines of text at the top of the page, make sure the figure is separated from the rest of the text with blank lines and/or try dropping the `h` option.




Figure 1: An example ATLAS figure.

A figure with subfigures can be made as shown in the example of Figure 2. In this example the `subfig` package is used. The syntax with the `subcaption` and `subfigure` packages is very similar. The following commands were used to produce Figure 2:

```
\begin{figure}[htbp]
\centering
\subfloat[One subfigure example]{
\includegraphics[width=0.45\textwidth]{AtlasExample}
\label{fig:SubfigureExample1}
}
\subfloat[Another subfigure example]{
\includegraphics[width=0.45\textwidth]{AtlasExample}
\label{fig:SubfigureExample2}
}
\caption{Subfigure example.
\protect\subref{fig:SubfigureExample1} shows the cross-section as a function of  $E_{\text{T,jet}}$  and
\protect\subref{fig:SubfigureExample2} shows exactly the same thing!}
\label{fig:subfigexample}
\end{figure}
```

You refer to the main figure using the usual `\ref` command, e.g. see Figure 2. You can refer to the subfigures using either the syntax `\ref{fig:subfiglabel}` (e.g. see Figure 2(b)) or `\ref{fig:mainfiglabel}\subref{fig:subfiglabel}` (e.g. see Figure 2(a)). Note that if you use the `subfig` package and want to use the labels of the subfigures in the caption, you have to use the syntax `\protect\subref{fig:SubfigureExample1}`. The packages `subfigure` and `subcaption` do not need `protect`, but it does not do any harm.




Figure 2: Subfigure example. (a) shows the cross-section as a function of $E_{T,jet}$ and (b) shows exactly the same thing!

16.6 Positions of figures and tables

In an ATLAS paper, all figures and tables should be printed before the conclusions. You can achieve this by using the macro `\FloatBarrier` from the `placeins` package.

In general, as mentioned above, you should separate the figure and table environments from the text by blank lines. This helps the line numbers. The standard options to use for the placement are `[htbp]`.

16.7 p_T or E_T – that is the question

Bold math should be automatically invoked in titles. This short section tests whether that works properly. It is of course good if things like p_T and E_T are automatically in bold face in a header and normal font in the text (and table of contents).

With the current setup, this works OK. However, if you just use the option `koma`, which then typesets titles using a sans serif font, the p and E are typeset with a serif font and T is typeset with a sans serif font, which is probably not what one wants! Work is still ongoing to find the optimal set of options – search for `detect` in the `siunitx` manual, to see the complete set of possibilities. This is not a problem for the ATLAS preprint style as it uses a serif font for the section titles.

17 Remarks on units and symbols

As discussed in the ‘General guidelines for ATLAS papers’ [10], it is highly recommended to use a units package to format your units properly. The package `siunitx` works very well and is the package of choice. Alternatives include `units` and `hepunits`, which is based on `SIunits`.

The basic command to use in `siunitx` is `\SI{20}{\GeV}` to get 20 GeV. There are also several other useful commands for specifying ranges: `\numrange` for a range of numbers and `SIRange` for a range of numbers with a unit. Options exist for specifying how they are formatted. The options can be set for an individual command or for the whole document. For example, in this document I have specified the options:

```
\sisetup{separate-uncertainty, range-units=single, list-units=single} and  
\sisetup{group-digits=integer, group-minimum-digits=4, detect-all}.
```

In addition several extra units are defined:

- `\micron` for μm ;
- `\mrad` for mrad;
- `\nb` for nb;
- `\pb` for pb;
- `\fb` for fb.

Use the syntax `\SI{20.3}{\per\fb}` to get 20.3 fb^{-1} .

Some things to note about using `siunitx`:

- It tries to isolate itself from other packages. If you just want to write GeV in your text, then you must write `\si{\GeV}`.
- It also contains two new column specifiers for tables “S” and “s”, which are extremely useful for formatting tables properly.

The option names are somewhat different for \TeX Live 2009, as this contained `siunitx` Version 1. You can use the older options by including `atlaspackage` with the option `texlive=2009`. You also have to turn off the inclusion of `atlasunits.sty` by including the option `units=false` with the `atlasphysics` package.

A Makefile

This section documents what the Makefile does when it creates a new document or compiles one.

When a new paper draft is created using the command
`make newspaper BASENAME=GROUP-YYYY-XX-PAPER`
the following files are created in the main directory. If a template filename is given in the table it is taken from the `template` directory, otherwise empty files are created.

template	main
<code>atlas-paper.tex</code>	<code>GROUP-YYYY-XX-PAPER.tex</code>
<code>atlas-paper-metadata.tex</code>	<code>GROUP-YYYY-XX-PAPER-metadata.tex</code>
<code>atlas-auxmat.tex</code>	<code>GROUP-YYYY-XX-PAPER-auxmat.tex</code>
<code>atlas-hepdata.tex</code>	<code>GROUP-YYYY-XX-PAPER-hepdata.tex</code>
	<code>GROUP-YYYY-XX-PAPER-defs.sty</code>
	<code>GROUP-YYYY-XX-PAPER.bib</code>

The following string substitutions are made in `GROUP-YYYY-XX-PAPER.tex`:

Old string	New string
<code>atlas-document</code>	<code>GROUP-YYYY-XX-PAPER</code>
<code>texlive=2016</code>	<code>texlive=YYYY</code>

The T_EX Live version is changed to YYYY (if given). Otherwise it is set to 2016.

The same thing is done for an ATLAS supporting note made with the command
`make newnote BASENAME=GROUP-YYYY-XX-INT1`,
except that the main file template is taken from `atlas-note.tex`, the metadata template is taken from `atlas-note-metadata.tex`, and the auxiliary material and HEPData files are not created.

The standard sequence of commands to compile a document is `pdflatex`, `biber`, `pdflatex`, `pdflatex`. You can change the `%.pdf` target if necessary. Better is to use `latexmk` via the target `run_latexmk`. I recommend you set this as the default command.

B Journal templates

This section contains some information on where the L^AT_EX templates for the different journals can be found and how to use them. However, with the advent of the ATLAS preprint style, it should no longer be necessary to format papers in the style used by the journals. This section has therefore been moved to an appendix.

The directory `journal` contains a very basic paper outline with the preamble needed for different journals. So far the `atlaslatex` package has been tested with the classes for Elsevier and APS journals and the style file used for JHEP and JINST. You should turn off the use of `biblatex` if you use a journal template. Add the option `biblatex=false` to `atlaspackage`.

Elsevier Elsevier uses the `elsarticle` class which should be already installed if you have a standard \TeX Live distribution. It can also be found at <http://www.elsevier.com/locate/latex>.

APS APS journals use `REV \TeX` . This is also usually installed. It can also be found at <https://journals.aps.org/revtex>. Note that you have to specify the author after `\begin{document}` with this class. Hence you should comment out the definition in your metadata file, e.g. `mydocument-metadata.tex`. If you want line numbers in a document typeset using `REV \TeX` , it is best to use the class option `linenumbers`. In addition you should include `atlaspackage` with the option `lineno=false`.

JHEP The package can be downloaded from http://jhep.sissa.it/jhep/help/JHEP_TeXclass.jsp. It contains a style file `jheppub.sty` as well as a \BibTeX style file `JHEP.bst`.

C From `atlasnote` to `atlasdoc`

The `atlasdoc` class replaces and supersedes `atlasnote`. The decision was taken to give the class a new name, as it is supposed to be able to be used for (almost) all ATLAS documents. Some small changes in the user setup are necessary to use the new class, style files and templates.

All style files are collected in the `latex` subdirectory. It is assumed that this directory is a direct subdirectory of your main \LaTeX file. If you want to keep the style files in a central place you can either put them in `${HOME}/texmf/tex/latex` or create a link from your main directory to the location of your `latex` directory.

The main changes the user has to make are:

- Change the class name from `atlasnote` to `latex/atlasdoc`;
- Specify the document language as an option: `UKenglish` or `USenglish`;
- Add `\usepackage{latex/atlaspackage}` at the beginning of the document;
- Change `\usepackage{atlasphysics}` to `\usepackage{latex/atlasphysics}`;
- Use the macro `\AtlasTitle` instead of `\title`.

The language specification means that dates etc. are also formatted according to the document language. If you use the package `\csquotes`, quotation symbols are also consistently and properly set when you use `\enquote`.

All the documentation uses `biblatex` and `biber` instead of traditional \BibTeX . The templates provide information on how to make the change in your own document. The default document settings also use `biblatex` and `biber`.

As of `atlaslatex-01-00-00` the same macro names are used in both `atlasdoc` and `atlascover` so that title, journal, version number and abstract only need to be specified once. This means that if you start from an old preamble the following changes should be made:

Old	New
<code>\title</code>	<code>\AtlasTitle</code>
<code>\draftversion</code>	<code>\AtlasVersion</code>
<code>\atlasnote</code>	<code>\AtlasNote</code>
<code>\journal</code>	<code>\AtlasJournal</code>
<code>\abstracttext</code>	<code>\AtlasAbstract</code>

If you use the old macro names `\draftversion`, `\journal`, `\abstracttext`, they will continue to work in the document itself, but not on the cover page.

When you want to circulate a draft with cover pages, you also need to set the macro `\AtlasRefCode`. This replaces `\AtlasCoverNumber` as it is used in several places.

The class and style files have been cleaned up and things that were thought to no longer be necessary have been removed. These pieces have been collected in `obsolete/atlasnote-obsolete.sty` in case they are needed. If something important has got lost, please let me know.

The `subfigure` package has been replaced with `subfig`, as `subfigure` is now deprecated. If you use `subfig`, then you have to use `\subfloat` instead of `\subfigure`. If you want to continue to use `subfigure` include `atlaspackage` with the option `subfigure=true`. You should also comment out the `\usepackage{subfigure}`.

Similarly, if you do not want to include `siunitx` set the option `siunitx=false`.

The option `\skipbeforetitle{<length>}` used to set the distance between the title page header and the note title. Given that stretchable space is now used, such an option is no longer appropriate. It can be given, but will be ignored.

D History

Quite a lot of people have contributed to the ATLAS L^AT_EX templates over time. Marco Delmastro set them up in the first place and added a number of improvements over time. Mike Vetterli implemented several changes to the cover pages, including switching to two pages. Cristina Oropeza, Vasia Mitsou, Chris Hays and Mike Vetterli all made contributions to the preprint cover page.

Sven Menke provided the code so that bold math works in titles correctly. Thorsten Kuhl had the idea of defining `\ATLASLATEXPATH`, which makes things much more flexible.

Juan Pedro Araque has done most of the work setting up the PO-GitLab project. This resulted in a much smoother submission process for papers and an improved handling of auxiliary material.

D.1 Changes in `atlaslatex-05-00-00`

Version 05-00-00 of `atlaslatex` is the first version set up to be fully compatible with the PO-GitLab scheme for papers.

Separate (dummy) files for auxiliary material and HEPData tables are created for new papers. The `make auxmat` command has been renamed to `make newdata`, as the auxiliary material for the webpage is now separated from a separate file for tables etc. for HEPData.

D.2 Changes in atlaslatex-04-00-00

As of Version 04-00-00 of `atlaslatex`, the Makefile for `atlaslatex` has been restructured to reduce duplications and make separate commands for a new paper and a new note. `biber` is now the default backend for `biblatex`, as this allows the use of the ‘related’ field for Errata. Errata are included in the ATLAS bibliography file. Metadata for notes and papers are now separate templates to prepare for them being created directly from Glance. This is the first version that is designed for the Glance/Git integration. As the above changes are quite major, there is a jump in the main version number.

D.3 Changes in atlaslatex-02-00-00

As of Version 02-00-00 of `atlaslatex`, only the KOMA-Script classes are supported. At the same time, the option `BOOK` was introduced, which uses `scrbook` as the base class. This is more suitable for long documents such as a TDR.

Several options, which make maintenance more difficult have been removed: `maketitle`, `nomaketitle`, `koma`. In addition, support for \TeX Live versions older than 2009 has been removed. A version of the class with these options, which should still work with \TeX Live 2007, but without the `BOOK` option is available as `atlasdoc1.cls`. However, the class (`atlasdoc1`) will not be actively maintained or developed any more. If you want to explicitly load the `atlascover` package, you should load `atlascover1` when using `atlasdoc1`.

The options `cernpreprint`, `preprint` and `auxmat` are no longer available in `atlascover`. You should pass these to `atlasdoc` instead, as the title pages are now part of the main class.

D.4 Changes in atlascover-01-00-00

As of `atlascover-01-00-00` the same macro names are used in both `atlasdoc` and `atlascover` so that title, journal and version number only need to be specified once. This means that if you start from an old cover page the following changes have to be made:

Old	New
<code>\AtlasCoverPaperTitle</code>	<code>\AtlasTitle</code>
<code>\AtlasCoverNumber</code>	<code>\AtlasRefCode</code>
<code>\AtlasCoverPaperVersion</code>	<code>\AtlasVersion</code>
<code>\AtlasCoverJournal</code>	<code>\AtlasJournal</code>
<code>\AtlasCoverAbstract</code>	<code>\AtlasAbstract</code>

Note that `atlaspreprint` is integrated into `atlascover` and not maintained as a separate style file. To get the CERN preprint front page, you have to include the option `cernpreprint` when you invoke `atlasdoc`. If you start from an old preprint front page the following changes have to be made:

Old	New
<code>\PreprintCoverPaperTitle</code>	<code>\AtlasTitle</code>
<code>\PreprintJournalName</code>	<code>\AtlasJournal</code>
<code>\PreprintCoverAbstract</code>	<code>\AtlasAbstract</code>

The following changes are needed for the macros:

- The macro `\AtlasCoverEdBoardMember` only has one argument, as a generic email list now exists for every EdBoard.

References

- [1] *Publication L^AT_EX Templates*,
URL: <https://twiki.cern.ch/twiki/bin/view/AtlasProtected/PubComLaTeX>.
- [2] *ATLAS L^AT_EX style files and templates in Git*,
URL: <https://gitlab.cern.ch/atlas-physics-office/atlaslatex>.
- [3] *ATLAS L^AT_EX Documents, Git and Continuous Integration*,
URL: <https://twiki.cern.ch/twiki/bin/view/AtlasProtected/AtlasLaTeXGit>.
- [4] I. Brock, *Symbols defined in atlasphysics.sty*, URL: https://twiki.cern.ch/twiki/pub/AtlasProtected/PubComLaTeX/atlas_physics.pdf.
- [5] *PubCom L^AT_EX FAQ*,
URL: <https://twiki.cern.ch/twiki/bin/view/AtlasProtected/PubComLaTeXFAQ>.
- [6] *The International System of Units (SI)*,
URL: <http://www.ctan.org/tex-archive/macros/latex/contrib/siunitx>.
- [7] *siunitx – A comprehensive (SI) units package*,
URL: <http://www.bipm.org/en/measurement-units>.
- [8] *Should there be a space before a percent sign?*,
URL: <https://english.stackexchange.com/questions/3281/should-there-be-a-space-before-a-percent-sign>.
- [9] *ATLAS Physics and Committees Office*,
URL: <https://twiki.cern.ch/twiki/bin/view/AtlasProtected/PhysicsOffice>.
- [10] ATLAS Publications Committee, *General guidelines for ATLAS papers*, URL: https://twiki.cern.ch/twiki/pub/AtlasProtected/PubComLaTeX/atlas_paper.pdf.