



ATLAS NOTE

22nd March 2016



Symbols defined in `atlasphysics.sty`

Ian C. Brock

University of Bonn

Abstract

This note lists the symbols defined in `atlasphysics.sty`. These provide examples of how to define your own symbols, as well as many symbols that are often used in ATLAS documents.

This document was generated using version 01-07-10 of the ATLAS \LaTeX package. The \TeX Live version is set to 2013. It uses the option `atlasstyle`, which implies that the standard ATLAS preprint style is used.

Contents

1 atlasphysics.sty style file	2
2 atlasparticle.sty	4
3 atlasjournal.sty	5
4 atlasmisc.sty	6
5 atlasxref.sty	7
6 atlasbsm.sty	8
7 atlasheavyion.sty	9
8 atlasmath.sty	10
9 atlasother.sty	10
10 atlasprocess.sty	11
11 atlasunit.sty	11
12 Old macros	13

1 atlasphysics.sty style file

The `atlasphysics.sty` style file implements a series of useful shortcuts to typeset a physics paper, such as particle symbols.

Options are parsed with the `kvoptions` package, which is included by default. The style file can be included in the preamble of your paper with the usual syntax:

```
\usepackage{\ATLASLATEXPATH atlasphysics}
```

As of version 01-00-00 the file is actually split into smaller files, which can be included or not using options. The following options are available, where the default setting is given in parentheses

BSM (false) BSM and SUSY particles;

hion (false) Useful macros for heavy ion physics;

journal (true) Journal abbreviations and a few other definitions for references;

math (false) A few extra maths definitions;

misc (true) Miscellaneous definitions that are often used;

other (false) Definitions that used to be in `atlasphysics.sty`, but are probably too specialised to be needed by most people;

particle (true) Standard Model particles and some combinations;

process (false) Some example processes. These are not included by default as the current choice is rather arbitrary and certainly not complete;

unit (true) Units that used to be defined – not needed if you use `siunitx` or `hepunits`;

xref (true) Useful abbreviations for cross-references;

texlive=YYYY (2013) set if you use an older version of T_EX Live like 2009;

texmf use the syntax `\usepackage{package}` instead of `\usepackage{\ATLASLATEXPATH package}` to include packages. This is needed if you install `atlaslatex` centrally, rather than in a `latex` subdirectory.

Note that `BSM` and `BSM=true` are equivalent. Use the syntax `option=false` to turn off an option.

If the option `texmf` is included, the subfiles are included using the command: `\RequirePackage{atlasparticle}` etc. instead of `\RequirePackage{\ATLASLATEXPATH atlasparticle}`. This is useful if you install the ATLAS L^AT_EX package in a central directory such as `#{HOME}/texmf/tex/latex`.

All definitions are done in a consistent way using `\newcommand*`. All definitions use `\ensuremath` where appropriate and are terminated with `\xspace`, so you can simply write `\ttbar production` instead of `\ttbar\ production` or `\ttbar{} production` to get ‘ $t\bar{t}$ production’.

See Section 12 for details on changes that were introduced when going from version 00-04-05 of `atlasnote` to version 01-00-00 of `atlaslatex`. Let me know if you spot some other changes that are not documented here!

The following sections list the macros defined in the various files.

2 atlasparticle.sty

Turn on including these definitions with the option
particle=true and off with the option particle=false.

<code>\tbar</code>	\bar{t}	<code>\Wmp</code>	W^\mp
<code>\ttbar</code>	$t\bar{t}$	<code>\pi</code>	π
<code>\bbbar</code>	$b\bar{b}$	<code>\pizero</code>	π^0
<code>\cbar</code>	\bar{c}	<code>\piplus</code>	π^+
<code>\ccbar</code>	$c\bar{c}$	<code>\piminus</code>	π^-
<code>\sbar</code>	\bar{s}	<code>\pipm</code>	π^\pm
<code>\ssbar</code>	$s\bar{s}$	<code>\pimp</code>	π^\mp
<code>\ubar</code>	\bar{u}	<code>\eta</code>	η
<code>\uubar</code>	$u\bar{u}$	<code>\etaprime</code>	η'
<code>\dbar</code>	\bar{d}	<code>\Kzero</code>	K^0
<code>\ddbar</code>	$d\bar{d}$	<code>\Kzerobar</code>	\bar{K}^0
<code>\fbar</code>	\bar{f}	<code>\kaon</code>	K
<code>\ffbar</code>	$f\bar{f}$	<code>\Kplus</code>	K^+
<code>\qbar</code>	\bar{q}	<code>\Kminus</code>	K^-
<code>\qqbar</code>	$q\bar{q}$	<code>\KzeroL</code>	K_L^0
<code>\nbar</code>	$\bar{\nu}$	<code>\Kzerol</code>	K_L^0
<code>\nnbar</code>	$\nu\bar{\nu}$	<code>\Klong</code>	K_L^0
<code>\pbar</code>	\bar{p}	<code>\KzeroS</code>	K_S^0
<code>\ppbar</code>	$p\bar{p}$	<code>\Kzeros</code>	K_S^0
<code>\ee</code>	e^+e^-	<code>\Kshort</code>	K_S^0
<code>\epm</code>	e^\pm	<code>\Kstar</code>	K^*
<code>\epem</code>	e^+e^-	<code>\psi</code>	ψ
<code>\mumu</code>	$\mu^+\mu^-$	<code>\jpsi</code>	J/ψ
<code>\tautau</code>	$\tau^+\tau^-$	<code>\Jpsi</code>	J/ψ
<code>\leplep</code>	$\ell^+\ell^-$	<code>\psip</code>	ψ'
<code>\ellell</code>	$\ell^+\ell^-$	<code>\Usp</code>	γ'
<code>\lnu</code>	$\ell\nu$	<code>\Upspp</code>	γ''
<code>\Zzero</code>	Z	<code>\Upsppp</code>	γ'''
<code>\Zboson</code>	Z	<code>\Upspppp</code>	γ''''
<code>\Wplus</code>	W^+	<code>\Upsppppp</code>	γ'''''
<code>\Wminus</code>	W^-	<code>\UoneS</code>	$\gamma(1S)$
<code>\Wboson</code>	W	<code>\Dstar</code>	D^*
<code>\Wpm</code>	W^\pm	<code>\Dsstar</code>	D^{**}
		<code>\Bd</code>	B_d^0
		<code>\Bs</code>	B_s^0
		<code>\Bu</code>	B_u
		<code>\Bc</code>	B_c
		<code>\Lb</code>	Λ_b
		<code>\Bstar</code>	B^*

<code>\chic</code>	χ_c
<code>\BoBo</code>	$B^0-\bar{B}^0$
<code>\BodBod</code>	$B_d^0-\bar{B}_d^0$
<code>\BosBos</code>	$B_s^0-\bar{B}_s^0$
<code>\chib</code>	χ_b

A generic macro `\Ups[1]` is available. It is defined such that `\Ups{3}` produces $\Upsilon(3S)$.

3 atlasjournal.sty

Turn on including these definitions with the option `journal=true` and off with the option `journal=false`.

<code>\AcPA</code>	Acta Phys. Austriaca
<code>\AREvNS</code>	Ann. Rev. Nucl. Sci.
<code>\CPC</code>	Comp. Phys. Comm.
<code>\FortP</code>	Fortschr. Phys.
<code>\IJMP</code>	Int. J. Mod. Phys.
<code>\JETP</code>	Sov. Phys. JETP
<code>\JETPL</code>	JETP Lett.
<code>\JaFi</code>	Jad. Fiz.
<code>\JMP</code>	J. Math. Phys.
<code>\MPL</code>	Mod. Phys. Lett.
<code>\NCim</code>	Nuovo Cimento
<code>\NIM</code>	Nucl. Instrum. Meth.
<code>\NP</code>	Nucl. Phys.
<code>\NPB</code>	Nucl. Phys. B
<code>\PL</code>	Phys. Lett.
<code>\PLB</code>	Phys. Lett. B
<code>\PR</code>	Phys. Rev.
<code>\PRC</code>	Phys. Rev. C
<code>\PRD</code>	Phys. Rev. D
<code>\PRL</code>	Phys. Rev. Lett.
<code>\PRep</code>	Phys. Rep.
<code>\RMP</code>	Rev. Mod. Phys.
<code>\ZfP</code>	Z. Phys.
<code>\EPJ</code>	Eur. Phys. J.
<code>\EPJC</code>	Eur. Phys. J. C
<code>\collab</code>	Collaboration

4 atlasmisc.sty

Turn on including these definitions with the option misc=true and off with the option misc=false.

<code>\pT</code>	p_T
<code>\pt</code>	p_T
<code>\ET</code>	E_T
<code>\eT</code>	E_T
<code>\et</code>	E_T
<code>\HT</code>	H_T
<code>\pTsqr</code>	p_T^2
<code>\MET</code>	E_T^{miss}
<code>\met</code>	E_T^{miss}
<code>\sumET</code>	$\sum E_T$
<code>\EjetRec</code>	E_{rec}
<code>\PjetRec</code>	p_{rec}
<code>\EjetTru</code>	E_{truth}
<code>\PjetTru</code>	p_{truth}
<code>\EjetDM</code>	E_{DM}
<code>\Rcone</code>	R_{cone}
<code>\abseta</code>	$ \eta $
<code>\Ecm</code>	E_{cm}
<code>\rts</code>	\sqrt{s}
<code>\sqs</code>	\sqrt{s}
<code>\Nevt</code>	N_{evt}
<code>\zvtx</code>	z_{vtx}
<code>\dzero</code>	d_0
<code>\zzsth</code>	$z_0 \sin(\theta)$
<code>\mh</code>	m_h
<code>\mW</code>	m_W
<code>\mZ</code>	m_Z
<code>\mH</code>	m_H
<code>\ALPGEN</code>	ALPGEN
<code>\GEANT</code>	GEANT
<code>\Herwigpp</code>	Herwig++
<code>\HERWIGpp</code>	Herwig++
<code>\Herwig</code>	Herwig

<code>\HERWIG</code>	HERWIG
<code>\JIMMY</code>	JIMMY
<code>\METOP</code>	METOP
<code>\POWHEG</code>	POWHEG
<code>\PROTOS</code>	PROTOS
<code>\PYTHIA</code>	PYTHIA
<code>\SHERPA</code>	SHERPA
<code>\ACERMC</code>	ACERMC
<code>\MCatNLO</code>	MC@NLO
<code>\AMCatNLO</code>	aMC@NLO
<code>\MADSPIN</code>	MADSPIN
<code>\MADGRAPH</code>	MADGRAPH
<code>\MGMCatNLO</code>	MADGRAPH5_aMC@NLO
<code>\MCFM</code>	MCFM
<code>\ra</code>	\rightarrow
<code>\la</code>	\leftarrow
<code>\rarrow</code>	\rightarrow
<code>\larrow</code>	\leftarrow
<code>\lapprox</code>	\lesssim
<code>\rapprox</code>	\gtrsim
<code>\gam</code>	γ
<code>\stat</code>	(stat.)
<code>\syst</code>	(syst.)
<code>\alphas</code>	α_s
<code>\NF</code>	N_F
<code>\NC</code>	N_C
<code>\CF</code>	C_F
<code>\CA</code>	C_A
<code>\TF</code>	T_F
<code>\Lms</code>	$\Lambda_{\overline{\text{MS}}}$
<code>\Lmsfive</code>	$\Lambda_{\overline{\text{MS}}}^{(5)}$
<code>\KT</code>	k_{\perp}
<code>\Vcb</code>	$ V_{cb} $
<code>\Vub</code>	$ V_{ub} $
<code>\Vtd</code>	$ V_{td} $
<code>\Vts</code>	$ V_{ts} $
<code>\Vtb</code>	$ V_{tb} $
<code>\Vcs</code>	$ V_{cs} $

$\backslash V_{ud}$ $|V_{ud}|$
 $\backslash V_{us}$ $|V_{us}|$
 $\backslash V_{cd}$ $|V_{cd}|$

A length $\backslash figwidth$ is defined that is 2 cm smaller than $\backslash textwidth$.

A generic macro $\backslash twomass$ is defined, so that for example $\backslash twomass\{\mu\}\{\mu\}$ produces $m_{\mu\mu}$ and $\backslash twomass\{\mu\}\{e\}$ produces $m_{\mu e}$.

A macro $\backslash dk$ is also defined which makes it easier to write down decay chains. For example

```

 $\backslash[\backslash eqalign{a \to & b+c\backslash$ 
 $\quad \& \backslash dk \& e+f \backslash$ 
 $\quad \&\& \backslash dk g+h\}$ 
 $\backslash]$ 

```

produces

$$\begin{array}{lcl}
 a \rightarrow b + c & & \\
 | \longrightarrow & e + f & \\
 & | \longrightarrow & g + h
 \end{array}$$

Note that $\backslash eqalign$ is also redefined in this package so that $\backslash dk$ works.

The following macro names have been changed:
 $\backslash ptsq \rightarrow \backslash pTsq$.

5 atlasxref.sty

Turn on including these definitions with the option $xref=true$ and off with the option $xref=false$.

The following macros with arguments are also defined:

$\backslash App\{1\}$	App. 1
$\backslash Eqn\{1\}$	Eq. 1
$\backslash Fig\{1\}$	Fig. 1
$\backslash Ref\{1\}$	Ref. 1
$\backslash Sect\{1\}$	Sect. 1
$\backslash Tab\{1\}$	Table 1
$\backslash Apps\{1\}\{4\}$	Apps. 1 and 4
$\backslash Eqns\{1\}\{4\}$	Eqs. 1 and 4
$\backslash Figs\{1\}\{4\}$	Figs. 1 and 4
$\backslash Refs\{1\}\{4\}$	Refs. 1 and 4
$\backslash Sects\{1\}\{4\}$	Sects. 1 and 4
$\backslash Tabs\{1\}\{4\}$	Tables 1 and 4
$\backslash Apprange\{1\}\{4\}$	Apps. 1–4
$\backslash Eqnrange\{1\}\{4\}$	Eqs. 1–4
$\backslash Figrange\{1\}\{4\}$	Figs. 1–4
$\backslash Refrange\{1\}\{4\}$	Refs. 1–4
$\backslash Sectrange\{1\}\{4\}$	Sects. 1–4
$\backslash Tabrange\{1\}\{4\}$	Tables 1–4

The idea is that you can adapt these definitions according to your own preferences (or those of a journal).

6 atlasbsm.sty

Turn on including these definitions with the option BSM and off with the option BSM=false.

The macro `\susy` simply puts a tilde ($\tilde{}$) over its argument, e.g. `\susy{q}` produces \tilde{q} .

For \tilde{q} , \tilde{t} , \tilde{b} , $\tilde{\ell}$, \tilde{e} , $\tilde{\mu}$ and $\tilde{\tau}$, L and R states are defined; for stop, sbottom and stau also the light (1) and heavy (2) states. There are four neutralinos and two charginos defined, the index number unfortunately needs to be written out completely. For the charginos the last letter(s) indicate(s) the charge: ‘p’ for +, ‘m’ for −, and ‘pm’ for \pm .

<code>\Azero</code>	A^0
<code>\hzero</code>	h^0
<code>\Hzero</code>	H^0
<code>\Hboson</code>	H
<code>\Hplus</code>	H^+
<code>\Hminus</code>	H^-
<code>\Hpm</code>	H^\pm
<code>\Hmp</code>	H^\mp
<code>\ggino</code>	$\tilde{\chi}$
<code>\chinop</code>	$\tilde{\chi}^+$
<code>\chinom</code>	$\tilde{\chi}^-$
<code>\chinopm</code>	$\tilde{\chi}^\pm$
<code>\chinomp</code>	$\tilde{\chi}^\mp$
<code>\chinoonep</code>	$\tilde{\chi}_1^+$
<code>\chinoonem</code>	$\tilde{\chi}_1^-$
<code>\chinoonepm</code>	$\tilde{\chi}_1^\pm$
<code>\chinotwop</code>	$\tilde{\chi}_2^+$
<code>\chinotwom</code>	$\tilde{\chi}_2^-$
<code>\chinotwopm</code>	$\tilde{\chi}_2^\pm$
<code>\nino</code>	$\tilde{\chi}^0$
<code>\ninoone</code>	$\tilde{\chi}_1^0$
<code>\ninotwo</code>	$\tilde{\chi}_2^0$
<code>\ninothree</code>	$\tilde{\chi}_3^0$
<code>\ninofour</code>	$\tilde{\chi}_4^0$
<code>\gravino</code>	\tilde{G}

<code>\Zprime</code>	Z'
<code>\Zstar</code>	Z^*
<code>\squark</code>	\tilde{q}
<code>\squarkL</code>	\tilde{q}_L
<code>\squarkR</code>	\tilde{q}_R
<code>\gluino</code>	\tilde{g}
<code>\stop</code>	\tilde{t}
<code>\stopone</code>	\tilde{t}_1
<code>\stoptwo</code>	\tilde{t}_2
<code>\stopL</code>	\tilde{t}_L
<code>\stopR</code>	\tilde{t}_R
<code>\sbottom</code>	\tilde{b}
<code>\sbottomone</code>	\tilde{b}_1
<code>\sbottomtwo</code>	\tilde{b}_2
<code>\sbottomL</code>	\tilde{b}_L
<code>\sbottomR</code>	\tilde{b}_R
<code>\slepton</code>	$\tilde{\ell}$
<code>\sleptonL</code>	$\tilde{\ell}_L$
<code>\sleptonR</code>	$\tilde{\ell}_R$
<code>\sel</code>	\tilde{e}
<code>\sell</code>	\tilde{e}_L
<code>\selR</code>	\tilde{e}_R
<code>\smu</code>	$\tilde{\mu}$
<code>\smuL</code>	$\tilde{\mu}_L$
<code>\smuR</code>	$\tilde{\mu}_R$
<code>\stau</code>	$\tilde{\tau}$
<code>\stauL</code>	$\tilde{\tau}_L$
<code>\stauR</code>	$\tilde{\tau}_R$
<code>\stauone</code>	$\tilde{\tau}_1$
<code>\stautwo</code>	$\tilde{\tau}_2$
<code>\snu</code>	$\tilde{\nu}$

7 atlasheavyion.sty

Turn on including these definitions with the option `hion=true` and off with the option `hion=false`. The heavy ion definitions use the package `mhchem` to help with the formatting of chemical elements. This package is included by `atlasheavyion.sty`.

<code>\NucNuc</code>	$A+A$
<code>\nn</code>	nn
<code>\pp</code>	pp
<code>\pn</code>	pn
<code>\np</code>	np
<code>\PbPb</code>	$Pb+Pb$
<code>\AuAu</code>	$Au+Au$
<code>\CuCu</code>	$Cu+Cu$
<code>\pNuc</code>	$p+A$
<code>\pdA</code>	$p/d+A$
<code>\dAu</code>	$d+Au$
<code>\pPb</code>	$p+Pb$
<code>\Npart</code>	N_{part}
<code>\avgNpart</code>	$\langle N_{\text{part}} \rangle$
<code>\Ncoll</code>	N_{coll}
<code>\avgNcoll</code>	$\langle N_{\text{coll}} \rangle$
<code>\TA</code>	T_A
<code>\avgTA</code>	$\langle T_A \rangle$
<code>\TPb</code>	T_{Pb}
<code>\avgTPb</code>	$\langle T_{\text{Pb}} \rangle$
<code>\TAA</code>	T_{AA}
<code>\avgTAA</code>	$\langle T_{AA} \rangle$
<code>\TAB</code>	T_{AB}
<code>\avgTAB</code>	$\langle T_{AB} \rangle$
<code>\TpPb</code>	$T_{p\text{Pb}}$
<code>\avgTpPb</code>	$\langle T_{p\text{Pb}} \rangle$
<code>\G1</code>	Glauber
<code>\GG</code>	Glauber-Gribov
<code>\sqn</code>	$\sqrt{s_{\text{NN}}}$
<code>\lns</code>	$\ln(\sqrt{s})$
<code>\sumETPb</code>	$\Sigma E_{\text{T}}^{\text{Pb}}$

<code>\sumETp</code>	ΣE_{T}^p
<code>\sumETA</code>	ΣE_{T}^A
<code>\RAA</code>	R_{AA}
<code>\RCP</code>	R_{CP}
<code>\RpA</code>	R_{pA}
<code>\RpPb</code>	$R_{p\text{Pb}}$
<code>\dif</code>	d
<code>\dNchdeta</code>	$dN_{\text{ch}}/d\eta$
<code>\dNevtdET</code>	$dN_{\text{evt}}/dE_{\text{T}}$
<code>\ystar</code>	y^*
<code>\ycms</code>	y_{CM}
<code>\ygappb</code>	$\Delta\eta_{\text{gap}}^{\text{Pb}}$
<code>\ygapp</code>	$\Delta\eta_{\text{gap}}^p$
<code>\fgap</code>	f_{gap}

8 atlasmath.sty

Turn on including these definitions with the option `math=true` and off with the option `math=false`.

`\boxsq` \Box^2
`\grad` ∇

The macro `\spinor` is also defined. `\spinor{u}`

produces $\begin{pmatrix} u_1 \\ u_2 \\ u_3 \\ u_4 \end{pmatrix}$.

9 atlasother.sty

Turn on including these definitions with the option `other` and off with the option `other=false`.

`\etpt` $1/p_T - 1/E_T$
`\etptsig` $(1/p_T - 1/E_T)/(\sigma(1/p_T))$
`\begL` $10^{31} \text{ cm}^{-2} \text{ s}^{-1}$
`\lowL` $10^{33} \text{ cm}^{-2} \text{ s}^{-1}$
`\highL` $10^{34} \text{ cm}^{-2} \text{ s}^{-1}$
`\Epsb` ϵ_b
`\Epsc` ϵ_c
`\Mtau` m_τ
`\swsq` $\sin^2 \theta_W$
`\swel` $\sin^2 \theta_{\text{eff}}^{\text{lept}}$
`\swsqb` $\sin^2 \theta_W$
`\swsqon` $\sin^2 \theta_W \equiv 1 - m_W^2/m_Z^2$
`\gv` g_V
`\ga` g_A
`\gvbar` \bar{g}_V
`\gabar` \bar{g}_A
`\Zzv` Z^*
`\Abb` $A_{b\bar{b}}$
`\Acc` $A_{c\bar{c}}$
`\Aqq` $A_{q\bar{q}}$
`\Afb` A_{fb}
`\GZ` Γ_Z
`\GW` Γ_W
`\GH` Γ_H
`\GamHad` Γ_{had}
`\Gbb` $\Gamma_{b\bar{b}}$
`\Rbb` $R_{b\bar{b}}$
`\Gcc` $\Gamma_{c\bar{c}}$
`\Gvis` Γ_{vis}
`\Ginv` Γ_{inv}

10 atlasprocess.sty

Turn on including these definitions with the option `process` and off with the option `process=false`.

<code>\btol</code>	$b \rightarrow \ell$
<code>\ctol</code>	$c \rightarrow \ell$
<code>\btoctol</code>	$b \rightarrow c \rightarrow \ell$
<code>\Jee</code>	$J/\psi \rightarrow e^+e^-$
<code>\Jmm</code>	$J/\psi \rightarrow \mu^+\mu^-$
<code>\Jmumu</code>	$J/\psi \rightarrow \mu^+\mu^-$
<code>\Wjj</code>	$W \rightarrow jj$
<code>\tjjb</code>	$t \rightarrow jjb$
<code>\Hbb</code>	$H \rightarrow b\bar{b}$
<code>\Hgg</code>	$H \rightarrow \gamma\gamma$
<code>\Hl1l1l</code>	$H \rightarrow ZZ^{(*)} \rightarrow \mu\mu\mu\mu$
<code>\Hmmmm</code>	$H \rightarrow \mu\mu\mu\mu$
<code>\Heeee</code>	$H \rightarrow eeee$
<code>\Zmm</code>	$Z \rightarrow \mu\mu$
<code>\Zee</code>	$Z \rightarrow ee$
<code>\Zll</code>	$Z \rightarrow \ell\ell$
<code>\Wln</code>	$W \rightarrow \ell\nu$
<code>\Wen</code>	$W \rightarrow e\nu$
<code>\Wmn</code>	$W \rightarrow \mu\nu$
<code>\Amm</code>	$A \rightarrow \mu\mu$
<code>\Ztautau</code>	$Z \rightarrow \tau\tau$
<code>\Wtaunu</code>	$W \rightarrow \tau\nu$
<code>\Atautau</code>	$A \rightarrow \tau\tau$
<code>\Htautau</code>	$H \rightarrow \tau\tau$
<code>\Brjl</code>	$\text{Br}(J/\psi \rightarrow \ell^+\ell^-)$

11 atlasunit.sty

Turn on including these definitions with the option `unit` and off with the option `unit=false`.

<code>\TeV</code>	TeV
<code>\GeV</code>	GeV
<code>\MeV</code>	MeV
<code>\keV</code>	keV
<code>\eV</code>	eV
<code>\TeVc</code>	TeV/c
<code>\GeVc</code>	GeV/c
<code>\MeVc</code>	MeV/c
<code>\keVc</code>	keV/c
<code>\eVc</code>	eV/c
<code>\TeVcc</code>	TeV/c ²
<code>\GeVcc</code>	GeV/c ²
<code>\MeVcc</code>	MeV/c ²
<code>\keVcc</code>	keV/c ²
<code>\eVcc</code>	eV/c ²
<code>\ifb</code>	fb ⁻¹
<code>\ipb</code>	pb ⁻¹
<code>\inb</code>	nb ⁻¹
<code>\degr</code>	°

Lower case versions of the units also exist, e.g. `\tev`, `\gev`, `\mev`, `\kev`, and `\ev`.

As mentioned above, it is highly recommended to use a units package instead of these definitions. `siunitx` is the preferred package; a good alternative is `hepunits`. If either of these packages are used `atlasunit.sty` is not needed.

Most units that are needed in ATLAS documents are already defined by `siunitx` or are defined in `atlaspackage.sty`. A selection of them is given below. In order to use them in your document the unit should be included in `\si` or `\SI`:

<code>\si{\TeV}</code>	TeV
<code>\si{\GeV}</code>	GeV
<code>\si{\MeV}</code>	MeV
<code>\si{\keV}</code>	keV
<code>\si{\eV}</code>	eV
<code>\si{\TeVc}</code>	TeV/c
<code>\si{\GeVc}</code>	GeV/c
<code>\si{\MeVc}</code>	MeV/c
<code>\si{\keVc}</code>	keV/c

<code>\si{\eVc}</code>	eV/c
<code>\si{\TeVcc}</code>	TeV/c ²
<code>\si{\GeVcc}</code>	GeV/c ²
<code>\si{\MeVcc}</code>	MeV/c ²
<code>\si{\keVcc}</code>	keV/c ²
<code>\si{\eVcc}</code>	eV/c ²
<code>\si{\nb}</code>	nb
<code>\si{\pb}</code>	pb
<code>\si{\fb}</code>	fb
<code>\si{\per\fb}</code>	fb ⁻¹
<code>\si{\per\pb}</code>	pb ⁻¹
<code>\si{\per\nb}</code>	nb ⁻¹
<code>\si{\ifb}</code>	fb ⁻¹
<code>\si{\ipb}</code>	pb ⁻¹
<code>\si{\inb}</code>	nb ⁻¹
<code>\si{\Hz}</code>	Hz
<code>\si{\kHz}</code>	kHz
<code>\si{\MHz}</code>	MHz
<code>\si{\GHz}</code>	GHz
<code>\si{\degr}</code>	°
<code>\si{\m}</code>	m
<code>\si{\cm}</code>	cm
<code>\si{\mm}</code>	mm
<code>\si{\um}</code>	μm
<code>\si{\micron}</code>	μm

12 Old macros

With the introduction of `atlaslatex` several macro names have been changed to make them more consistent. A few have been removed. The changes include:

- Kaons now have a capital “K” in the macro name, e.g. `\Kplus` for K^+ ;
- `\Ztau`, `\Wtau`, `\Htau` `\Atau` have been replaced by `\Ztautau`, `\Wtautau`, `\Htautau` `\Atautau`;
- `\Ups` replaces `\ups`; the use of `\ups` to produce Υ in text mode has been removed;
- `\cm` has been removed, as it was the only length unit defined for text and math mode;
- `\mass` has been removed, as `\twomass` can do the same thing and the name is more intuitive;
- `\mA` has been removed as it conflicts with `siunitx` Version 1, which uses the name for milliamp.
- `\mathcal` rather than `\mathscr` is recommended for luminosity and aplanarity.

Quite a few macros are more related to Z physics than they are to LHC physics and have been moved to the `atlasother.sty` file, which is not included by default. There are also macros for various decay processes, `atlasprocess.sty` which are not included by default, but may be useful for how you can define your favourite process.

It used to be the case that you had to use `\MET{}` rather than just `\MET` to get the spacing right, as somehow `xspace` did not do a good job for E_T^{miss} . However, with the latest version of the packages both forms work fine. You can compare E_T^{miss} and E_T^{miss} and see that the spacing is correct in both cases.