

Question 1 (a)


A	В	Output
0	0	0
0	1	0
1	0	1
1	1	1




The perceptron



A	В	Output
0	0	0
0	1	1
1	0	1
1	1	0




It is impossible to separate them and thus, we need to use a hidden layer




1		١
1	റ	
•	·	ı

A	В	Output
0	0	1
0	1	0
1	0	1
1	1	0

В




The perceptron is



Question 2: If you give me something reasonable such as the procedure of calculation or a program, you receive the full credit

Question 3:

(a)



(b) Forward pass:

Input to H1: 0.4 * 0.3 + 0.4 * (-0.6) - 0.2 = -0.32

Output of H1: Sigmod(-0.32) = 0.4207

Input to H2: -0.17 Output of H2: 0.4576

Input to H3: -0.26 Output of H3: 0.4354

Input of C: 0.0096 Output of C: 0.5024

Back-propagation:

 $del_C = 0.5024 * (1-0.5024)*(1-0.5024) = 0.1244$

 $W_{H1c} = 0.4 + (0.2 * 0.4207 * 0.1244) = 0.4105$

 $W_{H2c} = -0.1 + (0.2 * 0.4576 * 0.1244) = -0.0886$

 $W_{H3c} = 0.2 + (0.2 * 0.4354 * 0.1244) = 0.2108$

 $W_{bias} = 0.2 + (0.2 * -1 * 0.1244) = 0.1751$

 $del_H_1 = 0.4207 * (1 - 0.4207)*(0.4 * 0.1244) = 0.0121$

 $W_{AH1} = 0.4 + (0.2 * 0.3 * 0.0121) = 0.4007$

$$W_{BH1} = 0.4 + (0.2 * -0.6 * 0.0121) = 0.3985$$

 $W_{BiasH1} = 0.2 + (0.2 * -1 * 0.0121) = 0.1976$

$$del_{H_2} = 0.4576 * (1 - 0.4576)*(-0.1 * 0.1244) = -0.0031$$

 $W_{AH2} = -0.1 + (-0.2 * 0.3 * 0.0031) = -0.1002$

 $W_{BH2} = -0.1 + (-0.2 * -0.6 * 0.0031) = -0.0996$


 $W_{BiasH2} = 0.2 + (0.2 * 1 * 0.0031) = 0.2006$

$$del_H_3 = 0.4354 * (1 - 0.4354)*(0.2 * 0.1244) = 0.0061$$

 $W_{AH3} = 0.2 + (0.2 * 0.3 * 0.0061) = 0.2004$

 $W_{BH3} = 0.2 + (0.2 * -0.6 * 0.0061) = 0.1993$


 $W_{BiasH3} = 0.2 + (0.2 * -1 * 0.0061) = 0.1988$



Question 4

The mapping functions are

$$\begin{cases} X_1 = x \\ X_2 = (x - 1.5)^2 \end{cases}$$



The equation for the hyperplane is $X_2 = 1.25$

Question 5

1. Discussion: 15 Points

2. Reasonable: figure of SSE and accuracy 15 Points

3. Working code: 10 Points