A Catalogue of Observability and Evaluation Metrics for AI Agents

1st [TODO: Given Name Surname]
[TODO: dept. name of organization]
[TODO: name of organization]
[TODO: City, Country]
[TODO: email address or ORCID]

Abstract—[TODO: Rewrite once the structure is settled.] AI agents run many model calls and tool calls per task, and a growing number of tools claim to observe and evaluate them. We ask which observability and evaluation tools are most adopted or most visible, and which agent-execution metrics they provide out of the box. Following an adapted multivocal search over GitHub, the web and the OpenTelemetry standard, we selected 13 tools and three standards beneath them and collected 264 built-in metrics (226 from the tools, 38 from the standards) from their official documentation, each with a source URL, a verbatim quote and an access date. Merging equivalent metrics yields a taxonomy of 46 unique metrics in 13 categories: 18 observability metrics (whose values are captured from a run) and 28 evaluation metrics (whose values are judgements of agent behaviour or output). A worked example on a retrieval-augmented chatbot, traced with Langfuse and scored with Arize Phoenix and DeepEval, shows 30 of the 46 metrics reported by these three tools in a single run, and shows that a failure the application does not flag as an error is missed by the tracer's error metrics but caught by evaluators.

Index Terms—AI agents, observability, evaluation, LLM, metrics, taxonomy [TODO: confirm keywords]

I. Introduction

[TODO: Motivation: agents are non-deterministic, multi-step and tool-using, so a final answer alone says little about how a run went. Say why metrics need to be chosen deliberately, and why the vocabulary differs between tools.]

This paper makes three contributions:

1) A taxonomy and a catalogue of 46 observability and evaluation metrics for AI agents, built from 264 built-in metrics documented by the studied tools, each tied to documentation evidence (Section V).
2) The selection of the 13 tools and three telemetry standards those metrics come from, made with written rules from logged GitHub and Google queries (Section IV).
3) A worked example that shows, on one real application, which of these metrics three of the tools report and where they disagree (Sections II and VI).

Section II presents the application used as a running example. Section III defines the terms used in the rest of the paper. Section IV explains how the tools were chosen and their metrics collected, Section V presents the taxonomy and the catalogue, and Section VI returns to the example to show what the tools reported. Sections VII–IX discuss the results, their limitations and related work. [TODO: Research questions, if the venue expects them (for example: RQ1 which tools; RQ2 which built-in metrics; RQ3 how do metrics overlap across tools).]

II. Motivating example

Throughout the paper we use one real application as a running example. It is small enough to follow in full and it does what an LLM agent does: it calls a model several times, calls tools and composes an answer from what they return.

A. The application

The application is the course chatbot built in the DeepLearning.AI course on Claude Code [1]. It answers questions about four course transcripts. It is a single LLM with two tools: search_course_content looks up the passages of the transcripts that match a query, optionally within one course or lesson, and returns them; get_course_outline returns the list of lessons of a course. Its input is a user question, with the previous turns of the same conversation as history; its output is a text answer. For each question the model decides whether to call a tool, reads what the tool returns and either calls a tool again or writes the answer. We ran it with gpt-5-mini as the model; the model is a setting and can be replaced. The transcripts are stored in a vector database and are not redistributed; the rest of the application, the questions and the recorded results are in the folder example_rag of the accompanying repository.

B. The test

The test consisted of twelve scripted questions sent to the chatbot in nine sessions: six questions the transcripts answer (instructor names, lesson contents, a course outline), one question the transcripts do not cover (how to deploy MCP servers on Kubernetes; the chatbot still replies, from the model's own knowledge), one general-knowledge question (the capital of Australia) and one conversation of four turns in which the user states a fact about their project, asks two questions and then complains that the chatbot forgot the fact. The expected answer to




Fig. 1. One run of the example, redrawn from the graph the tracing tool draws for the question about deploying MCP servers on Kubernetes. The outer operation answer-course-question covers the whole run; inside it, three model calls (generate-response) alternate with two searches. The first search returned "No course found matching 'MCP' "; the second returned course content.

each question was taken from the transcripts and written before the run. Every run was recorded and later scored (Section VI).

As an illustration, Fig. 1 shows one of the twelve runs, the question about deploying MCP servers on Kubernetes, as it was recorded. The whole run is one timed operation, answer-course-question, which starts when the question arrives and ends when the answer is returned; inside it, the model was called three times and the search tool twice. The first search was restricted to a course named "MCP", which does not exist, and returned no course; the model searched again without the restriction, read the course content that came back and wrote the answer.

III. Background

This section fixes the vocabulary used in the rest of the paper, using the run in Fig. 1 as the reference.

A. Observability

Observability is the ability to understand what a system did from the data it emits; for an LLM agent, this is a record of every model call and tool call made while solving a task. To say what is recorded, we need a unit. A run is one execution of the agent, from an input (a user question or a task) to its final output: in Fig. 1, everything between ___start___ and ___end___. The data recorded for one run is a trace. A trace is made of spans. A span is one timed operation with a start, an end, a parent and attributes (model name, token counts, tool name, input, output), so spans nest: answer-course-question is the parent span of the run, and each model call and each search is a span inside it. A step is one action of the agent, a model call or a tool call, and usually corresponds to one span; spans also record other work, such as a retrieval. A session groups the runs of one conversation. The tools have their own names for these units; in this paper the terms above are used for every tool, and "run" always means the whole execution.

With the unit fixed, we can say what is computed from it. For the first two terms we follow OpenTelemetry. There, a metric instrument is defined by a name, a kind, an optional unit and an optional description [2]; a measurement is a data point (a value with attributes) reported through an instrument, and many measurements are combined by aggregation [2], [3]. Accordingly, a metric is a named, defined quantity. It states what is measured (a span, a run or a set of runs), the unit or scale, and how results are combined, so that it can be computed again and compared. "LLM call latency" is a metric. A measurement is a number obtained by applying such a metric to what was recorded: the third model call in Fig. 1 took 12.0 s, or the median over the twelve runs was 3.0 s. We call a metric an observability metric when it is computed from measurements captured during the run (tokens, cost, latency, counts, errors).

Most of the tools studied sit on a shared telemetry layer, which shapes what they can report. OpenTelemetry [4], an open standard for collecting traces, is the base: its conventions for LLM and agent spans fix which attributes a span carries (model name, token counts, tool name) and what they mean. OpenInference [5] and OpenLLMetry [6] are built on it. Both are instrumentation libraries that wrap an LLM or an agent framework and emit spans that follow such conventions; OpenLLMetry states that its own conventions are now part of OpenTelemetry. The platforms and frameworks studied here sit on top: they store and display the spans and compute metrics from them, or run evaluators over them. Most of them are built on OpenTelemetry or accept its traces (Table II, last column). Two consequences follow. First, the observability metrics are largely the same across tools because they are read from the same span attributes: Phoenix derives cost from the OpenInference token counts, and the OpenTelemetry conventions define the same quantities as metrics (duration of an agent invocation, counts of tool calls and model calls, token usage). Agreement between two tools on tokens, latency or counts is therefore weaker evidence than agreement between independent designs. Second, in the pages we read, the conventions give an attribute for the score an evaluator produced but no list of evaluation metrics. Faithfulness or task completion is defined by each tool, and this is where the vocabularies differ most.

B. Evaluation

Evaluation judges whether what the agent did, and what it answered, was good. Observability records; evaluation needs a judge: a rule, a model or a person. In the example, whether the answer about Kubernetes stayed within what the transcripts say is not in the trace; a judge has to read the answer and the retrieved passages and decide. The tools studied here offer observability, evaluation or both.

The following terms are our own usage, not established vocabulary. A score is the number an evaluator assigns to an output or a behaviour, for example a faithfulness of 0.9 given by an LLM judge. We call a metric an evaluation metric when it is a score from a judgement. The tools themselves draw a similar line without naming it: Arize Phoenix describes traces as showing "exactly what happened during a run" and, separately, scoring outputs with evaluators [7], and LangSmith lets feedback "score an individual run" [8]. The difference matters in use: a measurement is read from the trace, while a score depends on the judge (its prompt, its model or its reviewer) and can change when the judge changes. Surveys of LLM judges report that small changes in prompt wording or example order can give unstable results, and that the same input can receive different scores [9]; judges also show position, verbosity and self-enhancement bias [10]. Each tool's own metric is a tool-specific metric, with its own procedure; a unique metric groups tool-specific metrics that measure the same thing (Section V-A), so two tools can report different measurements, or different scores, for one unique metric.

IV. Method

Our goal is a taxonomy and a catalogue of observability and evaluation metrics for AI agents. Rather than proposing metrics, we collect the ones that practitioners can use today: the metrics that observability and evaluation tools ship, as documented by the tools themselves. To do this we (A) selected the most adopted or most visible tools with written rules, (B) read their documentation and recorded every built-in metric that describes how an agent run executes or how good its output is, and (C) grouped equivalent metrics into unique metrics and categories (Section V-A). Every recorded metric carries a documentation URL, a verbatim quote and an access date, and a script checks that each quote appears word for word in a saved copy of its page. The search logs, the evidence tables and the saved pages are in the accompanying repository.

A. Tool selection

Most tools are documented in repositories, vendor pages and blogs rather than in papers, so the search adapts the multivocal approach of Garousi et al. [11]: a search that covers such grey literature alongside papers, with fixed queries, written inclusion and exclusion rules, and a log of every query. We searched two channels on 2026-10-22. On GitHub, 17 queries through the API (10 topics and 7 keywords, 30 repositories each, limited to repositories with at least 1,000 stars, not archived and pushed in the last six months) returned 182 distinct repositories. On Google, six queries (two planned "comparison" queries were dropped) gave 173 results in their first 30 hits, whose titles and snippets named 68 tools. The GitHub queries can be rerun with the same limits; Google results depend on the date and the session, so that channel can be repeated but not reproduced exactly. The OpenTelemetry conventions for generative AI [4] were added as a third entry by hand, since a standard has no repository or product page that such queries rank.

Candidates were then screened by hand against written rules (Table I). A tool is included if its primary purpose is tracing, monitoring or evaluating LLM applications or agents (rule I1); open-source tools also need the star and activity limits above (I2), and closed-source tools need public documentation and mentions in at least two independent sources (I3). We exclude gateways and proxies (E1), agent-building frameworks (E2), model-level benchmark harnesses (E3), tutorials and lists (E4), duplicates such as an SDK and its own platform, which count as one tool (E5), and general-purpose observability, data, security or ML platforms whose LLM support is only a module, unless the LLM product is distributed on its own (E6). Of the 182 repositories, 145 were removed by I1 and E1–E4 (68 unrelated, 57 tutorials or lists, 7 gateways, 7 agent-building frameworks, 6 model-level harnesses); the 68 tools named by Google were screened with the same rules. Merging the two lists gave 42 candidates. A scope screening (S1) then kept the 31 whose own description gives observability or evaluation of LLM applications or agents as its primary purpose, and an agent relevance check (A1) kept the 30 whose official documentation explicitly covers agents, tool calls or multi-step traces, evidenced by a quote from a saved copy of the page. Each kept tool received one role (S2): platform (an application that stores and shows traces and offers evaluation or monitoring on top of them), framework (a library or command-line program that runs evaluations, with no trace storage of its own) or standard (telemetry conventions or an instrumentation library that emits them). The three standards have no backend or evaluators and only name what a trace contains; they went through the same screening but are kept as a separate layer from this point on.

The final selection uses different evidence for the two kinds of tool, because they leave different traces in public. A closed-source tool is selected by corroboration (C1): at least two sources that are not the tool's own website name it in the Google results; all four closed-source candidates passed. An open-source tool is selected by adoption (C2): it passes I2 and has at least 5,000 GitHub stars or at least one million downloads in the last 30 days (the larger of PyPI and npm), and, when a PyPI or npm

TABLE I
From search results to the 13 selected tools and three standards. The rules are explained in Section IV-A.

Stage	Rules	Count
GitHub: repositories returned	I2 (in query)	182
kept after manual check	I1, E1–E4	37
Google: tools named	–	68
closed-source kept	I1, I3, E1–E6, C1	5
Candidates (merged)	E5	42
Scope screening	S1	31
agent relevance	A1	30
Open source: adoption	C2	14 of 25
Closed source: corroboration	C1	4 of 4
new tools re-checked	E1–E6, S1	11 of 14
Selected: tools / standards	S2	13 / 3

package exists, at least 100,000 downloads; 14 of the 25 open-source candidates passed, and the rules E1–E6 and S1 were applied again to the tools this admitted, which removed Pydantic Logfire (a general observability platform, E6), Evidently (general ML monitoring, E6) and Harbor (a benchmark runner, E3). MLflow was kept under the E6 exception because its LLM tracing package, mlflow-tracing, is distributed on its own and had 14.8 million PyPI downloads in 30 days. The result is 13 tools and the three standards beneath them (Table II). Rules E6, A1, C1 and C2 were added after the first searches, and we report them as amendments to the protocol. The first selection applied C1 to every tool, open-source ones included, which left 13 entries and dropped widely installed open-source tools that the Google results did not name (MLflow, for example, because all eight results naming it were on its own website). We replaced C1 for open-source tools by C2 on 2026-11-06, after reading their stars and downloads, so the thresholds were chosen after seeing the data; the first selection is kept as a sensitivity comparison (Section VIII): it contains the same ten tools and three standards that C2 keeps, and C2 adds MLflow, Laminar and LangWatch.

Table II lists the 13 tools in two groups, open-source and closed-source, and then the three standards, with their role, stars and downloads where the entry is open source, and the number of independent Google sources. Twelve tools are platforms (Langfuse, MLflow, Laminar, DeepEval, Opik, Phoenix, LangWatch, Helicone, LangSmith, Braintrust, Galileo, Weave) and one is a framework (promptfoo). The entry named DeepEval is the open-source evaluation framework DeepEval together with Confident AI, its cloud platform, built by the same founders [24]; the platform's documentation states that its metrics are DeepEval's metrics [25], so by rule E5 the two are one entry. The role is a single label chosen from each tool's own description, so a tool that also ships a smaller component of another kind (Phoenix, for example, has an evaluation library) is labelled by its main purpose. For OpenLLMetry we use only the open-source library: its pages on the Traceloop platform, which Traceloop built on top of it and which has its own evaluators [26], are not part of the study. The last column records how each entry's documentation relates it to OpenTelemetry (Section III-A): Phoenix, Langfuse, Laminar and LangWatch are built on OpenTelemetry; Galileo receives traces through the OpenTelemetry Protocol (OTLP), the standard's transport format, following both the OpenTelemetry and the OpenInference conventions; LangSmith, Opik, Braintrust, MLflow and Confident AI accept OpenTelemetry traces; promptfoo can trace the providers it evaluates with OpenTelemetry. For Weave we only found that its calls are modelled like OpenTelemetry spans, and in the pages read Helicone shows no OpenTelemetry link. [TODO: Comment on the mix of roles and of open and closed source once final.]

B. Collecting built-in metrics

For each selected tool we read its official documentation and recorded every built-in metric: one the tool itself ships, as opposed to a user-written or user-defined metric, a community or third-party metric, or one available only through an integration. Each row stores the documentation URL, a verbatim quote, the saved plain-text copy of the page and the access date. A scope rule (M1) keeps only metrics that describe how an agent run executes (tool use, task and goal, plan and trajectory, tokens, cost, latency, errors and counts) or how good its output is (answer quality, grounding, safety and conversation). Text-match and format checks, retrieval scores, audio, voice and image metrics, task-specific output metrics and custom judges are out of scope. A metric that restates one already in the taxonomy is merged into it, not added; a metric provided by a single tool is kept. M1 set aside 222 rows that the tools document as built-in and kept 264, so the taxonomy covers about half of what the tools document; the set-aside rows, with the reason for each, are kept with the data, together with 127 rows that are custom-only, community or reached through integrations and so not built-in. For each tool and metric the data also records the strongest status found: built-in, integration, community, template, generic custom, records scores or not documented. The last status means nothing was found in the pages read, which is not proof that the tool lacks the capability.

TABLE II

The 13 selected tools and the three standards beneath them. Open-source tools are listed by downloads (the larger of PyPI and npm in the last 30 days), then by stars, both read on 2026-11-06; closed-source tools by independent Google sources ("Indep. sources"); the number is the order within each group, not a ranking across groups. Stars and downloads are blank for closed-source tools, which C1 judges on sources, and for OpenTelemetry, and Helicone has no package. "OTel link" is how the tool's documentation relates it to OpenTelemetry: it defines the conventions, is built on OpenTelemetry, accepts OpenTelemetry traces, offers optional OpenTelemetry tracing, or models its data like spans; "not found" means nothing was found in the pages read (evidence in tool_relations.csv).

#	Tool	Role	Found via	Stars	Downloads	Indep. sources	OTel link
Open-source tools (9)							
1	Langfuse [12]	platform	GitHub + Google	37,092	23.6M	15	built on
2	MLflow [13]	platform	GitHub	28,698	19.9M	0	accepts
3	Laminar [14]	platform	GitHub	3,474	6.0M	0	built on
4	promptfoo [15]	framework	GitHub + Google	26,896	3.8M	4	optional
5	DeepEval (with Confident AI) [16]	platform	GitHub + Google	19,328	2.6M	12	accepts
6	Opik [17]	platform	GitHub + Google	23,215	1.7M	3	accepts
7	Arize Phoenix [7]	platform	GitHub + Google	12,171	626k	16	built on
8	LangWatch [18]	platform	GitHub	5,014	346k	1	built on
9	Helicone [19]	platform	GitHub + Google	6,270	–	6	not found
Closed-source tools (4)							
1	LangSmith [8]	platform	Google only	–	–	13	accepts
2	Braintrust [20]	platform	Google only	–	–	5	accepts
3	Galileo [21]	platform	Google only	–	–	3	accepts
4	Weights & Biases Weave [22]	platform	Google only	–	–	2	span-like
Standards (3)							
1	OpenTelemetry [23]	standard	Google only	–	–	10	defines
2	OpenLLMetry [6]	standard	GitHub + Google	7,523	1.8M	4	built on
3	OpenInference [5]	standard	GitHub + Google	1,307	8.6M	2	built on

V. Taxonomy and Catalogue of Metrics

This section presents the taxonomy, the categories into which the metrics fall, and then the catalogue, the 46 unique metrics classified under those categories, each defined and, where the example run reported it, illustrated with a value from that run.

A. Taxonomy

Two tool-specific metrics are merged into one unique metric when they measure the same thing about the same object, whatever the tools call them: for example, DeepEval's "Faithfulness" and Phoenix's "Hallucination" both judge whether the claims in an answer are supported by the retrieved context, and OpenTelemetry's gen_ai.usage.output_tokens and Langfuse's "output tokens" both count the tokens the model generated. The object is usually the same (a tool call, an agent run, an LLM call or a token type); where tools compute the same thing on different objects, as for task completion on a response, a run or a conversation, the definition says so. Merging is by what is measured, not by how: the tool-specific metrics in one unique metric may compute it differently, and Section VI shows a case where two of them disagree. The mapping from tool-specific names to unique metrics (326 pairs) is made by hand and kept with the data; the definitions of the unique metrics are written by the authors and are not quoted from the documentation.

The unique metrics are then classified on two levels. The type says where the value comes from: a metric is an Observability metric if its values are captured from a run or derived from what was captured, and an Evaluation metric if its values are scores, that is, judgements of agent behaviour or output (Section III). The category says what part of the run the metric is about. Observability metrics fall into six categories: tool use (what happened to the tool calls), plan and trajectory (the sequence of steps), token usage, cost, latency, and errors and volume (how many runs, calls and failures). Evaluation metrics fall into seven: tool use (whether the tool calls were the right ones), task and goal (whether the agent did what was asked), plan and trajectory (whether the sequence of steps was a good one), answer quality, grounding (whether the answer stays within its sources), safety and policy, and conversation (properties of a multi-turn exchange). Two category names, tool use and plan and trajectory, appear under both types because the same part of a run can be counted (Observability) or judged (Evaluation).

The 13 tools and three standards document 264 built-in metrics that pass the scope rule (226 from the tools, 38 from the standards), which map to 46 unique metrics: 18 Observability and 28 Evaluation metrics in the 13 categories. One further metric, time per output token, is documented as built-in only by standards and no studied tool; it is not part of the 46 and is listed apart in Table III. Fig. 2 shows the taxonomy together with the tools that document each metric as built-in. Coverage is uneven. 21 of the 46 metrics are documented as built-in by at least five of the 16 tools and standards taken together, and 2 of them (input tokens, output tokens) by 14; 6 metrics are provided by exactly one tool (step count, tool response handling, plan quality, action progress toward goal, flow and reasoning coherence, fluency). These counts

include the three standards, which name attributes rather than compute metrics; they supply 22 of the 129 built-in observability cells and none of the 105 evaluation cells. Counting only the 13 tools, 17 metrics reach five tools, and estimated cost (12 tools) is the most widely documented, followed by input tokens, output tokens and faithfulness to context (11 each).

B. Catalogue

Table III defines the 46 unique metrics. The rest of this section walks through them by category, with the values the example run produced (Table IV) where one of the three tools used there reported the metric; a metric with no example value was not reported by those tools in that run, which says nothing about the metric itself.

1) Observability metrics: Tool use counts what happened to the tool calls: tool execution errors (failed tool executions, as a count, rate or flag), tool call count and tool execution latency. In the example, Langfuse recorded 10 tool calls in 12 runs, none marked as failed, with a median execution time of 18 ms. Plan and trajectory has one observability metric, step count, the number of steps in a run, documented by one tool only. Token usage splits what the model consumed into input tokens (the prompt), output tokens (the completion), total tokens, cached tokens (input read from or written to a provider-side cache) and reasoning tokens (spent on model reasoning; some tools count them within output tokens, others apart). Over the twelve runs Langfuse reported 19,684 input, 2,598 output, 5,632 reasoning and no cached tokens; it counts reasoning tokens apart from output tokens, so its total of 27,914 is the sum of the three. Cost has estimated cost, computed from token counts and model prices, and its breakdown by token type: $0.0214 in the example, of which $0.0113 for reasoning tokens. Latency has trace/run latency (end to end; median 8.8 s per run), LLM call latency (median 3.0 s), span duration (recorded on every span) and time to first token, which the example did not report because the application does not stream. Errors and volume counts error count/rate (failed runs, spans or model calls; zero in the example), trace/span count (12 traces, 44 spans) and LLM call count (22).

2) Evaluation metrics: Tool use judges the tool calls: tool selection (was the right tool chosen; Phoenix judged 8 of 10 calls correct), tool argument validity (were the arguments correct and well formed; 10 of 10 for Phoenix, mean 1.00 for DeepEval), tool call correctness (do the calls made match the calls expected; DeepEval mean 0.88), tool call efficiency (no redundant calls; not reported) and tool response handling (did the agent process what the tool returned, including errors; Phoenix 8 of 8 turns), documented by one tool only. Task and goal has task/goal completion, judged on a run, a conversation or a response: Phoenix found 10 of 12 turns complete and DeepEval gave a mean of 0.71. Plan and trajectory judges the sequence of steps: plan quality, plan adherence (did the actions follow the plan), trajectory accuracy (was the sequence logical, or does it match a reference), step/action efficiency, action progress toward goal and flow and reasoning coherence; none of the three tools used in the example reported any of these. Answer quality judges the final answer: answer correctness (against a reference or by a model), answer relevance (does it address the question; DeepEval mean 0.92), helpfulness, conciseness (Phoenix judged 1 of 12 answers concise), tone appropriateness and fluency. Grounding has faithfulness to context: are the claims in the answer supported by the retrieved passages, with unsupported claims counted as hallucination; Phoenix found 7 of 8 turns faithful and DeepEval gave a mean of 1.00 over the same 8, a disagreement examined in Section VI. Safety and policy has toxicity (0 of 12 turns), bias and fairness (DeepEval mean 1.00), sensitive data leakage (personal data or secrets in input or output; 0 of 12 for Phoenix, 0.99 for DeepEval), injection detection, refusal detection (did the model decline to answer; Phoenix flagged 1 of 11 turns, an instructor question on which the chatbot said it could not determine the answer; one call timed out, hence 11) and policy and moderation violations. Conversation has knowledge retention (does the agent keep facts the user gave earlier; DeepEval 1.00 on the one conversation), user satisfaction or frustration (Phoenix flagged friction on 1 of 12 turns, the complaint) and conversation coherence, which scores the dialogue rather than the agent's actions.

[TODO: Add the tool-by-metric matrix as a figure (export results/tool_metric_matrix.html to PDF) and describe the status counts: of the 736 cells (46 metrics, 16 columns), 234 are built-in, 228 generic custom, 84 records scores, 187 not documented, 2 integration and 1 template.]




Fig. 2. The metric taxonomy and the tools that document each metric as built-in. Rows are the 46 unique metrics, grouped by type and category; columns are the 13 tools (the three standards are not columns), grouped by role and in the order of Table II within each role. A coloured dot means the tool documents the metric as built-in; a grey dot means another status or nothing found (Section IV-B); a dagger marks a metric that only one tool documents as built-in. DeepEval stands for the DeepEval framework together with its cloud platform Confident AI (Table II). Definitions are in Table III.

TABLE III

Definitions of the 46 unique metrics, in the authors' wording, grouped as in Fig. 2, which shows the tools that document each metric as built-in, followed by the one metric documented only by standards. A dagger marks a metric that only one of the 13 tools in Fig. 2 documents as built-in; a double dagger marks a metric that at least one of the three standards also documents as built-in (14 metrics, all Observability: the standards document no evaluation metric).

Metric	Definition
Observability (18 metrics)	
Tool use	
Tool execution errors	Count, rate or detection of failed tool executions.
Tool call count‡	Number of tool calls made by an agent run.
Tool execution latency†‡	Time taken by tool executions.
Plan and trajectory	
Step count†	Number of steps in an agent run.
Token usage	
Input tokens‡	Number of tokens sent to the model (prompt).
Output tokens‡	Number of tokens generated by the model (completion).
Total tokens‡	Total number of tokens for a call, trace or model: input plus output, plus reasoning tokens where a tool counts them separately.
Cached tokens‡	Input tokens read from or written to a provider-side cache.
Reasoning tokens‡	Tokens spent on model reasoning; some tools count them within output tokens, others separately.
Cost	
Estimated cost‡	Monetary cost of model usage, computed from token counts and model prices.
Cost breakdown by token type‡	Cost split by input, output, cached or other token type.
Latency	
Trace/run latency‡	End-to-end duration of an agent run, workflow or trace.
LLM call latency‡	Duration of a single model call.
Span duration	Duration of an individual span or step of a trace (generic, not specific to LLM or tool spans).
Time to first token‡	Time from request to the first generated token.
Errors and volume	
Error count/rate‡	Count or rate of failed runs, traces, spans or model calls.
Trace/span count	Number of traces or spans recorded.
LLM call count‡	Number of model (inference) calls.
Evaluation (28 metrics)	
Tool use	
Tool selection	Whether the agent chose the appropriate tool for the task.
Tool argument validity	Whether the arguments of a tool call are correct and well-formed (for example against the tool's schema or expected values).
Tool call correctness	Whether the tool calls the agent made match the calls expected or appropriate for the task.
Tool call efficiency	Whether the agent called tools without redundant or unnecessary calls.
Tool response handling†	Whether the agent correctly processed what a tool returned, including errors.
Task and goal	
Task/goal completion	Whether the agent completed the task or achieved the goal it was given, judged on a run, a conversation or a response.
Plan and trajectory	
Plan quality†	Quality of the plan the agent produced.
Plan adherence	Whether the agent's actions followed its own plan.
Trajectory accuracy	Whether the sequence of agent steps and tool calls was logical or matches a reference trajectory.
Step/action efficiency	Whether the agent reached the goal with a minimal number of steps.
Action progress toward goal†	Whether each action moved the agent closer to its goal.
Flow and reasoning coherence†	Whether the agent's sequence of actions and reasoning steps is logically consistent.
Answer quality	
Answer correctness	Whether the agent's answer is factually correct, judged by a model or against a reference answer.
Answer relevance	Whether a response addresses the user's input, per answer or per turn, without off-topic content.
Helpfulness	How useful or helpful the answer is to the user.
Conciseness	Whether the answer gives the requested information without unnecessary or padded content.
Tone appropriateness	Whether the tone of the response is appropriate for the context.
Fluency†	Whether the response is grammatically correct and reads naturally.
Grounding	
Faithfulness to context	Whether the claims in the answer are supported by the provided context. Unsupported or contradicted claims count as hallucination.
Safety and policy	
Toxicity	Whether the output contains toxic, abusive, hateful or profane language.
Bias and fairness	Whether the output contains bias, stereotyping or discrimination against a person or group.
Sensitive data leakage	Whether the input or output exposes personal data or secrets (for example PII, credentials).
Injection detection	Whether an input contains an injection attempt (prompt, code or SQL injection) aimed at the agent.
Refusal detection	Whether the model refuses, declines or avoids answering a request.
Policy and moderation violations	Whether the output breaks a safety, moderation, compliance or content policy.
Conversation	
Knowledge retention	Whether the agent remembers and uses facts the user gave earlier in the conversation.
User satisfaction or frustration	Whether the user's messages show satisfaction, or frustration, corrections and repeated attempts.
Conversation coherence	Coherence and quality of the messages in a conversation, including repetition or degeneration. It scores the dialogue, not the agent's sequence of actions.
Standards only (1 metric; documented as built-in by standards, provided by none of the ten tools)	
Latency	
Time per output token/ generation time	Time spent generating tokens after the first one. Documented as built-in by OpenTelemetry and OpenLLMetry only.

VI. The example revisited

We now return to the twelve runs of Section II and show what three of the studied tools reported about them. The runs were traced with Langfuse [12]; the recorded turns were then scored offline with the built-in evaluators of Arize Phoenix [7] and DeepEval [16], with gpt-5-mini again as the judge model. This illustrates what such tools produce in practice; it does not evaluate them.

A. What the tools reported

Over the twelve runs, Langfuse reported 12 traces and 44 spans, 22 model calls and 10 tool calls; 19,684 input, 2,598 output and 5,632 reasoning tokens; a cost of $0.0214 split by token type; and latency per run, per model call and per tool call. It reported no first-token time because the application does not stream. Phoenix evals and DeepEval scored the twelve runs on tool selection, tool argument validity, tool call correctness, tool response handling, task completion, answer relevance, conciseness, faithfulness to the retrieved context, toxicity, bias, sensitive-data leakage, refusal, knowledge retention and user frustration. Tokens, cost and latency are Langfuse's own values; the counts of calls and spans were computed from its span records. Table IV lists the 30 unique metrics the tools reported and what each tool reported for each: measurements for the metrics recorded by the tracer, scores for those computed by the evaluators.

The observations below name the evaluators by the tools' own names, so we state here which unique metric of the catalogue each one maps to and on what scale it reports. DeepEval Task Completion (a score from 0 to 1) and Phoenix Completeness (a label, complete or incomplete) map to task/goal completion. DeepEval Tool Correctness (0 to 1) maps to tool call correctness. Phoenix Faithfulness (a label) and DeepEval Faithfulness (0 to 1) map to faithfulness to context. DeepEval Answer Relevancy (0 to 1) maps to answer relevance. DeepEval Knowledge Retention (0 to 1) maps to knowledge retention, and Phoenix User Friction (a label) to user satisfaction or frustration. Langfuse's error metrics count the spans the application marked as failed (tool execution errors and error count/rate).

B. Observations

- Error metrics missed a failure the application did not flag. In two of the twelve runs the course lookup failed ("No course found matching 'MCP' "). The application returns this message as an ordinary tool result, not as an error, so Langfuse's error counts stayed at zero although the message is in the recorded tool output: an error metric counts only what the application marks as an error. In one of the two runs the second search recovered (Fig. 1); in the other the agent gave a wrong answer, and the evaluators caught it: Task Completion scored 0.00, Completeness said incomplete and Tool Correctness scored 0.00.
- Two tools disagreed on the same unique metric. For the question the transcripts cannot answer, the answer said Kubernetes is not covered and then added Kubernetes instructions found nowhere in the retrieved text. Phoenix Faithfulness flagged it as unfaithful; DeepEval Faithfulness scored it 1.0. The two tool-specific metrics share a name and measure the same thing but not by the same procedure, which a unique metric does not show.
- An off-target answer was visible. When asked for an instructor's name, the application returned a lesson outline; Answer Relevancy scored 0.30.
- Conversation metrics behaved as expected on the one multi-turn conversation. Knowledge Retention scored 1.0 because the application kept the user's earlier statement, and User Friction fired only on the turn in which the user complained. With one conversation,

TABLE IV
Metrics reported by Langfuse (tracing) and by the Arize Phoenix and DeepEval evaluators for the 12-question run. Each row is a unique metric of the catalogue; a cell gives the measurement (tracer) or score (evaluators) the tool reported over the twelve runs, with n the number of turns scored. A dash means the tool reported nothing in this run, not that it lacks the metric: Langfuse was used only for tracing, and not every built-in evaluator was run. The LLM judge was gpt-5-mini, not validated against human labels. Generated by the authors' script from the tools' output.

Metric	Langfuse	Phoenix evals	DeepEval
Recorded by the tracer			
Tool execution errors	0 of 10 tool calls	–	–
Tool call count	10 in 12 turns	–	–
Tool execution latency	median 18 ms	–	–
Input tokens	19,684	–	–
Output tokens	2,598	–	–
Total tokens	27,914	–	–
Cached tokens	0	–	–
Reasoning tokens	5,632	–	–
Estimated cost	$0.0214	–	–
Cost breakdown by token type	in $0.0049; out $0.0052; reasoning $0.0113	–	–
Trace / run latency	median 8.8 s per turn	–	–
LLM call latency	median 3.0 s	–	–
Span duration	on every observation	–	–
Error count / rate	0 error observations	–	–
Trace / span count	12 traces, 44 observations	–	–
LLM call count	22	–	–
Scored by the evaluators			
Tool selection	–	8/10 calls correct	–
Tool argument validity	–	10/10 calls valid	mean 1.00 (n=8)
Tool call correctness	–	–	mean 0.88 (n=8)
Tool response handling	–	8/8 turns correct	–
Task / goal completion	–	10/12 turns complete	mean 0.71 (n=12)
Answer relevance	–	–	mean 0.92 (n=12)
Conciseness	–	1/12 turns concise	–
Faithfulness to context	–	7/8 turns faithful	mean 1.00 (n=8)
Toxicity	–	0/12 turns toxic	–
Bias and fairness	–	–	mean 1.00 (n=12)
Sensitive data leakage	–	0/12 turns flagged	mean 0.99 (n=12)
Refusal detection	–	1/11 turns refused	–
Knowledge retention	–	–	mean 1.00 (n=1)
User satisfaction or frustration	–	1/12 turns with friction	–

this shows that the metrics run, not that they are reliable.

- A score can mean less than its name suggests. Task Completion treats a plain question as a task to perform, so it can score a correct answer low (0.35 for "What is the capital of Australia?"); its mean over the twelve runs (0.71) should not be read as answer quality.

VII. Discussion

[TODO: Interpret: the split between measurements and judgements; metrics most tools share (token usage, cost, faithfulness) versus metrics only one tool offers (step count, tool call efficiency, tool response handling, plan quality, action progress toward goal, flow and reasoning coherence); why the same metric name can mean different things in different tools; what the example suggests about combining tracing with evaluators; which metrics no tool reported in the example (plan, trajectory, step, helpfulness, tone, injection, policy, conversation coherence).]

VIII. Limitations

- Search strategy. We could not include every tool, so the search follows fixed rules, and the two kinds of tool rest on different evidence. Open-source tools are selected by adoption (stars and downloads, rule C2), which measures adoption and not production use; closed-source tools have no such figures and are selected by how often independent sources name them (C1), which measures visibility. The two groups are not ranked against each other. C2 was introduced after we had read the adoption data, so its thresholds (5,000 stars or one million downloads in 30 days, and at least 100,000 downloads when a package exists) were chosen after seeing the data; the first selection (C1 for every tool) is kept as a sensitivity comparison. Because E5 merges an SDK with its platform, three of the 12 independent sources of DeepEval name only its platform Confident AI; DeepEval is selected on adoption, so this does not affect its inclusion. Closed-source tools that the first 30 results of the six Google queries do not name are absent, and the

source counts reflect what ranks in those queries, not usage. Google counts come from titles and snippets only, only six of the eight planned queries were run, and the region and language of the search session were not recorded (the searches ran in a private browser window). Cloud-vendor products that appear only under vendor-site queries were not searched for. A source counts as independent if it is not the tool's own website, so a competitor's comparison post counts; the source counts measure visibility, not independent assessment. Downloads include dependency and continuous-integration installs, and stars and downloads cannot be compared across languages and registries.

- Notable tools left out. Ragas, an evaluation library named by five independent sources and with 16 k GitHub stars, fails I2: its latest release (13 January 2026) and latest commit (24 February 2026) are older than the six-month window before the search date, so it is out although it is widely named. Evidently (8,047 stars, 0.8 M downloads in 30 days) and Pydantic Logfire (13.0 M) are out under E6, as general ML monitoring and as a general observability platform, and Harbor (4.8 M) is out as a benchmark runner like Inspect AI, which S1 removes. General-purpose observability platforms with an LLM module, such as Datadog and Grafana (two sources each), are also out under E6. MLflow is in only through an exception that we added to E6 for an LLM-specific package distributed on its own (mlflow-tracing); a stricter reading of E6 would remove it. Open-source tools below the adoption thresholds are out, for example OpenLIT (2,953 stars, 0.28 M downloads), AgentOps (5,950 stars, 95 k) and Giskard (5,944 stars, 13 k). The figures are in open_source_adoption_candidates.csv and excluded_tools_sensitivity.csv.
- Scope. Benchmarks and evaluation harnesses are out of scope, so metrics such as pass^k that come from them are not in the tables. The metric scope rule M1 removed about half of the documented rows, including retrieval scores, which many RAG applications rely on.
- Documentation only. Metrics come from official documentation pages. A metric present only in source code is not listed, and a cell marked "not documented" is not proof of absence. Row counts are not comparable across tools, because some documentation lists individual assertion types and other lists fewer, broader metrics.
- Shared foundations. Several tools build on the same conventions (Section III-A), so two tools documenting the same observability metric are not independent designs, and the number of tools per metric measures documentation overlap, not independent adoption. Section V-A therefore also gives the counts without the three standards.
- Taxonomy. The mapping of tool-specific metrics to unique metrics and the metric definitions are the authors' judgement. A finer or coarser split would change the count of 46. [TODO: State any validation, such as a second coder.]
- Example. One run of twelve questions on one application, with one small model acting as both application and judge and no human labels. Evaluator scores illustrate what each tool reports; they do not measure the accuracy of the tools. The example uses three of the 13 tools.

IX. Related work

Two earlier studies are closest to ours. Dong et al. [27] ran a mapping study of 17 tools for what they call AgentOps: the tracing, monitoring and operation of LLM agents, by analogy with DevOps for software. The tools were found through GitHub and Google searches in November 2024, the same two channels we use, and are compared on seven features (customisation, prompt management, evaluation, feedback, monitoring, tracing, guardrails), each marked present or absent; from them the authors derive a taxonomy of the artifacts that should be traced over an agent's life cycle. Yehudai et al. [28] come from the evaluation side. Their survey compares eight evaluation frameworks, four of which are in our set (LangSmith, Langfuse, Arize, Galileo), on six capabilities marked present or absent, and organises evaluation by granularity: the final response, each step (tool selection, arguments, progress toward the goal) and the whole trajectory (its match to a reference path), with monitoring (task completion rates, latency, throughput) as a separate capability. Our metric categories fit this view: answer quality, grounding, safety and conversation metrics are final-response evaluation; tool-use and goal-progress metrics are stepwise; plan and trajectory metrics are trajectory evaluation; and token, cost, latency and error metrics are monitoring (Section V). They also name cost efficiency and safety as gaps that future evaluation frameworks should cover, while in the pages we read several of the tools in our set already document built-in metrics for both.

The remaining work is further from ours. Wang et al. [29] tabulate monitoring tools by whether they offer logs, traces, and system, cost, RAG and performance metrics; Mohammadi et al. [30] organise agent evaluation by objective and process, naming tools only in passing; Solomon et al. [31] list in an appendix the kinds of data each tool collects (tokens, latency, cost, errors), at the level of metric families; and Souza and Machado [32] propose to map agent components and behaviours to metrics from LangSmith, DeepEval and Opik, but the mapping is not yet published. Naveed et al. [33] review ML monitoring tools with a search that also covers repositories, vendor pages and blogs, as ours does (Section IV), but not for LLM agents.

Compared with these works, ours differs in the unit of comparison and in the evidence. They compare tools on features or capabilities marked present or absent; we go one level down and record every built-in metric a tool documents, each with a quotation from the documentation and an access date, and we group the metrics by what they measure into one taxonomy that separates observability from evaluation metrics. Where monitoring is a single item for them, we split it into metrics such as cached and reasoning tokens or time to first token. The tool set is also current (2026) and selected by written rules: six of our 16 entries (Langfuse, LangSmith, Phoenix, Helicone, Laminar, OpenLLMetry) are among the 17 of Dong et al.

X. Conclusion

[TODO: Summarise the contributions and the main finding; state future work (for example validating evaluator scores against human labels, extending the example to a multi-agent application).]

Data availability

[TODO: Repository URL and archive (for example Zenodo). The repository holds the search logs, the evidence tables with quotes and saved pages, the taxonomy and mapping, and the example's scripts and results. The example's course transcripts are not redistributed.]

References

[1] DeepLearning.AI, "Claude code: a highly agentic coding assistant," https://www.deeplearning.ai/courses/claude-code-a-highly-agentic-coding-assistant.

[2] "Metrics," https://opentelemetry.io/docs/concepts/signals/metrics/, openTelemetry documentation. Accessed 2026-11-04.

[3] "Metrics API," https://github.com/open-telemetry/opentelemetry-specification/blob/main/specification/metrics/api.md, openTelemetry specification. Accessed 2026-11-04.

[4] "Semantic conventions for GenAI agent and framework spans," OpenTelemetry semantic conventions, accessed 2026-10-25. [Online]. Available: https://github.com/open-telemetry/semantic-conventions-genai/blob/main/docs/gen-ai/gen-ai-agent-spans.md

[5] "OpenInference: documentation," https://arize-ai.github.io/openinference/spec/semantic_conventions.html, accessed 2026-10-25.

[6] "OpenLLMetry: documentation," https://www.traceloop.com/docs/openllmetry/tracing/annotations, accessed 2026-10-25.

[7] "Arize Phoenix: documentation," https://arize.com/docs/phoenix, accessed 2026-10-25.

[8] "LangSmith: documentation," https://docs.langchain.com/langsmith/observability-concepts, accessed 2026-10-25.

[9] J. Gu, X. Jiang, Z. Shi, H. Tan, X. Zhai, C. Xu, W. Li, Y. Shen, S. Ma, H. Liu, S. Wang, K. Zhang, Y. Wang, W. Gao, L. Ni, and J. Guo, "A survey on LLM-as-a-judge," 2024.

[10] L. Zheng, W.-L. Chiang, Y. Sheng, S. Zhuang, Z. Wu, Y. Zhuang, Z. Lin, Z. Li, D. Li, E. P. Xing, H. Zhang, J. E. Gonzalez, and I. Stoica, "Judging LLM-as-a-judge with MT-bench and chatbot arena," in Advances in Neural Information Processing Systems 36 (NeurIPS 2023), Datasets and Benchmarks Track, 2023.

[11] V. Garousi, M. Felderer, and M. V. Mäntylä, "Guidelines for including grey literature and conducting multivocal literature reviews in software engineering," Information and Software Technology, vol. 106, 2019, [TODO: verify pages and DOI].

[12] "Langfuse: documentation," https://langfuse.com/docs/observability/features/agent-graphs, accessed 2026-10-25.

[13] "MLflow: tracing for LLM and agent observability (documentation)," https://mlflow.org/docs/latest/genai/tracing/, accessed 2026-11-09.

[14] "Laminar: documentation," https://laminar.sh/docs/, accessed 2026-11-09.

[15] "promptfoo: documentation," https://www.promptfoo.dev/docs/providers/openai-agents/, accessed 2026-10-25.

[16] "DeepEval: documentation," https://deepeval.com/docs/getting-started-agents, accessed 2026-10-25.

[17] "Opik: documentation," https://www.comet.com/docs/opik/tracing/overview, accessed 2026-10-25.

[18] "LangWatch: documentation," https://langwatch.ai/docs/introduction, accessed 2026-11-09.

[19] "Helicone: documentation," https://docs.helicone.ai/features/sessions, accessed 2026-10-25.

[20] "Braintrust: documentation," https://www.braintrust.dev/docs, accessed 2026-10-25.

[21] "Galileo: documentation," https://docs.galileo.ai/, accessed 2026-10-25.

[22] "Weights & Biases Weave: documentation," https://docs.coreweave.com/weave, accessed 2026-10-25.

[23] "OpenTelemetry: documentation," https://github.com/open-telemetry/semantic-conventions-genai/blob/main/docs/gen-ai/gen-ai-agent-spans.md, accessed 2026-10-25.

[24] "DeepEval: the open-source LLM evaluation framework (readme)," https://github.com/confident-ai/deepeval, accessed 2026-11-05.

[25] "Confident AI documentation," https://www.confident-ai.com/docs/llms.txt, accessed 2026-11-05.

[26] N. Gazit, "Traceloop is joining ServiceNow," https://traceloop.com/blog/traceloop-is-joining-servicenow, traceloop blog, March 2026. Accessed 2026-11-05.

[27] L. Dong, Q. Lu, and L. Zhu, "AgentOps: enabling observability of LLM agents," 2024.

[28] A. Yehudai, L. Eden, A. Li, G. Uziel, Y. Zhao, R. Bar-Haim, A. Cohan, and M. Shmueli-Scheuer, "Survey on evaluation of LLM-based agents," 2025.

[29] Z. Wang, J. Li, Q. Zhou, H. Si, Y. Liu, J. Li, G. Xie, F. Sun, D. Pei, and C. Pei, "A survey on AgentOps," 2025.

[30] M. Mohammadi, Y. Li, J. Lo, and W. Yip, "Evaluation and benchmarking of LLM agents: a survey," 2025.

[31] R. Solomon, Y. Y. Levi, L. Vaknin, E. Aizikovich, A. Baras, E. Ohana, A. Giloni, S. Bose, C. Picardi, Y. Elovici, and A. Shabtai, "LumiMAS: a comprehensive framework for real-time monitoring and enhanced observability in multi-agent systems," 2025.

[32] D. Souza and P. Machado, "Toward architecture-aware evaluation metrics for LLM agents," 2026.

[33] H. Naveed, S. Barnett, C. Arora, J. Grundy, H. Khalajzadeh, and O. Haggag, "Monitoring machine learning systems: a multivocal literature review," 2025.