

Resistors						
Item	Marked Value (Ω)	Tolerance (%)	Low spec value (Ω)	High spec value (Ω)	Measured value (Ω)	In spec ¹ (Y,N,M)
1	2.2	1%	2.178	2.222	2.2	Y
2	1000	1	990	1010	996	Y
3	150	1	148.5	151.5	148.2	M
4	3.3 million	1	3267000	3,333,000	3,330,000	Y
5	680	1	673.2	686.8	676	Y

Capacitors						
Item	Marked Value (nF)	Tolerance (%)	Low spec value (nF)	High spec value (nF)	Measured value (nF)	In spec ¹ (Y,N,M)
1	0.22	5	.231	0.21	0.21	Y
2	3.3	5	3.465	3.53	3.53	M
3	3.9	5	3.82	3.82	3.82	Y
4	4.7	5	4.435	4.87	4.87	Y
5	6.8	5	7.14	7.02	7.02	Y

Inductors						
Item	Marked Value (mH)	Tolerance (%)	Low spec value (mH)	High spec value (mH)	Measured value (mH)	In spec ¹ (Y,N,M)
1	2.7	10	2.43	2.97	2.6	Y
2	10	10	9	11	9.93	Y
3	1	10	0.9	1.1	1.06	Y
4	.01	10	0.009	0.011	0.0077	N
5	.220	10	.242	.198	.225	Y

¹Y= in-spec, M = marginally out of spec, N = out of spec