

The array located in the first few lines of the configs.php files needs to be adjusted for the server-side.

```
return array(
    'host' => "localhost",
    'username' => "root",
    'password' => "LetsGo",
    'dbname' => "LetsGo",
    'dbstorage' => "EventStorage"

);
```

The dbname name should include a database with the two tables described below. The dbstorage just needs to refer to any empty storage. The HOSTPATH variable in the thisUser.swift file needs to be altered accordingly.

Field	Type	Null	Key	Default	Extra
id	int(11)	NO	PRI	NULL	auto_increment
Owner	int(10) unsigned	YES		NULL	
StartTime	datetime	YES		NULL	
EndTime	datetime	YES		NULL	
Title	varchar(30)	YES		NULL	
Description	varchar(500)	YES		NULL	
Male	tinyint(1)	YES		NULL	
Female	tinyint(1)	YES		NULL	
LeastAge	int(3)	YES		NULL	
MaxAge	int(3)	YES		NULL	
Address	char(60)	YES		NULL	
longitude	double	YES		NULL	
lattitude	double	YES		NULL	
Duration	double	YES		NULL	
photopath	char(80)	YES		NULL	

Field	Type	Null	Key	Default	Extra
id	int(10) unsigned	NO	PRI	NULL	auto_increment
firstname	varchar(50)	YES		NULL	
lastname	varchar(50)	YES		NULL	
username	varchar(50)	NO		NULL	
birthday	date	YES		NULL	
password	varchar(50)	NO		NULL	
eventsattended	int(5)	NO		0	
eventsrsvpd	int(5)	NO		0	
gender	varchar(10)	YES		NULL	
email	varchar(50)	YES		NULL	
photopath	varchar(50)	YES		NULL	