



12. Formalar. Form control

Reja:

▼ Formalar



Bootstrap 5 yordamida **Formalarga** osongina style berish **imkoniyati** mavjud. Uning uchun Bootstrapning **maxsus klasslarini** ko'rsatish kifoya bo'ladi

```
<div class="container">
  <form>
    <div class="mb-3">
      <label for="email-input" class="form-label">Email manzili</label>
      <input type="email" class="form-control" id="email-input">
    </div>
    <div class="mb-3">
      <label for="password-input" class="form-label">Parol</label>
      <input type="password" class="form-control" id="password-input">
    </div>
    <div class="mb-3 form-check">
      <input type="checkbox" class="form-check-input" id="checkbox-input">
      <label class="form-check-label" for="checkbox-input">Yodda saqlash</label>
    </div>
    <button type="submit" class="btn btn-primary">Yuborish</button>
  </form>
</div>
```

Form text



Form input uchun tegishli bo'lgan **mattni** uning tagidan **.form-text** klassidan foydalanib yaratish mumkin

```
<label for="password-input" class="form-label">Parol</label>
<input type="password" id="password-input" class="form-control" aria-describedby="password-help">
<div id="password-help" class="form-text">
  Parol 8-20 simvol uzunligida bo'lib, xarflar va sonlardan qo'shilmasidan tashkil topgan bo'lishi kerak
</div>
```

Disabled inputs



Form uchun **disabled** ko'rinishini berish uchun **disabled** attributidan foydalanish mumkin

```
<input class="form-control" id="disabled-input" type="text" placeholder="Ma'lumot kiritishning imkoniy yo'q" disabled>
```

Forms

Bootstrap's form controls expand on our Rebooted form styles with classes. Use these classes to opt into their customized displays for a more consistent rendering across browsers and devices. Be sure to use an appropriate type attribute on all inputs (e.g., email for email address or number

<https://getbootstrap.com/docs/5.0/forms/overview/>



▼ Form control



<input> va **<textarea>** uchun style berishda **.form-control** klassidan foydalaniladi

```
<div class="mb-3">
  <label for="email-input" class="form-label">Email manzil</label>
  <input type="email" class="form-control" id="email-input" placeholder="usamigjonov@gmail.com">
</div>
<div class="mb-3">
  <label for="example-textarea" class="form-label">Textarea uchun misol</label>
  <textarea class="form-control" id="example-textarea" rows="3"></textarea>
</div>
```

O'lchov (Sizing)

```
<input class="form-control form-control-lg" type="text" placeholder=".form-control-lg" aria-label=".form-control-lg uchun misol">
<input class="form-control" type="text" placeholder="Default input" aria-label="default uchun misol">
<input class="form-control form-control-sm" type="text" placeholder=".form-control-sm" aria-label=".form-control-sm uchun misol">
```

Fayl yuklash (file input)

```
<label for="file-input" class="form-label">Fayl yuklash uchun misol</label>
<input class="form-control" type="file" id="file-input">
```

Rang tanlagich (Color picker)

```
<label for="color-input" class="form-label">Rang tanlagich</label>
<input type="color" class="form-control form-control-color" id="color-input" value="#563d7c" title="Rang tanlang">
```

Form controls

Set heights using classes like `.form-control-lg` and `.form-control-sm`. Add the disabled boolean attribute on an input to give it a grayed out appearance and remove pointer events. Add the readonly boolean attribute on an input to prevent modification of the input's value. Read-only

<https://getbootstrap.com/docs/5.0/forms/form-control/>

