

Homework 1

Problem 1:

1. Three accuracies for 1A, 1B, 1D

- a) Part 1A: 74.31373%
- b) Part 1B: 75.88235%
- c) Part 1D: 77.45098%

2. Screenshot of code:

- a) Test-Train Split:

```

29 # extract train data by randomly choosing 80% from origin dataset
30 train_index <- createDataPartition(y=input_y, p=.8, list=FALSE)

```

b) Probability Calculations:

```

43 # use a normal distribution to model distributions
44 # calculate mean and standard deviation
45 train_x_positive_mean <- sapply(train_x_positive, mean, na.rm=TRUE)
46 train_x_negative_mean <- sapply(train_x_negative, mean, na.rm=TRUE)
47
48 train_x_positive_sd <- sapply(train_x_positive, sd, na.rm=TRUE)
49 train_x_negative_sd <- sapply(train_x_negative, sd, na.rm=TRUE)
50
51 # calculate log probability
52 train_x_positive_offset <- t(t(train_x) - train_x_positive_mean)
53 train_x_positive_scale <- t(t(train_x_positive_offset) / train_x_positive_sd)
54 train_x_positive_square <- apply(train_x_positive_scale, c(1, 2), function(x)x^2)
55 train_x_positive_log_prob <- -(1/2)*rowSums(train_x_positive_square, na.rm=TRUE) - sum(log(train_x_positive_sd))
56
57 train_x_negative_offset <- t(t(train_x) - train_x_negative_mean)
58 train_x_negative_scale <- t(t(train_x_negative_offset) / train_x_negative_sd)
59 train_x_negative_square <- apply(train_x_negative_scale, c(1, 2), function(x)x^2)
60 train_x_negative_log_prob <- -(1/2)*rowSums(train_x_negative_square, na.rm=TRUE) - sum(log(train_x_negative_sd))
61

```

c) Evaluations:

```

74 # calculate log probability
75 test_x_positive_offset <- t(t(test_x) - train_x_positive_mean)
76 test_x_positive_scale <- t(t(test_x_positive_offset) / train_x_positive_sd)
77 test_x_positive_square <- apply(test_x_positive_scale, c(1, 2), function(x)x^2)
78 test_x_positive_log_prob <- -(1/2)*rowSums(test_x_positive_square, na.rm=TRUE) - sum(log(train_x_positive_sd))
79
80 test_x_negative_offset <- t(t(test_x) - train_x_negative_mean)
81 test_x_negative_scale <- t(t(test_x_negative_offset) / train_x_negative_sd)
82 test_x_negative_square <- apply(test_x_negative_scale, c(1, 2), function(x)x^2)
83 test_x_negative_log_prob <- -(1/2)*rowSums(test_x_negative_square, na.rm=TRUE) - sum(log(train_x_negative_sd))
84
85 # predict labels
86 test_predict_y <- test_x_positive_log_prob > test_x_negative_log_prob
87
88 # calculate test accuracy
89 test_correct_account <- test_predict_y == test_y
90 test_accuracy[iter] <- sum(test_correct_account)/(sum(test_correct_account)+sum(!test_correct_account))
91

```

Problem 2:

3.

a) Table of accuracies for all 12 cases:

Case	1	2	3	4
Accuracy	55.560%	69.850%	83.410%	74.330%
Case	5	6	7	8
Accuracy	72.705%	67.885%	96.115%	94.075%
Case	9	10	11	12
Accuracy	78.105%	68.880%	97.190%	95.285%

b) Screenshot of Kaggle


shuyuel2_1.csv 7 hours ago by Shuyue Lai add submission details	0.55560	✓
shuyuel2_2.csv 3 hours ago by Shuyue Lai add submission details	0.69850	✓
shuyuel2_3.csv 7 hours ago by Shuyue Lai add submission details	0.83410	✓
shuyuel2_4.csv 3 hours ago by Shuyue Lai add submission details	0.74330	✓
shuyuel2_5.csv 2 hours ago by Shuyue Lai add submission details	0.72705	✓
shuyuel2_6.csv 2 hours ago by Shuyue Lai add submission details	0.67885	✓
shuyuel2_7.csv 2 hours ago by Shuyue Lai add submission details	0.96115	✓
shuyuel2_8.csv 2 hours ago by Shuyue Lai add submission details	0.94075	✓
shuyuel2_9.csv 2 hours ago by Shuyue Lai add submission details	0.78105	✓
shuyuel2_10.csv 2 hours ago by Shuyue Lai add submission details	0.68880	✓
shuyuel2_11.csv 3 minutes ago by Shuyue Lai add submission details	0.97190	✓
shuyuel2_12.csv 2 hours ago by Shuyue Lai add submission details	0.95285	✓

c) A brief explanation of which model is better and why:


- According to the result, Bernoulli Naïve Bayes is better than Gaussian Naïve Bayes, because Bernoulli distribution works better in discrete cases which is MNIST acts.
- According to the result, Random Forest Classifier works better with larger number of trees and larger maximum depth.

4. 40 mean images (4 * 10 of part 2A)

a) Case 1: Gaussian + Untouched




b) Case 2: Gaussian + Stretched



c) Case 3: Bernoulli + Untouched



d) Case 4: Bernoulli + Stretched



5. Screenshot of code:

a) Library:

```

import csv
import numpy as np
import skimage.transform
from PIL import Image

from sklearn.naive_bayes import GaussianNB
from sklearn.naive_bayes import BernoulliNB
from sklearn.ensemble import RandomForestClassifier

```

b) Evaluations:

```

# Gaussian Naive Bayes Classifier
def gaussianNaiveBayes(train_input_x, train_input_y, test_input_x):
    classifier = GaussianNB()
    classifier.fit(train_input_x, train_input_y.ravel())

    test_output_y = classifier.predict(test_input_x)
    return test_output_y

# Bernoulli Naive Bayes Classifier
def bernoulliNaiveBayes(train_input_x, train_input_y, test_input_x):
    classifier = BernoulliNB()
    classifier.fit(train_input_x, train_input_y.ravel())

    test_output_y = classifier.predict(test_input_x)
    return test_output_y

# Random Forest Classifier
def randomForest(num_tree, max_depth, train_input_x, train_input_y, test_input_x):
    classifier = RandomForestClassifier(n_estimators=num_tree, criterion='entropy', max_depth=max_depth)
    classifier.fit(train_input_x, train_input_y)

    test_output_y = classifier.predict(test_input_x)
    return test_output_y

## EXECUTE
# 1. GAUSSIAN + UNTOUCHED
test_output_y = gaussianNaiveBayes(train_input_x, train_input_y, test_input_x)
writeCsvFile("shuyuel2_1.csv", test_output_y)

test_output_y = np.array(test_output_y).astype(float)
meanImage(test_input_x, test_output_y, 28, "shuyuel2_1")

# 2. GAUSSIAN + STRETCHED
test_output_y = gaussianNaiveBayes(train_input_x_stretched, train_input_y, test_input_x_stretched)
writeCsvFile("shuyuel2_2.csv", test_output_y)

test_output_y = np.array(test_output_y).astype(float)
meanImage(test_input_x_stretched, test_output_y, 20, "shuyuel2_2")

# 3. BERNOULLI + UNTOUCHED
test_output_y = bernoulliNaiveBayes(train_input_x, train_input_y, test_input_x)
writeCsvFile("shuyuel2_3.csv", test_output_y)

test_output_y = np.array(test_output_y).astype(float)
meanImage(test_input_x, test_output_y, 28, "shuyuel2_3")

# 4. BERNOULLI + STRETCHED
test_output_y = bernoulliNaiveBayes(train_input_x_stretched, train_input_y, test_input_x_stretched)
writeCsvFile("shuyuel2_4.csv", test_output_y)

test_output_y = np.array(test_output_y).astype(float)
meanImage(test_input_x_stretched, test_output_y, 20, "shuyuel2_4")

# 5. 10 TREES + 4 DEPTH + UNTOUCHED
test_output_y = randomForest(10, 4, train_input_x, train_input_y, test_input_x)
writeCsvFile("shuyuel2_5.csv", test_output_y)

# 6. 10 TREES + 4 DEPTH + STRETCHED
test_output_y = randomForest(10, 4, train_input_x_stretched, train_input_y, test_input_x_stretched)
writeCsvFile("shuyuel2_6.csv", test_output_y)

```