

Assignment Networking Fundamentals & Network Simulation Tools



Submitted by:

Abdullah

Reg No NETB01-6847

Supervised by:

Network Administrator Crypto

Department of Network Administrator

IT Simplera Solutions Institute

1. INTRODUCTION

Computer networking is a fundamental component of modern information technology, enabling communication and data exchange between computers, servers, smartphones, and other connected devices. Networks support essential services such as internet access, file sharing, cloud computing, resource management, and organizational communication. They play a crucial role in homes, businesses, educational institutions, and government organizations by ensuring efficient and reliable connectivity.

The objective of this assignment was to develop a strong understanding of basic networking concepts and gain practical experience with industry-standard network simulation tools, including Cisco Packet Tracer and GNS3. These platforms provide a virtual environment for designing, configuring, testing, and troubleshooting network infrastructures without requiring physical networking equipment.

As part of this task, a simple Local Area Network (LAN) topology was created and configured in both Cisco Packet Tracer and GNS3. Static IP addresses were assigned to the connected devices, and network connectivity was verified using the ping command. This hands-on activity enhanced my understanding of network design, IP addressing, connectivity testing, and troubleshooting while strengthening my practical networking skills.

2. OBJECTIVES OF THE ASSIGNMENT

The primary objective of this assignment was to develop a solid foundation in computer networking by understanding the fundamental concepts that govern network communication and connectivity. It aimed to provide practical knowledge of commonly used networking devices and their roles within a network infrastructure.

Another important objective was to gain hands-on experience with industry-standard network simulation tools, specifically Cisco Packet Tracer and GNS3, and to become familiar with their interfaces, features, and applications. Through the implementation of a simple Local Area Network (LAN) topology, the assignment focused on developing practical skills in network design and configuration.

Additionally, the assignment sought to enhance understanding of IP addressing by configuring static IP addresses on network devices and verifying successful communication between hosts

using the ping utility. Finally, it aimed to strengthen troubleshooting abilities and technical documentation skills, which are essential competencies for network administrators and IT professionals.

3. FUNDAMENTAL NETWORKING CONCEPTS

3.1 COMPUTER NETWORK

A computer network is a system of interconnected devices that are linked together to facilitate the exchange of data, communication, and resource sharing. These devices may include computers, servers, printers, smartphones, and other network-enabled equipment. Through networking, users can access information, share files, utilize common resources, and communicate efficiently regardless of their physical location.

Computer networks have become an essential part of modern society and are widely used in residential, educational, commercial, and industrial environments. From accessing the internet at home to managing large-scale enterprise operations, networks play a crucial role in supporting daily activities and business processes.

Common examples of computer networks include home networks, educational institution networks, corporate networks, and the global Internet. The implementation of networking offers numerous advantages, such as efficient resource sharing, improved communication, centralized administration, remote accessibility, enhanced collaboration, and reduced operational costs.

3.2 TYPES OF NETWORKS

Computer networks can be categorized based on their geographical coverage and scale. The most common types are Local Area Networks (LAN), Metropolitan Area Networks (MAN), and Wide Area Networks (WAN).

LOCAL AREA NETWORK (LAN)

A Local Area Network (LAN) is a network that connects devices within a limited geographical area, such as a home, office, laboratory, school, or university campus. LANs are typically owned and managed by a single organization or individual and are known for their high-speed communication and efficient performance.

The key characteristics of a LAN include fast data transmission rates, low latency, simplified management, enhanced security, and cost-effective deployment. Due to these advantages, LANs are the most commonly implemented type of network in modern computing environments.

METROPOLITAN AREA NETWORK (MAN)

A Metropolitan Area Network (MAN) is designed to interconnect multiple Local Area Networks within a city or metropolitan region. It provides broader coverage than a LAN while maintaining relatively high communication speeds. MANs are commonly used by large organizations, universities, government institutions, and service providers to connect multiple locations within the same city.

WIDE AREA NETWORK (WAN)

A Wide Area Network (WAN) spans large geographical areas and is capable of connecting networks across cities, countries, and even continents. WANs utilize various communication technologies, including leased lines, fiber-optic connections, and satellite links, to facilitate long-distance communication.

The most prominent example of a WAN is the Internet, which serves as the world's largest network, connecting billions of devices globally. WANs play a critical role in enabling global communication, cloud services, remote access, and international business operations.

4. NETWORKING DEVICES

Networking devices are specialized hardware components that facilitate communication, data transmission, and resource sharing within a network. Each device performs a specific function and contributes to the overall operation and efficiency of the network infrastructure.

4.1 SWITCH

A switch is one of the most commonly used networking devices in Local Area Networks (LANs). Operating primarily at the Data Link Layer (Layer 2) of the OSI model, a switch is responsible for connecting multiple devices within the same network and enabling efficient communication between them.

Unlike traditional hubs, a switch intelligently learns and stores the Media Access Control (MAC) addresses of connected devices in its MAC address table. By identifying the destination device, it

forwards data only to the intended recipient rather than broadcasting it to all devices. This improves network performance, reduces unnecessary traffic, and minimizes network collisions.

4.2 ROUTER

A router is a networking device that operates at the Network Layer (Layer 3) of the OSI model. Its primary purpose is to connect different networks and determine the most efficient path for data packets to travel between them.

Routers play a vital role in enabling communication between local networks and external networks such as the Internet. They analyze destination IP addresses, make routing decisions, and forward packets accordingly. In modern networks, routers also provide additional services such as Network Address Translation (NAT), traffic management, and security features.

4.3 HUB

A hub is a basic networking device used to connect multiple devices within a network segment. Unlike a switch, a hub does not possess the capability to identify destination devices or maintain a MAC address table. Instead, it broadcasts all incoming data to every connected device regardless of the intended recipient.

Due to its inefficient method of data transmission and increased likelihood of network collisions, hubs have largely been replaced by switches in modern networking environments. However, understanding their operation remains important for learning the evolution of networking technologies.

4.4 END DEVICES

End devices are the devices that act as the source or destination of data within a network. These devices enable users to access network services, communicate with other systems, and utilize shared resources.

Common examples of end devices include desktop computers, laptops, servers, smartphones, tablets, printers, and network storage devices. End devices are essential components of any network because they generate, receive, and process the information being transmitted across the network infrastructure.

5. OSI REFERENCE MODEL

The Open Systems Interconnection (OSI) Model is a universally recognized networking framework that illustrates how data is transmitted between devices across a network. Developed by the **International Organization for Standardization (ISO)**, the model divides the communication process into seven interconnected layers, each responsible for performing a specific set of functions. By organizing network operations into distinct layers, the OSI model provides a structured approach to understanding, designing, and troubleshooting network communications.

Layer	Name	Primary Function
7	Application	Provides network services to end-user applications
6	Presentation	Formats, encrypts, and translates data
5	Session	Establishes and manages communication sessions
4	Transport	Ensures reliable and efficient data delivery
3	Network	Handles logical addressing and packet routing
2	Data Link	Manages frame transmission and MAC addressing
1	Physical	Transmits raw binary data through physical media

At the highest level, the **Application Layer** acts as the point of interaction between users and network services, supporting applications such as web browsers, email clients, and file-sharing platforms. The **Presentation Layer** ensures that data is properly formatted, encrypted, and compressed so that it can be accurately interpreted by the receiving system. The **Session Layer** is responsible for establishing, maintaining, and terminating communication sessions between devices.

The **Transport Layer** plays a crucial role in guaranteeing reliable data transmission by managing segmentation, flow control, and error recovery mechanisms. The **Network Layer** determines the optimal path for data packets by utilizing logical addressing schemes such as IP addresses and routing protocols. The **Data Link Layer** facilitates node-to-node communication through the use of physical addresses (MAC addresses) and frame management. Finally, the **Physical Layer** represents the hardware and transmission media responsible for carrying digital signals across the network.

The OSI model serves as a fundamental blueprint for network communication and is widely used by network engineers and administrators to analyze network behavior and diagnose connectivity issues. By breaking the communication process into well-defined layers, the model simplifies complex networking operations and provides a systematic methodology for identifying and resolving network-related problems.

.

6. TCP/IP MODEL

The **Transmission Control Protocol/Internet Protocol (TCP/IP) Model** is the fundamental communication framework that powers modern computer networks and the Internet. Unlike the OSI model, which is primarily a theoretical reference model, the TCP/IP model is a practical architecture that is widely implemented in real-world networking environments. It defines how data is transmitted, routed, and received across interconnected networks.

The TCP/IP model consists of four layers, each responsible for specific communication functions:

1. **Application Layer**
2. **Transport Layer**
3. **Internet Layer**
4. **Network Access Layer**

The **Application Layer** provides network services directly to end-user applications such as web browsers, email clients, and file transfer programs. The **Transport Layer** ensures reliable communication between devices and manages data flow using protocols such as TCP and UDP. The **Internet Layer** is responsible for logical addressing and routing, ensuring that data packets reach their intended destinations. The **Network Access Layer** handles the physical transmission of data across network media and facilitates communication between devices on the same network.

Several important protocols operate within the TCP/IP model, including:

- **HTTP (Hypertext Transfer Protocol)** – Used for accessing websites.
- **HTTPS (Hypertext Transfer Protocol Secure)** – Provides encrypted web communication.
- **FTP (File Transfer Protocol)** – Used for transferring files between systems.
- **SMTP (Simple Mail Transfer Protocol)** – Responsible for email transmission.

- **TCP (Transmission Control Protocol)** – Ensures reliable and ordered data delivery.
- **UDP (User Datagram Protocol)** – Provides faster communication with minimal overhead.
- **IP (Internet Protocol)** – Handles addressing and routing of packets across networks.

The TCP/IP model serves as the foundation of modern networking and enables billions of devices worldwide to communicate efficiently over the Internet.

7. IP ADDRESSING

IP addressing is a fundamental concept in computer networking that enables devices to identify and communicate with one another across a network. Every device connected to a network must possess a unique IP address, which acts as its logical identifier. Without IP addressing, data packets would not be able to locate their intended destination.

IPV4 ADDRESSING

Internet Protocol Version 4 (IPv4) is the most widely used addressing standard in computer networks. An IPv4 address consists of **32 bits** and is represented in dotted-decimal notation, divided into four octets separated by periods.

Example:

192.168.1.10

Each IPv4 address contains two important components:

- **Network Portion** – Identifies the network.
- **Host Portion** – Identifies a specific device within that network.

SUBNET MASK

A subnet mask is used to distinguish the network portion of an IP address from the host portion. It enables devices to determine whether the destination device is located on the same network or a different network.

Example Subnet Mask:

255.255.255.0

For the IP address **192.168.1.10/24**, the addressing information is as follows:

- **Network Address:** 192.168.1.0
- **Broadcast Address:** 192.168.1.255

- **Valid Host Range:** 192.168.1.1 – 192.168.1.254

The **Network Address** identifies the entire network and cannot be assigned to a host device. The **Broadcast Address** is used to send data to all devices within the network simultaneously. The **Valid Host Range** represents the set of usable IP addresses that can be assigned to network devices such as computers, servers, printers, and routers.

A thorough understanding of IP addressing and subnetting is essential for network administrators, as these concepts form the basis of network design, device communication, troubleshooting, and efficient network management.

8. CISCO PACKET TRACER OVERVIEW

Cisco Packet Tracer is a widely used network simulation software developed by Cisco Systems for learning, designing, and testing computer networks in a virtual environment. It provides students, network administrators, and IT professionals with a practical platform to build network topologies, configure devices, and analyze network behavior without requiring physical networking equipment.

The software is extensively utilized in networking education and certification programs, particularly for CCNA studies, as it enables users to gain hands-on experience with routing, switching, IP addressing, and network troubleshooting. By simulating real-world networking scenarios, Cisco Packet Tracer helps bridge the gap between theoretical concepts and practical implementation.

Key Features

Cisco Packet Tracer offers a variety of features that support network learning and experimentation, including:


- Virtual network design and topology creation
- Configuration of routers, switches, and end devices
- Routing and switching simulation
- Packet flow analysis and monitoring
- Network troubleshooting and testing
- Support for IoT and wireless networking simulations

LAN TOPOLOGY DESIGN AND IMPLEMENTATION

As part of this assignment, a simple **Local Area Network (LAN)** topology was designed and implemented to demonstrate basic network communication between multiple devices within the same network. The topology consisted of **one switch and three personal computers (PCs)** connected through Ethernet cables. The switch acted as the central networking device, facilitating communication among all connected hosts and enabling efficient data exchange within the local network.

The purpose of creating this topology was to gain practical experience in network design, device connectivity, IP address configuration, and connectivity verification. By connecting multiple devices to a switch, it becomes possible to simulate a small office or home network environment where users can communicate and share resources over a common network infrastructure.

DEVICES USED & IP ADDRESS CONFIGURATION



LAN Topology in Packet Tracer

The following devices were utilized to construct the LAN topology:

Device	IP Address	Subnet Mask
PC0	192.168.10.1	255.255.255.0
PC1	192.168.10.2	255.255.255.0
PC2	192.168.10.3	255.255.255.0
Layer 2 Switch		

To ensure successful communication, each computer was assigned a unique IPv4 address belonging to the same network segment.

All devices were configured within the **192.168.1.0/24** network. Since the computers shared the same network address and subnet mask, they were able to communicate directly without requiring a router.

WORKING PRINCIPLE OF THE TOPOLOGY

When a device sends data to another device on the same network, the switch examines the destination MAC address and forwards the data frame only to the appropriate port. This intelligent forwarding process minimizes unnecessary network traffic and improves overall network performance.

As communication occurs, the switch dynamically builds a MAC address table by learning the addresses of connected devices. This allows the switch to deliver frames efficiently and maintain reliable communication between hosts.

CONNECTIVITY TESTING

After configuring the IP addresses and establishing the physical connections, network connectivity was verified using the **ping** command. Ping tests were successfully performed between all three computers, confirming that the devices could communicate with one another through the switch. The successful results indicated correct IP configuration, proper switch operation, and successful end-to-end communication within the network.

PC0 TO PC1 CONNECTIVITY TESTING

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.10.2

Pinging 192.168.10.2 with 32 bytes of data:

Reply from 192.168.10.2: bytes=32 time<1ms TTL=128
Reply from 192.168.10.2: bytes=32 time<1ms TTL=128
Reply from 192.168.10.2: bytes=32 time<1ms TTL=128
Reply from 192.168.10.2: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.10.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

Testing connectivity

9. GNS3 OVERVIEW

GNS3 (Graphical Network Simulator-3) is a professional network emulation platform widely used by network engineers, students, and cybersecurity professionals to design, test, and troubleshoot network infrastructures in a virtual environment. It enables users to create realistic network topologies by integrating virtual and physical devices, providing hands-on experience without requiring expensive networking hardware.

Key Features:

- Provides realistic network emulation that closely replicates real-world networking environments.
- Supports Cisco IOS and other vendor operating systems for advanced network configuration and testing.
- Integrates with virtual machines such as VMware and VirtualBox to enhance lab functionality.
- Allows the creation of complex and scalable network topologies for enterprise-level simulations.
- Offers packet capture and traffic analysis capabilities for troubleshooting and performance monitoring.
- Supports cybersecurity and penetration-testing labs for practical learning and research.
- Enables network professionals to test configurations before deploying them in production environments.


LAN TOPOLOGY DESIGN AND IMPLEMENTATION USING GNS3

As part of this assignment, a simple Local Area Network (LAN) topology was designed and implemented using **GNS3 (Graphical Network Simulator-3)** to demonstrate basic networking concepts and device communication in a virtual environment. The topology consisted of one Ethernet switch and three Virtual PCs (VPCS) interconnected through virtual Ethernet links. The switch served as the central networking device, enabling communication and data exchange among all connected hosts within the network.

The primary objective of creating this topology was to gain practical experience in network simulation, topology design, IP address configuration, and network troubleshooting using an

industry-standard network emulation platform. GNS3 provided a realistic environment for testing network configurations without requiring physical networking equipment.

DEVICES USED & IP ADDRESS CONFIGURATION



LAN Topology Configuration in GNS3

The following devices were used to build the LAN topology in GNS3:

Device	IP Address	Subnet Mask
VPCS1	192.168.10.1	255.255.255.0
VPCS2	192.168.10.2	255.255.255.0
VPCS3	192.168.10.3	255.255.255.0
Ethernet Switch	N/A	N/A

Each virtual PC was assigned a unique IPv4 address within the same network range. All devices were configured in the **192.168.10.0/24** network, allowing direct communication without the need for routing services. The common subnet mask ensured that all hosts belonged to the same broadcast domain.

A screenshot of a PuTTY terminal window titled "PC2 - PuTTY". The terminal shows a series of commands and responses. The prompt "PC2>" is repeated four times. Then, the command "ip 192.168.10.2 255.255.255.0" is entered. The response is "Checking for duplicate address...". Below that, the output "PC1 : 192.168.10.2 255.255.255.0" is displayed. Finally, the prompt "PC2>" is shown with a green cursor.

```
PC2>
PC2>
PC2>
PC2>
PC2> ip 192.168.10.2 255.255.255.0
Checking for duplicate address...
PC1 : 192.168.10.2 255.255.255.0
PC2> █
```

Assigning IP Address to PC

WORKING PRINCIPLE OF THE TOPOLOGY

The Ethernet switch operates at the Data Link Layer (Layer 2) of the OSI model. When a device transmits data, the switch examines the destination MAC address contained in the Ethernet frame and forwards the traffic only to the appropriate destination port.

As communication takes place, the switch dynamically learns the MAC addresses of connected devices and stores them in its MAC address table. This intelligent forwarding mechanism reduces unnecessary traffic, improves network efficiency, and ensures reliable communication between hosts connected to the network.

The virtual environment provided by GNS3 accurately simulates the behavior of real networking devices, enabling users to perform configuration, testing, and troubleshooting tasks in a controlled laboratory setting.

CONNECTIVITY TESTING

After completing the IP address configuration and establishing the virtual connections, network connectivity was verified using the **ping** command. Ping tests were conducted between all three virtual PCs to ensure successful communication across the network.


The successful ping responses confirmed that:

- End-to-end communication had been established.

VPCS1 TO VPCS2 CONNECTIVITY TESTING

A connectivity test was performed from VPCS1 (192.168.10.1) to VPCS2 (192.168.10.2) using the ping utility. The test returned successful replies from the destination host, indicating that packets were transmitted and received without any loss.

The successful result verified proper network configuration, correct switch operation, and reliable communication between the two devices within the LAN environment.



```
PC1>
PC1>
PC1>
PC1>
PC1> ping 192.168.10.2
84 bytes from 192.168.10.2 icmp_seq=1 ttl=64 time=4.081 ms
84 bytes from 192.168.10.2 icmp_seq=2 ttl=64 time=1.780 ms
84 bytes from 192.168.10.2 icmp_seq=3 ttl=64 time=2.177 ms
84 bytes from 192.168.10.2 icmp_seq=4 ttl=64 time=2.013 ms
84 bytes from 192.168.10.2 icmp_seq=5 ttl=64 time=1.395 ms
PC1> █
```

Testing Connectivity

14. TROUBLESHOOTING PROCESS

The following checks were performed:

- Verified cable connections.
- Confirmed IP address configuration.
- Ensured subnet masks matched.
- Checked switch connectivity.
- Repeated ping testing.

These steps helped identify and resolve potential connectivity issues.

17. CONCLUSION

This assignment provided a strong foundation in computer networking and network simulation technologies. Using Cisco Packet Tracer and GNS3, a simple LAN topology was successfully designed, configured, and tested. Static IP addressing was implemented, and successful ping tests confirmed end-to-end connectivity. The practical experience gained during this assignment

improved my understanding of network infrastructure, troubleshooting methodologies, and industry-standard networking tools. These skills form an essential base for advanced studies in network administration, routing and switching, network security, and enterprise networking.