

SearchSploit — Practical Tool Guide

Search Exploit-DB by product/version/CVE, read code, copy a local working copy, and connect the results to Nmap XML.

➤ Abdullah Nasser Almsan — Personal Pentest Reference

Usage note: The goal is to search and validate - not to run a random exploit.

BANNER

Product / Version

SEARCH

Find candidates

READ

Read the code

MATCH

Validate applicability

Contents

1. Concept and updating
2. Search by service and version
3. CVE and filtering
4. Read and copy an exploit
5. Connect SearchSploit with Nmap
6. Short workflow

1. Concept and updating

SearchSploit searches a local copy of Exploit-DB offline.

KALI TERMINAL — Help

```
searchsploit -h
```

KALI TERMINAL — Update Exploit-DB data

```
searchsploit -u
```

On Kali, updates can also depend on the exploitdb package version.

2. Search by service and version

Use the same product and version wording that Nmap/service fingerprinting reported.

KALI TERMINAL — Broad search

```
searchsploit apache 2.4.49
```

KALI TERMINAL — Title-only search to reduce false positives

```
searchsploit -t apache 2.4.49
```

KALI TERMINAL — Strict version search

```
searchsploit -s apache 2.4.49
```

Strict search disables fuzzy version-range behavior; it is useful when you want an explicit version match.

KALI TERMINAL — Exact and ordered title match

```
searchsploit -e "OpenSSH 7.2"
```

Product banners do not always match Exploit-DB titles literally. Start broad, then narrow with `-t` or `-s`.

3. CVE and filtering

KALI TERMINAL — Search by CVE

```
searchsploit --cve 2021-41773
```

KALI TERMINAL — Exclude DoS/PoC

```
searchsploit linux kernel 3.2 --exclude="(PoC)|/dos/"
```

KALI TERMINAL — JSON for automation

```
searchsploit -j apache 2.4.49 | jq
```

4. Read and copy an exploit

Note: Do not execute an exploit before reading the code and requirements.

KALI TERMINAL — Show full path from EDB-ID

```
searchsploit -p [EDB_ID]
```

KALI TERMINAL — Open for reading

```
searchsploit -x [EDB_ID]
```

KALI TERMINAL — Copy to the working directory

```
searchsploit -m [EDB_ID]
```

A generic exploit may require changes to target/port/path, may not match your version, or may crash the service. Read it first.

5. Connect SearchSploit with Nmap

KALI TERMINAL — Save Nmap XML

```
nmap -Pn -sV -oX nmap.xml [TARGET]
```

KALI TERMINAL — Feed XML to SearchSploit

```
searchsploit --nmap nmap.xml
```

Note: These are research leads, not proof the target is vulnerable. Manually review version, CVE, and preconditions.

6. Short workflow

Step	Tool	Action
1	Nmap	Get Product + Version.
2	SearchSploit	Search by product and version.
3	Filter	Exclude DoS and narrow by title/strict version.
4	Read	Open the exploit and understand its requirements.
5	Validate	Confirm version, OS, architecture, and preconditions.
6	Lab only	Run only in an authorized environment.

Prepared as a quick-reference companion to the canonical Arabic guide. Use only in labs or systems you are explicitly authorized to test.

References:

<https://www.exploit-db.com/searchsploit>