

enum4linux-ng — Practical Tool Guide

Windows/Samba enumeration for users, groups, shares, policy, OS information, RID cycling, and authenticated checks.

➤ Abdullah Nasser Almsan — Personal Pentest Reference

Usage note: Best used after Nmap confirms SMB/NetBIOS in the authorized scope.

NMAP

Is SMB present?

ENUM

Users / Shares

CREDS

Repeat with auth

VERIFY

Open resources

Contents

1. When to use it
2. Important options
3. Focused enumeration
4. Credentials
5. Saving results
6. SMB workflow

1. When to use it

Use enum4linux-ng when Nmap shows SMB/NetBIOS or Windows/Samba and you need focused enumeration.

KALI TERMINAL — Initial SMB scan

```
nmap -Pn -sV -p139,445 [TARGET]
```

KALI TERMINAL — Broad enumeration

```
enum4linux-ng -A [TARGET]
```

KALI TERMINAL — Broad scan without NetBIOS lookup

```
enum4linux-ng -As [TARGET]
```

2. Important options

Option	Meaning	When to use it
-U	Users through RPC	Enumerate users.
-G	Groups through RPC	Enumerate groups.
-Gm	Groups + members	See group membership.
-S	Shares through RPC	Enumerate shares.
-C	Services through RPC	Services, when supported.
-P	Password policy	Review password policy.
-O	OS information	System information.
-L	LDAP/LDAPS domain info	Useful with domain controllers.
-R	RID cycling	Not included by default in -A.
-N	NetBIOS names lookup	NetBIOS/workgroup naming.

3. Focused enumeration

KALI TERMINAL — Users + Shares

```
enum4linux-ng -U -S [TARGET]
```

KALI TERMINAL — Users + Groups + Policy

```
enum4linux-ng -U -G -P [TARGET]
```

KALI TERMINAL — RID cycling when needed

```
enum4linux-ng -R [TARGET]
```

Note: RID cycling increases queries and can be noisy. Do not run it automatically if -A already gave the information you need.

4. Credentials

If you obtain an authorized lab account, repeat enumeration with authentication.

KALI TERMINAL — Username/password

```
enum4linux-ng [TARGET] -u [USER] -p '[PASS]'
```

KALI TERMINAL — Domain supplied manually

```
enum4linux-ng [TARGET] -w [DOMAIN] -u [USER] -p '[PASS]'
```

KALI TERMINAL — NT hash if authorized and available

```
enum4linux-ng [TARGET] -u [USER] -H [NTHASH]
```

5. Saving results

KALI TERMINAL — YAML

```
enum4linux-ng -A [TARGET] -oY enum-out
```

KALI TERMINAL — JSON

```
enum4linux-ng -A [TARGET] -oJ enum-out
```

KALI TERMINAL — All outputs

```
enum4linux-ng -A [TARGET] -oA enum-out
```

6. SMB workflow

Step	Tool	Goal
1	Nmap	Find 139/445 and service/version.
2	enum4linux-ng	Users, groups, shares, policy.
3	smbclient	Open a share when permitted.
4	Metasploit auxiliary	Additional scanning if needed.
5	SearchSploit/CVE	Only when version/evidence supports research.

Prepared as a quick-reference companion to the canonical Arabic guide. Use only in labs or systems you are explicitly authorized to test.

References:

<https://github.com/cddmp/enum4linux-ng>