

Impacket Essentials — SMB / PsExec / WMIExec / SecretsDump

Choose the right Impacket example/script and understand target syntax, credentials, hashes, and Kerberos-related options in Windows labs.

» Abdullah Nasser Almsan — Personal Pentest Reference

Usage note: Focused on common Impacket examples used in eJPT/Windows labs. Use only against authorized targets.

SMB

Discover / verify

AUTH

Credentials

EXEC

psexec / wmi

ACCESS

Least required access

Contents

1. What is Impacket here?
2. smbclient.py
3. psexec / wmiexec
4. secretsdump
5. Hashes / Kerberos syntax
6. Workflow

1. What is Impacket here?

Impacket is a collection of protocol libraries and example tools for Windows/network workflows. Command names can differ slightly between packages.

On newer Kali packages you may see `impacket-psexec` rather than `psexec.py`. The same applies to `impacket-wmiexec` and `impacket-secretsdump`.

KALI TERMINAL — Find available examples

```
compgen -c | grep impacket  
ls /usr/share/doc/python3-impacket/examples
```

2. smbclient.py

An SMB mini-shell from Impacket.

KALI TERMINAL — Connect

```
impacket-smbclient [DOMAIN]/[USER]:[PASS]@[TARGET]
```

KALI TERMINAL — Help

```
impacket-smbclient -h
```

If your goal is only share listing/browsing/get/put, the traditional smbclient can be simpler.

3. psexec / wmiexec

Remote command execution requires credentials and suitable permissions.

AUTHORIZED LAB — PsExec style

```
impacket-psexec [DOMAIN]/[USER]:[PASS]@[TARGET]
```

AUTHORIZED LAB — WMIExec style

```
impacket-wmiexec [DOMAIN]/[USER]:[PASS]@[TARGET]
```

AUTHORIZED LAB — Local account

```
impacket-wmiexec [TARGET]/[USER]:[PASS]@[TARGET]
```

Domain/local-account syntax varies by scenario; check -h if parsing fails.

Note: These tools execute remote commands. Use them only on a Windows lab or system you are explicitly authorized to test.

4. secretsdump

Used to extract credential material from an authorized system/file context.

KALI TERMINAL — Help first

```
impacket-secretsdump -h
```

AUTHORIZED LAB — Remote example

```
impacket-secretsdump [DOMAIN]/[USER]:[PASS]@[TARGET]
```

Note: SAM/LSA/NTDS access needs specific privileges and can expose credential material. Run only when the lab objective requires Credential Access, and collect no more than needed.

5. Hashes / Kerberos syntax

Option	Idea
-hashes LMHASH:NTHASH	Use an NTLM hash instead of a password when the scenario explicitly permits it.
-k	Kerberos authentication.
-no-pass	Do not prompt for password, often used with Kerberos/key material.
-dc-ip [IP]	Specify a domain controller for Kerberos-related tooling.

Note: Pass-the-Hash/Kerberos workflows are sensitive. Use them only in the dedicated authorized lab and after confirming the account and scope.

6. Workflow

Step	Decision	Meaning
1	Verify service	Nmap/SMB enumeration.
2	Validate creds	smbclient or NetExec.
3	Choose exec	psexec or wmiexec only if permission allows.
4	Need secrets?	secretsdump only when the lab objective requires it.
5	Record	Document host, account, and result.

Prepared as a quick-reference companion to the canonical Arabic guide. Use only in labs or systems you are explicitly authorized to test.

References:

<https://github.com/fortra/impacket>

<https://github.com/fortra/impacket/blob/master/examples/psexec.py>

<https://github.com/fortra/impacket/blob/master/examples/wmiexec.py>

<https://github.com/fortra/impacket/blob/master/examples/smbclient.py>