

NEXORA

Nexora Cloud Product Documentation

Document ID: NX-TECH-001 **Version:** 6.0 **Publication:** March 2, 2026 **Last updated:** September 14, 2026

Department: Engineering **Category:** Technical Documentation **Confidentiality:** Internal / Customer Technical **Applicable customers:** All

Fictional training dataset. All entities, people, locations, policies, prices and contact details are synthetic and created solely for RAG development.

Architecture Overview

Nexora Cloud uses a tenant-isolated application architecture with an API gateway, workspace services, asynchronous job workers, an event bus and encrypted object storage. The exact internal topology is not exposed to customers.

Layer	Responsibility	Customer-facing implication
API gateway	Authentication, routing and rate enforcement	Requests receive HTTP status and structured error codes
Workspace service	Users, roles and configuration	Changes are scoped to a workspace
Job workers	Long-running imports/exports	Jobs may complete asynchronously
Event bus	Webhook and internal event delivery	Events can be retried
Object storage	Encrypted file storage	Files follow plan-specific size limits

Account and Workspace Setup

Create an account

Register with an approved email domain, verify the address, accept the Terms of Service and create an organization account.

Create a workspace

Organization administrators select Create Workspace, enter a workspace name, choose a region from the available list and confirm the default security policy.

Roles

Role	Core capability
Owner	Billing, security and workspace administration
Admin	User and configuration administration
Member	Operational use without administrative controls
Viewer	Read-only access where permitted

Authentication

Cloud supports password authentication and plan-dependent SSO. API requests use bearer tokens. Tokens should be stored as secrets and rotated after suspected exposure.

Example header: Authorization: Bearer nx_live_example_token

API Usage

Property	Standard value
Base URL	https://api.nexora.example/v1
Rate limit	120 requests/minute per workspace
Burst	240 requests/minute for up to 30 seconds
Max file size	2 GB per file
Formats for export	CSV and JSON; scheduled exports on Business and Enterprise

Example request

GET /v1/workspaces/wsp_2041/users with Authorization: Bearer nx_live_example_token. A successful response returns a JSON object containing data, pagination and request_id fields.

Webhooks

Cloud webhooks notify customer endpoints about selected workspace events. Failed deliveries are retried up to five times over 30 minutes. Endpoints should respond with a 2xx status within 10 seconds.

For duplicate delivery protection, customers should treat event_id as an idempotency key.

Import and Export

CSV and JSON imports are supported for selected objects. Large imports are processed asynchronously. Business and Enterprise plans support scheduled exports.

If an import fails, the job record displays an error code and row reference where available. Do not retry blindly when an error indicates a schema mismatch.

Error Codes

Code	Meaning	Typical action
NX-401	Authentication failed	Rotate or verify token
NX-403	Permission denied	Check role and workspace scope
NX-409	Conflict	Refresh resource and retry with current version
NX-429	Rate limit exceeded	Honor Retry-After and reduce request rate
NX-413	Payload too large	Reduce file or request size
NX-422	Validation error	Correct field values
NX-500	Transient platform error	Retry with backoff; escalate if persistent

Configuration Example

A production integration should store the API token in a secret manager, set exponential backoff for 429 and 5xx responses, verify webhook signatures where enabled, and log request_id values for support escalation.