

CP-Figma-W3

Scenario

You are designing a **Simple Shopping App Prototype** with:

- Login screen
- Home screen
- Product Detail screen

Your goal is to make it **interactive and smart**, not just static screens.

Learning Goals Covered

Use **Triggers & Actions**

- Build **Prototyping Flows**
 - Apply **Smart Animate**
 - Create & bind **Variables**
 - Implement **Conditional Logic**
-

Activity Instructions

◆ STEP 0: Setup

You must have:

- At least **3 screens (frames)**:
 - Login
 - Home
 - Product Detail
- A **Button component**

👉 If missing, quickly duplicate/create.

CP-Figma-W3

◆ TASK 1: Prototyping Flow

 **Goal: Connect screens using correct triggers & actions**

Instructions:

1. Connect:
 - Login → Home
 - Home → Product Detail
2. Use:
 - Trigger: **On Click**
 - Action: **Navigate To**
3. Add:
 - A **Back button** on Product screen → return to Home
4. Add:
 - A **modal (overlay)** on Home (e.g., “Add to Cart” popup)

✅ Checkpoint:

- Can move forward and backward between screens
 - Overlay appears on click
-

◆ TASK 2: Smart Animate

 **Goal: Create smooth transition animation**

Instructions:

1. Duplicate Home screen → create **Detail Version**
2. Select a **product card**
3. In second screen:
 - Resize it to **full screen**
 - Keep **same layer name**

CP-Figma-W3

4. Connect:

- Home → Detail screen
- Animation: **Smart Animate**
- Duration: ~300–400ms
- Easing: Ease Out

✅ Checkpoint:

- Card smoothly expands (not jumps)

TASK 3 & TASK 4 → Figma Educational Access :

<https://www.figma.com/education/apply>

◆ TASK 3: Variables

🎯 Goal: Create interactive state (counter)

Instructions:

1. Create a **Number variable**:

- Name: quantity
- Default: 1

2. Add on screen:

- Text (for number)
- “+” button
- “-” button

3. Bind:

- Text → quantity

4. Interactions:

- “+” → quantity + 1
- “-” → quantity - 1
- Add condition: quantity > 0

CP-Figma-W3

✅ Checkpoint:

- Number updates live when clicking buttons
-

♦ TASK 4: Conditional Logic

🎯 Goal: Simulate form validation

Instructions:

1. Create Boolean variable:
 - isLoggedIn = false
2. On Login screen:
 - Clicking input field → set isLoggedIn = true
3. On Login button:
 - Add **Conditional Interaction**:
 - IF isLoggedIn = true → Go to Home
 - ELSE → Show error (or go to Error screen)

✅ Checkpoint:

- Two different outcomes from same button
-

GOOD LUCK 😊