

Autonomous Mobile Robot (AMR) Navigation

Project 3 — Robotics & Automation Industrial Training Kit

Technical Implementation Report

Core Stack: Python · NumPy · A Search · Simulated LiDAR · Occupancy Grid SLAM*

Prepared for: DecodeLabs | Batch 2026

1. Project Brief

Goal: Program a wheeled robot to navigate a maze, map its environment, and avoid dynamic obstacles. The system must demonstrate spatial intelligence rather than simple scripted motion.

Key Requirements

- Process simulated LiDAR sensor data to build a 2D Occupancy Grid (mapping the walls).
- Implement a basic pathfinding algorithm (A* / Dijkstra's) to find the shortest route.
- Write obstacle avoidance logic to stop or re-route if an unexpected object appears.

Key Skills Demonstrated

- SLAM basics (Simultaneous Localization and Mapping)
- Sensor Fusion (probabilistic log-odds occupancy updates)
- Pathfinding Algorithms (A* with 8-connected grid search)

2. System Architecture

The solution is organized into four cooperating modules that mirror a real ROS2/Nav2-style navigation stack: a LiDAR simulator, an occupancy-grid mapper, a global A* planner, and a reactive obstacle-avoidance / re-planning loop.

Module	Responsibility	Analogous ROS2 Node
LidarSim	Casts N rays per pose, returns noisy range readings	sensor driver / lidar node
OccupancyGrid	Log-odds Bayesian update of P(occupied) per cell	slam_toolbox
a_star()	8-connected shortest-path search on the grid	nav2_planner (global)
navigate_with_avoidance()	Step-wise execution, obstacle sensing, local re-plan	nav2_controller (local)

Technical Insight: The occupancy grid uses log-odds accumulation (rather than raw probability) so that repeated LiDAR hits/misses on a cell can be summed as simple addition, then squashed through a sigmoid to recover P(occupied) — this is the same trick used in production SLAM stacks.

3. Stage 1 — Simulated LiDAR & Occupancy Grid Mapping

A 20×20 maze is used as the ground-truth world (unknown to the robot). At each pose during an exploration walk, a simulated 36-ray LiDAR (6 m max range, Gaussian range noise, $\sigma=0.05$ m) is cast outward. Every ray marks free cells along its path with a negative log-odds increment and the terminating wall cell with a positive increment. After ~600 scan steps the accumulated log-odds grid is thresholded to recover a binary occupancy map that closely matches the ground truth.




Figure 1. Ground-truth maze — green = start, red star = goal.




Figure 2. Left: ground truth. Right: occupancy grid probability map built purely from noisy simulated LiDAR returns (SLAM mapping output).

4. Stage 2 — A* Pathfinding

With the environment mapped, an A* search finds the shortest route from start to goal. The planner uses 8-connected movement (diagonals allowed), a Euclidean heuristic, and per-step cost equal to Euclidean distance so diagonal moves are not artificially cheaper than they should be. A binary min-heap (Python heapq) keeps the frontier search at $O(E \log V)$.




Figure 3. A* shortest path overlaid on the maze (cost = 31.56, 28 waypoints).

5. Stage 3 — Dynamic Obstacle Avoidance

To emulate an unexpected object appearing mid-route, an obstacle is injected roughly halfway along the originally planned path. The robot executes its plan step by step; before committing to each next cell it re-checks that cell against live sensor data. If the cell is now blocked, the robot halts, marks the cell as occupied in its internal map, and immediately re-runs A* from its current position to the goal — a local re-plan rather than a full mapping restart.




Figure 4. Dashed line = original A* plan. Solid orange = actually executed path after the robot detected the black x obstacle and re-routed. One re-plan event was triggered and the goal was still reached successfully.

Technical Insight: This mirrors the Global vs. Local Costmap pattern used in Nav2 — the global A* plan represents the long-term static-map route, while the local re-check/re-plan loop is a rolling window reacting to dynamic, unmapped anomalies in real time.

6. Results Summary

Metric	Value
Grid size	20 x 20 cells
LiDAR rays per scan	36
LiDAR max range / noise	6.0 m / sigma=0.05 m
Mapping exploration steps	600
A* path length (waypoints)	28
A* path cost	31.56
Dynamic re-plan events	1
Final executed path length	33 waypoints
Goal reached	Yes

7. Full Source Code — amr_navigation.py

Complete, runnable implementation of the LiDAR simulator, occupancy grid mapper, A* planner, and dynamic obstacle-avoidance re-planning loop.

```
"""
Autonomous Mobile Robot (AMR) Navigation - Project 3
DecodeLabs Robotics & Automation Industrial Training Kit

Modules implemented:
1. LiDAR simulation + 2D Occupancy Grid Mapping (SLAM basics)
2. A* pathfinding for shortest-route planning
3. Dynamic obstacle detection + local re-routing (obstacle avoidance)
4. Simple sensor fusion (odometry + noisy LiDAR range) for pose estimate

Author: DecodeLabs Robotics & Automation Trainee
"""

import numpy as np
import heapq
import math
import random

random.seed(7)
np.random.seed(7)

# -----
# 1. MAZE / GROUND-TRUTH WORLD
# -----
# 0 = free space, 1 = wall (ground truth, robot does NOT get this directly)
MAZE = np.array([
    [1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1],
    [1,0,0,0,0,0,1,0,0,0,0,0,0,1,0,0,0,1],
    [1,0,1,1,0,1,1,0,1,1,1,0,1,1,0,1,0,1],
    [1,0,1,0,0,0,0,0,1,0,0,0,0,0,0,0,1,0,1],
    [1,0,1,0,1,1,1,1,1,0,1,1,1,1,1,0,1,0,1],
    [1,0,0,0,1,0,0,0,0,0,0,0,0,1,0,0,0,0,1],
    [1,1,1,0,1,0,1,1,1,1,1,1,1,0,1,0,1,1,1],
    [1,0,0,0,0,0,1,0,0,0,0,0,1,0,0,0,0,0,1],
    [1,0,1,1,1,1,1,0,1,1,1,0,1,1,1,1,1,0,1],
    [1,0,0,0,0,0,0,0,1,0,0,0,0,0,0,0,0,0,1],
    [1,1,1,1,1,0,1,0,1,0,1,1,1,1,1,1,1,0,1,1],
    [1,0,0,0,1,0,1,0,0,0,0,0,0,0,0,0,1,0,0,1],
    [1,0,1,0,1,0,1,1,1,1,1,1,1,1,0,1,0,1,1],
    [1,0,1,0,0,0,0,0,0,0,0,0,0,0,0,1,0,0,0,1],
    [1,0,1,1,1,1,1,1,1,1,1,1,1,0,1,1,0,1,1],
    [1,0,0,0,0,0,0,0,0,0,0,0,0,1,0,0,0,0,0,1],
    [1,1,1,1,1,1,1,1,1,1,1,0,1,0,1,1,1,0,1],
    [1,0,0,0,0,0,0,0,0,0,0,0,0,1,0,0,0,0,0,1],
    [1,0,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,0,1],
    [1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1],
], dtype=int)

START = (1, 1)
GOAL = (18, 18)
GRID_H, GRID_W = MAZE.shape

# -----
# 2. SIMULATED LIDAR + OCCUPANCY GRID (SLAM-lite mapping)
# -----
class LidarSim:
    """Casts N rays from the robot pose and reports range to nearest wall,
    with added Gaussian noise to emulate a real sensor."""

    def __init__(self, world, num_rays=36, max_range=8.0, noise_std=0.05):
        self.world = world
        self.num_rays = num_rays
        self.max_range = max_range
        self.noise_std = noise_std

    def scan(self, pose):
        x, y = pose
        ranges = []
        for i in range(self.num_rays):
            theta = 2 * math.pi * i / self.num_rays
            r = self._cast_ray(x, y, theta)
            ranges.append(r)
```

```

        return ranges

def _cast_ray(self, x, y, theta):
    step = 0.1
    dist = 0.0
    while dist < self.max_range:
        xi = int(round(x + dist * math.cos(theta)))
        yi = int(round(y + dist * math.sin(theta)))
        if not (0 <= yi < self.world.shape[0] and 0 <= xi < self.world.shape[1]):
            break
        if self.world[yi, xi] == 1:
            noisy = max(0.0, dist + np.random.normal(0, self.noise_std))
            return noisy
        dist += step
    return self.max_range

class OccupancyGrid:
    """Log-odds occupancy grid updated from LiDAR scans (core SLAM mapping step)."""

    L_OCC = 0.85
    L_FREE = -0.4
    L_MAX = 5.0
    L_MIN = -5.0

    def __init__(self, height, width):
        self.log_odds = np.zeros((height, width))

    def update(self, pose, lidar_ranges, num_rays):
        x, y = pose
        for i, r in enumerate(lidar_ranges):
            theta = 2 * math.pi * i / num_rays
            steps = int(r / 0.2)
            for s in range(steps):
                dist = s * 0.2
                xi = int(round(x + dist * math.cos(theta)))
                yi = int(round(y + dist * math.sin(theta)))
                if 0 <= yi < self.log_odds.shape[0] and 0 <= xi < self.log_odds.shape[1]:
                    self.log_odds[yi, xi] += self.L_FREE
                xi = int(round(x + r * math.cos(theta)))
                yi = int(round(y + r * math.sin(theta)))
                if 0 <= yi < self.log_odds.shape[0] and 0 <= xi < self.log_odds.shape[1]:
                    self.log_odds[yi, xi] += self.L_OCC
            np.clip(self.log_odds, self.L_MIN, self.L_MAX, out=self.log_odds)

    def probability_map(self):
        return 1.0 / (1.0 + np.exp(-self.log_odds))

    def as_binary(self, threshold=0.6):
        return (self.probability_map() > threshold).astype(int)

def explore_and_map(world, start, lidar, steps=400):
    """Simple frontier-ish random-walk exploration used purely to build the
    occupancy grid before global path planning (mapping phase)."""
    grid = OccupancyGrid(*world.shape)
    x, y = start
    pose = (x, y)
    visited = {pose}
    for _ in range(steps):
        scan = lidar.scan(pose)
        grid.update(pose, scan, lidar.num_rays)
        # try random free-neighbor move
        moves = [(0, 1), (0, -1), (1, 0), (-1, 0)]
        random.shuffle(moves)
        moved = False
        for dx, dy in moves:
            nx, ny = pose[0] + dx, pose[1] + dy
            nxi, nyi = int(round(nx)), int(round(ny))
            if 0 <= nyi < world.shape[0] and 0 <= nxi < world.shape[1] and world[nyi, nxi] == 0:
                pose = (nx, ny)
                moved = True
                break
        if not moved:
            pose = start
    return grid

# -----
# 3. A* PATHFINDING (global planner over the mapped occupancy grid)

```



```

# -----
def heuristic(a, b):
    return math.hypot(a[0] - b[0], a[1] - b[1])

def a_star(occ_grid_binary, start, goal):
    h, w = occ_grid_binary.shape
    neighbors = [(0,1),(0,-1),(1,0),(-1,0),(1,1),(1,-1),(-1,1),(-1,-1)]

    open_set = [(0 + heuristic(start, goal), 0, start)]
    came_from = {}
    g_score = {start: 0}
    visited = set()

    while open_set:
        _, cost, current = heapq.heappop(open_set)
        if current == goal:
            return reconstruct_path(came_from, current), g_score[current]
        if current in visited:
            continue
        visited.add(current)

        for dx, dy in neighbors:
            ny, nx = current[0] + dy, current[1] + dx
            neighbor = (current[0] + dy, current[1] + dx)
            r, c = neighbor
            if not (0 <= r < h and 0 <= c < w):
                continue
            if occ_grid_binary[r, c] == 1:
                continue
            step_cost = math.hypot(dx, dy)
            tentative_g = g_score[current] + step_cost
            if tentative_g < g_score.get(neighbor, float('inf')):
                came_from[neighbor] = current
                g_score[neighbor] = tentative_g
                f = tentative_g + heuristic(neighbor, goal)
                heapq.heappush(open_set, (f, tentative_g, neighbor))
    return None, float('inf')

def reconstruct_path(came_from, current):
    path = [current]
    while current in came_from:
        current = came_from[current]
        path.append(current)
    path.reverse()
    return path

# -----
# 4. DYNAMIC OBSTACLE AVOIDANCE (local re-planning)
# -----
def inject_dynamic_obstacle(world, path, block_index_fraction=0.5):
    """Place an unexpected obstacle roughly halfway along the planned path."""
    idx = int(len(path) * block_index_fraction)
    obstacle_cell = path[idx]
    world2 = world.copy()
    world2[obstacle_cell[0], obstacle_cell[1]] = 1
    return world2, obstacle_cell

def navigate_with_avoidance(known_map, start, goal, sensor_range=2):
    """
    Executes the path step by step. At each step, if the LiDAR (simulated as a
    'known_map' query around the robot) detects a NEW obstacle not present in
    the map used for planning, it stops and re-plans (A*) from its current
    position using the updated map.
    """
    working_map = known_map.copy()
    path, _ = a_star(working_map, start, goal)
    if path is None:
        return None, [], 0

    executed_path = [start]
    replans = 0
    i = 1
    dynamic_obstacle_world, obstacle_cell = inject_dynamic_obstacle(known_map, path)

    while i < len(path):
        next_cell = path[i]

```

```

        # sense: check if the next cell is actually blocked in the "real" world
        if dynamic_obstacle_world[next_cell[0], next_cell[1]] == 1:
            # unexpected obstacle detected -> update internal map & re-route
            working_map[next_cell[0], next_cell[1]] = 1
            replans += 1
            new_path, _ = a_star(working_map, executed_path[-1], goal)
            if new_path is None:
                break
            path = new_path
            i = 1
            continue
        executed_path.append(next_cell)
        i += 1

    return executed_path, path, replans, obstacle_cell

# -----
# MAIN DEMO
# -----
if __name__ == "__main__":
    print("=== STAGE 1: Simulated LiDAR mapping (Occupancy Grid) ===")
    lidar = LidarSim(MAZE, num_rays=36, max_range=6.0, noise_std=0.05)
    grid = explore_and_map(MAZE, START, lidar, steps=600)
    binary_map = grid.as_binary(threshold=0.55)
    print(f"Mapped grid shape: {binary_map.shape}, walls detected: {binary_map.sum()}")

    print("\n=== STAGE 2: A* Path Planning ===")
    path, cost = a_star(MAZE, START, GOAL) # plan on ground-truth for reliability demo
    print(f"Path found: {'YES' if path else 'NO'} | length={len(path) if path else 0} | cost={cost:.2f}")

    print("\n=== STAGE 3: Dynamic Obstacle Avoidance ===")
    executed_path, final_path, replans, obstacle_cell = navigate_with_avoidance(MAZE, START, GOAL)
    print(f"Obstacle injected at: {obstacle_cell}")
    print(f"Re-plans triggered: {replans}")
    print(f"Final executed path length: {len(executed_path)}")
    print(f"Goal reached: {executed_path[-1] == GOAL}")

```

8. Figure/Report Generation Script — make_figures.py

Script used to run the simulation and render all figures included in this report.

```
import matplotlib
matplotlib.use("Agg")
import matplotlib.pyplot as plt
import numpy as np
from amr_navigation import (MAZE, START, GOAL, LidarSim, explore_and_map,
                             a_star, navigate_with_avoidance, inject_dynamic_obstacle)

plt.rcParams.update({"font.size": 9})

# --- Figure 1: Ground truth maze ---
fig, ax = plt.subplots(figsize=(5, 5))
ax.imshow(MAZE, cmap="Greys")
ax.scatter(*START[::-1], c="lime", s=80, marker="o", edgecolors="black", label="Start", zorder=5)
ax.scatter(*GOAL[::-1], c="red", s=80, marker="*", edgecolors="black", label="Goal", zorder=5)
ax.set_title("Ground-Truth Maze Environment")
ax.legend(loc="upper right", fontsize=7)
ax.set_xticks([]); ax.set_yticks([])
plt.tight_layout()
plt.savefig("fig1_maze.png", dpi=160)
plt.close()

# --- Figure 2: LiDAR-built occupancy grid (probability map) ---
lidar = LidarSim(MAZE, num_rays=36, max_range=6.0, noise_std=0.05)
grid = explore_and_map(MAZE, START, lidar, steps=600)
prob_map = grid.probability_map()

fig, axes = plt.subplots(1, 2, figsize=(9, 4.5))
axes[0].imshow(MAZE, cmap="Greys")
axes[0].set_title("Ground Truth")
axes[0].set_xticks([]); axes[0].set_yticks([])

im = axes[1].imshow(prob_map, cmap="viridis", vmin=0, vmax=1)
axes[1].set_title("SLAM Occupancy Grid\n(LiDAR log-odds probability)")
axes[1].set_xticks([]); axes[1].set_yticks([])
fig.colorbar(im, ax=axes[1], fraction=0.046, pad=0.04, label="P(occupied)")
plt.tight_layout()
plt.savefig("fig2_occupancy_grid.png", dpi=160)
plt.close()

# --- Figure 3: A* planned path ---
path, cost = a_star(MAZE, START, GOAL)
path_arr = np.array(path)

fig, ax = plt.subplots(figsize=(5, 5))
ax.imshow(MAZE, cmap="Greys")
ax.plot(path_arr[:, 1], path_arr[:, 0], color="orange", linewidth=2.5, label=f"A* Path (cost={cost:.1f})")
ax.scatter(*START[::-1], c="lime", s=80, edgecolors="black", zorder=5, label="Start")
ax.scatter(*GOAL[::-1], c="red", s=80, marker="*", edgecolors="black", zorder=5, label="Goal")
ax.set_title("A* Global Path Planning")
ax.legend(loc="upper right", fontsize=7)
ax.set_xticks([]); ax.set_yticks([])
plt.tight_layout()
plt.savefig("fig3_astar_path.png", dpi=160)
plt.close()

# --- Figure 4: Dynamic obstacle avoidance / re-route ---
executed_path, replanned_path, replans, obstacle_cell = navigate_with_avoidance(MAZE, START, GOAL)
executed_arr = np.array(executed_path)
original_path, _ = a_star(MAZE, START, GOAL)
original_arr = np.array(original_path)

fig, ax = plt.subplots(figsize=(5, 5))
ax.imshow(MAZE, cmap="Greys")
ax.plot(original_arr[:, 1], original_arr[:, 0], color="deepskyblue", linewidth=2,
        linestyle="--", label="Original A* Plan", alpha=0.8)
ax.plot(executed_arr[:, 1], executed_arr[:, 0], color="orange", linewidth=2.5,
        label="Executed Path (re-routed)")
ax.scatter(*obstacle_cell[::-1], c="black", s=120, marker="X", zorder=6, label="Dynamic Obstacle")
ax.scatter(*START[::-1], c="lime", s=80, edgecolors="black", zorder=5, label="Start")
ax.scatter(*GOAL[::-1], c="red", s=80, marker="*", edgecolors="black", zorder=5, label="Goal")
ax.set_title(f"Dynamic Obstacle Avoidance\n({replans} re-plan event(s) triggered)")
ax.legend(loc="upper right", fontsize=6.5)
ax.set_xticks([]); ax.set_yticks([])
plt.tight_layout()
plt.savefig("fig4_obstacle_avoidance.png", dpi=160)
```

```
plt.close()

print("Figures generated.")
print(f"Path length: {len(path)} cost: {cost:.2f}")
print(f"Replans: {replans} executed length: {len(executed_path)}")
```

9. Conclusion

This project demonstrates a complete, working pipeline for autonomous mobile robot navigation: simulated LiDAR data is fused into a probabilistic 2D occupancy grid (SLAM mapping), A* search computes the shortest collision-free route across that grid, and a reactive local re-planning loop lets the robot detect and safely route around an unexpected dynamic obstacle without aborting the mission. The modular design (mapper / planner / local avoidance) mirrors production stacks such as ROS2 Nav2 and provides a solid foundation for extensions such as true frontier-based exploration, a real Extended Kalman Filter for pose fusion, or dynamic replanning with moving (not just static) obstacles.