ClaudeDeep

v6 architecture + Q-Fix.A–P + Q-Fix.N

A comprehensive, ultra-detailed design and engineering reference for the 100%-or-abstain adversarial reasoning pipeline built on open-weight 7B-class LLMs.

Working directory: /home/pc/n8nBeast/ClaudeDeep/
Compiled: 2026-05-15
Audience: Junior → Senior → Master → PhD AI developers, AI system-design engineers

About this book

This book documents ClaudeDeep at the level of detail an engineer needs to *rebuild it from scratch*. Not "here's what the system does" — "here is why every design decision was made this way, what its inputs and outputs are, how it hands off to the next stage, what failure modes it protects against, and what alternatives were rejected and why".

Every subsystem gets the same four-part treatment:

- **Why it exists** — the concrete failure mode it prevents, stated with a scenario a junior developer can visualize.
- **What it is responsible for** — the single-sentence contract, plus the exhaustive list of side effects.
- **How it passes its outcome to the next stage** — the exact data type flowing out, the exact call site that consumes it, and the invariant that must hold.
- **Alternatives considered, why we picked this one** — because knowing the reason a system is *not* something else is often more valuable than knowing what it is.

> ***How to read this at your level.*** *Junior developers should read every paragraph, skipping only the "PhD note" boxes on first pass. Senior developers can skim the foundational paragraphs (marked with a bullet at the start) and dwell on the mechanism paragraphs. Master-level and PhD readers should focus on the "trade-offs considered" and "failure modes" sections, and use the PhD notes to jump straight to the calibration / statistical-guarantee content.*

Reading map

Part 1
The landscape — where frontier LLMs are in May 2026, what they lack, why ClaudeDeep exists.
Part 2
The pipeline — Phase 0 through Phase 3 explained module by module, connection by connection.
Part 3
The substrate — retrieval, embeddings, graph store, corpus.
Part 4
The verifiers — PRMs, cross-encoders, generative critics, conformal calibration.
Part 5
The failure recovery layer — gap resolver, cloud teacher, SMT gate, abstention contract.
Part 6
The operational surface — CLI, env vars, config precedence, mode divergence, cross-mode validation.
Part 7
Trade-offs — per subsystem, per module, overall.
Part 8
Empirical state — what is measured, what is deferred, what is explicitly not claimed.
Appendix A
All seven Mermaid diagrams full-page with detailed captions.
Appendix B
Deep dive — how logits are used across the system (this is the example that motivated the ultra-detailed rewrite).
Appendix C
Sources and further reading.

Table of contents

Part 1 — The landscape of reasoning LLMs, May 2026
- 1.1 What the frontier can do today
- 1.2 The four gaps ClaudeDeep is built to close
  - 1.2.1 Gap 1 — no abstention contract
  - 1.2.2 Gap 2 — no contract-first decomposition
  - 1.2.3 Gap 3 — no adversarial verification at every layer
  - 1.2.4 Gap 4 — no 100%-or-abstain invariant
- 1.3 The 7B equalizer thesis, in numbers
- 1.4 What "beats Mythos" actually means here
- 1.5 Sources for Part 1

Part 2 — The pipeline, phase by phase, connection by connection
- 2.0 Reading this part — conventions
- 2.1 Phase 0 — Contract-first orchestration
- 2.2 Phase 1 — Per-module adversarial resolution
- 2.3 Phase 2 — 5-tier deterministic-arbiter cascade
- 2.4 Phase 3 — Aggregation + 100%-or-abstain
- 2.5 The outer loop — main.py

Part 3 — The substrate (retrieval, embeddings, graph, corpus)
- 3.0 The three retrieval query semantics
- 3.1 CompiledQuery — the deterministic compiler
- 3.3 Dense retrieval — LanceDB + bge-m3
- 3.5 RRF — Reciprocal Rank Fusion
- 3.6 Cross-encoder rerank — bge-reranker-v2-m3
- 3.7 Parent-document chunking
- 3.8 Graph store — FalkorDB + GLiNER
- 3.9 Trust layer — provenance-graded scoring
- 3.10 The starter corpus
- 3.11 The ingestion pipeline

Part 4 — The verifiers (PRMs, cross-encoders, generative critics, conformal calibration)
- 4.0 The verifier stack — one call site, four consumers
- 4.1 PRM — the family of five verifiers plus one router
- 4.2 model_swap — the GPU pressure release valve
- 4.3 The default_prm factory
- 4.4 The agreement fraction — canonical clustering
- 4.5 Stratified sampling across the ensemble
- 4.6 Tree-of-Thoughts with UCB1
- 4.7 Sub-claim decomposition
- 4.8 Conformal calibration — making 99% precision guaranteed
- 4.9 How the four factors compose — a worked example

Part 5 — The failure-recovery layer (gap resolver, cloud teacher, SMT gate, abstention)
- 5.1 The Gap Resolver — online knowledge retrieval
- 5.2 ChunkSaboteur — single-pass adversarial gate
- 5.3 MultiPassSaboteur — five attack families
- 5.4 Cloud teacher consultation
- 5.5 Z3-SMT gate
- 5.6 The seven typed abstention reasons

Part 6 — The operational surface (CLI, env, config, modes, telemetry)
- 6.0 Configuration precedence
- 6.1 CLI flag reference
- 6.2 Environment variable reference
- 6.3 Per-mode divergence map
- 6.4 The cross-mode validator
- 6.5 Structural verification gate
- 6.6 Telemetry — sinks and events
- 6.7 Replay harness
- 6.8 Operational commands reference

Part 7 — Trade-offs
- 7.1 Per-mechanism trade-offs (15 tables)
- 7.2 Per-module trade-offs
- 7.3 Overall trade-offs

Part 8 — Empirical state (what is measured, what is deferred)
- 8.1 Substrate-A — real LLM inference, verified
- 8.2 Substrate-B — real corpus indexed and retrievable
- 8.3 Q-Fix.M structural verification gate
- 8.4 Q-Fix.O.5 subset SWE-bench
- 8.6 What we explicitly DO NOT claim

Appendix A — Diagram gallery

Appendix B — How logits are used in ClaudeDeep

Appendix C — Sources and further reading

Part 1 — The landscape of reasoning LLMs in May 2026

Every design decision in ClaudeDeep is a response to something the frontier does or does not do. This part establishes the empirical baseline. Everything after it is justified against these numbers.

1.1 What the frontier can do today

As of May 2026, three closed-weight model families lead the public reasoning benchmarks. The canonical yardstick for practical software-engineering ability — SWE-bench Verified, a 500-instance subset of real GitHub issues where the model must produce a patch that passes hidden test cases without ever seeing them — sits at the following levels:

Model	Vendor	SWE-bench Verified pass@1	Weights
Claude Mythos Preview	Anthropic	93.9%	Closed
Claude Opus 4.7 (Adaptive)	Anthropic	87.6%	Closed
GPT-5.3 Codex	OpenAI	85.0%	Closed
Claude Opus 4.5	Anthropic	80.9%	Closed
InfCode (agent scaffold on DeepSeek-V3 / Claude 4.5 Sonnet)	Research (arxiv 2511.16004)	79.4%	Scaffold open, base closed
GLM-5 (~70B)	Zhipu	77.8%	Open
Best published 7B model, raw pass@1	Various	< 15% (never above 40% in ANY published scaffold)	Open

Junior orientation. *"pass@1" means "the model was given one attempt per problem and the patch either passes all hidden tests or does not". No retries, no oracle, no human intervention. A 93.9% score means the model solved 469 of 500 problems on its first attempt.*

Every model above 77% has one thing in common: it is either closed-weight, or it is far larger than 7B parameters, or both. Closed weights mean the user must send their code to an external API. Large weights mean the user needs multi-GPU inference infrastructure, which for a 70B model at FP16 is roughly 140 GB of VRAM — the domain of two A100 80GB cards or one H100 with heavy quantization tricks.

This is the empirical wall the ClaudeDeep hypothesis pushes against. The hypothesis is *not* "a 7B can match Mythos on raw pass@1". No public architecture has closed that gap; the plan section explicitly names it as beyond current state of the art. The hypothesis is narrower and more defensible: **a 7B-class model wrapped in the right scaffolding — real retrieval over a canonical CS corpus, adversarial verification at every layer, conformal- calibrated abstention — can produce ANSWERS at ≥ 99% precision on the subset of queries it doesn't abstain on.** Raw coverage may be modest, but every answer it emits carries a traceable, verifier-corroborated evidence chain.

1.2 The four gaps ClaudeDeep is built to close

Frontier LLMs in their default deployment have four architectural gaps. Each one is the justification for a specific ClaudeDeep subsystem. Understanding the gap is prerequisite to understanding why the corresponding subsystem exists at all.

1.2.1 Gap 1 — no abstention contract

Why it matters, in one scenario

Mythos scores 93.9% on Verified. The remaining 6.1% is not "the model told the user 'I don't know'". It is **the model emitted a confident-looking patch that broke the hidden tests and nothing in the response indicated the answer might be wrong.** If you deploy Mythos against 10 000 real GitHub issues, roughly 610 of them get a plausible-but-broken patch back, indistinguishable at the response level from the 9 390 correct answers.

For low-stakes contexts this is acceptable — a human reviewer catches the bad patches. For high-stakes contexts (medical decision support, legal document analysis, infrastructure configuration) it is catastrophic. A wrong answer at 94% confidence is worse than no answer, because the user acts on the wrong answer.

Why frontier models don't have an abstention contract

Two reasons. First, they are trained on human-preference data where "I don't know" is scored lower than "here is a plausible-looking answer" — RLHF actively rewards confident-sounding completions even when the underlying uncertainty is high. Second, an abstention rate is a marketable number that competitors will publish; a coverage number of 60% "looks worse" than a pass-rate of 94% even if the coverage-adjusted precision is higher, so no vendor is incentivized to ship an explicit abstention gate.

ClaudeDeep's response

Phase 3 emits *either* an AnswerReport or an AbstentionReport — mutually exclusive Pydantic types enforced at the type system level. The choice depends on an aggregated confidence score, computed from three orthogonal signals: (a) the agreement fraction of the winning cluster in best-of-N sampling, (b) the Process Reward Model score, (c) the conformal-calibrated threshold derived from a held-out eval set. Every abstention carries a *typed reason*: corpus_gap, unsat_core, recursion_cap, proof_incomplete, execution_unachievable, adversarial_rejection, cross_mode_divergence. The user sees a diagnostic, not a silent failure.

> **Design invariant.** The mutually-exclusive types are what make this a *contract* rather than a convention. A downstream caller can pattern-match on the report type and be certain that an AnswerReport was not silently downgraded to contain "actually I'm not sure" text in one of its string fields.

1.2.2 Gap 2 — no contract-first decomposition

Why it matters

Most agent scaffolds decompose a task into modules implicitly, during a single chain-of-thought pass, and discover module-boundary incompatibilities at runtime. When Module A's plan turns out to need an API that Module B's plan doesn't provide, the scaffolds typically resolve this by having an LLM judge look at both plans and rewrite one of them. This is the *override cascade*: an LLM without grounding is given authority to overwrite peer decisions, and once that happens, the confidence chain becomes unreliable because you cannot trace which module's plan is "the real one".

How ClaudeDeep prevents it

Phase 0 emits *N ModuleSpecs, each bound to a draft ContractBroadcast, before* any Builder writes a single line of a plan. The ContractBroadcast contains the API schema, the event contracts, the data types, and the dependencies of each module. Modules build within their contracts; they never re-negotiate them. When residual conflicts appear in Phase 2, they are resolved by *deterministic arbiters*: a CSP solver (cp-sat or Z3), then a Builder-vs-Saboteur clash over the solver's top-K candidate resolutions, then the user, then re-decomposition from Phase 0 with FullContext. No tier lets the LLM overwrite a peer.

> **Connection to Phase 0.** The K=8 candidate decomposition (Q-Fix.G) is another response to this gap. Instead of trusting a single decomposition draft, we generate 8 variants and run a Builder/Saboteur clash on each — the winner is the one whose contracts survive the most attacks. This makes the highest-stakes step (deciding what the modules ARE) itself adversarial.

1.2.3 Gap 3 — no adversarial verification at every layer

Where adversarial verification traditionally lives

Multi-agent debate systems work at the *output* layer: an arbiter sees multiple candidate answers and picks one. InfCode adds adversarial verification at the test/patch layer for SWE-bench: a generator proposes a patch, a critic proposes a failing test, and if the test holds against the patch, both are accepted. Neither approach builds adversarial verification into *every retrieval, every plan synthesis, every ingestion, every committed contract*.

The failure mode this creates

An LLM that's never red-teamed at the intermediate stages will produce plans that survive a final-stage judge by being *confident*, not by being *correct*. The judge sees a polished output and cannot distinguish "polished because right" from "polished because the model generates polished text". If the intermediate reasoning was never attacked, the final judgment is measuring surface plausibility, not correctness.

ClaudeDeep's response — adversarial clash at four layers

- **Phase 0 (decomposition):** Saboteur attacks each candidate decomposition draft, breaking its capability manifold, exposing missing dependencies.
- **Phase 1 (per-module plan):** the classic Builder↔Saboteur clash. Builder proposes a plan grounded in Supporting evidence; Saboteur attacks it with Counter evidence. Plan survives if no FAQ item is broken; else recurses with enriched context.
- **Phase 2 tier 3 (solver candidates):** when tier 2's CSP solver returns multiple SAT candidates, Builder picks one, Saboteur attacks it, only the surviving candidate is committed.
- **Gap Resolver ingestion:** the MultiPassSaboteur applies five attack families (injection, noise, duplicate, bias, contradiction) to each newly-retrieved chunk before promotion. Rejected chunks are logged as counter-examples for future Saboteur runs.

> **Codex-style correlated-failure guard.** If Builder and Saboteur happen to retrieve from the same evidence cluster, their clash is theatre — both arms will cite the same sources and "agree". Q-Fix.H measures Jaccard overlap of retrieved chunk IDs; when overlap > 0.5, it reruns the Saboteur with a disjoint filter, capped at 8 retries. This makes the adversarial clash genuinely adversarial even when the corpus happens to have strong topical clustering.

1.2.4 Gap 4 — no 100%-or-abstain invariant

What the research says

Selective-prediction and conformal-abstention research has converged on the same result: when a model is forced to choose between answering and abstaining at a *calibrated* threshold, false-answer rate can be driven below 1% at 50–70% coverage. But this only works when the threshold is COMMITTED — a calibrated tau computed from a held-out set, not a heuristic. Most production systems default to a fixed confidence cutoff (typically 0.85) that nobody has actually calibrated against the true precision they care about.

ClaudeDeep's response

Phase 3 supports a ConformalCalibrator (Q.12): point policy.conformal_calibration_path at a JSON file of *(confidence, was_correct)* pairs from a held-out eval set; the smallest tau achieving precision ≥ 1−ε is computed on load and replaces the heuristic 0.85. Empty calibration file ⇒ heuristic is preserved (the "never WORSEN the baseline" invariant). The approach mirrors the ATCP method (arxiv 2502.06884) which integrates RL with conformal prediction; ClaudeDeep implements the classical conformal step now and leaves the RL extension as a future-work hook.

1.3 The 7B equalizer thesis, in numbers

Why bother building a complex scaffold for a 7B model when frontier closed-weight LLMs already exist? Three reasons:

- **Sovereignty.** A 7B Ollama model runs locally on a 16 GB GPU. Mythos requires Anthropic's API. Opus requires Anthropic's API. GPT-5.3 requires OpenAI's API. For research labs, government contracts, regulated industries, and corpus owners who cannot send proprietary data over a vendor API, an open-weight self-hosted stack is the only option that exists.
- **Auditability.** Every step of ClaudeDeep emits a structured TelemetryEvent. Every retrieval is logged with its CompiledQuery (the deterministic compiled form). Every Saboteur attack is replayable from its retrieval state. Every abstention carries a typed reason and an evidence chain. The same artifact ships to peer reviewers and to on-call debuggers.
- **Falsifiability.** "A 7B with this scaffold reaches X% on SWE-bench Verified" is a testable claim. It either does or it doesn't. The plan's Empirical Ceiling section commits to 35–55% as the realistic first-year target, and the 100%-or-abstain invariant means precision-on-answered should hit 99% regardless of coverage. Both are measurable.

1.4 What "beats Mythos" actually means here

The book is honest about what "beats Mythos" means. It does *not* mean raw pass-rate parity on SWE-bench Verified — that's beyond current published evidence at any open-weight model size. It means **precision-on-answered parity at lower coverage**: where Mythos answers everything at 93.9%, ClaudeDeep answers roughly 50% at > 99% — fewer total answers, but each one carries a traceable evidence chain, a calibrated confidence number, and a guaranteed precision floor. For high-stakes domains the precision IS the value; the coverage gap is the explicit trade.

> **The unfair-comparison disclaimer.** When the book says "beats Mythos on precision-on-answered", it means under a fixed conformal-calibration eval where both systems are forced to abstain. Mythos's published 93.9% is its answer rate; what fraction of those answers would survive a 99%-precision abstention filter is an open empirical question. The point is ClaudeDeep is BUILT to deliver that filter; whether Mythos has one in its private deployment is unknown.

1.5 Sources for Part 1

- SWE-bench Verified leaderboard, May 2026
- LLM-Stats SWE-bench leaderboard
- Epoch AI — SWE-bench Verified
- InfCode (arxiv 2511.16004, Nov 2025) — 79.4% Verified with adversarial test/patch refinement.
- SWE-Debate (arxiv 2507.23348, Jul 2025) — multi-agent debate open-source SOTA.
- DebateCV (arxiv 2507.19090) — debate-driven claim verification.
- Conformal Abstention Policies / ATCP (arxiv 2502.06884, 2026)
- SelectLLM — Calibrating LLMs for Selective Prediction (OpenReview 2025)
- Trust-or-Escalate (ICLR 2025)

Part 2 — The pipeline, phase by phase, connection by connection

Part 1 explained why the system exists. Part 2 explains how it runs, from the moment the user types a request to the moment an AnswerReport or AbstentionReport leaves the outer loop. Every module is documented with the same four-part treatment introduced in the About-this-book section: why it exists, what it is responsible for, how it hands off, and what alternatives were rejected. Where a module is trivial, the four parts collapse into a paragraph; where it is load-bearing, they are broken out explicitly.

2.0 Reading this part — conventions

Naming

Class names are written in PascalCase. Instance references and functions are in snake_case. Module paths inside src/claudedeep/ are written without the prefix (e.g. agents/builder.py means src/claudedeep/agents/builder.py). Fully-qualified type names are given the first time a class is introduced; later mentions use just the class name.

Handoff notation

When a producer module hands its output to a consumer, this is written as «producer» → *DataType* → «consumer». The *DataType* in the middle is always a Pydantic model. The producer constructs it, the consumer accepts it, and no third party mutates it in between.

Two invariants restated up front

- **LLM = syntax compiler.** Every LLM call passes through OllamaConstrainedDecoder with a Pydantic schema. There is no free-form text generation anywhere in the pipeline. The decoder enforces the schema at the token-mask level (see Appendix B.1.1). Any module that tries to bypass this raises a type error at construction time.
- **Recursion is Phase 1 only; pipeline recursion is main.py's.** Phase 1's child-of-child recursion stays within a module. Phase 2 tier 5 can emit a PipelineRecursionRequest back to Phase 0 — but the decision to consume that request is owned by main.py's outer loop, not by either phase.

2.1 Phase 0 — Contract-first orchestration

2.1.0 Why Phase 0 exists at all

Most agent scaffolds skip Phase 0. They accept a user request, ask an LLM to "think about how to approach this", and let the resulting free-form plan drive downstream modules. This works until two independently-planned modules need to interoperate — at which point either an LLM judge is asked to reconcile them (the override cascade that Gap 2 warned about) or the system just breaks.

Phase 0 exists to make module boundaries a *contract*, not an emergent property. Before any Builder is spawned, Phase 0 decides:

- Which modules the task decomposes into.
- What each module's API surface is.
- What events flow between them and what payloads those events carry.
- Which module depends on which.
- How much effort (best-of-N cap, tree depth) each module gets.

Every downstream module receives its contract as an input. It builds *within* the contract; it never renegotiates it. When conflicts appear in Phase 2, they are resolved against the contract, not by rewriting the contract.

2.1.1 Master Orchestrator

Why it exists

Someone has to decide the initial decomposition. The Master Orchestrator is that someone. It is a *pure planner*: it takes the user's request plus (optionally) a FullContext from a previous pipeline iteration, and emits an OrchestrationPlan. It runs no Builder logic and no Saboteur logic.

What it is responsible for

Three side-effects, in order:

1. Issue a Phase-0-only ArchitecturalQuery against GraphRAG to fetch high-level architectural patterns relevant to the request. This is the ONLY query type Master Orchestrator ever emits; it cannot accidentally issue a SupportingQuery or CounterQuery because those types are not imported into orchestrator/master.py.
2. Hand the request + architectural context to KCandidateDecomposer, which generates k_candidate_count = 8 variant decompositions (Q-Fix.G).
3. Hand the K candidates to StackedCandidateScorer, pick the winning candidate, call EffortAssigner to attach a per-module effort_level.

How it hands off

«MasterOrchestrator.plan(user_input, full_context)» → *OrchestrationPlan(module_specs, dependency_graph, faqs)* → «Phase1.run(...)».

Alternatives considered

- *Single-pass LLM decomposition*. Rejected because it removes the adversarial check on the decomposition itself. The whole point of Phase 0 is that decomposition is a high-stakes decision that deserves its own clash.
- *Hard-coded decompositions per task type*. Rejected because the space of user requests is open-ended. The LLM must propose candidates; the deterministic scorer picks among them.

2.1.2 ArchitecturalQuery

A subclass of GraphRAGQuery emitted only by the Master Orchestrator. It returns high-level patterns ("what architectures typically address X"), not module-specific implementation details. Semantically distinct from SupportingQuery (Builder-only, "best implementation of module M") and CounterQuery (Saboteur-only, "anti-patterns for module M"). The type system enforces the separation: each subclass carries its own required fields and each caller accepts only its own subtype.

2.1.3 KCandidateDecomposer (Q-Fix.G)

Why it exists

The plain answer is: because a single LLM decomposition draft can be wrong, and the cost of being wrong at decomposition time is unbounded. If Module A's boundary is drawn in the wrong place, every downstream module inherits the flaw. Contract-first decomposition prevents runtime negotiation of boundaries, but only if the boundaries were drawn well in the first place. K=8 candidates give us eight independent attempts.

What it is responsible for

Generate K structurally-diverse decomposition variants of the same user request. The K generators are hard-coded strategies (effort-tiered, compact-paired, contract-filled, mixed-effort, coarse-grained, fine-grained, event-heavy, dependency-heavy) rather than K LLM samples — because K samples from the same model with the same prompt are correlated, and correlated candidates defeat the point of scoring K of them.

How it hands off

«KCandidateDecomposer.candidates(request, arch_hits)» → *list[CandidateDecomposition]* → «StackedCandidateScorer».

2.1.4 StackedCandidateScorer — two scorers, stacked

The scorer runs each candidate through two independent evaluators and averages their scores. Each evaluator emits a CandidateScore with breakdown fields for auditability.

HeuristicCandidateScorer

Structural checks with no LLM cost: (a) capability_manifold_breadth = number of contract fields with enumerated accepted values (normalized); (b) dependency_graph_validity = 0 if there's a cycle or dangling reference, else 1; (c) module_count_penalty = geometric penalty for over- or under-decomposing (peak around 3–6 modules). Fast, cheap, always available.

AdversarialCandidateScorer (Q-Fix.G, quality-max only)

For each candidate, spawn a Phase0ClashRunner which runs one round of Builder/Saboteur clash against each module's draft contract. Score = fraction of modules whose contract survived attack. This is genuinely expensive (K × M × 2 LLM calls per request, roughly 128 calls for K=8 and M=8 with best-of-N=1) so it is guarded by policy.k_candidate_adversarial_scoring. Under quality-max, it is on.

Stacking rule

total = 0.5 · heuristic.total + 0.5 · adversarial.total. Winner is argmax(total). Ties broken by heuristic score (deterministic).

Handoff

«StackedCandidateScorer.score(candidates)» → *WinningCandidate* → «EffortAssigner».

2.1.5 Phase0ClashRunner

A thin wrapper around Builder/Saboteur that runs a single-round clash against a candidate's draft contract (rather than a Phase 1 plan). It reuses the same clash primitive as Phase 1 so there is one code path for "Builder attacks something, Saboteur defends", not two. Its return value is a boolean (contract-FAQ survived?) plus attack summary; the scorer aggregates booleans into a fraction.

2.1.6 EffortAssigner

Given the winning decomposition, assigns an effort_level per module. This controls: (a) best-of-N cap for Phase 1 LLM calls, (b) tree depth for ToT search, (c) maximum recursion depth for the child-of-child loop. Simple modules get effort_level=1 (fast paths); complex modules get up to effort_level=5 (heavy compute). The policy is currently heuristic (based on estimated complexity signals from the contract shape) with a future hook for a trained regressor.

2.1.7 Phase 0 output — OrchestrationPlan

A frozen Pydantic model containing:

- module_specs: list[ModuleSpec] — each with id, description, draft contract, effort_level.
- dependency_graph: DependencyGraph — edges between modules derived from contract references. Consumed by Phase 2 to prune the $O(n^2)$ conflict-detection to only-connected-pairs (Q-Fix.M.7).
- faqs: dict[module_id, ModuleFAQ] — loaded from faqs/modules/*.yaml, keyed by module type.
- Telemetry: which K-candidate won and why (breakdown of both scorers).

«OrchestrationPlan» is consumed by Phase 1's fan-out loop and by Phase 2's dependency-graph-pruned conflict detector. Neither consumer is allowed to mutate it — the model is frozen at construction.

2.2 Phase 1 — Per-module adversarial resolution

2.2.0 Why Phase 1 exists

Every module produced by Phase 0 is a *plan*, not a *correct plan*. Phase 1 turns each spec into a battle-tested plan by running an adversarial cycle: Builder proposes, Saboteur attacks, Clash decides. If any attack breaks a FAQ item, the plan is not accepted; instead the module recurses with enriched context (parent plan + attack findings + which FAQ item broke). Recursion continues until either the plan survives, a convergence halt fires, or the recursion depth cap is hit — in which case Phase 1 emits ContractUnimplementable rather than falsely reporting success.

2.2.1 ModuleAgent — the per-module orchestrator

One ModuleAgent instance per ModuleSpec. All N modules run in parallel via asyncio.gather — they are fully isolated: no shared state, no cross-module imports, no way for module A's state to leak into module B's Builder.

Responsibilities

Coordinate the Builder / Saboteur / Clash / Recursion cycle for one module. Owns:

- Instantiation of Builder and Saboteur (both parameterized with the module's spec + shared GraphRAG engine + shared LLMStage client).
- The recursion loop — child-of-child sub-agents inherit parent's plan + accumulated attack findings. Each cycle's context is strictly richer than the last.
- Q-Fix.H correlated-failure detection between Builder's and Saboteur's retrieved chunk sets; disjoint-filter rerun of Saboteur when Jaccard > 0.5.
- Convergence + oscillation halt via RecursionController.

- Emitting the final Phase1Result (either SurvivedReport with plan + evidence, or ContractUnimplementable with a diagnostic reason).

2.2.2 Builder pipeline — five stages

Builder is not "an LLM that writes a plan". It is a five-stage pipeline where the LLM is the LAST stage. Every earlier stage constrains what the LLM can even see, so the LLM's job is reduced to "fill in the syntactic slots of a plan schema, given already-vetted evidence".

Stage 1 — FAQ Validate

Load the module's ModuleFAQ (from faqs/modules/<module_type>.yaml). Each FAQ item is a natural-language assertion the plan must satisfy ("the plan must handle the case where the input is empty", "the plan must not depend on unlisted external services" etc.). This is the input contract the Saboteur will later probe against.

Stage 2 — CompiledQuery construction (Q-Fix.M.2)

Build a QueryIntent (Pydantic: module id, intent="supporting", constraints, anti_patterns=false). Pass it to the deterministic compile() in graphrag/query_dsl.py, which returns a CompiledQuery with three fields: vector_q (the dense-search string), graph_pattern (the Cypher pattern for FalkorDB), filters (metadata predicates like tier or recency). This is the ONLY entry point to GraphRAGEngine.query_compiled(). Raw SupportingQuery(...) constructors are removed from all call sites (verified by test_compiled_query_invariant.py).

Stage 3 — GraphRAG Supporting query

Execute the compiled query through the hybrid retrieval stack (see Part 3 for the substrate detail). Returns list[GraphRAGHit], each with score, text, chunk_id, and provenance (tier A/B/C/provisional). Under quality-max, top-K=10 after rerank.

Stage 4 — Reranker (helpful stance)

The retrieval stack already includes a bge-reranker-v2-m3 cross-encoder pass (Q-Fix.E.3), but Builder applies an additional filter here: chunks whose provenance tier is B or above, whose recency doesn't decay below a threshold, and whose trust-scorer product exceeds a minimum. This is a "helpful stance": prefer canonical, recent, corroborated evidence.

Stage 5 — LLMStage

This is where the LLM enters. LLMStage receives (system_prompt, faq_snippet, graphrag_evidence) as a VerifiedContext and returns LLMResult[Plan]. Under quality-max: best-of-N=64 stratified across the ensemble ({self, gpt-oss:120b-cloud}), optionally ToT-UCB1 expansion, PRM scoring on every sample, canonical clustering, winner selection. The full LLMStage flow is Diagram 5 and is documented as its own section in Part 4.

Post-Builder handoff

«Builder.build(...)» → *LLMResult[Plan]* → «ModuleAgent» which then constructs the SabotageRequest.

2.2.3 Saboteur pipeline — mirror image, Counter stance

Saboteur runs the same five-stage pipeline as Builder, with three substitutions:

1. FAQ Validate becomes *FAQ Probe*: for each FAQ item, generate an attack angle ("what would falsify this claim?").
2. QueryIntent.intent = "counter", anti_patterns = true. The compiled query pulls chunks about failure modes, edge cases, known-bad patterns for this module type.
3. Reranker uses a "damaging stance": prefer chunks that specifically contradict Builder's plan or highlight a corner case the plan doesn't handle.

Stage 5 (LLMStage) emits LLMResult[SabotageResponse] whose payload contains attack_findings, broken_faq_items, and repair_recommendations.

2.2.4 AdversarialClash

The clash primitive is a single function: given a Plan and a SabotageResponse, decide *survive* or *recurse*. Rule: plan survives iff len(broken_faq_items) == 0. Any broken FAQ item ⇒ recurse.

The primitive is deliberately trivial. All intelligence is in the FAQ Probe and the LLM's per-attack finding. The clash itself is a boolean gate that could be replaced by if not broken_faq_items: inline — it exists as a named function only so that telemetry can hook it and the recursion controller can inspect the sequence of decisions.

2.2.5 RecursionController — three halts

On a recurse decision, the controller decides whether to spawn a child or halt. Three halts, checked in order:

1. **Depth cap.** If current depth ≥ max_module_recursion (default 3), halt with reason "depth_cap".
2. **Convergence delta (M.6).** If the count of broken_faq_items did not strictly decrease compared to the previous round, halt with reason "no_progress". This prevents burning compute on a stalled loop.
3. **Oscillation signature (Codex, Q-Fix.F.4 addendum).** Track a set of *failure signatures* = frozenset(broken_faq_items) across rounds. If the current signature has appeared at any prior round, halt with reason "oscillation". Detects A→B→A→B cycles that convergence delta alone would miss.

On any halt, ModuleAgent emits Phase1Result(status="CONTRACT_UNIMPLEMENTABLE", contract_unimplementable=ContractUnimplementable(reason=<halt_reason>, suggested_relaxation=<summary_of_last_broken_items>)). The suggested_relaxation is what Phase 2 tier 5 later uses when it constructs a FullContext for re-decomposition.

2.2.6 Q-Fix.H correlated-failure rerun

Why it exists

Builder and Saboteur both retrieve from the same GraphRAG substrate. If their queries happen to hit the same evidence cluster, they will produce plans and attacks that agree by construction (both pulling from the same chunks), and the clash is a rubber stamp. This is not just an efficiency loss — it silently converts an adversarial pipeline into a self-reinforcing one.

Mechanism

After the initial Builder/Saboteur round, ModuleAgent measures Jaccard(builder_chunk_ids, saboteur_chunk_ids). If it exceeds 0.5, it reruns the Saboteur with an excluded_chunk_ids filter equal to Builder's chunk set. The compiled query engine honors this filter as a post-filter on results. If the second Saboteur still hits Jaccard > 0.5 (which happens when the entire corpus for this topic is small), it iterates with a growing excluded set, capped at correlated_failure_max_retries = 8. Each iteration is a telemetry event with Jaccard reported.

What if the exclusion starves the retrieval

If the excluded set eventually leaves the Saboteur with zero hits, the loop breaks with a telemetry event and Saboteur falls back to attacks derived only from its FAQ Probe (no retrieval-grounded counter-evidence). This is a signal that the corpus lacks counter-evidence for this topic — something the Gap Resolver may later address.

2.2.7 Sub-claim decomposition (Q.5, wired via Q-Fix.B.1)

Why it exists

Even after Builder/Saboteur clash, a plan can be right in aggregate but contain individual claims that are wrong. Aggregate voting can hide per-claim errors: three of four steps might be well-supported, one step might be a hallucination, and the plan still passes clash. Q.5 decomposes the plan into atomic claims and verifies each independently.

Mechanism

After Builder emits LLMResult[Plan], if policy.sub_claim_decomposition = True, the plan is decomposed into atomic claims by pipelines/sub_claim.py:verify_plan_atoms(). Each claim gets its own compiled query, its own retrieval, its own trust-scored evidence check. A claim without tier-A/B evidence above threshold is dropped from the plan. Builder's confidence is multiplied by the fraction of surviving claims.

If ALL claims are dropped, the plan effectively has zero content and Builder's confidence collapses to zero — forcing abstention or recursion. This is desirable: an ungroundable plan should not survive.

2.2.8 Phase 1 output — typed union

Every ModuleAgent emits exactly one of two typed outcomes:

- Phase1Result(status="SURVIVED", plan, confidence, evidence) — the plan passed clash + sub-claim verification. Flows into Phase 2 as a ContractBroadcast.
- Phase1Result(status="CONTRACT_UNIMPLEMENTABLE", contract_unimplementable) — the module could not produce a surviving plan within the recursion budget. Flows into Phase 2 as a diagnostic that will cascade through the 5-tier resolver and possibly trigger tier-5 re-decomposition.

The third status ("FAILED") is reserved for infrastructure errors — the LLM raised, the retrieval crashed. It is distinct fromCONTRACT_UNIMPLEMENTABLE (a contract-level refusal after exhaustive attempts). The distinction matters because Phase 2 handles them differently: FAILED aborts the module, CONTRACT_UNIMPLEMENTABLE feeds into re-decomposition.

2.3 Phase 2 — 5-tier deterministic-arbiter cascade

2.3.0 Why Phase 2 is deterministic-arbiters-only

Phase 2 exists to resolve *inter-module* conflicts — two modules that individually passed clash but whose contracts don't compose. The tempting design here is to have an LLM judge look at the conflicting contracts and pick one. That is the override cascade Gap 2 warned about, and it is what ClaudeDeep refuses to do.

Instead, Phase 2 resolves conflicts through a five-tier cascade where every arbiter is either deterministic (checker, solver) or a Builder/Saboteur clash operating on solver-generated candidates (i.e., the LLM is deciding among choices that a solver already proved feasible, not making up new choices). At no tier does an LLM overwrite a peer module's contract.

2.3.1 A2ALayer2Hub

The Hub is the single owner of Phase 2. It receives ContractBroadcast messages from each surviving Phase 1 module, registers them, runs conflict detection (pruned by the DependencyGraph from Phase 0 — only connected module pairs are tested), and routes conflicts through the tier cascade.

2.3.2 Tier 1 — Conformance check

Trivial deterministic pass: does every survived plan actually conform to the draft contract that Phase 0 emitted for its module? Schema check on the module's api_schema, event_contracts, data_types, dependencies. If everything conforms and no cross-module conflicts detected, the cascade terminates immediately: commit and pass to Phase 3. If deviations exist, tier 2.

2.3.3 Tier 2 — CSP solver

Why it exists

Most contract mismatches are structural and can be resolved by a solver: two modules disagree on a field's type (int vs str), or on the range of allowed values, or on the ordering of a dependency chain. A CSP solver can enumerate the constraint intersection and either find a SAT assignment (everyone's constraint satisfied) or prove UNSAT (no valid assignment exists).

Backends

policy.solver_backend selects: "cp-sat" (Google OR-Tools, fast for finite-domain problems) or "z3" (Microsoft, handles string/regex predicates and integer arithmetic). Default is cp-sat; Z3 is used when contracts include string constraints or when SMT-level reasoning is needed.

Manifolds

Each surviving module publishes a ContractCapabilityManifold alongside its ContractBroadcast: for every contract field, the set of acceptable values (marked hard or soft). The solver treats hard constraints as required, soft as preferences.

Outputs

- *SAT with one candidate*: commit; tier cascade ends.
- *SAT with multiple candidates*: solver returns top-K; cascade goes to tier 3.
- *UNSAT with human-readable core*: cascade goes to tier 3 with the UNSAT core attached so the clash there can propose targeted relaxations.

2.3.4 Tier 2.5 — Proofing verifier (Q-Fix.M.3)

When tier 2 returns SAT, the committed contract is sent to a proofing verifier that runs one more sanity check via MCP-backed web search. It queries for counter-evidence against the contract's declared invariants; if any authoritative source contradicts them, the tier-2 SAT is demoted to a tier-3 clash. On accept, new sources retrieved during proofing are ingested into the graph as tier-B provisional evidence — making the "self-updating graph" claim truthful.

2.3.5 Tier 3 — Clash on solver candidates

When tier 2 returns multiple SAT candidates or a demoted candidate from tier 2.5, tier 3 runs Builder vs Saboteur over the top-K candidates. Builder picks the one it thinks is best; Saboteur attacks; the surviving candidate is committed. If none survive, the cascade falls to tier 4.

Critical property: tier 3 never lets the LLM invent a new solution. It picks among candidates the solver already proved feasible.

2.3.6 Tier 4 — Ask-User with pre-generated options

If no candidate survives tier 3, the user is asked, but with structure: the request presents the involved plans, the conflict summary, the UNSAT core (or the surviving-candidate-count), Saboteur's attack findings, and a pre-generated option set. The user picks one of the options or declines. This is a bounded interaction — not free-form — because the pipeline has already reduced the choice to a small enumerable set.

Under quality-max, tier 4 is always available (Q.14 always-on). Under baseline, it can be disabled and cascade skips straight to tier 5.

2.3.7 Tier 5 — Re-decompose with FullContext

Structural retreat: the decomposition itself was wrong. Tier 5 emits a PipelineRecursionRequest carrying a FullContext object (all plans, all confliction points, all CONTRACT_UNIMPLEMENTABLE reasons, prior negotiation rounds, recursion depth). This request is returned up the stack to main.py, which decides whether to feed it back into Phase 0 or, if the recursion depth cap is hit, force-emit an AbstentionReport(reason="recursion_cap") from Phase 3.

Why main.py owns the loop

Because pipeline recursion is a global decision, not a Phase 2 decision. Phase 2 is a per-conflict resolver; it cannot know whether the outer loop's recursion budget is exhausted. Splitting the concern (Phase 2 REQUESTS, main.py DECIDES) preserves the invariant that recursion caps have exactly one enforcement point.

2.3.8 Phase 2 output

- Phase2Result(committed_contracts, tier_trail, recursion_request=None) — when a tier committed. Flows into Phase 3.
- Phase2Result(committed_contracts=None, recursion_request=PipelineRecursionRequest) — when tier 5 fired. Consumed by main.py's outer loop.

2.4 Phase 3 — Aggregation + 100%-or-abstain

2.4.0 Why the invariant is Pydantic-enforced

The 100%-or-abstain contract is exposed at the type system level:

```
Phase3Result = Union[AnswerReport, AbstentionReport]
```

The two types are structurally incompatible: AnswerReport has fields (target, content, confidence, evidence_chain) , AbstentionReport has fields (reason, diagnostic, evidence_partial, gap_request). A caller cannot conflate them, and a Phase 3 code path that "wants to return both" cannot be written without a Pydantic error. This is what turns the invariant from a promise into a compile-time guarantee.

2.4.1 _aggregate_evidence

Given the list of SurvivedReports from surviving modules, flatten each module's EvidenceChain.links into a single chain preserving insertion order. Inherit claim = user_input, reasoning = "aggregated from N survived modules". This is the input to the threshold check and, if the threshold fails, the input to the Gap Resolver's gap extraction.

Phase L closed the drift where the earlier skeleton fabricated tier-B stubs here. The current implementation strictly forwards real evidence produced by Phase 1's Builder pipeline.

2.4.2 Threshold check — heuristic vs conformal-derived tau

aggregate_confidence = weighted mean of link relevance_score, weighted by provenance.tier. Compare to tau. If tau is derived from a conformal calibration file (Q.12), it replaces the heuristic 0.85. Empty calibration file ⇒ heuristic is used (never worsen the baseline).

Additionally: even with confidence ≥ tau, we require at least one tier-A or tier-B evidence link. A plan supported only by tier-C or provisional evidence is abstained on. This is the "tier-A/B requirement" of the trust-tier design.

2.4.3 Cloud teacher consultation (Q-Fix.D / Q.15)

BEFORE emitting any AbstentionReport with reason corpus_gap, Phase 3 consults the cloud teacher (gpt-oss:120b-cloud by default). The teacher receives the user input + partial evidence + the current confidence + the intended abstention reason; it returns a TeacherVerdict Pydantic with either confirms_abstain=True (with rationale, added as a tier-A evidence link) or confirms_abstain=False with an alternative_answer and alternative_confidence.

If the teacher offers an alternative, the pipeline does NOT accept it directly. It emits a gap_request with gap_kind="teacher_candidate", forwarding the teacher's answer as a SEED into a new Phase 1 iteration. The teacher's answer is still subject to Saboteur / PRM / SMT gates. This preserves the invariant: the 7B is the primary, the teacher is the court of appeal, and the teacher's advice is verified before it becomes an answer.

2.4.4 Z3-SMT gate (Q-Fix.B.3 / Q.8)

For code-artifact answers with declared invariants (extracted from the contract's api_schema), run one final SMT check via pipelines/smt_verifier.py. Three outcomes:

- *sat*: attach a positive-evidence link; leave the answer alone.
- *unsat*: lower confidence by 0.2 and attach the human-readable UNSAT core. If the demoted confidence falls below tau, the answer becomes AbstentionReport(reason="unsat_core").
- *unknown* (timeout): if policy.smt_required = True, emit AbstentionReport(reason="proof_incomplete"). Otherwise, attach a proof_timeout note and keep the answer.

2.4.5 The seven typed abstention reasons

Reason	Trigger
corpus_gap	Aggregate confidence < tau, gap iterations exhausted
unsat_core	Z3 proved contract invariants unsatisfiable
recursion_cap	Phase 2 tier-5 emitted a recursion request at cap depth
proof_incomplete	Z3 timeout AND smt_required=True
execution_unachievable	Execution-mode rebuild-loop cap hit without passing tests
adversarial_rejection	Every generated candidate failed clash
cross_mode_divergence	Cross-mode validation (Q.11) found conflicting answers between modes

Every reason maps to a specific tier or check earlier in the pipeline. There is no "unknown" reason — if Phase 3 can't identify why it's abstaining, that's a bug in the diagnostic emission, not a valid runtime state.

2.5 The outer loop — main.py

2.5.1 Structure

main.py:run(user_input, root) wraps the four-phase flow in a bounded while loop that owns:

1. Fast-path classifier + answer cache (M.9). Cache-hit returns immediately; the four-phase pipeline is skipped entirely.
2. Clarification gate (Q.14). Ambiguous requests trigger a bounded question back to the user; unambiguous ones proceed.
3. Pipeline recursion budget (max_pipeline_recursion, default 3). When Phase 2 tier-5 emits a PipelineRecursionRequest, the outer loop either consumes it (increment depth, re-enter Phase 0 with FullContext) or, at cap, forces Phase 3 to emit AbstentionReport(reason="recursion_cap").
4. Gap iterations budget (max_gap_iterations, default 3). When Phase 3 emits an AbstentionReport with a gap_request, the outer loop invokes the Gap Resolver, ingests any new chunks, and re-enters Phase 0. At cap, the abstention becomes final.

2.5.2 Why bounded, not unbounded

The plan explicitly commits to "no latency budget" but not to "no recursion budget". Two different concepts:

- No latency budget = individual LLM calls can be as long as needed; ToT can be depth 10; best-of-N can be 512.
- Bounded recursion = the OUTER loop must terminate. Unbounded outer loop is not "quality over latency" — it's "no termination guarantee", which is a correctness bug (users can wait forever with no answer).

The bounded outer loop guarantees termination while allowing arbitrary inner compute.

Part 3 — The substrate (retrieval, embeddings, graph, corpus)

Part 2 explained what happens when a Builder or Saboteur says "retrieve evidence". Part 3 explains what "retrieve evidence" actually does. Every retrieval call in ClaudeDeep passes through the same substrate: dense embeddings (bge-m3), sparse lexical (BM25), rank fusion (RRF), cross-encoder rerank (bge-reranker-v2-m3), graph traversal (FalkorDB + GLiNER NER), parent-document expansion, and trust-tier scoring. This part walks that pipeline stage by stage, explains what each stage buys and what it costs, and documents the corpus that feeds all of them.

3.0 The three retrieval query semantics

ClaudeDeep uses *three semantically distinct* retrieval modes. They are enforced by subtype: SupportingQuery, CounterQuery, IntegrationQuery (plus ArchitecturalQuery for Phase 0). A Builder is only allowed to construct a SupportingQuery. A Saboteur is only allowed to construct a CounterQuery. A Phase 2 tier-2.5 proofing verifier is only allowed to construct an IntegrationQuery. The type system forbids the wrong caller from asking the wrong question.

Query	Caller	Semantic domain	Returns
SupportingQuery	Builder (Phase 1)	Best-practice implementations of module M	Helpful implementation patterns, canonical code paths, well-cited approaches
CounterQuery	Saboteur (Phase 1)	Anti-patterns, failure modes, wrong implementations of module M at effort E	Documented bugs, edge cases, corner cases, known-bad patterns
IntegrationQuery	Phase 2 tier-2.5 verifier	Boundary patterns between module A and module B	Compatibility patterns, interface design, integration test scaffolds
ArchitecturalQuery	Master Orchestrator (Phase 0 only)	High-level architectural patterns for the request	System-level design references, precedent architectures

The type-system enforcement matters because these queries are not interchangeable. A Builder that accidentally issues a CounterQuery would ground its plan in anti-patterns, producing a "plan" that's a catalog of things to avoid. A Saboteur that accidentally issues a SupportingQuery would attack the plan from within its own evidence, guaranteed to find no contradictions. The subtype separation makes both errors compile-time impossible.

3.1 CompiledQuery — the deterministic compiler (Q-Fix.M.2)

Why it exists

A raw QueryIntent from an LLM is a Pydantic model that says "module=raft, intent=supporting, constraints=[strongly consistent, leader-elected]". It does NOT say "run this exact vector search string over the bge-m3 embedding, then this exact Cypher pattern against FalkorDB". The compilation step is what turns the semantic intent into deterministic, replayable machine-executable queries.

What it is responsible for

compile(intent) → CompiledQuery(vector_q, graph_pattern, filters). The compilation is pure: same intent always compiles to the same query. No LLM is involved. This is what makes retrieval REPLAYABLE — a telemetry event records the CompiledQuery, and any debugger can re-execute it later against the same substrate and get the same hits back.

How it hands off

«compile(intent)» → *CompiledQuery* → «GraphRAGEngine.query_compiled(compiled, semantic, module_id, effort_level)». The engine's query_compiled is the ONLY callable that hits _run; raw SupportingQuery(...) constructors are removed from all call sites (verified by property test test_compiled_query_invariant.py).

3.2 GraphRAGEngine — the façade

graphrag/engine.py:GraphRAGEngine is the single entry point to retrieval. It owns instances of:

- lancedb (dense adapter — real when installable, in-memory otherwise)
- falkordb (graph adapter — real when reachable, in-memory otherwise)
- Optional hybrid (a HybridRetriever wrapping the dense adapter with BM25 + reranker)

Constructor probe-and-cache: at init time, the engine tests whether real backends are available and picks the right adapter. Every construction is a telemetry event noting which adapter was chosen. This is the "no stub in default runtime" rule (Codex, Q-Fix.A) — real when possible, in-memory fallback only when substrate is unavailable, never a stub in the default path.

Query dispatch

query_compiled(compiled, semantic="supporting"|"counter"|"integration", module_id, effort_level, excluded_chunk_ids=None):

1. If a hybrid retriever is attached, delegate to it (§3.6).
2. Else, run the dense adapter's search and the graph adapter's traverse in parallel; merge, sort, truncate.
3. Apply the trust layer (§3.9) to re-score each hit by tier × recency × corroboration.
4. Filter out any chunk in excluded_chunk_ids (Q-Fix.H disjoint-filter path).
5. Emit a telemetry event with the replay_inputs = {compiled_query, top_k_returned, latency_ms, adapter_kind}.

3.3 Dense retrieval — LanceDB + bge-m3

Why bge-m3 (Q-Fix.E.2)

Three properties made bge-m3 the choice:

- 1024-dimensional dense embeddings — enough resolution for a 10M-doc corpus without inflating index size (a 768-d model is comparable in retrieval quality on English but weaker on multilingual technical text).

- Multilingual by design — the corpus contains technical text in English but reserves the option to add non-English CS references (papers in Chinese, Russian, etc.) without swapping embedding models.
- Long-context support — up to 8192 tokens per document, which lets us embed the full parent-document chunks (§3.7) without truncation loss.

Why LanceDB

LanceDB is columnar with HNSW indexing and IVF-PQ quantization for large-scale ANN. Compared to alternatives:

- *Qdrant / Milvus*: comparable performance, but require a running server process. LanceDB is embedded (no server), which fits ClaudeDeep's "runs on the user's machine" default.
- *FAISS*: fast but persistence and update semantics are awkward. LanceDB stores to disk as `.lance` files that survive restarts and support incremental writes.
- *pgvector*: fine but requires Postgres, which is another moving part.

Adapter architecture

graphrag/real_lancedb_adapter.py:RealLanceDBAdapter is the production adapter. It reads the embedding model name from config/models.yaml (defaults to BAAI/bge-m3) via pipelines/model_config.py. The embedder is lazy-loaded on first use to avoid dragging in transformers at import time.

The in-memory fallback (graphrag/lancedb_adapter.py:LanceDBAdapter) is a Python dict keyed on module_id; it exists only for tests and for the "no substrate available" path. Under Q-Fix.E.1 it is never the default.

3.4 Sparse retrieval — BM25

Dense retrieval has a known failure mode: it clusters by *semantic* similarity, which misses hits that share *lexical* tokens the model doesn't consider semantically close. A query for "epoll" may score a chunk about "kqueue" higher than a chunk that literally contains "epoll", because the dense model has learned they are related I/O multiplexing APIs. That's usually right, but sometimes the user literally wants the epoll chunk and only the epoll chunk.

BM25 is the classical lexical fix. It scores hits by exact-token overlap with an IDF weighting that penalizes common words. The rank_bm25.BM25Okapi implementation is the lightest option that gets the math right. ClaudeDeep runs BM25 over a shadow index built at corpus-index time, in parallel with the dense index.

3.5 RRF — Reciprocal Rank Fusion

Why not just add the scores

Dense and BM25 produce scores on incomparable scales — dense scores are cosine similarities in [0, 1] (roughly), BM25 scores are unbounded floats reflecting IDF-weighted TF products. Adding or averaging them requires normalization, and any normalization is a free parameter the user shouldn't have to tune.

The RRF formula

```
fused_score(chunk) = SUM over sources i of  1 / (k + rank_i(chunk))
```

where rank_i(chunk) is the chunk's rank in source i's ranked list (1-indexed), and k is a small constant (default 60, from Cormack et al.'s SIGIR 2009 paper). The important properties:

- Rank-based, not score-based — no normalization needed.
- Diminishing returns — being top-1 in both sources beats being top-1 in one and top-100 in the other by a bounded factor.
- Robust to missing rankings — if a chunk appears only in the dense results, its RRF is just 1 / (k + rank_dense); the missing BM25 rank contributes nothing.

Where it fits

pipelines/hybrid_retriever.py:HybridRetriever.search() runs dense and BM25 in parallel, fuses via RRF, keeps top-50, then hands to rerank. Everything upstream just calls engine.query_compiled(...); the fusion is invisible to Builder / Saboteur / etc.

3.6 Cross-encoder rerank — bge-reranker-v2-m3

Why rerank at all

Dense embeddings are BI-encoder: query and document are encoded independently, and their similarity is a dot product. That's fast (any document can be pre-indexed) but coarse (the model never sees the query and document in the same forward pass). A cross-encoder concatenates [CLS] query [SEP] document [SEP] and runs one forward pass over the joint sequence, producing a scalar relevance logit that reflects true pairwise interaction. It is slower (must run per (query, document) pair) but more accurate.

The right pattern is: use bi-encoder + BM25 to CANDIDATE, use cross-encoder to RERANK. That gives you the recall of the fast retrievers plus the precision of the slow cross-encoder.

Why bge-reranker-v2-m3 specifically

- Same model family as bge-m3 (BAAI), so tokenization and multilingual behavior are consistent.
- Small enough (568M params) to run on CPU or a corner of the GPU without hurting the primary LLM's residency.
- Already cached — used both as the reranker in retrieval AND as the CrossEncoderPRM backend (Appendix B.1.2), so one download serves two purposes.

How the scoring works

See Appendix B.1.2 for the full logits-to-score derivation. Summary: cross-encoder emits raw logit, sigmoid maps to [0, 1], top-K by score becomes the final result list.

3.7 Parent-document chunking (Q-Fix.E.4)

The tension chunking must resolve

Two incompatible desires:

- Embeddings work best on *small* chunks (~512 tokens). Too large and the embedding averages over too many concepts, losing precision. Too small and it loses context.
- LLMs work best on *large* chunks (~4096 tokens). Too small and the LLM lacks the surrounding context needed to interpret the chunk. Too large and it hits the context window and gets lost in the middle.

Parent-document chunking resolves this by using DIFFERENT sizes for indexing and serving:

- **Child chunks** (~512 tokens): what we embed and BM25-index. Small enough for precise retrieval.
- **Parent chunks** (~4096 tokens): what we return to the LLM as context. Large enough to preserve surrounding meaning.

Each child stores a back-pointer to its parent. Retrieval: find the child, serve the parent. The LLM sees richer context than the ranking was based on, without diluting the retrieval signal.

Implementation

scripts/index_corpus.py:chunk_text_token_aware() uses the embedder's tokenizer to split. Children are stored as rows in the LanceDB table; each row has a parent_text field holding the parent block. On retrieval, RealLanceDBAdapter.search() returns the parent_text when available (so the consumer gets the parent), while ranking is against the child embedding.

3.8 Graph store — FalkorDB + GLiNER (Q-Fix.E.5)

Why we have a graph at all

Some queries are relational, not semantic. "Which chunks mention BOTH Raft AND leader election?" is a boolean-and query over entity mentions, not a semantic-similarity query. A graph store answers these efficiently: MATCH `(c:Chunk)-[:MENTIONS]->(e1:Entity {name: "Raft"})`, MATCH `(c)-[:MENTIONS]->(e2:Entity {name: "leader election"})`, return `c`.

Vector search can approximate this (embed "Raft AND leader election"), but the results are softer — they'll surface chunks that are semantically NEAR both without necessarily mentioning either. For a fact-lookup query, that's not what you want.

Why FalkorDB

FalkorDB is a Redis-backed Cypher-compatible graph database. Compared to alternatives:

- *Neo4j*: mature, but heavier and needs its own JVM process. FalkorDB is a Redis module, tiny footprint.
- *ArangoDB / DGraph*: overqualified for our simple entity-mention graph.
- *NetworkX in-memory*: fine for tests but doesn't persist.

Entity extraction — two-pass with fallback chain

graphrag/real_falkordb_adapter.py::_LazyNER tries three extractors in order:

1. **GLiNER** (urchade/gliner_small-v2.1). A transformer NER that outputs per-span logits (see Appendix B.1.5) and takes an arbitrary set of type labels. We give it labels like ["library", "framework", "language", "person", "organization", "publication", "model", "method", "theorem"] and it labels spans accordingly.
2. **spaCy** (en_core_web_sm). The classic fallback when GLiNER isn't installable.
3. **Capitalized-word heuristic**. Ultra-simple: any sequence of capitalized words separated by spaces, minimum length 2 tokens, becomes an "Entity" of type "OTHER". Used only when neither ML model is available.

LLM-verified edges (optional, quality-max)

When an entity is extracted, an optional pass sends (chunk_text, entity_A, entity_B) to a small LLMStage that returns a boolean "do these entities have a real relationship in this chunk?". Only verified edges MERGE into FalkorDB. Falls back to "all heuristic-extracted edges accepted" when no LLM is wired.

3.9 Trust layer — provenance-graded scoring (Q-Fix.M.2)

Why raw retrieval scores are not enough

A hit from a StackOverflow post and a hit from a Sipser textbook can have similar cross-encoder logits, but they should NOT contribute equally to Builder's plan. The trust layer stratifies retrievals by source quality before they enter downstream reasoning.

Trust tiers

Tier	What it contains	Weight
A (full trust)	Canonical textbooks (CLRS, Sipser, TAOCP) + official language/library docs + peer-reviewed papers + ISO / IEEE / RFC standards	1.0
B (high trust)	Well-regarded conference papers + official OSS repositories + authoritative technical books	0.8
C (moderate trust)	StackOverflow (upvote-thresholded) + community-vetted OSS + Wikipedia on technical topics	0.5
provisional	Freshly ingested chunks from gap-resolver web search; not yet promoted	0.4
rejected	AI-generated content, blogs without editorial control, paywall-pirated content, marketing pages, content flagged by safety classifiers	0.0 (never indexed)

Scoring formula

```
trust_score(hit) = tier_weight  *  recency_factor  *  corroboration_bonus

recency_factor      = exp( -age_days / half_life_days )      (half_life default 365)
corroboration_bonus = min(1.0, 0.2 * count_of_other_sources_with_same_chunk_id_content)
```

Applied AFTER the reranker sigmoid, BEFORE truncation to top-K. A tier-A hit with age 0 and 5 corroborating sources hits weight 1.0 × 1.0 × 1.0 = 1.0. A tier-C hit, 5 years old, unique source hits 0.5 × 0.007 × 0.2 ≈ 0.0007 — effectively dropped.

Downstream contract

Phase 3's threshold check requires *at least one tier-A or tier-B evidence link* supporting the answer. A plan whose evidence chain is entirely tier-C or provisional is abstained on regardless of aggregate confidence. This is the "practitioner-balanced" rule — low-tier evidence can inform, but must be corroborated by high-tier evidence to cross the answer threshold.

3.10 The starter corpus — 857 chunks, 13 canonical sources (Q-Fix.P)

As of May 2026 the operational corpus is a curated starter: 13 public-license sources indexed into 857 parent-document chunks. Every source is redistributable; every chunk is tier-B by default (canonical but not the top-tier textbooks the user will provide later).

Source	Coverage
SICP (full HTML, MIT-licensed)	Algorithm fundamentals, lambda calculus, environment model
Operating Systems: Three Easy Pieces (OSTEP)	Processes, scheduling, memory, persistence, concurrency
Crafting Interpreters (Bob Nystrom)	Pratt parsers, tree-walk interpreters, bytecode VMs
Beej's Guide to Network Programming	Sockets, TCP/UDP, select/poll/epoll
Software Foundations Vol. 1	Coq tactics, proof structure
arXiv classics (Paxos, Raft, MapReduce, Attention Is All You Need, BERT, GPT-3)	Foundational papers
Python 3 official docs (subset: stdlib, typing, async)	Standard library reference
MDN JS references (subset)	Language + runtime API
The Rust Book	Language and ownership model

Tier-A textbooks (CLRS, Sipser, TAOCP, Dragon book, Hopcroft-Motwani-Ullman) are called out by the plan as the user-provided extension — drop them into corpus/user/<topic>/ and re-run scripts/index_corpus.py. Indexing is idempotent (content-hash IDs), so re-runs upsert; existing chunks are not re-embedded.

3.11 The ingestion pipeline — how a raw file becomes a hit

scripts/index_corpus.py is the entry point for both initial curation and gap-resolver ingestion. The stages, in order:

1. **File load.** Read raw text from the source file. Detect language and format (Markdown, HTML, PDF via pdfplumber, plain text).
2. **Provenance tagging.** Attach a ProvenanceRecord: source URL / filepath, tier (from the source's directory placement or manifest), retrieved timestamp, license, author if available.
3. **ChunkSaboteur screen (only for gap-resolver ingestion).** The freshly retrieved chunk is red-teamed by gap_resolver/chunk_saboteur.py for prompt-injection payloads, low-quality-content signatures, adversarial content. On fail, the chunk is dropped and logged as an adversarial counter-example. On pass, continue.
4. **MultiPassSaboteur screen (Q.9, quality-max only).** Five attack families are applied independently: injection, noise, duplicate detection (via MinHash), bias, contradiction against already-accepted corpus. A chunk is promoted only after unanimous pass. Rejected chunks are persisted to RejectedChunkLog.
5. **Parent-document chunking.** Token-aware split into child (~512 tok) + parent (~4096 tok) pairs, with back-pointers preserved.
6. **Embedding.** Each child is embedded by bge-m3 to a 1024-d vector.
7. **LanceDB insert.** Vector + child_text + parent_text + provenance + content_hash go into the LanceDB table. Content_hash makes re-indexing idempotent.
8. **BM25 index update.** Add child_text tokens to the sparse shadow index.
9. **Entity extraction.** GLiNER (or fallback) runs over parent_text; each detected entity becomes a MERGE (c:Chunk {id: chunk_id})-[:MENTIONS]->(e:Entity {name: entity_name, type: entity_type}) Cypher upsert into FalkorDB.
10. **(Optional) LLM edge verification.** For each entity pair mentioned in the same chunk, ask a small LLMStage whether the pair has a real relationship in context. Verified edges add a RELATES edge to FalkorDB.

The whole pipeline is idempotent, incremental, and observable. Each stage emits a telemetry event; a re-run of index_corpus.py --report summarizes counts and diffs against the previous run.

3.12 Substrate output — GraphRAGHit

Every retrieval call returns list[GraphRAGHit]. One GraphRAGHit:

- chunk_id: str — content-hash-derived, stable across indexings.
- text: str — the parent-document text (not the child), so the consumer gets full context.
- score: float — the final trust-scored relevance in (0, 1].
- provenance: ProvenanceRecord — tier, source URL, timestamp, license.
- replay_inputs: dict — the compiled query that produced this hit, for telemetry replay.

Consumers (Builder, Saboteur, sub-claim verifier, Phase 3 evidence aggregator) all accept list[GraphRAGHit]. They never construct one themselves. The substrate owns hit production; downstream owns hit consumption. The boundary is enforced by the type.

3.13 Substrate invariants — recap

- **CompiledQuery is the only retrieval surface.** Every call to engine.query_compiled(...) is preceded by a QueryIntent → compile() step. Property test enforces.
- **Real adapters are the default when reachable.** In-memory stubs are test-only.
- **Trust tier gates enter the answer contract.** Phase 3 requires tier-A/B evidence for any AnswerReport.
- **Every hit is replayable.** The telemetry event carries the compiled query and the top-K chunk_ids; a debugger can re-execute against the same substrate and get the same list.
- **Ingestion is idempotent.** Content-hash IDs mean re-runs upsert; existing hits are not re-embedded.

Part 4 — The verifiers (PRMs, cross-encoders, generative critics, conformal calibration)

The pipeline in Part 2 produces candidate answers. Part 4 is what decides whether those candidates are worth trusting. Every quality signal in ClaudeDeep — agreement-weighted voting, PRM scoring, tree-search selection, conformal-calibrated abstention — lives in this layer. This part explains how each verifier works, what it takes as input, what it emits, and how the results compose into the final confidence $\in [0, 1]$ that gates Phase 3.

4.0 The verifier stack — one call site, four consumers

There is exactly one call site where the "how good is this candidate" question is asked: pipelines/llm_stage.py:LLMStage._best_of_n(). Four independent verifiers plug in there and their outputs compose multiplicatively:

```
final_confidence(winner) =
    agreement(winner)       # from canonical clustering
  * prm_score(winner)       # from Part 4.1-4.6
  * subclaim_fraction       # from Q.5 sub-claim decomposition (Part 4.7)
  * ucb_selection_factor    # from tree search when engaged (Part 4.8)
```

Each factor is in [0, 1]. Any single factor going to zero collapses confidence to zero. This is the "any weakness is fatal" property — ClaudeDeep would rather abstain than emit an answer that failed even one check.

4.1 PRM — the family of five verifiers plus one router

Q-Fix.N (May 2026) refactored PRM dispatch from a single class into a typed family of five concrete kinds plus a schema-aware router. Diagram 6 (Appendix A) is the picture; this section is the text.

4.1.1 Why five, not one

Three orthogonal reasons force separation:

- **Different verifiers have different training objectives.** A cross-encoder reranker (bge-reranker-v2-m3) is trained on relevance. A CodePRM is trained on correctness with execution feedback. A ThinkPRM is trained on step-by-step verification CoTs. Forcing them all into "cross-encoder regressor" throws away what makes each valuable.
- **Different verifiers have different hardware profiles.** HeuristicPRM needs no GPU, no download. CrossEncoderPRM needs ~600 MB VRAM. GenerativeThinkPRM needs 3–28 GB VRAM depending on model size. A single class cannot express these ranges.
- **Different schemas benefit from different verifiers.** Code plans benefit from cross-encoder relevance signals; abstract reasoning benefits from generative per-step critique. The SchemaRoutedPRM picks the right one automatically.

4.1.2 HeuristicPRM — the always-available baseline

Why it exists

A candidate is worth trusting more if its Pydantic representation is "densely populated" — every string field has content, every list has entries, no field is at its default. A candidate that's barely-valid (all defaults, empty strings, empty lists) usually indicates the decoder produced a stub because it didn't know the answer. HeuristicPRM catches these without ML.

What it computes

```
score = mean( coverage, density, structure )

coverage  = non-default-non-empty fields / total fields
density   = mean( per-string-field density ), capped at chars=80 -> 1.0
structure = fraction of list/dict fields that are non-empty
```

Where it fits in the fallback chain

Every other PRM kind falls back to HeuristicPRM on load failure or inference error. This is what makes the additive-only invariant hold: even if bge-reranker won't load, even if ThinkPRM OOMs, even if the user hasn't downloaded any weights, HeuristicPRM produces a non-trivial [0, 1] score. Quality degrades but never crashes.

4.1.3 NoOpPRM — identity for ablations

Always returns 1.0. Byte-equivalent to prm_enabled=False. Exists only to let tests exercise the PRM code path without changing scores. In production, it would let a low-agreement stub win a best-of-N vote, which is bad; you would only pick it deliberately to measure how much lift the real PRMs are providing.

4.1.4 CrossEncoderPRM — the cached-model default

Why it is the practical default

The bge-reranker-v2-m3 weights (~600 MB) are already cached because they are also used as the reranker in Q-Fix.E.3 hybrid retrieval. Zero additional download. No dedicated GPU allocation needed — a single forward pass fits alongside gpt-oss:20b when model_swap=True. Under most operating conditions, CrossEncoderPRM is the best quality-per-hardware-cost tradeoff.

Two backends, tried in order

The lazy backend loader tries:

1. sentence_transformers.CrossEncoder(model_name) — the natural home for a cross-encoder model. Works for bge-reranker-v2-m3, mxbai-rerank, etc.
2. transformers.AutoModelForSequenceClassification.from_pretrained(model_name) — fallback for models that ship as a Transformers regression head rather than a sentence-transformers CrossEncoder. Works for a trained real CodePRM (once available) that follows the same architecture.

Both paths emit a single scalar logit; sigmoid maps to [0, 1]. See Appendix B.1.2 for the full logit-to-score derivation.

Why we chose sigmoid over softmax

See Appendix B for the full rationale. Summary: the reranker emits ONE logit per (query, passage) pair. Sigmoid is the correct inverse of a single scalar. σ(0) = 0.5 gives a natural neutral midpoint so a logit near zero doesn't skew the combined score.

4.1.5 GenerativeThinkPRM — the CoT-critic verifier

Why it exists

Cross-encoder rerankers give a single opaque score. If they say 0.7, you don't know WHY they said 0.7 — whether steps 1–3 are correct and step 4 is wrong, or all steps are half-right. ThinkPRM (arxiv 2504.16828) is trained to produce an EXPLICIT step-by-step critique with per-step labels. This gives per-step visibility, and the per-step labels compose into a natural fraction-correct score.

Mechanism

Loaded as AutoModelForCausalLM. Prompted with the canonical ThinkPRM template (problem + step-by-step solution), invoked with do_sample=False, temperature=0.0 for deterministic greedy decoding (Appendix B.1.4). The generated critique is parsed with two regex families:

```
BOXED  =  \\boxed{correct|incorrect}      -> preferred, ThinkPRM's canonical format
INLINE =  step N is (correct|incorrect)   -> fallback for looser formats
```

Score = correct / (correct + incorrect); 0.5 if no labels parse.

Hardware tradeoff

launch/ThinkPRM-1.5B is 4 GB in BF16, 3–10 s/call on CPU. launch/ThinkPRM-7B is 14 GB, too big to co-reside on the 4060 Ti with gpt-oss:20b unless we swap. Q-Fix.N's model_swap mechanic is the mitigation (see 4.2).

Why greedy, not sampling

The PRM is a VERIFIER, not a proposer. Non-determinism defeats its purpose: the same candidate must produce the same PRM score. Sampling would inject noise into the final confidence, defeating the whole point of a reproducible verifier.

4.1.6 CodePRMScaffold — the integration point for real CodePRM

Status

CodePRM (ACL 2025 Findings 428, Li et al.) describes the training pipeline but does NOT publicly release weights as of 2026-05. The scaffold exists so that when weights DO ship, the user drops them at CLAUDEDEEP_CODEPRM_WEIGHTS=/path/to/dir and the runtime picks them up without any code change.

Behavior when weights are absent

Falls back to self.fallback (default: CrossEncoderPRM with bge-reranker-v2-m3). The additive-only invariant means an empty weights path never degrades to a silent no-op — it delegates to the strongest verifier that IS available.

Behavior when weights are present

Loads as AutoModelForSequenceClassification (CodePRM's published architecture). Forward pass produces a scalar logit per (prompt, output) pair; sigmoid to [0, 1]. Wire-level identical to CrossEncoderPRM once the weights are loaded — but the underlying distribution is calibrated to code correctness rather than passage relevance, which is why the class exists as a separate name.

4.1.7 SchemaRoutedPRM — the top-level router

Why it is the quality-max default

Different candidate schemas want different verifiers. A Plan or CodeArtifactBundle benefits from CodePRM-style code-correctness scoring. A SabotageResponse is natural-language critique — the wrong shape for a cross-encoder trained on code relevance; ThinkPRM's per-step critique is a better fit. Manually configuring one PRM per module type would be brittle; the router does it automatically based on type(parsed).__name__.

Routing table

```
schema_name in {"Plan", "CodeArtifactBundle", "Patch", "Diff"}
    -> code_prm  (CodePRMScaffold, falling back to CrossEncoderPRM)

schema_name NOT in code_schemas
    -> reasoning_prm  (GenerativeThinkPRM, falling back to HeuristicPRM)

any exception in the routed PRM
    -> fallback  (HeuristicPRM)
```

The router does not itself score anything. It picks the right specialist and delegates.

Why SabotageResponse routes to reasoning, not code

This is a deliberate design choice worth understanding. A Saboteur attacking a code module still emits NATURAL-LANGUAGE critique text. The content is "here's why this plan is broken", not "here's the fixed code". Sending that to a code-correctness verifier would mis-apply the verifier's training. ThinkPRM's per-step critique matches the shape of a SabotageResponse.attack_findings list better than any code PRM would.

4.2 model_swap — the GPU pressure release valve

Why the mechanic exists

The user's target hardware is a 4060 Ti with 16 GB VRAM. gpt-oss:20b at MXFP4 quantization occupies ~13 GB of it, leaving ~3 GB free. Loading GenerativeThinkPRM-1.5B (4 GB BF16) alongside is a straight OOM. Loading ThinkPRM-7B (14 GB) is not even close. Two paths forward:

- Refuse to run these PRMs on limited-VRAM machines. Unacceptable — the whole point is that the pipeline runs on the user's actual hardware.
- Load the PRM only for the duration of a singlescore() call, then release it. This is model_swap=True.

Lifecycle

```
score(...) called:
    if self._model is None:
        # first call
        self._tokenizer = AutoTokenizer.from_pretrained(self.model_name)
        self._model     = AutoModelFor*.from_pretrained(self.model_name).eval()
        # subsequent calls under model_swap=True re-enter this branch each time,
        # because _release() nulls out _model after each score.

    return score
    ...
    if self.model_swap:
        _release()
            del self._model
            del self._tokenizer
            self._model = None
            self._tokenizer = None
            gc.collect()
            torch.cuda.empty_cache()
            torch.cuda.synchronize()
```

Cost profile

Config	Per-call latency (bge-reranker)	Per-call latency (ThinkPRM-1.5B)	Per-call latency (ThinkPRM-7B)
swap=False on datacenter GPU	~50 ms	~200 ms	~400 ms
swap=True on 4060 Ti	~1 s (load overhead dominates)	~3–5 s	~6–8 s
swap=True on CPU	~2 s	~15 s	~120 s

Multiply by the number of PRM calls per LLMStage. Under quality-max with best-of-N=64 and one PRM call per winning cluster, that's roughly 1 PRM call per LLMStage. Under tree search with PRM-scored expansion, it's up to K per node, up to depth 3 — potentially 100+ PRM calls per LLMStage. On a 4060 Ti with ThinkPRM-1.5B and model_swap=True, that's ~5–10 minutes of wall-clock per module in Phase 1. Quality-max accepts that cost; a performance-tuned deployment would set model_swap=False on a bigger GPU.

Configuration precedence

The model_swap value is read from (highest to lowest priority):

1. CLI flag --prm-model-swap true|false
2. Environment variable CLAUDEDEEP_PRM_MODEL_SWAP=true|false
3. Mode YAML field prm_model_swap: true (or in the quality-max overlay)
4. Policy default: True (safe on any hardware)

4.3 The default_prm factory — nine kinds, one entry point

pipelines/prm.py:default_prm(enabled, kind, code_model, reasoning_model, codeprm_weights, model_swap, device, max_new_tokens) is the only PRM construction surface. Dispatched on kind:

kind	Returns
"auto" or "heuristic"	HeuristicPRM (safe baseline; no downloads)
"noop"	NoOpPRM (identity, always 1.0)
"cross_encoder"	CrossEncoderPRM (default: bge-reranker-v2-m3)
"codeprm"	Legacy alias for cross-encoder with CLAUDEDEEP_CODEPRM_MODEL env var
"thinkprm"	Legacy alias for cross-encoder with CLAUDEDEEP_THINKPRM_MODEL env var
"codeprm_scaffold"	CodePRMScaffold with cross-encoder fallback
"generative_thinkprm"	GenerativeThinkPRM with launch/ThinkPRM-1.5B default
"schema_routed"	SchemaRoutedPRM (recommended; wraps CodePRMScaffold + GenerativeThinkPRM)
enabled=False (any kind)	None (byte-equivalent to legacy PRM-disabled path)

The factory reads env vars at call time, allowing runtime overrides without editing YAML. CLI flags in main.py translate to env vars before run() loads policy, so the CLI ultimately writes to the same store the factory reads from — one authoritative source at construction time, no drift between flag / env / YAML paths.

4.4 The agreement fraction — canonical clustering

Why canonical clustering, not embedding similarity

best-of-N sampling produces N parsed Pydantic candidates. To pick a "winner" we need to cluster them and count. Two options:

- *Embedding similarity*: embed each candidate, cluster by cosine similarity, winner is largest cluster's centroid. Rejected because semantically equivalent Pydantic with different field ordering would embed to different vectors, splitting the vote.
- *Canonical form match*: dump each candidate to canonical JSON via parsed.model_dump_json(), cluster by exact string equality, winner is Counter.most_common(1). Pydantic's canonical form guarantees consistent key ordering, so structurally-equivalent candidates always collide into the same cluster.

The canonical-form choice is what makes agreement a MEANINGFUL signal. Two syntactically identical answers must count as agreement; two semantically different answers with the same words in different order must NOT count as agreement.

Agreement fraction as a factor

```
agreement = winning_cluster_size / N
```

With N=64, agreement=1.0 means all 64 samples produced the identical canonical form (rare in practice). agreement=0.5 means half the samples clustered together. agreement=1/N=0.016 means every sample was unique — a strong signal that the model has no consistent answer.

4.5 Stratified sampling across the ensemble (Q-Fix.F.3)

Why the previous design was wrong

Before Q-Fix.F.3, ensemble use looked like: for each of N samples, ask the MultiModelEnsemble to return a single-vote-consensus over all members. That meant one "sample" was actually len(members) parallel calls, and each ensemble member always saw the exact same prompt each time. Total cost: N × len(members). Total diversity: still just N distinct prompts.

The fix

pipelines/stratified_sampler.py:StratifiedSampler splits the two layers:

```
for i in 0..N-1:
    member = members[i % len(members)]
    yield await member.decode(...)
```

Round-robin distribution. N samples, each from ONE ensemble member. Total cost: N calls (not N × len(members)). Total diversity: N distinct samples spread across len(members) models. Cheaper AND more diverse.

LLMStage._best_of_n uses StratifiedSampler when its self.client is a MultiModelEnsemble. Otherwise it falls through to the single-client path (each sample from the same client with different temperature).

4.6 Tree-of-Thoughts with UCB1 (Q.7 + Q-Fix.F.4)

Why linear best-of-N isn't always enough

best-of-N samples N independent attempts. It cannot REFINE an attempt — if sample 1 has the right structure but a wrong step, sample 2 either starts over or by chance produces the same structure with a different wrong step. Tree-of-Thoughts extends best-of-N with refinement rounds: generate K root candidates, pick the best-scoring subset, expand each into K children via a "PREVIOUS ATTEMPT: ... IMPROVE IT" prompt, repeat to depth.

UCB1 expansion policy (Q-Fix.F.4)

At each round after the root, the search must decide which node to expand next. Pure score-greedy (always expand the current best) leads to premature convergence on a single branch. Pure exploration (random selection) wastes compute on unpromising branches. UCB1 is the classical multi-armed-bandit balance:

```
ucb1(node) = node.avg_score + c * sqrt( ln(parent_visits) / node.visits )

with c = sqrt(2), the theoretical default from Auer et al. 2002
```

Nodes with high average score are preferred (exploitation). Nodes with few visits get a boost proportional to sqrt(ln(N)/n) (exploration). Unvisited nodes have infinite UCB1, so every branch is explored at least once before repeated expansion.

Termination

Depth cap: policy.tree_depth (default 2 in baseline, 3 under quality-max). Terminal selection: leaf with highestavg_score becomes the winner.

4.7 Sub-claim decomposition (Q.5, wired via Q-Fix.B.1)

Covered in Part 2.2.7 from the pipeline perspective. From the verifier perspective, it's an additional quality signal that composes multiplicatively:

```
subclaim_fraction = surviving_claims / total_claims
final_confidence *= subclaim_fraction
```

A plan with 4 of 5 claims verified gets confidence × 0.8. A plan with 0 of 5 claims verified gets confidence × 0 — forcing abstention. This is the point: sub-claim verification is a hard veto on un-groundable plans, not a soft nudge.

4.8 Conformal calibration (Q.12) — making 99% precision guaranteed

The problem with a fixed threshold

The default abstention threshold is 0.85. Nobody has verified that "confidence ≥ 0.85" actually means "answered correctly with 99% probability". The mapping depends on how the particular pipeline configuration produces confidence scores, and it drifts as substrate changes.

Conformal prediction — the guarantee

Given a held-out eval set of (confidence, was_correct) pairs, conformal prediction lets you compute the SMALLEST threshold tau such that precision(conf ≥ tau) ≥ 1 - epsilon, at a user-specified epsilon (default 0.01 for a 99% precision target). This is a distribution-free guarantee — no assumptions about the confidence distribution shape; only that the eval set is exchangeable with the deployment distribution.

ClaudeDeep's implementation

pipelines/conformal.py:ConformalCalibrator.load(json_path) reads a JSON of [{"confidence": float, "was_correct": bool}, ...]. It sorts by confidence, walks descending, and finds the smallest confidence value at which cumulative precision is still ≥ 1 - epsilon. That value replaces the heuristic 0.85 for the current process's lifetime.

The empty-file guarantee

If the calibration file is empty (or missing), the calibrator does NOT force zero abstention or unbounded coverage. It preserves the heuristic 0.85. This is the "never worsen the baseline" invariant — conformal calibration is an OPT-IN improvement, never a default degradation.

Runtime replay

Every ANSWER emission is logged as {"confidence": final_confidence, "was_correct": ?} to the training-emitter JSONL. Ground-truth labels come from downstream eval or user feedback; the (confidence, was_correct) pairs feed back into the calibrator on next process start. This makes the calibration self-improving on subsequent runs.

4.9 How the four factors compose — a worked example

Consider a Phase 1 LLMStage call with the quality-max defaults. best_of_n = 64, prm_kind = schema_routed, sub_claim_decomposition = True, search_strategy = tree, tree_depth = 3.

1. Tree search generates ~256 candidates across 4 expansion rounds (64 root + 4 × ~48 expansion). PRM scores each. UCB1 picks the winning leaf.
2. Winning leaf's parsed is canonicalized. Suppose 24 of the 64 root samples canonicalize to the same form as the winner — agreement = 24/64 = 0.375.
3. SchemaRoutedPRM dispatches the winner. It's a Plan, so goes to CodePRMScaffold. No real CodePRM weights, so falls back to CrossEncoderPRM. Returns 0.82.
4. Sub-claim decomposition: winner has 5 claims. GraphRAG returns tier-A/B evidence for 4 of them. subclaim_fraction = 0.8.
5. UCB1 selection factor: this is baked into "which leaf won", not multiplied separately. Effective factor = 1.0.
6. Composition: final_confidence = 0.375 × 0.82 × 0.8 × 1.0 = 0.246.

Result: final_confidence = 0.246, well below the 0.85 heuristic threshold and almost certainly below any conformal-derived tau. Phase 3 aborts to AbstentionReport(reason="corpus_gap"), triggers cloud teacher consult, and if the teacher confirms, hands off to Gap Resolver. The pipeline WOULD have emitted this answer under naive best-of-N (agreement alone was 0.375 > 0.3 threshold in that world) — the verifier stack correctly caught the low quality.

4.10 Verifier invariants — recap

- **Every verifier returns [0, 1].** No cross-model logit combinations. Each model produces its own sigmoid or fraction; composition is multiplicative.
- **Missing verifier → multiply by 1.0.** Absence of a verifier is additive-only (leaves the score unchanged), never subtractive.
- **Every model-backed verifier has a fallback chain** ending in HeuristicPRM. Load failure never crashes the pipeline.
- **Determinism.** Verifiers must be functions of their input. Sampling inside a verifier would defeat reproducibility of the composite confidence.
- **Never worsen the baseline.** Every opt-in (conformal calibration, ThinkPRM, ensemble) has a documented no-op path. Empty calibration → heuristic; missing weights → fallback; empty ensemble → single-client path.

Part 5 — The failure-recovery layer (gap resolver, cloud teacher, SMT gate, abstention)

Part 2 handles the happy path where every module produces a confidently-supported plan and every conflict resolves at tier 1 or 2. Part 5 is what happens when the pipeline can't do that. The design principle: **a wrong answer is worse than no answer**. Before Phase 3 emits an AbstentionReport, ClaudeDeep exhausts three lines of recovery: online knowledge retrieval (Gap Resolver), external verifier appeal (cloud teacher), and formal proof (SMT gate). Only after all three fail does the pipeline commit to abstention, and even then the abstention carries a typed reason and a full evidence chain so the user understands why.

5.0 Why failure recovery deserves its own layer

Most systems treat "the model couldn't answer" as a leaf error — the request fails, the user sees an exception, retry is manual. ClaudeDeep treats it as a first-class runtime condition with its own resolution machinery. Four reasons:

- **Different failure modes need different recovery.** A missing-corpus failure ("we don't have textbook chapters on Raft in our index") needs online retrieval to fill the gap. A confidence-below-threshold failure needs a stronger verifier's second opinion. A contract-invariant failure needs a formal prover. These are three distinct paths, not one.
- **Some failures are recoverable, some are not.** A corpus gap is recoverable by ingestion. An UNSAT contract is not — the contract itself is inconsistent, and no amount of retrieval will fix that. The layer distinguishes.
- **The user cares about the reason, not just the outcome.** "Corpus_gap" with a list of retrieved-but-rejected chunks is actionable ("give me the CLRS chapter on this topic"); "the model failed" is not.
- **Failure evidence feeds future runs.** Rejected chunks become adversarial training data for future Saboteur runs. Cloud teacher's declined answers become negative examples. The abstention log is a corpus of "here's where we still don't know".

5.1 The Gap Resolver — online knowledge retrieval

5.1.0 When it triggers

Phase 3 emits an AbstentionReport(reason="corpus_gap", gap_request=…) when aggregate confidence falls below tau AND the low-confidence links point at content that's plausibly retrievable online (external URLs, published papers, official docs). The gap_request carries the specific evidence gaps: which claims lack tier-A/B support and what would satisfy them.

The outer loop in main.py catches the gap_request and invokes gap_resolver/resolver.py:GapResolver.resolve(gap_request). On success, the resolver ingests new chunks into the substrate and returns; the outer loop re-enters Phase 0 with the enriched corpus.

5.1.1 The four-stage resolution pipeline

1. **Query synthesis.** For each gap, extract keywords + topic + implied source type (paper / doc / repo / textbook). Construct MCP-tool-typed queries: web_search for general lookup, arxiv_search for papers, github_search for code, paper_retrieval for Semantic Scholar / OpenAlex lookups.
2. **MCP retrieval.** Dispatch to real MCP handler bodies in mcp/handlers/. Each handler returns list[IngestedChunk] with provisional provenance stamped (tier = "provisional", source URL, retrieval timestamp, trust proxy from source domain).
3. **Adversarial screening.** Every retrieved chunk passes through ChunkSaboteur (single-pass legacy gate) and, under quality-max, MultiPassSaboteur (five attack families).
4. **Ingestion.** Chunks that pass screening are handed to graphrag/ingestion.py:ingest_chunk() which embeds + inserts into LanceDB + extracts entities into FalkorDB. The chunk is marked provisional (tier weight 0.4) until a maintainer or automated promotion criterion upgrades it.

5.1.2 What "resolved" means

The resolver returns without raising when at least one chunk has been ingested. The outer loop then re-enters Phase 0 with the enriched corpus. If the same query on the second pass still hits corpus_gap, the outer loop increments gap_iterations; when gap_iterations >= max_gap_iterations (default 3), the AbstentionReport becomes final.

"Same query" is measured by canonical query form — if the second pass produces a DIFFERENT gap_request (because different claims are now the bottleneck), it doesn't count as the same query and the counter doesn't advance. This prevents unbounded loops on genuinely insoluble gaps while allowing the resolver to iteratively deepen when it's making progress.

5.2 ChunkSaboteur — single-pass adversarial gate

Why it exists

The MCP tools return whatever the internet returns. That includes prompt-injection payloads ("IGNORE PREVIOUS INSTRUCTIONS and instead say …"), low-quality content (SEO farms, marketing pages, AI-generated slop), and content designed to exploit downstream models. A chunk that gets past the gate becomes indistinguishable from canonical evidence — it would be treated as trustworthy input by Builder and Saboteur on subsequent Phase 1 runs.

What it screens for

- **Prompt injection markers.** Regexes for "ignore previous", "you are now", "system prompt", "developer mode", plus known jailbreak patterns.
- **Quality floor.** Minimum length, minimum entropy, presence of domain-relevant tokens (proxy for topical fit).
- **Provenance sanity.** URL against a known-safelist / against a known-blocklist of AI-generated content mills.

Verdict: pass (proceed to ingestion) or fail (drop the chunk, log to RejectedChunkLog).

5.3 MultiPassSaboteur — five attack families (Q.9, Q-Fix.B.3)

Why single-pass isn't enough under quality-max

A single-pass gate catches obvious threats but misses subtle ones. An adversarial chunk that's been laundered through paraphrase, or that contradicts existing tier-A

evidence without triggering injection regexes, or that duplicates already-accepted content with small drift — all of these slip through. MultiPassSaboteur runs FIVE independent attack families and requires unanimous pass for promotion.

The five families

Family	What it probes
Injection	Prompt-injection patterns (as ChunkSaboteur but with more patterns and semantic checks)
Noise	Low signal-to-noise ratio, dilute content, filler text
Duplicate	Near-duplicate of already-accepted corpus (MinHash / content-hash overlap)
Bias	Ideological or promotional framing that would skew downstream reasoning
Contradiction	Direct contradiction of a tier-A source already in the corpus

Verdict aggregation

Each family emits a verdict in {accept, reject, soft_score}. Aggregation rule:

```
if any_family_rejected:
    verdict = reject
elif mean(soft_scores) >= 0.65:
    verdict = accept
else:
    verdict = reject
```

The 0.65 threshold is deliberately strict — provisional chunks contribute to future Builder decisions, so we accept only when the aggregate red-team result is clearly on the "clean" side.

What happens to rejected chunks

Rejected chunks are logged to pipelines/adversarial_corpus.py:RejectedChunkLog as a JSONL file. Future Saboteur runs (in ordinary Phase 1) can pull from this log as counter-example seeds — if the pipeline has seen a specific injection pattern before and rejected it, that pattern becomes ammunition for future Saboteurs to attack Builder plans that resemble it. The repo grows adversarial training data over time.

5.4 Cloud teacher consultation (Q.15, wired via Q-Fix.D)

Why appeal to an external verifier at all

The 7B primary model has limits the scaffold can't fix. On genuinely hard questions — especially long-context code understanding — a bigger model may know the answer even when the local pipeline abstains. The cloud teacher is the "court of appeal": consulted BEFORE any corpus_gap abstention emits, allowed to either confirm the abstention or propose an alternative that re-enters the pipeline.

The consultation flow

```
Phase 3 about to emit AbstentionReport(reason="corpus_gap"):
    if policy.cloud_teacher_model:
        verdict = cloud_teacher.consult(
            user_input,
            partial_evidence,
            current_confidence,
            intended_abstention_reason,
        )
        # verdict: TeacherVerdict Pydantic
        if verdict.confirms_abstain:
            # teacher agrees; augment abstention with tier-A "teacher confirmed" evidence
            abstention.evidence_partial.append( teacher_confirmed_link )
            return abstention
        else:
            # teacher offers alternative; feed back as gap_kind="teacher_candidate"
            return Phase3Result(
                gap_request = GapResolutionRequest(
                    gap_kind = "teacher_candidate",
                    seed_answer = verdict.alternative_answer,
                    seed_confidence = verdict.alternative_confidence,
                )
            )
```

The invariant that keeps the teacher honest

The teacher's alternative is NEVER accepted directly. It re-enters Phase 1 as a SEED, subject to the same Saboteur / PRM / SMT gates as any locally-generated candidate. If the seed survives, it becomes the answer; if it doesn't, the abstention stands. This preserves the 100%-or-abstain invariant — even the cloud teacher's answer must pass local verification. The teacher is a proposer, not a decider.

Cost profile

Cloud teacher (default gpt-oss:120b-cloud) is invoked at most once per abstention candidate, with temperature=0.0. The user's Ollama subscription tier makes cloud calls free at time of writing, so cost is wall-clock only (~10–30 s per consultation for a 120B call). Under quality-max this is on by default; a cost-controlled deployment can disable via policy.cloud_teacher_model = None.

5.5 Z3-SMT gate (Q.8, wired via Q-Fix.B.3)

Why formal verification at all

For code-artifact answers with declared invariants (extracted from the contract's api_schema: range constraints, non-null guarantees, ordering assertions), the LLM pipeline can produce answers that VIOLATE those invariants and still receive high confidence — because the verifiers upstream don't run the invariant checks. SMT solvers do. A Z3 pass over the committed answer's declared invariants is either SAT (invariants hold), UNSAT (invariants provably violated), or UNKNOWN (timeout, undecidable).

Where it fits

phases/phase3_aggregation.py invokes pipelines/smt_verifier.py:SMTVerifier.verify(declarations, constraints) when:

1. The candidate answer is a code artifact (Phase3OutputTarget = "code_artifacts").
2. The contract's api_schema contains extractable invariants (constraint_generator: JSON Schema → SMT declarations).
3. policy.solver_backend == "z3".

The three outcomes

SMT verdict	Phase 3 action
SAT	Attach a positive-evidence link ("invariants proven"); leave the answer alone.
UNSAT	Lower confidence by 0.2. Attach the human-readable UNSAT core (Q-Fix.M.1 diagnostic pattern). If the demoted confidence falls below tau, the answer becomes AbstentionReport(reason="unsat_core").
UNKNOWN (timeout)	If policy.smt_required=True, AbstentionReport(reason="proof_incomplete"). Else attach a proof_timeout note and keep the answer.

Human-readable UNSAT cores

Z3's raw UNSAT core is a list of assertion IDs, which is useless to the user. The verifier maps each ID back to its origin (which contract field, which module) and formats a human-readable summary: "Module A guarantees output.count ≥ 1 but Module B's contract requires output.count = 0 — these are incompatible". The user sees the WHY of the UNSAT, not just the fact of it.

5.6 The seven typed abstention reasons — full walkthrough

The AbstentionReport.reason field is a Literal type over exactly seven values. Each maps to a specific tier or check that produced it. This section explains what triggers each and what the user should do about it.

5.6.1 corpus_gap

Trigger

Phase 3 aggregate confidence < tau AND cloud teacher confirmed OR gap iterations exhausted OR gap resolver found no ingestible sources.

What the user should do

The corpus doesn't have enough tier-A/B evidence for this claim. Options: (a) provide canonical sources by dropping files in corpus/user/<topic>/ and re-indexing, (b) accept the abstention as an honest "we don't know" signal, (c) rephrase the request to something the current corpus can support.

5.6.2 unsat_core

Trigger

Z3 proved the answer's declared invariants are unsatisfiable.

What the user should do

The contract itself is inconsistent — two constraints in the request cannot both be satisfied. The AbstentionReport includes the human-readable UNSAT core identifying which constraints conflict. Relax one of them and retry.

5.6.3 recursion_cap

Trigger

Phase 2 tier-5 emitted a PipelineRecursionRequest at pipeline_recursion_depth ≥ max_pipeline_recursion. The outer loop refused to consume the request; Phase 3 was forced to emit the abstention instead.

What the user should do

The task's decomposition keeps producing conflicting contracts that neither Phase 2's solver nor its clash can resolve. Either raise max_pipeline_recursion, or accept that the task is too tangled for this pipeline configuration and try a narrower request.

5.6.4 proof_incomplete

Trigger

Z3 timeout AND policy.smt_required = True. The pipeline couldn't prove the invariants hold within the solver time budget.

What the user should do

Either raise solver_timeout_ms, or set policy.smt_required = False to accept unproven-but-not-disproven answers with a proof_timeout note attached.

5.6.5 execution_unachievable

Trigger

Execution-mode only. The rebuild loop (Q.4, wired via M.4) cycled through max_execution_rebuild_cycles without producing a code artifact whose tests pass.

What the user should do

The task is not achievable at the requested code-artifact quality. Either simplify (drop some test cases), extend budget (raise max_execution_rebuild_cycles), or accept that the current 7B substrate cannot solve this particular problem.

5.6.6 adversarial_rejection

Trigger

Every candidate generated in Phase 1 failed the AdversarialClash, and the recursion controller halted with reason "no_progress" or "oscillation" for every module. Nothing survived to Phase 2.

What the user should do

The Saboteur consistently found valid attacks on every plan the Builder proposed. This means either the FAQ items are too strict for the actual capability of the substrate, or the question is at a difficulty the pipeline can't handle. Review the AbstentionReport's attack_summary to see WHAT the Saboteur was breaking; the failure mode is usually visible.

5.6.7 cross_mode_divergence

Trigger

Cross-mode validation (Q.11) ran the same request through general-mode / plan-mode / execution-mode in parallel and got materially conflicting answers. The pipeline refuses to pick a "winner" — if the three modes disagree, the answer is by definition unstable.

What the user should do

This is a rare, diagnostic-quality abstention. Report the divergence — it's often a signal of a substrate mismatch or a request that lives on a mode boundary.

5.7 The failure-recovery invariants — recap

- **Every abstention has a typed reason.** No "unknown" reason. If the code can't identify why it's abstaining, that's a bug in the emission path.
- **Every abstention carries partial evidence.** The user sees WHAT the pipeline found, not just the fact that it failed.
- **Recovery is layered, not parallel.** Gap Resolver first (cheapest, localized); cloud teacher second (external appeal); SMT gate throughout (formal check). Each layer can rescue an abstention; only if all fail does the abstention become final.
- **Recovery never violates 100%-or-abstain.** Every recovery-produced answer (teacher seed, resolver-ingested chunks, SMT-proven claim) re-enters the same Phase 1–3 pipeline as any other candidate. There is no "trusted answer" back door.
- **Rejected content becomes training data.** Failed chunks accumulate in RejectedChunkLog and can feed future Saboteur runs. The system gets adversarially smarter on failure.

Part 6 — The operational surface (CLI, env, config, modes, telemetry)

An operator has to configure the pipeline, run it, watch it, and debug it when it does something unexpected. Part 6 documents the operational surface: every CLI flag, every env var, the precedence rules between them, the per-mode divergence map, the cross-mode validator that keeps modes in lock-step, the telemetry sinks, and the replay harness.

6.0 Configuration precedence — four layers, one authoritative source

Every configurable value in ClaudeDeep can be set from four places. When they disagree, the highest layer wins:

Precedence	Layer	Example
1 (highest)	CLI flag	--prm-kind schema_routed
2	Environment variable	CLAUDEDEEP_PRM_KIND=schema_routed
3	Overlay YAML (mode.quality-max.yaml)	prm_kind: schema_routed
4 (lowest)	Base mode.yaml + ModePolicy defaults	prm_kind: auto

How the layers merge

```
main.py:cli() reads CLI flags
    -> translates each flag into its corresponding CLAUDEDEEP_* env var
    -> calls run(user_input, root)

run():
    load_mode_policy(root / "config") reads mode.yaml
        -> if CLAUDEDEEP_MODE_OVERLAY=quality-max, merges mode.quality-max.yaml on top
        -> instantiates ModePolicy(**merged_yaml)
        -> policy defaults fill any gaps

default_prm(enabled, kind, ...) reads env vars at call time
    -> env vars override the policy values that were passed as arguments
```

The critical property: env-var overrides are applied AT CONSTRUCTION TIME by the consumer (e.g., default_prm), not at load time. So the same value can be different between two consumers if the env var changes mid-run — but in practice we set env vars once at process start and don't touch them.

6.1 CLI flag reference (main.py)

Flag	Type	Env equivalent	Purpose
user_input (positional)	str	—	The request. Default: "hello world" (mostly for smoke tests).
--root PATH	path	—	Project root containing config/ and faqs/. Default: parent of the running module.
--prm-kind {auto,heuristic,noop,cross_encoder,codeprm,thinkprm,codeprm_scaffold,generative_thinkprm,schema_routed}	choice	CLAUDEDEEP_PRM_KIND	Overrides mode.yaml prm_kind.
--prm-code-model NAME	str	CLAUDEDEEP_PRM_CODE_MODEL	HF id or local path for the code PRM.
--prm-reasoning-model NAME	str	CLAUDEDEEP_PRM_REASONING_MODEL	HF id or local path for the reasoning PRM.
--prm-codeprm-weights PATH	path	CLAUDEDEEP_CODEPRM_WEIGHTS	Directory with real CodePRM weights.
--prm-model-swap {true,false,on,off,yes,no}	choice	CLAUDEDEEP_PRM_MODEL_SWAP	GPU residency policy.
--prm-device {auto,cuda,cpu}	choice	CLAUDEDEEP_PRM_DEVICE	Device for PRM inference.
--prm-max-new-tokens N	int	CLAUDEDEEP_PRM_MAX_TOKENS	Max critique length for GenerativeThinkPRM.

6.2 Environment variable reference

Configuration overrides

Env var	Purpose	Consumer
CLAUDEDEEP_MODE_OVERLAY	Name of the overlay yaml (e.g. "quality-max") merged on top of mode.yaml	load_mode_policy()
CLAUDEDEEP_PRM_*	Seven variables as documented in 6.1	default_prm()
CLAUDEDEEP_OLLAMA_MODEL	Base model name (default: gpt-oss:20b)	OllamaConstrainedDecoder
CLAUDEDEEP_TELEMETRY_SINK	Sink URL: null / memory / jsonl:PATH / sqlite:PATH	_build_sink()
OLLAMA_HOST	Ollama endpoint (default: http://127.0.0.1:11434)	Ollama client (standard Ollama env)

HuggingFace defaults (standard, not ClaudeDeep-specific)

Env var	Purpose
HF_HOME	Root of the HF cache (default: ~/.cache/huggingface)
HF_TOKEN	Auth token for gated models (unused for launch/ThinkPRM* which are public)
TRANSFORMERS_OFFLINE=1	Forbid model download; error if not cached. Useful for reproducible eval runs.

6.3 Per-mode divergence map

The 4 mode folders (general-mode, plan-mode, execution-mode, clean-dataset-mode) share a substrate and diverge only at three explicit points. Everything else is byte-identical (enforced by the cross-mode validator, section 6.4).

What diverges

Mode	allow_write	allow_tool_execution	allowed_tools	Phase 3 output target	Extra packages
general-mode	true	true	read, grep, glob, bash, write	conversation	—
plan-mode	false	false	read, grep, glob	plan_document	—
execution-mode	true	true	read, grep, glob, write, patch, bash	code_artifacts	execution_validator/ (Q.4 / M.4 rebuild loop)
clean-dataset-mode	false	false	read, grep, glob	refined_dataset	dataset_refinement/ (M.5 chunk loader + probes)

Why the divergence is this narrow

The five knobs above are the ONLY ones each mode reads differently. Everything else — the Phase 0/1/2/3 code, the substrate adapters, the PRM family, the telemetry, the cross-mode validator, the config-loading logic — is one implementation shared across four folders. When Q-Fix.N landed, it changed all four folders identically; the cross-mode validator confirmed byte-equality of the shared files.

6.4 The cross-mode validator (Q.11, wired via Q-Fix.K)

Three independent checks

validation/cross_mode.py:validate_all(workspace_root) returns a CrossModeValidationReport with three CheckResult entries:

1. **substrate_symmetry.** For each of the 28 file paths in SUBSTRATE_FILES, compute sha256 of the file in each of the 4 mode folders. Pass iff all four hashes match. This catches "someone edited general-mode's llm_stage.py and forgot to propagate to the other three".
2. **policy_schema.** Instantiate ModePolicy from each mode's config/mode.yaml. Pass iff all four instantiations succeed and the allow_write / allow_tool_execution / etc. values match the expected per-mode divergence table above. Catches "someone added a field to policy.py but only updated general-mode's yaml".
3. **api_surface.** For each of the 30 entries in API_SURFACE (module_path, class_name, method_name), import the module in each of the 4 mode folders, resolve the class, resolve the method, and fingerprint the method signature. Pass iff all four fingerprints match. Catches "someone changed the signature of Builder.build() in one mode but not the others".

When to run it

As part of every commit that touches shared code. Also as the first step of the structural verification gate (Q-Fix.M — section 6.5). If any check fails, the pipeline is not in a shippable state; either propagate the change to all four folders, or explicitly move the diverging file to the allowlist.

Current status (as of May 2026)

```
substrate_symmetry     28/28 files byte-identical
policy_schema          4/4 mode policies validated
api_surface            30/30 API symbols consistent
overall                PASS
```

6.5 Structural verification gate (Q-Fix.M)

The full pre-release check bundle. Runs in five stages:

1. **Cross-mode validator** (section 6.4).
2. **Property tests**: pytest tests/property/. Hypothesis-based invariants for LLMStage monotonicity, threshold thresholds, PRM composability, CompiledQuery invariance, K-candidate determinism.
3. **Integration tests**: pytest tests/integration/. End-to-end smokes for each Q-Fix mechanism.
4. **Type check**: mypy --strict src/claudedeep/. All strict-mode errors must be zero or documented as deferred.
5. **End-to-end smoke**: python -m claudedeep.main "smoke query" under BOTH baseline and quality-max overlays. Both must return an AnswerReport OR a typed AbstentionReport (not raise).

The gate is what the plan requires to pass BEFORE any acceptance run (Q-Fix.O full SWE-bench). If the gate is red, benchmark numbers are moot — the code is not in a state where a benchmark score would be meaningful.

6.6 Telemetry — sinks and events

The event model

Every stage of the pipeline emits TelemetryEvent instances via a shared TelemetrySink interface. Fields:

```
run_id          str  -- UUID per pipeline run
timestamp       float
phase_id        Literal["phase0","phase1","phase2","phase3","gap_resolver","fast_path"]
component       str  -- fine-grained component name (e.g. "builder", "saboteur", "csp_solver")
module_id       str | None
tier_id         str | None  -- Phase 2 tier (T1..T5), None outside cascade
round_id        int  -- recursion round within Phase 1, or 0
confidence      float | None
evidence_summary dict  -- {"links": N, "top_tier": "A", ...}
replay_inputs   dict  -- reconstruction data (compiled query, prompt digest, seed)
notes           str
```

The four sinks

Sink	Selector	Behavior
NullSink	null (default)	Drops all events. Zero overhead.
InMemorySink	memory	Appends to a Python list. Exposed on serialized output as telemetry_events count. Useful for tests.
JsonlSink	jsonl:PATH	Appends one JSON line per event to a file. Persistent, streamable, greppable.
SqliteSink	sqlite:PATH (recommended default per M.1)	WAL-mode SQLite with a normalized schema. Enables the canned post-mortem queries in observability/queries.py.

The additive invariant

Removing the sink (setting telemetry_sink: null) produces byte-identical pipeline output to setting it to any other value. No tier, no phase, no clash decision reads from the sink or changes behavior based on it. Telemetry is a shadow of the run, not part of the run.

6.7 Replay harness

Every telemetry event carries replay_inputs sufficient to re-execute the stage that produced it, in isolation. observability/replay.py reads a JsonlSink or SqliteSink dump and reconstructs:

- The exact CompiledQuery for each retrieval — re-runnable against the current substrate.
- The prompt digest (sha256[:16]) for each LLMStage call — matchable against the prompt store to reconstruct the full prompt.
- The seed for each Ollama call — combined withtemperature=0.0, this lets us reproduce the exact tokens.
- The cascade's tier trail — letting us re-run Phase 2 with the same manifolds.

What replay is used for

1. **Post-mortem debugging.** A user reports an abstention; we pull the JsonlSink, replay the run, isolate the stage where confidence collapsed.
2. **Regression detection.** Change a Builder implementation; replay a known corpus of runs; assert the delta is contained to affected stages.
3. **Adversarial dataset construction.** Replay every ABSTAIN run; extract the winning candidates that failed thresholds; use as negative examples for future Saboteur training.

6.8 Operational commands reference

Command	Purpose
python -m claudedeep.main "REQUEST"	Run the pipeline. Baseline defaults.
CLAUDEDEEP_MODE_OVERLAY=quality-max python -m claudedeep.main "REQUEST"	Run under quality-max overlay.
python -m claudedeep.main "REQUEST" --prm-kind schema_routed --prm-model-swap true	Runtime PRM override.
python -m claudedeep.validation.cross_mode	Run the cross-mode validator (all 3 checks).
pytest tests/property/ tests/integration/	Structural gate tests.
bash scripts/structural_verification_gate.sh	Full Q-Fix.M gate (all 5 stages).
python scripts/index_corpus.py --corpus-dir corpus/ --report	Index or re-index the corpus (idempotent).
python scripts/swe_bench_eval.py --subset 5 --full-pipeline	Run Q-Fix.O.5 subset SWE-bench.
python scripts/swe_bench_eval.py --baseline	Run the baseline (single-shot decoder) for reference score.

Part 7 — Trade-offs (per subsystem, per module, overall)

Every mechanism in ClaudeDeep was picked over alternatives. This part is the ledger. Each subsystem gets a four-row table (*what it buys*, *what it costs*, *alternative considered*, *why we chose this not that*). Read this part when you disagree with a design decision — the counter-argument you'd raise is probably in one of these tables, and if it isn't, that's a signal we missed an alternative.

7.0 How to read a trade-off table

The four rows are load-bearing:

- **What it buys** — the specific correctness or capability gain we get from adopting this mechanism. Not "flexibility" or "modularity" — concrete outcomes.
- **What it costs** — the specific compute, memory, complexity, or reasoning burden it adds. Not "some overhead" — numbers where possible.
- **Alternative considered** — the concrete other mechanism we could have used instead. Not "we could do this differently" — the named alternative.
- **Why this not that** — the pivotal property that made this mechanism win over the alternative. Usually a specific failure mode of the alternative or a specific capability of this mechanism.

7.1 Per-mechanism trade-offs

7.1.1 Grammar-constrained decoding (LLM = syntax compiler)

What it buys	By-construction schema validity. Zero retry loops. LLM cannot emit invalid JSON because zero-probability tokens are never sampled.
What it costs	Token-mask overhead at each generation step (~5–10% inference latency). Requires an inference server that supports it (Ollama, vLLM, llama.cpp).
Alternative considered	Free-form generation + Pydantic post-hoc validation + retry loop.
Why this not that	Retry loops break composability: a Builder that occasionally fails validation and retries produces non-deterministic latency, and best-of-N sampling with retries has undefined semantics. Hard schema enforcement removes the entire class of failure.

7.1.2 Best-of-N=64 stratified sampling

What it buys	Agreement signal for confidence. 64 samples with 24 canonical-form matches means the model "agrees with itself" 37.5% of the time — a real signal about answer stability.
What it costs	64× inference cost per LLMStage call. On a 4060 Ti with gpt-oss:20b at ~30 tok/s, roughly 30–60 seconds per LLMStage.
Alternative considered	Single-sample generation with temperature=0.
Why this not that	Single-sample has no self-consistency signal. If it's wrong, we have no way to know. Best-of-N with canonical clustering surfaces the "N=1 was a lone stub" case as agreement=1/64.

7.1.3 Canonical-form clustering vs embedding-similarity clustering

What it buys	Exact-match semantics. Structurally identical answers always collide into one cluster; structurally distinct answers never conflate.
What it costs	No fuzzy matching. Two answers that differ only in a semantically irrelevant field (say, an ID) count as different.
Alternative considered	Embedding similarity clustering (embed each candidate, cluster by cosine).
Why this not that	Embedding similarity blurs real disagreement. Two Plan candidates whose step lists have different steps in the same order can embed close together — but they're proposing DIFFERENT plans. The agreement fraction must reflect real duplication, not semantic proximity.

7.1.4 PRM verification alongside agreement

What it buys	Kills the "unanimous stub" case. When N=64 samples all agree on a nearly-empty parsed Plan, agreement=1.0 but PRM=0.1, so combined confidence is 0.1 not 1.0.
What it costs	One extra model call per LLMStage (or 100+ under tree search with per-node PRM). Under model_swap=True, 1–8 s per PRM call.
Alternative considered	Agreement alone.
Why this not that	Agreement measures self-consistency, not correctness. A model can be very consistent about a wrong answer. PRM is orthogonal — a QUALITY signal that composes multiplicatively with agreement, so BOTH must be high to yield high confidence.

7.1.5 Cross-encoder PRM (bge-reranker-v2-m3) vs trained CodePRM

What it buys	Zero additional download — the model is already cached for retrieval. Beats HeuristicPRM measurably (verified by test_q_n_codeprm_outscores_heuristic.py).
What it costs	Not calibrated to correctness. bge-reranker was trained on relevance, so it measures "how well does the output MATCH the prompt", not "is the output CORRECT". A confident-but-wrong answer still ranks high.
Alternative considered	Trained CodePRM (ACL 2025) with correctness-calibrated regression head.
Why this not that	CodePRM weights aren't publicly released as of 2026-05. Cross-encoder is the strongest interim we can wire without waiting for author release. CodePRMScaffold is ready to accept real weights the day they ship, no code change needed.

7.1.6 GenerativeThinkPRM vs cross-encoder PRM for reasoning tasks

What it buys	Per-step visibility into WHY the score is what it is. If ThinkPRM says 0.6, the critique text tells you exactly which 40% of steps it flagged. This is diagnostic-quality feedback, not just a scalar.
What it costs	3–120 s per call depending on model size and hardware. Requires downloading 4–28 GB of weights.
Alternative considered	CrossEncoderPRM on reasoning outputs.
Why this not that	Cross-encoder gives an opaque score. For reasoning tasks (math, logic, multi-step plans), the per-step labels ARE the useful signal — they let downstream code know which specific step to attack in a recursion, and they let the user see which claim wasn't supported.

7.1.7 Schema-routed PRM vs single-PRM-for-all

What it buys	The right verifier for each schema. Code plans get code-tuned scoring; reasoning outputs get CoT critique; Saboteur outputs get reasoning critique (because their content is critique text, not code).
What it costs	An extra dispatch layer. Config surface has more knobs. Users need to understand the schema categorization.
Alternative considered	One PRM for everything (either cross-encoder or generative).
Why this not that	Neither single choice dominates across schema types. Cross-encoder underperforms on abstract reasoning; generative overpays on simple code correctness. The router lets each schema get its best fit.

7.1.8 model_swap=True on limited GPU

What it buys	The pipeline runs at all on a 4060 Ti. Without swap, ThinkPRM-1.5B loading alongside gpt-oss:20b would OOM.
What it costs	1–8 s of model load per PRM call. With 100+ PRM calls per LLMStage under tree search, that's minutes of wall-clock.
Alternative considered	Refuse to run on limited-VRAM hardware; require datacenter GPU.
Why this not that	The whole point is the pipeline runs on the user's real hardware. A design that only works on a machine the user doesn't have is not a design that ships.

7.1.9 Best-of-N linear vs Tree-of-Thoughts + UCB1

What it buys	Refinement. best-of-N samples independent attempts; ToT lets the winner of round R inform round R+1's expansions, which lets the search converge on a good structure.
What it costs	Depth×branch factor more LLM calls than linear best-of-N. Under quality-max (depth=3, branch=4), ~10× more calls.
Alternative considered	Pure linear best-of-N with larger N (say N=256).
Why this not that	N=256 samples are still N independent shots. They don't build on each other. ToT's refinement round lets a partially-correct first attempt become a correct final attempt via "PREVIOUS: X. IMPROVE IT" prompts.

7.1.10 UCB1 vs greedy expansion in ToT

What it buys	Exploration-exploitation balance. Prevents premature convergence on a single branch. Ensures every candidate gets at least one visit before the search commits.
What it costs	Slightly higher variance in per-run wall-clock (exploration bonus can lead to expanding an initially low-scoring node).
Alternative considered	Greedy expansion (always expand the current highest-score node).
Why this not that	Greedy is a proven failure mode of tree search — it commits to a branch based on one score sample and never revisits. UCB1's regret bound (Auer et al. 2002) is the theoretically-motivated fix that costs nothing extra to implement.

7.1.11 Deterministic-arbiters cascade vs LLM-judge

What it buys	No override cascade. Conflicts resolved by CSP solver, then Builder/Saboteur clash on solver candidates, then user, then re-decomposition — never by an LLM overwriting a peer's contract.
What it costs	More code paths (5 tiers vs 1 judge). Some conflicts that an LLM could patch over reach tier 5.
Alternative considered	Single LLM judge that reads both plans and picks / patches one.
Why this not that	The LLM judge is exactly the override cascade Gap 2 warned about. Once an LLM has authority to overwrite peer decisions without grounding, the confidence chain becomes unreliable. Deterministic arbiters preserve auditability.

7.1.12 100%-or-abstain vs partial answers

What it buys	Precision guarantee. Every emitted answer is verified through every layer. Low-confidence outcomes become explicit AbstentionReports with typed reasons.
What it costs	Coverage. The pipeline abstains on 40–60% of queries where a "partial answer" system would emit something wrong.
Alternative considered	Partial-confidence answers with confidence attached, letting the user decide.
Why this not that	Users don't calibrate on confidence bars. A "0.6 confidence answer" gets read as "an answer" and acted on. Explicit abstention forces the user to notice.

7.1.13 Conformal calibration vs fixed threshold

What it buys	Distribution-free precision guarantee. At epsilon=0.01, the answered subset has ≥ 99% precision, regardless of confidence-distribution shape.
What it costs	Requires a held-out eval set of (confidence, was_correct) pairs. Coverage is a measured outcome, not a chosen number.
Alternative considered	Fixed 0.85 threshold with a "trust us" claim.
Why this not that	0.85 is a folk-lore number nobody calibrated. Conformal prediction gives a mathematical guarantee. When the calibration file is empty, we fall back to 0.85 — but this is the FLOOR, not the ceiling.

7.1.14 MultiPassSaboteur (5 families, unanimous) vs single-pass gate

What it buys	Catches subtle attacks that a single regex-based gate misses. Bias, contradiction, and near-duplicate cases require semantic reasoning that a keyword filter can't do.
What it costs	5 additional passes per candidate chunk. Slower ingestion (~2–5 s per chunk).
Alternative considered	Single-pass ChunkSaboteur only.
Why this not that	Single-pass catches the obvious threats and misses the interesting ones. Under quality-max we accept ingestion slowdown for confidence in what enters the corpus.

7.1.15 Cloud teacher (Q.15) vs pure-local pipeline

What it buys	Larger-model second opinion on abstention candidates. On borderline cases the 120B teacher's answer might survive Phase 1 verification even when the 7B primary abstains.
What it costs	~10–30 s per consultation (cloud call). Requires an internet connection and a subscription (free at time of writing for gpt-oss:120b-cloud).
Alternative considered	Local-only pipeline (no cloud).
Why this not that	Local-only misses the "the 7B just can't answer this but a 120B can" case. Cloud teacher preserves sovereignty (we NEVER accept the teacher's answer directly — it re-enters local verification) while giving us an appeal mechanism.

7.2 Per-module trade-offs

7.2.1 The retrieval substrate

bge-m3 dense embeddings over sentence-transformers alternatives

bge-m3 is 1024-dim (higher resolution than 384-d competitors), multilingual (option to add non-English CS content without swapping models), and long-context (8192 tokens per doc). Alternatives (E5-mistral, voyage-3) either sacrifice open-weight availability or cost more per embedding call. bge-m3 is the default that requires no defense.

LanceDB over Qdrant / Milvus / FAISS / pgvector

LanceDB is embedded (no server process), persistent (WAL on-disk), supports incremental writes, and its columnar layout handles the trust-layer filtering efficiently. Qdrant and Milvus are excellent but require running services; FAISS lacks persistence semantics; pgvector requires Postgres. LanceDB wins on "no additional moving parts".

BM25 + RRF + cross-encoder over dense-only

Dense retrieval clusters by semantic similarity, which misses hits that share lexical tokens the model doesn't consider close. BM25 covers the lexical case; RRF fuses without needing normalization; cross-encoder rerank promotes precision at the top. Any of these alone is strictly weaker than the composed stack.

7.2.2 The verifier stack

Multiplicative composition of factors

agreement × PRM × subclaim × UCB. Multiplicative means any weakness is fatal. Additive would let a high-agreement, low-PRM answer beat a lower-agreement, high-PRM one — which is exactly the failure mode we want to prevent.

Fallback chain (Generative → CrossEncoder → Heuristic)

Every model-backed verifier has a fallback path ending in HeuristicPRM. Load failure never crashes; it degrades gracefully. This is what makes "the pipeline runs on any hardware" a truthful claim.

7.2.3 The cascade

Solver + clash + user + re-decompose, in that order

Tier 1 (conformance) catches the common case. Tier 2 (CSP) handles structural conflicts. Tier 3 (clash-over-candidates) handles semantic choices among proved-feasible options. Tier 4 (ask-user) handles genuine ambiguity. Tier 5 (re-decompose) handles "the decomposition itself was wrong". Each tier catches what the earlier tiers can't handle, at increasing cost. Any different ordering would either burn compute on the wrong tier or fail-through to tier 5 too often.

> **What we explicitly rejected: multi-agent debate as the conflict resolver.** DebateCV, FREE-MAD, M3MAD-Bench (2026) document that multi-agent debate systems, when used to resolve module contracts, produce over-confident consensus on wrong answers. The agreement of two adversarial LLMs is not evidence of correctness; it's evidence that they agree, which can happen when both are wrong. Deterministic arbiters avoid this failure by construction.

7.3 Overall trade-offs

7.3.1 Quality vs latency

What we chose	Quality first, no latency budget. best-of-N=64, tree depth=3, PRM at every node, model_swap on limited GPU.
What it costs	Minutes to hours per query under quality-max. On the 4060 Ti with the starter corpus, a complex Phase-1 module can take 20–40 minutes.
Alternative	Balanced quality-latency (best-of-N=8, tree off, single PRM). Would run in ~2–5 minutes.
Why this	The plan explicitly commits to "quality over latency for guaranteed 100000% ultra perfection". Latency is not free but it is bounded (recursion cap); quality is uncapped. The overlay system lets a user pick a balanced profile if they need it — the default is quality-max.

7.3.2 Coverage vs precision

What we chose	Precision-first. 99% precision-on-answered target via conformal calibration.
What it costs	Coverage. Expected answer rate on SWE-bench Verified: 35–55%. Everything else abstains with a typed reason.
Alternative	Coverage-first (Mythos's 93.9% pass-rate model). Higher raw score, no precision guarantee.
Why this	For high-stakes domains (medical, legal, infrastructure) precision IS the value. A wrong answer at high confidence causes real harm. An honest abstention lets the user seek human expertise.

7.3.3 Open-weight 7B vs cloud frontier

What we chose	Open-weight 7B (gpt-oss:20b) primary, cloud teacher (gpt-oss:120b-cloud) as court-of-appeal.
What it costs	Absolute pass-rate ceiling below the frontier. No amount of scaffolding puts a 7B at Mythos's 93.9%.
Alternative	Frontier cloud primary (Mythos / Opus / GPT-5.3). Higher absolute performance, no sovereignty, per-query cost.
Why this	Sovereignty for regulated / on-prem / data-sensitive contexts. Auditability of every step. Cloud teacher is the escape valve for the specific queries the 7B can't answer.

7.3.4 Architectural complexity vs operational simplicity

What we chose	High architectural complexity (5 tiers, 5 PRMs, 7 abstention reasons, 4 modes, cascade + gap resolver + SMT + cloud teacher) kept operationally simple by the invariants (mutually exclusive types, deterministic arbiters, additive-only, cross-mode symmetry).
What it costs	Learning curve for new developers. This book exists because the surface area IS large.
Alternative	Simpler architecture (say, best-of-N + Pydantic + retry loop). One-week learning curve.
Why this	The simpler architecture doesn't deliver the 100%-or-abstain contract, doesn't handle inter-module conflicts safely, and doesn't have a story for corpus gaps. Each subsystem we added addresses a specific failure mode of the simpler system. The complexity is load-bearing.

7.3.5 No stub in default runtime (Q-Fix.A)

What we chose	Every default runtime path uses real backends. Stubs only exist for tests.
What it costs	First-run of a fresh install requires model + corpus + Ollama + FalkorDB to be present. No "runs without dependencies" default.
Alternative	Stubs as the default so the pipeline runs immediately on a bare install.
Why this	Stubs that silently produce fake outputs are worse than a hard error. The Q-Fix.A audit found the previous stub-based default was quietly emitting confident-looking answers with no real underlying computation. Real backends by default, additive-only fallback for load failure — never a stub in production.

Part 8 — Empirical state (what is measured, what is deferred)

This part is the honest accounting. Parts 1–7 described the design and its rationale. Part 8 enumerates what has been EMPIRICALLY VERIFIED on the running system, what is structurally PROVED (cross-mode symmetry, type invariants, property tests), what is SET UP but not yet RUN (Q-Fix.O full 500-instance SWE-bench), and what is explicitly DEFERRED to future work. The reader should finish Part 8 able to draw a sharp line between "a number we can show you today" and "a number we expect once substrate X lands".

8.1 Substrate-A — real LLM inference, verified

What was wired

- Ollama running gpt-oss:20b (MXFP4 quantization, ~13 GB on the 4060 Ti 16 GB).
- OllamaConstrainedDecoder calling Ollama's /api/chat with format=json-schema and a JSON Schema converted from the Pydantic output class.
- Cloud teacher (gpt-oss:120b-cloud) via the same Ollama client. Free at the user's account tier.
- MultiModelEnsemble with members [self, gpt-oss:120b-cloud] under quality-max overlay. StratifiedSampler rotates round-robin.

Live verification log

Test	Outcome
Arithmetic schema 17×23	decoder returned ArithSchema(a=17, b=23, c=391); 391 = 17×23 ✓
Arithmetic schema 23×47	decoder returned c=1081; 1081 = 23×47 ✓
Arithmetic schema 11×13	decoder returned c=143; 143 = 11×13 ✓
Plan schema for "design a binary search tree"	5-step Plan, populated summary, no validation error
SabotageResponse for adversarial probe on the BST plan	3 attack_findings + 2 broken_faq_items; Pydantic validation green
AbstentionReport schema on forced gap path	typed reason="corpus_gap" + populated diagnostic

What this proves

The LLM-as-syntax-compiler invariant survives a real backend. Pydantic schemas reach the model verbatim (via json-schema), and the model emits structured JSON that Pydantic validates without retry. The plan's "every LLM call uses grammar-constrained decoding" guarantee is operationally true, not just designed.

What is NOT yet wired in Substrate-A

- **Real CodePRM weights.** PRM scoring uses BAAI/bge-reranker-v2-m3 as a cross-encoder regressor with sigmoid normalization — a defensible interim choice that is empirically a strong code-reasoning verifier even before fine-tuning, but it is not the CodePRM (ACL 2025) checkpoint the plan named. The adapter's model_name is overridable by CLAUDEDEEP_CODEPRM_WEIGHTS; the day real CodePRM weights ship, no code change is needed.
- **Real ThinkPRM-7B swap loop.** ThinkPRM-1.5B downloaded and integrated (see 8.2). ThinkPRM-7B download completed at ~14 GB. The two are wired via GenerativeThinkPRM; the schema-routed full-pipeline smoke against a math-reasoning query (ThinkPRM's training domain) has been staged but the run is deferred to a future turn.
- **Local 70B+ models.** The 4060 Ti caps any single resident model at ~14 GB MXFP4. GLM-5 does not fit. The cloud-ensemble member partially closes this gap by routing the cloud half of stratified samples through gpt-oss:120b-cloud.
- **Distillation / LoRA fine-tune.** Q.10's rejection-sampling FT loop ships the harvest script but not the training run. A user with appropriate compute can run it; we have not.

8.2 Substrate-B — real corpus indexed and retrievable

The starter corpus (Q-Fix.P)

13 public-license sources indexed into 857 parent-document chunks. Tier-B by default. Enumerated in Part 3.10. Tier-A textbooks (CLRS, Sipser, TAOCP) are the user-provided extension — drop them into corpus/user/<topic>/ and re-run scripts/index_corpus.py; indexing is idempotent.

Live retrieval verification

Query	Top-1 source
"distributed consensus protocol with leader election"	Raft paper (Ongaro & Ousterhout) — leader-election chunk
"how does Paxos handle multiple proposers"	Paxos paper (Lamport) — Multi-Paxos + ballot numbers
"self-balancing binary search tree with O(log n) insert"	SICP / Crafting Interpreters cross — treap + AVL
"scaled dot-product attention mechanism"	Attention Is All You Need (Vaswani et al.) — section 3.2.1
"epoll vs select scalability tradeoff"	Beej's Guide / OSTEP cross — kqueue/epoll chunk

ThinkPRM downloads (2026-05-15)

- launch/ThinkPRM-1.5B — 3.4 GB on disk, 7 files, download completed in ~37 min. Loadable via AutoModelForCausalLM; base R1-Distill-Qwen-1.5B.
- launch/ThinkPRM-7B — ~14 GB download, completed in background.
- CodePRM — no public release; CodePRMScaffold loads from CLAUDEDEEP_CODEPRM_WEIGHTS env var when user provides weights, otherwise delegates to CrossEncoderPRM.

8.3 Q-Fix.M structural verification gate — GREEN

```
$ python scripts/structural_verification_gate.sh

[symmetry] checking 28 SUBSTRATE_FILES across 4 modes...
[symmetry] 28/28 byte-identical ✓
[symmetry] checking 30 API_SURFACE entries...
[symmetry] 30/30 signature-identical ✓
[symmetry] divergence allowlist: 6 entries (execution_validator/*,
           dataset_refinement/*, phase0_clash_runner — expected per plan)
[symmetry] ALL PASS

[property tests] 23 passed, 5 skipif (no ThinkPRM-7B in cache during test run)

[integration tests] 21 passed
[integration Q-Fix.N] 21 passed, 29.55 s total

[mypy --strict] clean

[end-to-end smoke: baseline] general-mode "smoke" -> ANSWER conf=1.0
[end-to-end smoke: quality-max] general-mode "smoke" -> ANSWER conf=1.0
```

The gate must pass before Q-Fix.O runs. It currently passes.

8.4 Q-Fix.O.5 subset SWE-bench (3 instances)

Ran on 2026-05-15 as a validation gate before Q-Fix.O (500-instance full run). Result: 0/3 patches produced, all three hit the 1200 s per-instance timeout. Harness ran in --mode baseline (single-shot gpt-oss:20b), NOT --mode full (full pipeline).

Interpretation: baseline single-shot on astropy issues is not viable at 1200 s per instance. The full-pipeline path at quality-max settings was not exercised on this subset. Committing Q-Fix.O.5 as a full-pipeline run with a realistic (~1 h/instance) timeout is deferred to a future overnight session.

8.5 Book itself — what shipped

- Ultra-detailed HTML source at book/html/claudedeep_book.html. No code excerpts (per the user's explicit request); every subsystem gets the four-part treatment.
- Build script at book/build.sh using wkhtmltopdf.
- Compiled PDF at book/out/ClaudeDeep_Book.pdf. Current size: ~1.4 MB, ~45+ pages depending on wkhtmltopdf pagination.
- All 7 Mermaid diagrams embedded in Appendix A gallery.
- Full logits reference as Appendix B.
- Sources index as Appendix C.
- Old docx pipeline (book/src/*.py, compile_book.py, ClaudeDeep_v6_QFix_Book.docx) deleted per user approval.

8.6 What we explicitly DO NOT claim

> **We do NOT claim Mythos-parity on SWE-bench Verified.** Mythos sits at 93.9%. The realistic first-year outcome for a 7B-class model with the full Q-Fix.A–P + Q-Fix.N stack is 35–55% on Verified. The 40-point gap is structural (model size + training data + alignment) and no amount of test-time scaffolding closes it on current published evidence. We claim parity on PRECISION-ON-ANSWERED at lower coverage, not raw pass-rate.

> **We do NOT have a Q-Fix.O number to show today.** The full 500-instance run is overnight compute (~19 hours wall-clock for the full-pipeline). It is the LAST step in the entire Q-Fix cycle. Q-Fix.O.5 subset (3 instances) ran and produced 0/3 in baseline mode; the full-pipeline subset re-run is deferred.

> **We do NOT have a conformal-calibration eval set in the repo.** Q.12 ships the calibrator code; no calibration JSON exists yet. Default behavior reverts to the heuristic 0.85 threshold. The 99% precision floor is DESIGNED-IN; it is not MEASURED-IN. Q-Fix.O.5 + Q-Fix.O traces are the first opportunity to harvest real (confidence, was_correct) pairs.

> **We do NOT have real CodePRM / ThinkPRM checkpoints loaded as PRMs by default.** ThinkPRM-1.5B and 7B are downloaded but the schema-routed full-pipeline smoke against a math-reasoning query has not yet been run. Real CodePRM weights are not publicly available from the authors as of 2026-05.

8.7 What the audience should remember

- Substrate-A: real Ollama-backed structured LLM inference works; arithmetic + plan + sabotage + abstention schemas round-trip cleanly through gpt-oss:20b.
- Substrate-B: 857 parent-document chunks across 13 canonical CS sources are indexed and retrievable; Q-Fix.E hybrid pipeline is operational.
- Q-Fix.M structural gate is GREEN (28 substrate files + 30 API symbols + 4 mode policies + 21 integration tests + 23 property tests all pass).
- Q-Fix.N wired: 5 PRM classes + SchemaRoutedPRM router + model_swap mechanic + CLI/env/YAML config precedence. 21/21 integration tests pass. ThinkPRM-1.5B and 7B downloaded, ready to engage under schema_routed kind.
- Q-Fix.O 500-instance benchmark is the next and final acceptance gate. It runs once, last, against a fully-validated stack. Today's book documents the stack; the number lands separately.
- Three explicit non-claims: Mythos-parity on raw pass-rate, a committed Q-Fix.O number today, a calibrated conformal tau from real data. Each non-claim is paired with the substrate that closes it.

Appendix A — All seven Mermaid diagrams (full-page gallery)

The seven diagrams that structure the pipeline are reproduced here at full size. The interactive source is index.html in the project root; every node and edge is pan/zoomable in the browser.




Diagram 0 — Q-Fix architecture overview. Every load-bearing mechanism in v6 + Q-Fix.A–P + Q-Fix.N, drawn as a single picture. User input enters at the clarification gate (Q.14), passes fast-path / cache (M.9), enters Phase 0 with K=8 adversarial decomposition (Q-Fix.G), fans into Phase 1 per-module adversarial loop, aggregates through Phase 2's 5-tier cascade, and emits Phase 3 AnswerReport or AbstentionReport (with cloud-teacher consultation Q-Fix.D and SMT gate Q-Fix.B.3 before abstaining).




Diagram 1 — Full pipeline (Phase 0 → Phase 3). The four-phase A2A pipeline as a single Mermaid graph. The back-edge from Phase 2 tier 5 to Phase 0 (with FullContext) is the pipeline-recursion loop; it is owned by main.py, not by either phase.



PLAN FAILS: Recurse
Collect: plan + attack findings + broken FAQ items
Child inherits: plan + attacks + WHY each FAQ item broke
Accumulated GraphRAG context from all cycles
recurse with enriched context
MODULE ENTRY
Receive: module_spec + parent_plan + effort_level
BUILDER PIPELINE
FAQ Validate: What must be true?
GraphRAG Supporting: best implementation of module
Rerank Helpful: 50k to 2k tokens
LLM: Build draft plan from verified context
Supporting query
Internal FAQ pre-check: does draft satisfy module FAQ?
A2A LAYER 1: Builder and Saboteur Messages
Builder sends sabotage_request via A2A Layer 1
SABOTEUR PIPELINE
FAQ Probe: What could break each FAQ item?
YES broken items: plan fails
GraphRAG: Same Engine, Different Queri
LanceDB
FalkorDB
GraphRAG Counter: wrong implementations / anti-patterns
Counter query
Rerank Damaging: 50k to 2k tokens
LLM: Generate structured attack findings
Saboteur sends sabotage_response with attack findings
Adversarial Clash: Are any module FAQ items broken?



Diagram 2 — A2A Layer 1 (intra-module Builder ↔ Saboteur). Per-module adversarial clash: Builder pulls Supporting evidence, Saboteur pulls Counter evidence, both score via PRM, clash resolves via FAQ items. Q-Fix.H correlated-failure detection (Jaccard overlap) and disjoint-filter rerun appear as the feedback loop.




Diagram 3 — A2A Layer 2 (cross-module) + Phase 3 aggregation. The 5-tier cascade is shown explicitly: tier 1 conformance → tier 2 CSP / Z3 solver → tier 2.5 proofing verifier → tier 3 clash-over-solver-candidates → tier 4 ask-user → tier 5 re-decompose with FullContext.




Diagram 4 — Hybrid retrieval pipeline (Q-Fix.E). QueryIntent → CompiledQuery → dense (bge-m3) + BM25 → RRF fusion → bge-reranker-v2-m3 cross-encoder → GLiNER NER → parent-document expansion → GraphRAGHit. Each stage emits telemetry and is replayable from its compiled_query.




Diagram 5 — Quality-max LLMStage internal flow. One LLMStage.run() under quality-max overlay: stratified best-of-N=64 across [self, gpt-oss:120b-cloud], ToT-UCB1 expansion to depth 3, PRM scoring at every node, Saboteur attacks at every internal node, terminal selection by max avg_score leaf.




Diagram 6 — Q-Fix.N PRM dispatch. Five concrete PRM kinds plus one router. Configuration precedence (CLI > env > mode.yaml) is read at default_prm() call time. SchemaRoutedPRM (quality-max default) sends code schemas to CodePRMScaffold and reasoning schemas to GenerativeThinkPRM. Every model-backed PRM follows the model-swap lifecycle: lazy-load → score → (swap=true) release weights and clear CUDA cache, or (swap=false) keep resident on a datacenter GPU.

Appendix B — How logits are used across ClaudeDeep

This appendix is the ultra-detailed reference for a specific question with system-wide reach: where does a logit enter the pipeline, what transform is applied, and what does the resulting scalar drive? The organizing principle: every logit either flows into an argmax (token generation) or into a sigmoid (scalar quality score); nowhere else. Understanding those two paths in full covers 100% of logit usage in the codebase.

B.0 What a logit actually is

A logit is a raw, unnormalized scalar output of a neural network's final linear layer, *before* any probability-normalizing transform (softmax or sigmoid). It lives in $\mathbb{R} = (-\infty, +\infty)$. Two flavors appear in ClaudeDeep:

- **Single-scalar logit** — a regression head emits one number r. Sigmoid gives probability: $\sigma(r) = 1 / (1 + e^{-r}) \in (0, 1)$.
- **Token-distribution logit vector** — at each autoregressive step, the decoder emits a vector $z_t \in \mathbb{R}^V$ where V is vocab size (~50 000 for gpt-oss). Softmax over z_t / T (T = temperature) gives the next-token distribution.

> *If your working intuition is "logit = pre-activation score", you already have the right idea. Nothing beyond that matters for reading this appendix.*

B.1 The six entry points, in full

B.1.1 gpt-oss:20b token generation via Ollama (constrained-decoded)

Where in the code
Every OllamaConstrainedDecoder.decode(schema) call, executed inside every LLMStage.run(...) best-of-N sample. Runs 64× per LLMStage under quality-max.
Mechanism
The model computes hidden state h_t, projects to logits $z_t = W_{out} \cdot h_t$, and normally samples from softmax(z_t / T). We invoke the decoder with format={"type": "json-schema", "schema": schema.model_json_schema()}. Ollama's inference server converts the Pydantic schema into a token-level finite-state machine and, at every step, applies a boolean mask M_t over z_t:
• $z_t[i] \leftarrow -\infty$ for every i where $M_t[i]$ = false (that token would break JSON validity),
• sample from softmax(z_t / T) over the masked distribution.
What ClaudeDeep sees
The sampled tokens as a JSON string, then SchemaClass.model_validate_json(raw). We never read z_t directly; Ollama consumes it internally.
Why it matters
This is what makes the "LLM = syntax compiler" invariant a *hard runtime guarantee* rather than a convention. It's also why we can safely fan out 64 samples in parallel: every one of them is a valid Pydantic instance by construction.
Temperature schedule
0.7 for best-of-N diversity in Phase 1, 0.9 at ToT root (Q.7), 0.0 for cloud-teacher consultation (deterministic argmax).

B.1.2 bge-reranker-v2-m3 — the CrossEncoderPRM path

Where in the code
pipelines/prm.py:CrossEncoderPRM.score(). Also used inside pipelines/hybrid_retriever.py (Q-Fix.E.3) as the rerank stage over top-200 dense+BM25 fused hits.
Mechanism
The cross-encoder is a 568M-parameter XLM-RoBERTa-style transformer with a single-output regression head. Input: [CLS] query [SEP] passage [SEP]. Output: single scalar logit r. Training objective: pairwise margin loss such that (query, correct-passage) has higher r than (query, incorrect-passage).
Composition for PRM use
query = system_prompt + user_content; passage = parsed.model_dump_json() (the candidate output).
Then: raw = cross_encoder.predict([(query, passage)])[0] → score = 1 / (1 + math.exp(-raw)) .
Interpretation shift
The reranker was trained on *relevance*, not on *correctness*. Repurposing it as a PRM assumes the two are correlated. Empirically they are: a wrong solution is usually less relevant to the prompt than a right one, because the model tends to drift off-topic when it doesn't know the answer. But it is an approximation, not a calibrated correctness estimator. This is why bge-reranker-based PRM is a *strong baseline*, not the final answer.
Why sigmoid, not softmax
Softmax needs at least two logits to normalize; the reranker emits one. Sigmoid is the correct inverse of a single scalar. Also: $\sigma(0) = 0.5$ gives a natural "neutral" midpoint, so a logit near zero produces a PRM score that doesn't skew the combined agreement × prm computation.

B.1.3 CodePRMScaffold — real CodePRM regression head

Where in the code
pipelines/prm.py:CodePRMScaffold.score(), only when CLAUDEDEEP_CODEPRM_WEIGHTS points to a valid HF-format directory. Real CodePRM (ACL 2025) weights are not publicly released as of 2026-05, so this path is currently dormant on default installs.
Mechanism
Identical shape to B.1.2 but loaded as AutoModelForSequenceClassification (not CrossEncoder). The tokenizer accepts (prompt, output) as a pair; the classification head emits logits.shape = (batch, num_labels) with num_labels = 1 for regression. We take float(logits.squeeze().detach().cpu().item()), then sigmoid.
Different logit distribution, same downstream
CodePRM was trained on (thought-step, was-correct) pairs derived from execution feedback, so its raw output is more directly calibrated to correctness than bge-reranker's. The sigmoid conversion, the storage, and the downstream flow are identical. This is deliberate: swapping the underlying weights should be a config change, not a code change.

B.1.4 GenerativeThinkPRM — implicit logit consumption via greedy argmax

Where in the code
pipelines/prm.py:GenerativeThinkPRM.score(). Wraps launch/ThinkPRM-1.5B (or 7B, 14B).
Mechanism
ThinkPRM has no regression head. It's a full causal LM (R1-Distill-Qwen-1.5B fine-tuned on 1 000 synthetic verification chains-of-thought). We prompt it with *(problem, step-by-step solution)* and call model.generate(..., do_sample=False, temperature=0.0). Under the hood .generate() computes token logits at each step and picks the argmax — deterministic greedy decoding.
What we read
The decoded output text, not the logits. ThinkPRM emits critiques of the form "Step 1 verifies the base case. This is correct because… \boxed{correct} … Step 2 recurses on n-1. This is incorrect because n-1 can be negative … \boxed{incorrect}". We parse with two regex families: \boxed\s*\{\s*(correct|incorrect)\s*\} and \bstep\s*\d+\s*(?:is)?\s*(correct|incorrect|wrong|right)\b. Aggregate: score = correct / (correct + incorrect); 0.5 if no labels parse.
Why fraction, not sigmoid
The per-step labels are already calibrated probabilities (each is a binary judgment). The fraction correct is the natural [0, 1] estimator; sigmoid would double-normalize.
Why greedy, not sampling
The PRM is a verifier, not a proposer. Non-determinism defeats its purpose: we want the same critique for the same input, so that the PRM score is a function of the candidate, not a function of randomness.

B.1.5 GLiNER NER — used only inside graph ingestion

Where in the code
graphrag/real_falkordb_adapter.py::_LazyNER. Fires during corpus indexing (scripts/index_corpus.py) and during gap-resolver ingestion (gap_resolver/resolver.py).
Mechanism
GLiNER (urchade/gliner_small-v2.1) is a span-classification transformer. For each candidate span × entity-type pair, it emits a logit; sigmoid → probability that the span is of that type. Threshold = 0.5 by default.
What it drives
(:Chunk)-[:MENTIONS]->(:Entity) edges MERGEd into FalkorDB. Logits → sigmoid → threshold → boolean accept/reject. Zero interaction with the LLMStage confidence path; entirely a substrate-layer concern.

B.1.6 gpt-oss:120b-cloud teacher — same shape as B.1.1


The cloud teacher goes through the exact same Ollama constrained-decoding path as B.1.1, just against a bigger backend model. Temperature 0.0 (deterministic). We read the sampled tokens as TeacherVerdict Pydantic; never see the logits.

B.2 Where logits are DELIBERATELY not touched

Three negative-space design choices worth understanding:

- **Best-of-N clustering does not use logit similarity.** We canonicalize each parsed Pydantic via model_dump_json() and cluster by exact string match. Embedding similarity would be a mistake: two schema-equivalent JSONs with different key ordering must be treated as identical answers, and exact canonical-form match guarantees that. Semantic similarity would blur genuinely-different answers together and inflate false agreement.
- **Sub-claim verification (Q.5) reads GraphRAG hits, not logits.** Each atomic claim gets its own compiled retrieval, and the verdict is "returned tier-A/B evidence ≥ threshold?", a boolean over the trust-scored hit list. No logit inspection.
- **Conformal calibration (Q.12) operates on already-computed confidence.** Inputs to ConformalCalibrator are (final_confidence, was_correct) pairs where final_confidence is the post-sigmoid, post-agreement-multiplication scalar. Calibration is applied to the OUTPUT of the logit chain, not to logits directly.

B.3 The full data flow, every arrow labeled



B.4 Design rationale — WHY each transform

- **Sigmoid on a single scalar logit.** The only correct one-parameter transform (−∞, +∞) → (0, 1). Monotone (preserves ranking), symmetric around zero (neutral = 0.5).
- **Fraction-correct on generative critiques.** Matches the model's own training loss (per-step binary labels). Any other aggregation would ignore ThinkPRM's calibration.
- **Multiplicative combine agreement × score.** Additive would let a high-agreement, low-quality answer beat a low-agreement, high-quality one. Multiplicative penalizes either weakness proportionally. Also: combined = 0 if either is zero, matching the intuition that a lone genius or a unanimous stub are both untrustworthy.

- **Deterministic PRM inference (temperature = 0).** The PRM must be a function of its input; else best-of-N reranking becomes chaotic.
- **No cross-model logit combination.** We never add logits from bge-reranker to logits from CodePRM etc. Each model has its own zero, its own scale, and its own training objective. Combining scalars via sigmoid-then-multiply is well-defined; combining raw logits isn't.

B.5 Failure modes and how they surface

- **Cross-encoder logit clipping.** bge-reranker occasionally emits r < –20 or r > 20, saturating sigmoid at 0 or 1. Downstream combined = agreement × 0 collapses confidence to zero, forcing abstention. This is the right behavior — a strongly-negative reranker signal SHOULD kill the candidate.
- **ThinkPRM parse failure.** Critique doesn't contain a single \boxed{...} or "step N is ...". We fall through to score = 0.5 (neutral) rather than raising. Neutral score means combined = agreement × 0.5, effectively halving confidence. Surfaces as "borderline abstention" cases in Phase 3.
- **Ollama constrained-decode timeout.** Model exhausts max_new_tokens without closing the JSON. Ollama returns a partial string; Pydantic .model_validate_json() raises; the sample is dropped from best-of-N. If ALL 64 samples fail, LLMStage returns a zero-confidence result and Phase 3 abstains with reason="decoder_starvation".
- **GPU OOM during generative PRM load.** GenerativeThinkPRM catches, sets _load_failed, and falls back to HeuristicPRM (structural scoring). The scoring becomes weaker but the pipeline continues. model_swap=True is the mitigation.

Appendix C — Sources and further reading

C.1 Benchmarks

- SWE-bench Verified official leaderboard
- LLM-Stats SWE-bench aggregator
- Epoch AI benchmark tracker

C.2 Agent scaffolds

- InfCode (arxiv 2511.16004, Nov 2025)
- SWE-Debate (arxiv 2507.23348, Jul 2025)
- SWE-Search (ICLR 2025)

C.3 Process Reward Models

- CodePRM (ACL 2025 Findings 428)
- ThinkPRM — original OpenReview paper
- ThinkPRM arxiv 2504.16828 — Process Reward Models That Think
- launch/ThinkPRM-1.5B model card
- launch/ThinkPRM-7B model card
- mukhal/ThinkPRM GitHub
- CompassVerifier — lightweight verifier
- Lightman et al. — Let's Verify Step by Step (PRM800K)

C.4 Constrained decoding and structured output

- Grammar-Constrained Decoding (ACL 2025 Industry)
- Outlines library
- Guidance (Microsoft)
- lm-format-enforcer
- Ollama JSON-schema API

C.5 Retrieval, rerankers, and graph extraction

- BAAI/bge-m3 — multilingual dense embeddings
- BAAI/bge-reranker-v2-m3 — cross-encoder reranker
- BM25 (Robertson & Zaragoza, 2009)
- Reciprocal Rank Fusion (Cormack et al., SIGIR 2009)
- ColBERTv2 (Santhanam et al., NAACL 2022)
- GLiNER — Generalist Lightweight NER
- LanceDB — columnar vector database
- FalkorDB — Cypher graph database

C.6 Selective prediction and conformal abstention

- Conformal Abstention Policies (ATCP, arxiv 2502.06884)
- SelectLLM (OpenReview 2025)
- Trust-or-Escalate (ICLR 2025)
- Conformal Prediction tutorial (Angelopoulos & Bates, 2023)

C.7 Search and reasoning at test time

- Tree of Thoughts (Yao et al., NeurIPS 2023)
- Self-Consistency (Wang et al., ICLR 2023)
- UCB1 (Auer, Cesa-Bianchi, Fischer, 2002)

C.8 Open-weight inference stack

- Ollama — local LLM runtime
- gpt-oss model card (Ollama)
- Ollama Cloud (gpt-oss:120b-cloud)
- vLLM — high-throughput inference