

DOM events and browser APIs

Module 2 - Lesson 2

Overview

The Document Object Model is how JavaScript sees and changes the page. Events let you respond to user interaction, and browser APIs give you access to the platform: the network, storage, geolocation, and more.

Key Concepts

- `querySelector` and `createElement` are the core tools for reading and building the DOM.
- `addEventListener` attaches behavior to clicks, submits, key presses, and dozens of other events.
- Event bubbling and delegation let you handle many elements with a single listener on a parent.
- The `DOMContentLoaded` and `load` events control when your scripts safely run.
- Browser APIs like `fetch`, `localStorage`, and `navigator` expose platform capabilities through JavaScript.
- Avoid inline `onclick` attributes; keep behavior in separate, testable modules.

Example

```
const list = document.querySelector('#todos');
list.addEventListener('click', (e) => {
  if (e.target.matches('button.delete')) {
    e.target.closest('li').remove();
  }
});
```

Summary

The DOM is your live view of the page; events connect user actions to your code. Delegation, proper event listeners, and the modern browser APIs turn static HTML into an interactive application.

Practice Checklist

- Build a todo list that adds and removes items without reloading the page.
- Use event delegation to handle clicks on dynamically added buttons.
- Persist the todo list across reloads using `localStorage`.