

Assignment 1

This assignment is due by 11:59 p.m. on Wednesday, May 14. All reports should be submitted as PDFs. Only one report must be submitted per team, but all team member's names must appear on the report.

Part 1

In class, we discussed a method to perform image contrast enhancement known as histogram equalization. There are many other ways to perform contrast enhancement that are commonly used in practice. One important contrast enhancement operation is known as *gamma correction*.

To perform gamma correction, a user modifies each pixel value $u \in \{0, \dots, 255\}$ of a grayscale image using the following mapping

$$v = 255 \left(\frac{u}{255} \right)^\gamma \quad (1)$$

to obtain the modified pixel value y . The parameter γ is a user specified constant that shapes how the image's pixel value histogram is stretched. The value of gamma is always strictly greater than zero.

- Write a Matlab function that performs gamma correction on a grayscale digital image. This function should accept an image (already read into Matlab) along with the value of γ as inputs and produce a Matlab variable representing the image in unsigned 8-bit integer format as an output. Please comment your code and append it to your report.
- Use your gamma correction function to perform contrast enhancement on the image **pout.tiff**. What happens if $\gamma > 1$? What happens to the image and its pixel value histogram if $\gamma < 1$? What happens if $\gamma = 1$?
- Use your gamma correction function to enhance the low contrast image **moonPhobos.tiff**. Try several different values of γ and report the value that you feel works best. Be sure to include your contrast enhanced image and its pixel value histogram in your report. Additionally, use Matlab's histogram equalization function *histeq* to enhance the image. Compare the results you obtain using gamma correction with the results you obtain using histogram equalization.

Part 2

High-boost filtering is an image enhancement technique that is used to sharpen an image. It works by extracting first extracting the high frequency content $g(x, y)$ from $f(x, y)$. This is then scaled and added back to the original image to obtain the sharpened image $f_s(x, y)$ according to the equation

$$f_s(x, y) = f(x, y) + \alpha g(x, y) \quad (2)$$

where α is a user specified scaling constant. In many cases, the Laplacian filter

$$\begin{bmatrix} 0 & -0.25 & 0 \\ -0.25 & 1 & -0.25 \\ 0 & -0.25 & 0 \end{bmatrix} \quad (3)$$

is used to obtain $g(x, y)$.

- Write a Matlab function that sharpens an image through high-boost filtering using the Laplacian filter. This function should accept an image (already read into Matlab) along with the value of α as inputs and produce a Matlab variable representing the image in unsigned 8-bit integer format as an output. Please comment your code and append it to your report.

- Use your sharpening function to sharpen the image **moon.tiff**. Try several different values of α and report the value that you feel works best. Be sure to include your sharpened image in your report.
- Now use your sharpening function to sharpen the blurry image **outoffocus.tiff**. Try several different values of α and report the value that you feel works best. Be sure to include your sharpened image in your report. Is it possible to completely recover the original in-focus image? Are there any downsides or unintended artifacts introduced by sharpening the image?

Part 3

An noisy image can be denoised using several different filters. In class, we discussed both the averaging and the median filter.

- Write a Matlab script to denoise the images **peppersNoise1.tiff** and **peppersNoise2.tiff** using both the median filter and the averaging filter. Examine the effect of using different filter window sizes including 3×3 pixels and 5×5 pixels. From your results, what are the advantages or disadvantages of each filter? What are the advantages or disadvantages of changing the filter size? Include your denoised images in your report.
- In many cases, edges must be extracted from a noisy image. If this is necessary, it is important to denoise the image first. Write a Matlab script that generates an edgemap from the 3×3 averaging filtered and median filtered versions of **peppersNoise1.tiff**. Create the edgemap by first calculating the image's gradient using the Sobel filters

$$S_X = \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix} \quad S_Y = \begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ 1 & 2 & 1 \end{bmatrix} \quad (4)$$

to approximate the gradient in the row and column directions, then by comparing the magnitude of the gradient to a threshold. Use the same threshold for both images when generating the edgemap. Please comment your code and append it to your report. What difference do you see between the edgemaps of each filtered image? Which filter has better edge preserving properties?