

```

"use client";
import { useEffect, useState } from "react";
import { addMetric, listMetrics, generateSummary, getToken } from "../api";
import { useRouter } from "next/navigation";

export default function Dashboard() {
  const router = useRouter();
  const [metrics, setMetrics] = useState([]);
  const [name, setName] = useState("");
  const [value, setValue] = useState("");
  const [summary, setSummary] = useState(null);
  const [loadingSummary, setLoadingSummary] = useState(false);
  const [error, setError] = useState("");

  useEffect(() => {
    if (!getToken()) {
      router.push("/login");
      return;
    }
    refreshMetrics();
  }, []);

  async function refreshMetrics() {
    try {
      const data = await listMetrics();
      setMetrics(data);
    } catch (err) {
      setError(err.message);
    }
  }

  async function handleAddMetric(e) {
    e.preventDefault();
    try {
      await addMetric(name, parseFloat(value));
      setName("");
      setValue("");
      refreshMetrics();
    } catch (err) {
      setError(err.message);
    }
  }
}

```

```

async function handleGenerateSummary() {
  setLoadingSummary(true);
  setError("");
  try {
    const data = await generateSummary();
    setSummary(data.summary);
  } catch (err) {
    setError(err.message);
  } finally {
    setLoadingSummary(false);
  }
}

return (
  <main style={{ maxWidth: 700, margin: "40px auto", fontFamily: "sans-serif" }}
    <h1>Analytics Dashboard</h1>

    <section style={{ marginBottom: 32 }}>
      <h2>Add a metric</h2>
      <form onSubmit={handleAddMetric} style={{ display: "flex", gap: 8 }}>
        <input placeholder="Metric name (e.g. monthly_revenue)" value={name}
          onChange={e => setName(e.target.value)} required />
        <input placeholder="Value" type="number" value={value}
          onChange={e => setValue(e.target.value)} required />
        <button type="submit">Add</button>
      </form>
    </section>

    <section style={{ marginBottom: 32 }}>
      <h2>Your metrics</h2>
      {metrics.length === 0 ? (
        <p>No metrics yet – add one above.</p>
      ) : (
        <ul>
          {metrics.map((m) => (
            <li key={m.id}>
              {m.metric_name}: {m.metric_value} ({new Date(m.recorded_at).toLocaleString()})
            </li>
          ))}
        </ul>
      )}
    </section>

    <section>
      <h2>AI KPI Summary</h2>
      <button onClick={handleGenerateSummary} disabled={!loadingSummary}>

```

```
        {loadingSummary ? "Generating..." : "Generate Summary"}
      </button>
      {summary && <p style={{ marginTop: 12, padding: 12, background: "#f5f5f5"
    </section>

    {error && <p style={{ color: "red" }}>{error}</p>}
  </main>
);
}
```