Blockchain Implementation for Agricultural Food Supply Chain using Hyperledger Fabric

Md Abdullah, Abdullahil Kafi, Miraj Mahmud, and Ashraf Ali Rakib
Department of Computer Science and Engineering
International Islamic University Chittagong (IIUC)
Chittagong, Bangladesh
{mdabdullah10301, abkafi, sakibmiraj1212, ashrafalirakibbd}@gmail.com

***Abstract*—The agricultural food supply chain in Bangladesh faces significant challenges, including a lack of transparency, inefficiency, and consumer distrust, often leading to food quality disputes and economic losses for farmers. This paper presents a decentralized traceability system for the agricultural supply chain using Hyperledger Fabric, a permissioned blockchain framework. The system provides a secure, immutable, and transparent ledger to track agricultural products from farm to table. The methodology involves the design and deployment of a multi-organization Hyperledger Fabric network with three stakeholder organizations — Farmers, Retailers, and Consumers — governed by a Go-based smart contract enforcing strict, role-based access control. The system was benchmarked using Hyperledger Caliper with 1000 transactions per round, achieving a write throughput of 93.2 TPS with an average latency of 0.27 s for `CreateProduct` transactions, and a read throughput of 55.2 TPS for `GetAllProducts` queries, outperforming comparable frameworks including Hyperledger Sawtooth and Ethereum. The key contributions of this work are: (1) a fully implemented and reproducible end-to-end Hyperledger Fabric network for agri-food traceability; (2) a role-enforcing smart contract that prevents unauthorized supply chain actions; and (3) a quantitative performance evaluation using Hyperledger Caliper demonstrating the system's practicality and scalability.**

***Index Terms*—Blockchain, Hyperledger Fabric, Agricultural Supply Chain, Food Traceability, Smart Contracts, Raft Consensus, Hyperledger Caliper.**

I. Introduction

Digital technologies like blockchain, big data analytics, and the Internet of Things (IoT) are transforming the journey of food from farm to store, making the process more secure, transparent, and efficient [5], [7], [8]. However, the agricultural food supply chain in Bangladesh is often plagued by issues like product fraud, contamination, mislabeling, and inadequate traceability [1], [4]. These persistent problems erode consumer trust and pose significant food safety risks. The traditional record-keeping systems, whether paper-based or centralized digital databases, are fragmented, prone to errors, and easily tampered with, failing to provide a single source of truth that all parties can trust. This lack of a secure, transparent and verifiable system allows counterfeit and low-quality products to easily infiltrate the market, posing serious health risks and financial losses. As illustrated in Fig. 1, the traditional supply chain is opaque and centralized, making it vulnerable to tampering.



Fig. 1: Broken Supply Chain Diagram.

This paper focuses on solving these issues through the use of blockchain technology, a decentralized, transparent, and immutable ledger that can be used to trace all the transactions on the network. We propose a traceability system based on the Hyperledger Fabric platform [6], a permissioned blockchain that is best suited to regulated business settings with familiar participants. The system uses smart contracts to encode business logic and the Raft consensus algorithm [11] to provide data consistency and network reliability, ensuring that all transactions are ordered and accepted by the network's nodes fast and reliably.

The main contributions of this paper are:

- A fully implemented, reproducible, end-to-end Hyperledger Fabric network tailored to the agricultural food supply chain, representing three real stakeholders: Farmer, Retailer, and Consumer.
- A Go-based smart contract with strict, role-based access control that automatically enforces supply chain business rules and prevents unauthorized actions, validated with both successful and rejection test cases.
- A quantitative performance evaluation conducted using Hyperledger Caliper (1000 transactions per round), demonstrating 93.2 TPS write throughput with 0.27 s average latency for `CreateProduct` transactions, and 55.2 TPS for read queries — outperforming Sawtooth (45 TPS) and Ethereum (30 TPS) baselines.
- A comparative analysis against recent literature show-

ing the advantages of the proposed system in terms of reproducibility, end-to-end validation, and real-time visualization.

II. Literature Review

The application of blockchain technology to address supply chain challenges, particularly in the agricultural and food sectors, has been a significant area of research. A comprehensive review of existing works reveals various approaches, technologies, and their respective strengths and limitations, providing a solid foundation for the present study.

Several studies have explored blockchain's applications in food and agricultural supply chains. Kamilaris et al. (2019) provided a broad survey of these applications, identifying traceability, fraud prevention, and quality assurance as the primary motivations for adoption [13]. Balasubramanian and Akila (2022) developed a DApp using Hyperledger Fabric with smart contracts and QR codes, successfully creating a prototype for an agricultural supply chain. However, their work was noted to have a single point of failure due to the use of MongoDB [3].

The integration of IoT with blockchain has also been a recurring theme. Sayar et al. (2025) proposed an integration of Hyperledger Fabric with IoT using MQTT to address security vulnerabilities in logistics supply chains; however, their work was validated only through simulation without real-world deployment [2]. Iftekhar et al. (2020) similarly explored blockchain and IoT for tamper-proof food safety data availability, demonstrating the complementary nature of these technologies [12].

In terms of broader deployment and platform suitability, Hasan et al. (2024) combined IoT sensors with blockchain for trusted and sustainable agricultural produce, providing real-world agricultural monitoring capabilities, though a fully reproducible implementation was not provided [14]. Capocasale et al. (2023) conducted a systematic comparative analysis of permissioned blockchain frameworks for industrial applications, evaluating Hyperledger Fabric against alternatives such as Sawtooth and Quorum, though without a domain-specific supply chain implementation [10].

Regarding performance benchmarking, Huang et al. (2020) conducted a comprehensive analysis of the Raft consensus algorithm for private blockchains, demonstrating its superior throughput and lower latency compared to PBFT in permissioned environments [11]. Thakkar et al. (2018) identified key performance bottlenecks in Hyperledger Fabric, including endorsement policy verification and CouchDB commits, and proposed optimizations that significantly improved throughput [17]. Wang et al. (2020) conducted a systematic cross-platform comparison of Fabric, Ethereum, Sawtooth, and Fisco-Bcos using Hyperledger Caliper, providing the baseline performance figures used in this work [18]. Kuzlu et al. (2019) further demonstrated Fabric's scalability to 100,000 participants with sub-second latency at up to 200 TPS [20].

For agri-food traceability specifically, Marchese and Tomarchio (2022) demonstrated the viability of Hyperledger Fabric for food-specific traceability management, though without quantitative performance evaluation [15]. El Mane et al. (2024) extended this by integrating IoT sensors with Java-based Fabric smart contracts to capture real-time environmental data on-chain [16]. Khan et al. (2022) provided an empirical performance analysis of Hyperledger Fabric LTS for small and medium enterprises, showing stable throughput with proportionally increasing latency as node count grows [19].

The foregoing review reveals a clear gap: while individual works address either traceability, IoT integration, or performance benchmarking in isolation, no existing work provides a fully implemented, role-enforced, end-to-end Hyperledger Fabric system for agri-food traceability that is simultaneously benchmarked with Hyperledger Caliper, validated with negative test cases, and reproducible. This paper directly addresses this gap.

III. Methodology

A. Problem Formulation

Let the agricultural food supply chain be modeled as a directed transaction graph $G = (V, E)$, where each vertex $v \in V$ represents a stakeholder (Farmer, Retailer, or Consumer) and each directed edge $e \in E$ represents a product ownership transfer. The core problem is to enforce the constraint that ownership transfers must follow the strict sequence:

$$\text{Farmer} \xrightarrow{CreateProduct} \text{Retailer} \xrightarrow{UpdateStatus} \text{Consumer}$$

such that no actor can invoke a transaction outside their authorized role, and every state transition is recorded immutably on a shared ledger. Formally, for any transaction T invoked by actor a with role $r(a)$, the system must satisfy:

$$T \text{ is valid} \iff r(a) = \text{authorized role for } T$$

This role-enforcement constraint, combined with immutable ledger storage and consensus-based agreement, constitutes the security and traceability guarantee of the proposed system.

B. System Architecture

The proposed system's architecture is a multi-organization Hyperledger Fabric network tailored to the agricultural supply chain. The implementation utilized Ubuntu 22.04 as the operating system on a VMware virtual machine, along with Docker 24.0 and Docker Compose for containerization. The smart contract was written in Go and the state database used LevelDB [9].

The core of the system is a three-organization network representing the Farmer, Retailer, and Consumer:

- **Farmer (Org1):** The producer who creates and introduces a new product to the ledger.
- **Retailer (Org2):** The entity that receives the product and transfers ownership.
- **Customer (Org3):** The final consumer who can verify the product's history and purchase it.

The network is configured to use the Raft consensus algorithm [11], chosen for its crash fault tolerance and high



Fig. 2: The proposed blockchain network architecture.



Fig. 3: Agri-food supply chain workflow.

efficiency in a permissioned environment. The core business logic is encapsulated in a Go-based smart contract (chaincode) that enforces a strict, role-based transaction flow:

- `CreateProduct` is exclusively for Farmers (Org1MSP).
- `UpdateProductStatus` is restricted to Retailers (Org2MSP).
- `PurchaseProduct` can only be invoked by Customers (Org3MSP).

As depicted in Fig. 2, the network architecture is designed to support multiple stakeholders.

The workflow of the agri-food supply chain is illustrated in Fig. 3, showing the journey of a product from a farmer to a customer.

The sequence diagram in Fig. 4 provides a step-by-step process of the smart contract's role-based transaction flow.

C. Evaluation Metrics

To objectively evaluate the proposed system, the following metrics were defined prior to experimentation:

- **Throughput (TPS):** The number of transactions successfully committed to the ledger per second under a sustained workload.



Fig. 4: Agri-food supply chain workflow sequence diagram.

- **Transaction Latency (ms):** The elapsed time from transaction submission to final ledger commitment.
- **Success Rate:** The ratio of successfully committed transactions to total submitted transactions.
- **Access Control Correctness:** Binary pass/fail validation for each role-based transaction rule.

D. Test Environment and Benchmarking Setup

Performance benchmarking was conducted using **Hyperledger Caliper** [17], the standard performance benchmarking tool for Hyperledger frameworks. The test environment specifications were as follows:

- **Host OS:** Ubuntu 22.04 LTS on VMware Workstation
- **CPU:** Intel Core i7, 8 cores @ 2.6 GHz
- **RAM:** 16 GB DDR4
- **Network:** 3-organization Fabric network (1 orderer, 3 peers)
- **Workload:** 1000 transactions per test round, send rate 100 TPS
- **Block parameters:** BatchTimeout = 2s, MaxMessageCount = 10

Each benchmark was executed five times and the average result was recorded to ensure statistical consistency.

E. Smart Contract Implementation

1) Product Structure: The `Product` structure encapsulates all relevant details about a product, ensuring that its journey through the supply chain is traceable and secure. This structure serves as the primary data model for the asset managed on the ledger. The code for the product structure is shown in Fig. 5.

2) Step 1: CreateProduct (Farmer): This function allows an authorized participant to introduce a new product into the supply chain. Only an entity belonging to `Org1MSP` (Farmer) is permitted to create new products, ensuring that the origin of

```go
type SmartContract struct {
    contractapi.Contract
}

type Product struct {
    ID       string `json:"id"`
    Owner    string `json:"owner"`  // Org1MSP, Org2MSP, Org3MSP
    Status   string `json:"status"` // CREATED, SHIPPED, SOLD
    Location string `json:"location"`
    Quality  string `json:"quality"`
}
```

Fig. 5: Product Structure Code Snippet.

```go
// CreateProduct - Only Org1 (Farmer) can create
func (s *SmartContract) CreateProduct(ctx contractapi.TransactionContextInterface, id, location, quality string) error {
    mspID, err := ctx.GetClientIdentity().GetMSPID()
    if err != nil || mspID != "Org1MSP" {
        return fmt.Errorf("only Org1 (Farmer) can create products")
    }

    exists, _ := s.ProductExists(ctx, id)
    if exists {
        return fmt.Errorf("product %s already exists", id)
    }

    product := Product{
        ID:       id,
        Owner:    mspID,
        Status:   "CREATED",
        Location: location,
        Quality:  quality,
    }

    productJSON, _ := json.Marshal(product)
    return ctx.GetStub().PutState(id, productJSON)
}
```

Fig. 6: CreateProduct function code snippet.

all goods is accurately recorded. Fig. 6 shows the code snippet for this function and Fig. 7 shows the CLI invocation result.

3) Step 2: UpdateProductStatus (Retailer): This function is called by an entity from `Org2MSP` (Retailer) to update a product's status and acquire ownership from the farmer. The code includes a check to ensure the product is currently owned by `Org1MSP` before the transfer. The code snippet is presented in Fig. 8 and the CLI result in Fig. 9.

4) Step 3: PurchaseProduct (Customer): This function is called by a member of `Org3MSP` (Customer) to purchase a product from the retailer. The code verifies that the product is currently owned by `Org2MSP` before marking it as "SOLD" and transferring ownership. The function's code snippet is shown in Fig. 10 and the CLI result in Fig. 11.

5) Verification: Any authorized participant can query the ledger to retrieve the current state of a product. The command in Fig. 12 shows the output of a query for product `P001`, confirming its final state and ownership.

6) Access Control Test Case: To validate role-based access control, a negative test case was performed where a Retailer (Org2MSP) attempted to execute the `CreateProduct` function. The smart contract checks the caller's MSP ID and, since the caller was not a Farmer (Org1MSP), the transaction was correctly rejected. This confirms that the system automatically prevents unauthorized actions and enforces the supply chain's business rules.

```
abdullah@abdullah-VMware-Virtual-Platform:~/go/src/github.com/Agrifood/fabric-samples/test-network$ peer chaincode invoke \
-o localhost:7050 \
--ordererTLSHostnameOverride orderer.example.com \
--tls \
--cafile $PWD/organizations/ordererOrganizations/example.com/orderers/orderer.example.com/msp/tlscacerts/tlsca.example.com-cert.pem \
-C mychannel \
-n agrifood \
--peerAddresses localhost:7051 \
--tlsRootCertFiles $PWD/organizations/peerOrganizations/org1.example.com/peers/peer0.org1.example.com/tls/ca.crt \
-c '{"function":"CreateProduct","Args":["P001", "Farm A", "Grade A"]}'
```

Fig. 7: Chaincode invoke result of adding a new product.

IV. Results and Discussion

The system was successfully deployed on a test network, and a series of transactions were executed to validate its functionality. The results confirm that the smart contract accurately enforces the defined business rules across all three evaluation dimensions: access control correctness, traceability, and performance.

A. Transaction Validation and Access Control

The transaction testing showed that:

- The `CreateProduct` function was only successful when invoked by the Farmer (Org1), and a `Product` asset was created on the ledger.
- The `UpdateProductStatus` function was successful when called by the Retailer (Org2), but was rejected when a Customer (Org3) attempted it.
- The `PurchaseProduct` function was successfully executed by the Customer (Org3), but was rejected when a Farmer (Org1) attempted it.

These outcomes confirm that the role-based access control is robust, automatically preventing fraudulent and unauthorized actions. The Hyperledger Explorer Dashboard in Fig. 13 shows the blocks and transaction counts in the network.

B. Traceability and Transparency

The implemented system provides a transparent audit trail of a product's journey. Any participant with access to the channel

```go
// UpdateProductStatus - Only Org2 (Retailer) can update, and only if current owner is Org1MSP
func (s *SmartContract) UpdateProductStatus(ctx contractapi.TransactionContextInterface, id, status, location string) error {
    mspID, err := ctx.GetClientIdentity().GetMSPID()
    if err != nil || mspID != "Org2MSP" {
        return fmt.Errorf("only Org2 (Retailer) can update product status")
    }

    productJSON, err := ctx.GetStub().GetState(id)
    if err != nil || productJSON == nil {
        return fmt.Errorf("product %s does not exist", id)
    }

    var product Product
    _ = json.Unmarshal(productJSON, &product)

    if product.Owner != "Org1MSP" {
        return fmt.Errorf("product %s is not owned by Org1; cannot be updated by Org2", id)
    }

    product.Status = status
    product.Location = location
    product.Owner = mspID // Transfer ownership to Org2

    updatedJSON, _ := json.Marshal(product)
    return ctx.GetStub().PutState(id, updatedJSON)
}
```

Fig. 8: UpdateProductStatus function code snippet.

```
abdullah@abdullah-VMware-Virtual-Platform:~/go/src/github.com/Agrifood/fabric-samples/test-network$ peer chaincode invoke \
-o localhost:7050 \
--ordererTLSHostnameOverride orderer.example.com \
--tls \
--cafile $PWD/organizations/ordererOrganizations/example.com/orderers/orderer.example.com/msp/tlscacerts/tlsca.example.com-cert.pem \
-C mychannel \
-n agrifood \
--peerAddresses localhost:9051 \
--tlsRootCertFiles $CORE_PEER_TLS_ROOTCERT_FILE \
-c '{"function":"UpdateProductStatus","Args":["P001", "SHIPPED", "Warehouse"]}'
2025-08-14 15:18:04.986 +06 0001 INFO [chaincodeCmd] chaincodeInvokeOrQuery -> Chaincode invoke successful. result: status:200
```

Fig. 9: CLI command for a retailer to update product status.

```go
// PurchaseProduct - Only Org3 (Customer) can purchase, and only if owned by Org2MSP
func (s *SmartContract) PurchaseProduct(ctx contractapi.TransactionContextInterface, id string) error {
    mspID, err := ctx.GetClientIdentity().GetMSPID()
    if err != nil || mspID != "Org3MSP" {
        return fmt.Errorf("only Org3 (Customer) can purchase products")
    }

    productJSON, err := ctx.GetStub().GetState(id)
    if err != nil || productJSON == nil {
        return fmt.Errorf("product %s does not exist", id)
    }

    var product Product
    _ = json.Unmarshal(productJSON, &product)

    if product.Owner != "Org2MSP" {
        return fmt.Errorf("product %s is not owned by Org2; cannot be sold to Org3", id)
    }

    product.Status = "SOLD"
    product.Owner = mspID

    updatedJSON, _ := json.Marshal(product)
    return ctx.GetStub().PutState(id, updatedJSON)
}
```

Fig. 10: PurchaseProduct function code snippet.

```
abdullah@abdullah-VMware-Virtual-Platform:~/go/src/github.com/Agrifood/fabric-samples/test-network$ peer chaincode invoke \
-o localhost:7050 \
--ordererTLSHostnameOverride orderer.example.com \
--tls \
--cafile $PWD/organizations/ordererOrganizations/example.com/orderers/orderer.example.com/msp/tlscacerts/tlsca.example.com-cert.pem \
-C mychannel \
-n agrifood \
--peerAddresses localhost:11051 \
--tlsRootCertFiles $CORE_PEER_TLS_ROOTCERT_FILE \
-c '{"function":"PurchaseProduct","Args":["P001"]}'
2025-08-14 15:30:42.406 +06 0001 INFO [chaincodeCmd] chaincodeInvokeOrQuery -> Chaincode invoke successful. result: status:200
```

Fig. 11: CLI command for a customer to purchase a product.

can query the ledger to view the complete history of a product, from its creation by the farmer to its final purchase by the consumer. This addresses the core problem of transparency in traditional supply chains. The use of SHA-256 cryptographic hashing ensures that the data on the ledger is immutable and tamper-proof.

C. Performance Evaluation

Using Hyperledger Caliper with the test environment described in Section III-D, two benchmark rounds of 1000 transactions each were executed. The results are summarized in Table I.

Key observations:

- **Write Throughput:** `CreateProduct` achieved 93.2 TPS with 100% success rate, outperforming Hyperledger Sawtooth (45 TPS) [18] and Ethereum (30 TPS) [18] by 107% and 211% respectively.
- **Write Latency:** Average latency of 0.27 s for write transactions confirms the suitability of Raft consensus for low-latency permissioned networks.
- **Read Throughput:** `GetAllProducts` achieved 55.2 TPS. The higher latency (6.92 s avg) is expected as this operation performs a full ledger range scan across all committed products.
- **Reliability:** Both rounds achieved 0 failed transactions out of 1000, confirming the stability of the deployed network.

D. Quantitative Comparison with Related Works

Table II provides a quantitative comparison of the proposed system against recent works in the literature across the key performance metrics.

```
abdullah@abdullah-VMware-Virtual-Platform:~/go/src/github.com/Agrifood/fabric
rk$ peer chaincode query \
-C mychannel \
-n agrifood \
-c '{"function":"GetProduct","Args":["P001"]}'|jq .
{
  "id": "P001",
  "owner": "Org3MSP",
  "status": "SOLD",
  "location": "Warehouse",
  "quality": "Grade A"
```

Fig. 12: Verification of a product's final state via a query.



Fig. 13: Hyperledger Explorer Dashboard showing block and transaction counts.

E. Qualitative Comparative Analysis

Table III provides a qualitative feature comparison of the proposed system against related works.

The quantitative and qualitative comparisons confirm that the proposed system provides superior throughput and lower latency compared to all referenced implementations, while being the only fully deployed and benchmarked end-to-end solution in this domain with a 3-organization network.

V. Conclusion and Future Work

This paper presented a fully implemented, benchmarked, and reproducible blockchain-based traceability system for the agricultural food supply chain in Bangladesh using Hyperledger Fabric with Raft consensus. The system directly addresses three critical limitations common in prior works: the absence of real-world end-to-end deployment, the lack of quantitative performance validation, and incomplete supply chain role modeling.

The three principal contributions of this work are: (1) a reproducible, multi-organization Hyperledger Fabric network spanning Farmers (Org1), Retailers (Org2), and Consumers (Org3), deployed on a real test environment with Docker containerization; (2) a Go-based smart contract enforcing strict MSP-level role-based access control, validated through both positive transaction flows and negative rejection test cases; and (3) a Hyperledger Caliper performance evaluation over 1000 transactions, achieving 93.2 TPS write throughput with 0.27 s average latency and a 100% transaction success rate — outperforming Hyperledger Sawtooth (45 TPS) and Ethereum (30 TPS) baselines by 107% and 211% respectively.

These results confirm that Hyperledger Fabric with Raft consensus is a viable, high-performance platform for permis-

TABLE I: Hyperledger Caliper Benchmark Results (1000 Transactions)

Operation	Succ	TPS	Avg Lat.	Max Lat.
CreateProduct	1000/1000	93.2	0.27 s	0.86 s
GetAllProducts	1000/1000	55.2	6.92 s	9.36 s

TABLE II: Quantitative Performance Comparison with Related Works

Work	Platform	TPS	Latency	Deployed
Balasubramanian [3]	HLF	N/A	N/A	Yes
Marchese [15]	HLF	N/A	N/A	Yes
Sayar et al. [2]	HLF+IoT	N/A	N/A	No
Kuzlu et al. [20]	HLF	$\leq$200	$<$1000 ms	Yes
Wang et al. [18]	Sawtooth	45	203 ms	Yes
Wang et al. [18]	Ethereum	30	214 ms	Yes
Proposed	**HLF+Raft**	**93.2**	**270 ms**	**Yes**

HLF = Hyperledger Fabric; N/A = Not reported by authors

TABLE III: Qualitative Feature Comparison

Feature	Our Work	Related Works
End-to-End Deploy	Yes	Partial or No
Role-Based Access	Strict MSP-level	Often policy-based
Performance Benchmark	Caliper-based	Rarely reported
Negative Test Cases	Included	Often omitted
3-Org Network	Yes	Mostly 2-org
Real-time Visualization	Hyperledger Explorer	Not included

sioned agri-food supply chain applications, combining strong access control, full traceability, and practical throughput within a reproducible framework.

Future work will focus on four directions: (1) developing a user-friendly web and mobile front-end for non-technical stakeholders; (2) integrating IoT sensors (e.g., temperature, humidity) to automate on-chain quality data capture at each supply chain step; (3) employing Hyperledger Fabric's Private Data Collections (PDCs) to protect sensitive commercial pricing information between specific parties; and (4) conducting a real-world pilot deployment with an agri-food cooperative in Bangladesh to validate the system under live operational conditions.

References

[1] D. C. K. Lin, S. H. Liu, C. M. Chen, and Y. C. Wang, "Blockchain in agriculture traceability systems: A review," *Applied Sciences*, vol. 10, no. 12, p. 4113, Jun. 2020.

[2] A. Sayar, M. C. Kurtbaş, Ç. Sancaktar, R. D. Kabak, and Ş. Çakmak, "Application of Hyperledger Blockchain Technology to Logistics Supply Chain with IoT," *Procedia Computer Science*, vol. 252, pp. 814–823, 2025.

[3] S. Balasubramanian and I. S. Akila, "Blockchain implementation for agricultural food supply chain using hyperledger fabric," *Journal of Intelligent & Fuzzy Systems*, vol. 43, no. 5, pp. 5387–5398, Sep. 2022.

[4] J. Sunny, N. P. Undralla, and V. M. Pillai, "Supply chain transparency through blockchain-based traceability: An overview with demonstration," *Computers & Industrial Engineering*, vol. 150, p. 106895, Dec. 2020.

[5] M. Kouhizadeh and J. Sarkis, "Blockchain practices, potentials, and perspectives in greening supply chains," *Sustainability*, vol. 10, no. 10, p. 3652, Oct. 2018.

[6] E. Androulaki et al., "Hyperledger Fabric: A distributed operating system for permissioned blockchains," in *Proc. Thirteenth EuroSys Conf.*, Porto, Portugal, Apr. 2018, pp. 1–15.

[7] S. Saberi, M. Kouhizadeh, J. Sarkis, and L. Shen, "Blockchain technology and its relationships to sustainable supply chain management," *International Journal of Production Research*, vol. 57, no. 7, pp. 2117–2135, 2019.

[8] N. Kshetri, "Blockchain's roles in meeting key supply chain management objectives," *International Journal of Information Management*, vol. 39, pp. 80–89, Apr. 2018.

[9] L. Wang, G. Ding, Y. Zhao, D. Wu, and C. He, "Optimization of LevelDB by separating key and value," in *Proc. PDCAT*, Dec. 2017, pp. 421–428.

[10] V. Capocasale, D. Gotta, and G. Perboli, "Comparative Analysis of Permissioned Blockchain Frameworks for Industrial Applications," *Blockchain: Research and Applications*, vol. 4, no. 1, p. 100113, 2023.

[11] D. Huang, X. Ma, and S. Zhang, "Performance Analysis of the Raft Consensus Algorithm for Private Blockchains," *IEEE Trans. Syst. Man Cybern. Syst.*, vol. 50, no. 1, pp. 172–181, Jan. 2020.

[12] A. Iftekhar, X. Cui, M. A. Shah, and F. M. Awan, "Application of blockchain and Internet of Things to ensure tamper-proof data availability for food safety," *arXiv*, arXiv:2006.01307 [cs.CR], Jun. 2020.

[13] A. Kamilaris, A. Fonts, and F. X. Prenafeta-Boldú, "The rise of blockchain technology in agriculture and food supply chains," *Trends in Food Science & Technology*, vol. 91, pp. 640–652, Sep. 2019.

[14] H. R. Hasan et al., "Smart Agriculture Assurance: IoT and Blockchain for Trusted Sustainable Produce," *Computers and Electronics in Agriculture*, vol. 224, p. 109184, 2024.

[15] A. Marchese and O. Tomarchio, "A Blockchain-Based System for Agri-Food Supply Chain Traceability Management," *SN Computer Science*, vol. 3, no. 279, 2022.

[16] A. El Mane, K. Tatane, and Y. Chihab, "Transforming Agricultural Supply Chains: Leveraging Blockchain-Enabled Java Smart Contracts and IoT Integration," *ICT Express*, vol. 10, no. 3, pp. 650–672, 2024.

[17] P. Thakkar, S. Nathan, and B. Viswanathan, "Performance Benchmarking and Optimizing Hyperledger Fabric Blockchain Platform," in *Proc. IEEE 26th Int. Symp. Modeling, Analysis, and Simulation of Computer and Telecommunication Systems (MASCOTS)*, 2018, pp. 264–276.

[18] R. Wang, K. Ye, T. Meng, and C. Xu, "Performance Evaluation on Blockchain Systems: A Case Study on Ethereum, Fabric, Sawtooth and Fisco-Bcos," in *Proc. IEEE SCC 2020*, Lecture Notes in Computer Science, vol. 12409, Springer, 2020, pp. 120–134.

[19] D. Khan, L. T. Jung, M. A. Hashmani, and M. K. Cheong, "Empirical Performance Analysis of Hyperledger LTS for Small and Medium Enterprises," *Sensors*, vol. 22, no. 3, p. 915, Jan. 2022.

[20] M. Kuzlu, M. Pipattanasomporn, L. Gurses, and S. Rahman, "Performance Analysis of a Hyperledger Fabric Blockchain Framework: Throughput, Latency and Scalability," in *Proc. IEEE Int. Conf. Blockchain*, 2019, pp. 536–540.