



# برمجة I Programming I


Ahmad Khoj  
King Abdulaziz University



## Chapter 5 Methods



```
return ...  
}   
NetworkStream ns = server.GetStream();  
int recv = ns.Read(data, 0, data.Length);  
stringData = Encoding.  
ASCII.GetString(data, 0, recv);  
Console.WriteLine(stringData);  
while(true){  
    input = Console.ReadLine();  
    if (input == "exit") break;  
    newChild.Properties["out"].Add  
    ("Auditing Department");  
    newChild.DismatchChange();  
    newChild.Clone();  
    newChild.Dispose();  
}
```




# Introducing Methods


**A method** is a collection of statements that are grouped together to perform an operation.

## ❑ Benefits of Methods:

1. **Write a method once** and reuse it anywhere.
2. **Information hiding**. Hide the implementation from the user.
3. **Reduce complexity**.



# The syntax for defining a method



## 2. Defining method return value:

```
public static int sum (int num1 , int num2){  
    int result = num1 + num2 ;  
    return result ;  
} // End defining method
```

### Note:

You have to define a method:

1. Inside a Class
2. Outside a main method

# Defining Void

```
public class KHOJ {  
  
    public static void main(String[] args) {  
        int num1 = 3;  
        int num2 = 4;  
        sum(num1 , num2);  
        System.out.println("Ahmad Khoj");  
    } // End Main Method
```

2) Calling Method

```
    public static void sum (int num1 , int num2){  
        int result = num1 + num2 ;  
        System.out.println(result);  
    } // End sum Method
```

1) Defining Method

```
} // End Class
```

Output:

7

Ahmad Khoj

# Defining Void

```
public class KHOJ {
```

```
    public static void sum (int num1 , int num2) {  
        int result = num1 + num2 ;  
        System.out.println(result);  
    } // End sum Method
```

1) Defining Method

```
    public static void main(String[] args) {  
        int num1 = 3;  
        int num2 = 4;  
        sum(num1 , num2);  
        System.out.println("Ahmad Khoj");  
    } // End Main Method
```

2) Calling Method

```
} // End Class
```

Output:

7

Ahmad Khoj

# Defining method return value

```
public class KHOJ {
```

```
    public static int sum (int num1 , int num2) {  
        int result = num1 + num2 ;  
        return result ;  
    } // End sum Method
```

**1) Defining Method**

```
    public static void main(String[] args) {  
        int num1 = 3;  
        int num2 = 4;  
        int num3 = sum(num1 , num2);  
        System.out.println(num3);  
        System.out.println("Ahmad Khoj");  
    } // End Main Method
```

**2) Calling Method**

```
} // End Class
```

Output:

7

Ahmad Khoj

```
public class KHOJ {  
  
    public static int max (int num1 , int num2) {  
        int result ;  
  
        if(num1 > num2)  
            result = num1 ;  
        else  
            result = num2 ;  
  
        System.out.println("Ahmad");  
        return result ;  
    } // End sum Method  
  
    public static void main(String[] args) {  
        int num1 = 3;  
        int num2 = 4;  
        int num3 = max(num1 , num2);  
        System.out.println(num3);  
        System.out.println("Khoj");  
    } // End Main Method  
  
} // End Class
```

num1 is now 3



```

public class KHOJ {

    public static int max (int num1 , int num2) {
        int result ;

        if(num1 > num2)
            result = num1 ;
        else
            result = num2 ;

        System.out.println("Ahmad");
        return result ;
    } // End sum

    public static void main(String[] args) {
        int num1 = 3;
        int num2 = 4;
        int num3 = max(num1 , num2);
        System.out.println(num3);
        System.out.println("Khoj");
    } // End Main Method

} // End Class

```

num2 is now 4

```

public class KHOJ {

    public static int max (int num1 , int num2) {
        int result ;

        if(num1 > num2)
            result = num1 ;
        else
            result = num2 ;

        System.out.println("Ahmad");
        return result ;
    } // End sum Method

    public static void main(String args) {
        int num1 = 3;
        int num2 = 4;
        int num3 = max(num1 , num2);
        System.out.println(num3);
        System.out.println("Khoj");
    } // End Main Method

} // End Class

```

invoke max(num1 , num2)

```
public class KHOJ {  
  
    public static int max (int num1 , int num2){  
        int result ;  
  
        if(num1 > num2)  
            result = num1 ;  
        else  
            result = num2 ;  
  
        System.out.println("Ahmad");  
        return result ;  
    } // End sum Method  
  
    public static void main(String[] args) {  
        int num1 = 3;  
        int num2 = 4;  
        int num3 = max(num1 , num2);  
        System.out.println(num3);  
        System.out.println("Khoj");  
    } // End Main Method  
  
} // End Class
```

invoke max(num1 , num2)  
Pass the value of num1 to num1  
Pass the value of num2 to num2

declare variable result

```
public class KHOJ {  
  
    public static int max (int num1 , int num2) {  
        int result ;  
  
        if(num1 > num2)  
            result = num1 ;  
        else  
            result = num2 ;  
  
        System.out.println("Ahmad");  
        return result ;  
    } // End sum Method  
  
    public static void main(String[] args) {  
        int num1 = 3;  
        int num2 = 4;  
        int num3 = max(num1 , num2);  
        System.out.println(num3);  
        System.out.println("Khoj");  
    } // End Main Method  
  
} // End Class
```

```

public class KHOJ {
    public static int max(int num1 , int num2) {
        int result ;

        if(num1 > num2)
            result = num1 ;
        else
            result = num2 ;

        System.out.println("Ahmad");
        return result ;
    } // End sum Method

    public static void main(String[] args) {
        int num1 = 3;
        int num2 = 4;
        int num3 = max(num1 , num2);
        System.out.println(num3);
        System.out.println("Khoj");
    } // End Main Method

} // End Class

```

(num1 > num2) is false

```
public class KHOJ {  
  
    public static int max (int num1 , int num2) {  
        int result ;  
  
        if(num1 > num2)  
            result = num1  
        else  
            result = num2 ;  
  
        System.out.println("Ahmad");  
        return result ;  
    } // End sum Method  
  
    public static void main(String[] args) {  
        int num1 = 3;  
        int num2 = 4;  
        int num3 = max(num1 , num2);  
        System.out.println(num3);  
        System.out.println("Khoj");  
    } // End Main Method  
  
} // End Class
```

result is now 4

```

public class KHOJ {

    public static int max (int num1 , int num2) {
        int result ;

        if(num1 > num2)
            result = num1;
        else
            result = num2;

        System.out.println("Ahmad");
        return result ;
    } // End sum Method

    public static void main(String[] args) {
        int num1 = 3;
        int num2 = 4;
        int num3 = max(num1 , num2);
        System.out.println(num3);
        System.out.println("Khoj");
    } // End Main Method

} // End Class

```



Print Ahmad

Output:  
Ahmad

```

public class KHOJ {

    public static int max (int num1 , int num2) {
        int result ;

        if(num1 > num2)
            result = num1 ;
        else
            result = num2 ;

        System.out.println("Ahmad");
        return result ;
    } // End sum Method

    public static void main(String[] args) {
        int num1 = 3;
        int num2 = 4;
        int num3 = max(num1 , num2);
        System.out.println(num3);
        System.out.println("Khoj");
    } // End Main Method

} // End Class

```

return result, which is 4

Output:  
Ahmad



```

public class KHOJ {

    public static int max (int num1 , int num2) {
        int result ;

        if(num1 > num2)
            result = num1 ;
        else
            result = num2 ;

        System.out.println("Ahmad");
        return result ;
    } // End sum

    public static
    int num1 = 3;
    int num2 = 4;
    int num3 = max(num1 , num2);
    System.out.println(num3);
    System.out.println("Khoj");
} // End Main Method

} // End Class

```

return max(num1,num2) and assign the return value to num3

Output:  
Ahmad

```

public class KHOJ {

    public static int max (int num1 , int num2) {
        int result ;

        if(num1 > num2)
            result = num1 ;
        else
            result = num2 ;

        System.out.println("Ahmad");
        return result ;
    } // End sum Method

    public static void main (String args[]) {
        int num1 = 3;
        int num2 = 4;
        int num3 = max(num1 , num2);
        System.out.println(num3);
        System.out.println("Khoj");
    } // End Main Method

} // End Class

```

Print num3 which is 4

Output:  
Ahmad  
4

```

public class KHOJ {

    public static int max (int num1 , int num2) {
        int result ;

        if(num1 > num2)
            result = num1 ;
        else
            result = num2 ;

        System.out.println("Ahmad");
        return result ;
    } // End sum Method

    public static void main (String[] args) {
        int num1 = 5;
        int num2 = 4;
        int num3 = max (num1 , num2);
        System.out.println(num3);
        System.out.println("Khoj");
    } // End Main Method

} // End Class

```



Print Ahmad

Output:  
Ahmad  
4  
Khoj

## Example: sum 2 numbers method - return no value

```
public static void main(String[] args){  
    int num1 = 3;  
    int num2 = 4;  
    sum(num1, num2);  
}
```

```
public static void sum(int num1, int num2){  
    int result = num1 + num2;  
    System.out.println(result);  
}
```

## Example: sum 2 numbers method - return int value

```
public static void main(String[] args){  
    int num1 = 3;  
    int num2 = 4;  
    int num3 = sum(num1, num2);  
    System.out.println(num3);  
}
```

```
public static int sum(int n1, int n2){  
    int result = n1 + n2;  
    return result;  
}
```

## Exercise: max method – return no value

```
public static void main(String[] args) {  
    int n1 = 3;  
    int n2 = 4;  
    max(n1, n2);  
}
```

```
public static void max (int n1, int n2) {  
    if (n1 > n2)  
        System.out.println(n1);  
    else  
        System.out.println(n2);  
}
```

## Exercise: max method – return int value

```
public static void main(String[] args) {  
    int n1 = 3;  
    int n2 = 4;  
    int n3 = max(n1, n2);  
    System.out.println(n3);  
}
```

```
public static int max (int n1, int n2) {  
    if (n1 > n2)  
        return n1;  
    else  
        return n2;  
}
```

# Method assists to **avoid repeating** codes

```
public class KHOJ {  
    public static void main(String[] args) {  
  
        int sum = 0;  
        for (int i = 1; i <= 10; i++)  
            sum += i;  
        System.out.println("Sum from 1 to 10 is " + sum);  
  
        sum = 0;  
        for (int i = 12; i <= 22; i++)  
            sum += i;  
        System.out.println("Sum from 12 to 22 is " + sum);  
  
        sum = 0;  
        for (int i = 32; i <= 40; i++)  
            sum += i;  
        System.out.println("Sum from 32 to 40 is " + sum);  
  
    } // End Main Method  
} // End Class
```

```
run:  
Sum from 1 to 10 is 55  
Sum from 12 to 22 is 187  
Sum from 32 to 40 is 324  
BUILD SUCCESSFUL (total time: 0 seconds)
```

# Method assists to avoid repeating codes

```
public class KHOJ {  
  
    public static void sumFromTo(int start , int end) {  
        int sum = 0;  
        for (int i = start ; i <= end ; i++){  
            sum += i;  
        } //End for  
        System.out.println("Sum from " + start + " to " + end + " is " + sum);  
    } // End sumFromTo method  
  
    public static void main(String[] args) {  
        sumFromTo(1 , 10);  
        sumFromTo(12 , 22);  
        sumFromTo(32 , 44);  
    } // End Main Method  
  
} // End Class
```

```
run:  
Sum from 1 to 10 is 55  
Sum from 12 to 22 is 187  
Sum from 32 to 44 is 324  
BUILD SUCCESSFUL (total time: 0 seconds)
```

## Exercise: sum loops method – return no value

```
public static void main(String[] args){  
  
    sumVoid(1 , 10);  
    sumVoid(12 , 22);  
    sumVoid(32 , 44);  
  
}
```

```
public static void sumVoid(int start,int end){  
    int sum = 0;  
    for (int i = start; i <= end; i++) {  
        sum += i;  
    }  
    System.out.println("Sum from "+start+" to "+end+"is "+ sum);  
}
```

## Exercise: sum loops method – return int value

```
public static void main(String[] args){  
    System.out.println("Sum from 1 to 10 is "  
+ sumInt(1, 10));  
    System.out.println("Sum from 12 to 22 is "  
+ sumInt(12, 22));  
    System.out.println("Sum from 32 to 44 is "  
+ sumInt(32, 44));  
}
```

```
public static int sumInt(int start,int end){  
  
    int sum = 0;  
    for (int i = start; i <= end; i++) {  
        sum += i;  
    }  
    return sum;  
}
```



# Passing Parameters

```
public class KHOJ {  
  
    public static void nPrintln(String message, int n){  
        for(int i=0 ; i<n ; i++){  
            System.out.println(message);  
        } //End nPrintln Method  
  
    public static void main(String[] args) {  
        nPrintln("Ahmad Khoj" , 5);  
  
        nPrintln("COCS 202" , 15);  
    } // End Main Method  
  
} // End Class
```

run:  
Ahmad Khoj  
Ahmad Khoj  
Ahmad Khoj  
Ahmad Khoj  
Ahmad Khoj  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202  
COCS 202

# Scope of Local Variables

- **A local variable:** a variable defined inside a method.
- **Scope:** the part of the program where the variable can be referenced.
- The scope of a local variable **starts from its declaration and continues to the end of the block that contains the variable.**
- A local variable **must be declared before it can be used.**

## Scope of Local Variables, cont.

- A variable declared in the initial action part of a `for` loop header has **its scope in the entire loop**.
- But a variable declared inside a `for` loop body has **its scope limited in the loop body from its declaration and to the end of the block that contains the variable**.

```
public static void method1() {  
    .  
    .  
    for (int i = 1; i < 10; i++) {  
        .  
        .  
        int j;  
        .  
        .  
        .  
    }  
}
```

The scope of i →

The scope of j →

# Scope of Local Variables, cont.

- It is **fine** to declare i in two non-nesting blocks
- It is **wrong** to declare i in two nesting blocks

```
public class KHOJ {  
    public static void main(String[] args) {  
  
        int x = 0;  
        int y = 0;  
  
        for(int i=1 ; i<=10 ; i++) {  
            x+=i;  
        }  
  
        for(int i=1 ; i<=10 ; i++) {  
            y+=i;  
        }  
  
        System.out.println("x= " + x);  
        System.out.println("y= " + y);  
    } // End Main Method  
} // End Class
```

```
public class KHOJ {  
    public static void main(String[] args) {  
  
        int sum = 0;  
  
        for(int i=1 ; i<=10 ; i++) {  
            for(int i=1 ; i<=10 ; i++)  
                sum+=i;  
        } //end for #1  
  
        System.out.println("sum= " + sum);  
    } // End Main Method  
} // End Class
```

# The Math Class

- Class constants:

- PI

- ```
Math.PI; //returns 3.141592653589793
```

- Class methods:

- Trigonometric Methods

- Exponent Methods

- Rounding Methods

- min, max, abs, and random Methods

# Trigonometric Methods

Examples:

```
Math.sin(0) //returns 0.0
```

```
Math.sin(Math.PI/ 6) //returns 0.5
```

```
Math.sin(Math.PI/ 2) //returns 1.0
```

```
Math.cos(0) //returns 1.0
```

```
Math.cos(Math.PI/6) //returns 0.866
```

```
Math.cos(Math.PI / 2) //returns 0
```

- `sin(double a)`
- `cos(double a)`
- `tan(double a)`

# Exponent Methods

- `pow(double a, double b)`

Returns a raised to the power of b.

```
Math.pow(2, 3);    //returns 8.0
```

- `sqrt(double a)`

Returns the square root of a.

```
Math.sqrt(4);      //returns 2.0
```

# Rounding Methods

- `double ceil(double x)`  
x rounded up to its nearest integer. This integer is returned as a double value.
- `double floor(double x)`  
x is rounded down to its nearest integer. This integer is returned as a double value.
- `int round(float x)`  
Return `(int)Math.floor(x+0.5)`.



## Rounding Methods Examples

`Math.ceil(2.1) //returns 3.0`

`Math.ceil(2.0) //returns 2.0`

`Math.floor(2.1) //returns 2.0`

`Math.floor(2.0) //returns 2.0`

`Math.round(2.5) //returns 3.0`

`Math.round(2.4) //returns 2.0`

# random Method

Generates a random **double value** greater than or equal to 0.0 and less than 1.0.

Examples:

```
Math.random();
```



Returns a **random double** between **0.0** and **1.0**

```
(int) (Math.random() * 10);
```



Returns a **random integer** between **0** and **9**.

# The Math Class

```
/** Class constants */
double a = Math.PI; //3.141592653589793
/** Class methods */
//Trigonometric Methods
double b = Math.sin(0); //0.0
double c = Math.cos(Math.PI/6); //0.8660254037844387
double d = Math.tan(Math.PI/2); //1.633123935319537E16
//Exponent Methods
double e = Math.pow(2, 3); //8.0
double f = Math.sqrt(4); //2.0
//Rounding Methods
double g = Math.ceil(7.1); //8.0
double h = Math.floor(7.9); //7.0
double i = Math.round(7.5); //8.0
double j = Math.round(7.4); //7.0
//min, max, abs, and random Methods
double k = Math.min(10, 5); //5.0
double l = Math.max(10, 5); //10.0
double m = Math.abs(-10); //10.0
double n = Math.random(); //from 0.0 to 1.0
int o = (int) (Math.random() * 10); //from 1 to 10;

System.out.println("PI= "+a+"\nsin= "+b+"\ncos= "+c+"\ntan= "+
d+"\npow= "+e+"\nsqrt= "+f+"\nceil= "+
g+"\nfloor= "+h+"\nround= "+i+"\nround= "+
j+"\nmin= "+k+"\nmax= "+l+"\nabs= "+
m+"\nrandom= "+n+"\nrandom= "+o);
```

run:  
PI= 3.141592653589793  
sin= 0.0  
cos= 0.8660254037844387  
tan= 1.633123935319537E16  
pow= 8.0  
sqrt= 2.0  
ceil= 8.0  
floor= 7.0  
round= 8.0  
round= 7.0  
min= 5.0  
max= 10.0  
abs= 10.0  
random= 0.2270823610314524  
random= 8  
BUILD SUCCESSFUL (total time: 0 seconds)

❑ Create the following methods to calculate area of (Triangle and Rectangle):

1. `public static void triangleArea (double base , double height)`
2. `public static double recArea(double length , double width)`

❑ What you should have inside each method:

1. **triangleArea method:** calculate triangle area using this formula:

$$\text{triangle} = 0.5 * \text{base} * \text{height}$$

2. **recArea method:** calculate rectangle area using this formula:

$$\text{rectangle} = \text{length} * \text{width}$$

❑ Main

- Make decision by using switch to choose which area will be calculated
- When user chooses one, prompt him to enter base and height for triangle
- When user chooses two, prompt him to enter length and width for rectangle
- When user chooses other numbers, display this message “Wrong Choice”

```

import java.util.Scanner;
public class KHOJ {
    public static void triangleArea(double base, double height){
        double triangle = 0.5 * base * height;
        System.out.println("The area of triangle is " + triangle);
    } //end triangleArea


    public static double recArea(double length, double width){
        double rectangle = length * width;
        return rectangle;
    } //end recArea

    public static void main(String[] args) {
        Scanner input = new Scanner( source: System.in);
        System.out.print( s: "Enter 1 to calculate area of Triangle or 2 to calculate area of rectangle: ");
        int ch = input.nextInt();

        switch(ch){
            case 1:
                System.out.print( s: "Enter base: " );
                double base = input.nextDouble();
                System.out.print( s: "Enter height: " );
                double height = input.nextDouble();
                triangleArea(base, height);
                break;
            case 2:
                System.out.print( s: "Enter length: " );
                double length = input.nextDouble();
                System.out.print( s: "Enter width: " );
                double width = input.nextDouble();
                System.out.println("The area of rectangle is " + recArea(length, width) );
                break;
            default:
                System.out.println( s: "Wrong choice");
        } //end switch
    } //end main
} //end class

```

# Introduction to Java Programming (10<sup>th</sup> Edition)



By  
Y. Daniel Liang