Official Technical Data Sheet (TDS)

Technical Data Sheet: ET-POT-01 Oil Terminator

Concentrated Microbial Bioremediation Formulation for Crude Oil, Fuel Spills & Industrial Sludge

Product Identification & Formulation

ET-POT-01 — Oil Terminator Microbial Bioremediation Agent

Concentrated non-pathogenic bacterial consortium engineered for hydrocarbon remediation.

8	≥5×10⁹	85%	Class 1
Bacterial Strains	**Concentration (CFU/g)**	**TPH Degradation**	**Biosafety Rating**
Synergistic Isolates	High Colonization	Within 30 Days	Non-Pathogenic / Safe

Technical Parameter	Verified Specification	Testing Method	Operational Remarks
Active Microorganisms	8 Synergistic Hydrocarbon-Degrading Strains (Pseudomonas, Bacillus, Rhodococcus)	DNA Isolation & Plate Verification	Natural non-GMO isolates; Class 1 biosafety
Viable Bacterial Count	≥ 5 × 10^9 CFU/g	Standard Plate Count (CFU)	Rapid logarithmic enzymatic colonization
Physical Form & Carrier	Dry granular tan powder / liquid concentrate	Visual & Sieve Analysis	Organic bran/mineral carrier base
Effective Operating pH	5.5 – 9.0 (Optimal Range: 6.8 – 7.5)	Calibrated pH Meter	Add neutral buffer if soil pH < 5.0
Active Temperature	10°C to 45°C (Survives up to 55°C)	Controlled Incubation Trials	Peak metabolic digestion at 25°C–35°C
TPH Reduction Rate	Up to 85% reduction within 30 days	GC-FID / US EPA Method 8015	Proven on crude oil, diesel, bunker fuel & lube
Shelf Life & Storage	24 Months (sealed dry storage < 30°C)	Viability Retention Assay	Keep away from strong oxidizers & chlorine

Field Applications & Dosing Guidelines

Protocol for Soil Remediation, Industrial Tanks & Oily Lagoons

Zero-solvent bioremediation preserving marine and terrestrial ecosystems.

Recommended Field Application & Dosing Schedules

Industrial & Oilfield Approved

- Oil-Contaminated Soil & Land-Farming: Pre-hydrate ET-POT-01 and apply 1 kg per 10 m³ of contaminated soil. Till thoroughly to ensure even contact, keep soil moisture between 35%–50%, and turn weekly for aeration.
- Storage Tank Degreasing & Wastewater Lagoons: Dose 1 kg of concentrate per 5,000 L of oily water under continuous aeration or mechanical circulation.
- Critical Compatibility Warning: Never co-apply simultaneously with free chlorine, sodium hypochlorite, harsh acids, or synthetic biocides that neutralize living microbial biomass.

Official Corporate Desk & Free Consultations

100% Free Consultation

All consultations provided by SAMI BIN AYYAD GROUP are completely free of charge.

Our relevant sector specialists review business inquiries, tenders, OEM/FOB programs, and investment proposals via our centralized consultation portal: **www.sami-trade.com/request-consultation**

- Official Email: info@sami-trade.com · Direct Business Line & WhatsApp: +20 12 222 380 72 / +20 12 222 380 73
- Corporate Registry No.: 209627 · Tax Registration No.: 753702878 · Headquarters: Cairo, Egypt