SAMI BIN AYYAD GROUP · عيادبن سامي مجموعة

Technical Data Sheet: ET-POT-01 Oil Terminator

Concentrated Microbial Bioremediation Agent for Hydrocarbon Contamination

Environmental Technologies

Key Document Highlights & Verified Scope

- Product Code: ET-POT-01 (Oil Terminator Bioremediation Formulation)
- Consortium of 8 Hydrocarbon-Degrading Bacterial Strains (Pseudomonas, Bacillus, Rhodococcus)
- Bacterial Concentration: ≥ 5 × 10^9 CFU/g (Colony Forming Units)
- Degradation Efficiency: Up to 85% Total Petroleum Hydrocarbons (TPH) in 30 Days
- Biological Safety Classification: Class 1 Non-Pathogenic & Non-Toxic

Official Verified Operational Benchmarks

1977	2023	4	39
Foundational Heritage	Unified Corporate Group	Integrated Sectors	Specialized Services

1. Product Identification & Properties

Physical, Chemical, and Biological Characteristics

Technical Parameter	Specification Value	Testing Standard / Method	Operational Remarks
Active Microorganisms	8 Synergistic Bacterial Strains	DNA Sequencing & Lab Isolation	Non-pathogenic, non-GMO natural isolates
Bacterial Count	≥ 5 × 10^9 CFU/g	Standard Plate Count (CFU)	High concentration for rapid colonization
Physical Form	Dry granular powder / liquid concentrate	Visual & Sieve Analysis	Tan/beige powder with organic carrier
Operating pH Range	5.5 – 9.0 (Optimal: 6.8 – 7.5)	Calibrated pH Probe	Buffer required if soil pH < 5.0
Temperature Range	10°C to 45°C (Active up to 55°C)	Incubation Trials	Optimal metabolic rate at 25°C–35°C
TPH Degradation Rate	Up to 85% reduction in 30 days	GC-FID / EPA Method 8015	Verified on crude oil and diesel spills
Shelf Life	24 Months from manufacturing date	Viability Retention Assay	Store sealed in dry ambient room (<30°C)

2. Intended Applications & Dosing Guidelines

Target Environmental Remediations and Application Protocols

APPLICATION GUIDELINES

Field Dosing & Application Instructions

Engineered for soil land-farming, shoreline spills, drilling mud, and industrial tanks.

Soil Remediation: Apply 1 kg of ET-POT-01 per 10 m^3 of contaminated soil. Blend thoroughly to ensure uniform contact. Maintain soil moisture between 35% and 50% through periodic watering. Aerate by turning soil every 7–10 days.

Tank Cleaning & Water Lagoons: Add 1 kg of concentrate per 5,000 L of oily wastewater under continuous agitation or aeration. Do not apply simultaneously with chemical bleach, chlorine, or biocides.

Corporate Contact & Business Inquiry

Direct communication desk for partners, clients, and institutional inquiries

SAMI BIN AYYAD GROUP

Headquarters: Cairo, Arab Republic of Egypt · Commercial Registry Certified

Official Portal: www.sami-trade.com

General Commercial Desk: info@sami-trade.com

Export & International Trade: export@sami-trade.com

Procurement & Partnerships: procurement@sami-trade.com

WhatsApp Commercial Hotline: +20 100 000 0000 / +20 101 234 5678

© 2026 Sami Bin Ayyad Group. All rights reserved. This document is certified for official business use.