

بناء صف يمثل الطالب **student**

فيه رقم الطالب – المعدل – تاريخ الميلاد
تابع طباعة معلومات الطالب او **profile**
ملاحظة: بناء صف يمثل **التاريخ**؟

```
#pragma once
class Cdate
{
private:
    int hour;           int minute;           int second;
public:
    Cdate(int = 0, int = 0, int = 0); //constructor
    void setTime(int, int, int); //set Time
    void setHour(int);
    void setMinute(int);
    void setSecond(int);
    //Get Functions.
    int getHour() const;
    int getMinute() const;
    int getSecond() const;
    void printStandard(); //standard format
    void printUniversal() const;
};
```

```
#include "Cdate.h"
#include <iostream>
using namespace std;

Cdate::Cdate(int a, int b, int c){ setTime(a, b, c);}
void Cdate::setTime(int a, int b, int c)
{
    setHour(a); setMinute(b); setSecond(c);
}
void Cdate::setHour(int a) { hour = a; }
void Cdate::setMinute(int b) { minute = b; }
void Cdate::setSecond(int c) { second = c; }
int Cdate::getHour() const{ return hour;}
int Cdate::getMinute() const{ return minute;}
int Cdate::getSecond() const{ return second;}
void Cdate::printStandard()
{
    cout << ((hour == 0 || hour == 12) ? 12 : hour % 12)
          << ":" << minute << ":" << second
          << (hour < 12 ? " AM" : " PM");
}
void Cdate::printUniversal() const
{
    cout << hour << ":" << minute << ":" << second;
}
```

```
#pragma once
```

```

#include "Cdate.h"
class Employee
{
    int Id; float Avg; Cdate birth;
public:
    Employee(int, float, Cdate);
    void print();
};

```

```

#include "Employee.h"
#include <iostream>
using namespace std;

Employee::Employee(int id, float avg, Cdate bir)
{
    Id = id; Avg = avg; birth = bir;
}

void Employee::print()
{
    cout << "ID " << Id << "\nAverage " << Avg
        << "\nBirthDate ";
    birth.printStandard();
    cout << endl;
    birth.printUniversal();
}

```

```

#include <iostream>
#include "Employee.h"
using namespace std;
void main()
{
    Cdate dd(1, 1, 2000);
    Employee em(1, 3.5, dd);
    em.print();
}

```