

```

#include<iostream>
using namespace std;
void main()
{
    cout << "enter the first Number: ";
    int x; cin >> x;
    cout << "enter the second Number: ";
    int y; cin >> y;
    cout << "enter the third Number: ";
    int z; cin >> z;    int mx;
    if (x > y)
        mx = x;
    else
        mx = y;
    if(mx>z)
        cout << mx << endl;
    else
        cout << z << endl;
}

```

برنامج يحاكي العمليات الحسابية الأربعة في الآلة الحاسبة؟

```

#include<iostream>
using namespace std;
void main()
{
    cout << "enter the first Number: ";
    int x; cin >> x;
    cout << "enter the Operation: ";
    char op; cin >> op;
    cout << "enter the second Number: ";
    int y; cin >> y;
    if (op == '+')
        cout << x << " + " << y << " = " << x + y << endl;
    else if (op == '-')
        cout << x << " - " << y << " = " << x - y << endl;
    else if (op == '*')
        cout << x << " * " << y << " = " << x * y << endl;
    else if (op == '/')
        cout << x << " / " << y << " = " << (float)x / y << endl;
    else
        cout << "try again PLZ..," << endl;
}

```

Another solution

```

#include<iostream>
using namespace std;
void main()

```

```

{
    cout << "enter the first Number: ";
    int x; cin >> x;
    cout << "enter the Operation: ";
    char op; cin >> op;
    cout << "enter the second Number: ";
    int y; cin >> y;
    switch (op)
    {
    case '+':
        cout << x << " + " << y << " = " << x + y << endl; break;
    case '-':
        cout << x << " - " << y << " = " << x - y << endl; break;
    case '*':
        cout << x << " * " << y << " = " << x * y << endl; break;
    case '/':
        cout << x << " / " << y << " = " << (float)x / y << endl; break;
    default:
        cout << "try again PLZ..," << endl;
        break;
    }
}

```

مثال:

برنامج يقوم بطباعة اليوم الموافق لعدد يتم إدخاله محصور بين 1 و 7

```

#include<iostream>
using namespace std;
void main()
{
    cout << "enter the first Number: ";
    int x; cin >> x;
    if (x > 0 && x < 8)
    {
        switch (x)
        {
        case 1: cout << "Sunday" << endl; break;
        case 2: cout << "Monday" << endl; break;
        }
    }
    else
        cout << "the number must between 1 and 7" << endl;
}

```

مثال:

```

#include<iostream>
using namespace std;
void main()

```

```

{
    const int x = 10;
    x = 19; // error ??

    cout << x << endl;
}

```

مثال:

```

#include<iostream>
using namespace std;
void main()
{
    int x = 10;
    int y = 3;

    cout << (float)x/y << endl;
}

```

Ex:

```

int x = 10;
cout << x << endl; //10
cout << x++ << endl; //10
cout << x << endl; //11
cout << ++x << endl; //12

```

cout << x << endl; //12

الاعداد من 1 الى عشرة

```

int i = 1;
while (i<=10)
{
    cout << i << endl;
    i++;
}

```

طباعة بالعكس

```

#include<iostream>
using namespace std;
void main()
{
    int i = 10;
    while (i>0)
    {
        cout << i << endl;
        i--;
    }
}

```

Ex:

```

int i = 10;
while (i>0)
{
    cout << i << endl;
}

```

```
        i-=2;  
    }
```

**Ex:**

```
void main()  
{  
    int i = 1,sum=0;  
    while (i<=10)  
    {  
        sum = sum + i;  
        i++;  
    }  
    cout << sum << endl;  
}
```