Program 6. Create an application to demonstrate the use of Intents to communicate between different activities

Activity main.xml

```
<?xml version="1.0" encoding="utf-8"?>
<androidx.constraintlayout.widget.ConstraintLayout
   app:layout constraintEnd toEndOf="parent"
   app:layout constraintHorizontal bias="0.454"
</androidx.constraintlayout.widget.ConstraintLayout>
```

Activitysec.xml

MainActivity.java

```
package com.example.intents;
import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
import android.view.View;
import android.content.Intent;
import android.widget.Button;

public class MainActivity extends AppCompatActivity {
    Button button;
    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
        button=findViewById(R.id.button);
        //button.setOnClickListener(this);
    }
    public void show(View view) {
        Intent intent = new Intent(Intent.ACTION_VIEW);
        intent.setData(Uri.parse("https://www.fisat.ac.in"));
        startActivity(intent);
    }
    public void callSecondActivity(View view) {
        Intent i = new Intent (getApplicationContext(), MainActivity2.class);
        startActivity(i);
    }
}
```

MainActivity2.java

```
package com.example.intents;
import android.content.Intent;
import android.os.Bundle;
import android.view.View;
import android.widget.Button;
import androidx.appcompat.app.AppCompatActivity;
```

```
public class MainActivity2 extends AppCompatActivity {
   Button button;
   @Override
   protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activitysec);
        Bundle extras = getIntent().getExtras();
        button=findViewById(R.id.button);
   }
   public void callFirstActivity(View view) {
        Intent i=new Intent(getApplicationContext(), MainActivity.class);
        startActivity(i);
   }
}
```

Output:



