

Package ‘hpgltools’

April 28, 2025

Type Package

Title A pile of (hopefully) useful R functions

Version 1.0

Date 2018-03-01

Author Ashton Trey Belew, Keith Hughitt

Maintainer Ashton Trey Belew <abelew@gmail.com>

Description This is a set of functions I have been using in my various analyses in the El-Sayed laboratory. The set of tasks included herein run a spectrum from preprocessing count-tables from RNAseq-like data, through differential expression analyses, to post-processing tasks like gene ontology enrichment. Along the way, these function seek to make plotting analyses consistent, provide multiple entry-points to the various tools, and handle corner cases which are not flexibly handled by the packages this is based upon.

License GPL-2 | file LICENSE

Suggests affy, AnnotationDbi, AnnotationForge, AnnotationHub, ape, BiocGenerics, BiocManager, biomaRt, Biostrings, bluster, broom, BRAIN, BSgenome, caret, Category, cleaver, clusterProfiler, corpcor, corrplot, curl, DALEX, DBI, DESeq2, DESeqReport, desc, DESeq2, devEMF, devtools, digest, directlabels, doParallel, dorothea, doSNOW, dotwhisker, DSS, EBSeq, EDASeq, edgeR, enrichplot, fastcluster, fastICA, ffpe, fission, flashClust, genefilter, GenomicRanges, GenomeInfoDb, genoPlotR, ggdendro, ggrepel, ggsankey, ggstatsplot, ggthemes, goseq, GO.db, GOstats, graph, GSVA, GSVAdata, gtools, gplots, gProfileR, gprofiler2, Heatplus, Hmisc, Homo.sapiens, htmlwidgets, hpgldata, httr, iDA, igraph, IHW, inflection, IRanges, isva, iterators, jsonlite, KEGGREST, KEGGgraph, kmer, lattice, limma, locfit, lubridate, MatrixGenerics, matrixStats, miscTools, motifRG, MSnbase, mygene, mzR, networkD3, NOISeq, numform, openxlsx, OrganismDbi, pandeur, parallel, pasilla, pathfindR, pathview, pcaMethods, Peptides, pheatmap, plyr, preprocessCore, pROC, PROPER, purrr, qvalue, R.utils, RColorBrewer, RCurl, readr, reactome.db, ReactomePA, readODS, readxl,

reshape2, rGADEM, Rgraphviz, rhdf5, Rhdf5lib, rjson, rmarkdown, robust,
 robustbase, Rsamtools, Rtsne,
 rtracklayer, ruv, RUVSeq, rvest,
 scales, Seurat, seqLogo, skimr, SmartSVA, spgs, statmod, stringi,
 stringr, SWATH2stats,
 taxize, testthat, tibble, tidyr, tidymodels, tidyselect, topGO, tximport,
 UniProt.ws, UpSetR, uwot, webp,
 varhandle, variancePartition, Vennerable,
 WGCNA,
 xCell, xml2

Imports Biobase, BiocGenerics, broom,
 data.table, DOSE, dplyr,
 forcats, foreach,
 GenomicFeatures, ggplot2, glue, GSEABase,
 IRanges,
 knitr,
 magrittr, Matrix, methods,
 plotly,
 rlang, RSQLite,
 S4Vectors, shiny, SummarizedExperiment, sva,
 tidyselect,
 varhandle, variancePartition

VignetteBuilder knitr

ByteCompile true

biocViews DifferentialExpression

Encoding UTF-8

RoxygenNote 7.3.2

Collate '01_hpgltools.R'
 'alt_splicing.R'
 'annotation_biomart.R'
 'annotation_genbank.R'
 'annotation_gff.R'
 'annotation_kegg.R'
 'annotation_microbesonline.R'
 'annotation_orfdb.R'
 'annotation_txt.R'
 'annotation_uniprot.R'
 'annotation_shared.R'
 'attributes.R'
 'classify.R'
 'counts.R'
 'de_shared.R'
 'de_basic.R'
 'de_edger.R'
 'de_deseq.R'
 'de_ebseq.R'
 'de_limma.R'
 'de_noiseq.R'
 'de_plots.R'
 'de_xlsx.R'

'de_varpart.R'
'dimension_reduction.R'
'expt.R'
'genes.R'
'gene_sets.R'
'gsva.R'
'helpers_misc.R'
'metadata.R'
'model_testing.R'
'model_varpartition.R'
'motif.R'
'network.R'
'normalize_shared.R'
'normalize_filter.R'
'normalize_convert.R'
'normalize_transform.R'
'normalize_norm.R'
'normalize_batch.R'
'ontology_shared.R'
'ontology_goseq.R'
'ontology_gprofiler.R'
'ontology_gostats.R'
'ontology_topgo.R'
'ontology_clusterprofiler.R'
'ontology_plots.R'
'ontology_xlsx.R'
'ontology_kegg.R'
'pcr.R'
'peptides.R'
'phylo.R'
'plot_shared.R'
'plot_bar.R'
'plot_distribution.R'
'plot_dotplot.R'
'plot_heatmap.R'
'plot_hist.R'
'plot_point.R'
'plot_proteomics.R'
'plot_venn.R'
'plot_circos.R'
'plot_genplot.R'
'plot_misc.R'
'power_estimation.R'
'proteomics.R'
'sanitize.R'
'se.R'
'sequence.R'
'shiny.R'
'singlecell.R'
'tf.R'
'tnseq.R'
'variants.R'

'xlsx.R'

'zzz_subset.R'

Contents

.data	16
[.expt	17
[[,expt,character,ANY-method	17
%:::%	18
add_binary_states	18
add_clonotype_annotations	19
add_conditional_nas	19
adjuster_expt_svs	20
all_adjusters	21
all_cprofiler	22
all_gprofiler	23
all_ontology_searches	24
all_pairwise	25
annotate_network	27
annotate_network_df	28
annotation,expt-method	28
annotation<-,expt,ANY-method	29
assay,ExpressionSet,ANY-method	29
assay,expt,ANY-method	30
assay<-,ExpressionSet,ANY-method	30
assay<-,expt,ANY-method	31
backup_file	31
base_size	32
basic_pairwise	32
batch_counts	33
binary_pairwise	35
bioc_all	35
broom	36
calculate_aucc	36
cbcb_batch	37
cbcb_combat	38
cbcb_filter_counts	39
cheap_tm	40
check_circos	40
check_includes	41
check_metadata_year	41
check_plot_scale	42
check_xlsx_worksheet	43
choose_basic_dataset	43
choose_binom_dataset	44
choose_dataset	44
choose_limma_dataset	45
choose_sequence_regions	46
circos-class	46
circos_arc	47
circos_check_chromosomes	48
circos_heatmap	48

circos_hist	50
circos_ideogram	51
circos_karyotype	52
circos_make	53
circos_plus_minus	53
circos_prefix	55
circos_suffix	57
circos_ticks	57
circos_tile	60
classify_n_times	61
classify_variants	62
clear_session	62
cleavage_histogram	63
cluster_trees	64
colData,ExpressionSet-method	65
colData,expt-method	65
colData<-,ExpressionSet,ANY-method	66
colData<-,expt,ANY-method	66
color_int	67
colors,expt-method	67
colors,SummarizedExperiment-method	67
colors<-,expt-method	68
colors<-,SummarizedExperiment-method	68
combine_de_tables	69
combine_expts	71
combine_extracted_plots	72
combine_mapped_table	73
combine_single_de_table	74
compare_batches	76
compare_de_results	76
compare_de_tables	77
compare_go_searches	78
compare_logfc_plots	79
compare_pc_sv	79
compare_significant_contrasts	80
compare_surrogate_estimates	81
concatenate_runs	82
convert_counts	83
convert_gsc_ids	83
convert_ids	84
cordist	85
correlate_de_tables	86
count_clonotype_by_cluster	87
count_expt_snps	87
count_nmer	88
count_nmer,character-method	89
counts_from_surrogates	89
cp_options	90
create_expt	91
create_partitions	93
create_scd	94
create_se	95

de_venn	96
default_proper	97
deparse_go_value	98
deseq_lrt	99
deseq_pairwise	99
deseq_try_sv	100
deseq2_pairwise	101
disjunct_pvalues	102
dispatch_count_lines	103
dispatch_csv_search	104
dispatch_fasta_lengths	105
dispatch_filename_search	105
dispatch_gc	106
dispatch_metadata_extract	106
dispatch_metadata_ratio	107
dispatch_regex_search	108
dispatch_sum_column	109
divide_seq	110
do_batch	110
do_pairwise	111
do_topgo	112
download_gbk	113
download_microbesonline_files	113
dream_pairwise	114
ebseq_few	116
ebseq_pairwise	116
ebseq_pairwise_subset	118
ebseq_size_factors	119
ebseq_two	120
edger_pairwise	121
enrichResult-class	122
exclude_genes_expt	123
exprs,expt-method	123
exprs,SummarizedExperiment-method	123
exprs<-,ExpressionSet,data.frame-method	124
exprs<-,expt,ANY-method	124
exprs<-,SummarizedExperiment,ANY-method	124
expt	125
extract_abundant_genes	126
extract_coefficient_scatter	127
extract_de_plots	128
extract_eupath_orthologs	130
extract_go	131
extract_interesting_goseq	132
extract_keepers	132
extract_lengths	134
extract_linear_regression	135
extract_logistic_regression	136
extract_mayu_pps_fdr	137
extract_metadata	137
extract_msraw_data	138
extract_mzML_scans	139

extract_mzXML_scans	140
extract_peprophet_data	141
extract_pyprophet_data	142
extract_scan_data	143
extract_siggenes	144
extract_significant_genes	144
factor_rsquared	146
fData,expt-method	146
fData,SummarizedExperiment-method	147
fData<-,expt,ANY-method	147
fData<-,SummarizedExperiment,ANY-method	147
features_greater_than	148
features_in_single_condition	149
features_less_than	150
filter_counts	150
filter_scd	151
find_subseq_target_temp	152
find_working_dataset	153
find_working_mart	153
flanking_sequence	154
gather_cp_genes	155
gather_eupath_utrs_padding	155
gather_genes_organismdb	156
gather_masses	156
gather_ontology_genes	157
gather_preprocessing_metadata	158
gather_utrs_padding	159
gather_utrs_txdb	160
genefilter_cv_counts	161
genefilter_kofa_counts	161
genefilter_pofa_counts	162
generate_expt_colors	163
generate_nn_groups	163
genomic_kmer_dist	164
genoplot_chromosome	165
get_abundant_genes	165
get_degrees	166
get_expt_colors	167
get_formula_factors	167
get_formula_factors,formula-method	168
get_genesizes	168
get_git_commit	169
get_group_gsva_means	169
get_gsvadb_names	170
get_identifier	170
get_individual_snps	171
get_inter_txdb	171
get_kegg_compounds	171
get_kegg_genes	172
get_kegg_orgn	173
get_kegg_sub	173
get_microbesonline_taxid	174

get_msigdb_metadata	175
get_pairwise_gene_abundances	175
get_plot_columns	176
get_proportion_snp_sets	176
get_res	178
get_sig_genes	178
get_sig_gsva_categories	179
get_snp_sets	180
get_yyyymm_commit	181
getEdgeWeights	182
gff2gr	182
gff2irange	183
ggplotly_url	184
ggplt	184
godef	185
golev	186
golevel	187
golevel_df	187
goont	188
gosec	189
goseq_msigdb	189
goseq_table	191
goseq_trees	192
goseq2enrich	192
gostats_kegg	193
gostats_trees	194
gostats2enrich	195
gosyn	195
goterm	196
gotest	197
gprofiler2enrich	197
graph_metrics	198
group_mean_cds_length	200
guess_factors	200
guess_num_surrogates	201
guess_orgdb_keytype	201
heatmap.3	202
hpgl_arescore	205
hpgl_cor	206
hpgl_dist	207
hpgl_filter_counts	207
hpgl_GOplot	208
hpgl_GroupDensity	209
hpgl_log2cpm	209
hpgl_norm	210
hpgl_padjust	211
hpgl_qshrink	212
hpgl_qstats	213
hpgl_rpkm	214
hpgl_voom	214
hpgl_voomweighted	216
hpgltools	217

iDA	218
iDA,matrix-method	218
ihw_adjust	219
import_deseq	220
import_edger	220
impute_expt	221
init_xlsx	221
intersect_signatures	222
intersect_significant	223
iterate_linear_regression	224
iterate_logistic_regression	224
kegg_vector_to_df	225
libsize	226
libsize,SummarizedExperiment-method	226
libsize<-	226
limma_pairwise	227
load_annotations	228
load_biomart_annotations	229
load_biomart_go	231
load_biomart_orthologs	232
load_genbank_annotations	234
load_gff_annotations	235
load_gmt_signatures	236
load_kegg_annotations	236
load_microbesonline_annotations	237
load_microbesonline_go	238
load_orfdb_annotations	239
load_orfdb_go	240
load_trinotate_annotations	241
load_trinotate_go	242
load_uniprot_annotations	243
load_uniprot_go	244
loadme	244
local_get_value	245
make_assembly_spec	245
make_dnaseq_spec	246
make_gsc_from_abundant	246
make_gsc_from_ids	247
make_gsc_from_pairwise	249
make_id2gomap	250
make_kegg_df	250
make_limma_tables	251
make_ntile_factor	252
make_pairwise_contrasts	252
make_pombe_expt	254
make_pombe_se	254
make_quartile_factor	255
make_rnaseq_spec	255
make_simplified_contrast_matrix	256
make_tx_gene_map	256
make_varpart_tables	257
map_keepers	258

map_orgdb_ids	259
map_species_orgdb	259
mean_by_bioreplicate	260
mean_by_factor	260
median_by_factor	261
mesg	261
my_identifyAUBlocks	262
my_isva	262
my_runsims	263
mymakeContrasts	264
myretrieveKGML	264
network_from_matrix	265
noiseq_pairwise	266
normalize	267
normalize,expt-method	267
normalize,SummarizedExperiment-method	267
normalize_counts	268
normalize_expt	269
normalize_se	271
normalize_todo	272
notes,expt-method	273
orgdb_from_ah	273
overlap_geneids	274
overlap_groups	274
parse_msgdb	275
parse_msgdb_sqlite	275
parse_msgdb_xml	275
pattern_count_genome	276
pc_fstatistics	277
pca_highscores	277
pca_information	278
pct_all_kegg	279
pct_kegg_diff	280
pData,expt-method	281
pData,SummarizedExperiment-method	281
pData<-,expt,ANY-method	282
pData<-,SummarizedExperiment,ANY-method	282
plot_3d_pca	283
plot_batchsv	283
plot_bcv	284
plot_boxplot	285
plot_cleaved	286
plot_corheat	286
plot_de_pvals	287
plot_density	288
plot_disheat	289
plot_dist_scatter	290
plot_enrichresult	291
plot_epitrochoid	292
plot_essentiality	292
plot_exprs_by_chromosome	293
plot_forest_from_regression	294

plot_fun_venn	294
plot_goseq_pval	295
plot_gostats_pval	296
plot_gprofiler_pval	297
plot_gprofiler2_pval	297
plot_heatmap	298
plot_heatmap,data.frame-method	299
plot_heatmap,ExpressionSet-method	300
plot_heatmap,expt-method	300
plot_heatmap,SummarizedExperiment-method	301
plot_heatplus	301
plot_histogram	302
plot_hypotrochoid	303
plot_intensity_mz	304
plot_legend	305
plot_libsize	305
plot_libsize,data.frame,factor,character-method	306
plot_libsize,ExpressionSet,ANY,ANY-method	307
plot_libsize,expt,ANY,ANY-method	307
plot_libsize,SummarizedExperiment,ANY,ANY-method	308
plot_libsize_prepost	309
plot_linear_scatter	309
plot_ly	311
plot_ma_condition_de	311
plot_ma_de	313
plot_meta_sankey	314
plot_meta_sankey,expt-method	315
plot_metadata_factors	315
plot_multihistogram	316
plot_multiplot	317
plot_mzxml_boxplot	317
plot_nonzero	318
plot_nonzero,ExpressionSet-method	319
plot_nonzero,expt-method	320
plot_nonzero,SummarizedExperiment-method	320
plot_num_siggenes	321
plot_ontpval	322
plot_pairwise_ma	323
plot_pca	323
plot_pca_genes	325
plot_pcfactor	326
plot_pclload	327
plot_pcs	328
plot_pct_kept	329
plot_peprophet_data	330
plot_pyprophet_counts	331
plot_pyprophet_distribution	332
plot_pyprophet_points	333
plot_pyprophet_protein	334
plot_pyprophet_xy	335
plot_qq_all	336
plot_rmats	336

plot_rpm	337
plot_sample_bars	338
plot_sample_cvheatmap	339
plot_sample_heatmap	340
plot_sample_heatmap,ExpressionSet-method	341
plot_sample_heatmap,expt-method	341
plot_sample_heatmap,SummarizedExperiment-method	342
plot_sankey_de	343
plot_scatter	343
plot_seurat_scatter	344
plot_significant_bar	345
plot_single_qq	345
plot_sm	346
plot_sm,data.frame-method	347
plot_sm,ExpressionSet-method	348
plot_sm,expt-method	348
plot_sm,SummarizedExperiment-method	349
plot_spirograph	349
plot_suppa	350
plot_svfactor	351
plot_topgo_densities	352
plot_topgo_pval	352
plot_topn	353
plot_topn_gsea	354
plot_topn_gsea,all_cprofiler-method	354
plot_topn_gsea,clusterprofiler_result-method	354
plot_tsne	355
plot_variance_coefficients	355
plot_variance_coefficients,ExpressionSet-method	356
plot_variance_coefficients,expt-method	356
plot_variance_coefficients,SummarizedExperiment-method	357
plot_volcano_condition_de	357
plot_volcano_de	358
plotly_pca	360
pp	361
primer_qc	362
print.abundant_genes	363
print.all_gprofiler	363
print.all_pairwise	364
print.annotations_biomart	364
print.aucc_info	365
print.biomart_go	365
print.cds_variant_primers	366
print.classified_mutations	366
print.classifier_evaluation	367
print.clusterprofiler_result	367
print.combined_de	368
print.combined_de_upset	368
print.combined_table	369
print.correlation_heatmap	369
print.cross_table_comparison	370
print.density_plot	370

print.density_primers	371
print.deseq_lrt	371
print.distance_heatmap	372
print.dream_pairwise	372
print.expt	373
print.goseq_result	373
print.gostats_result	374
print.gprofiler_result	374
print.graphed_metrics	375
print.gsva_result	375
print.gsva_sig	376
print.legend_plot	376
print.libsize_plot	376
print.linear_scatter	377
print.mapped_keepers	377
print.meta_sankey	377
print.nonzero_plot	378
print.partitioned_data	378
print.pattern_counted	379
print.pca_result	379
print.prepost_filter	380
print.preprocessing_metadata	380
print.proper_estimate	381
print.reordered_varpart	381
print.sig_genes	382
print.sig_intersect	382
print.snp_intersections	383
print.snp_sets	383
print.snps_genes	384
print.standardmedian_plot	384
print.topgo_result	385
print.topn_plot	385
print.varcoef_plot	385
print.varpart	386
print.written_expt	386
print.written_xlsx	386
print_ups_downs	387
proportions_by_factors	387
prune_network	388
pull_git_commit	388
random_ontology	389
rank_order_scatter	389
rbind_summary_rows	390
read_counts	391
read_metadata	392
read_snp_columns	393
read_thermo_xlsx	394
recolor_points	394
record_seurat_samples	395
renderme	396
replot_varpart_percent	396
rex	397

rowData,ExpressionSet-method	397
rowData,expt-method	397
rowData<-,expt-method	398
rowmax_filter_counts	398
rowMeans	398
s2s_all_filters	399
sampleNames,expt-method	400
sampleNames,SummarizedExperiment-method	400
sampleNames<-,expt,ANY-method	401
sampleNames<-,SummarizedExperiment,character-method	401
sanitize_expt	401
sanitize_expt_fData	402
sanitize_expt_pData	402
sanitize_metadata	403
sanitize_model	404
sanitize_number_encoding	405
sanitize_percent	405
saveme	406
score_gsva_likelihooods	407
score_mhess	408
self_evaluate_model	408
semantic_copynumber_extract	409
semantic_copynumber_filter	409
semantic_expt_filter	410
sequence_attributes	411
sequential_variants	412
set_expt_batches	412
set_expt_colors	413
set_expt_conditions	414
set_expt_factors	415
set_expt_genename_column	416
set_expt_genenames	416
set_expt_samplenames	417
shiny	417
sig_ontologies	418
significant_barplots	418
sillydist	420
simple_clusterprofiler	421
simple_cp_enricher	423
simple_cprofiler	423
simple_dorothea	424
simple_filter_counts	425
simple_gadem	425
simple_goseq	426
simple_gostats	428
simple_gprofiler	429
simple_gprofiler2	429
simple_gsva	431
simple_motifRG	433
simple_pathview	433
simple_proper	435
simple_topgo	436

simple_topgo,character-method	437
simple_varpart	438
simple_xcell	439
single_topgo_tree	440
skim_seurat_metadata	440
slide_de_threshold	441
sm	442
snp_by_chr	442
snp_cds_primers	443
snp_density_primers	444
snp_subset_genes	445
snpsnames2gr	446
snps_intersections	447
snps_vs_genes	448
snps_vs_genes_padded	449
state	450
state,expt-method	450
state,SummarizedExperiment-method	451
state<-	451
state<-,expt-method	451
state<-,SummarizedExperiment-method	452
steal_salmon_tx_ids	452
subset_expt	453
subset_expt,SummarizedExperiment-method	454
subset_genes	454
subset_ontology_search	455
subtract_expt	456
sum_eupath_exon_counts	457
sum_exon_widths	457
summarize_scd_clusters	458
summarize_ups_downs	459
sv_fstatistics	459
sva_modify_pvalues	460
svpc_fstats	461
synchronize_expt	461
table_style	461
tar_meta_column	462
tar_meta_column,character-method	462
tempfile	463
test_design_model_rank	463
test_design_model_rank,expt-method	464
test_model_rank	464
tmpmd5file	465
tnseq_multi_saturation	465
tnseq_saturation	466
topDiffGenes	467
topgo_tables	467
topgo_trees	468
topgo2enrich	469
transform_counts	470
u_plot	471
unAsIs	471

update.RNAseq.SimOptions.2grp	471
upsetr_combined_de	472
upsetr_sig	472
variance_expt	473
varpart_summaries	474
verbose	474
wgcna_network	475
what_happened	475
write_basic	476
write_cds_entries	477
write_classifier_summary	477
write_combined_legend	478
write_combined_summary	479
write_cp_data	479
write_de_table	480
write_density_primers	481
write_deseq	482
write_edger	483
write_expt	483
write_go_xls	485
write_goseq_data	486
write_gostats_data	487
write_gprofiler_data	488
write_gsva	489
write_limma	489
write_sample_design	490
write_sig_legend	490
write_snps	490
write_subset_ontologies	491
write_suppa_table	492
write_snpc_fstats	493
write_topgo_data	493
write_xlsx	494
write_xlsx,ANY,ANY,ANY,written_xlsx-method	495
xlsx_insert_png	496
xref_regions	497
ymxb_print	498

Index**499**

*.data**Taken from Nathan Eastwood to help using mutate and friends.*

Description

It is fairly common for me to get annoyed with R CMD check due to NSE, thus the previous declarations and the rando NULL assignments in this package. <https://nathaneastwood.github.io/2019/08/18/no-visible-binding-for-global-variable/>

[.expt	<i>Subset an expt</i>
--------	-----------------------

Description

Working on improving my understanding of how R sets up functions by type.

Usage

```
## S3 method for class 'expt'
expt[i, j, ...]
```

Arguments

expt	expt to subset
i	Set of genes to keep
j	Set of samples to keep.
...	Parameters to pass to subset_genes/subset_expt.

[[,expt,character,ANY-method	<i>Simplifying subset on metadata.</i>
------------------------------	--

Description

Simplifying subset on metadata.

Usage

```
## S4 method for signature 'expt,character,ANY'
x[[i, j, ...]]
```

Arguments

x	an expt
i	Column to extract

```
%:::%
```

```
R CMD check is super annoying about :::.
```

Description

In a fit of pique, I did a google search to see if anyone else has been annoyed in the same way as was I. Yihui Xie was, and in his email to r-devel in 2013 he proposed a game of hide-and-seek; which I am repeating here.

Usage

```
pkg %:::% fun
```

Arguments

pkg	on the left hand side
fun	on the right hand side

Details

This just implements ::: as an infix operator that will not trip check.

```
add_binary_states
```

```
Add binary state information to the scd.
```

Description

I am adding these only so that it is easier to visualize the cells compared when performing FindAllMarkers(); e.g. it compares each identity to all others; so I imagine it would be nice to see a dimplot or something of each state vs. all others as a binary pair rather than as n separate groups.

Usage

```
add_binary_states(scd, column = NULL)
```

Arguments

scd	Seurat single cell dataset.
column	Get identities from this metadata column.

Value

The scd with some new identities set with predicates.

```
add_clonotype_annotations
```

Add VDJ information using some code I found.

Description

The original implementation of this idea resides at: https://ucdavis-bioinformatics-training.github.io/2020-Advanced_Single_Cell_RNA_Seq/data_analysis/VDJ_Analysis_fixed

Usage

```
add_clonotype_annotations(scd, start_path, type = "t")
```

Arguments

scd	Seurat object to which we will add some information.
start_path	root of the 10x data in which the vdj information should reside.
type	The type of VDJ we expect, heavy(B) or light(T).

Details

The seurat documentation always uses 'obj' for their datastructures; I chose to use 'scd' to signify that I am explicitly adding a couple pieces of information to them. They remain the datastructures returned by seurat.

Value

The Seurat object with some new information.

```
add_conditional_nas
```

Replace 0 with NA if not all entries for a given condition are 0.

Description

This will hopefully handle a troubling corner case in Volker's data: He primarily wants to find proteins which are found in one condition, but `_not_` in another. However, due to the unknown unknown problem in DIA acquisition, answering this question is difficult. If one uses a normal expressionset or msnset or whatever, one of two things will happen: either the 0/NA proteins will be entirely removed/ignored, or they will lead to spurious 'significant' calls. MSstats, to its credit, does a lot to try to handle these cases; but in the case Volker is most interested, it will exclude the interesting proteins entirely.

Usage

```
add_conditional_nas(expt, fact = "condition", method = "NA")
```

Arguments

expt	Expressionset to examine.
fact	Experimental design factor to use.
method	Specify whether to leave the NAs as NA, or replace them with the mean of all non-NA values.

Details

So, here is what I am going to do: Iterate through each element of the chosen experimental design factor, check if all samples for that condition are 0, if so; leave them. If not all the samples have 0 for the given condition, then replace the zero entries with NA. This should allow for stuff like `rowMeans(na.rm = TRUE)` to provide useful information.

Finally, this will add columns to the annotations which tell the number of observations for each protein after doing this.

Value

New expressionset with some, but not all, 0s replaced with NA.

adjuster_expt_svs	<i>Search for SVs in an expressionset-like object.</i>
-------------------	--

Description

Search for SVs in an expressionset-like object.

Usage

```
adjuster_expt_svs(
  input,
  model_fstring = "~ 0 + condition",
  null_fstring = NULL,
  model_svs = "sva",
  batch1 = "batch",
  batch2 = NULL,
  num_surrogates = "be",
  low_to_zero = FALSE,
  cpus = NULL,
  na_to_zero = TRUE,
  confounders = NULL,
  filter = "raw",
  thresh = 1,
  noscale = FALSE,
  prior_plots = FALSE,
  control_type = "norm"
)
```

all_adjusters	<i>Combine all surrogate estimators and batch correctors into one function.</i>
---------------	---

Description

For a long time, I have mostly kept my surrogate estimators and batch correctors separate. However, that separation was not complete, and it really did not make sense. This function brings them together. This now contains all the logic from the freshly deprecated `get_model_adjust()`.

Usage

```
all_adjusters(
  input,
  design = NULL,
  estimate_type = "sva",
  batch1 = "batch",
  batch2 = NULL,
  surrogates = "be",
  low_to_zero = FALSE,
  cpus = 4,
  na_to_zero = TRUE,
  expt_state = NULL,
  confounders = NULL,
  chosen_surrogates = NULL,
  adjust_method = "ruv",
  filter = "raw",
  thresh = 1,
  noscale = FALSE,
  prior_plots = FALSE
)
```

Arguments

input	Dataframe or expt or whatever as the data to analyze/modify.
design	If the data is not an expt, then put the design here.
estimate_type	Name of the estimator.
batch1	Column in the experimental design for the first known batch.
batch2	Only used by the limma method, a second batch column.
surrogates	Either a number of surrogates or a method to search for them.
low_to_zero	Move elements which are <0 to 0?
cpus	Use parallel and split intensive operations?
na_to_zero	Set any NA entries to 0?
expt_state	If this is not an expt, provide the state of the data here.
confounders	List of confounded factors for smartSVA/iSVA.
chosen_surrogates	Somewhat redundant with surrogates above, but provides a second place to enter because of the way I use ... in <code>normalize_expt()</code> .

adjust_method	Choose the method for applying the estimates to the data.
filter	Filter the data?
thresh	If filtering, use this threshold.
noscale	If using combat, scale the data?
prior_plots	Plot the priors?

Details

This applies the methodologies very nicely explained by Jeff Leek at <https://github.com/jtleek/svaseq/blob/master/recount> and attempts to use them to acquire estimates which may be applied to an experimental model by either EdgeR, DESeq2, or limma. In addition, it modifies the count tables using these estimates so that one may play with the modified counts and view the changes (with PCA or heatmaps or whatever). Finally, it prints a couple of the plots shown by Leek in his document. In other words, this is entirely derivative of someone much smarter than me.

Value

List containing surrogate estimates, new counts, the models, and some plots, as available.

See Also

[all_adjuster()] [isva] [sva] [limma::removeBatchEffect()] [corpcor] [edgeR] [RUVSeq] [SmartSVA] [variancePartition] [counts_from_surrogates()]

all_cprofiler	<i>Run simple_clusterprofiler on every table from extract_significant_genes()</i>
---------------	---

Description

Run simple_clusterprofiler on every table from extract_significant_genes()

Usage

```
all_cprofiler(
  sig,
  tables,
  according_to = "deseq",
  together = FALSE,
  orgdb = "org.Hs.eg.db",
  orgdb_from = NULL,
  orgdb_to = "ENTREZID",
  go_level = 3,
  pcutoff = 0.05,
  qcutoff = 0.2,
  fc_column = "logFC",
  second_fc_column = "deseq_logfc",
  internal = FALSE,
  updown = "up",
  permutations = 1000,
```

```

    min_groupsize = 5,
    kegg_prefix = NULL,
    kegg_organism = NULL,
    do_gsea = TRUE,
    categories = 12,
    do_david = FALSE,
    do_kegg = TRUE,
    padj_type = "BH",
    plot_type = "all",
    do_reactome = TRUE,
    excel = "excel/all_cp.xlsx",
    ...
)

```

Arguments

sig	Result from extract_significant_genes
tables	Result from combine_de_tables
according_to	Use this result type for the clusterprofiler searches.
together	Concatenate the up/down genes into one set?
plot_type	Choose a plot method as the default.
...	Arguments to pass to simple_clusterprofiler().

all_gprofiler	<i>Run simple_gprofiler on every table from extract_significant_genes()</i>
---------------	---

Description

Run simple_gprofiler on every table from extract_significant_genes()

Usage

```

all_gprofiler(
  sig,
  according_to = "deseq",
  together = FALSE,
  sleep = 7,
  plot_type = "dotplot",
  excel = "excel/all_gp.xlsx",
  ...
)

```

Arguments

sig	Result from extract_significant_genes
according_to	Use this result type for the gprofiler searches.
together	Concatenate the up/down genes into one set?
sleep	Give the gProfiler servers a break between queries.
plot_type	Choose a plot method as the default.
...	Arguments to pass to simple_gprofiler().

all_ontology_searches *Perform ontology searches given the results of a differential expression analysis.*

Description

This takes a set of differential expression results, extracts a subset of up/down expressed genes; passes them to goseq, clusterProfiler, topGO, GOSTats, and gProfiler; collects the outputs; and returns them in a (hopefully) consistent fashion. It attempts to handle the differing required annotation/GOid inputs required for each tool and/or provide supported species in ways which the various tools expect.

Usage

```
all_ontology_searches(
  de_out,
  gene_lengths = NULL,
  goids = NULL,
  n = NULL,
  z = NULL,
  lfc = NULL,
  p = NULL,
  overwrite = FALSE,
  species = "unsupported",
  orgdb = "org.Dm.eg.db",
  goid_map = "reference/go/id2go.map",
  gff_file = NULL,
  gff_type = "gene",
  do_goseq = TRUE,
  do_cluster = TRUE,
  do_topgo = TRUE,
  do_gostats = TRUE,
  do_gprofiler = TRUE,
  do_trees = FALSE,
  ...
)
```

Arguments

de_out	List of topTables comprising limma/deseq/edger outputs.
gene_lengths	Data frame of gene lengths for goseq.
goids	Data frame of goids and genes.
n	Number of genes at the top/bottom of the fold-changes to define 'significant.'
z	Number of standard deviations from the mean fold-change used to define 'significant.'
lfc	Log fold-change used to define 'significant'.
p	Maximum pvalue to define 'significant.'
overwrite	Overwrite existing excel results file?
species	Supported organism used by the tools.

orgdb	Provide an organismDbi/Orgdb to hold the various annotation data, in response to the shift of clusterprofiler and friends towards using them.
goid_map	Mapping file used by topGO, if it does not exist then goids_df creates it.
gff_file	gff file containing the annotations used by gff2genetable from clusterprofiler.
gff_type	Column to use from the gff file for the universe of genes.
do_goseq	Perform simple_goseq()?
do_cluster	Perform simple_clusterprofiler()?
do_topgo	Perform simple_topgo()?
do_gostats	Perform simple_gostats()?
do_gprofiler	Perform simple_gprofiler()?
do_trees	make topGO trees from the data?
...	Arguments to pass through in arglist.

Value

a list of up/down ontology results from goseq/clusterprofiler/topgo/gostats, and associated trees.

See Also

[goseq] [clusterProfiler] [topGO] [goStats] [gProfiler] [GO.db]

Examples

```
## Not run:
many_comparisons = limma_pairwise(expt = an_expt)
tables = many_comparisons$limma
this_takes_forever = limma_ontology(tables, gene_lengths = lengthdb,
                                   goids = goids_df, z = 1.5, gff_file='length_db.gff')

## End(Not run)
```

all_pairwise	<i>Perform limma, DESeq2, EdgeR pairwise analyses.</i>
--------------	--

Description

This takes an expt object, collects the set of all possible pairwise comparisons, sets up experimental models appropriate for the differential expression analyses, and performs them.

Usage

```
all_pairwise(
  input = NULL,
  model_fstring = "~ 0 + condition + batch",
  null_fstring = "~",
  model_svs = NULL,
  modify_p = FALSE,
  filter = NULL,
  extra_contrasts = NULL,
```

```

    libsize = NULL,
    test_pca = TRUE,
    annot_df = NULL,
    do_basic = TRUE,
    do_deseq = TRUE,
    do_ebseq = TRUE,
    do_edger = TRUE,
    do_limma = TRUE,
    do_noiseq = TRUE,
    do_dream = TRUE,
    keepers = NULL,
    convert = "cpm",
    norm = "quant",
    verbose = TRUE,
    num_surrogates = "be",
    methods = NULL,
    keep_underscore = TRUE,
    dream_model = NULL,
    ...
)

```

Arguments

input	Dataframe/vector or expt class containing count tables, normalization state, etc.
modify_p	Depending on how it is used, sva may require a modification of the p-values.
filter	Added because I am tired of needing to filter the data before invoking all_pairwise().
extra_contrasts	Optional extra contrasts beyone the pairwise comparisons. This can be pretty neat, lets say one has conditions A,B,C,D,E and wants to do (C/B)/A and (E/D)/A or (E/D)/(C/B) then use this with a string like: "c_vs_b_ctrla = (C-B)-A, e_vs_d_ctrla = (E-D)-A, de_vs_cb = (E-D)-(C-B)".
libsize	Library size of the original data to help voom().
test_pca	Perform some tests of the data before/after applying a given batch effect.
annot_df	Annotations to add to the result tables.
do_basic	Perform a basic analysis?
do_deseq	Perform DESeq2 pairwise?
do_ebseq	Perform EBSeq (caveat, this is NULL as opposed to TRUE/FALSE so it can choose).
do_edger	Perform EdgeR?
do_limma	Perform limma?
do_noiseq	Perform noiseq?
do_dream	Perform dream?
keepers	Limit the pairwise search to a set of specific contrasts.
convert	Modify the data with a 'conversion' method for PCA?
norm	Modify the data with a 'normalization' method for PCA?
verbose	Print extra information while running?
...	Picks up extra arguments into arglist.
surrogates	Either a number of surrogates or method to estimate it.

Details

This runs `limma_pairwise()`, `deseq_pairwise()`, `edger_pairwise()`, `basic_pairwise()` each in turn. It collects the results and does some simple comparisons among them.

Value

A list of limma, deseq, edger results.

See Also

`[limma_pairwise()]` `[edger_pairwise()]` `[deseq_pairwise()]` `[ebseq_pairwise()]` `[basic_pairwise()]`

Examples

```
## Not run:
lotsodata <- all_pairwise(input = expt, model_batch = "svaseq")
summary(lotsodata)
## limma, edger, deseq, basic results; plots; and summaries.

## End(Not run)
```

annotate_network	<i>Use grep to add a vector of annotations/colors to a network.</i>
------------------	---

Description

The igraph syntaxes are a little clunky, but the `set_attr()` functions mostly make sense.

Usage

```
annotate_network(
  network,
  names,
  color = NULL,
  default = NULL,
  annot_name = "type",
  annot_value = "high"
)
```

Arguments

network	Input network
names	set of node-names to which to add annotations.
color	Color to attach to the added annotation.
default	Set a default annotation for this name to all nodes.
annot_name	Annotation name to attach to the nodes.
annot_value	and the associated value.

Value

a new network!

annotate_network_df	<i>A version of annotate_network, but which uses a dataframe as input.</i>
---------------------	--

Description

The `annotate_network()` function uses a vector of values, this extends that logic to add every column of a dataframe. I would like to make this function a little more fun via a vis abilities to add colors and such.

Usage

```
annotate_network_df(network, df, default = NULL)
```

Arguments

<code>network</code>	input network.
<code>df</code>	input dataframe, columns are the new metadata, rows are the node-strings to search on.
<code>default</code>	Set a default?

annotation,expt-method	<i>A getter for the annotation databased used to create an expt/se.</i>
------------------------	---

Description

A getter for the annotation databased used to create an expt/se.

Usage

```
## S4 method for signature 'expt'
annotation(object)
```

Arguments

<code>object</code>	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
---------------------	---

```
annotation<-,expt,ANY-method
```

A setter for the annotation database used to create an expt/se.

Description

A setter for the annotation database used to create an expt/se.

Usage

```
## S4 replacement method for signature 'expt,ANY'
annotation(object) <- value
```

Arguments

object	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
value	New annotation slot for the expt/se.

```
assay,ExpressionSet,ANY-method
```

A getter to pull the assay data from an ExpressionSet.

Description

A getter to pull the assay data from an ExpressionSet.

Usage

```
## S4 method for signature 'ExpressionSet,ANY'
assay(x, i, withDimnames = TRUE, ...)
```

Arguments

x	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
withDimnames	I do not know.
...	Extra args!

assay,expt,ANY-method *A getter to pull the assay data from an expt.*

Description

A getter to pull the assay data from an expt.

Usage

```
## S4 method for signature 'expt,ANY'
assay(x, i, withDimnames = TRUE, ...)
```

Arguments

x	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
---	---

assay<-,ExpressionSet,ANY-method
A setter to put the assay data into an ExpressionSet.

Description

A setter to put the assay data into an ExpressionSet.

Usage

```
## S4 replacement method for signature 'ExpressionSet,ANY'
assay(x, i, withDimnames = TRUE, ...) <- value
```

Arguments

x	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
i	Subset to replace.
withDimnames	I do not know, I need to look this up.
...	Extra args.
value	New values for the expressionset.

```
assay<-, expt, ANY-method
```

A setter to put the assay data into an expt.

Description

A setter to put the assay data into an expt.

Usage

```
## S4 replacement method for signature 'expt,ANY'
assay(x, i, withDimnames = TRUE, ...) <- value
```

Arguments

x	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
i	specific samples to replace the data.
withDimnames	I do not know.
...	Extra args, currently unused.
value	New assay values to fill in the data structure.

```
backup_file
```

Make a backup of an existing file with n revisions, like VMS!

Description

Sometimes I just want to kick myself for overwriting important files and then I remember using VMS and wish modern computers were a little more like it.

Usage

```
backup_file(backup_file, backups = 4)
```

Arguments

backup_file	Filename to backup.
backups	How many revisions?

base_size	<i>The following sets the ggplot2 default text size.</i>
-----------	--

Description

The following sets the ggplot2 default text size.

Usage

```
base_size
```

Format

An object of class numeric of length 1.

basic_pairwise	<i>The simplest possible differential expression method.</i>
----------------	--

Description

Perform a pairwise comparison among conditions which takes nothing into account. It `_only_` takes the conditions, a mean value/variance among them, divides by condition, and returns the result. No fancy normalizations, no statistical models, no nothing. It should be the very worst method possible. But, it should also provide a baseline to compare the other tools against, they should all do better than this, always.

Usage

```
basic_pairwise(
  input = NULL,
  model_fstring = "~ 0 + condition + batch",
  null_fstring = "~",
  model_svs = NULL,
  annot_df = NULL,
  keepers = NULL,
  fx = "mean",
  keep_underscore = TRUE,
  ...
)
```

Arguments

input	Count table by sample.
keepers	Set of specific contrasts to perform instead of all.
fx	What function to use for mean/median?
...	Extra options passed to arglist.
design	Data frame of samples and conditions.
conditions	Not currently used, but passed from <code>all_pairwise()</code>

batches	Not currently used, but passed from all_pairwise()
model_cond	Not currently used, but passed from all_pairwise()
model_intercept	Not currently used, but passed from all_pairwise()
alt_model	Not currently used, but passed from all_pairwise()
model_batch	Not currently used, but passed from all_pairwise()
force	Force as input non-normalized data?

Details

Tested in test_27de_basic.R This function was written after the corresponding functions in de_deseq.R, de_edger.R, and de_limma.R. Like those, it performs the full set of pairwise comparisons and returns a list of the results. As mentioned above, unlike those, it is purposefully stupid.

Value

Df of pseudo-logFC, p-values, numerators, and denominators.

See Also

[deseq_pairwise()] [limma_pairwise()] [edger_pairwise()] [ebseq_pairwise()]

Examples

```
## Not run:
expt <- create_expt(metadata = "sample_sheet.xlsx", gene_info = "annotations")
basic_de <- basic_pairwise(expt)
basic_tables <- combine_de_tables(basic_de)

## End(Not run)
```

batch_counts	<i>Perform different batch corrections using limma, sva, ruvq, and cbc-SEQ.</i>
--------------	---

Description

I found this note which is the clearest explanation of what happens with batch effect data: <https://support.bioconductor.org>. Just to be clear, there's an important difference between removing a batch effect and modelling a batch effect. Including the batch in your design formula will model the batch effect in the regression step, which means that the raw data are not modified (so the batch effect is not removed), but instead the regression will estimate the size of the batch effect and subtract it out when performing all other tests. In addition, the model's residual degrees of freedom will be reduced appropriately to reflect the fact that some degrees of freedom were "spent" modelling the batch effects. This is the preferred approach for any method that is capable of using it (this includes DESeq2). You would only remove the batch effect (e.g. using limma's removeBatchEffect function) if you were going to do some kind of downstream analysis that can't model the batch effects, such as training a classifier. I don't have experience with ComBat, but I would expect that you run it on log-transformed CPM values, while DESeq2 expects raw counts as input. I couldn't tell you how to properly use the two methods together.

Usage

```
batch_counts(
  count_table,
  method = TRUE,
  design = NULL,
  batch1 = "batch",
  current_state = NULL,
  current_design = NULL,
  expt_state = NULL,
  surrogate_method = NULL,
  surrogates = NULL,
  low_to_zero = FALSE,
  cpus = 4,
  batch2 = NULL,
  noscale = TRUE,
  adjust_method = "ruv"
)
```

Arguments

count_table	Matrix of (pseudo)counts.
method	Choose the method for batch/surrogate estimation.
batch1	String describing the method to try to remove the batch effect (or FALSE to leave it alone, TRUE uses limma).
current_state	Current state of the expt in an attempt to avoid double-normalization.
current_design	Redundant with expt_design above, but provides another place for normalize_expt() to send data.
expt_state	Current state of the data
surrogate_method	Also redundant for normalize_expt()
surrogates	Number of surrogates or method to estimate them.
low_to_zero	Send <0 entries to 0 to avoid shenanigans.
cpus	Parallelize intensive operations.
batch2	Column in the design table describing the second covariant to remove (only used by limma at the moment).
noscale	Used for combatmod, when true it removes the scaling parameter from the invocation of the modified combat.
expt_design	Model matrix defining the experimental conditions/batches/etc.
...	More options for you!

Value

The 'batch corrected' count table and new library size. Please remember that the library size which comes out of this may not be what you want for voom/limma and would therefore lead to spurious differential expression values.

See Also

[limma] [edgeR] [RUVSeq] [sva]

Examples

```
## Not run:
limma_batch <- batch_counts(table, design, batch1='batch', batch2='strain')
sva_batch <- batch_counts(table, design, batch='sva')

## End(Not run)
```

binary_pairwise	<i>Perform all_pairwise only using deseq/edger.</i>
-----------------	---

Description

The thing I want to do which I presume will be of use to Zhezhen is to have a variant of this which takes the list of interesting contrasts and only performs them rather than my default of doing all possible pairwise contrasts. I think that will only require a little logic in make_contrasts to skip contrasts not in the list of interest.

Usage

```
binary_pairwise(...)
```

Arguments

```
...           Args usually passed to all_pairwise()
```

bioc_all	<i>Grab a copy of all bioconductor packages and install them by type</i>
----------	--

Description

This uses jsonlite to get a copy of all bioconductor packages by name and then iterates through them with BiocManager to install all of them. It performs a sleep between each installation in an attempt to avoid being obnoxious. As a result, it will of a necessity take forever.

Usage

```
bioc_all(
  release = NULL,
  mirror = "bioconductor.statistik.tu-dortmund.de",
  base = "packages",
  type = "software",
  suppress_updates = TRUE,
  suppress_auto = TRUE,
  force = FALSE
)
```

Arguments

release	Bioconductor release to use, should probably be adjusted to automatically find it.
mirror	Bioconductor mirror to use.
base	Base directory on the mirror to download from.
type	Type in the tree to use (software or annotation)
suppress_updates	For BiocLite(), don't update?
suppress_auto	For BiocLite(), don't update?
force	Install if already installed?

Value

a number of packages installed

See Also

[BiocManager] [jsonlite]

Examples

```
## Not run:
go_get_some_coffee_this_will_take_a_while <- bioc_all()

## End(Not run)
```

broom	<i>broom provides accessors to models</i>
-------	---

Description

I am spending a lot more time messing with models from various tools, as a result broom turns out to be quite handy.

calculate_aucc	<i>Calculate the Area under the Concordance Curve.</i>
----------------	--

Description

This is taken verbatim from a recent paper sent to me by Julie Cridland. 10.1038/s41467-021-25960-2

Usage

```
calculate_aucc(
  tbl,
  tbl2 = NULL,
  px = "deseq_adj",
  py = "edger_adj",
  lx = "deseq_logfc",
  ly = "edger_logfc",
  cor_method = "pearson",
  topn = 0.1
)
```

Arguments

tbl	DE table
tbl2	Second table
px	first set of p-values column
py	second set
lx	first set of logFCs column
ly	second set
cor_method	Method to pass to cor().
topn	Number of genes to consider (or percentage of the whole).

cbcb_batch	<i>A function suggested by Hector Corrada Bravo and Kwame Okrah for batch removal.</i>
------------	--

Description

During a lab meeting, the following function was suggested as a quick and dirty batch removal tool. It takes data and a model including a 'batch' factor, invokes limma on them, removes the batch factor, does a cross product of the fitted data and modified model and uses that with residuals to get a new data set.

Usage

```
cbcb_batch(
  normalized_counts,
  model,
  conditional_model = NULL,
  batch_model = NULL,
  batch1 = "batch",
  condition = "condition",
  matrix_scale = "linear",
  return_scale = "linear",
  method = "subtract"
)
```

Arguments

normalized_counts	Data frame of log2cpm counts.
model	Balanced experimental model containing condition and batch factors.
conditional_model	Experimental model with the conditional factor.
batch_model	Experimental model with the batch factor.
batch1	Column containing the first batch's metadata in the experimental design.
condition	Column containing the condition information in the metadata.
matrix_scale	Is the data on a linear or log scale?
return_scale	Do you want the data returned on the linear or log scale?
method	I found a couple ways to apply the surrogates to the data. One method subtracts the residuals of a batch model, the other adds the conditional.

Value

Dataframe of residuals after subtracting batch from the model.

See Also

[limma::voom()] [limma::lmFit()]

Examples

```
## Not run:
newdata <- cbcb_batch_effect(counts, expt_model)

## End(Not run)
```

cbcb_combat	<i>A modified version of comBatMod.</i>
-------------	---

Description

This is a hack of Kwame Okrah's `combatMod` to make it not fail on corner-cases. This was mostly copy/pasted from <https://github.com/kokrah/cbcbSEQ/blob/master/R/transform.R>

Usage

```
cbcb_combat(dat, batch, mod, noscale = TRUE, prior.plots = FALSE, ...)
```

Arguments

dat	Df to modify.
batch	Factor of batches.
mod	Factor of conditions.
noscale	The normal 'scale' option squishes the data too much, so this defaults to TRUE.
prior.plots	Print out prior plots?
...	Extra options are passed to <code>arglist</code>

Value

Df of batch corrected data

See Also

[sva] [sva::ComBat()]

Examples

```
## Not run:
df_new = cbcb_combat(df, batches, model)

## End(Not run)
```

cbcb_filter_counts	<i>Filter low-count genes from a data set using cpm data and a threshold.</i>
--------------------	---

Description

This was a function written by Kwame Okrah and perhaps also Laura Dillon to remove low-count genes. It drops genes based on a cpm threshold and number of samples.

Usage

```
cbcb_filter_counts(count_table, threshold = 1, min_samples = 2, libsize = NULL)
```

Arguments

count_table	Data frame of (pseudo)counts by sample.
threshold	Lower threshold of counts for each gene.
min_samples	Minimum number of samples.
libsize	Table of library sizes.

Value

Dataframe of counts without the low-count genes.

See Also

[edgeR]

Examples

```
## Not run:
filtered_table <- cbcb_filter_counts(count_table)

## End(Not run)
```

cheap_tm	<i>Simplified TM calculator</i>
----------	---------------------------------

Description

A quick and dirty TM calculator, taken from: Taken from: <https://www.biostars.org/p/58437/>

Usage

```
cheap_tm(sequence)
```

Arguments

sequence	String of atgc letters (not smart enough to do RNA).
----------	--

check_circos	<i>Validation function when creating a circos class.</i>
--------------	--

Description

This is the one of the first steps taken to make the circos plot builder into an object oriented set of functions. Thank you, Theresa!

Usage

```
check_circos(object)
```

Arguments

object	The object to check for validity.
--------	-----------------------------------

Value

TRUE or FALSE

check_includes	<i>Convert a vector of yes/no by DE method to a list.</i>
----------------	---

Description

This compiles the set of possible methods to include in an `all_pairwise()` from a series of booleans into a simpler list and checks that the elements have some data that may be used.

Usage

```
check_includes(
  apr,
  basic = TRUE,
  deseq = TRUE,
  ebseq = TRUE,
  edger = TRUE,
  dream = TRUE,
  limma = TRUE,
  noiseq = TRUE
)
```

Arguments

<code>apr</code>	The result from <code>all_pairwise()</code>
<code>basic</code>	The user wants the basic analysis, let us see if we can provide it here.
<code>deseq</code>	The user wants DESeq2.
<code>ebseq</code>	The user wants EBSeq.
<code>edger</code>	The user wants EdgeR.
<code>dream</code>	The user wants the variancePartition method.
<code>limma</code>	The user wants limma.
<code>noiseq</code>	The user wants NoiSeq.

Value

List containing TRUE/FALSE for each method desired, depending on if we actually have the relevant data.

check_metadata_year	<i>Figure out when mappings were performed by their timestamp</i>
---------------------	---

Description

I got bit in the butt by mismatching ensembl IDs from some older count tables and newer annotations. Happily my biomart annotation gatherer is smart enough to collect from the archive servers, so it should not be difficult for me to ensure that they match in the future.

Usage

```
check_metadata_year(metadata = NULL, column = NULL)
```

Arguments

metadata	File containing the metadata for this experiment. If none is provided, this function will just give the current year, which is only what you want if this is brand new data.
column	Sanitized column name in the metadata containing the count tables of interest. If this is not provided, it will return the month/year of the timestamp for the metadata. This has a reasonable chance of giving correct information.

Details

With that in mind, provide this function with the filename of some metadata and the file column in it, and it will look at the first file and return the year and month it was created. Therefore, you may ask ensembl for the appropriately dated gene annotations.

check_plot_scale	<i>Look at the range of the data for a plot and use it to suggest if a plot should be on log scale.</i>
------------------	---

Description

There are a bunch of plots which often-but-not-always benefit from being displayed on a log scale rather than base 10. This is a quick and dirty heuristic which suggests the appropriate scale. If the data 'should' be on the log scale and it has 0s, then they are moved to 1 so that when logged they will return to 0. Similarly, if there are negative numbers and the intended scale is log, then this will set values less than 0 to zero to avoid imaginary numbers.

Usage

```
check_plot_scale(data, scale = NULL, max_data = 10000, min_data = 10)
```

Arguments

data	Data to plot.
scale	If known, this will be used to define what (if any) values to change.
max_data	Define the upper limit for the heuristic.
min_data	Define the lower limit for the heuristic.

check_xlsx_worksheet	<i>Create the named worksheet in a workbook, this function was not well named.</i>
----------------------	--

Description

This tries to make sure that some of the problems of creating new worksheets do not occur. E.g. Names must be less than something and must be unique.

Usage

```
check_xlsx_worksheet(wb, sheet)
```

Arguments

wb	Workbook to modify
sheet	Sheet to check/create.

Value

The workbook object hopefully with a new worksheet.

See Also

[openxlsx::addWorksheet()]

choose_basic_dataset	<i>Attempt to ensure that input data to basic_pairwise() is suitable.</i>
----------------------	---

Description

basic_pairwise() assumes log2 data as input, use this to ensure that is true.

Usage

```
choose_basic_dataset(input, force = FALSE, ...)
```

Arguments

input	An expressionset containing expt to test and/or modify.
force	If we want to try out other distributed data sets, force it in using me.
...	future options, I think currently unused.

Value

data ready for basic_pairwise()

See Also

[Biobase] [choose_dataset()] [normalize()]

Examples

```
## Not run:
ready <- choose_basic_dataset(expt)

## End(Not run)
```

choose_binom_dataset	<i>A sanity check that a given set of data is suitable for methods which assume a negative binomial distribution of input.</i>
----------------------	--

Description

Take an expt and poke at it to ensure that it will not result in troubled results.

Usage

```
choose_binom_dataset(input, force = FALSE, ...)
```

Arguments

input	Expressionset containing expt object.
force	Ignore every warning and just use this data.
...	Extra arguments passed to arglist.

Details

Invoked by `deseq_pairwise()` and `edger_pairwise()`.

Value

dataset suitable for limma analysis

See Also

[DESeq2] [edgeR] [choose_basic_dataset()] [choose_limma_dataset()]

choose_dataset	<i>Choose a suitable data set for Edger/DESeq</i>
----------------	---

Description

The `_pairwise` family of functions all demand data in specific formats. This tries to make that consistent.

Usage

```
choose_dataset(input, choose_for = "limma", force = FALSE, ...)
```

Arguments

input	Expt input.
choose_for	One of limma, deseq, edger, or basic. Defines the requested data state.
force	Force non-standard data?
...	More options for future expansion.

Details

Invoked by `_pairwise()`.

Value

List the data, conditions, and batches in the data.

See Also

[`choose_binom_dataset()`] [`choose_limma_dataset()`] [`choose_basic_dataset()`]

Examples

```
## Not run:
starting_data <- create_expt(metadata)
modified_data <- normalize(starting_data, transform = "log2", norm = "quant")
a_dataset <- choose_dataset(modified_data, choose_for = "deseq")
## choose_dataset should see that log2 data is inappropriate for DESeq2 and
## return it to a base10 state.

## End(Not run)
```

`choose_limma_dataset` *A sanity check that a given set of data is suitable for analysis by limma.*

Description

Take an expt and poke at it to ensure that it will not result in troubled limma results.

Usage

```
choose_limma_dataset(input, force = FALSE, which_voom = "limma", ...)
```

Arguments

input	Expressionset containing expt object.
force	Ignore warnings and use the provided data as is.
which_voom	Choose between limma'svoom, voomWithQualityWeights, or the hpgl equivalents.
...	Extra arguments passed to arglist.

Value

dataset suitable for limma analysis

See Also

[limma] [choose_dataset()]

choose_sequence_regions

Given a named vector of fun regions, make a dataframe which includes putative primers and the spec strings for expected variants.

Description

This function came out of our TMRC2 work and seeks to provide an initial set of potential PCR primers which are able to distinguish between different aspects of the data. In the actual data, we were looking for differences between the zymodemes 2.2 and 2.3.

Usage

```
choose_sequence_regions(
  long_variant_vector,
  max_primer_length = 45,
  topn = NULL,
  bin_width = 600,
  genome = NULL,
  target_temp = 58,
  min_gc_prop = 0.25,
  max_nmer_run = 5
)
```

Arguments

long_variant_vector	variant-based set of putative regions with variants between conditions of interest.
max_primer_length	given this length as a start, whittle down to a hopefully usable primer size.
topn	Choose this number of variant regions from the rather larger set of possibilities..
bin_width	Separate the genome into chunks of this size when hunting for primers, this size will therefore be the approximate PCR amplicon length.
genome	(BS)Genome to search.
target_temp	PCR temperature to attempt to match.
min_gc_prop	Cutoff for minimum required GC content.
max_nmer_run	Maximum run of the same nucleotide allowed.

circos-class

Create a class for circos data

Description

Create a class for circos data

circos_arc*Write arcs between chromosomes in circos.*

Description

Ok, so when I said I only do 1 chromosome images, I lied. This function tries to make writing arcs between chromosomes easier. It too works in 3 stages, It writes out a data file using cfgout as a basename and the data from df in the circos arc format into circos/data/bob_arc.txt It then writes out a configuration plot stanza in circos/conf/bob_arc.conf and finally adds an include to circos/bob.conf

Usage

```
circos_arc(  
  cfg,  
  df,  
  first_col = "seqnames",  
  second_col = "seqnames.2",  
  color = "blue",  
  radius = 0.75,  
  thickness = 3,  
  ribbon = "yes",  
  show = "yes",  
  z = "0"  
)
```

Arguments

cfg	Result of circos_prefix(), contains a bunch of useful material.
df	Dataframe with starts/ends and the floating point information.
first_col	Name of the first chromosome.
second_col	Name of the second chromosome.
color	Color of the chromosomes.
radius	Outer radius at which to add the arcs.
thickness	Integer thickness of the arcs.
ribbon	Print as a ribbon?
show	Show these arcs?
z	Correction parameter.

Details

In its current implementation, this only understands two chromosomes. A minimal amount of logic and data organization will address this weakness.

Value

The file to which the arc configuration information was written.

circos_check_chromosomes

Make sure I haven't mixed and matched genomes.

Description

This is mostly intended to stop things early if I accidentally use the wrong reference genome, but it currently does return the number of observed chromosomes.

Usage

```
circos_check_chromosomes(
  cfg,
  df,
  annot_chr_column = "chr",
  annot_gene_column = "rownames",
  df_chr_column = "names",
  df_gene_column = NULL
)
```

Arguments

cfg	circos configuration object.
df	dataframe of chromosome information.
annot_chr_column	Column containing the chromosome names.
annot_gene_column	Column containing the gene IDs.
df_chr_column	Column in the cfg df containing the chromosome names.
df_gene_column	Column containing the gene names.

circos_heatmap

Write tiles of arbitrary heat-mappable data in circos.

Description

This function tries to make the writing circos heatmaps easier. Like `circos_plus_minus()` and `circos_hist()` it works in 3 stages, It writes out a data file using `cfgout` as a basename and the data from `df` in the circos histogram format into `circos/data/bob_heatmap.txt` It then writes out a configuration plot stanza in `circos/conf/bob_heatmap.conf` and finally adds an include to `circos/bob.conf`

Usage

```

circos_heatmap(
  cfg,
  input,
  tablename = NULL,
  colname = "logFC",
  color_mapping = 0,
  min_value = NULL,
  max_value = NULL,
  basename = "",
  colors = NULL,
  color_choice = "spectral-9-div",
  scale_log_base = 1,
  outer = 0.9,
  rules = NULL,
  width = 0.08,
  spacing = 0.02
)

```

Arguments

cfg	Result of circos_prefix(), contains a bunch of useful material.
input	Dataframe with starts/ends and the floating point information.
tablename	Provide a name for the input table in case it is coming from a combine_de_tables result.
colname	Name of the column with the data of interest.
color_mapping	0 means no overflows for min/max, 1 means overflows of min get a chosen color, 2 means overflows of both min/max get chosen colors.
min_value	Minimum value for the data.
max_value	Maximum value for the data.
basename	Make sure the written configuration files get different names with this.
colors	Colors of the heat map.
color_choice	Name of the heatmap to use, I forget how this interacts with color...
scale_log_base	Defines how the range of colors will be ranged with respect to the values in the data.
outer	Floating point radius of the circle into which to place the heatmap.
rules	some extra rules?
width	Width of each tile in the heatmap.
spacing	Radial distance between outer, inner, and inner to whatever follows.

Value

Radius after adding the histogram and the spacing.

circos_hist

Write histograms of arbitrary floating point data in circos.

Description

This function tries to make the writing of histogram data in circos easier. Like `circos_plus_minus()` it works in 3 stages, It writes out a data file using `cfgout` as a basename and the data from `df` in the circos histogram format into `circos/data/bob_hist.txt` It then writes out a configuration plot stanza in `circos/conf/bob_hist.conf` and finally adds an include to `circos/bob.conf`

Usage

```
circos_hist(
  cfg,
  input,
  tablename = NULL,
  annot_source = "cfg",
  colname = "logFC",
  basename = "",
  color = "blue",
  fill_color = "blue",
  fill_under = "yes",
  extend_bin = "no",
  thickness = "0",
  orientation = "out",
  outer = 0.9,
  width = 0.08,
  spacing = 0
)
```

Arguments

<code>cfg</code>	Result of <code>circos_prefix()</code> , contains a bunch of useful material.
<code>input</code>	Dataframe or table with starts/ends and the floating point information.
<code>tablename</code>	A likely input for this is a <code>combine_de_tables()</code> result, if so, provide the table's name here.
<code>annot_source</code>	This parameter was added to make it possible to add an arbitrary dataframe of other annotation information.
<code>colname</code>	Name of the column with the data of interest.
<code>basename</code>	Location to write the circos data (usually <code>cwd</code>).
<code>color</code>	Color of the plotted data.
<code>fill_color</code>	Guess
<code>fill_under</code>	The circos histogram fill under parameter
<code>extend_bin</code>	Extend bins?
<code>thickness</code>	histogram thickness.
<code>orientation</code>	facing in or out?
<code>outer</code>	Floating point radius of the circle into which to place the data.
<code>width</code>	Radial width of each tile.
<code>spacing</code>	Distance between outer, inner, and inner to whatever follows.

Value

Radius after adding the histogram and the spacing.

circos_ideogram	Create the description of chromosome markings.
-----------------	--

Description

This function writes ideogram files for circos.

Usage

```
circos_ideogram(
  name = "default",
  conf_dir = "circos/conf",
  band_url = NULL,
  fill = "yes",
  stroke_color = "black",
  show_bands = "yes",
  fill_bands = "yes",
  thickness = "20",
  stroke_thickness = "2",
  label_font = "condensedbold",
  spacing_default = "0",
  spacing_break = "0",
  fill_color = "black",
  radius = "0.85",
  radius_padding = "0.05",
  label_size = "36",
  band_stroke_thickness = "2"
)
```

Arguments

name	Name of the configuration file to which to add the ideogram.
conf_dir	Where does the configuration live?
band_url	Provide a url for making these imagemaps?
fill	Fill in the strokes?
stroke_color	What color?
show_bands	Show the bands for the ideogram?
fill_bands	and fill them in?
thickness	How thick to color the lines
stroke_thickness	How much of them to fill in
label_font	What font to use.
spacing_default	How much space between elements.
spacing_break	Space between breaks.

fill_color	What color to fill
radius	Where on the circle to put them
radius_padding	How much to pad between radii.
label_size	How large to make the labels in px.
band_stroke_thickness	How big to make the strokes!

Value

The file to which the ideogram configuration was written.

circos_karyotype	<i>Create the description of (a)chromosome(s) for circos.</i>
------------------	---

Description

This function tries to save me from having to get the lengths of arcs for bacterial chromosomes manually correct, and writes them as a circos compatible karyotype file. The outfile parameter was chosen to match the configuration directive outlined in circos_prefix(), however that will need to be changed in order for this to work in variable conditions. Next time I make one of these graphs I will do that I suspect. In addition, this currently only understands how to write bacterial chromosomes, that will likely be fixed when I am asked to write out a L.major karyotype. These defaults were chosen because I have a chromosome of this length that is correct.

Usage

```
circos_karyotype(
  cfg,
  segments = 6,
  color = "white",
  fasta = NULL,
  lengths = NULL,
  chromosomes = NULL
)
```

Arguments

cfg	Result from circos_prefix(), contains a bunch of useful things.
segments	How many segments to cut the chromosome into?
color	Color segments of the chromosomal arc?
fasta	Fasta file to use to create the karyotype.
lengths	If no sequence file is provided, use a named numeric vector to provide them.
chromosomes	Force the chromosome names if the annotations are malformed for some reason.

Value

The output filename.

circos_make	<i>Write a simple makefile for circos.</i>
-------------	--

Description

I regenerate all my circos pictures with make(1). This is my makefile.

Usage

```
circos_make(cfg, target = "", circos = "circos", verbose = FALSE)
```

Arguments

cfg	Configuration from circos_prefix().
target	Default make target.
circos	Location of circos. I have a copy in home/bin/circos and use that sometimes.
verbose	Print some information from make?

Value

a kitten, or you know, a plot.

circos_plus_minus	<i>Write tiles of bacterial ontology groups using the categories from microbesonline.org.</i>
-------------------	---

Description

This function tries to save me from writing out ontology definitions and likely making mistakes. It uses the start/ends from the gff annotation along with the 1 letter GO-like categories from microbesonline.org. It then writes two data files circos/data/bob_plus_go.txt, circos/data/bob_minus_go.txt along with two configuration files circos/conf/bob_minus_go.conf and circos/conf/bob_plus_go.conf and finally adds an include to circos/bob.conf

Usage

```
circos_plus_minus(
  cfg,
  outer = 1,
  width = 0.08,
  thickness = 95,
  spacing = 0,
  padding = 1,
  margin = 0,
  plus_orientation = "out",
  minus_orientation = "in",
  layers = 1,
  layers_overflow = "hide",
  acol = "orange",
```

```

bcol = "reds-9-seq",
ccol = "yellow",
dcol = "vlpurple",
ecol = "vlgreen",
fcol = "dpblue",
gcol = "vlgreen",
hcol = "vlpblue",
icol = "vvdpgreen",
jcol = "dpred",
kcol = "orange",
lcol = "vvlorange",
mcol = "dpgreen",
ncol = "vvlpblue",
ocol = "vvlgreen",
pcol = "vvdpred",
qcol = "ylgn-3-seq",
rcol = "vlgrey",
scol = "grey",
tcol = "vlpurple",
ucol = "greens-3-seq",
vcol = "vlred",
wcol = "vvdppurple",
xcol = "black",
ycol = "lred",
zcol = "vlpblue",
max = NULL,
label_column = NULL,
url_string = ""
)

```

Arguments

cfg	Result from <code>circos_prefix()</code> .
outer	Floating point radius of the circle into which to place the plus-strand data.
width	Radial width of each tile.
thickness	How wide to make the bars.
spacing	Radial distance between outer, inner, and inner to whatever follows.
padding	How much space between them.
margin	Margin between elements.
plus_orientation	Orientation of the plus pieces.
minus_orientation	Orientation of the minus pieces.
layers	How many layers to use
layers_overflow	How to handle too many layers.
acol	A color: RNA processing and modification. (orange)
bcol	B color: Chromatin structure and dynamics. (red-9)
ccol	C color: Energy production conversion. (yellow)

dcol	D color: Cell cycle control, mitosis and meiosis. (very light purple)
ecol	E color: Amino acid transport metabolism. (very light green)
fcol	F color: Nucleotide transport and metabolism. (deep blue)
gcol	G color: Carbohydrate transport and metabolism. (very light green)
hcol	H color: Coenzyme transport and metabolism. (very light purple blue)
icol	I color: Lipid transport and metabolism. (very very deep green)
jcol	J color: Translation, ribosome structure and biogenesis. (deep red)
kcol	K color: Transcription. (orange)
lcol	L color: Replication, recombination, and repair. (very very light orange)
mcol	M color: Cell wall/membrane biogenesis. (deep green)
ncol	N color: Cell motility (very very light purple blue)
ocol	O color: Posttranslational modification, protein turnover, chaperones. (very very light green)
pcol	P color: Inorganic ion transport and metabolism. (very very deep red)
qcol	Q color: Secondary metabolite biosynthesis, transport, and catabolism. (very light green 3)
rcol	R color: General function prediction only. (very light grey)
scol	S color: Function unknown. (grey)
tcol	T color: Signal transduction mechanisms. (very light purple)
ucol	U color: Intracellular trafficking(sp?) and secretion. (green 3)
vcol	V color: Defense mechanisms. (very light red)
wcol	W color: Extracellular structures. (very very deep purple)
xcol	X color: Not in COG. (black)
ycol	Y color: Nuclear structure. (light red)
zcol	Z color: Cytoskeleton. (very light purple blue)
max	Maximum length for chromosomal lengths
label_column	Use this column for labelling interactive svg outputs.
url_string	printf formatting string for interactive svg outputs.

Value

Radius after adding the plus/minus information and the spacing between them.

circos_prefix	<i>Write the beginning of a circos configuration file.</i>
---------------	--

Description

A few parameters need to be set when starting circos. This sets some of them and gets ready for plot stanzas.

Usage

```

circos_prefix(
  annotation,
  name = "mgas",
  base_dir = "circos",
  chr_column = "seqnames",
  cog_column = "COGFun",
  start_column = "start",
  stop_column = "end",
  strand_column = "strand",
  id_column = NULL,
  cog_map = NULL,
  radius = 1800,
  chr_units = 1000,
  band_url = NULL,
  ...
)

```

Arguments

annotation	Annotation data frame.
name	Name of the map, called with 'make name'.
base_dir	Base directory for writing the data.
chr_column	Name of the column containing the chromosome names in the annotations.
cog_column	Name of the column containing the COG groups in the annotations.
start_column	Name of the column containing the starts in the annotations.
stop_column	Name of the column containing the stops in the annotations.
strand_column	Name of the column containing the strand information.
id_column	Where do the gene IDs live? NULL means rownames.
cog_map	Not yet used, but used to provide an alternate map of groups/colors.
radius	Size of the image.
chr_units	How often to print chromosome in 'prefix' units.
band_url	Place to imagemap link.
...	Extra arguments passed to the tick/karyotype makers.

Details

In its current implementation, this really assumes that there will be no highlight stanzas and at most 1 link stanza. chromosomes. A minimal amount of logic and data organization will address these weaknesses.

Value

The master configuration file name.

circos_suffix	<i>Write the end of a circos master configuration.</i>
---------------	--

Description

circos configuration files need an ending. This writes it.

Usage

```
circos_suffix(cfg)
```

Arguments

cfg	Result from circos_prefix()
-----	-----------------------------

Value

Filename of the configuration.

circos_ticks	<i>Create the ticks for a circos plot.</i>
--------------	--

Description

This function writes ticks for circos. This has lots of options, the defaults are all taken from the circos example documentation for a bacterial genome.

Usage

```
circos_ticks(  
  name = "default",  
  conf_dir = "circos/conf",  
  show_ticks = "yes",  
  show_tick_labels = "yes",  
  show_grid = "no",  
  skip_first_label = "yes",  
  skip_last_label = "no",  
  tick_separation = 2,  
  min_label_distance = 0,  
  label_separation = 5,  
  label_offset = 5,  
  label_size = 8,  
  multiplier = 0.001,  
  main_color = "black",  
  main_thickness = 3,  
  main_size = 20,  
  first_size = 10,  
  first_spacing = 1,  
  first_color = "black",  
  first_show_label = "no",
```

```

first_label_size = 12,
second_size = 15,
second_spacing = 5,
second_color = "black",
second_show_label = "yes",
second_label_size = 16,
third_size = 18,
third_spacing = 10,
third_color = "black",
third_show_label = "yes",
third_label_size = 16,
fourth_spacing = 100,
fourth_color = "black",
fourth_show_label = "yes",
suffix = " kb",
fourth_label_size = 36,
include_first_label = TRUE,
include_second_label = TRUE,
include_third_label = TRUE,
include_fourth_label = TRUE,
...
)

```

Arguments

name	Name of the configuration file to which to add the ideogram.
conf_dir	Where does the configuration live.
show_ticks	Show them or not.
show_tick_labels	Show the tick labels, or do not.
show_grid	Print a grid behind.
skip_first_label	Like a clock.
skip_last_label	Ditto.
tick_separation	Top-level separation between tick marks.
min_label_distance	distance to the edge of the plot for labels.
label_separation	radial distance between labels.
label_offset	The offset for the labels.
label_size	Top-level label size.
multiplier	When writing the position, by what factor to lower the numbers?
main_color	Color for top-level labels?
main_thickness	Top-level thickness of lines etc.
main_size	Top-level size of text.
first_size	Second level size of text.
first_spacing	Second level spacing of ticks.

```

first_color      Second-level text color.
first_show_label      Show a label for the second level ticks?
first_label_size      Text size for second level labels?

second_size      Size of ticks for the third level.
second_spacing    third-level spacing
second_color      Text color for the third level.
second_show_label      Give them a label?
second_label_size      And a size.

third_size      Now for the size of the almost-largest ticks
third_spacing    How far apart?
third_color      and their color
third_show_label      give a label?
third_label_size      and a size.

fourth_spacing    The largest ticks!
fourth_color      The largest color.
fourth_show_label      Provide a label?

suffix      String for printing chromosome distances.
fourth_label_size      They are big!

include_first_label      Provide the smallest labels?
include_second_label      Second smallest labels?
include_third_label      Second biggest labels?
include_fourth_label      Largest labels?

...      Extra arguments from circos_prefix().

```

Value

The file to which the ideogram configuration was written.

circos_tile	<i>Write tiles of arbitrary categorical point data in circos.</i>
-------------	---

Description

This function tries to make the writing circos tiles easier. Like `circos_plus_minus()` and `circos_hist()` it works in 3 stages, It writes out a data file using `cfgout` as a basename and the data from `df` in the circos histogram format into `circos/data/bob_tile.txt` It then writes out a configuration plot stanza in `circos/conf/bob_tile.conf` and finally adds an include to `circos/bob.conf`

Usage

```
circos_tile(
  cfg,
  df,
  colname = "logFC",
  basename = "",
  colors = NULL,
  thickness = 80,
  padding = 1,
  margin = 0,
  stroke_thickness = 0,
  orientation = "out",
  outer = 0.9,
  width = 0.08,
  spacing = 0
)
```

Arguments

<code>cfg</code>	Result from <code>circos_prefix()</code> .
<code>df</code>	Dataframe with starts/ends and the floating point information.
<code>colname</code>	Name of the column with the data of interest. chromosome)
<code>basename</code>	Used to make unique filenames for the data/conf files.
<code>colors</code>	Colors of the data.
<code>thickness</code>	How thick to make the tiles in radial units.
<code>padding</code>	Space between tiles.
<code>margin</code>	How much space between other rings and the tiles?
<code>stroke_thickness</code>	Size of the tile outlines.
<code>orientation</code>	Facing in or out.
<code>outer</code>	Floating point radius of the circle into which to place the categorical data.
<code>width</code>	Width of each tile.
<code>spacing</code>	Radial distance between outer, inner, and inner to whatever follows.

Value

Radius after adding the histogram and the spacing.

classify_n_times	<i>Rerun a model generator and classifier on a training/testing set multiple times.</i>
------------------	---

Description

Rerun a model generator and classifier on a training/testing set multiple times.

Usage

```
classify_n_times(
  full_df,
  interesting_meta,
  outcome_column = "finaloutcome",
  p = 0.4,
  list = FALSE,
  formula_string = NULL,
  run_times = 10,
  method = "xgbTree",
  sampler = "cv",
  sample_number = 10,
  tuner = NULL,
  state = NULL,
  ...
)
```

Arguments

full_df	The matrix of preProcessed() data.
interesting_meta	dataframe of metadata of potential interest.
outcome_column	metadata column of interest.
p	The proportion of training/testing
list	How to return the partitions.
formula_string	Optional formula string, otherwise generated on the fly.
run_times	How many times to repeat this process
method	Modelling method to employ with caret.
sampler	Sampler to employ, bootstrap or cv right now.
sample_number	How many times to use the sampler
tuner	Tuning arguments for the method above.
state	When provided, passes the state of the data to the return so it may be reported later.
...	Others, currently unused I think

classify_variants	<i>Given a pile of variants from freebayes and friends, make a table of what changed.</i>
-------------------	---

Description

My post-processor of the results from mpileup/freebayes provides some hopefully fun output files. This function seeks to leverage them into tables which might be fun to look at.

Usage

```
classify_variants(
  metadata,
  coverage_column = "bedtoolscoveragefile",
  variants_column = "freebayesvariantsbygene",
  min_missing = 100
)
```

Arguments

metadata	Usually the result of gather_preprocessing_metadata(), but whatever it is, it should have a column containing the observed coverage and observed variants as a table.
coverage_column	Metadata column name containing coverage information from bedtools in a tabular format.
variants_column	Metadata column name containing the variants/gene.
min_missing	Bin size above which to call a region missing from one or more samples when looking for large-scale deletions using coverage information.

Value

List containing some fun stuff.

clear_session	<i>Clear an R session, this is probably unwise given what I have read about R.</i>
---------------	--

Description

Clear an R session, this is probably unwise given what I have read about R.

Usage

```
clear_session(keepers = NULL, depth = 10)
```

Arguments

keepers	List of namespaces to leave alone (unimplemented).
depth	Cheesy forloop of attempts to remove packages stops after this many tries.

Value

A spring-fresh R session, hopefully.

See Also

[R.utils]

cleavage_histogram	<i>Make a histogram of how many peptides are expected at every integer dalton from a given start to end size for a given enzyme digestion.</i>
--------------------	--

Description

This is very similar to plot_cleaved() above, but tries to be a little bit smarter.

Usage

```
cleavage_histogram(  
  pep_sequences,  
  enzyme = "trypsin",  
  start = 600,  
  end = 1500,  
  color = "black"  
)
```

Arguments

pep_sequences	Protein sequences as per plot_cleaved().
enzyme	Compatible enzyme name from cleaver.
start	Print histogram from here
end	to here.
color	Make the bars this color.

Value

List containing the plot and size distribution.

cluster_trees	<i>Take clusterprofile group data and print it on a tree as per topGO.</i>
---------------	--

Description

TopGO's ontology trees can be very illustrative. This function shoe-horns clusterProfiler data into the format expected by topGO and uses it to make those trees.

Usage

```
cluster_trees(
  de_genes,
  cpdata,
  goid_map = "id2go.map",
  go_db = NULL,
  score_limit = 0.2,
  overwrite = FALSE,
  selector = "topDiffGenes",
  pval_column = "adj.P.Val"
)
```

Arguments

de_genes	List of genes deemed 'interesting'.
cpdata	Data from simple_clusterprofiler().
goid_map	Mapping file of IDs to GO ontologies.
go_db	Dataframe of mappings used to build goid_map.
score_limit	Scoring limit above which to ignore genes.
overwrite	Overwrite an existing goid mapping file?
selector	Name of a function for applying scores to the trees.
pval_column	Name of the column in the GO table from which to extract scores.

Value

plots! Trees! oh my!

See Also

[Ramigo] [topGO::showSigOfNotes()]

Examples

```
## Not run:
cluster_data <- simple_clusterprofiler(genes, stuff)
ctrees <- cluster_trees(genes, cluster_data)

## End(Not run)
```

colData,ExpressionSet-method

A getter to pull the sample data from an ExpressionSet.

Description

A getter to pull the sample data from an ExpressionSet.

Usage

```
## S4 method for signature 'ExpressionSet'
colData(x, withDimnames = TRUE, ...)
```

Arguments

x	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
withDimnames	indeed.
...	extra args.

colData,expt-method *A getter to pull the sample data from an expt.*

Description

A getter to pull the sample data from an expt.

Usage

```
## S4 method for signature 'expt'
colData(x, withDimnames = TRUE, ...)
```

Arguments

x	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
withDimnames	Again, haven't looked it up yet.
...	Extra args.

```
colData<- ,ExpressionSet,ANY-method
```

A setter to put the sample data into an ExpressionSet.

Description

A setter to put the sample data into an ExpressionSet.

Usage

```
## S4 replacement method for signature 'ExpressionSet,ANY'
colData(x, i, withDimnames = TRUE, ...) <- value
```

Arguments

x	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
i	Slice to replace.
withDimnames	yes
...	args for the arglist
value	New values for the expressionset.

```
colData<- ,expt,ANY-method
```

A setter to put the sample data into an expt.

Description

A setter to put the sample data into an expt.

Usage

```
## S4 replacement method for signature 'expt,ANY'
colData(x, i, withDimnames = TRUE, ...) <- value
```

Arguments

x	One of my various expressionset analogs, expt, expressionSet, or summarized-Experiment.
i	Subset to replace.
withDimnames	indeed.
...	extra args.
value	New Sample data for the expt.

color_int	<i>Translate the hexadecimal color codes to three decimal numbers.</i>
-----------	--

Description

Translate the hexadecimal color codes to three decimal numbers.

Usage

```
color_int(rgb)
```

Arguments

rgb	hexadecimal color input.
-----	--------------------------

colors,expt-method	<i>A getter to pull the colors from an expt.</i>
--------------------	--

Description

A getter to pull the colors from an expt.

Usage

```
## S4 method for signature 'expt'  
colors(expt)
```

Arguments

expt	An expt.
------	----------

colors,SummarizedExperiment-method	<i>A getter to pull the colors from a SummarizedExperiment.</i>
------------------------------------	---

Description

A getter to pull the colors from a SummarizedExperiment.

Usage

```
## S4 method for signature 'SummarizedExperiment'  
colors(expt)
```

Arguments

expt	An expt.
------	----------

colors<-, expt-method *A setter to put the colors into an expt.*

Description

A setter to put the colors into an expt.

Usage

```
## S4 replacement method for signature 'expt'  
colors(expt) <- value
```

Arguments

expt	An expt.
value	List of new colors.

colors<-, SummarizedExperiment-method
A setter to put the colors into a SummarizedExperiment.

Description

A setter to put the colors into a SummarizedExperiment.

Usage

```
## S4 replacement method for signature 'SummarizedExperiment'  
colors(expt) <- value
```

Arguments

expt	A SummarizedExperiment.
value	List of new colors.

combine_de_tables	<i>Combine portions of deseq/limma/edger table output.</i>
-------------------	--

Description

This hopefully makes it easy to compare the outputs from limma/DESeq2/EdgeR on a table-by-table basis.

Usage

```
combine_de_tables(  
  apr,  
  extra_annot = NULL,  
  keepers = "all",  
  excludes = NULL,  
  adjp = TRUE,  
  include_limma = TRUE,  
  include_deseq = TRUE,  
  include_edger = TRUE,  
  include_ebseq = TRUE,  
  include_basic = TRUE,  
  include_noiseq = TRUE,  
  include_dream = TRUE,  
  add_plots = TRUE,  
  loess = FALSE,  
  plot_dim = 6,  
  compare_plots = TRUE,  
  padj_type = "ihw",  
  fancy = FALSE,  
  lfc_cutoff = 1,  
  p_cutoff = 0.05,  
  excel_title = "Table SXXX: Combined Differential Expression of YYY",  
  increment_start = "SXXX",  
  start_worksheet_num = 2,  
  rda = NULL,  
  rda_input = FALSE,  
  label = 10,  
  label_column = "hgnc_symbol",  
  format_sig = 4,  
  excel = NULL,  
  plot_columns = 10,  
  alpha = 0.4,  
  z = 1.5,  
  z_lines = TRUE,  
  wanted_genes = NULL,  
  scale_p = FALSE,  
  ...  
)
```

Arguments

apr Output from all_pairwise().

extra_annot	Add some annotation information?
keepers	List of reformatted table names to explicitly keep certain contrasts in specific orders and orientations.
excludes	List of columns and patterns to use for excluding genes.
adjp	Perhaps you do not want the adjusted p-values for plotting?
include_limma	Include limma analyses in the table?
include_deseq	Include deseq analyses in the table?
include_edger	Include edger analyses in the table?
include_ebseq	Include ebseq analyses in the table?
include_basic	Include my stupid basic logFC tables?
include_noiseeq	Include results from NoiSeq?
include_dream	Include results from the variancePartition 'dream' method?
add_plots	Add plots to the end of the sheets with expression values?
loess	Add time intensive loess estimation to plots?
plot_dim	Number of inches squared for the plot if added.
compare_plots	Add some plots comparing the results.
padj_type	Add a consistent p adjustment of this type.
fancy	Save a set of fancy plots along with the xlsx file?
lfc_cutoff	In this context, only used for plotting volcano/MA plots.
p_cutoff	In this context, used for volcano/MA plots.
excel_title	Title for the excel sheet(s). If it has the string 'YYY', that will be replaced by the contrast name.
increment_start	When incrementing the table number for each contrast, look for this string and increment when it is found. It should therefore be found in the excel_title.
start_worksheet_num	Start writing data at this worksheet number. (in case you want to put other stuff in)
rda	Write a rda file of the results.
rda_input	Include the input all_pairwise() result in the rda?
label	Label this number of top-n genes on the plots?
label_column	Use this gene annotation column to pick up gene labels.
format_sig	Use this many significant digits for printing wacky numbers.
excel	Filename for the excel workbook, or null if not printed.
plot_columns	A guesstimate of how wide plots are with respect to 'normally' sized columns in excel.
alpha	Use the alpha channel with this transparency when plotting.
z	Use this z-score for defining significant in coefficient plots.
z_lines	Add z-score lines to coefficient plots?
rownames	Add rownames to the xlsx printed table?
de_types	Used for plotting pvalue/logFC cutoffs.

Value

Table combining limma/edger/deseq outputs.

See Also

[all_pairwise()] [extract_significant_genes()]

Examples

```
## Not run:
expt <- create_expt(metadata="some_metadata.xlsx", gene_info=funkytown)
big_result <- all_pairwise(expt, model_batch=FALSE)
pretty <- combine_de_tables(big_result, table='t12_vs_t0')
pretty <- combine_de_tables(big_result, table='t12_vs_t0',
                           keepers=list("avsb"=c("a","b")))
pretty <- combine_de_tables(big_result, table='t12_vs_t0',
                           keepers=list("avsb"=c("a","b")),
                           excludes=list("description"=c("sno","rRNA")))

## End(Not run)
```

combine_expts

Take two expressionsets and smoosh them together.

Description

Because of the extra sugar I added to expressionSets, the combine() function needs a little help when combining expts. Notably, the information from tximport needs some help.

Usage

```
combine_expts(
  expt1,
  expt2,
  condition = "condition",
  all_x = TRUE,
  all_y = TRUE,
  batch = "batch",
  merge_meta = TRUE
)
```

Arguments

expt1	First expt object.
expt2	Second expt object.
condition	Column with which to reset the conditions.
all_x	Keep all of the first expt's annotations/counts if there are mismatches?
all_y	Keep all the second expt's annotations/counts if there are mismatches?
batch	Column with which to reset the batches.
merge_meta	Merge the metadata when they mismatch? This should perhaps default to TRUE.

Value

Larger expt.

See Also

[set_expt_batches()] [set_expt_conditions()] [set_expt_colors()] [set_expt_genenames()] [set_expt_samplenames()]
[subset_expt()] [create_expt()]

Examples

```
## Not run:
## I am trying to get rid of all my dontrun sections, but I don't have two
## expressionsets to combine.
expt1 <- create_expt(first_meta)
expt2 <- create_expt(second_meta)
combined <- combine_expts(expt1, expt2, merge_meta = TRUE)

## End(Not run)
```

combine_extracted_plots

Gather data required to make MA/Volcano plots for pairwise comparisons.

Description

It should be possible to significantly simplify the arguments passed to this function, but I have thus far focused only on getting it to work with the newly split-apart combine_de_tables() functions.

Usage

```
combine_extracted_plots(
  name,
  combined,
  denominator,
  numerator,
  plot_inputs,
  loess = FALSE,
  lfc_cutoff = 1,
  p_cutoff = 0.05,
  found_table = NULL,
  p_type = "all",
  plot_colors = NULL,
  fancy = FALSE,
  adjp = TRUE,
  do_inverse = FALSE,
  invert_colors = FALSE,
  z = 1.5,
  alpha = 0.4,
  z_lines = FALSE,
  label = 10,
  label_column = "hgnc_symbol"
)
```


Arguments

name	Name of the table to plot.
combined	Modified pairwise result, containing the various DE methods.
denominator	Name of the denominator coefficient.
numerator	Name of the numerator coefficient.
plot_inputs	The individual outputs from limma etc.
loess	Add a loess estimation?
found_table	The table name actually used.
p_type	Use this/these methods' p-value for determining significance.
plot_colors	Use these colors for numerators/denominators.
fancy	Include fancy pdf/svg versions of plots for publication?
adjp	Use adjusted p-values?
do_inverse	Flip the numerator/denominator?
invert_colors	Conversely, keep the values the same, but flip the colors. I think these invert parameters are not needed anymore.
z	Use a z-score cutoff for coefficient plots.
alpha	Add some transparency to the plots.
z_lines	Add lines for zscore cutoffs?
label	Label this number of the top genes.
label_column	Label the top genes with this column.
plot_basic	Add basic data?
plot_deseq	Add deseq data?
plot_edger	Add edger data?
plot_limma	Add limma data?
plot_ebseq	Add ebseq data?
plot_noiseq	Add noiseq plots?
logfc	For Volcano/MA plot lines.
pval	For Volcano/MA plot lines.

combine_mapped_table *Combine data taken from map_keepers() into a single large table.*

Description

This is part of an ongoing attempt to simplify and clean up the combine_de_tables() function. I am hoping that map_keepers and this will be able to take over all the logic currently held in the various extract_keepers_xxx() functions.

Usage

```

combine_mapped_table(
  entry,
  includes,
  adjp = TRUE,
  padj_type = "fdr",
  annot_df = NULL,
  excludes = NULL,
  lfc_cutoff = 1,
  p_cutoff = 0.05,
  format_sig = 4,
  sheet_count = 0,
  keep_underscore = TRUE,
  wanted_genes = NULL,
  scale_p = FALSE
)

```

Arguments

entry	Single entry from map_keepers() which provides orientation information about the table from all_pairwise(), along with the actual data.
includes	List of methods to include.
adjp	Used adjusted pvalues when defining 'significant'.
padj_type	Perform this type of pvalue adjustment.
annot_df	Include these annotations in the result tables.
excludes	When provided as a list, remove any rows with values in the column defined by the list names, otherwise exclude rownames.
lfc_cutoff	Use this value for a log2FC significance cutoff.
p_cutoff	Use this value for a(n adjusted) pvalue significance cutoff.
format_sig	Use this many significant digits for some of the unwieldy numbers.
sheet_count	Start with these sheet number and increment for excel.

```
combine_single_de_table
```

Given a limma, edger, and deseq table, combine them into one.

Description

This combines the outputs from the various differential expression tools and formalizes some column names to make them a little more consistent.

Usage

```

combine_single_de_table(
  li = NULL,
  ed = NULL,
  eb = NULL,
  de = NULL,

```

```

ba = NULL,
table_name = "",
final_table_names = c(),
wanted_numerator = NULL,
wanted_denominator = NULL,
invert_table = FALSE,
invert_plots = FALSE,
annot_df = NULL,
adjp = TRUE,
padj_type = "fdr",
include_deseq = TRUE,
include_edger = TRUE,
include_ebseq = TRUE,
include_limma = TRUE,
include_basic = TRUE,
lfc_cutoff = 1,
p_cutoff = 0.05,
format_sig = 4,
do_inverse = FALSE,
excludes = NULL,
sheet_count = 0,
invert_exclude = TRUE,
wanted_genes = NULL
)

```

Arguments

li	Limma output table.
ed	Edger output table.
eb	EBSeq output table
de	DESeq2 output table.
ba	Basic output table.
table_name	Name of the table to merge.
final_table_names	Vector of the final table names.
wanted_numerator	The numerator we would like to find.
wanted_denominator	The denominator we would like to find.
invert_table	Boolean to see if we already think we should switch n/d
invert_plots	Conversely, we can invert the plots.
annot_df	Add some annotation information?
adjp	Use adjusted p-values?
padj_type	Add this consistent p-adjustment.
include_deseq	Include tables from deseq?
include_edger	Include tables from edger?
include_ebseq	Include tables from ebseq?
include_limma	Include tables from limma?

include_basic	Include the basic table?
lfc_cutoff	Preferred logfoldchange cutoff.
p_cutoff	Preferred pvalue cutoff.
format_sig	How many significant digits to print? Set it to something not numeric to not use any significant digit formatting.
do_inverse	Dead parameter? invert the data?
excludes	Set of genes to exclude from the output.
sheet_count	What sheet is being written?

Value

List containing a) Dataframe containing the merged limma/edger/deseq/basic tables, and b) A summary of how many genes were observed as up/down by output table.

See Also

[data.table] [hpgl_padjust()] [extract_keepers_all()] [extract_keepers_lst()] [extract_keepers_single()]

compare_batches	<i>Attempt to compare the results from the various batch/sv methods.</i>
-----------------	--

Description

Given an expressionset and list of methods, try to find out how well the various methods agree via correlation.

Usage

```
compare_batches(expt = NULL, methods = NULL)
```

Arguments

expt	Input expressionset
methods	Set of methods to try out.

compare_de_results	<i>Compare the results of separate all_pairwise() invocations.</i>
--------------------	--

Description

Where compare_led_tables looks for changes between limma and friends, this function looks for differences/similarities across the models/surrogates/etc across invocations of limma/deseq/edger.

Usage

```
compare_de_results(
  first,
  second,
  cor_method = "pearson",
  try_methods = c("limma", "deseq", "edger")
)
```

Arguments

first	One invocation of combine_de_tables to examine.
second	A second invocation of combine_de_tables to examine.
cor_method	Method to use for cor.test().
try_methods	List of methods to attempt comparing.

Details

Tested in 29de_shared.R

Value

A list of compared columns, tables, and methods.

See Also

[all_pairwise()]

Examples

```
## Not run:
first <- all_pairwise(expt, model_batch = FALSE, excel = "first.xlsx")
second <- all_pairwise(expt, model_batch = "svaseq", excel = "second.xlsx")
comparison <- compare_de_results(first$combined, second$combined)

## End(Not run)
```

compare_de_tables	<i>Use plot_linear_scatter to compare to de tables.</i>
-------------------	---

Description

Use plot_linear_scatter to compare to de tables.

Usage

```
compare_de_tables(
  first,
  second,
  fcx = "deseq_logfc",
  px = "deseq_adj_p",
  fcy = "deseq_logfc",
```

```

py = "deseq_adj",
first_table = NULL,
second_table = NULL
)

```

Arguments

first	First table to compare.
second	Second table to compare.
fcx	Column for the x-axis fold-change.
px	Column for the x-axis p-value.
fcy	Column containing the y-axis fold-change.
py	Column containing the y-axis p-value.
first_table	If the input data are actually of type de_table, then find the table(s) inside them.
second_table	Ibid.

Value

List result from plot_linear_scatter

compare_go_searches	<i>Compare the results from different ontology tools</i>
---------------------	--

Description

Combine the results from goseq, cluster profiler, topgo, and gostats; poke at them with a stick and see what happens. The general idea is to pull the p-value data from each tool and contrast that to the set of all possible ontologies. This allows one to do a correlation coefficient between them. In addition, take the 1-pvalue for each ontology for each tool. Thus for strong p-values the score will be near 1 and so we can sum the scores for all the tools. Since topgo has 4 tools, the total possible is 7 if everything has a p-value equal to 0.

Usage

```
compare_go_searches(goseq = NULL, cluster = NULL, topgo = NULL, gostats = NULL)
```

Arguments

goseq	Result from simple_goseq()
cluster	Result from simple_clusterprofiler()
topgo	Result from topGO
gostats	Result from GOstats

Value

Summary of the similarities of ontology searches

See Also

[goseq] [clusterProfiler] [topGO] [goStats]

compare_logfc_plots	<i>Compare logFC values from limma and friends</i>
---------------------	--

Description

There are some peculiar discrepancies among these tools, what is up with that?

Usage

```
compare_logfc_plots(combined_tables)
```

Arguments

combined_tables
The combined tables from limma et al.

Details

Invoked by combine_de_tables() in order to compare the results.

Value

Some plots

See Also

[plot_linear_scatter()]

Examples

```
## Not run:  
limma_vs_deseq_vs_edger <- compare_logfc_plots(combined)  
## Get a list of plots of logFC by contrast of LvD, LvE, DvE  
## It provides comparisons against the basic analysis, but who cares about that.  
  
## End(Not run)
```

compare_pc_sv	<i>Incomplete function to compare PCs and SVs.</i>
---------------	--

Description

This function is the beginning of a method to get a sense of what happens to data when performing things like SVA.

Usage

```
compare_pc_sv(
  expt,
  norm = NULL,
  transform = "log2",
  convert = "cpm",
  filter = TRUE,
  batch = "svaseq"
)
```

Arguments

expt	Input expressionset.
norm	Normalization performed.
transform	Assuming using PCA and so log2 the data.
convert	Scale the data, presumably with cpm().
filter	Low-count filter the data?
batch	Method which provides SVs to apply.

Value

Currently just a plot of the SVs.

compare_significant_contrasts

Implement a cleaner version of 'subset_significants' from analyses with Maria Adelaida.

Description

This should provide nice venn diagrams and some statistics to compare 2 or 3 contrasts in a differential expression analysis.

Usage

```
compare_significant_contrasts(
  sig_tables,
  second_sig_tables = NULL,
  compare_by = "deseq",
  weights = FALSE,
  contrasts = c(1, 2, 3)
)
```

Arguments

sig_tables	Set of significance tables to poke at.
second_sig_tables	Separate set of significant results, intra vs. inter comparisons.
compare_by	Use which program for the comparisons?
weights	When printing venn diagrams, weight them?
contrasts	List of contrasts to compare.

Value

List containing the intersections of the contrasts and plots describing them.

See Also

[Vennerable]

compare_surrogate_estimates

Perform a comparison of the surrogate estimators demonstrated by Jeff Leek.

Description

This is entirely derivative, but seeks to provide similar estimates for one's own actual data and catch corner cases not taken into account in that document (for example if the estimators don't converge on a surrogate variable). This will attempt each of the surrogate estimators described by Leek: pca, sva supervised, sva unsupervised, ruv supervised, ruv residuals, ruv empirical. Upon completion it will perform the same limma expression analysis and plot the ranked t statistics as well as a correlation plot making use of the extracted estimators against condition/batch/whatever else. Finally, it does the same ranking plot against a linear fitting Leek performed and returns the whole pile of information as a list.

Usage

```
compare_surrogate_estimates(
  expt,
  extra_factors = NULL,
  filter_it = TRUE,
  filter_type = TRUE,
  do_catplots = FALSE,
  surrogates = "be",
  ...
)
```

Arguments

expt	Experiment containing a design and other information.
extra_factors	Character list of extra factors which may be included in the final plot of the data.
filter_it	Most of the time these surrogate methods get mad if there are 0s in the data. Filter it?
filter_type	Type of filter to use when filtering the input data.
do_catplots	Include the catplots? They don't make a lot of sense yet, so probably no.
surrogates	Use 'be' or 'leek' surrogate estimates, or choose a number.
...	Extra arguments when filtering.

Value

List of the results.

See Also

[normalize_expt()] [plot_pca()] [all_adjuster()] [corrplot] [ffpe]

concatenate_runs	<i>Sum the reads/gene for multiple sequencing runs of a single condition/batch.</i>
------------------	---

Description

On occasion we have multiple technical replicates of a sequencing run. This can use a column in the experimental design to identify those replicates and sum the counts into a single column in the count tables.

Usage

```
concatenate_runs(expt, column = "replicate")
```

Arguments

expt	Experiment class containing the requisite metadata and count tables.
column	Column of the design matrix used to specify which samples are replicates.

Details

Untested as of 2016-12-01, but used in a couple of projects where sequencing runs got repeated.

Value

Expt with the concatenated counts, new design matrix, batches, conditions, etc.

See Also

[Biobase] [exprs()] [fData()] [pData()] [create_expt()]

Examples

```
## Not run:
compressed <- concatenate_runs(expt)

## End(Not run)
```

convert_counts	<i>Perform a cpm/rpkm/whatever transformation of a count table.</i>
----------------	---

Description

I should probably tell it to also handle a simple df/vector/list of gene lengths, but I haven't. cp_seq_m is a cpm conversion of the data followed by a rp-ish conversion which normalizes by the number of the given oligo. By default this oligo is 'TA' because it was used for tnseq which should be normalized by the number of possible transposition sites by mariner. It could, however, be used to normalize by the number of methionines, for example – if one wanted to do such a thing.

Usage

```
convert_counts(count_table, method = "raw", annotations = NULL, ...)
```

Arguments

count_table	Matrix of count data.
method	Type of conversion to perform: edgecpm/cpm/rpkm/cp_seq_m.
...	Options I might pass from other functions are dropped into arglist, used by rpkm (gene lengths) and divide_seq (genome, pattern to match, and annotation type).

Value

Dataframe of cpm/rpkm/whatever(counts)

See Also

[edgeR] [Biobase]

Examples

```
## Not run:
  converted_table = convert_counts(count_table, method='cbcbcpm')

## End(Not run)
```

convert_gsc_ids	<i>Use AnnotationDbi to translate geneIDs from type x to type y.</i>
-----------------	--

Description

This is intended to convert all the IDs in a geneSet from one ID type to another and giving back the geneSet with the new IDs. FIXME: This should use convert_ids() to simplify itself

Usage

```
convert_gsc_ids(
  gsc,
  orgdb = "org.Hs.eg.db",
  from_type = NULL,
  to_type = "ENTREZID"
)
```

Arguments

gsc	geneSetCollection with IDs of a type one wishes to change.
orgdb	Annotation object containing the various IDs.
from_type	Name of the ID which your gsc is using. This can probably be automatically detected...
to_type	Name of the ID you wish to use.

Details

One caveat: this will collapse redundant IDs via unique().

Value

Fresh gene set collection replete with new names.

See Also

[AnnotationDbi] [guess_orgdb_keytypes()] [convert_ids()] [GSEABase]

convert_ids	<i>Change gene IDs to the format expected by gsva using an orgdb.</i>
-------------	---

Description

Though it is possible to use gsva without ENTREZ IDs, it is not trivial. This function attempts to ensure that the IDs in one's expressionset are therefore entrez IDs. It is possible that this function is at least partially redundant with other functions in this package and should be replaced.

Usage

```
convert_ids(ids, from = "ENSEMBL", to = "ENTREZID", orgdb = "org.Hs.eg.db")
```

Arguments

ids	Vector of IDS to modify.
from	Change from this format.
to	Change to this format.
orgdb	Using this orgdb instance.

Value

New vector of ENTREZ IDs.

See Also

[AnnotationDbi]

cordist	<i>Similarity measure which combines elements from Pearson correlation and Euclidean distance.</i>
---------	--

Description

Here is Keith's summary: Where the cor returns the Pearson correlation matrix for the input matrix, and the dist function returns the Euclidean distance matrix for the input matrix. The LHS of the equation is simply the sign of the correlation function, which serves to preserve the sign of the interaction. The RHS combines the Pearson correlation and the log inverse Euclidean distance with equal weights. The result is a number in the range from -1 to 1 where values close to -1 indicate a strong negative correlation and values close to 1 indicate a strong positive correlation. While the Pearson correlation and Euclidean distance each contribute equally in the above equation, one could also assign tuning parameters to each of the metrics to allow for unequal contributions.

Usage

```
cordist(
  data,
  cor_method = "pearson",
  dist_method = "euclidean",
  cor_weight = 0.5,
  ...
)
```

Arguments

data	Matrix of data
cor_method	Which correlation method to use?
dist_method	Which distance method to use?
cor_weight	0-1 weight of the correlation, the distance weight will be 1-cor_weight.
...	extra arguments for cor/dist

Value

Matrix of the correlation-modified distances of the original matrix.

Author(s)

Keigh Hughitt

correlate_de_tables *See how similar are results from limma/deseq/edger/ebseq.*

Description

limma, DEseq2, and EdgeR all make somewhat different assumptions. and choices about what makes a meaningful set of differentially. expressed genes. This seeks to provide a quick and dirty metric describing the degree to which they (dis)agree.

Usage

```
correlate_de_tables(results, annot_df = NULL, extra_contrasts = NULL)
```

Arguments

`results` Data from `do_pairwise()`
`annot_df` Include annotation data?
`extra_contrasts` include some extra contrasts when comparing results.

Details

Invoked by `all_pairwise()`.

Value

Heatmap showing how similar they are along with some correlations between the three players.

See Also

`[limma_pairwise()]` `[edger_pairwise()]` `[deseq_pairwise()]`

Examples

```
## Not run:
l = limma_pairwise(expt)
d = deseq_pairwise(expt)
e = edger_pairwise(expt)
fun = compare_led_tables(limma = l, deseq = d, edger = e)

## End(Not run)
```

count_clonotype_by_cluster

Add a df of clonotype observations by cell cluster to @misc of a Seurat datastructure.

Description

This seeks to count up and provide a couple of metric of how many B/T cells are in each cluster of a VDJ single cell dataset.

Usage

```
count_clonotype_by_cluster(
  scd,
  column = "res0p2_clusters",
  clono_column = "raw_clonotype_id",
  add_sum = TRUE
)
```

Arguments

scd	Seurat single cell datastructure.
column	Cluster column in the metadata.
clono_column	Column containing VDJ annotations.
add_sum	Add sums of the clusters to the metadata?

Value

The scd with some new metadata.

count_expt_snps

Gather snp information for an expt

Description

I made some pretty significant changes to the set of data which I retain when using mpileup/freebayes. As a result, this function needs to be reworked.

Usage

```
count_expt_snps(
  expt,
  annot_column = "bcftable",
  tolower = TRUE,
  snp_column = NULL,
  numerator_column = "PAO",
  denominator_column = "DP",
  reader = "table",
  verbose = FALSE
)
```

Arguments

expt an expressionset from which to extract information.
annot_column Column in the metadata for getting the table of bcftools calls.
tolower Lowercase stuff like 'HPGL'?
snp_column Which column of the parsed bcf table contains our interesting material?
numerator_column When provided, use this column as the numerator of a proportion.
denominator_column When provided, use this column as the denominator of a proportion.#'

Details

This function attempts to gather a set of variant positions using an extant expressionset. This therefore seeks to keep the sample metadata consistent with the original data. In its current iteration, it therefore makes some potentially bad assumptions about the naming conventions for its input files. It furthermore assumes inputs from the variant calling methods in cyoa.

Value

A new expt object

See Also

[Biobase] freebayes:DOI:10.48550/arXiv.1207.3907, mpileup:DOI:10.1093/gigascience/giab008

Examples

```
## Not run:
expt <- create_expt(metadata, gene_information)
snp_expt <- count_expt_snps(expt)
## This assumes that the metadata has a column named 'bcftable' with one file per
## cell. These files in turn should have a column named 'diff_count' which will
## be the source of the numbers found when doing exprs(snp_expt).

## End(Not run)
```

count_nmer

Count n-mers in a given data set using Biostrings

Description

This just calls PDict() and vcountPDict() on a sequence database given a pattern and number of mismatches. This may be used by divide_seq() normalization.

Usage

```
count_nmer(genome, pattern = "ATG", mismatch = 0)
```


Arguments

genome	Sequence database, genome in this case.
pattern	Count off this string.
mismatch	How many mismatches are acceptable?

Value

Set of counts by sequence.

count_nmer,character-method

Count nmers given a filename instead of genome object.

Description

Count nmers given a filename instead of genome object.

Usage

```
## S4 method for signature 'character'
count_nmer(genome, pattern = "ATG", mismatch = 0)
```

Arguments

genome	filename of the genome in question
pattern	Pattern for which to search.
mismatch	Number of mismatches allowed.

counts_from_surrogates

A single place to extract count tables from a set of surrogate variables.

Description

Given an initial set of counts and a series of surrogates, what would the resulting count table look like? Hopefully this function answers that question.

Usage

```
counts_from_surrogates(
  data,
  adjust = NULL,
  design = NULL,
  method = "ruv",
  model_fstring = "~ 0 + condition + batch",
  matrix_scale = "linear",
  return_scale = "linear",
  ...
)
```

Arguments

data	Original count table, may be an expt/expressionset or df/matrix.
adjust	Surrogates with which to adjust the data.
design	Experimental design if it is not included in the expressionset.
method	Which methodology to follow, ideally these agree but that seems untrue.
matrix_scale	Was the input for the surrogate estimator on a log or linear scale?
return_scale	Does one want the output linear or log?
...	Arguments passed to downstream functions.
cond_column	design column containing the condition data.
batch_column	design column with the batch data, used for subtractive methods.

Value

A data frame of adjusted counts.

See Also

[sva] [RUVSeq] [crossprod()] [tcrossprod()] [solve()]

cp_options

Set up appropriate option sets for clusterProfiler

Description

This hard-sets some defaults for orgdb/kegg databases when using clusterProfiler.

Usage

```
cp_options(species)
```

Arguments

species Currently it only works for humans and fruit flies.

create_expt	<i>Wrap bioconductor's expressionset to include some extra information.</i>
-------------	---

Description

Note: You should just be using create_se(). It does everything the expt does, but better.

Usage

```
create_expt(
  metadata = NULL,
  gene_info = NULL,
  count_dataframe = NULL,
  sanitize_rownames = TRUE,
  sample_colors = NULL,
  title = NULL,
  notes = NULL,
  include_type = "all",
  countdir = NULL,
  include_gff = NULL,
  file_column = "file",
  id_column = NULL,
  savefile = NULL,
  low_files = FALSE,
  handle_na = "drop",
  researcher = "elsayed",
  study_name = NULL,
  file_type = NULL,
  annotation_name = "org.Hs.eg.db",
  tx_gene_map = NULL,
  feature_type = "gene",
  ignore_tx_version = TRUE,
  keep_underscore = TRUE,
  ...
)
```

Arguments

metadata	Comma separated file (or excel) describing the samples with information like condition, batch, count_filename, etc.
gene_info	Annotation information describing the rows of the data set, this often comes from a call to import.gff() or biomaRt or organismdbi.
count_dataframe	If one does not wish to read the count tables from the filesystem, they may instead be fed as a data frame here.
sanitize_rownames	Clean up weirdly written gene IDs?
sample_colors	List of colors by condition, if not provided it will generate its own colors using colorBrewer.
title	Provide a title for the expt?

notes	Additional notes?
include_type	I have usually assumed that all gff annotations should be used, but that is not always true, this allows one to limit to a specific annotation type.
countdir	Directory containing count tables.
include_gff	Gff file to help in sorting which features to keep.
file_column	Column to use in a gene information dataframe for
id_column	Column which contains the sample IDs.
savefile	Rdata filename prefix for saving the data of the resulting expt.
low_files	Explicitly lowercase the filenames when searching the filesystem?
handle_na	How does one wish to deal with NA values in the data?
researcher	Used to make the creation of gene sets easier, set the researcher tag.
study_name	Ibid, but set the study tag.
file_type	Explicitly state the type of files containing the count data. I have code which autodetects the method used to import count data, this short-circuits it.
annotation_name	Ibid, but set the orgdb (or other annotation) instance.
tx_gene_map	Dataframe of transcripts to genes, primarily for tools like salmon.
feature_type	Make explicit the type of feature used so it may be printed later.
...	More parameters are fun!

Details

The primary innovation of this function is that it will check the metadata for columns containing filenames for the count tables, thus hopefully making the collation and care of metadata/counts easier. For example, I have some data which has been mapped against multiple species. I can use this function and just change the file_column argument to pick up each species' tables.

Value

experiment an expressionset

See Also

[Biobase] [cdm_expt_rda] [example_gff] [sb_annot] [sb_data] [extract_metadata()] [set_expt_conditions()] [set_expt_batches()] [set_expt_samplenames()] [subset_expt()] [set_expt_colors()] [set_expt_genenames()] [tximport] [load_annotations()]

Examples

```
cdm_expt_rda <- system.file("share", "cdm_expt.rda", package = "hpgldata")
load(file = cdm_expt_rda)
head(cdm_counts)
head(cdm_metadata)
## The gff file has differently labeled locus tags than the count tables, also
## the naming standard changed since this experiment was performed, therefore I
## downloaded a new gff file.
example_gff <- system.file("share", "gas.gff", package = "hpgldata")
gas_gff_annot <- load_gff_annotations(example_gff)
rownames(gas_gff_annot) <- make.names(gsub(pattern = "(Spy)_", replacement = "\\1",
x = gas_gff_annot[["locus_tag"]]), unique = TRUE)
```

```

mgas_expt <- create_expt(metadata = cdm_metadata, gene_info = gas_gff_annot,
                        count_dataframe = cdm_counts)
head(pData(mgas_expt))
## An example using count tables referenced in the metadata.
sb_annot <- system.file("share", "sb", "trinotate_head.csv.xz", package = "hpgldata")
sb_annot <- load_trinotate_annotations(trinotate = sb_annot)
sb_annot <- as.data.frame(sb_annot)
rownames(sb_annot) <- make.names(sb_annot[["transcript_id"]], unique = TRUE)
sb_annot[["rownames"]] <- NULL
sb_data <- system.file("share", "sb", "preprocessing.tar.xz", package = "hpgldata")
untarred <- utils::untar(tarfile = sb_data)
sb_expt <- create_expt(metadata = "preprocessing/kept_samples.xlsx",
                      gene_info = sb_annot)

dim(exprs(sb_expt))
dim(fData(sb_expt))
pData(sb_expt)
## There are lots of other ways to use this, for example:
## Not run:
new_experiment <- create_expt(metadata = "some_csv_file.csv", gene_info = gene_df)
## Remember that this depends on an existing data structure of gene annotations.
meta <- extract_metadata("some_supplementary_materials_xls_file_I_downloaded.xls")
another_expt <- create_expt(metadata = meta, gene_info = annotations, count_dataframe = df_I_downloaded)

## End(Not run)

```

create_partitions	<i>Use createDataPartition to create test/train sets and massage them a little.</i>
-------------------	---

Description

This will also do some massaging of the data to make it easier to work with for downstream tasks. Most notably, since I am mostly evaluating classifiers of clinical data to see how well they agree with extant annotations, I want to make sure the relevant columns are renamed in the testing sets.

Usage

```

create_partitions(
  full_df,
  interesting_meta,
  outcome_factor = "condition",
  p = 0.4,
  list = FALSE,
  times = 5
)

```

Arguments

full_df	Dataframe containing the measured data and relevant factors.
interesting_meta	Other metadata (maybe not needed)
outcome_factor	Name of the outcome column
p	Ratio to split trainer and testers.

list	Generate result as list or dataframe
times	How many times to iterate

See Also

<https://topepo.github.io/caret/data-splitting.html#simple-splitting-based-on-the-outcome> and <https://github.com/compge/supervisedLearning.Rmd>

create_scd	<i>Create a combined seurat object from a sample sheet.</i>
------------	---

Description

I would like to have a simpler function for creating seurat data structures similar to my `create_expt()`. This will try to do so.

Usage

```
create_scd(
  metadata,
  expression_column = "gexfile",
  vdj_t_column = "vdjtcells",
  vdj_b_column = "vdjbcells",
  prefix = NULL,
  separate = FALSE,
  types = "gex",
  mito_pattern = "^mt-",
  ribo_pattern = "^Rp[s1]"
)
```

Arguments

metadata	Sample sheet.
expression_column	
vdj_t_column	Metadata column containing the base location of the cellranger outputs.
vdj_b_column	Column, which if filled in, tells this to look for VDJ information specific to light chains.
vdj_b_column	Column, which if filled in, tells this to look for VDJ information specific to heavy chains.
prefix	Arbitrary prefix for the location information, included because I am messing with cellranger and have multiple output directories and want to be able to switch between them.
separate	When true, this function should return a list comprised of the individual sample objects.
types	Types of data to add to the scd.
mito_pattern	Pattern used to find mitochondrial genes.
ribo_pattern	Pattern used to find ribosomal proteins.

Value

Either a list or merged seurat object(s).

create_se

*Create a SummarizedExperiment given some metadata***Description**

This function was taken from `create_expt()` and repurposed to create `SummarizedExperiments`.

Usage

```
create_se(
  metadata = NULL,
  gene_info = NULL,
  count_dataframe = NULL,
  sanitize_rownames = FALSE,
  sample_colors = NULL,
  title = NULL,
  notes = NULL,
  include_type = "all",
  count_source = "htseq",
  countdir = NULL,
  include_gff = NULL,
  file_column = "file",
  file_type = NULL,
  savefile = NULL,
  low_files = FALSE,
  annotation = "org.Hs.eg.db",
  palette = "Dark2",
  round = FALSE,
  tx_gene_map = NULL,
  ...
)
```

Arguments

<code>metadata</code>	Filename or table of metadata about the samples of interest.
<code>gene_info</code>	Annotations for the genes in the count data.
<code>count_dataframe</code>	Optional table of counts.
<code>sanitize_rownames</code>	Clean up unruly gene IDs?
<code>sample_colors</code>	Specify the colors for the samples?
<code>title</code>	Provide a title for the experiment.
<code>notes</code>	Provide arbitrary notes.
<code>include_type</code>	Used to specify types of genes/annotations to use.
<code>countdir</code>	(deprecated) Directory containing count tables.
<code>include_gff</code>	Keep a copy of the gff with the data?
<code>file_column</code>	Metadata column containing the counts for each sample.
<code>savefile</code>	Filename to which to save a rda file of the data structure.

low_files	I don't remember this, I bet it is deprecated.
annotation	orgDB associated with this, primarily used with gsva-like tools.
palette	Color palette when auto-choosing colors for the samples.
round	Round the data if/when it is not integer?
tx_gene_map	When using tximport, use this to convert from transcripts to genes.
...	Extra options.
id_column	Non-default column containing the sample IDs.

See Also

[summarizedExperiment]

de_venn	<i>Create venn diagrams describing how well deseq/limma/edger agree.</i>
---------	--

Description

The sets of genes provided by limma and friends would ideally always agree, but they do not. Use this to see out how much the (dis)agree.

Usage

```
de_venn(table, adjp = FALSE, p = 0.05, lfc = 0, ...)
```

Arguments

table	Which table to query?
adjp	Use adjusted p-values
p	p-value cutoff, I forget what for right now.
lfc	What fold-change cutoff to include?
...	More arguments are passed to arglist.

Value

A list of venn plots

See Also

[Vennerable] [get_sig_genes()]

Examples

```
## Not run:
bunchovenns <- de_venn(pairwise_result)

## End(Not run)
```


default_proper

*Invoke PROPER and replace its default data set with data of interest.***Description**

Recent reviewers of Najib's grants have taken an increased interest in knowing the statistical power of the various experiments. He queried Dr. Corrada-Bravo who suggested PROPER. I spent some time looking through it and, with some reverervations, modified its workflow to (at least in theory) be able to examine any dataset. The workflow in question is particularly odd and warrants further discussion/analysis. This function invokes PROPER exactly as it was performed in their paper.

Usage

```
default_proper(
  de_tables,
  p = 0.05,
  experiment = "cheung",
  nsims = 20,
  reps = c(3, 5, 7, 10),
  de_method = "edger",
  alpha_type = "fdr",
  alpha = 0.1,
  stratify = "expr",
  target = "lfc",
  add_coverage = TRUE,
  filter = "none",
  delta = 0.5
)
```

Arguments

de_tables	A set of differential expression results, presumably from EdgeR or DESeq2.
p	Cutoff
experiment	The default data set in PROPER is entitled 'cheung'.
nsims	Number of simulations to perform.
reps	Simulate these number of experimental replicates.
de_method	There are a couple choices here for tools which are pretty old, my version of this only accepts deseq or edger.
alpha_type	I assume p-adjust type.
alpha	Accepted fdr rate.
stratify	There are a few options here, I don't fully understand them.
target	Cutoff.
add_coverage	Add a line showing the actual coverage observed?
filter	Apply a filter?
delta	Not epsilon! (E.g. I forget what this does).

Value

List containing the various results and plots from proper.

See Also

[PROPER] DOI:10.1093/bioinformatics/btu640

deparse_go_value	<i>Extract more easily readable information from a GOTERM datum.</i>
------------------	--

Description

The output from the GOTERM/GO.db functions is inconsistent, to put it nicely. This attempts to extract from that heterogeneous datatype something easily readable. Example: `Synonym()` might return any of the following: NA, NULL, "NA", "NULL", `c("NA",NA,"GO:00001")`, "GO:00002", `c("Some text",NA, NULL, "GO:00003")` This function will boil that down to 'not found', ', ', 'GO:00004', or "GO:0001, some text, GO:00004"

Usage

```
deparse_go_value(value)
```

Arguments

value	Result of <code>try(as.character(somefunction(GOTERM[id])), silent = TRUE)</code> . some-function would be 'Synonym' 'Secondary' 'Ontology', etc...
-------	---

Value

something more sane (hopefully).

See Also

[GO.db]

Examples

```
## Not run:
## goterms = GOTERM[ids]
## sane_goterms = deparse_go_value(goterms)

## End(Not run)
```

deseq_lrt	<i>Bring together some of the likelihood ratio test analyses.</i>
-----------	---

Description

This function hopes to wrap up some of the ideas/methods for LRT.

Usage

```
deseq_lrt(
  expt,
  interactor_column = "visitnumber",
  interest_column = "clinicaloutcome",
  transform = "rlog",
  factors = NULL,
  cutoff = 0.05,
  minc = 3,
  interaction = TRUE
)
```

Arguments

expt	Input expressionset
interactor_column	Potentially interacting metadata
interest_column	Essentially the condition in other analyses.
transform	DESeq2 transformation applied (vst or rlog).
factors	Other factors of interest
cutoff	Significance cutoff
minc	Minimum number of elements for a group
interaction	Use an interaction model?

See Also

DOI:10.1186/s13059-014-0550-8

deseq_pairwise	<i>deseq_pairwise() Because I can't be trusted to remember '2'.</i>
----------------	---

Description

This calls `deseq2_pairwise(...)` because I am determined to forget typing `deseq2`.

Usage

```
deseq_pairwise(...)
```

Arguments

... I like cats.

Value

stuff deseq2_pairwise results.

See Also

[deseq2_pairwise()]

deseq_try_sv	<i>Given a set of surrogate variables from sva and friends, try adding them to a DESeqDataSet.</i>
--------------	--

Description

Sometimes sva returns a set of surrogate variable estimates which lead to models which are invalid according to DESeq2. This function will try before buying and tell the user if the sva model additions are valid according to DESeq.

Usage

```
deseq_try_sv(data, summarized, svcs, num_sv = NULL)
```

Arguments

data	DESeqDataSet to test out.
summarized	Existing DESeq metadata to append svcs.
svcs	Surrogates from sva and friends to test out.
num_sv	Optionally, provide the number of SVs, primarily used if recursing in the hunt for a valid number of surrogates.

Value

DESeqDataSet with at least some of the SVs appended to the model.

See Also

[sva] [RUVSeq] [all_adjusters()] [normalize()]

deseq2_pairwise	<i>Set up model matrices contrasts and do pairwise comparisons of all conditions using DESeq2.</i>
-----------------	--

Description

Invoking DESeq2 is confusing, this should help.

Usage

```
deseq2_pairwise(
  input = NULL,
  model_fstring = "~ 0 + condition + batch",
  null_fstring = "~",
  model_svs = NULL,
  filter = FALSE,
  extra_contrasts = NULL,
  annot_df = NULL,
  force = FALSE,
  keepers = NULL,
  deseq_method = "long",
  fittype = "parametric",
  num_surrogates = "be",
  keep_underscore = TRUE,
  ...
)
```

Arguments

input	Dataframe/vector or expt class containing data, normalization state, etc.
extra_contrasts	Provide extra contrasts here.
annot_df	Include some annotation information in the results?
force	Force deseq to accept data which likely violates its assumptions.
keepers	List of explicit contrasts to perform instead of all.
deseq_method	The DESeq2 manual shows a few ways to invoke it, I make 2 of them available here.
fittype	Method to fir the data.
...	Triple dots! Options are passed to arglist.
conditions	Factor of conditions in the experiment.
batches	Factor of batches in the experiment.
model_cond	Is condition in the experimental model?
model_batch	Is batch in the experimental model?
model_intercept	Use an intercept model?
alt_model	Provide an arbitrary model here.

Details

Like the other `_pairwise()` functions, this attempts to perform all pairwise contrasts in the provided data set. The details are of course slightly different when using DESeq2. Thus, this uses the function `choose_binom_dataset()` to try to ensure that the incoming data is appropriate for DESeq2 (if one normalized the data, it will attempt to revert to raw counts, for example). It continues on to extract the conditions and batches in the data, choose an appropriate experimental model, and run the DESeq analyses as described in the manual. It defaults to using an experimental batch factor, but will accept a string like 'sva' instead, in which case it will use sva to estimate the surrogates, and append them to the experimental design. The `deseq_method` parameter may be used to apply different DESeq2 code paths as outlined in the manual. If you want to play with non-standard data, the `force` argument will round the data and shoe-horn it into DESeq2.

Value

List including the following information: `run` = the return from calling `DESeq()` `denominators` = list of denominators in the contrasts `numerators` = list of the numerators in the contrasts `conditions` = the list of conditions in the experiment `coefficients` = list of coefficients making the contrasts `all_tables` = list of DE tables

See Also

[DESeq2] [basic_pairwise()] [limma_pairwise()] [edger_pairwise()] [ebseq_pairwise()] DOI:10.1186/s13059-014-0550-8.

Examples

```
## Not run:
pretend = deseq2_pairwise(data, conditions, batches)

## End(Not run)
```

disjunct_pvalues

Test for infected/control/beads – a placebo effect?

Description

This was a function I copied out of Keith/Hector/Laura/Cecilia's paper in which they sought to discriminate the effect of inert beads on macrophages vs. the effect of parasites. The simpler way of expressing it is: take the worst p-value observed for the pair of contrasts, infected/uninfected and beads/uninfected.

Usage

```
disjunct_pvalues(contrast_fit, cellmeans_fit, conj_contrasts, disj_contrast)
```

Arguments

`contrast_fit` Result of `lmFit`.
`cellmeans_fit` Result of a `cellmeans` fit.
`conj_contrasts` Result from the `makeContrasts` of the first set.
`disj_contrast` Result of the `makeContrasts` of the second set.

Details

The goal is therefore to find responses different than beads The null hypothesis is (H0): (infected == uninfected) | (infected == beads) The alt hypothesis is (HA): (infected != uninfected) & (infected != beads)

dispatch_count_lines	<i>Count the number of lines in an input file spec and add it to the meta-data.</i>
----------------------	---

Description

Sometimes the number of lines of a file is a good proxy for some aspect of a sample. For example, jellyfish provides 1 line for every kmer observed in a sample. This function extracts that number and puts it into each cell of a sample sheet.

Usage

```
dispatch_count_lines(
  meta,
  search,
  input_file_spec,
  verbose = verbose,
  species = "*",
  basedir = "preprocessing",
  type = "genome",
  subtype = "gene",
  tag = "ID",
  new_spec = NULL,
  inverse = FALSE
)
```

Arguments

meta	Input metadata
search	Pattern to count
input_file_spec	Input file specification to hunt down the file of interest.
verbose	Print diagnostic information while running?
species	Specify a species to search for.
basedir	Root directory containing the files/logs of metadata.
type	Add columns for only the genome mapping and/or rRNA by default.
inverse	Count the lines that do <code>_not_</code> match the pattern.

dispatch_csv_search *Pull some information from a csv/tsv file.*

Description

This function is a bit more generic than the others, but it grabs from a column of a csv/tsv file.

Usage

```
dispatch_csv_search(
  meta,
  column,
  input_file_spec,
  file_type = "csv",
  chosen_func = NULL,
  species = "*",
  type = "genome",
  subtype = "gene",
  tag = "ID",
  basedir = "preprocessing",
  which = "first",
  verbose = FALSE,
  ...
)
```

Arguments

meta	Input metadata
column	Column to yank from
input_file_spec	Input file specification to hunt down the file of interest.
file_type	csv or tsv?
chosen_func	If set, use this function to summarize the result.
species	Specify a species, or glob it.
type	Specify a type of search, usually genome and/or rRNA.
basedir	Root directory containing the files/logs of metadata.
which	Take the first entry, or some subset.
verbose	Print diagnostic information while running?
...	Other arguments for glue.

`dispatch_fasta_lengths`*Get the lengths of sequences from a fasta file.*

Description

Get the lengths of sequences from a fasta file.

Usage

```
dispatch_fasta_lengths(  
  meta,  
  input_file_spec,  
  verbose = verbose,  
  basedir = "preprocessing"  
)
```

Arguments

<code>meta</code>	Input metadata
<code>input_file_spec</code>	Input file specification to hunt down the file of interest.
<code>verbose</code>	Print diagnostic information while running?
<code>basedir</code>	Root directory containing the files/logs of metadata.

`dispatch_filename_search`*Pull out the filename matching an input spec*

Description

This is useful for putting the count table name into a metadata file.

Usage

```
dispatch_filename_search(  
  meta,  
  input_file_spec,  
  verbose = verbose,  
  species = "*",  
  type = "genome",  
  subtype = "gene",  
  tag = "ID",  
  basedir = "preprocessing",  
  new_spec = NULL  
)
```

Arguments

meta	Input metadata
input_file_spec	Input file specification to hunt down the file of interest.
verbose	Print diagnostic information while running?
species	Specify a species to search for, or '*' for anything.
type	Some likely filename searches may be for genome vs. rRNA vs other feature types.
basedir	Root directory containing the files/logs of metadata.

dispatch_gc	<i>Pull GC content into the metadata sheet.</i>
-------------	---

Description

As the name suggests, this only works for fasta files.

Usage

```
dispatch_gc(meta, input_file_spec, verbose = FALSE, basedir = "preprocessing")
```

Arguments

meta	Input metadata
input_file_spec	Input file specification to hunt down the file of interest.
verbose	Print diagnostic information while running?
basedir	Root directory containing the files/logs of metadata.

dispatch_metadata_extract	<i>This is basically just a switch and set of regexes for finding the numbers of interest in the various log files.</i>
---------------------------	---

Description

When I initially wrote this, it made sense to me to have it separate from the top-level function. I am not sure that is true now, having slept on it.

Usage

```
dispatch_metadata_extract(
  meta,
  entry_type,
  input_file_spec,
  specification,
  basedir = "preprocessing",
  verbose = FALSE,
  new_spec = NULL,
  species = "*",
  type = "genome",
  subtype = "gene",
  tag = "ID",
  ...
)
```

Arguments

meta	Starting metadata
entry_type	String which defines the type of log entry to hunt down. If the specification does not include a column, this will be used as the column name to write to the metadata.
input_file_spec	Glue specification defining the log file for each sample to hunt down.
specification	This is the reason I am thinking having this as a separate function might be stupid. I added it to make it easier to calculate ratios of column_x/column_y; but it is a def-facto argument to either get rid of input_file_spec as an arg or to just get rid of this function.
basedir	Root directory containing the files/logs of metadata.
verbose	used for testing regexes.
species	Choose a specific species for which to search (for filenames generally).
type	Set the type of file to search.
...	passed to glue to add more variables to the file spec.

Value

Vector of entries which will be used to populate the new column in the metadata.

dispatch_metadata_ratio

Given two metadata columns, print a ratio.

Description

Given two metadata columns, print a ratio.

Usage

```
dispatch_metadata_ratio(
  meta,
  numerator_column = NULL,
  denominator_column = NULL,
  digits = 3,
  numerator_add = FALSE,
  verbose = FALSE,
  as = "numeric",
  species = "*"
)
```

Arguments

meta	metadata, contains the column names!
numerator_column	what it says on the tin.
denominator_column	what it says on the tin.
digits	Number of significant digits to keep in the output.
numerator_add	Add this column to the numerator in case one needs multiple columns.
verbose	unused for the moment.

dispatch_regex_search *Generic dispatcher to hunt down useful information from logs.*

Description

Given the metadata, a couple of regular expressions, and a filename specification, this should be able to pull out the interesting number(s) from one logfile per sample from the metadata.

Usage

```
dispatch_regex_search(
  meta,
  search,
  replace,
  input_file_spec,
  species = "*",
  basedir = "preprocessing",
  extraction = "\\1",
  which = "first",
  new_spec = NULL,
  as = NULL,
  verbose = FALSE,
  type = "genome",
  ...
)
```

Arguments

meta	Input metadata.
search	regex used to go hunting for the line of interest.
replace	probably the same regex with parentheses in place for gsub().
input_file_spec	filename extractor expression.
species	Specify a species or glob it.
basedir	Root directory containing the files/logs of metadata.
extraction	the replacement portion of gsub(). I am thinking to make it possible to have this function return more interesting outputs if this changes, but for the moment I am sort of assuming \1 will always suffice.
which	Usually 'first', which means grab the first match and get out.
as	Coerce the output to a specific data type (numeric/character/etc).
verbose	For testing regexes.
type	Make explicit the type of data (genome/rRNA/Tx/etc).
...	Used to pass extra variables to glue for finding files.

dispatch_sum_column *Note: This is not taking some important things into account yet.*

Description

Note: This is not taking some important things into account yet.

Usage

```
dispatch_sum_column(
  meta,
  input_file_spec,
  verbose = verbose,
  species = "*",
  basedir = "preprocessing",
  type = "genome",
  subtype = "gene",
  new_spec = NULL,
  tag = "ID"
)
```

divide_seq	<i>Express a data frame of counts as reads per pattern per million.</i>
------------	---

Description

This uses a sequence pattern rather than length to normalize sequence. It is essentially fancy pants rpkms.

Usage

```
divide_seq(counts, ...)
```

Arguments

counts	Read count matrix.
...	Options I might pass from other functions are dropped into arglist.

Value

The RPseqM counts

See Also

[edgeR] [Rsamtools::FaFile()] [Biostrings::PDict()] [Biostrings::vcountPDict()] [GenomeInfoDb] [GenomicRanges]

Examples

```
## Not run:
cptam <- divide_seq(cont_table, fasta = "mgas_5005.fasta.xz", gff = "mgas_5005.gff.xz")

## End(Not run)
```

do_batch	<i>Actually runs the batch method, this more than anything shows that hpgl_norm is too complicated.</i>
----------	---

Description

Actually runs the batch method, this more than anything shows that hpgl_norm is too complicated.

Usage

```
do_batch(
  count_table,
  method = "raw",
  design,
  batch1 = "batch",
  current_state = NULL,
  current_design = NULL,
```

```

    expt_state = NULL,
    surrogate_method = "be",
    surrogates = NULL,
    low_to_zero = FALSE,
    cpus = 4,
    batch2 = NULL,
    noscale = TRUE,
    adjust_method = "ruv",
    batch_step = 4
  )

```

Arguments

count_table	The counts in their current state.
method	Batch/SV method to employ.
design	Experimental design, requiring columns named 'condition' and 'batch'.
current_state	State of the data before messing with it.
adjust_method	Method to use to modify the counts after finding the surrogates.
batch_step	Choose when to perform this in the set of normalization tasks.
...	Extra arguments passed to sva and friends.

do_pairwise	<i>Generalize pairwise comparisons</i>
-------------	--

Description

I want to multithread my pairwise comparisons, this is the first step in doing so.

Usage

```
do_pairwise(type, ...)
```

Arguments

type	Which type of pairwise comparison to perform
...	Set of arguments intended for limma_pairwise(), edger_pairwise(), and friends.

Details

Used to make parallel operations easier.

Value

Result from limma/deseq/edger/basic

See Also

[all_pairwise()]

do_topgo

*An attempt to make topgo invocations a bit more standard.***Description**

My function 'simple_topgo()' was excessively long and a morass of copy/pasted fragments. This attempts to simplify that and converge on a single piece of code for all the methodologies provided by topgo.

Usage

```
do_topgo(
  type,
  go_map = NULL,
  fisher_genes = NULL,
  ks_genes = NULL,
  selector = "topDiffGenes",
  sigforall = TRUE,
  numchar = 300,
  pval_column = "adj.P.Val",
  overwrite = FALSE,
  cutoff = 0.05,
  densities = FALSE,
  pval_plots = TRUE
)
```

Arguments

type	Type of topgo search to perform: fisher, KS, EL, or weight.
go_map	Mappings of gene and GO IDs.
fisher_genes	List of genes used for fisher analyses.
ks_genes	List of genes used for KS analyses.
selector	Function to use when selecting genes.
sigforall	Provide significance metrics for all ontologies observed, not only the ones deemed statistically significant.
numchar	A limit on characters printed when printing topgo tables (used?)
pval_column	Column from which to extract DE p-values.
overwrite	Overwrite an existing gene ID/GO mapping?
cutoff	Define 'significant'?
densities	Perform gene density plots by ontology?
pval_plots	Print p-values plots as per clusterProfiler?

Value

List of results from the various tests in topGO.

See Also

[topGO]

download_gbk

A genbank accession downloader scurrilously stolen from ape.

Description

This takes and downloads genbank accessions.

Usage

```
download_gbk(accessions = "AE009949", write = TRUE)
```

Arguments

accessions	An accession – actually a set of them.
write	Write the files? Otherwise return a list of the strings

Details

Tested in test_40ann_biomartgenbank.R In this function I stole the same functionality from the ape package and set a few defaults so that it hopefully fails less often.

Value

A list containing the number of files downloaded and the character strings acquired.

Author(s)

The ape authors with some modifications by atb.

See Also

[ape]

Examples

```
written <- download_gbk(accessions = "AE009949")
written$written_file
```

download_microbesonline_files

Download the various file formats from microbesoline.

Description

Microbesonline provides an interesting set of file formats to download. Each format proves useful under one condition or another, ergo this defaults to iterating through them all and getting every file.

Usage

```
download_microbesonline_files(id = "160490", type = NULL)
```

Arguments

id	Species ID to query.
type	File type(s) to download, if left null it will grab the genbank, tab, protein fasta, transcript fasta, and genome.

Value

List describing the files downloaded and their locations.

dream_pairwise	<i>Set up a model matrix and set of contrasts for pairwise comparisons using voom/limma.</i>
----------------	--

Description

Creates the set of all possible contrasts and performs them using voom/limma.

Usage

```
dream_pairwise(
  input = NULL,
  model_fstring = "~ 0 + condition + batch",
  null_fstring = "~",
  model_svs = NULL,
  extra_contrasts = NULL,
  annot_df = NULL,
  libsize = NULL,
  filter = TRUE,
  limma_method = "ls",
  limma_robust = FALSE,
  voom_norm = "none",
  limma_trend = FALSE,
  force = FALSE,
  keepers = NULL,
  keep_underscore = TRUE,
  adjust = "BH",
  ...
)
```

Arguments

input	Dataframe/vector or expt class containing count tables, normalization state, etc.
extra_contrasts	Some extra contrasts to add to the list. This can be pretty neat, lets say one has conditions A,B,C,D,E and wants to do (C/B)/A and (E/D)/A or (E/D)/(C/B) then use this with a string like: "c_vs_b_ctrla = (C-B)-A, e_vs_d_ctrla = (E-D)-A, de_vs_cb = (E-D)-(C-B),"
annot_df	Data frame for annotations.
libsize	I've recently figured out that libsize is far more important than I previously realized. Play with it here.

limma_method	Choose one of limma's lm methods.
limma_robust	Make the significance estimation robust?
voom_norm	Use this method to normalize the voom inputs.
limma_trend	Add trend lines to limma's voom plot?
force	Force data which may not be appropriate for limma into it?
keepers	Perform an explicit set of contrasts instead of all.
...	Use the elipsis parameter to feed options to write_limma().
conditions	Factor of conditions in the experiment.
batches	Factor of batches in the experiment.
model_cond	Include condition in the model?
model_batch	Include batch in the model? If this is a character instead of a logical, then it is passed to all_adjusers() to attempt to find model parameters which describe surrogate variables in the data.
model_intercept	Perform a cell-means or intercept model? A little more difficult for me to understand. I have tested and get the same answer either way.
alt_model	Specify another model.

Value

List including the following information: macb = the mashing together of condition/batch so you can look at it macb_model = The result of calling model.matrix(~0 + macb) macb_fit = The result of calling lmFit(data, macb_model) voom_result = The result from voom() voom_design = The design from voom (redundant from voom_result, but convenient) macb_table = A table of the number of times each condition/batch pairing happens cond_table = A table of the number of times each condition appears (the denominator for the identities) batch_table = How many times each batch appears identities = The list of strings defining each condition by itself all_pairwise = The list of strings defining all the pairwise contrasts contrast_string = The string making up the makeContrasts() call pairwise_fits = The result from calling contrasts.fit() pairwise_comparisons = The result from eBayes() limma_result = The result from calling write_limma()

See Also

[limma] [Biobase] [deseq_pairwise()] [edger_pairwise()] [basic_pairwise()] DOI:10.1101/2023.03.17.533005

Examples

```
## Not run:
pretend <- dream_pairwise(expt)

## End(Not run)
```

ebseq_few	<i>Invoke EBMultiTest() when we do not have too many conditions to deal with.</i>
-----------	---

Description

Starting at approximately 5 conditions, ebseq becomes too unwieldy to use effectively. But, its results until then are pretty neat.

Usage

```
ebseq_few(
  data,
  conditions,
  model_fstring = "~ 0 + condition + batch",
  patterns = NULL,
  ng_vector = NULL,
  rounds = 10,
  target_fdr = 0.05,
  norm = "median"
)
```

Arguments

data	Expressionset/matrix
conditions	Factor of conditions in the data to compare.
patterns	Set of patterns as described in the ebseq documentation to query.
ng_vector	Passed along to ebmultitest().
rounds	Passed to ebseq.
target_fdr	Passed to ebseq.
norm	Normalization method to apply to the data.

See Also

[ebseq_pairwise()]

ebseq_pairwise	<i>Set up model matrices contrasts and do pairwise comparisons of all conditions using EBSeq.</i>
----------------	---

Description

Invoking EBSeq is confusing, this should help.

Usage

```
ebseq_pairwise(
  input = NULL,
  patterns = NULL,
  model_fstring = "~ 0 + condition + batch",
  null_fstring = "~",
  model_svs = NULL,
  keepers = NULL,
  ng_vector = NULL,
  rounds = 20,
  target_fdr = 0.05,
  method = "pairwise_subset",
  norm = "median",
  force = FALSE,
  keep_underscore = TRUE,
  ...
)
```

Arguments

input	Dataframe/vector or expt class containing data, normalization state, etc.
patterns	Set of expression patterns to query.
keepers	Perform a specific set of contrasts instead of all?
ng_vector	I think this is for isoform quantification, but am not yet certain.
rounds	Number of iterations for doing the multi-test
target_fdr	Definition of 'significant'
method	The default ebseq methodology is to create the set of all possible 'patterns' in the data; for data sets which are more than trivially complex, this is not tenable, so this defaults to subsetting the data into pairs of conditions.
norm	Normalization method to use.
force	Force ebseq to accept bad data (notably NA containing stuff from proteomics).
...	Extra arguments currently unused.
conditions	Not currently used, but passed from all_pairwise()
batches	Not currently used, but passed from all_pairwise()
model_cond	Not currently used, but passed from all_pairwise()
model_intercept	Not currently used, but passed from all_pairwise()
alt_model	Not currently used, but passed from all_pairwise()
model_batch	Not currently used, but passed from all_pairwise()

Value

List containing tables from ebseq, the conditions tested, and the ebseq table of conditions.

See Also

[limma_pairwise()] [deseq_pairwise()] [edger_pairwise()] [basic_pairwise()]

Examples

```
## Not run:
expt <- create_expt(metadata = "sample_sheet.xlsx", gene_info = annotations)
ebseq_de <- ebseq_pairwise(input = expt)

## End(Not run)
```

ebseq_pairwise_subset *Perform pairwise comparisons with ebseq, one at a time.*

Description

This uses the same logic as in the various *_pairwise functions to invoke the 'normal' ebseq pairwise comparison for each pair of conditions in an expressionset. It therefore avoids the strange logic inherent in the ebseq multitest function.

Usage

```
ebseq_pairwise_subset(
  input,
  model_fstring = "~ 0 + condition + batch",
  ng_vector = NULL,
  rounds = 10,
  target_fdr = 0.05,
  keepers = NULL,
  conditions = NULL,
  norm = "median",
  force = FALSE,
  keep_underscore = TRUE,
  ...
)
```

Arguments

input	Expressionset/expt to perform de upon.
ng_vector	Passed on to ebseq, I forget what this does.
rounds	Passed on to ebseq, I think it defines how many iterations to perform before return the de estimates
target_fdr	If we reach this fdr before iterating rounds times, return.
keepers	Specify a set of contrasts to perform here.
conditions	Factor of conditions in the data, used to define the contrasts.
norm	EBseq normalization method to apply to the data.
force	Flag used to force inappropriate data into the various methods.
...	Extra arguments passed downstream.
model_batch	Provided by all_pairwise() I do not think a Bayesian analysis really cares about models, but if one wished to try to add a batch factor, this would be the place to do it. It is currently ignored.
model_cond	Provided by all_pairwise(), <i>ibid</i> .

model_intercept	Ibid.
alt_model	Ibid.

Value

A pairwise comparison of the various conditions in the data.

See Also

[ebseq_pairwise()]

ebseq_size_factors	<i>Choose the ebseq normalization method to apply to the data.</i>
--------------------	--

Description

EBSeq provides three normaliation methods. Median, Quantile, and Rank. Choose among them here.

Usage

```
ebseq_size_factors(data_mtrx, norm = NULL)
```

Arguments

data_mtrx	This is exprs(expressionset)
norm	The method to pass along.

Value

a new matrix using the ebseq specific method of choice.

See Also

[EBSeq]

ebseq_two*The primary function used in my EBSeq implementation.*

Description

Most of the time, my invocation of ebseq will fall into this function.

Usage

```
ebseq_two(  
  pair_data,  
  conditions,  
  numerator = 2,  
  denominator = 1,  
  fast = TRUE,  
  ng_vector = NULL,  
  rounds = 20,  
  Alpha = NULL,  
  Beta = NULL,  
  Qtrm = 1,  
  QtrmCut = 0,  
  step1 = 1e-06,  
  step2 = 0.01,  
  thre = log(2),  
  sthre = 0,  
  filter = 10,  
  stopthre = 1e-04,  
  target_fdr = 0.05,  
  norm = "median",  
  force = FALSE  
)
```

Arguments

pair_data	Matrix containing the samples comprising two experimental factors of interest.
conditions	Factor of conditions in the data.
numerator	Which factor has the numerator in the data.
denominator	Which factor has the denominator in the data.
ng_vector	Passed to ebseq.
rounds	Passed to ebseq.
target_fdr	Passed to ebseq.
norm	Normalization method of ebseq to apply.
force	Force inappropriate data into ebseq?

Value

EBSeq result table with some extra formatting.

See Also

[ebseq_pairwise()]

edger_pairwise	<i>Set up a model matrix and set of contrasts to do pairwise comparisons using EdgeR.</i>
----------------	---

Description

This function performs the set of possible pairwise comparisons using EdgeR.

Usage

```
edger_pairwise(
  input = NULL,
  model_fstring = "~ 0 + condition + batch",
  null_fstring = "~",
  model_svs = NULL,
  extra_contrasts = NULL,
  annot_df = NULL,
  force = FALSE,
  keepers = NULL,
  filter = FALSE,
  edger_method = "long",
  edger_test = "lrt",
  keep_underscore = FALSE,
  num_surrogates = "be",
  ...
)
```

Arguments

input	Dataframe/vector or expt class containing data, normalization state, etc.
extra_contrasts	Add some extra contrasts to add to the list of pairwise contrasts. This can be pretty neat, lets say one has conditions A,B,C,D,E and wants to do (C/B)/A and (E/D)/A or (E/D)/(C/B) then use this with a string like: "c_vs_b_ctrla = (C-B)-A, e_vs_d_ctrla = (E-D)-A, de_vs_cb = (E-D)-(C-B),"
annot_df	Annotation information to the data tables?
force	Force edgeR to accept inputs which it should not have to deal with.
keepers	Ask for a specific set of contrasts instead of all.
edger_method	I found a couple/few ways of doing edger in the manual, choose with this.
...	The elipsis parameter is fed to write_edger() at the end.
conditions	Factor of conditions in the experiment.
batches	Factor of batches in the experiment.
model_cond	Include condition in the experimental model?
model_batch	Include batch in the model? In most cases this is a good thing(tm).
model_intercept	Use an intercept containing model?
alt_model	Alternate experimental model to use?

Details

Like the other `_pairwise()` functions, this attempts to perform all pairwise contrasts in the provided data set. The details are of course slightly different when using EdgeR. Thus, this uses the function `choose_binom_dataset()` to try to ensure that the incoming data is appropriate for EdgeR (if one normalized the data, it will attempt to revert to raw counts, for example). It continues on to extract the conditions and batches in the data, choose an appropriate experimental model, and run the EdgeR analyses as described in the manual. It defaults to using an experimental batch factor, but will accept a string like 'sva' instead, in which case it will use sva to estimate the surrogates, and append them to the experimental design. The `edger_method` parameter may be used to apply different EdgeR code paths as outlined in the manual. If you want to play with non-standard data, the `force` argument will round the data and shoe-horn it into EdgeR.

Value

List including the following information: `contrasts` = The string representation of the contrasts performed. `lrt` = A list of the results from calling `glmLRT()`, one for each contrast. `contrast_list` = The list of each call to `makeContrasts()` I do this to avoid running into the limit on # of contrasts addressable by `topTags()` `all_tables` = a list of tables for the contrasts performed.

See Also

[edgeR] [deseq_pairwise()] [ebseq_pairwise()] [limma_pairwise()] [basic_pairwise()] DOI:10.12688/f1000research.8987

Examples

```
## Not run:
expt <- create_expt(metadata = "metadata.xlsx", gene_info = annotations)
pretend <- edger_pairwise(expt, model_batch = "sva")

## End(Not run)
```

enrichResult-class *The enrichResult class.*

Description

I create `enrichResult` objects in each of the `xxx2enrich()`.

Details

I am not completely certain how to properly use roxygen to make available classes from another package. It looks like I should just need to do 'importClassesFrom package class', but I thought I already did that? I have a series of functions which coerce various enrichment results to DOSE's `enrichResult`. I thought this class was actually in a package named soemthing like 'enrich' but I think that was just one of my fever dreams. In any event, I am going to mess around here and try to stop the error: '## Error in getClass(Class, where = topenv(parent.frame())): ## "enrichResult" is not a defined class' from making me sad.

One note, this seems only to be a problem in my containerized version of `hpgltools`, opening the possibility that this is dependency mismanagement.

exclude_genes_expt	<i>A temporary alias to subset_genes</i>
--------------------	--

Description

A temporary alias to subset_genes

Usage

```
exclude_genes_expt(...)
```

Arguments

...	Parameters passed to subset_genes().
-----	--------------------------------------

exprs, expt-method	<i>A getter to pull the expression data from an expt.</i>
--------------------	---

Description

A getter to pull the expression data from an expt.

Usage

```
## S4 method for signature 'expt'
exprs(object)
```

Arguments

expt	An expt.
------	----------

exprs, SummarizedExperiment-method	<i>A getter to pull the expression data from a SummarizedExperiment.</i>
------------------------------------	--

Description

A getter to pull the expression data from a SummarizedExperiment.

Usage

```
## S4 method for signature 'SummarizedExperiment'
exprs(object)
```

Arguments

expt	A SummarizedExperiment.
------	-------------------------

```
exprs<-, ExpressionSet, data.frame-method
```

A setter to put the expression data into an expt.

Description

A setter to put the expression data into an expt.

Usage

```
## S4 replacement method for signature 'ExpressionSet, data.frame'
exprs(object) <- value
```

Arguments

object	ExpressionSet to modify.
value	New expression data.

```
exprs<-, expt, ANY-method
```

A setter to put the expression data into an expt.

Description

A setter to put the expression data into an expt.

Usage

```
## S4 replacement method for signature 'expt, ANY'
exprs(object) <- value
```

Arguments

expt	An expt.
------	----------

```
exprs<-, SummarizedExperiment, ANY-method
```

A setter to put the expression data to a SummarizedExperiment.

Description

A setter to put the expression data to a SummarizedExperiment.

Usage

```
## S4 replacement method for signature 'SummarizedExperiment, ANY'
exprs(object) <- value
```

Arguments

object	A SummarizedExperiment.
--------	-------------------------

expt

An expt is an ExpressionSet superclass with a shorter name.

Description

It is also a simple list so that one may summarize it more simply, provides colors and some slots to make one's life easier. It is created via the function `create_expt()` which perhaps should be changed.

Usage

```
expt(...)
```

Arguments

... Parameters for `create_expt()`

Details

Another important caveat: `expressionSets` and their methods are all S4; but I did not want to write S4 methods, so I made my `expt` a S3 class. As a result, in order to make use of `exprs`, `notes`, `pData`, `fData`, and `friends`, I made use of `setMethod()` to set up calls for the `expressionSet` portion of the `expt` objects.

Slots

`title` Title for the `expressionSet`.

`notes` Notes for the `expressionSet` (redundant with `S4 notes()`).

`design` Copy of the experimental metadata (redundant with `pData()`).

`annotation` Gene annotations (redundant with `fData()`).

`gff_file` filename of a gff file which feeds this data.

`state` What is the state of the data vis a vis normalization, conversion, etc.

`conditions` Usually the condition column from `pData`.

`batches` Usually the batch column from `pData`.

`libsize` Library sizes of the data in its current state.

`colors` Chosen colors for plotting the data.

`tximport` Data provided by `tximport()` to create the `exprs()` data.

`extract_abundant_genes`*Extract the sets of genes which are significantly more abundant than the rest.*

Description

Given the output of `something_pairwise()`, pull out the genes for each contrast which are the most/least abundant. This is in contrast to `extract_significant_genes()`. That function seeks out the most changed, statistically significant genes.

Usage

```
extract_abundant_genes(  
  pairwise,  
  according_to = "deseq",  
  n = 100,  
  z = NULL,  
  unique = FALSE,  
  excel = "excel/abundant_genes.xlsx",  
  ...  
)
```

Arguments

<code>pairwise</code>	Output from <code>_pairwise()</code> .
<code>according_to</code>	What tool(s) define 'most'? One may use <code>deseq</code> , <code>edger</code> , <code>limma</code> , <code>basic</code> , <code>all</code> .
<code>n</code>	How many genes to pull?
<code>z</code>	Instead take the distribution of abundances and pull those past the given <code>z</code> score.
<code>unique</code>	One might want the subset of unique genes in the top- <code>n</code> which are unique in the set of available conditions. This will attempt to provide that.
<code>excel</code>	Excel file to write.
<code>...</code>	Arguments passed into <code>arglist</code> .

Value

The set of most/least abundant genes by contrast/tool.

See Also

`openxlsx`

extract_coefficient_scatter

Perform a coefficient scatter plot of a limma/deseq/edger/basic table.

Description

Plot the gene abundances for two coefficients in a differential expression comparison. By default, genes past 1.5 z scores from the mean are colored red/green.

Usage

```
extract_coefficient_scatter(
  output,
  toptable = NULL,
  type = "limma",
  x = 1,
  y = 2,
  z = 1.5,
  logfc = NULL,
  n = NULL,
  z_lines = FALSE,
  loess = FALSE,
  alpha = 0.4,
  color_low = "#DD0000",
  color_high = "#7B9F35",
  coefficient_column = "condition"
)
```

Arguments

output	Result from the de_ family of functions, all_pairwise, or combine_de_tables().
toptable	Chosen table to query for abundances.
type	Query limma, deseq, edger, or basic outputs.
x	The x-axis column to use, either a number or name.
y	The y-axis column to use.
z	Define the range of genes to color (FIXME: extend this to p-value and fold-change).
logfc	Set a fold-change cutoff for coloring points in the scatter plot (currently not supported.)
n	Set a top-n fold-change for coloring the points in the scatter plot (this should work, actually).
z_lines	Add lines to show the z-score demarcations.
loess	Add a loess estimation (This is slow.)
alpha	How see-through to make the dots.
color_low	Color for the genes less than the mean.
color_high	Color for the genes greater than the mean.

See Also

[plot_linear_scatter()]

Examples

```
## Not run:
expt <- create_expt(metadata = "some_metadata.xlsx", gene_info = annotations)
pairwise_output <- all_pairwise(expt)
scatter_plot <- extract_coefficient_scatter(pairwise_output,
                                           type = "deseq", x = "uninfected", y = "infected")

## End(Not run)
```

extract_de_plots	<i>Make a MA plot of some limma output with pretty colors and shapes.</i>
------------------	---

Description

Yay pretty colors and shapes! This function should be reworked following my rewrite of combine_de_tables(). It is certainly possible to make the logic here much simpler now.

Usage

```
extract_de_plots(
  pairwise,
  combined = NULL,
  type = NULL,
  invert = FALSE,
  invert_colors = c(),
  numerator = NULL,
  denominator = NULL,
  alpha = 0.4,
  z = 1.5,
  n = NULL,
  lfc_cutoff = 1,
  p_cutoff = 0.05,
  adjp = TRUE,
  found_table = NULL,
  p_type = "adj",
  color_high = NULL,
  color_low = NULL,
  loess = FALSE,
  z_lines = FALSE,
  label = 10,
  label_column = "hgnc_symbol"
)
```

Arguments

pairwise	The result from all_pairwise(), which should be changed to handle other invocations too.
----------	--

combined	Result from one of the combine_de_table functions.
type	Type of table to use: deseq, edger, limma, basic.
invert	Invert the plot?
invert_colors	vector of new colors.
numerator	Use this factor as the numerator.
denominator	Use this factor as the denominator.
alpha	Use this transparency.
z	z-score cutoff for coefficient significance.
n	Choose the top/bottom-n by logFC.
adjp	Use adjusted p-value?
found_table	Result from edger to use, left alone it chooses the first.
p_type	Adjusted or raw pvalues?
color_high	Color to use for the 'high' genes.
color_low	Color to use for the 'low' genes.
loess	Add a loess estimator to the coefficient plot?
z_lines	Add the z-score lines?
label	Label this number of top-diff genes.
label_column	Use this column for labelling genes.
logfc	What logFC to use for the MA plot horizontal lines.
pval	Cutoff to define 'significant' by p-value.

Value

a plot!

See Also

[plot_ma_de()] [plot_volcano_de()]

Examples

```
## Not run:
prettyplot <- edger_ma(all_aprwise) ## [sic, I'm witty! and can spell]

## End(Not run)
```

```
extract_eupath_orthologs
```

Given 2 species names from the eupathdb, make orthology tables between them.

Description

The eupathdb provides such a tremendous wealth of information. For me though, it is difficult sometimes to boil it down into just the bits of comparison I want for 1 species or between 2 species. A singularly common question I am asked is: "What are the most similar genes between species x and y among these two arbitrary parasites?" There are lots of ways to poke at this question: run BLAST/fasta36, use biomaRt, query the ortholog tables from the eupathdb, etc. However, in all these cases, it is not trivial to ask the next question: What about: a:b and b:a? This function attempts to address that for the case of two eupath species from the same domain. (tritrypdb/fungidb/etc.) It does however assume that the sqlite package has been installed locally, if not it suggests you run the make_organismdbi function in order to do that.

Usage

```
extract_eupath_orthologs(
  db,
  master = "GID",
  query_species = NULL,
  id_column = "ORTHOLOGS_GID",
  org_column = "ORTHOLOGS_ORGANISM",
  group_column = "ANNOT_GENE_ORTHOMCL_NAME",
  name_column = "ORTHOLOGS_PRODUCT",
  count_column = "ORTHOLOGS_COUNT",
  print_speciesnames = FALSE,
  webservice = "eupathdb"
)
```

Arguments

db	Species name (subset) from one eupath database.
master	Primary keytype to use for indexing the various tables.
query_species	A list of exact species names to search for. If uncertain about them, add print_speciesnames=TRUE and be ready for a big blob of text. If left null, then it will pull all species.
id_column	What column in the database provides the set of ortholog IDs?
org_column	What column provides the species name?
group_column	Ortholog group column name.
name_column	Name of the gene for this group.
count_column	Name of the column with the count of species represented.
print_speciesnames	Dump the species names for diagnostics?
webservice	Which eupathdb project to query?

Details

One other important caveat: this function assumes queries in the format 'table_column' where in this particular instance, the table is further assumed to be the ortholog table.

Value

A big table of orthoMCL families, the columns are:

1. GID: The gene ID
2. ORTHOLOG_ID: The gene ID of the associated ortholog.
3. ORTHOLOG_SPECIES: The species of the associated ortholog.
4. ORTHOLOG_URL: The OrthoMCL group ID's URL.
5. ORTHOLOG_COUNT: The number of all genes from all species represented in this group.
6. ORTHOLOG_GROUP: The family ID
7. QUERIES_IN_GROUP: How many of the query species are represented in this group?
8. GROUP_REPRESENTATION: ORTHOLOG_COUNT / the number of possible species.

Author(s)

atb

extract_go	<i>Extract a set of geneID to GOID mappings from a suitable data source.</i>
------------	--

Description

Like extract_lengths above, this is primarily intended to read gene ID and GO ID mappings from a OrgDb/OrganismDbi object.

Usage

```
extract_go(db, metadf = NULL, keytype = "ENTREZID")
```

Arguments

db	Data source containing mapping information.
metadf	Data frame containing extant information.
keytype	Keytype used for querying

Value

Dataframe of 2 columns: geneID and goID.

See Also

[AnnotationDbi]

```
extract_interesting_goseq
```

Filter a goseq significance search

Description

Given a goseq result, use some simple filters to pull out the categories of likely interest.

Usage

```
extract_interesting_goseq(
  godata,
  expand_categories = TRUE,
  pvalue = 0.05,
  minimum_interesting = 1,
  adjust = 0.05,
  padjust_method = "BH"
)
```

Arguments

godata	goseq result
expand_categories	Extract GO terms from GO.db and add them to the table
pvalue	Significance filter.
minimum_interesting	The category should have more than this number of elements.
adjust	Adjusted p-value filter.
padjust_method	Method for adjusting the p-values.

```
extract_keepers
```

When a list of 'keeper' contrasts is specified, extract it from the data.

Description

This is the most interesting of the extract_keeper functions. It must check that the numerators and denominators match the desired contrast and flip the signs in the logFCs when appropriate.

Usage

```
extract_keepers(
  extracted,
  keepers,
  table_names,
  all_coefficients,
  apr,
  adjp,
  annot_df,
```

```

    includes,
    excludes,
    padj_type,
    fancy = FALSE,
    loess = FALSE,
    lfc_cutoff = 1,
    p_cutoff = 0.05,
    format_sig = 4,
    plot_colors = plot_colors,
    z = 1.5,
    alpha = 0.4,
    z_lines = FALSE,
    label = 10,
    label_column = "hgnc_symbol",
    wanted_genes = NULL,
    scale_p = FALSE
)

## S4 method for signature 'list,character'
extract_keepers(
  extracted,
  keepers,
  table_names,
  all_coefficients,
  apr,
  adjp,
  annot_df,
  includes,
  excludes,
  padj_type,
  fancy = FALSE,
  loess = FALSE,
  lfc_cutoff = 1,
  p_cutoff = 0.05,
  format_sig = 4,
  plot_colors = plot_colors,
  z = 1.5,
  alpha = 0.4,
  z_lines = FALSE,
  label = 10,
  label_column = "hgnc_symbol",
  scale_p = FALSE
)

```

Arguments

<code>extracted</code>	Tables extracted from the <code>all_pairwise</code> data.
<code>keepers</code>	In this case, one may assume either <code>NULL</code> or <code>'all'</code> .
<code>table_names</code>	The set of tables produced by <code>all_pairwise()</code> .
<code>all_coefficients</code>	The set of all experimental conditions in the experimental metadata.
<code>apr</code>	The result from <code>all_pairwise()</code> , containing the limma/edger/deseq/etc data.

adjp	Pull out the adjusted p-values from the data?
annot_df	What annotations should be added to the table?
includes	List of predicates by method.
excludes	Set of genes to exclude.
padj_type	Choose a specific p adjustment.
fancy	Include larger pdf/svg plots with the xlsx output?
loess	Add a loess to plots?
lfc_cutoff	Passed for volcano/MA plots and defining 'significant'
p_cutoff	Passed for volcano/MA plots and defining 'significant'
format_sig	Number of significant digits for stuff like pvalues.
plot_colors	Define what colors should be used for 'up'/'down'
z	Define significantly away from the identity line in a coefficient plot.
alpha	Use this alpha transparency for plots.
z_lines	Include lines denoting significant z-scores?
label	When not NULL, label this many genes.
label_column	Try using this column for labeling genes.

Value

The extracted, but with more stuff at the end!

Methods (by class)

- `extract_keepers(extracted = list, keepers = character)`: Use a character vector instead of a list.

<code>extract_lengths</code>	<i>Take gene/exon lengths from a suitable data source (gff/TxDb/OrganismDbi)</i>
------------------------------	--

Description

Primarily goseq, but also other tools on occasion require a set of gene IDs and lengths. This function is responsible for pulling that data from either a gff, or TxDb/OrganismDbi.

Usage

```
extract_lengths(
  db = NULL,
  gene_list = NULL,
  type = "GenomicFeatures::transcripts",
  id = "TXID",
  possible_types = c("GenomicFeatures::genes", "GenomicFeatures::cds",
    "GenomicFeatures::transcripts"),
  ...
)
```

Arguments

db	Object containing data, if it is a string then a filename is assumed to a gff file.
gene_list	Set of genes to query.
type	Function name used for extracting data from TxDb objects.
id	Column from the resulting data structure to extract gene IDs.
possible_types	Character list of types I have previously used.
...	More arguments are passed to arglist.

Value

Dataframe containing 2 columns: ID, length

See Also

[GenomicFeatures]

extract_linear_regression

Gather the models and perform forest plots to look at various regression analyses.

Description

Gather the models and perform forest plots to look at various regression analyses.

Usage

```
extract_linear_regression(  
  meta,  
  query = "condition",  
  multivariable = TRUE,  
  scale = TRUE,  
  intercept = FALSE,  
  factors = NULL,  
  excel = NULL  
)
```

Arguments

meta	Experimental design
query	Factor to query against
multivariable	If set to FALSE, this will iterate over every factor individually.
intercept	Set an intercept? (unused)
factors	Set of factors to query
excel	output excel file.

```
extract_logistic_regression
```

Invoke what I think is an appropriate logistical regression model.

Description

The current implementation uses `lm()` and assumes everything is a linear model, this will attempt to invoke an appropriate logistic model via `glm()` and provide similar/identical tables/plots.

Usage

```
extract_logistic_regression(
  design,
  query = "condition",
  multivariable = TRUE,
  factors = NULL,
  family = "binomial",
  conf = 0.95,
  scale = TRUE,
  excel = NULL,
  intercept = FALSE
)
```

Arguments

<code>design</code>	Experimental design, I need to change this it is not a matrix.
<code>query</code>	Response variable.
<code>multivariable</code>	When not true, this will iterate over every factor individually.
<code>factors</code>	set of factors to query against the query.
<code>family</code>	The family passed to <code>glm</code> .
<code>conf</code>	Confidence interval chosen for plotting.
<code>excel</code>	Output <code>xlsx</code> file to which we print the <code>f</code> values etc.

Details

A reference to myself regarding families: gaussian: identity, log, inverse binomial: logit, probit, cauchit Gamma: inverse, identity, log ?? ooo Gamma.log etc quasi: logit, probit, cloglog, identity, inverse, log $1/\mu^2$, sqrt

For the purposes of a 'normal' logistic regression, I think 'binomial' is sufficient.

extract_mayu_pps_fdr	<i>Read output from mayu to get the IP/PP number corresponding to a given FDR value.</i>
----------------------	--

Description

Read output from mayu to get the IP/PP number corresponding to a given FDR value.

Usage

```
extract_mayu_pps_fdr(file, fdr = 0.01)
```

Arguments

file	Mayu output file.
fdr	Chosen fdr value to acquire.

Value

List of two elements: the full mayu table sorted by fdr and the number corresponding to the chosen fdr value.

extract_metadata	<i>Pull metadata from a table (xlsx/xls/csv/whatever)</i>
------------------	---

Description

I find that when I acquire metadata from a paper or collaborator, annoyingly often there are many special characters or other shenanigans in the column names. This function performs some simple sanitizations. In addition, if I give it a filename it calls my generic 'read_metadata()' function before sanitizing.

Usage

```
extract_metadata(
  metadata,
  id_column = "sampleid",
  fill = NULL,
  fill_condition = TRUE,
  fill_batch = TRUE,
  keep_underscore = TRUE,
  sanitize = TRUE,
  ...
)
```

Arguments

metadata	file or df of metadata
id_column	Column in the metadat containing the sample names.
fill	Fill missing data with this.
fill_condition	Add a condition column if there is not one?
fill_batch	Add a batch column if there is not one?
sanitize	Perform my various sanitizers on the data?
...	Arguments to pass to the child functions (read_csv etc).

Value

Metadata dataframe hopefully cleaned up to not be obnoxious.

Examples

```
## Not run:
sanitized <- extract_metadata("some_random_supplemental.xls")
saniclean <- extract_metadata(some_goofy_df)

## End(Not run)
```

extract_msraw_data	<i>Read a bunch of mzXML files to acquire their metadata.</i>
--------------------	---

Description

I have had difficulties getting the full set of correct parameters for a DDA/DIA experiment. After some poking, I eventually found most of these required prameters in the mzXML raw files. Ergo, this function uses them. 20190310: I had forgotten about the mzR library. I think much (all?) of this is redundant with respect to it and perhaps should be removed in deference to the more complete and fast implementation included in mzR.

Usage

```
extract_msraw_data(
  metadata,
  write_windows = TRUE,
  id_column = "sampleid",
  file_column = "raw_file",
  allow_window_overlap = FALSE,
  start_add = 0,
  format = "mzXML",
  parallel = TRUE,
  savefile = NULL,
  ...
)
```

Arguments

metadata	Data frame describing the samples, including the mzXML filenames.
write_windows	Write out SWATH window frames.
id_column	What column in the sample sheet provides the ID for the samples?
file_column	Which column in the sample sheet provides the filenames?
allow_window_overlap	What it says on the tin, some tools do not like DIA windows to overlap, if TRUE, this will make sure each annotated window starts at the end of the previous window if they overlap.
start_add	Another strategy is to just add a static amount to each window.
format	Currently this handles mzXML or mzML files.
parallel	Perform operations using an R foreach cluster?
savefile	If not null, save the resulting data structure to an rda file.
...	Extra arguments, presumably color palettes and column names and stuff like that.

Value

List of data extracted from every sample in the MS run (DIA or DDA).

extract_mzML_scans	<i>Parse a mzML file and return the relevant data.</i>
--------------------	--

Description

This does the actual work for `extract_scan_data()`. This leveres mzR to provide the data and goes a step further to pull out the windows acquired in the MS/MS scan and print them in formats acceptable to TPP/OpenMS (eg. with and without headers).

Usage

```
extract_mzML_scans(
  file,
  id = NULL,
  write_acquisitions = TRUE,
  allow_window_overlap = FALSE,
  start_add = 0
)
```

Arguments

file	Input mzML file to parse.
id	Chosen ID for the given file.
write_acquisitions	Write acquisition windows.
allow_window_overlap	Some downstream tools cannot deal with overlapping windows. Toggle that here.
start_add	Other downstream tools appear to expect some padding at the beginning of each window. Add that here.

Value

The list of metadata, scan data, etc from the mzXML file.

extract_mzXML_scans	<i>Parse a mzXML file and return the relevant data.</i>
---------------------	---

Description

This does the actual work for `extract_scan_data()`. When I wrote this function, I had forgotten about the `mzR` library; with that in mind, this seems to give a bit more information and be a bit faster than my short tests with `mzR` (note however that my tests were to compare `mzR` parsing `mzML` files vs. this function with `mzXML`, which is a classic apples to oranges).

Usage

```
extract_mzXML_scans(
  file,
  id = NULL,
  write_acquisitions = TRUE,
  allow_window_overlap = FALSE,
  start_add = 0
)
```

Arguments

<code>file</code>	Input mzXML file to parse.
<code>id</code>	Chosen ID for the given file.
<code>write_acquisitions</code>	Write acquisition windows.
<code>allow_window_overlap</code>	Some downstream tools cannot deal with overlapping windows. Toggle that here.
<code>start_add</code>	Other downstream tools appear to expect some padding at the beginning of each window. Add that here.

Details

This goes a step further to pull out the windows acquired in the MS/MS scan and print them in formats acceptable to TPP/OpenMS (eg. with and without headers).

Value

The list of metadata, scan data, etc from the mzXML file.

```
extract_peprophet_data
```

Get some data from a peptideprophet run.

Description

I am not sure what if any parameters this should have, but it seeks to extract the useful data from a peptide prophet run. In the situation in which I wish to use it, the input command was: > xinteract -dDECOY_ -OARPPd -Nfdr_library.xml comet_result.pep.xml Eg. It is a peptideprophet result provided by TPP. I want to read the resulting xml table and turn it into a data.table so that I can plot some metrics from it.

Usage

```
extract_peprophet_data(pepxml, decoy_string = "DECOY_", ...)
```

Arguments

pepxml	The file resulting from the xinteract invocation.
decoy_string	What prefix do decoys have in the data.
...	Catch extra arguments passed here, currently unused.

Value

data table of all the information I saw fit to extract The columns are: * protein: The name of the matching sequence (DECOYs allowed here) * decoy: TRUE/FALSE, is this one of our decoys? * peptide: The sequence of the matching spectrum. * start_scan: The scan in which this peptide was observed * end_scan: Ibid * index This seems to just increment * precursor_neutral_mass: Calculated mass of this fragment assuming no isotope shenanigans (yeah, looking at you C13). * assumed_charge: The expected charge state of this peptide. * retention_time_sec: The time at which this peptide eluted during the run. * peptide_prev_aa: The amino acid before the match. * peptide_next_aa: and the following amino acid. * num_tot_proteins: The number of matches not counting decoys. * num_matched_ions: How many ions for this peptide matched? * tot_num_ions: How many theoretical ions are in this fragment? * matched_ion_ratio: num_matched_ions / tot_num_ions, bigger is better! * cal_neutral_pep_mass: This is redundant with precursor_neutral_mass, but recalculated by peptideProphet, so if there is a discrepancy we should yell at someone! * massdiff How far off is the observed mass vs. the calculated? (also redundant with massd later) * num_tol_term: The number of peptide termini which are consistent with the cleavage (hopefully 2), but potentially 1 or even 0 if digestion was bad. (redundant with ntt later) * num_missed_cleavages: How many cleavages must have failed in order for this to be a good match? * num_matched_peptides: Number of alternate possible peptide matches. * xcorr: cross correlation of the experimental and theoretical spectra (this is supposedly only used by sequest, but I seem to have it here...) * deltacn: The normalized difference between the xcorr values for the best hit and next best hit. Thus higher numbers suggest better matches. * deltacnstar: Apparently 'important for things like phospho-searches containing homologous top-scoring peptides when analyzed by peptideprophet...' – the comet release notes. * spscore: The raw value of preliminary score from the sequest algorithm. * sprank: The rank of the match in a preliminary score. 1 is good. * expect: E-value of the given peptide hit. Thus how many identifications one expect to observe by chance, lower is therefore better * prophet_probability: The peptide prophet probability score, higher is better. * fval: 0.6(the dot function + 0.4(the delta dot function) - (the dot bias penalty function) – which is to say... well I dunno,

but it is supposed to provide information about how similar this match is to other potential matches, so I presume higher means the match is more ambiguous. * ntt: Redundant with num_tol_term above, but this time from peptide prophet. * nmc: Redundant with num_missed_cleavages, except it coalesces them. * massd: Redundant with massdiff * isomassd: The mass difference, but taking into account stupid C13. * RT: Retention time * RT_score: The score of the retention time! * modified_peptides: A string describing modifications in the found peptide * variable_mods: A comma separated list of the variable modifications observed. * static_mods: A comma separated list of the static modifications observed.

extract_pyprophet_data

Read a bunch of scored swath outputs from pyprophet to acquire their metrics.

Description

This function is mostly cribbed from the other extract_ functions in this file. With it, I hope to be able to provide some metrics of a set of openswath runs, thus potentially opening the door to being able to objectively compare the same run with different options and/or different runs.

Usage

```
extract_pyprophet_data(
    metadata,
    pyprophet_column = "diascored",
    savefile = NULL,
    ...
)
```

Arguments

metadata	Data frame describing the samples, including the mzXML filenames.
pyprophet_column	Which column from the metadata provides the requisite filenames?
savefile	If not null, save the data from this to the given filename.
...	Extra arguments, presumably color palettes and column names and stuff like that.

Details

Likely columns generated by exporting OpenMS data via pyprophet include: transition_group_id: Incrementing ID of the transition in the MS(.ppq) library used for matching (I am pretty sure). decoy: Is this match of a decoy peptide? run_id: This is a bizarre encoding of the run, OpenMS/pyprophet re-encodes the run ID from the filename to a large signed integer. filename: Which raw mzXML file provides this particular intensity value? rt: Retention time in seconds for the matching peak group. assay_rt: The expected retention time after normalization with the iRT. (how does the iRT change this value?) delta_rt: The difference between rt and assay_rt irt: (As described in the abstract of Claudia Escher's 2012 paper: "Here we present iRT, an empirically derived dimensionless peptide-specific value that allows for highly accurate RT prediction. The iRT of a peptide is a fixed number relative to a standard set of reference iRT-peptides that can be transferred across laboratories and chromatographic systems.") assay_irt: The iRT observed in the actual chromatographic run.

delta_irt: The difference. I am seeing that all the delta iRTs are in the -4000 range for our actual experiment; since this is in seconds, does that mean that it is ok as long as they stay in a similar range? id: unique long signed integer for the peak group. sequence: The sequence of the matched peptide fullunimodpeptidename: The sequence, but with unimod formatted modifications included. charge: The assumed charge of the observed peptide. mz: The m/z value of the precursor ion. intensity: The sum of all transition intensities in the peak group. aggr_prec_peak_area: Semi-colon separated list of intensities (peak areas) of the MS traces for this match. aggr_prec_peak_apex: Intensity peak apexes of the MS1 traces. leftwidth: The start of the peak group in seconds. rightwidth: The end of the peak group in seconds. peak_group_rank: When multiple peak groups match, which one is this? d_score: I think this is the score as returned by openMS (higher is better). m_score: I am pretty sure this is the result of a SELECT QVALUE operation in pyprophet. aggr_peak_area: The intensities of this fragment ion separated by semicolons. aggr_peak_apex: The intensities of this fragment ion separated by semicolons. aggr_fragment_annotation: Annotations of the fragment ion traces by semicolon. proteinname: Name of the matching protein. m_score_protein_run_specific: I am guessing the fdr for the pvalue for this run. mass: Mass of the observed fragment.

Value

List of data from each sample in the pyprophet scored DIA run.

extract_scan_data	<i>Read a mzML/mzXML file and extract from it some important meta-data.</i>
-------------------	---

Description

When working with swath data, it is fundamentally important to know the correct values for a bunch of the input variables. These are not trivial to acquire. This function attempts to make this easier (but slow) by reading the mzXML file and parsing out helpful data.

Usage

```
extract_scan_data(
    file,
    id = NULL,
    write_acquisitions = TRUE,
    format = "mzXML",
    allow_window_overlap = FALSE,
    start_add = 0
)
```

Arguments

file	Filename to read.
id	An id to give the result.
write_acquisitions	If a filename is provided, write a tab separated table of windows.
format	Either mzXML or mzML.
allow_window_overlap	One may choose to force windows to not overlap.
start_add	Add a minute to the start of the windows to avoid overlaps?

Value

List containing a table of scan and precursor data.

extract_siggenes	<i>Alias for extract_significant_genes because I am dumb.</i>
------------------	---

Description

Alias for extract_significant_genes because I am dumb.

Usage

```
extract_siggenes(...)
```

Arguments

... The parameters for extract_significant_genes()

Value

It should return a reminder for me to remember my function names or change them to something not stupid.

extract_significant_genes	<i>Extract the sets of genes which are significantly up/down regulated from the combined tables.</i>
---------------------------	--

Description

Given the output from combine_de_tables(), extract the genes in which we have the greatest likely interest, either because they have the largest fold changes, lowest p-values, fall outside a z-score, or are at the top/bottom of the ranked list.

Usage

```
extract_significant_genes(
  combined,
  according_to = "all",
  lfc = 1,
  p = 0.05,
  sig_bar = TRUE,
  z = NULL,
  n = NULL,
  min_mean_exprs = NULL,
  exprs_column = NULL,
  top_percent = NULL,
  p_type = "adj",
  invert_barplots = FALSE,
```



```

    excel = NULL,
    fc_column = NULL,
    p_column = NULL,
    siglfc_cutoffs = c(0, 1, 2),
    column_suffix = TRUE,
    gmt = FALSE,
    category = "category",
    fancy = FALSE,
    phenotype_name = "phenotype",
    set_name = "set",
    current_id = "ENSEMBL",
    comparison = "orequal",
    required_id = "ENTREZID",
    min_gmt_genes = 10,
    ...
)

```

Arguments

combined	Output from combine_de_tables().
according_to	What tool(s) decide 'significant'? One may use the deseq, edger, limma, basic, meta, or all.
lfc	Log fold change to define 'significant'.
p	(Adjusted)p-value to define 'significant'.
sig_bar	Add bar plots describing various cutoffs of 'significant'?
z	Z-score to define 'significant'.
n	Take the top/bottom-n genes.
min_mean_exprs	Add a minimum expression value.
exprs_column	Use this column to define expression.
top_percent	Use a percentage to get the top-n genes.
p_type	use an adjusted p-value?
invert_barplots	Invert the significance barplots as per Najib's request?
excel	Write the results to this excel file, or NULL.
fc_column	Column in the DE data containing the foldchange values.
p_column	Column in the DE data containing the pvalues.
siglfc_cutoffs	Set of cutoffs used to define levels of 'significant.'
column_suffix	Used to help determine which columns are used to find significant genes via logfc/p-value.
gmt	Write a gmt file using this result?
category	When writing gmt files, set the category here.
fancy	Write fancy plots with the xlsx file?
phenotype_name	When writing gmt files, set the phenotype flag here.
set_name	When writing gmt files, assign the set here.
current_id	Choose the current ID type for an output gmt file.
comparison	The cutoff may be '> <' or '<= >='.

required_id	Choose the desired ID type for an output gmt file.
min_gmt_genes	Define the minimum number of genes in a gene set for writing a gmt file.
...	Arguments passed into arglist.

Value

The set of up-genes, down-genes, and numbers therein.

See Also

[combine_de_tables](#)

factor_rsquared	<i>Collect the r^2 values from a linear model fitting between a singular value decomposition and factor.</i>
-----------------	---

Description

Collect the r^2 values from a linear model fitting between a singular value decomposition and factor.

Usage

```
factor_rsquared(datum, fact, type = "factor")
```

Arguments

datum	Result from corpcor::fast.svd.
fact	Experimental factor from the original data.
type	Make this categorical or continuous with factor/continuous.

Value

The r^2 values of the linear model as a percentage.

See Also

[corpcor] [stats::lm()]

fData,expt-method	<i>A getter to pull the gene annotation data from an expt.</i>
-------------------	--

Description

A getter to pull the gene annotation data from an expt.

Usage

```
## S4 method for signature 'expt'
fData(object)
```

Arguments

expt	An expt.
------	----------

fData, SummarizedExperiment-method

A getter to pull the gene annotation data from a SummarizedExperiment.

Description

A getter to pull the gene annotation data from a SummarizedExperiment.

Usage

```
## S4 method for signature 'SummarizedExperiment'
fData(object)
```

Arguments

object A SummarizedExperiment.

fData<-, expt, ANY-method

A setter to put the gene annotation data into an expt.

Description

A setter to put the gene annotation data into an expt.

Usage

```
## S4 replacement method for signature 'expt,ANY'
fData(object) <- value
```

Arguments

expt An expt.

fData<-, SummarizedExperiment, ANY-method

A setter to put the gene annotation data into a SummarizedExperiment.

Description

A setter to put the gene annotation data into a SummarizedExperiment.

Usage

```
## S4 replacement method for signature 'SummarizedExperiment,ANY'
fData(object) <- value
```

Arguments

object A SummarizedExperiment.

features_greater_than *Count the number of features(genes) greater than x in a data set.*

Description

Sometimes I am asked how many genes have $\geq x$ counts. Well, here you go.

Usage

```
features_greater_than(data, cutoff = 1, hard = TRUE, inverse = FALSE)
```

Arguments

data	Dataframe/exprs/matrix/whatever of counts.
cutoff	Minimum number of counts.
hard	Greater-than is hard, greater-than-equals is not.
inverse	when inverted, this provides features less than the cutoff.

Details

Untested as of 2016-12-01 but used with Lucia. I think it would be interesting to iterate this function from small to large cutoffs and plot how the number of kept genes decreases.

Value

A list of two elements, the first comprised of the number of genes greater than the cutoff, the second with the identities of said genes.

See Also

[Biobase]

Examples

```
## Not run:
features <- features_greater_than(expt)
fewer <- features_greater_than(expt, cutoff = 100)

## End(Not run)
```

`features_in_single_condition`

I want an easy way to answer the question: what features are in only condition x?

Description

The answer to this lies in a combination of `subset_expt()` and `features_greater_than()`.

Usage

```
features_in_single_condition(  
  expt,  
  cutoff = 2,  
  factor = "condition",  
  chosen = NULL  
)
```

Arguments

<code>expt</code>	An experiment to query.
<code>cutoff</code>	What is the minimum number of counts required to define 'included.'
<code>factor</code>	What metadata factor to query?
<code>chosen</code>	Either choose a subset or all conditions to query.

Value

A set of features.

See Also

[`subset_expt()`]

Examples

```
## Not run:  
unique_genes  
  
## End(Not run)
```

features_less_than	<i>Do features_greater_than() inverted!</i>
--------------------	---

Description

Do features_greater_than() inverted!

Usage

```
features_less_than(...)
```

Arguments

... Arguments passed to features_greater_than()

Value

The set of features less than whatever you would have done with features_greater_than().

See Also

[features_greater_than()]

filter_counts	<i>Call various count filters.</i>
---------------	------------------------------------

Description

This calls the various filtering functions in genefilter along with suggestions made in our lab meetings; defaulting to the threshold based filter suggested by Hector.

Usage

```
filter_counts(
  count_table,
  method = "cbcb",
  p = 0.01,
  A = 1,
  k = 1,
  cv_min = 0.01,
  cv_max = 1000,
  thresh = 2,
  min_samples = 2,
  ...
)
```

Arguments

count_table	Some counts to filter.
method	Filtering method to apply (cbcb, pofa, kofa, cv right now).
p	Used by genefilter's pofa().
A	Also for pofa().
k	Used by genefilter's kofa().
cv_min	Used by genefilter's cv().
cv_max	Also used by cv().
thresh	Minimum threshold across samples for cbcb.
min_samples	Minimum number of samples for cbcb.
...	More options might be needed, especially if I fold cv/p/etc into ...

Value

Data frame of filtered counts.

See Also

[genefilter]

Examples

```
## Not run:
new <- filter_counts(old)

## End(Not run)
```

filter_scd

Perform a series of filters on a single-cell dataset.

Description

This function should perform a series of relatively consistent filters on a single-cell dataset, with options to play with the various filters and their parameters.

Usage

```
filter_scd(
  scd,
  min_num_rna = 200,
  max_num_rna = NULL,
  min_pct_ribo = 5,
  max_pct_ribo = NULL,
  remerge = NULL,
  max_pct_mito = 15,
  min_pct_mito = NULL,
  mito_pattern = "^mt-",
  ribo_pattern = "^Rp[sl]",
  min_gene_counts = 3,
  verbose = FALSE
)
```

Arguments

scd	Single Cell Dataset to filter.
min_num_rna	Drop cells with fewer than this number of observed RNA species.
max_num_rna	An unlikely filter for maximum number of RNAs.
min_pct_ribo	Drop cells with less than this percentage of ribosomal protein RNAs observed.
max_pct_ribo	Drop cells with more than this percentage of ribosomal protein RNAs observed.
remerge	Merge the data back if there are multiple assays.
max_pct_mito	Drop cells with more than this percentage of mitochondrial RNA observed.
min_pct_mito	Drop cells with less than this percentage of mitochondrial RNA observed.
mito_pattern	Regex pattern to search RNA symbols for mitochondrial species.
ribo_pattern	Regex pattern to search RNA symbols for ribosomal protein species.
min_gene_counts	Drop genes across cells which are observed less than this number of times, I don't expect many of these.
verbose	Be chatty about what you are doing?

Value

Filtered scd

find_subseq_target_temp

Find a subsequence with a target PCR temperature.

Description

Given a relatively large sequence, this function will iteratively remove a single nucleotide and recalculate the TM until the TM falls to the target temperature.

Usage

```
find_subseq_target_temp(
  sequence,
  target = 53,
  direction = "forward",
  verbose = FALSE
)
```

Arguments

sequence	Starting sequence.
target	Desire TM of the final sequence.
direction	What strand is expected for annealing this primer?
verbose	Be chatty?

find_working_dataset	<i>Search a mart for a usable dataset.</i>
----------------------	--

Description

Search a mart for a usable dataset.

Usage

```
find_working_dataset(mart, trydataset, species)
```

Arguments

mart	Biomart instance to poke at in an attempt to find a dataset.
trydataset	Dataset to attempt to query.
species	Species at the mart for which to search.

find_working_mart	<i>Find a functional biomart instance.</i>
-------------------	--

Description

In my experience, the various biomart mirrors are not varyingly likely to be functional at any given time. In addition, I often find it useful to use an archive instance rather than the most recent ensembl instance. This function therefore iterates over the various mirrors; or if archive = TRUE it will try a series of archive servers from 1, 2, and 3 years ago.

Usage

```
find_working_mart(  
  default_hosts = c("useast.ensembl.org", "uswest.ensembl.org", "www.ensembl.org",  
    "asia.ensembl.org"),  
  trymart = "ENSEMBL_MART_ENSEMBL",  
  archive = FALSE,  
  year = NULL,  
  month = NULL  
)
```

Arguments

default_hosts	List of biomart mirrors to try.
trymart	Specific mart to query.
archive	Try an archive server instead of a mirror? If this is a character, it will assume it is a specific archive hostname.
year	Choose specific year(s) for the archive servers?
month	Choose specific month(s) for the archive servers?

Value

Either a mart instance or NULL if no mart was forthcoming.

See Also

[biomaRt::useMart()] [biomaRt::listMarts()]

flanking_sequence	<i>Extract sequence flanking a set of annotations (generally coding sequences)</i>
-------------------	--

Description

Given a set of annotations and genome, one might want to get the set of adjacent sequences.

Usage

```
flanking_sequence(
  bsgenome,
  annotation,
  distance = 200,
  type = "gene",
  prefix = ""
)
```

Arguments

bsgenome	Genome sequence
annotation	Set of annotations
distance	How far from each annotation is desired?
type	What type of annotation is desired?
prefix	Provide a prefix to the names to distinguish them from the existing annotations.

Value

List of sequences before and after each sequence.

See Also

[load_gff_annotations()] [GenomicRanges] [IRanges]

gather_cp_genes	<i>Collect gene IDs from a table and make them readable.</i>
-----------------	--

Description

Collect gene IDs from a table and make them readable.

Usage

```
gather_cp_genes(table, mappings, new = "ORF", primary_key = 1)
```

Arguments

table	Gene table from (initially) clusterProfiler.
mappings	Table of mapped gene IDs.
new	String used to disambiguate mappings when it is not provided by the table.
primary_key	Column name to use when extracting IDs.

gather_eupath_utrs_padding

Given an eupathdb species lacking UTR boundaries, extract an arbitrary region before/after each gene.

Description

This is a very domain-specific function.

Usage

```
gather_eupath_utrs_padding(
  species_name = "Leishmania major",
  entry = NULL,
  webservice = "tritrypdb",
  padding = 200,
  ...
)
```

Arguments

species_name	Species name for which to query the eupathdb.
entry	EuPathDB metadatum entry.
webservice	If specified, makes the query faster, I always used tritrypdb.org.
padding	Number of nucleotides to gather.
...	Extra arguments for the various EuPathDB functions.

Value

Set of padding UTR sequences/coordinates.

gather_genes_orgdb	<i>Use the orgdb instances from clusterProfiler to gather annotation data for GO.</i>
--------------------	---

Description

Since clusterProfiler no longer builds gomaps, I need to start understanding how to properly get information from orgDBs.

Usage

```
gather_genes_orgdb(goseq_data, orgdb_go, orgdb_ensembl)
```

Arguments

goseq_data	Some data from goseq and friends.
orgdb_go	The orgDb instance with GO data.
orgdb_ensembl	The orgDb instance with ensembl data.

Value

GO mapping

See Also

[goseq]

gather_masses	<i>Use BRAIN to find the peptide mass from a sequence.</i>
---------------	--

Description

This rounds the avgMass from BRAIN to deal with isotopes, maybe this should be changed.

Usage

```
gather_masses(sequence)
```

Arguments

sequence	Sequence to count.
----------	--------------------

Value

Rounded average mass.

`gather_ontology_genes` *Given a set of goseq data from `simple_goseq()`, make a list of genes represented in each ontology.*

Description

This function uses the GO2ALLEG data structure to reverse map ontology categories to a list of genes represented. It therefore assumes that the GO2ALLEG.rda data structure has been deposited in `pwd()`. This in turn may be generated by `clusterProfilers buildGOMap()` function if it doesn't exist. For some species it may also be auto-generated. With little work this can be made much more generic, and it probably should.

Usage

```
gather_ontology_genes(
  result,
  ontology = NULL,
  column = "over_represented_pvalue",
  pval = 0.1,
  include_all = FALSE,
  ...
)
```

Arguments

<code>result</code>	List of results as generated by <code>simple_*</code> ().
<code>ontology</code>	Ontology to search (MF/BP/CC).
<code>column</code>	Which column to use for extracting ontologies?
<code>pval</code>	Maximum accepted pvalue to include in the list of categories to cross reference.
<code>include_all</code>	Include all genes in the ontology search?
<code>...</code>	Extra options without a purpose just yet.

Value

Data frame of categories/genes.

See Also

[`simple_goseq()`]

Examples

```
## Not run:
data <- simple_goseq(sig_genes = limma_output, lengths = annotation_df, goids = goids_df)
genes_in_cats <- gather_genes(data, ont='BP')

## End(Not run)
```

gather_preprocessing_metadata

Automagically fill in a sample sheet with the results of the various preprocessing tools.

Description

I am hoping to fill this little function out with a bunch of useful file specifications and regular expressions. If I do a good job, then it should become trivial to fill in a sample sheet with lots of fun useful numbers in preparations for creating a nice table S1. I am thinking to split this up into sections for trimming/mapping/etc. But for the moment I just want to add some specifications/regexes and see if it proves itself robust. If Theresa reads this, I think this is another good candidate for a true OO implementation. E.g. make a base-class for the metadata and use S4 multi-dispatch to pick up different log files. I wrote the downstream functions with this in mind already, but I am too stupid/lazy to do the full implementation until I am confident that these functions/ideas actually have merit.

Usage

```
gather_preprocessing_metadata(
  starting_metadata = NULL,
  specification = NULL,
  basedir = "preprocessing",
  new_metadata = NULL,
  species = "*",
  type = "genome",
  subtype = "gene",
  tag = "ID",
  verbose = FALSE,
  id_column = 1,
  md5 = FALSE,
  ...
)
```

Arguments

starting_metadata	Existing sample sheet or NULL. When NULL it will look in basedir for subdirectories not named 'test' and containing subdirectories named 'scripts' and use them to create an empty sample sheet.
specification	List containing one element for each new column to append to the sample sheet. Each element in turn is a list containing column names and/or input filenames (and presumably other stuff as I think of it).
basedir	Root directory containing the files/logs of metadata.
new_metadata	Filename to which to write the new metadata
species	Define a desired species when file hunting.
type	Define a feature type when file hunting.
verbose	Currently just used to debug the regexes.

... This is one of the few instances where I used ... intelligently. Pass extra variables to the file specification and glue will pick them up (note the species entries in the example specifications).

Value

For the moment it just returns the modified metadata, I suspect there is something more useful it should do.

gather_utrs_padding	<i>Take a BSgenome and data frame of chr/start/end/strand, provide 5' and 3' padded sequence.</i>
---------------------	---

Description

For some species, we do not have a fully realized set of UTR boundaries, so it can be useful to query some arbitrary and consistent amount of sequence before/after every CDS sequence. This function can provide that information. Note, I decided to use tibble for this so that if one accidentally prints too much it will not freak out.

Usage

```
gather_utrs_padding(
  bsgenome,
  annot_df,
  gid = NULL,
  name_column = "gid",
  chr_column = "chromosome",
  start_column = "start",
  end_column = "end",
  strand_column = "strand",
  type_column = "annot_gene_type",
  gene_type = "protein coding",
  padding = c(80, 160),
  ...
)
```

Arguments

bsgenome	BSgenome object containing the genome of interest.
annot_df	Annotation data frame containing all the entries of interest, this is generally extracted using a function in the load_something_annotations() family (load_orgdb_annotations() being the most likely).
gid	Specific GID(s) to query.
name_column	Give each gene a name using this column.
chr_column	Column name of the chromosome names.
start_column	Column name of the start information.
end_column	Ibid, end column.
strand_column	Ibid, strand.

type_column	Subset the annotation data using this column, if not null.
gene_type	Subset the annotation data using the type_column with this type.
padding	Return this number of nucleotides for each gene.
...	Arguments passed to child functions (I think none currently).

Value

Dataframe of UTR, CDS, and UTR+CDS sequences.

gather_utrs_txdb	<i>Get UTR sequences using information provided by TxDb and fiveUTRsByTranscript</i>
------------------	--

Description

For species like *Mus musculus*, `load_organism_annotations(Mus.musculus)` should return a list including the requisite GRanges for the 5'/3' UTRs.

Usage

```
gather_utrs_txdb(
  bsgenome,
  fivep_utr = NULL,
  threep_utr = NULL,
  start_column = "start",
  end_column = "end",
  strand_column = "strand",
  chr_column = "seqnames",
  name_column = "group_name",
  ...
)
```

Arguments

bsgenome	A BSgenome instance containing the encoded genome.
fivep_utr	Locations of the 5' UTRs.
threep_utr	Locations of the 3' UTRs.
start_column	What column in the annotation data contains the starts?
end_column	Column in the data with the end locations.
strand_column	What column in the annotation data contains the sequence strands?
chr_column	Column in the df with the chromosome names.
name_column	Finally, where are the gene names?
...	Parameters passed to child functions.

Value

UTRs!

genefilter_cv_counts *Filter genes from a dataset outside a range of variance.*

Description

This function from genefilter removes genes surpassing a variance cutoff. It is not therefore a low-count filter per se.

Usage

```
genefilter_cv_counts(count_table, cv_min = 0.01, cv_max = 1000)
```

Arguments

count_table	Input data frame of counts by sample.
cv_min	Minimum coefficient of variance.
cv_max	Maximum coefficient of variance.

Value

Dataframe of counts without the high/low variance genes.

See Also

[genefilter::kOverA()]

Examples

```
## Not run:  
  filtered_table = genefilter_kofa_counts(count_table)  
  
## End(Not run)
```

genefilter_kofa_counts

Filter low-count genes from a data set using genefilter's kOverA().

Description

This is the most similar to the function suggested by Hector I think.

Usage

```
genefilter_kofa_counts(count_table, k = 1, A = 1)
```

Arguments

count_table	Input data frame of counts by sample.
k	Minimum number of samples to have >A counts.
A	Minimum number of counts for each gene's sample in kOverA().

Value

Dataframe of counts without the low-count genes.

See Also

[genefilter::kOverA()]

Examples

```
## Not run:
  filtered_table = genefilter_kofa_counts(count_table)

## End(Not run)
```

genefilter_pofa_counts

Filter low-count genes from a data set using genefilter's pOverA().

Description

I keep thinking this function is pofa... oh well. Of the various tools in genefilter, this one to me is the most intuitive. Take the ratio of counts/samples and make sure it is \geq a score.

Usage

```
genefilter_pofa_counts(count_table, p = 0.01, A = 100)
```

Arguments

count_table	Input data frame of counts by sample.
p	Minimum proportion of each gene's counts/sample to be greater than a minimum(A).
A	Minimum number of counts in the above proportion.

Value

Dataframe of counts without the low-count genes.

See Also

[genefilter::pOverA()]

Examples

```
## Not run:
  filtered_table = genefilter_pofa_counts(count_table)

## End(Not run)
```

generate_expt_colors	<i>Set up default colors for a data structure containing usable metadata</i>
----------------------	--

Description

In theory this function should be useful in any context when one has a blob of metadata and wants to have a set of colors. Since my taste is utterly terrible, I rely entirely upon RColorBrewer, but also allow one to choose his/her own colors.

Usage

```
generate_expt_colors(
  sample_definitions,
  cond_column = "condition",
  by = "sampleid",
  ...
)
```

Arguments

sample_definitions	Metadata, presumably containing a 'condition' column.
cond_column	Which column in the sample data provides the set of 'conditions' used to define the colors?
by	Name the factor of colors according to this column.
...	Other arguments like a color palette, etc.

Value

Colors!

See Also

[create_expt()]

generate_nn_groups	<i>Given an n-dimensional matrix, try some KNN-esque clustering on it.</i>
--------------------	--

Description

I want some functions to help me understand clustering. This is a first pass at that goal.

Usage

```
generate_nn_groups(
  mtrx,
  resolution = 1,
  k = 10,
  type = "snn",
  full = TRUE,
  merge_to = NULL,
  ...
)
```

Arguments

mtrx	Matrix to cluster, usually 2d from a point plot.
resolution	Used after cluster generation for making neighbor groups.
k	Used during cluster generation.
type	Define the type of clustering to perform, currently only KNN/SNN
full	Get the full set of metrics from bluster.
merge_to	Use the neighborhood collapse function to set a hard ceiling on the number of clusters in the final result.
...	Extra args for bluster.

Value

List containing the resulting groups and some information about them.

genomic_kmer_dist	<i>Use ape to generate a distance based nj tree from fasta files.</i>
-------------------	---

Description

I was thinking that a standardized version of this might be useful for Theresa's recent exploration of variants in her data.

Usage

```
genomic_kmer_dist(directory = "tree", root = NULL)
```

Arguments

directory	Directory of fasta genomes.
root	Species ID to place at the root of the tree.

Value

List containing the phylogeny and some other stuff.

genoplot_chromosome	<i>Try plotting a chromosome (region)</i>
---------------------	---

Description

genoplotr is cool, I don't yet understand it though

Usage

```
genoplot_chromosome(
  accession = "AE009949",
  start = NULL,
  end = NULL,
  plot_title = "Genome plot"
)
```

Arguments

accession	An accession to plot, this will download it.
start	First segment to plot (doesn't quite work yet).
end	Final segment to plot (doesn't quite work yet).
plot_title	Put a title on the resulting plot.

Value

Hopefully a pretty plot of a genome

See Also

[genoPlotR]

get_abundant_genes	<i>Find the set of most/least abundant genes according to limma and friends following a differential expression analysis.</i>
--------------------	---

Description

Given a data set provided by limma, deseq, edger, etc; one might want to know what are the most and least abundant genes, much like get_sig_genes() does to find the most significantly different genes for each contrast.

Usage

```
get_abundant_genes(
  datum,
  type = "limma",
  n = NULL,
  z = NULL,
  fx = "mean",
  unique = FALSE
)
```

Arguments

datum	Output from the <code>_pairwise()</code> functions.
type	Extract abundant genes according to what?
n	Perhaps take just the top/bottom n genes.
z	Or take genes past a given z-score.
fx	Choose a function when choosing the most abundant genes.
unique	Unimplemented: take only the genes unique among the conditions surveyed.

Value

List of data frames containing the genes of interest.

See Also

`[get_sig_genes()]`

Examples

```
## Not run:
abundant <- get_abundant_genes(all_pairwise_output, type = "deseq", n = 100)
## Top 100 most abundant genes from deseq
least <- get_abundant_genes(all_pairwise_output, type = "deseq", n = 100, least = TRUE)
## Top 100 least abundant genes from deseq
abundant <- get_abundant_genes(all_pairwise_output, type = "edger", z = 1.5)
## Get the genes more than 1.5 standard deviations from the mean.

## End(Not run)
```

get_degrees

Use a vector of factors and design to count up the levels.

Description

Use a vector of factors and design to count up the levels.

Usage

```
get_degrees(design, fctrs)
```

get_expt_colors	<i>Get a named vector of colors by condition.</i>
-----------------	---

Description

Usually we give a vector of all samples by colors. This just simplifies that to one element each. Currently only used in combine_de_tables() but I think it will have use elsewhere.

Usage

```
get_expt_colors(expt, keep_underscore = TRUE)
```

Arguments

expt	Expression from which to gather colors.
------	---

Value

List of colors by condition.

get_formula_factors	<i>Simplify a model formula string to a simple vector of factors.</i>
---------------------	---

Description

I would like to be able to make my various pairwise methods generalizable, therefore I need to no longer rely on an expected pair of factors: 'condition' and 'batch', instead I want to observe the first factor and anything which follows. Thus, I will string split the formula string by punctuation and yank out the names of interest.

Usage

```
get_formula_factors(formula_string = NULL)
```

Arguments

formula_string	Formula describing the formula of interest.
----------------	---

Value

Ordered vector of factors in the formula ignoring interactions etc.

```
get_formula_factors, formula-method
```

Set method for formula input to get_formula_factors

Description

Set method for formula input to get_formula_factors

Usage

```
## S4 method for signature 'formula'
get_formula_factors(formula_string = NULL)
```

Arguments

formula_string What should have been a string, but is a formula.

Value

List describing the formula

```
get_genesizes
```

Grab gene length/width/size from an annotation database.

Description

This function tries to gather an appropriate gene length column from whatever annotation data source is provided.

Usage

```
get_genesizes(
  annotation = NULL,
  type = "gff",
  gene_type = "gene",
  type_column = "type",
  key = NULL,
  length_names = NULL,
  ...
)
```

Arguments

annotation	There are a few likely data sources when getting gene sizes, choose one with this.
type	What type of annotation data are we using?
gene_type	Annotation type to use (3rd column of a gff file).
type_column	Type identifier (10th column of a gff file).
key	What column has ID information?
length_names	Provide some column names which give gene length information?
...	Extra arguments likely for load_annotations()

Value

Data frame of gene IDs and widths.

See Also

[rtracklayer] [load_gff_annotations()]

Examples

```
pa_gff <- system.file("share", "paeruginosa_pa14.gff", package = "hpgldata")
pa_genesizes <- get_genesizes(gff = pa_gff)
head(pa_genesizes)
```

get_git_commit

Get the current git commit for hpgltools

Description

One might reasonably ask about this function: "Why?" I invoke this function at the end of my various knitr documents so that if necessary I can do a > git reset <commit id> and get back to the exact state of my code.

Usage

```
get_git_commit(gitdir = "~/hpgltools")
```

Arguments

gitdir Directory containing the git repository.

get_group_gsva_means

Create dataframe which gets the maximum within group mean gsva score for each gene set

Description

Create dataframe which gets the maximum within group mean gsva score for each gene set

Usage

```
get_group_gsva_means(gsva_scores, groups, keep_single = TRUE, method = "mean")
```

Arguments

gsva_scores Result from simple_gsva()
groups list of groups for which to calculate the means
keep_single Keep categories with only 1 element.
method mean or median?

Value

dataframe containing max_gsva_score, and within group means for gsva scores

See Also

[simple_gsva()]

get_gsvadb_names	<i>Extract the GeneSets corresponding to the provided name(s).</i>
------------------	--

Description

Many of the likely GSCs contain far more gene sets than one actually wants to deal with. This will subset them according to a the desired 'requests'.

Usage

```
get_gsvadb_names(sig_data, requests = NULL)
```

Arguments

sig_data	The pile of GeneSets, probably from GSVAdata.
requests	Character list of sources to keep.

Value

Whatever GeneSets remain.

get_identifier	<i>Get an Identifier function from a shorthand name.</i>
----------------	--

Description

I am hoping to write one for EuPathDB and some other source, thus the switch.

Usage

```
get_identifier(type)
```

Arguments

type	String name for the identifier in question.
------	---

get_individual_snps	<i>Extract the observed snps unique to individual categories in a snp set.</i>
---------------------	--

Description

The result of get_snp_sets provides sets of snps for all possible categories. This is cool and all, but most of the time we just want the results of a single group in that rather large set ($2^{\text{number of categories}}$)

Usage

```
get_individual_snps(retlist)
```

Arguments

retlist	The result from get_snp_sets().
---------	---------------------------------

get_inter_txdb	<i>Given an input gff, create intron/intergenic gff files.</i>
----------------	--

Description

I was poking around for ways to mix and match gff files and found this: <https://support.bioconductor.org/p/66003/>

Usage

```
get_inter_txdb(  
  input,  
  intron_gff = "introns.gff",  
  intergenic_gff = "intergenic.gff"  
)
```

get_kegg_compounds	<i>Gather all Compounds from all pathways for a given species.</i>
--------------------	--

Description

This function attempts to iterate over every pathway for a given abbreviation/species and extract from them the set of compounds. This was mostly copy/pasted from get_kegg_genes.

Usage

```
get_kegg_compounds(  
  pathway = "all",  
  abbreviation = NULL,  
  species = "leishmania major",  
  savefile = NULL  
)
```

Arguments

pathway	One or more pathways, all does what it says on the tin.
abbreviation	Approximately 3 character KEGG abbreviation.
species	If you do not have the abbreviation, this will try to find it.
savefile	Currently unused I think, but eventually should make a savefile of the results.

get_kegg_genes	<i>Extract the set of geneIDs matching pathways for a given species.</i>
----------------	--

Description

This uses KEGGREST to extract the mappings for all genes for a species and pathway or 'all'. Because downloading them takes a while, it will save the results to kegg_species.rda. When run interactively, it will give some information regarding the number of genes observed in each pathway.

Usage

```
get_kegg_genes(
  pathway = "all",
  abbreviation = NULL,
  species = "leishmania major",
  savefile = NULL
)
```

Arguments

pathway	Either a single pathway kegg id or 'all'.
abbreviation	Optional 3 letter species kegg id.
species	Stringified species name used to extract the 3 letter abbreviation.
savefile	Filename to which to save the relevant data.

Value

Dataframe of the various kegg data for each pathway, 1 row/gene.

See Also

[KEGGREST]

Examples

```
## Not run:
kegg_info <- get_kegg_genes(species = "Canis familiaris")

## End(Not run)
```

get_kegg_orgn	<i>Search KEGG identifiers for a given species name.</i>
---------------	--

Description

KEGG identifiers do not always make sense. For example, how am I supposed to remember that *Leishmania major* is *lmj*? This takes in a human readable string and finds the KEGG identifiers that match it.

Usage

```
get_kegg_orgn(species = "Leishmania", short = TRUE)
```

Arguments

species	Search string (Something like 'Homo sapiens').
short	Only pull the orgid?

Value

Data frame of possible KEGG identifier codes, genome ID numbers, species, and phylogenetic classifications.

See Also

[RCurl]

Examples

```
## Not run:
fun = get_kegg_orgn('Canis')
## >   Tid   orgid   species   phylogeny
## > 17 T01007   cfa Canis familiaris (dog) Eukaryotes;Animals;Vertebrates;Mammals

## End(Not run)
```

get_kegg_sub	<i>Provide a set of simple substitutions to convert geneIDs from KEGG->TriTryDB</i>
--------------	--

Description

This function should provide 2 character lists which, when applied sequentially, will result in a hopefully coherent set of mapped gene IDs matching the TriTryDB/KEGG specifications.

Usage

```
get_kegg_sub(species = "lma")
```

Arguments

species 3 letter abbreviation for a given kegg type

Value

2 character lists containing the patterns and replace arguments for gsub(), order matters!

See Also

[KEGGREST]

get_microbesonline_taxid

Extract microbesonline taxon IDs without having to click on the weird boxes at the top of the website.

Description

This should simplify getting material from microbesonline.

Usage

```
get_microbesonline_taxid(species = "Acyrrhosiphon pisum virus")
```

Arguments

species String to search the set of microbesonline taxa.

Value

NULL or 1 or more taxon ids.

See Also

[xml2]

Examples

```
coli_taxids <- get_microbesonline_taxid(species = "coli S88")  
head(coли_taxids)
```

get_msigdb_metadata	<i>Create a metadata dataframe of msigdb data, this hopefully will be usable to fill the fData slot of a gsva returned expressionset.</i>
---------------------	---

Description

Create a metadata dataframe of msigdb data, this hopefully will be usable to fill the fData slot of a gsva returned expressionset.

Usage

```
get_msigdb_metadata(
  msig_db = "msigdb_v6.2.xml",
  wanted_meta = c("ORGANISM", "DESCRIPTION_BRIEF", "AUTHORS", "PMID")
)
```

Arguments

msig_db	Filename containing the MSigDB metadata.
wanted_meta	Choose metadata columns of interest.

Value

list containing 2 data frames: all metadata from broad, and the set matching the sig_data GeneSets.

See Also

[xml2] [rvest]

get_pairwise_gene_abundances	<i>A companion function for get_abundant_genes()</i>
------------------------------	--

Description

Instead of pulling to top/bottom abundant genes, get all abundances and variances or stderr.

Usage

```
get_pairwise_gene_abundances(datum, type = "limma", excel = NULL)
```

Arguments

datum	Output from _pairwise() functions.
type	According to deseq/limma/ed ger/basic?
excel	Print this to an excel file?

Value

List containing the expression values and some metrics of variance/error.

See Also

[get_abundant_genes()]

Examples

```
## Not run:
abundance_excel <- get_pairwise_gene_abundances(combined, excel = "abundances.xlsx")
## This should provide a set of abundances after voom by condition.

## End(Not run)
```

get_plot_columns	<i>A small rat's nest of if statements intended to figure out what columns are wanted to plot a MA/Volcano from any one of a diverse set of possible input types.</i>
------------------	---

Description

I split this function away from the main body of extract_de_plots() so that I can come back to it and strip it down to something a bit more legible. Eventually I want to dispatch this logic off to separate functions depending on the class of the input.

Usage

```
get_plot_columns(data, type, p_type = "adj", adjp = TRUE)
```

Arguments

data	Data structure in which to hunt columns/data.
type	Type of method used to make the data.
p_type	Use adjusted p-values?
adjp	I think this is redundant.

Details

This function should die in a fire.

get_proportion_snp_sets	<i>Create all possible sets of variants by sample (types).</i>
-------------------------	--

Description

I like this function. It generates an exhaustive catalog of the snps by chromosome for all the various categories as defined by factor.

Usage

```
get_proportion_snp_sets(
  snp_expt,
  factor = "pathogenstrain",
  stringency = NULL,
  do_save = FALSE,
  savefile = "variants.rda",
  minmax_cutoff = 0.05,
  hetero_cutoff = 0.3
)
```

Arguments

snp_expt	Expressionset of variants.
factor	Use this metadata factor to split the data.
stringency	Allow for some wiggle room in the calls.
do_save	Save the results to an rda fil.
savefile	This is redundant with do_save.
minmax_cutoff	Cutoffs used to define homozygous vs. no-observation.
hetero_cutoff	Cutoff to define heterozygous vs. observed/homozygous

Value

A funky list by chromosome containing: 'medians', the median number of hits / position by sample type; 'possibilities', the; 'intersections', the groupings as detected by Vennerable; 'chr_data', the raw data; 'set_names', a character list of the actual names of the groupings; 'invert_names', the opposite of set_names which is to say the names of groups which do *not* include samples x,y,z; 'density', a list of snp densities with respect to chromosomes. Note that this last one is approximate as I just calculate with the largest chromosome position number, not the explicit number of nucleotides in the chromosome.

See Also

[medians_by_factor()]

Examples

```
## Not run:
expt <- create_expt(metadata, gene_information)
snp_expt <- count_expt_snps(expt)
snp_sets <- get_snp_sets(snp_expt, factor = "condition")
## This assumes a column in the metadata for the expt named 'condition'.

## End(Not run)
```

get_res	<i>Attempt to get residuals from tsne data</i>
---------	--

Description

I strongly suspect that this is not correct, but it is a start.

Usage

```
get_res(
  svd_result,
  design,
  factors = c("condition", "batch"),
  res_slot = "v",
  var_slot = "d"
)
```

Arguments

svd_result	The set of results from one of the many potential svd-ish methods.
design	Experimental design from which to get experimental factors.
factors	Set of experimental factors for which to calculate rsquared values.
res_slot	Where is the res data in the svd result?
var_slot	Where is the var data in the svd result?

Value

Data frame of rsquared values and cumulative sums.

get_sig_genes	<i>Get a set of up/down differentially expressed genes.</i>
---------------	---

Description

Take one or more criteria (fold change, rank order, (adj)p-value, z-score from median FC) and use them to extract the set of genes which are defined as 'differentially expressed.' If no criteria are provided, it arbitrarily chooses all genes outside of 1-z.

Usage

```
get_sig_genes(
  table,
  n = NULL,
  z = NULL,
  lfc = NULL,
  p = NULL,
  min_mean_exprs = NULL,
  exprs_column = "deseq_basemean",
)
```

```

    column = "logFC",
    fold = "plusminus",
    p_column = "adj.P.Val",
    comparison = "orequal"
  )

```

Arguments

table	Table from limma/edger/deseq.
n	Rank-order top/bottom number of genes to take.
z	Number of z-scores >/< the median to take.
lfc	Fold-change cutoff.
p	P-value cutoff.
min_mean_exprs	Exclude genes with less than this mean expression.
exprs_column	Use this column for filtering by expression.
column	Table's column used to distinguish top vs. bottom.
fold	Identifier reminding how to get the bottom portion of a fold-change (plusminus says to get the negative of the positive, otherwise 1/positive is taken). This effectively tells me if this is a log fold change or not.
p_column	Table's column containing (adjusted or not)p-values.
comparison	When set to orequal, use >=/<= instead of jsut >/<.

Value

Subset of the up/down genes given the provided criteria.

See Also

[extract_significant_genes()] [get_abundant_genes()]

Examples

```

## Not run:
sig_table <- get_sig_genes(table, lfc = 1)

## End(Not run)

```

```
get_sig_gsva_categories
```

Attempt to score the results from simple_gsva()

Description

This function uses a couple of methods to try to get an idea of whether the results from gsva are actually interesting. It does so via the following methods: 1. Use limma on the expressionset returned by simple_gsva(), this might provide an idea of if there are changing signatures among the sample types. 2. Perform a simplified likelihood estimate to get a sense of the significant categories.

Usage

```
get_sig_gsva_categories(  
  gsva_result,  
  cutoff = 0.95,  
  excel = "excel/gsva_subset.xlsx",  
  model_batch = FALSE,  
  factor_column = "condition",  
  factor = NULL,  
  label_size = NULL,  
  col_margin = 6,  
  row_margin = 12,  
  type = "mean"  
)
```

Arguments

gsva_result	Result from simple_gsva()
cutoff	Significance cutoff
excel	Excel file to write the results.
model_batch	Add batch to limma’s model.
factor_column	When extracting significance information, use this metadata factor.
factor	Use this metadata factor as the reference.
label_size	Used to make the category names easier to read at the expense of dropping some.
col_margin	Attempt to make heatmaps fit better on the screen with this and...
row_margin	this parameter
type	Either mean or median of the scores to return.

Value

List containing the gsva results, limma results, scores, some plots, etc.

See Also

[score_gsva_likelihoods()] [get_group_gsva_means()] [limma_pairwise()] [simple_gsva()]

get_snp_sets	<i>Collect variants associated with specific conditions.</i>
--------------	--

Description

Collect variants associated with specific conditions.

Usage

```
get_snp_sets(
  snp_expt,
  factor = "pathogenstrain",
  stringency = NULL,
  do_save = FALSE,
  savefile = "variants.rda",
  proportion = 0.9
)
```

Arguments

snp_expt	variant collection.
factor	metadata factor
stringency	method to determin 'real' variants.
do_save	Save the result?
savefile	outptu savefile.
proportion	Used with stringency.

get_yyyymm_commit	<i>Find the git commit closest to the given yyyymmdd.</i>
-------------------	---

Description

Find the git commit closest to the given yyyymmdd.

Usage

```
get_yyyymm_commit(
  gitdir = "~/hpgltools",
  version = NULL,
  year = NULL,
  month = NULL,
  day = NULL
)
```

Arguments

gitdir	Location of the git repository, I assume hpgltools.
version	String containing all yyyymmdd.
year	Chosen year which will be coerced to yyyy.
month	Chosen month coerced to mm.
day	Chosen day coerced to dd.

getEdgeWeights	<i>Plot the ontology DAG.</i>
----------------	-------------------------------

Description

This function was stolen from topgo in order to figure out where it was failing.

Usage

```
getEdgeWeights(graph)
```

Arguments

graph	Graph from topGO
-------	------------------

Value

Weights!

gff2gr	<i>Rewrite a gff file as a granges with full seqinfo if possible.</i>
--------	---

Description

Rewrite a gff file as a granges with full seqinfo if possible.

Usage

```
gff2gr(gff, type = NULL, type_column = "type")
```

Arguments

gff	Input gff file.
type	Feature type to extract.
type_column	Tag from the gff file to use when extracting the type.

`gff2irange`*Extract annotation information from a gff file into an irange object.*

Description

Try to make `import.gff` a little more robust; I acquire (hopefully) valid gff files from various sources: yeastgenome.org, microbesonline, tritrypdb, ucsc, ncbi. To my eyes, they all look like reasonably good gff3 files, but some of them must be loaded with `import.gff2`, `import.gff3`, etc. That is super annoying. Also, I pretty much always just do `as.data.frame()` when I get something valid from `rtracklayer`, so this does that for me, I have another function which returns the `iranges` etc. This function wraps `import.gff/import.gff3/import.gff2` calls in `try()` because sometimes those functions fail in unpredictable ways.

Usage

```
gff2irange(gff, type = NULL)
```

Arguments

<code>gff</code>	Gff filename.
<code>type</code>	Subset to extract.

Details

This is essentially `load_gff_annotations()`, but returns data suitable for `getSet()` This is another place which should be revisited for improvements via `mcols()`. Check `snpr` for ideas.

Value

`Iranges!` (useful for `getSeq()`.)

See Also

[`rtracklayer`] [`load_gff_annotations()`] [import.gff](#)

Examples

```
example_gff <- system.file("share", "gas.gff", package = "hpgldata")
gas_iranges <- gff2irange(example_gff)
colnames(as.data.frame(gas_iranges))
```

ggplotly_url

Add a little logic to ggplotly to simplify adding clicky link.

Description

There are some other ease of life improvements I have in a few of my plotly invocations which I should add here.

Usage

```
ggplotly_url(
  plot,
  filename = "ggplotly_url.html",
  id_column = "id",
  plot_title = NULL,
  url_info = NULL,
  tooltip = "all",
  url_column = "url"
)
```

Arguments

plot	Plot generated via ggplot2.
filename	filename to save the output html plot.
id_column	Column containing the gene IDs.
plot_title	Provide a title for the generated html file.
url_info	Either a glue() string or column of urls.
tooltip	Passed to ggplotly().
url_column	Column in the url_info containing URLs.

Value

plotly with clicky links.

ggplt

Simplify plotly ggplot conversion so that there are no shenanigans.

Description

I am a fan of ggplotly, but its conversion to an html file is not perfect. This hopefully will get around the most likely/worst problems.

Usage

```
ggplt(
  gg,
  filename = "ggplot.html",
  selfcontained = TRUE,
  libdir = NULL,
  background = "white",
  plot_title = class(gg)[[1]],
  knitrOptions = list(),
  ...
)
```

Arguments

<code>gg</code>	Plot from <code>ggplot2</code> .
<code>filename</code>	Output filename.
<code>selfcontained</code>	<code>htmlwidgets</code> : Return the plot as a self-contained file with images re-encoded base64.
<code>libdir</code>	<code>htmlwidgets</code> : Directory into which to put dependencies.
<code>background</code>	<code>htmlwidgets</code> : String for the background of the image.
<code>plot_title</code>	<code>htmlwidgets</code> : Title of the page!
<code>knitrOptions</code>	<code>htmlwidgets</code> : I am not a fan of camelCase, but nonetheless, options from <code>knitr</code> for <code>htmlwidgets</code> .
<code>...</code>	Any remaining elipsis options are passed to <code>ggplotly</code> .

Value

The final output filename

See Also

[`htmlwidgets`] [`plotly`] [`ggplot2`]

godef

Get a go long-form definition from an id.

Description

Sometimes it is nice to be able to read the full definition of some GO terms.

Usage

```
godef(go = "GO:0032432")
```

Arguments

<code>go</code>	GO ID, this may be a character or list (assuming the elements are goids).
-----------------	---

Value

Some text providing the long definition of each provided GO id.

See Also

[AnnotationDbi] [GO.db]

Examples

```
## Not run:
godef("GO:0032432")
## > GO:0032432
## > "An assembly of actin filaments that are on the same axis but may be
## > same or opposite polarities and may be packed with different levels of tightness."

## End(Not run)
```

golev

Get a go level approximation from an ID.

Description

Sometimes it is useful to know how far up/down the ontology tree a given id resides. This attempts to answer that question.

Usage

```
golev(go)
```

Arguments

go GO id, this may be a character or list (assuming the elements are goids).

Value

Set of numbers corresponding to approximate tree positions of the GO ids.

See Also

[AnnotationDbi] [GO.db]

Examples

```
## Not run:
golev("GO:0032559")
## > 3

## End(Not run)
```

golevel	<i>Get a go level approximation from a set of IDs.</i>
---------	--

Description

This just wraps golev() in mapply.

Usage

```
golevel(go = c("GO:0032559", "GO:0000001"))
```

Arguments

go Character list of IDs.

Value

Set of approximate levels within the ontology.

See Also

[golev()]

Examples

```
## Not run:
golevel(c("GO:0032559", "GO:0000001"))
## > 3 4

## End(Not run)
```

golevel_df	<i>Extract a dataframe of golevels using getGOLevel() from clusterProfiler.</i>
------------	---

Description

This function is way faster than my previous iterative golevel function. That is not to say it is very fast, so it saves the result to ontlevel.rda for future lookups.

Usage

```
golevel_df(ont = "MF", savefile = "ontlevel.rda")
```

Arguments

ont Ontology to recurse.
 savefile File to save the results for future lookups.

Value

Dataframe of goids<->highest level

See Also

[clusterProfiler]

goont

Get a go ontology name from an ID.

Description

Get a go ontology name from an ID.

Usage

```
goont(go = c("GO:0032432", "GO:0032433"))
```

Arguments

go GO id, this may be a character or list (assuming the elements are goids).

Value

The set of ontology IDs associated with the GO ids, thus 'MF' or 'BP' or 'CC'.

See Also

[AnnotationDbi] [GO.db]

Examples

```
## Not run:
goont(c("GO:0032432", "GO:0032433"))
## > GO:0032432 GO:0032433
## > "CC" "CC"

## End(Not run)
```

gosec	<i>Get a GO secondary ID from an id.</i>
-------	--

Description

Unfortunately, GOTERM's returns for secondary IDs are not consistent, so this function has to have a whole bunch of logic to handle the various outputs.

Usage

```
gosec(go = "GO:0032432")
```

Arguments

go	GO ID, this may be a character or list(assuming the elements, not names, are goids).
----	--

Value

Some text comprising the secondary GO id(s).

See Also

[AnnotationDbi] [GO.db]

Examples

```
## Not run:
gosec("GO:0032432")
## > GO:0032432
## > "GO:0000141" "GO:0030482"

## End(Not run)
```

goseq_msigdb	<i>Pass MSigDB categorical data to goseq and run it.</i>
--------------	--

Description

goseq is probably the easiest method to push varying data types into. Thus it was the first thing I thought of when looking to push MSigDB data into a GSEA method.

Usage

```
goseq_msigdb(
  sig_genes,
  signatures = "c2BroadSets",
  data_pkg = "GSVAdata",
  signature_category = "c2",
  current_id = "ENSEMBL",
  required_id = "ENTREZID",
  length_db = NULL,
  doplot = TRUE,
  adjust = 0.1,
  pvalue = 0.1,
  length_keytype = "transcripts",
  go_keytype = "entrezid",
  goseq_method = "Wallenius",
  padjust_method = "BH",
  excel = NULL,
  orgdb = "org.Hs.eg.db"
)
```

Arguments

sig_genes	Character list of genes deemed significant. I think in the current implementation this must be just a list of IDs as opposed to the full dataframe of interesting genes because we likely need to convert IDs.
signatures	Used by load_gmt_signatures(), the signature file or set.
data_pkg	Used by load_gmt_signatures().
signature_category	Ibid, but the name of the signatures group.
current_id	Used by convert_msig_ids(), when converting IDs, the name of the existing type.
required_id	What type to convert to in convert_msig_ids().
length_db	Dataframe of lengths. It is worth noting that goseq explicitly states that one might wish to use other potentially confounding factors here, but they only examine lengths in their paper. Starting with this parameter, everything is just passed directly to simple_goseq()
doplot	Print the prior plot?
adjust	passed to simple_goseq()
pvalue	passed to simple_goseq()
length_keytype	passed to simple_goseq()
go_keytype	passed to simple_goseq()
goseq_method	passed to simple_goseq()
padjust_method	passed to simple_goseq()
excel	passed to simple_goseq()
orgdb	Ideally used to help goseq collect lengths.

Value

Some goseq data!

See Also

[gsva] [goseq]

goseq_table	<i>Enhance the goseq table of gene ontology information.</i>
-------------	--

Description

While goseq has some nice functionality, the table of outputs it provides is somewhat lacking. This attempts to increase that with some extra helpful data like ontology categories, definitions, etc.

Usage

```
goseq_table(df, file = NULL)
```

Arguments

df	Dataframe of ontology information. This is intended to be the output from goseq including information like numbers/category, GOids, etc. It requires a column 'category' which contains: GO:000001 and such.
file	Csv file to which to write the table.

Value

Ontology table with annotation information included.

See Also

[goseq] [GO.db]

Examples

```
## Not run:
annotated_go = goseq_table(go_ids)
head(annotated_go, n = 1)
## >      category numDEInCat numInCat over_represented_pvalue
## > 571 GO:0006364          9      26      4.655108e-08
## >      under_represented_pvalue      qvalue ontology
## > 571      1.0000000 6.731286e-05      BP
## >      term
## > 571      rRNA processing
## >      synonym
## > 571      "35S primary transcript processing, GO:0006365"
## >      secondary      definition
## > 571 GO:0006365 Any process involved in the conversion of a primary ribosomal
##      RNA (rRNA) transcript into one or more mature rRNA molecules.

## End(Not run)
```

goseq_trees	<i>Make fun trees a la topgo from goseq data.</i>
-------------	---

Description

This seeks to force goseq data into a format suitable for topGO and then use its tree plotting function to make it possible to see significantly increased ontology trees.

Usage

```
goseq_trees(
  goseq,
  goid_map = "id2go.map",
  score_limit = 0.01,
  overwrite = FALSE,
  selector = "topDiffGenes",
  pval_column = "adj.P.Val"
)
```

Arguments

goseq	Data from goseq.
goid_map	File to save go id mapping.
score_limit	Score limit for the coloring.
overwrite	Overwrite the trees?
selector	Function for choosing genes.
pval_column	Column to acquire pvalues.

Value

A plot!

See Also

[Ramigo]

goseq2enrich	<i>Create a clusterProfiler compatible enrichResult data structure from a goseq result.</i>
--------------	---

Description

The metrics and visualization methods in clusterProfiler are the best. It is not always trivial to get non-model organisms working well with clusterProfiler. Therefore I still like using tools like topgo/goseq/gostats/gprofiler. This function and its companions seek to make them cross-compatible. Ideally, they will lead me to being able to rip out a lot of superfluous material.

Usage

```
goseq2enrich(
  retlist,
  ontology = "MF",
  cutoff = 1,
  cutoff_column = "over_represented_pvalue",
  organism = NULL,
  padjust_method = "BH"
)
```

Arguments

retlist	Result from simple_goseq().
ontology	Ontology sub-tree of interest.
cutoff	(adjusted)p cutoff.
cutoff_column	Choose a column of p-values.
organism	Currently unused.
padjust_method	Define the desired p.adjust method.

Value

enrichResult object ready to pass to things like dotplot.

gostats_kegg	<i>Use gostats() against kegg pathways.</i>
--------------	---

Description

This sets up a GSEABase analysis using KEGG pathways rather than gene ontologies. Does this even work? I don't think I have ever tested it yet. oh, it sort of does, maybe if I export it I will rembmber it.

Usage

```
gostats_kegg(
  organism = "Homo sapiens",
  pathdb = "org.Hs.egPATH",
  godb = "org.Hs.egGO"
)
```

Arguments

organism	The organism used to make the KEGG frame, human readable no taxonomic.
pathdb	Name of the pathway database for this organism.
godb	Name of the ontology database for this organism.

Value

Results from hyperGTest using the KEGG pathways.

See Also

[AnnotationDbi] [GSEABase] [Category]

`gostats_trees`

Take gostats data and print it on a tree as topGO does.

Description

This shoeorns gostats data into a format acceptable by topgo and uses it to print pretty ontology trees showing the over represented ontologies.

Usage

```
gostats_trees(  
  gostats_result,  
  goid_map = "id2go.map",  
  score_limit = 0.01,  
  overwrite = FALSE,  
  selector = "topDiffGenes",  
  pval_column = "adj.P.Val"  
)
```

Arguments

<code>gostats_result</code>	Return from <code>simple_gostats()</code> .
<code>goid_map</code>	Mapping of IDs to GO in the Ramigo expected format.
<code>score_limit</code>	Maximum score to include as 'significant'.
<code>overwrite</code>	Overwrite the <code>goid_map</code> ?
<code>selector</code>	Function to choose differentially expressed genes in the data.
<code>pval_column</code>	Column in the data to be used to extract pvalue scores.

Value

plots! Trees! oh my!

See Also

topGO `gostats`

gostats2enrich	<i>Create a clusterProfiler compatible enrichResult data structure from a gostats result.</i>
----------------	---

Description

The metrics and visualization methods in clusterProfiler are the best. It is not always trivial to get non-model organisms working well with clusterProfiler. Therefore I still like using tools like topgo/goseq/gostats/gprofiler. This function and its companions seek to make them cross-compatible. Ideally, they will lead me to being able to rip out a lot of superfluous material.

Usage

```
gostats2enrich(
  retlist,
  ontology = "MF",
  cutoff = 0.1,
  cutoff_column = "qvalue",
  organism = NULL,
  padjust_method = "BH"
)
```

Arguments

retlist	Result from simple_gostats().
ontology	Ontology sub-tree of interest.
cutoff	(adjusted)p cutoff.
cutoff_column	Choose a column of p-values.
organism	Currently unused.
padjust_method	Define the desired p.adjust method.

Value

enrichResult object ready to pass to things like dotplot.

gosyn	<i>Get a go synonym from an ID.</i>
-------	-------------------------------------

Description

I think I will need to do similar parsing of the output for this function as per gosec() In some cases this also returns stuff like c("some text", "GO:someID") versus "some other text" versus NULL versus NA. This function just goes a mapply(gosn, go).

Usage

```
gosyn(go = "GO:0000001")
```

Arguments

go GO id, this may be a character or list(assuming the elements are goids).

Value

Some text providing the synonyms for the given id(s).

See Also

[AnnotationDbi] [GO.db]

Examples

```
## Not run:
text = gosyn("GO:000001")
text
## > GO:000001
## > "mitochondrial inheritance"

## End(Not run)
```

goterm

Get a go term from ID.

Description

Get a go term from ID.

Usage

```
goterm(go = "GO:0032559")
```

Arguments

go GO id or a list thereof, this may be a character or list(assuming the elements, not names, are goids).

Value

Some text containing the terms associated with GO id(s).

See Also

[AnnotationDbi] [GO.db]

Examples

```
## Not run:
goterm("GO:0032559")
## > GO:0032559
## > "adenyl ribonucleotide binding"

## End(Not run)
```

gotest	<i>Test GO ids to see if they are useful.</i>
--------	---

Description

This just wraps gotst in mapply.

Usage

```
gotest(go)
```

Arguments

go go IDs as characters.

Value

Some text

See Also

[GO.db]

Examples

```
## Not run:
gotest("GO:0032559")
## > 1
gotest("GO:0923429034823904")
## > 0

## End(Not run)
```

gprofiler2enrich	<i>Recast gProfiler data to the output class produced by clusterProfiler.</i>
------------------	---

Description

I would like to use the various clusterProfiler plots more easily. Therefore I figured it would be advantageous to coerce the various outputs from gprofiler and friends into the datastructure produced by clusterProfiler.

I would like to use the various clusterProfiler plots more easily. Therefore I figured it would be advantageous to coerce the various outputs from gprofiler and friends into the datastructure produced by clusterProfiler.

Usage

```
gprofiler2enrich(
  retlst,
  ontology = "MF",
  cutoff = 1,
  organism = NULL,
  padjust_method = "BH",
  min_go_level = 3
)
```

```
gprofiler2enrich(
  retlst,
  ontology = "MF",
  cutoff = 1,
  organism = NULL,
  padjust_method = "BH",
  min_go_level = 3
)
```

Arguments

retlst	Output from simple_gprofiler()
ontology	Category type to extract, currently only GO?
cutoff	Use a p-value cutoff to get only the significant categories?
organism	Set the orgdb organism name?
padjust_method	what it says on the tin.
retlist	Output from simple_gprofiler()

Value

enrichResult object ready to pass to things like dotplot.

The same 'enrich' datastructure produced by clusterProfiler.

graph_metrics	<i>Make lots of graphs!</i>
---------------	-----------------------------

Description

Plot out a set of metrics describing the state of an experiment including library sizes, # non-zero genes, heatmaps, boxplots, density plots, pca plots, standard median distance/correlation, and qq plots.

Usage

```
graph_metrics(
  expt,
  cormethod = "pearson",
  distmethod = "euclidean",
  title_suffix = NULL,
```

```

    qq = NULL,
    ma = NULL,
    cv = NULL,
    gene_heat = NULL,
    ...
)

```

Arguments

expt	an expt to process
cormethod	The correlation test for heatmaps.
distmethod	define the distance metric for heatmaps.
title_suffix	Text to add to the titles of the plots.
qq	Include qq plots?
ma	Include pairwise ma plots?
cv	Include coefficient of variance plots? (they are slow)
gene_heat	Include a heatmap of the gene expression data?
...	Extra parameters optionally fed to the various plots

Value

a loooong list of plots including the following:

1. nonzero = a ggplot2 plot of the non-zero genes vs library size
2. libsize = a ggplot2 bar plot of the library sizes
3. boxplot = a ggplot2 boxplot of the raw data
4. corheat = a recordPlot()ed pairwise correlation heatmap of the raw data
5. smc = a recordPlot()ed view of the standard median pairwise correlation of the raw data
6. disheat = a recordPlot()ed pairwise euclidean distance heatmap of the raw data
7. smd = a recordPlot()ed view of the standard median pairwise distance of the raw data
8. pcaplot = a recordPlot()ed PCA plot of the raw samples
9. pccable = a table describing the relative contribution of condition/batch of the raw data
10. pcars = a table describing the relative contribution of condition/batch of the raw data
11. pcavar = a table describing the variance of the raw data
12. qq = a recordPlotted() view comparing the quantile/quantiles between the mean of all data and every raw sample
13. density = a ggplot2 view of the density of each raw sample (this is complementary but more fun than a boxplot)

See Also

[plot_nonzero()] [plot_legend()] [plot_libsize()] [plot_disheat()] [plot_corheat()] [plot_topn()] [plot_pca()]
[plot_sm()] [plot_boxplot()]

Examples

```
## Not run:
toomany_plots <- graph_metrics(expt)
toomany_plots$pcaplot
norm <- normalize_expt(expt, convert = "cpm", batch = TRUE, filter_low = TRUE,
                       transform = "log2", norm = "rle")
holy_asscrackers <- graph_metrics(norm, qq = TRUE, ma = TRUE)

## End(Not run)
```

group_mean_cds_length *Average the cds length over known transcripts for a single gene.*

Description

Average the cds length over known transcripts for a single gene.

Usage

```
group_mean_cds_length(
  annot,
  gene_column = "ensembl_gene_id",
  tx_column = "ensembl_transcript_id",
  length_column = "cds_length"
)
```

Arguments

annot	Dataframe of annotations.
gene_column	Column containing the gene IDs.
tx_column	Column containing the transcript IDs.
length_column	Column containing the cds lengths.

Value

The annotations with a new column 'mean_cds_len' at the end.

guess_factors *A silly function to guesstimate factor columns in metadata.*

Description

Use the heuristic that any column with a number of different elements which is \leq (samples / ratio) has a reasonable chance of being usable as a categorical.

Usage

```
guess_factors(meta_df, ratio = 3)
```

guess_num_surrogates	<i>Use methods from sva/RUVseq to guesstimate the number of surrogates.</i>
----------------------	---

Description

Use methods from sva/RUVseq to guesstimate the number of surrogates.

Usage

```
guess_num_surrogates(
  design,
  linear_mtrx,
  log2_mtrx,
  model_svs = "svaseq",
  conditional_fstring = "~ condition",
  guess_type = "be"
)
```

guess_orgdb_keytype	<i>Iterate over keytypes looking for matches against a set of IDs.</i>
---------------------	--

Description

Sometimes, one does not know what the correct keytype is for a given set of IDs. This will hopefully find them.

Usage

```
guess_orgdb_keytype(ids, orgdb = NULL, verbose = FALSE)
```

Arguments

ids	Set of gene IDs to seek.
orgdb	Orgdb instance to iterate through.
verbose	talky talk

Value

Likely keytype which provides the desired IDs.

See Also

[org.Dm.eg.db]

Examples

```
ids <- c("Dm.9", "Dm.2294", "Dm.4971")
dm_orgdb <- "org.Dm.eg.db"
keytype_guess <- guess_orgdb_keytype(ids, dm_orgdb)
keytype_guess
```

heatmap.3

*a minor change to heatmap.2 makes heatmap.3***Description**

heatmap.2 is the devil.

Usage

```
heatmap.3(
  x,
  Rowv = TRUE,
  Colv = if (symm) "Rowv" else TRUE,
  distfun = dist,
  hclustfun = fastcluster::hclust,
  dendrogram = c("both", "row", "column", "none"),
  reorderfun = function(d, w) reorder(d, w),
  symm = FALSE,
  scale = c("none", "row", "column"),
  na.rm = TRUE,
  revC = identical(Colv, "Rowv"),
  add.expr,
  breaks,
  symbreaks = min(x < 0, na.rm = TRUE) || scale != "none",
  col = "heat.colors",
  colsep,
  rowsep,
  sepcolor = "white",
  sepwidth = c(0.05, 0.05),
  cellnote,
  notecex = 1,
  notecol = "cyan",
  na.color = par("bg"),
  trace = c("column", "row", "both", "none"),
  tracecol = "cyan",
  hline = median(breaks),
  vline = median(breaks),
  linecol = tracecol,
  margins = c(5, 5),
  ColSideColors,
  RowSideColors,
  cexRow = 0.2 + 1/log10(nr),
  cexCol = 0.2 + 1/log10(nc),
  labRow = NULL,
  labCol = NULL,
  srtRow = NULL,
  srtCol = NULL,
  adjRow = c(0, NA),
  adjCol = c(NA, 0),
  offsetRow = 0.5,
  offsetCol = 0.5,
```

```

    key = TRUE,
    keysize = 1.5,
    density.info = c("histogram", "density", "none"),
    denscol = tracecol,
    symkey = min(x < 0, na.rm = TRUE) || symbreaks,
    densadj = 0.25,
    key.title = NULL,
    key.xlab = NULL,
    key.ylab = NULL,
    key.xtickfun = NULL,
    key.ytickfun = NULL,
    key.par = list(),
    main = NULL,
    xlab = NULL,
    ylab = NULL,
    lmat = NULL,
    lhei = NULL,
    lwid = NULL,
    extrafun = NULL,
    linewidth = 1,
    ...
)

```

Arguments

x	data
Rowv	add rows?
Colv	add columns?
distfun	distance function to use
hclustfun	clustering function to use
dendrogram	which axes to put trees on
reorderfun	reorder the rows/columns?
symm	symmetrical?
scale	add the scale?
na.rm	remove nas from the data?
revC	reverse the columns?
add.expr	no clue
breaks	also no clue
symbreaks	still no clue
col	colors!
colsep	column separator
rowsep	row separator
sepcolor	color to put between columns/rows
sepwidth	how much to separate
cellnote	mur?
notecex	size of the notes

notecol	color of the notes
na.color	a parameter call to bg
trace	do a trace for rows/columns?
tracecol	color of the trace
hline	the hline
vline	the vline
linecol	the line color
margins	margins are good
ColSideColors	colors for the columns as annotation
RowSideColors	colors for the rows as annotation
cexRow	row size
cexCol	column size
labRow	hmmmm
labCol	still dont know
srtRow	srt the row?
srtCol	srt the column?
adjRow	adj the row?
adjCol	adj the column?
offsetRow	how far to place the text from the row
offsetCol	how far to place the text from the column
key	add a key?
keysize	if so, how big?
density.info	for the key, what information to add
denscol	tracecol hmm ok
symkey	I like keys
densadj	adj the dens?
key.title	title for the key
key.xlab	text for the x axis of the key
key.ylab	text for the y axis of the key
key.xtickfun	add text to the ticks of the key x axis
key.ytickfun	add text to the ticks of the key y axis
key.par	parameters for the key
main	the main title of the plot
xlab	main x label
ylab	main y label
lmat	the lmat
lhei	the lhei
lwid	the lwid
extrafun	I do enjoy me some extra fun
linewidth	the width of lines
...	because this function did not already have enough options

Value

a heatmap!

See Also

[heatmap.2](#)

hpgl_arescore

Implement the arescan function in R

Description

This function was taken almost verbatim from AREScore() in SeqTools Available at: <https://github.com/lianos/seqtools.g>
 At least on my computer I could not make that implementation work So I rewrapped its apply() calls
 and am now hoping to extend its logic a little to make it more sensitive and get rid of some of the
 spurious parameters or at least make them more transparent.

Usage

```
hpgl_arescore(
  x,
  basal = 1,
  overlapping = 1.5,
  d1.3 = 0.75,
  d4.6 = 0.4,
  d7.9 = 0.2,
  within.AU = 0.3,
  aub.min.length = 10,
  aub.p.to.start = 0.8,
  aub.p.to.end = 0.55
)
```

Arguments

x	DNA/RNA StringSet containing the UTR sequences of interest
basal	I dunno.
overlapping	default = 1.5
d1.3	default = 0.75 These parameter names are so stupid, lets be realistic
d4.6	default = 0.4
d7.9	default = 0.2
within.AU	default = 0.3
aub.min.length	default = 10
aub.p.to.start	default = 0.8
aub.p.to.end	default = 0.55

Value

a DataFrame of scores

See Also

[IRanges] [Biostrings] [GenomicRanges]

Examples

```
## Not run:
## Extract all the genes from my genome, pull a static region 120nt following the stop
## and test them for potential ARE sequences.
## FIXME: There may be an error in this example, another version I have
## handles the +/- strand genes separately, I need to return to this and check
## if it is providing the 5' UTR for 1/2 the genome, which would be
## unfortunate -- but the logic for testing remains the same.
are_candidates <- hpgl_arescore(genome)
utr_genes <- subset(lmajor_annotations, type == 'gene')
threep <- GenomicRanges::GRanges(seqnames = Rle(utr_genes[,1]),
                                ranges = IRanges(utr_genes[,3], end=(utr_genes[,3] + 120)),
                                strand = Rle(utr_genes[,5]),
                                name = Rle(utr_genes[,10]))
threep_seqstrings <- Biostrings::getSeq(lm, threep)
are_test <- hpgltools::hpgl_arescore(x = threep_seqstrings)
are_genes <- rownames(are_test[ which(are_test$score > 0), ])

## End(Not run)
```

hpgl_cor

Wrap cor() to include robust correlations.

Description

Take covRob's robust correlation coefficient and add it to the set of correlations available when one calls cor(). I should reimplement this using S4.

Usage

```
hpgl_cor(df, method = "pearson", ...)
```

Arguments

df	Data frame to test.
method	Correlation method to use. Includes pearson, spearman, kendal, robust.
...	Other options to pass to stats::cor().

Value

Some fun correlation statistics.

See Also

[robust]

Examples

```
## Not run:
  hpgl_cor(df = df)
  hpgl_cor(df = df, method = "robust")

## End(Not run)
```

hpgl_dist

*Because I am not smart enough to remember t()***Description**

It seems to me there should be a function as easy for distances as there is for correlations.

Usage

```
hpgl_dist(df, method = "euclidean", ...)
```

Arguments

df	data frame from which to calculate distances.
method	Which distance calculation to use?
...	Extra arguments for dist.

hpgl_filter_counts

*Filter low-count genes from a data set using cpm data and a threshold.***Description**

This is identical to cbc_b_filter_counts except it does not do the somewhat tortured log2CPM() but instead just uses a 4 cpm non-log threshold. It should therefore give basically the same result, but without the shenanigans.

Usage

```
hpgl_filter_counts(
  count_table,
  threshold = 2,
  min_samples = 2,
  libsize = NULL,
  ...
)
```

Arguments

count_table	Data frame of (pseudo)counts by sample.
threshold	Lower threshold of counts for each gene.
min_samples	Minimum number of samples.
libsize	Table of library sizes.
...	Arguments passed to cpm and friends.

Value

Dataframe of counts without the low-count genes.

See Also

[edgeR]

Examples

```
## Not run:
  filtered_table <- cbcfilter_counts(count_table)

## End(Not run)
```

hpgl_GOplot

A minor hack of the topGO GOplot function.

Description

This allows me to change the line widths from the default.

Usage

```
hpgl_GOplot(
  dag,
  sigNodes,
  dag.name = "GO terms",
  edgeTypes = TRUE,
  nodeShape.type = c("box", "circle", "ellipse", "plaintext")[3],
  genNodes = NULL,
  wantedNodes = NULL,
  showEdges = TRUE,
  useFullNames = TRUE,
  oldSigNodes = NULL,
  nodeInfo = NULL,
  maxchars = 30
)
```

Arguments

dag	DAG tree of ontologies.
sigNodes	Set of significant ontologies (with p-values).
dag.name	Name for the graph.
edgeTypes	Types of the edges for graphviz.
nodeShape.type	Shapes on the tree.
genNodes	Generate the nodes?
wantedNodes	Subset of the ontologies to plot.
showEdges	Show the arrows?
useFullNames	Full names of the ontologies (they can get long).

oldSigNodes	I dunno.
nodeInfo	Hmm.
maxchars	Maximum characters per line inside the shapes.

Value

Topgo plot!

See Also

[topGO]

hpgl_GroupDensity	<i>A hack of topGO's groupDensity()</i>
-------------------	---

Description

This just adds a couple wrappers to avoid errors in groupDensity.

Usage

```
hpgl_GroupDensity(object, whichGO, ranks = TRUE, rm.one = FALSE)
```

Arguments

object	TopGO enrichment object.
whichGO	Individual ontology group to compare against.
ranks	Rank order the set of ontologies?
rm.one	Remove pvalue = 1 groups?

Value

plot of group densities.

hpgl_log2cpm	<i>Converts count matrix to log2 counts-per-million reads.</i>
--------------	--

Description

Based on the method used by limma as described in the Law et al. (2014) voom paper.

Usage

```
hpgl_log2cpm(counts, lib.size = NULL)
```

Arguments

counts	Read count matrix.
lib.size	Library size.

Value

log2-CPM read count matrix.

See Also

[edgeR]

Examples

```
## Not run:
l2cpm <- hpgl_log2cpm(counts)

## End(Not run)
```

hpgl_norm

Normalize a dataframe/expt, express it, and/or transform it

Description

There are many possible options to this function. Refer to `normalize_expt()` for a more complete list.

Usage

```
hpgl_norm(
  data,
  expt_state = NULL,
  design = NULL,
  transform = "raw",
  norm = "raw",
  convert = "raw",
  batch = "raw",
  batch1 = "batch",
  batch2 = NULL,
  low_to_zero = TRUE,
  filter = "raw",
  annotations = NULL,
  fasta = NULL,
  thresh = 2,
  batch_step = 4,
  min_samples = 2,
  p = 0.05,
  k = 0.01,
  A = 1000,
  cv_min = 0.001,
  cv_max = 1,
  entry_type = "gene",
  adjust_method = "ruv",
  surrogates = "be",
  ...
)
```

Arguments

data	Some data as a df/expt/whatever.
...	I should put all those other options here

Value

edgeR's DGEList expression of a count table. This seems to me to be the easiest to deal with.

See Also

[edgeR] [DESeq2] [edgeR::cpm()] [filter_counts()] [batch_counts()] [convert_counts()] [transform_counts()]

Examples

```
## Not run:
df_raw = hpgl_norm(expt = expt) ## Only performs low-count filtering
df_raw = hpgl_norm(df = a_df, design = a_design) ## Same, but using a df
df_ql2rpkm = hpgl_norm(expt = expt, norm='quant', transform='log2',
                      convert='rpkm') ## Quantile, log2, rpkm
count_table = df_ql2rpkm$counts

## End(Not run)
```

hpgl_padjust

Wrap p.adjust to add IHW adjustments as an option.

Description

IHW and apeglm are the two new toys I found, this adds the former as a way to adjust p-values.

Usage

```
hpgl_padjust(
  data,
  pvalue_column = "pvalue",
  mean_column = "base_mean",
  method = "fdr",
  significance = 0.05,
  type = NULL
)
```

Arguments

data	Column or table containing values to adjust.
pvalue_column	Name of the column in a table containing the p-values.
mean_column	Name of the column in a table containing the mean count values to weight.
method	p adjustment method to apply.
significance	Passed to IHW
type	Assuming a DE table, what type of DE is this?

Value

Newly adjusted p-values using either `p.adjust()` or IHW.

See Also

[IHW]

hpgl_qshrink

A hacked copy of Kwame's qsmooth/qstats code.

Description

I made a couple small changes to Kwame's `qstats()` function to make it not fail when on corner-cases. I sent him a diff, but haven't checked to see if it was useful yet.

Usage

```
hpgl_qshrink(
  data = NULL,
  groups = NULL,
  refType = "mean",
  groupLoc = "mean",
  window = 99,
  groupCol = NULL,
  plot = TRUE,
  ...
)
```

Arguments

<code>data</code>	Count table to modify
<code>groups</code>	Factor of the experimental conditions
<code>refType</code>	Method for grouping conditions
<code>groupLoc</code>	Method for grouping groups
<code>window</code>	Window, for looking!
<code>groupCol</code>	Column to define conditions
<code>plot</code>	Plot the quantiles?
<code>...</code>	More options

Value

New data frame of normalized counts

See Also

[qsmooth]

Examples

```
## Not run:  
df <- hpgl_qshrink(data)  
  
## End(Not run)
```

hpgl_qstats*A hacked copy of Kwame's qsmooth/qstats code.*

Description

I made a couple small changes to Kwame's qstats() function to make it not fail when on corner-cases. I sent him a diff, but haven't checked to see if it was useful yet.

Usage

```
hpgl_qstats(data, groups, refType = "mean", groupLoc = "mean", window = 99)
```

Arguments

data	Initial count data
groups	Experimental conditions as a factor.
refType	Method to separate groups, mean or median.
groupLoc	I don't remember what this is for.
window	Window for basking!

Value

Some new data.

See Also

[matrixStats]

Examples

```
## Not run:  
qstated <- hpgl_qstats(data, conditions)  
  
## End(Not run)
```

hpgl_rpkm	<i>Reads/(kilobase(gene) * million reads)</i>
-----------	---

Description

Express a data frame of counts as reads per kilobase(gene) per million(library). This function wraps EdgeR's rpkm in an attempt to make sure that the required gene lengths get sent along.

Usage

```
hpgl_rpkm(count_table, ...)
```

Arguments

count_table	Data frame of counts, alternately an edgeR DGEList.
...	extra options including annotations for defining gene lengths.

Value

Data frame of counts expressed as rpkm.

See Also

[edgeR::rpkm()]

Examples

```
## Not run:
rpkm_df = hpgl_rpkm(df, annotations = gene_annotations)

## End(Not run)
```

hpgl_voom	<i>A slight modification of limma's voom().</i>
-----------	---

Description

Estimate mean-variance relationship between samples and generate 'observational-level weights' in preparation for linear modeling RNAseq data. This particular implementation was primarily scabbed from cbcSEQ, but changes the mean-variance plot slightly and attempts to handle corner cases where the sample design is confounded by setting the coefficient to 1 for those samples rather than throwing an unhelpful error. Also, the Elist output gets a 'plot' slot which contains the plot rather than just printing it.

Usage

```
hpgl_voom(
  dataframe,
  model = NULL,
  libsize = NULL,
  normalize.method = "none",
  span = 0.5,
  stupid = FALSE,
  logged = FALSE,
  converted = FALSE,
  ...
)
```

Arguments

<code>dataframe</code>	Dataframe of sample counts which have been normalized and log transformed.
<code>model</code>	Experimental model defining batches/conditions/etc.
<code>libsize</code>	Size of the libraries (usually provided by edgeR).
<code>normalize.method</code>	Normalization method used in <code>voom()</code> .
<code>span</code>	The span used in <code>voom()</code> .
<code>stupid</code>	Cheat when the resulting matrix is not solvable?
<code>logged</code>	Is the input data is known to be logged?
<code>converted</code>	Is the input data is known to be cpm converted?
<code>...</code>	Extra arguments are passed to <code>arglist</code> .

Value

EList containing the following information: `E` = The normalized data weights = The weights of said data `design` = The resulting design `lib.size` = The size in pseudocounts of the library `plot` = A ggplot of the mean/variance trend with a blue loess fit and red trend fit

See Also

`[limma::voom()]`

Examples

```
## Not run:
funkytown = hpgl_voom(samples, model)

## End(Not run)
```

hpgl_voomweighted	<i>A minor change to limma's voom with quality weights to attempt to address some corner cases.</i>
-------------------	---

Description

This copies the logic employed in `hpgl_voom()`. I suspect one should not use it.

Usage

```
hpgl_voomweighted(
  data,
  fun_model,
  libsize = NULL,
  normalize.method = "none",
  plot = TRUE,
  span = 0.5,
  var.design = NULL,
  method = "genebygene",
  maxiter = 50,
  tol = 1e-10,
  trace = FALSE,
  replace.weights = TRUE,
  col = NULL,
  ...
)
```

Arguments

<code>data</code>	Some data!
<code>fun_model</code>	A model for <code>voom()</code> and <code>arrayWeights()</code>
<code>libsize</code>	Library sizes passed to <code>voom()</code> .
<code>normalize.method</code>	Passed to <code>voom()</code>
<code>plot</code>	Do the plot of mean variance?
<code>span</code>	yes
<code>var.design</code>	maybe
<code>method</code>	kitty!
<code>maxiter</code>	50 is good
<code>tol</code>	I have no tolerance.
<code>trace</code>	no trace for you.
<code>replace.weights</code>	Replace the weights?
<code>col</code>	yay columns!
<code>...</code>	more arguments!

Value

a voom return

See Also

[limma::voom()]

Examples

```
## Not run:  
## No seriously, dont run this, I think it is wiser to use the functions  
## provided by limma. But this provides a place to test stuff out.  
voom_result <- hpgl_voomweighted(dataset, model)  
  
## End(Not run)
```

hpgltools

hpgltools: a suite of tools to make our analyses easier

Description

This provides a series of helpers for working with sequencing data

Details

It falls under a few main topics

- Data exploration, look for trends in sequencing data and identify batch effects or skewed distributions.
- Differential expression analyses, use DESeq2/limma/EdgeR in a hopefully robust and flexible fashion.
- Ontology analyses, use goseq/clusterProfiler/topGO/GOstats/gProfiler in hopefully robust ways.
- Perform some simple TnSeq analyses.

To see examples of this in action, check out the vignettes: `browseVignettes(package = 'hpgltools')`

Author(s)

Maintainer: Ashton Belew <abelew@gmail.com>

Authors:

- Keith Hughitt <khughitt@umd.edu>
- Jerry Zhao <zhaojerry123@gmail.com>

iDA	<i>Generic method to input data to iDA</i>
-----	--

Description

Generic method to input data to iDA

Usage

```
iDA(object, ...)
```

Arguments

object	The object to run iDA on
...	Additonal arguments passed to object constructors

Value

iDA output with clustering, gene weights, and cell weights

iDA,matrix-method	<i>Set method for matrix to input data to iDA</i>
-------------------	---

Description

Set method for matrix to input data to iDA

Usage

```
## S4 method for signature 'matrix'
iDA(object, ...)
```

Arguments

object	The object to run iDA on
...	Additonal arguments passed to object constructors

Value

iDA output with clustering, gene weights, and cell weights

ihw_adjust	<i>Make sure the outputs from limma and friends are in a format suitable for IHW.</i>
------------	---

Description

IHW seems like an excellent way to improve the confidence in the p-values provided by the various DE methods. It expects inputs fairly specific to DESeq2, however, it is trivial to convert other methods to this, ergo this function.

Usage

```
ihw_adjust(  
  de_result,  
  pvalue_column = "pvalue",  
  type = NULL,  
  mean_column = "baseMean",  
  significance = 0.05  
)
```

Arguments

de_result	Table which should have the 2 types of requisite columns: mean value of counts and p-value.
pvalue_column	Name of the column of p-values.
type	If specified, this will explicitly perform the calculation for the given type of differential expression analysis: limma, edger, deseq, etc.
mean_column	Name of the column of mean values.
significance	IHW uses this parameter, I don't know why.

Details

https://bioconductor.org/packages/release/bioc/vignettes/IHW/inst/doc/introduction_to_ihw.html

Value

weight adjusted p-values.

See Also

[IHW] 10.1038/nmeth.3885

import_deseq	<i>Try to add data to DESeq in a flexible fashion. This currently only handles matrices, htseq data, and tximport data.</i>
--------------	---

Description

This will hopefully make adding counts to a DESeq data set easier, as it tries to handle the various arguments with minimal fuss.

Usage

```
import_deseq(data, column_data, model_string, tximport = NULL)
```

Arguments

data	Counts from htseq/mtrx/tximport/etc
column_data	I think this is the sample names, I forget.
model_string	Model describing the data by sample names.
tximport	Where is this data coming from?

See Also

[DESeq2::DESeqDataSetFromMatrix]

import_edger	<i>Import tximport information into edgeR.</i>
--------------	--

Description

This was taken from the tximport manual with minor modifications.

Usage

```
import_edger(data, conditions, tximport = NULL)
```

Arguments

data	data to be coerced into edgeR.
conditions	Set of conditions used to make the DGEList.
tximport	Tell this if the data is actually coming from tximport.

Value

Hopefully valid DGEList for edgeR.

See Also

[import_deseq()]

impute_expt	<i>Impute missing values using code from DEP reworked for expression-sets.</i>
-------------	--

Description

[impute_expt()] imputes missing values in a proteomics dataset.

Usage

```
impute_expt(
  expt,
  filter = TRUE,
  p = 0.5,
  fun = c("bpca", "knn", "QRILC", "MLE", "MinDet", "MinProb", "min", "zero", "mixed",
    "nbavg"),
  ...
)
```

Arguments

expt	An ExpressionSet (well, expt), I think it is assumed that this should have been normalized and filtered for features which have no values across 'most' samples.
filter	Use normalize_expt() to filter the data?
p	When filtering with pofa, use this p parameter.
fun	"bpca", "knn", "QRILC", "MLE", "MinDet", "MinProb", "man", "min", "zero", "mixed" or "nbavg", Function used for data imputation based on [MSnbase::impute-methods()]
...	Additional arguments for imputation functions.

Value

An imputed expressionset.

See Also

[MSnbase]

init_xlsx	<i>Initialize an xlsx file with a little bit of logic to make sure there are no annoying downstream errors.</i>
-----------	---

Description

Initialize an xlsx file with a little bit of logic to make sure there are no annoying downstream errors.

Usage

```
init_xlsx(excel = "excel/something.xlsx")
```

Arguments

`excel` Excel file to create.

Value

List containing the basename of the excel file along with the openxlsx workbook data structure.

See Also

[openxlsx::createWorkbook()]

`intersect_signatures` *Take a result from simple_gsva(), a list of gene IDs, and intersect them.*

Description

Najib is curious about the relationship of genes in sets, the sets, and the genes that comprise those sets. This is pushing gsva towards a oroborous-ish state.

Usage

```
intersect_signatures(
  gsva_result,
  lst,
  freq_cutoff = 2,
  sig_weights = TRUE,
  gene_weights = TRUE
)
```

Arguments

`gsva_result` Result from simple_gsva().

`lst` List of genes of interest.

`freq_cutoff` Minimum number of observations to be counted.

`sig_weights` When making venn diagrams, weight them?

`gene_weights` When venning genes, weight them?

Value

List containing some venns, lists, and such.

See Also

[Vennerable] [simple_gsva()]

intersect_significant *Find the sets of intersecting significant genes*

Description

Use `extract_significant_genes()` to find the points of agreement between `limma/deseq/edger`.

Usage

```
intersect_significant(
  combined,
  lfc = 1,
  p = 0.05,
  padding_rows = 2,
  z = NULL,
  p_type = "adj",
  selectors = c("limma", "deseq", "edger"),
  order = "inverse",
  excel = "excel/intersect_significant.xlsx",
  ...
)
```

Arguments

<code>combined</code>	Result from <code>combine_de_tables()</code> .
<code>lfc</code>	Define significant via fold-change.
<code>p</code>	Or p-value.
<code>padding_rows</code>	How much space to put between groups of data?
<code>z</code>	Use a z-score filter?
<code>p_type</code>	Use normal or adjusted p-values.
<code>selectors</code>	List of methods to intersect.
<code>order</code>	When set to the default 'inverse', go from the set with the most least intersection to the most. E.g. Start with abc,bc,ac,c,ab,b,a as opposed to a,b,ab,c,ac,bc,abc.
<code>excel</code>	An optional excel workbook to which to write.
<code>...</code>	Extra arguments for <code>extract_significant_genes()</code> and friends.

Value

List containing the intersections between the various DE methods for both the up and down sets of genes. It should also provide some venn diagrams showing the degree of similarity between the methods.

Examples

```
## Not run:
expt <- create_expt(metadata="some_metadata.xlsx", gene_info=funkytown)
big_result <- all_pairwise(expt, model_batch=FALSE)
pretty <- combine_de_tables(big_result, excel="excel/combined_expt.xlsx")
intersect <- intersect_significant(pretty, excel="excel/intersecting_genes.xlsx")

## End(Not run)
```

```
iterate_linear_regression
```

Perform a series of single regression analyses and tabulate/plot the results.

Description

Perform a series of single regression analyses and tabulate/plot the results.

Usage

```
iterate_linear_regression(  
  design,  
  query = "condition",  
  factors = NULL,  
  conf = 0.95,  
  excel = NULL  
)
```

Arguments

design	Experimental design.
query	Factor of primary interest.
factors	Set of factors to query against (if not set, then query will be the first design column, and these will be 2:end)
conf	Choose the confidence interval.
excel	Write the results to this file.

```
iterate_logistic_regression
```

Perform a series of single regression analyses and tabulate/plot the results.

Description

Perform a series of single regression analyses and tabulate/plot the results.

Usage

```
iterate_logistic_regression(  
  design,  
  query = "condition",  
  factors = NULL,  
  family = "binomial",  
  conf = 0.95,  
  excel = NULL  
)
```


Arguments

design	Experimental design.
query	Factor of primary interest.
factors	Set of factors to query against (if not set, then query will be the first design column, and these will be 2:end)
conf	Choose the confidence interval.
excel	Write the results to this file.

kegg_vector_to_df	<i>Convert a potentially non-unique vector from kegg into a normalized data frame.</i>
-------------------	--

Description

This function seeks to reformat data from KEGGREST into something which is rather easier to use.

Usage

```
kegg_vector_to_df(vector, final_colname = "first", flatten = TRUE)
```

Arguments

vector	Information from KEGGREST
final_colname	Column name for the new information
flatten	Flatten nested data?

Details

This could probably benefit from a tidyr-ish revisitation.

Value

A normalized data frame of gene IDs to whatever.

See Also

[KEGGREST] [load_kegg_annotations()]

libsize	<i>Getter for library sizes in an expt.</i>
---------	---

Description

Getter for library sizes in an expt.

Usage

```
libsize(x)
```

Arguments

x	input
---	-------

libsize, SummarizedExperiment-method
<i>Get the library sizes of a summarized experiment.</i>

Description

Get the library sizes of a summarized experiment.

Usage

```
## S4 method for signature 'SummarizedExperiment'
libsize(x)
```

libsize<-	<i>Setter for library sizes in an expt.</i>
-----------	---

Description

Setter for library sizes in an expt.

Usage

```
libsize(x, vector) <- value
```

limma_pairwise	<i>Set up a model matrix and set of contrasts for pairwise comparisons using voom/limma.</i>
----------------	--

Description

Creates the set of all possible contrasts and performs them using voom/limma.

Usage

```
limma_pairwise(
  input = NULL,
  model_fstring = "~ 0 + condition + batch",
  null_fstring = "~",
  model_svs = NULL,
  filter = FALSE,
  extra_contrasts = NULL,
  annot_df = NULL,
  libsize = NULL,
  adjust = "BH",
  which_voom = "limma",
  limma_method = "ls",
  limma_robust = FALSE,
  voom_norm = "quantile",
  limma_trend = TRUE,
  force = FALSE,
  keep_underscore = TRUE,
  num_surrogates = "be",
  keepers = NULL,
  ...
)
```

Arguments

input	Dataframe/vector or expt class containing count tables, normalization state, etc.
extra_contrasts	Some extra contrasts to add to the list. This can be pretty neat, lets say one has conditions A,B,C,D,E and wants to do (C/B)/A and (E/D)/A or (E/D)/(C/B) then use this with a string like: "c_vs_b_ctrla = (C-B)-A, e_vs_d_ctrla = (E-D)-A, de_vs_cb = (E-D)-(C-B),"
annot_df	Data frame for annotations.
libsize	I've recently figured out that libsize is far more important than I previously realized. Play with it here.
which_voom	Try out different invocations of voom.
limma_method	And different invocations of limma itself.
limma_robust	Pass along the robust args for limma?
voom_norm	Use a specific normalization for voom?
limma_trend	Include a trendline in the limma plot?

force	Force data which may not be appropriate for limma into it?
keepers	Choose a set of contrasts instead of all.
...	Use the elipsis parameter to feed options to write_limma().
conditions	Factor of conditions in the experiment.
batches	Factor of batches in the experiment.
model_cond	Include condition in the model?
model_batch	Include batch in the model? If this is a character instead of a logical, then it is passed to all_adjusers() to attempt to find model parameters which describe surrogate variables in the data.
model_intercept	Perform a cell-means or intercept model? A little more difficult for me to understand. I have tested and get the same answer either way.
alt_model	Separate model matrix instead of the normal condition/batch.

Value

List including the following information: macb = the mashing together of condition/batch so you can look at it macb_model = The result of calling model.matrix(~0 + macb) macb_fit = The result of calling lmFit(data, macb_model) voom_result = The result from voom() voom_design = The design from voom (redundant from voom_result, but convenient) macb_table = A table of the number of times each condition/batch pairing happens cond_table = A table of the number of times each condition appears (the denominator for the identities) batch_table = How many times each batch appears identities = The list of strings defining each condition by itself all_pairwise = The list of strings defining all the pairwise contrasts contrast_string = The string making up the makeContrasts() call pairwise_fits = The result from calling contrasts.fit() pairwise_comparisons = The result from eBayes() limma_result = The result from calling write_limma()

See Also

[limma] [Biobase] [deseq_pairwise()] [edger_pairwise()] [basic_pairwise()] DOI:10.1093/nar/gkv007

Examples

```
## Not run:
pretend <- limma_pairwise(expt)

## End(Not run)
```

load_annotations	<i>Use one of the load_*_annotations() functions to gather annotation data.</i>
------------------	---

Description

We should be able to have an agnostic annotation loader which can take some standard arguments and figure out where to gather data on its own.

Usage

```
load_annotations(type = NULL, ...)
```

Arguments

type	Explicitly state the type of annotation data to load. If not provided, try to figure it out automagically.
...	Arguments passed to the other load_*_annotations().

Value

Some annotations, hopefully.

See Also

[load_biomart_annotations()] [load_gff_annotations()] [load_genbank_annotations()] [load_kegg_annotations()]
[load_trinotate_annotations()] [load_microbesonline_annotations()] [load_uniprot_annotations()]

Examples

```
example_gff <- get_paeruginosa_data()[["gff"]]
gff_annotations <- load_annotations(type = "gff", gff = example_gff)
dim(gff_annotations)
```

```
load_biomart_annotations
```

Extract annotation information from biomart.

Description

Biomart is an amazing resource of information, but using it is a bit annoying. This function hopes to alleviate some common headaches.

Usage

```
load_biomart_annotations(
  species = "hsapiens",
  overwrite = FALSE,
  do_save = TRUE,
  host = NULL,
  trymart = "ENSEMBL_MART_ENSEMBL",
  archive = TRUE,
  default_hosts = c("useast.ensembl.org", "uswest.ensembl.org", "www.ensembl.org",
    "asia.ensembl.org"),
  year = NULL,
  month = NULL,
  drop_haplotypes = FALSE,
  trydataset = NULL,
  gene_requests = c("ensembl_gene_id", "version", "ensembl_transcript_id",
    "transcript_version", "description", "gene_biotype"),
  length_requests = c("ensembl_transcript_id", "cds_length", "chromosome_name", "strand",
    "start_position", "end_position"),
  gene_tx_map = TRUE,
  gene_id_column = "ensembl_gene_id",
  gene_version_column = "version",
```

```

tx_id_column = "ensembl_transcript_id",
tx_version_column = "transcript_version",
symbol_columns = NULL,
include_lengths = TRUE,
do_load = TRUE,
savefile = NULL
)

```

Arguments

species	Choose a species.
overwrite	Overwrite an existing save file?
do_save	Create a savefile of annotations for future runs?
host	Ensembl hostname to use.
trymart	Biomart has become a circular dependency, this makes me sad, now to list the marts, you need to have a mart loaded.
archive	Try an archive server instead of a mirror? If this is a character, it will assume it is a specific archive hostname.
default_hosts	List of biomart mirrors to try.
year	Choose specific year(s) for the archive servers?
month	Choose specific month(s) for the archive server?
drop_haplotypes	Some chromosomes have stupid names because they are from non-standard haplotypes and they should go away. Setting this to false stops that.
trydataset	Choose the biomart dataset from which to query.
gene_requests	Set of columns to query for description-ish annotations.
length_requests	Set of columns to query for location-ish annotations.
gene_tx_map	Provide a gene2tx map for things like salmon (perhaps rename this to tx_gene_map?)
gene_id_column	Column containing the gene ID.
gene_version_column	Column containing the ensembl gene version.
tx_id_column	Column containing the transcript ID.
tx_version_column	Columns containing the ensembl transcript version.
symbol_columns	Vector of columns containing the gene symbols.
include_lengths	Also perform a search on structural elements in the genome?
do_load	Load the data?
savefile	Use this savefile.

Details

Tested in test_40ann_biomart.R This goes to some lengths to find the relevant tables in biomart. But biomart is incredibly complex and one should carefully inspect the output if it fails to see if there are more appropriate marts, datasets, and columns to download.

Value

List containing: a data frame of the found annotations, a copy of The mart instance to help with finding problems, the hostname queried, the name of the mart queried, a vector of rows queried, vector of the available attributes, and the ensembl dataset queried.

See Also

[biomaRt::listDatasets()] [biomaRt::getBM()] [find_working_mart()]

Examples

```
## This downloads the hsapiens annotations by default.
hs_biomart_annot <- load_biomart_annotations()
summary(hs_biomart_annot)
dim(hs_biomart_annot$annotation)
```

load_biomart_go

Extract gene ontology information from biomart.

Description

I perceive that every time I go to acquire annotation data from biomart, they have changed something important and made it more difficult for me to find what I want. I recently found the *.archive.ensembl.org, and so this function uses that to try to keep things predictable, if not consistent.

Usage

```
load_biomart_go(
  species = "hsapiens",
  overwrite = FALSE,
  do_save = TRUE,
  host = NULL,
  trymart = "ENSEMBL_MART_ENSEMBL",
  archive = FALSE,
  default_hosts = c("useast.ensembl.org", "uswest.ensembl.org", "www.ensembl.org",
    "asia.ensembl.org"),
  year = NULL,
  month = NULL,
  trydataset = NULL,
  dl_rows = c("ensembl_gene_id", "go_id"),
  dl_rowsv2 = c("ensembl_gene_id", "go_id")
)
```

Arguments

species	Species to query.
overwrite	Overwrite existing savefile?
do_save	Create a savefile of the annotations? (if not false, then a filename.)
host	Ensembl hostname to use.

trymart	Biomart has become a circular dependency, this makes me sad, now to list the marts, you need to have a mart loaded.
archive	Try an archive server instead of a mirror? If this is a character, it will assume it is a specific archive hostname.
default_hosts	List of biomart mirrors to try.
year	Choose specific year(s) for the archive servers?
month	Choose specific month(s) for the archive servers?
trydataset	Define a dataset to which to attempt connecting.
dl_rows	List of rows from the final biomart object to download.
dl_rowsv2	A second list of potential rows.

Details

Tested in test_40ann_biomart.R This function makes a couple of attempts to pick up the correct tables from biomart. It is worth noting that it uses the archive.ensembl host(s) because of changes in table organization after December 2015 as well as an attempt to keep the annotation sets relatively consistent.

Value

List containing the following: data frame of ontology data, a copy of the biomart instance for further querying, the host queried, the biomart queried, a vector providing the attributes queried, and the ensembl dataset queried.

See Also

[biomaRt::listMarts()] [biomaRt::useDatasets()] [biomaRt::getBM()]

Examples

```
hs_biomart_ontology <-load_biomart_go()
summary(hs_biomart_ontology)
dim(hs_biomart_ontology$go)
```

load_biomart_orthologs

Use biomart to get orthologs between supported species.

Description

Biomart's function getLDS is incredibly powerful, but it makes me think very polite people are going to start knocking on my door, and it fails weirdly pretty much always. This function attempts to alleviate some of that frustration.

Usage

```
load_biomart_orthologs(
  gene_ids = NULL,
  first_species = "hsapiens",
  second_species = "mmusculus",
  host = NULL,
  trymart = "ENSEMBL_MART_ENSEMBL",
  archive = TRUE,
  default_hosts = c("useast.ensembl.org", "uswest.ensembl.org", "www.ensembl.org",
    "asia.ensembl.org"),
  year = NULL,
  month = NULL,
  trydataset = NULL,
  attributes = "ensembl_gene_id"
)
```

Arguments

<code>gene_ids</code>	List of gene IDs to translate.
<code>first_species</code>	Linnean species name for one species.
<code>second_species</code>	Linnean species name for the second species.
<code>host</code>	Ensembl server to query.
<code>trymart</code>	Assumed mart name to use.
<code>archive</code>	Use an archive server?
<code>default_hosts</code>	Set of default hosts to query.
<code>year</code>	When using an archive server, use this year (otherwise it will choose last year).
<code>month</code>	When using an archive server, use this month (otherwise, this month).
<code>trydataset</code>	Choose a dataset to query.
<code>attributes</code>	Key to query

Details

Tested in test_40ann_biomart.R As with my other biomart functions, this one grew out of frustrations when attempting to work with the incredibly unforgiving biomart service. It does not attempt to guarantee a useful biomart connection, but will hopefully point out potentially correct marts and attributes to use for a successful query. I can say with confidence that it works well between mice and humans.

Value

list of 4 elements: The first is the set of all ids, as getLDS seems to always send them all; the second is the subset corresponding to the actual ids of interest, and the 3rd/4th are other, optional ids from other datasets.

See Also

[biomaRt::getLDS()]

Examples

```
mouse_yeast_orthologs <- load_biomart_orthologs(gene_ids = NULL, first_species = "mmusculus",
                                                second_species = "scerevisiae")
head(mouse_yeast_orthologs$all_linked_genes)
```

```
load_genbank_annotations
```

Given a genbank accession, make a txDb object along with sequences, etc.

Description

Let us admit it, sometimes biomart is a pain. It also does not have easily accessible data for microbes. Genbank does!

Usage

```
load_genbank_annotations(
  accession = "AE009949",
  file = NULL,
  sequence = TRUE,
  reread = TRUE,
  savetxdb = FALSE
)
```

Arguments

accession	Accession to download and import.
file	Use a file instead of downloading the accession?
sequence	Download the sequence with the annotations?
reread	Re-read (download) the file from genbank.
savetxdb	Attempt saving a txdb object?

Details

Tested in test_40ann_biomartgenbank.R and test_70expt_spyogenes.R This primarily sets some defaults for the genbankr service in order to facilitate downloading genomes from genbank and dumping them into a local txdb instance.

Value

List containing a txDb, sequences, and some other stuff which I haven't yet finalized.

See Also

[Biostrings] [GenomicFeatures] [genbankr::import()] [genbankr::readGenBank()]

Examples

```
sagalacticae_genbank_annot <- load_genbank_annotations(accession = "AE009948")
dim(as.data.frame(sagalacticae_genbank_annot$cds))
```

load_gff_annotations	<i>Extract annotation information from a gff file into a df</i>
----------------------	---

Description

Try to make import.gff a little more robust; I acquire (hopefully) valid gff files from various sources: yeastgenome.org, microbesonline, tritrypdb, ucsc, ncbi. To my eyes, they all look like reasonably good gff3 files, but some of them must be loaded with import.gff2, import.gff3, etc. That is super annoying. Also, I pretty much always just do as.data.frame() when I get something valid from rtracklayer, so this does that for me, I have another function which returns the iranges etc. This function wraps import.gff/import.gff3/import.gff2 calls in try() because sometimes those functions fail in unpredictable ways.

Usage

```
load_gff_annotations(  
  gff,  
  type = NULL,  
  id_col = "ID",  
  ret_type = "data.frame",  
  second_id_col = "locus_tag",  
  try = NULL,  
  row.names = NULL  
)
```

Arguments

gff	Gff filename.
type	Subset the gff file for entries of a specific type.
id_col	Column in a successful import containing the IDs of interest.
ret_type	Return a data.frame or something else?
second_id_col	Second column to check.
try	Give your own function call to use for importing.
row.names	Choose another column for setting the rownames of the data frame.

Value

Dataframe of the annotation information found in the gff file.

See Also

[rtracklayer] [GenomicRanges]

Examples

```
example_gff <- system.file("share", "gas.gff", package = "hpgldata")  
gas_gff_annot <- load_gff_annotations(example_gff)  
dim(gas_gff_annot)
```

load_gmt_signatures	<i>Load signatures from either a gmt file, xml file, or directly from the GSVAdata data set in R.</i>
---------------------	---

Description

There are a bunch of places from which to acquire signature data. This function attempts to provide a single place to load them. The easiest way to get up to date signatures is to download them from msigdb and set the signatures parameter to the downloaded filename.

Usage

```
load_gmt_signatures(
  signatures = "c2BroadSets",
  data_pkg = "GSVAdata",
  signature_category = "c2",
  id_type = "entrez"
)
```

Arguments

signatures	Either the filename downloaded or the variable's name as found in the environment created by data_pkg.
data_pkg	Used when signatures is not a filename to load a data package, presumably GSVAdata.
signature_category	Probably not needed unless you download a signature file containing lots of different categories.
id_type	Specify the ID type in the data.

Value

signature dataset which may be used by gsva()

See Also

[GSEABase]

load_kegg_annotations	<i>Create a data frame of pathways to gene IDs from KEGGREST</i>
-----------------------	--

Description

This seeks to take the peculiar format from KEGGREST for pathway<->genes and make it easier to deal with. Sadly, this only works for a subset of species now.

Usage

```
load_kegg_annotations(species = "coli", abbreviation = NULL, flatten = TRUE)
```

Arguments

species	String to use to query KEGG abbreviation.
abbreviation	If you already know the abbreviation, use it.
flatten	Flatten nested tables?

Value

dataframe with rows of KEGG gene IDs and columns of NCBI gene IDs and KEGG paths.

See Also

[KEGGREST]

Examples

```
sc_kegg_annot <- load_kegg_annotations(species = "cerevisiae")
head(sc_kegg_annot)
```

```
load_microbesonline_annotations
```

Skip the db and download all the text annotations for a given species.

Description

The microbesonline publicly available mysqldb is rather more complex than I prefer. This skips that process and just grabs a tsv copy of everything and loads it into a dataframe. I have not yet figured out how to so-easily query microbesonline for species IDs, thus one will have to manually query the database to find species of interest.

Usage

```
load_microbesonline_annotations(species = NULL, id = NULL)
```

Arguments

species	Microbesonline species.
id	Microbesonline ID to query.

Details

Tested in test_70expt_spyogenes.R There is so much awesome information in microbesonline, but damn is it annoying to download. This function makes that rather easier, or so I hope at least.

Value

Dataframe containing the annotation information.

See Also

[rvest] [xml2] [readr]

Examples

```
pa14_microbesonline_annot <- load_microbesonline_annotations(species = "PA14")
colnames(pa14_microbesonline_annot)
```

```
load_microbesonline_go
```

Extract the set of GO categories by microbesonline locus

Description

The microbesonline is such a fantastic resource, it is a bit of a shame that it is such a pain to query.

Usage

```
load_microbesonline_go(
  id = NULL,
  species = NULL,
  table_df = NULL,
  id_column = "name",
  data_column = "GO",
  name = NULL
)
```

Arguments

<code>id</code>	Which species to query.
<code>species</code>	Microbesonline species.
<code>table_df</code>	Pre-existing data frame of annotations containing GO stuff.
<code>id_column</code>	This no longer uses MySQL, so which column from the html table to pull?
<code>data_column</code>	Similar to above, there are lots of places from which one might extract the data.
<code>name</code>	Allowing for non-specific searches by species name.

Details

Tested in test_42ann_microbes.R I am not 100 ontology accessions. At the very least, it does return a large number of them, which is a start.

Value

data frame of GO terms from www.microbesonline.org

See Also

[tidyr]

Examples

```
pa14_microbesonline_go <- load_microbesonline_go(species = "PA14")
head(pa14_microbesonline_go)
```

load_orgdb_annotations

Load organism annotation data from an orgdb sqlite package.

Description

Creates a dataframe gene and transcript information for a given set of gene ids using the AnnotationDbi interface.

Usage

```
load_orgdb_annotations(
  orgdb = NULL,
  gene_ids = NULL,
  include_go = FALSE,
  keytype = "ensembl",
  strand_column = "cdsstrand",
  start_column = "cdsstart",
  end_column = "cdsend",
  chromosome_column = "cdschrom",
  type_column = "gene_type",
  name_column = "cdsname",
  fields = NULL,
  sum_exon_widths = FALSE
)
```

Arguments

orgdb	OrganismDb instance.
gene_ids	Search for a specific set of genes?
include_go	Ask the Dbi for gene ontology information?
keytype	mmm the key type used?
strand_column	There are a few fields I want to gather by default: start, end, strand, chromosome, type, and name; but these do not necessarily have consistent names, use this column for the chromosome strand.
start_column	Use this column for the gene start.
end_column	Use this column for the gene end.
chromosome_column	Use this column to identify the chromosome.
type_column	Use this column to identify the gene type.
name_column	Use this column to identify the gene name.
fields	Columns included in the output.
sum_exon_widths	Perform a sum of the exons in the data set?

Details

Tested in test_45ann_organdb.R This defaults to a few fields which I have found most useful, but the brave or pathological can pass it 'all'.

Value

Table of geneids, chromosomes, descriptions, strands, types, and lengths.

See Also

[AnnotationDbi] [AnnotationDbi::select()] [GenomicFeatures]

Examples

```
hs_orgdb_annot <- load_orgdb_annotiations()
summary(hs_orgdb_annot$genes)
```

load_orgdb_go	<i>Retrieve GO terms associated with a set of genes.</i>
---------------	--

Description

AnnotationDbi provides a reasonably complete set of GO mappings between gene ID and ontologies. This will extract that table for a given set of gene IDs.

Usage

```
load_orgdb_go(
  orgdb = NULL,
  gene_ids = NULL,
  keytype = "ensembl",
  columns = c("go", "goall", "goid")
)
```

Arguments

orgdb	OrganismDb instance.
gene_ids	Identifiers of the genes to retrieve annotations.
keytype	The mysterious keytype returns yet again to haunt my dreams.
columns	The set of columns to request.

Details

Tested in test_45ann_organdb.R This is a nice way to extract GO data primarily because the Orgdb data sets are extremely fast and flexible, thus by changing the keytype argument, one may use a lot of different ID types and still score some useful ontology data.

Value

Data frame of gene IDs, go terms, and names.

Author(s)

I think Keith provided the initial implementation of this, but atb messed with it pretty extensively.

See Also

[AnnotationDbi] [GO.db]

Examples

```
drosophila_orgdb_go <- load_orgdb_go(orgdb = "org.Dm.eg.db")
head(drosophila_orgdb_go)
```

```
load_trinotate_annotations
```

Read a csv file from trinotate and make an annotation data frame.

Description

Trinotate performs some neat sequence searches in order to seek out likely annotations for the trinity contigs. The resulting csv file is encoded in a peculiar fashion, so this function attempts to make it easier to read and put them into a format usable in an expressionset.

Usage

```
load_trinotate_annotations(
  trinotate = "reference/trinotate.csv",
  collapse = FALSE
)
```

Arguments

trinotate	CSV of trinotate annotation data.
collapse	Collapse isoforms to genes?

Value

Dataframe of fun data.

See Also

[tidyr] [readr]

Examples

```
sb_annot <- get_sbetaceum_data()[["annot"]]
a_few_trinotate <- load_trinotate_annotations(trinotate = sb_annot)
dim(a_few_trinotate)
```

load_trinotate_go	<i>Read a csv file from trinotate and extract ontology data from it.</i>
-------------------	--

Description

Trinotate performs some neat sequence searches in order to seek out likely annotations for the trinity contigs. This function extracts ontology data from it. Keep in mind that this data is primarily from Blast2GO.

Usage

```
load_trinotate_go(
  trinotate = "reference/trinotate.csv",
  blast2go_column = "gene_ontology_BLASTX",
  pfam_column = "gene_ontology_pfam",
  length_column = "transcript",
  fill = 1500,
  collapse = TRUE,
  id_column = "#gene_id"
)
```

Arguments

trinotate	CSV of trinotate annotation data.
blast2go_column	Column name containing BLAST2GO data.
pfam_column	Column containing data from pfam searches.
length_column	Column containing the gene lengths.
fill	Cheat and fill in an arbitrary value for gene lengths if all else fails.
collapse	Collapse isoforms to genes?
id_column	Column containing the gene IDs.

Value

List of the extracted GO data, a table of it, length data, and the resulting length table.

See Also

[load_trinotate_annotations()]

Examples

```
sb_annot <- get_sbetaceum_data()[["annot"]]
trinotate_go <- load_trinotate_go(trinotate = sb_annot)
dim(trinotate_go$go_data)
dim(trinotate_go$go_table)
```

`load_uniprot_annotations`*Download the txt uniprot data for a given accession/species.*

Description

Uniprot is an astonishing resource, but man is it a pain to use. Hopefully this function will help. It takes either a uniprot accession, taxonomy ID, or species name and does its best to find the appropriate uniprot data. This is therefore primarily used by `load_uniprot_annotations()`.

Usage

```
load_uniprot_annotations(  
  accession = NULL,  
  species = "H37Rv",  
  taxonomy = NULL,  
  all = FALSE,  
  first = FALSE  
)
```

Arguments

<code>accession</code>	Which accession to grab?
<code>species</code>	Or perhaps species?
<code>taxonomy</code>	Query for a specific taxonomy ID rather than species/accession?
<code>all</code>	If there are more than 1 hit, grab them all?
<code>first</code>	Or perhaps just grab the first hit?

Value

A filename/accession tuple.

See Also

[xml2] [rvest]

Examples

```
uniprot_sc_downloaded <- load_uniprot_annotations(species = "Saccharomyces cerevisiae S288c")  
uniprot_sc_downloaded$filename  
uniprot_sc_downloaded$species
```

load_uniprot_go	<i>Extract ontology information from a uniprot dataframe.</i>
-----------------	---

Description

Extract ontology information from a uniprot dataframe.

Usage

```
load_uniprot_go(...)
```

Arguments

... Whatever args are required for load_uniprot_annotations()

Value

Ontology dataframe

See Also

[load_uniprot_annotations()] [stringr] [tidyr]

Examples

```
## Not run:
uniprot_sc_downloaded <- download_uniprot_proteome(species = "Saccharomyces cerevisiae S288c")
sc_uniprot_annot <- load_uniprot_annotations(file = uniprot_sc_downloaded$filename)
sc_uniprot_go <- load_uniprot_go(sc_uniprot_annot)
head(sc_uniprot_go)

## End(Not run)
```

loadme	<i>Load a backup rdata file</i>
--------	---------------------------------

Description

I often use R over a sshfs connection, sometimes with significant latency, and I want to be able to save/load my R sessions relatively quickly. Thus this function uses my backup directory to load its R environment.

Usage

```
loadme(directory = "savefiles", filename = "Rdata.rda.xz")
```

Arguments

directory	Directory containing the RData.rda.xz file.
filename	Filename to which to save.

Value

a bigger global environment

See Also

[saveme()]

Examples

```
## Not run:
loadme()

## End(Not run)
```

local_get_value	<i>Perform a get_value for delimited files</i>
-----------------	--

Description

Keith wrote this as .get_value() but functions which start with . trouble me.

Usage

```
local_get_value(x, delimiter = ": ")
```

Arguments

x	Some stuff to split
delimiter	The tritrypdb uses ' ' ergo the default.

Value

A value!

make_assembly_spec	<i>Generate an assembly annotation specification for use by gather_preprocessing_metadata()</i>
--------------------	---

Description

This is the default set of files/information that will be sought. It is a bit much. Each name of the returned list is one column in the final metadata. The values within that name are the relevant parameters for the associated dispatcher.

Usage

```
make_assembly_spec()
```

Details

The assembly pipeline I wrote for which this was written does the following: 1. Trimomatic (the assemblies I was doing were miseq phage). 2. Fastqc the trimmed reads. 3. Racer to correct sequencer-based errors. 4. Perform an initial classification with kraken vs. the standard database. (thus if there is contamination we can pick it up) 5. Use kraken to make a hypothetical host for the phage and filter it. 6. Classify the remaining sequence with kraken vs a viral database. 7. Generate an initial assembly via unicycler. 8. Depth-filter said assembly. 9. Use Blast to search the ICTV for likely taxonomy. 10. Count ORFs to define the +/- strands. 11. Use Phageterm to define the DTRs and/or reorient the genome. 12. Perform a taxonomy search on the assembled genome via phastaf (thus we can see if it is segmented or multiple genomes). 13. Calculate coverage on a per-nucleotide basis. 14. Search for likely terminases, and reorient the genome if phageterm (#11) failed. 15. Create an initial annotation genbank file via prokka. 16. Supplement the prokka ORFs via a trained prodigal run. 17. Supplement them again via a promiscuous run of glimmer. 18. Use phanotate as the arbiter of 'correct' phage ORFs. (e.g. the ORFs from #15-17 will only be used if they agree with and/or do not interfere with these). 19. Merge the results from #15-18 into a single set of ORFs/genbank. 20. Calculate the assembly kmer content via jellyfish. 21. Look for t(m)RNAs via aragorn. 22. Look for tRNAs via tRNAscan. 23. Perform the set of blast/etc searches defined by trinotate. 24. Look for MDR genes via abricate. 25. Perform the set of blast/etc searches defined by interproscan. 26. Cross reference the genome against the extant restriction enzyme catalog. 27. Calculate the codon adaptation index of each ORF against the putative host from #5. 28. Search for phage promoters. 29. Search for Rho termination signals. 30. Attempt to classify the phage's likelihood to be lysogenic/lytic via bacphlip. 31. Search for strong RNA secondary structures via RNAfold. 32. Merge the annotations collected from #21-29 into a larger genbank file. 33. Repeat #32, but this time with feeling. (#32 adds comments with confidence intervals, this strips those out). 34. Make an initial visualization of the assembly via cgview. 35. Collect all the most likely useful stuff from above into a single archive. 36. Clean up the mess.

make_dnaseq_spec	<i>Generate a DNaseq specification for use by gather_preprocessing_metadata()</i>
------------------	---

Description

This currently assumes the set of tools used by one doing RNASeq to be trimomatic, fastqc, hisat2, htseq, freebayes, and my variant post-processor.

Usage

```
make_dnaseq_spec()
```

make_gsc_from_abundant	<i>Given a pairwise result, make a gene set collection.</i>
------------------------	---

Description

If I want to play with gsva and friends, then I need GeneSetCollections! Much like make_gsc_from_significant(), this function extract the genes deemed 'abundant' and generates gene sets accordingly.

Usage

```
make_gsc_from_abundant(
  pairwise,
  according_to = "deseq",
  annotation_name = "org.Hs.eg.db",
  researcher_name = "elsayed",
  study_name = "macrophage",
  category_name = "infection",
  phenotype_name = NULL,
  pair_names = "high",
  current_id = "ENSEMBL",
  required_id = "ENTREZID",
  ...
)
```

Arguments

<code>pairwise</code>	A pairwise result, or combined de result, or extracted genes.
<code>according_to</code>	When getting significant genes, use this method.
<code>annotation_name</code>	Name of the annotation dataset.
<code>researcher_name</code>	Prefix of the name for the generated set(s).
<code>study_name</code>	Second element in the name of the generated set(s).
<code>category_name</code>	Third element in the name of the generated set(s).
<code>phenotype_name</code>	Optional phenotype data for the generated set(s).
<code>pair_names</code>	The suffix of the generated set(s).
<code>current_id</code>	What type of ID is the data currently using?
<code>required_id</code>	What type of ID should the use?
<code>...</code>	Extra arguments for <code>extract_abundant_genes()</code> .

Value

List containing 3 GSCs, one containing both the highs/lows called 'colored', one of the highs, and one of the lows.

See Also

[`extract_abundant_genes()`] [`make_gsc_from_ids()`] [`GSEABase`]

<code>make_gsc_from_ids</code>	<i>Create a gene set collection from a set of arbitrary IDs.</i>
--------------------------------	--

Description

This function attempts to simplify the creation of a gsva compatible GeneSet. Some important caveats when working with gsva, notably the gene IDs we use are not usually compatible with the gene IDs used by gsva, thus the primary logic in this function is intended to bridge these IDs.

Usage

```

make_gsc_from_ids(
  first_ids,
  second_ids = NULL,
  annotation_name = "org.Hs.eg.db",
  researcher_name = "elsayed",
  study_name = "macrophage",
  category_name = "infection",
  phenotype_name = NULL,
  identifier_type = "entrez",
  organism = NULL,
  pair_names = "up",
  current_id = "ENSEMBL",
  required_id = "ENTREZID",
  min_gmt_genes = 10
)

```

Arguments

<code>first_ids</code>	The required IDs for a single set.
<code>second_ids</code>	Potentially null optionally used for a second, presumably contrasting set.
<code>annotation_name</code>	Orgdb annotation, used to translate IDs to the required type.
<code>researcher_name</code>	Prefix of the name for the generated set(s).
<code>study_name</code>	Second element in the name of the generated set(s).
<code>category_name</code>	Third element in the name of the generated set(s).
<code>phenotype_name</code>	Optional phenotype data for the generated set(s).
<code>identifier_type</code>	ID type to use in the gene set.
<code>organism</code>	Set the organism for the gsc object.
<code>pair_names</code>	The suffix of the generated set(s).
<code>current_id</code>	What type of ID is the data currently using?
<code>required_id</code>	What type of ID should the use?
<code>min_gmt_genes</code>	Minimum number of genes in the set for consideration.

Value

Small list comprised of the created gene set collection(s).

See Also

[GSEABase]

make_gsc_from_pairwise

Given a pairwise result, make a gene set collection.

Description

If I want to play with gsva and friends, then I need GeneSetCollections! To that end, this function uses `extract_significant_genes()` in order to gather sets of genes deemed 'significant'. It then passes these sets to `make_gsc_from_ids()`.

Usage

```
make_gsc_from_pairwise(
  pairwise,
  according_to = "deseq",
  annotation_name = "org.Hs.eg.db",
  pair_names = c("ups", "downs"),
  category_name = "infection",
  phenotype_name = "parasite",
  set_name = "elsayed_macrophage",
  color = TRUE,
  current_id = "ENSEMBL",
  required_id = "ENTREZID",
  ...
)
```

Arguments

<code>pairwise</code>	A pairwise result, or combined de result, or extracted genes.
<code>according_to</code>	When getting significant genes, use this method.
<code>annotation_name</code>	Name of the annotation database for the data.
<code>pair_names</code>	Describe the contrasts of the GSC: up vs. down, high vs. low, etc.
<code>category_name</code>	What category does the GSC describe?
<code>phenotype_name</code>	When making color sets, use this phenotype name.
<code>set_name</code>	A name for the created gene set.
<code>color</code>	Make a colorSet?
<code>current_id</code>	Usually we use ensembl IDs, but that does not <code>_need_</code> to be the case.
<code>required_id</code>	gsva uses entrezids by default.
<code>...</code>	Extra arguments for <code>extract_significant_genes()</code> .

Value

List containing 3 GSCs, one containing both the ups/downs called 'colored', one of the ups, and one of the downs.

See Also

[`combine_de_tables()`] [`extract_significant_genes()`] [`make_gsc_from_ids()`] [`GSEABase`]

`make_id2gomap`*Make a go mapping from IDs in a format suitable for topGO.*

Description

When using a non-supported organism, one must write out mappings in the format expected by topgo. This handles that process and gives a summary of the new table.

Usage

```
make_id2gomap(  
  goid_map = "reference/go/id2go.map",  
  go_db = NULL,  
  overwrite = FALSE  
)
```

Arguments

<code>goid_map</code>	TopGO mapping file.
<code>go_db</code>	If there is no <code>goid_map</code> , create it with this data frame.
<code>overwrite</code>	Rewrite the mapping file?

Value

Summary of the new goid table.

See Also

[topGO]

`make_kegg_df`*Use pathfindR to get a dataframe of KEGG IDs.*

Description

The various KEGG conversion methods from KEGGREST appear to only work for a small subset of species now. This uses a different query format to get a less flexible version of the same information. But at least it works.

Usage

```
make_kegg_df(org_code)
```

Arguments

<code>org_code</code>	Organism code from KEGG.
-----------------------	--------------------------

Value

Dataframe of gene IDs to KEGG IDs.

make_limma_tables	<i>Writes out the results of a limma search using toptable().</i>
-------------------	---

Description

However, this will do a couple of things to make one's life easier: 1. Make a list of the output, one element for each comparison of the contrast matrix 2. Write out the toptable() output in separate .csv files and/or sheets in excel 3. Since I have been using qvalues a lot for other stuff, add a column for them.

Usage

```
make_limma_tables(
  fit = NULL,
  adjust = "BH",
  n = 0,
  coef = NULL,
  annot_df = NULL,
  intercept = FALSE
)
```

Arguments

fit	Result from lmFit()/eBayes()
adjust	Pvalue adjustment chosen.
n	Number of entries to report, 0 says do them all.
coef	Which coefficients/contrasts to report, NULL says do them all.
annot_df	Optional data frame including annotation information to include with the tables.
intercept	Intercept model?

Value

List of data frames comprising the toptable output for each coefficient, I also added a qvalue entry to these toptable() outputs.

See Also

[limma] [write_xlsx()]

Examples

```
## Not run:
finished_comparison = eBayes(limma_output)
table = make_limma_tables(finished_comparison, adjust = "fdr")

## End(Not run)
```

make_ntile_factor	<i>Make an arbitrary factor out of a numeric vector</i>
-------------------	---

Description

Make an arbitrary factor out of a numeric vector

Usage

```
make_ntile_factor(numeric_vector, n)
```

Arguments

`numeric_vector` Vector of numbers!
`n` number of levels for the resulting factor.

Value

Factor with levels from q1 to q4.

make_pairwise_contrasts	<i>Run makeContrasts() with all pairwise comparisons.</i>
-------------------------	---

Description

In order to have uniformly consistent pairwise contrasts, I decided to avoid potential human errors(sic) by having a function generate all contrasts.

Usage

```
make_pairwise_contrasts(
  model,
  conditions,
  contrast_factor = "condition",
  do_identities = FALSE,
  do_extras = TRUE,
  do_pairwise = TRUE,
  keepers = NULL,
  extra_contrasts = NULL,
  keep_underscore = TRUE,
  ...
)
```

Arguments

model	Describe the conditions/batches/etc in the experiment.
conditions	Factor of conditions in the experiment.
do_identities	Include all the identity strings? Limma can use this information while edgeR can not.
do_extras	Include extra contrasts? This seems redundant with extra_contrasts below, but there is a reason for it.
do_pairwise	Include all pairwise strings? This shouldn't need to be set to FALSE, but just in case.
keepers	Only extract this subset of all possible pairwise contrasts.
extra_contrasts	Optional string of extra contrasts to include.
...	Extra arguments passed here are caught by arglist.

Details

Invoked by the `_pairwise()` functions.

Value

List including the following information:

1. `all_pairwise_contrasts` = the result from `makeContrasts(...)`
2. `identities` = the string identifying each condition alone
3. `all_pairwise` = the string identifying each pairwise comparison alone
4. `contrast_string` = the string passed to R to call `makeContrasts(...)`
5. `names` = the names given to the identities/contrasts

See Also

`[limma::makeContrasts()]`

Examples

```
## Not run:
pretend <- make_pairwise_contrasts(model, conditions)

## End(Not run)
```

make_pombe_expt	Create a <i>Schizosaccharomyces cerevisiae</i> expt.
-----------------	--

Description

This just saves some annoying typing if one wishes to make a standard expressionset superclass out of the publicly available fission data set.

Usage

```
make_pombe_expt(annotation = TRUE, host = "nov2020-fungi.ensembl.org")
```

Arguments

annotation	Add annotation data?
------------	----------------------

Value

Expressionset/expt of fission.

See Also

[fission] [create_expt()]

make_pombe_se	Analagous function to make_pombe_expt()
---------------	---

Description

Analagous function to make_pombe_expt()

Usage

```
make_pombe_se(annotation = TRUE, host = "nov2020-fungi.ensembl.org")
```

Arguments

annotation	Include annotations?
------------	----------------------

make_quartile_factor	<i>Make a quartile factor out of a numeric vector</i>
----------------------	---

Description

Make a quartile factor out of a numeric vector

Usage

```
make_quartile_factor(numeric_vector)
```

Arguments

`numeric_vector` Vector of numbers!

Value

Factor with levels from q1 to q4.

make_rnaseq_spec	<i>Generate a RNASeq specification for use by gather_preprocessing_metadata()</i>
------------------	---

Description

This currently assumes the set of tools used by one doing RNASeq to be trimomatic, fastqc, hisat2, and htseq.

Usage

```
make_rnaseq_spec(umi = FALSE)
```

Arguments

`umi` Include entries for umi-barcoded samples?

```
make_simplified_contrast_matrix
```

Create a contrast matrix suitable for MSstats and similar tools.

Description

I rather like makeContrasts() from limma. I troubled me to have to manually create a contrast matrix when using MSstats. It turns out it troubled me for good reason because I managed to reverse the terms and end up with the opposite contrasts of what I intended. Ergo this function.

Usage

```
make_simplified_contrast_matrix(numerators, denominators)
```

Arguments

numerators	Character list of conditions which are the numerators of a series of a/b comparisons.
denominators	Character list of conditions which are the denominators of a series of a/b comparisons.

Details

Feed make_simplified_contrast_matrix() a series of numerators and denominators names after the conditions of interest in an experiment and it returns a contrast matrix in a format acceptable to MSstats.

Value

Contrast matrix suitable for use in tools like MSstats.

See Also

[MSstats]

```
make_tx_gene_map
```

I keep messing up the creation of the salmon transcript to gene map.

Description

Maybe this will help. I have a smarter but much slower method in the tmrc3 data which first creates an expressionset without annotations then cross references the rownames against combinations of columns in the annotations to figure out the correct pairing. This helps when I have a combined transcriptome and get confused.

Usage

```
make_tx_gene_map(
  annotations,
  gene_column = "ensembl_gene_id",
  transcript_column = "ensembl_transcript_id",
  tx_version_column = "transcript_version",
  new_column = "salmon_transcript"
)
```

Arguments

annotations	Annoation database to merge.
gene_column	Column containing the gene IDs.
transcript_column	Column containing the transcript IDs.
tx_version_column	Salmon uses tx version numbers, find them here.
new_column	Add the new combined IDs here.

Details

This probably doesn't belong in this file.

make_varpart_tables	<i>Writes out the results of a limma search using toptable().</i>
---------------------	---

Description

However, this will do a couple of things to make one's life easier: 1. Make a list of the output, one element for each comparison of the contrast matrix 2. Write out the toptable() output in separate .csv files and/or sheets in excel 3. Since I have been using qvalues a lot for other stuff, add a column for them.

Usage

```
make_varpart_tables(
  fit = NULL,
  adjust = "BH",
  n = 0,
  coef = NULL,
  annot_df = NULL,
  intercept = FALSE
)
```

Arguments

fit	Result from lmFit()/eBayes()
adjust	Pvalue adjustment chosen.
n	Number of entries to report, 0 says do them all.

coef	Which coefficients/contrasts to report, NULL says do them all.
annot_df	Optional data frame including annotation information to include with the tables.
intercept	Intercept model?

Value

List of data frames comprising the toptable output for each coefficient, I also added a qvalue entry to these toptable() outputs.

See Also

[limma] [write_xlsx()]

Examples

```
## Not run:
finished_comparison = eBayes(limma_output)
table = make_limma_tables(finished_comparison, adjust = "fdr")

## End(Not run)
```

map_keepers	<i>Find the correct tables given a set of definitions of desired tables, numerators/denominators.</i>
-------------	---

Description

This is responsible for hunting down tables which correspond to the various ways one may represent them.

Usage

```
map_keepers(keepers, table_names, datum)
```

Arguments

keepers	List/scalar representation of desired tables.
table_names	The actual list of results produced by the various methods employed.
datum	The full dataset.

map_orgdb_ids	<i>Map AnnotationDbi keys from one column to another.</i>
---------------	---

Description

Given a couple of keytypes, this provides a quick mapping across them. I might have an alternate version of this hiding in the gsva code, which requires ENTREZIDs. In the mean time, this creates a dataframe of the mapped columns for a given set of gene ids using the in a sqLite instance.

Usage

```
map_orgdb_ids(orgdb, gene_ids = NULL, mapto = "ensembl", keytype = "geneid")
```

Arguments

orgdb	OrganismDb instance.
gene_ids	Gene identifiers for retrieving annotations.
mapto	Key to map the IDs against.
keytype	Choose a keytype, this will yell if it doesn't like your choice.

Value

a table of gene information

Author(s)

Keith Hughitt with changes by atb.

See Also

[AnnotationDbi]

Examples

```
dm_unigene_to_ensembl <- map_orgdb_ids("org.Dm.eg.db", mapto = "ensembl", keytype = "unigene")
head(dm_unigene_to_ensembl)
```

map_species_orgdb	<i>Guess the orgdb from a genus/species.</i>
-------------------	--

Description

Guess the orgdb from a genus/species.

Usage

```
map_species_orgdb(species, genus = NULL)
```

mean_by_bioreplicate	<i>An attempt to address a troubling question when working with DIA data.</i>
----------------------	---

Description

My biggest concern when treating DIA data in a RNASeqish manner is the fact that if a given peptide is not identified, that is not the same thing as stating that it was not translated. It is somewhat reminiscent of the often mocked and repeated Donald Rumsfeld statement regarding known unknowns vs. unknown unknowns. Thus, in an RNASeq experiment, if one sees a zero, one may assume that transcript was not transcribed, it may be assumed to be a known zero(unknown). In contrast, if the same thing happens in a DIA data set, that represents an unknown unknown. Perhaps it was not translated, and perhaps it was not identified.

Usage

```
mean_by_bioreplicate(expt, fact = "bioreplicate", fun = "mean")
```

Arguments

expt	Starting expressionset to mangle.
fact	Metadata factor to use when taking the mean of biological replicates.
fun	Assumed to be mean, but one might want median.

Details

This function therefore does the following: 1. Backfill all 0s in the matrix to NA. 2. Performs a mean across all samples which are known technical replicates of the same biological replicate. This mean is performed using na.rm = TRUE. Thus the entries which used to be 0 should no longer affect the result. 3. Recreate the expressionset with the modified set of samples.

Value

new expressionset

mean_by_factor	<i>Runs median_by_factor with fun set to 'mean'.</i>
----------------	--

Description

Runs median_by_factor with fun set to 'mean'.

Usage

```
mean_by_factor(data, fact = "condition")
```

Arguments

data	Input expt
fact	Metadata factor over which to perform mean().

median_by_factor	Create a data frame of the medians of rows by a given factor in the data.
------------------	---

Description

This assumes of course that (like expressionsets) there are separate columns for each replicate of the conditions. This will just iterate through the levels of a factor describing the columns, extract them, calculate the median, and add that as a new column in a separate data frame.

Usage

```
median_by_factor(data, fact = "condition", fun = "median")
```

Arguments

data	Data frame, presumably of counts.
fact	Factor describing the columns in the data.
fun	Optionally choose mean or another function.

Details

Used in write_expt() as well as a few random collaborations.

Value

Data frame of the medians.

See Also

[Biobase] [matrixStats]

Examples

```
## Not run:
compressed = median_by_factor(data, experiment$condition)

## End(Not run)
```

mesg	message() but with a verbose flag.
------	------------------------------------

Description

message() but with a verbose flag.

Usage

```
mesg(..., verbosity = NULL, warn = FALSE)
```

Arguments

...	parameters for message()
verbosity	actually print the message?
warn	Also print a warning?

my_identifyAUBlocks	<i>copy/paste the function from SeqTools and figure out where it falls on its ass.</i>
---------------------	--

Description

Yeah, I do not remember what I changed in this function.

Usage

```
my_identifyAUBlocks(x, min.length = 20, p.to.start = 0.8, p.to.end = 0.55)
```

Arguments

x	Sequence object
min.length	I dunno.
p.to.start	P to start of course
p.to.end	The p to end – wtf who makes names like this?

Value

a list of IRanges which contain a bunch of As and Us.

my_isva	<i>There are some funky scoping problems in isva::DoISVA().</i>
---------	---

Description

Thus I copy/pasted the function and attempted to address them here.

Usage

```
my_isva(
  data.m,
  pheno.v,
  cf.m = NULL,
  factor.log = FALSE,
  pvthCF = 0.01,
  th = 0.05,
  ncomp = NULL,
  icamethod = "fastICA"
)
```

Arguments

data.m	Input matrix.
pheno.v	Vector of conditions of interest in the data.
cf.m	Matrix of confounded conditions in the data.
factor.log	I forget.
pvthCF	Minimal p-value for considering.
th	threshold for inclusion.
ncomp	Number of SVA components to estimate.
icamethod	Which ICA implementation to use?

See Also

[isva]

my_runsims	<i>A version of PROPER::runsims which is (hopefully) a little more robust.</i>
------------	--

Description

When I was testing PROPER, it fell down mysteriously on a few occasions. The source ended up being in runsims(), ergo this function. This is therefore mostly a copy/paste of that function with a few small changes.

Usage

```
my_runsims(
  Nreps = c(3, 5, 7, 10),
  Nreps2,
  nsims = 100,
  sim.opts,
  DEmethod = c("edgeR", "DSS", "DESeq", "DESeq2"),
  verbose = TRUE
)
```

Arguments

Nreps	Vector of numbers of replicates to simulate.
Nreps2	Second vector of replicates.
nsims	How many simulations to perform?
sim.opts	Options provided in a list which include information about the expression, numbers of genes, logFC values, etc.
DEmethod	I suggest using only either edgeR or DESeq2.
verbose	Print some information along the way?

See Also

[PROPER]

mymakeContrasts	<i>A copy of limma::makeContrasts() with special sauce.</i>
-----------------	---

Description

This is a copy of limma::makeContrasts without the test of make.names() Because I want to be able to use it with interaction models potentially and if a model has first:second, make.names() turns the ':' to a '.' and then the equivalence test fails, causing makeContrasts() to error spuriously (I think).

Usage

```
mymakeContrasts(..., contrasts = NULL, levels)
```

Arguments

...	Conditions used to make the contrasts.
contrasts	Actual contrast names.
levels	contrast levels used.

Value

Same contrasts as used in makeContrasts, but with unique names.

See Also

[limma::makeContrasts()]

myretrieveKGML	<i>A couple functions from KEGGgraph that have broken</i>
----------------	---

Description

Some material in KEGGREST is borken.

Usage

```
myretrieveKGML(  
  pathway,  
  organism,  
  destfile,  
  silent = TRUE,  
  hostname = "http://www.kegg.jp",  
  ...  
)
```


Arguments

pathway	The path to query.
organism	Which organism to query?
destfile	File to which to download.
silent	Send stdout and stderr to dev null?
hostname	Host to download from (this is what is broken.)
...	Arglist!

network_from_matrix	<i>Given a matrix of scores (bit score, e-value, etc), create an adjacency graph.</i>
---------------------	---

Description

I am hoping to use this as the starting point for a generic network generator. In its current form it takes a matrix of pairwise scores and generates an adjacency graph of those scores.

Usage

```
network_from_matrix(
  scores,
  metadata = NULL,
  type = "distcor",
  simplify = TRUE,
  mode = "undirected",
  weighted = TRUE,
  diag = FALSE
)
```

Arguments

scores	tsv or matrix of scores with column and row names containing IDs.
metadata	Currently unused, but intended to provide a starting point for annotating the resulting adjacency network. When implemented, it should make use of the <code>annotate_network()</code> functions which follow.
type	Currently I only know of networks which use correlation, distance, and distcor matrices of the original scores; but I suspect a cursory glance at the WGCNA documentation will teach me that there are many more possibilities.
simplify	Return a simplified matrix without loops and redundancies?
mode	Network type to create, I don't yet understand the implications of changing this.
weighted	Add weights to the nodes? I also don't yet understand what happens when you mess with this.
diag	Include the matrix-diagonal nodes? I do not know when one would want these.

Value

igraph adjacency network.

noiseq_pairwise	<i>Perform pairwise comparisons using noiseq.</i>
-----------------	---

Description

Perform pairwise comparisons using noiseq.

Usage

```
noiseq_pairwise(
  input = NULL,
  model_fstring = "~ 0 + condition + batch",
  null_fstring = "~",
  model_svs = NULL,
  extra_contrasts = NULL,
  annot_df = NULL,
  force = FALSE,
  keepers = NULL,
  batch = FALSE,
  logtransf = FALSE,
  k = 0.5,
  norm = "tmm",
  factor = NULL,
  lc = 1,
  r = 20,
  adj = 1.5,
  a0per = 0.9,
  filter = 1,
  keep_underscore = TRUE,
  ...
)
```

Arguments

input	Expressionset to compare.
annot_df	Extra annotations.
keepers	Perform the comparison only over these specific contrasts instead of all.
k	Taken from the noiseq docs.
norm	Normalization method (noiseq oddly defaults to rpkm).
factor	Metadata factor over which to iterate.
lc	taken from the noiseq docs.
r	taken from the noiseq docs.
adj	taken from the noiseq docs.
a0per	taken from the noiseq docs.
filter	Filter the data?
...	Extra arguments.
conditions	Set of conditions to query

batches	known batches in the data, or a surrogate estimator.
model_cond	Add condition to the model?
model_batch	Add batch to the model, noiseseq has its own combat-like method, so maybe not necessary?

Value

List similar to `deseq_pairwise/edger_pairwise/etc.`

See Also

DOI:10.1093/nar/gkv711

normalize	<i>Normalization dispatcher.</i>
-----------	----------------------------------

Description

Normalization dispatcher.

Usage

```
normalize(input, ...)
```

normalize,expt-method	<i>Normalization of expt</i>
-----------------------	------------------------------

Description

Normalization of expt

Usage

```
## S4 method for signature 'expt'
normalize(input, ...)
```

normalize,SummarizedExperiment-method	<i>Normalization of se</i>
---------------------------------------	----------------------------

Description

Normalization of se

Usage

```
## S4 method for signature 'SummarizedExperiment'
normalize(input, ...)
```

normalize_counts	<i>Perform a simple normalization of a count table.</i>
------------------	---

Description

This provides shortcut interfaces for normalization functions from `deseq2`/`edger` and friends.

Usage

```
normalize_counts(  
  data,  
  design = NULL,  
  method = "raw",  
  condition_column = "condition",  
  ...  
)
```

Arguments

<code>data</code>	Matrix of count data.
<code>design</code>	Dataframe describing the experimental design. (conditions/batches/etc)
<code>method</code>	Normalization to perform: 'sflquantlqsmoothltnmmlupperquartileltnmmlrle' I keep wishy-washing on whether design is a required argument.
<code>...</code>	More arguments might be necessary.

Value

Dataframe of `normalized(counts)`

See Also

[`edgeR`] [`limma`] [`DESeq2`] [`preprocessCore`] [`BiocGenerics`]

Examples

```
## Not run:  
norm_table = normalize_counts(count_table, design = design, norm='qsmooth')  
  
## End(Not run)
```

normalize_expt	<i>Normalize the data of an expt object. Save the original data, and note what was done.</i>
----------------	--

Description

It is the responsibility of `normalize_expt()` to perform any arbitrary normalizations desired as well as to ensure that the data integrity is maintained. In order to do this, it writes the actions performed in `expt$state` and saves the intermediate steps of the normalization in `expt$intermediate_counts`. Furthermore, it should tell you every step of the normalization process, from count filtering, to normalization, conversion, transformation, and batch correction.

Usage

```
normalize_expt(
  expt,
  transform = "raw",
  norm = "raw",
  convert = "raw",
  batch = "raw",
  filter = FALSE,
  annotations = NULL,
  fasta = NULL,
  entry_type = "gene",
  batch1 = "batch",
  batch2 = NULL,
  batch_step = 4,
  low_to_zero = TRUE,
  thresh = 2,
  min_samples = 2,
  p = 0.01,
  A = 1,
  k = 1,
  cv_min = 0.01,
  cv_max = 1000,
  na_to_zero = FALSE,
  adjust_method = "ruv",
  verbose = TRUE,
  surrogates = "be",
  ...
)
```

Arguments

<code>expt</code>	Original expt.
<code>transform</code>	Transformation desired, usually log2.
<code>norm</code>	How to normalize the data? (raw, quant, sf, upperquartile, tmm, rle)
<code>convert</code>	Conversion to perform? (raw, cpm, rpkm, cp_seq_m)
<code>batch</code>	Batch effect removal tool to use? (limma sva fsva ruv etc)
<code>filter</code>	Filter out low/undesired features? (cbcb, pofa, kofa, others?)

annotations	Used for rpkm – probably not needed as this is in fData now.
fasta	Fasta file for cp_seq_m counting of oligos.
entry_type	For getting genelengths by feature type (rpkm or cp_seq_m).
batch1	Experimental factor to extract first.
batch2	Second factor to remove (only with limma's removebatcheffect()).
batch_step	From step 1-5, when should batch correction be applied?
low_to_zero	When log transforming, change low numbers (< 0) to 0 to avoid NaN?
thresh	Used by cbc_lowfilter().
min_samples	Also used by cbc_lowfilter().
p	Used by genefilter's pofa().
A	Also used by genefilter's pofa().
k	Used by genefilter's kofa().
cv_min	Used by genefilter's cv().
cv_max	Also used by genefilter's cv().
na_to_zero	Sometimes rpkm gives some NA values for very low numbers.
adjust_method	Given a set of sv estimates, change the counts with this method.
verbose	Print what is happening while the normalization is performed? I am not sure why, but I think they should be 0.
...	more options
use_original	Use the backup data in the expt class?

Value

Expt object with normalized data and the original data saved as 'original_expressionset'

See Also

[convert_counts()] [normalize_counts()] [batch_counts()] [filter_counts()] [transform_counts()]

Examples

```
## Not run:
normed <- normalize_expt(exp, transform='log2', norm='rle', convert='cpm',
                        batch='raw', filter='pofa')
normed_batch <- normalize_expt(exp, transform='log2', norm='rle', convert='cpm',
                              batch='sva', filter='pofa')

## End(Not run)
```

normalize_se	<i>Normalize a SummarizedExperiment and think about how I want to reimplement some of this.</i>
--------------	---

Description

Normalize a SummarizedExperiment and think about how I want to reimplement some of this.

Usage

```
normalize_se(
  se,
  transform = "raw",
  norm = "raw",
  convert = "raw",
  batch = "raw",
  filter = FALSE,
  annotations = NULL,
  fasta = NULL,
  entry_type = "gene",
  batch1 = "batch",
  batch2 = NULL,
  batch_step = 4,
  low_to_zero = TRUE,
  thresh = 2,
  min_samples = 2,
  p = 0.01,
  A = 1,
  k = 1,
  cv_min = 0.01,
  cv_max = 1000,
  na_to_zero = FALSE,
  adjust_method = "ruv",
  verbose = TRUE,
  surrogates = "be",
  surrogate_method = NULL,
  cpus = 4,
  noscale = TRUE,
  ...
)
```

Arguments

se	Summarized Experiment as input.
transform	Transformation desired, usually log2.
norm	How to normalize the data? (raw, quant, sf, upperquartile, tmm, rle)
convert	Conversion to perform? (raw, cpm, rpkm, cp_seq_m)
batch	Batch effect removal tool to use? (limma sva fsva ruv etc)
filter	Filter out low/undesired features? (cbcb, pofa, kofa, others?)

annotations	Used for rpkm – probably not needed as this is in fData now.
fasta	Fasta file for cp_seq_m counting of oligos.
entry_type	For getting genelengths by feature type (rpkm or cp_seq_m).
batch1	Experimental factor to extract first.
batch2	Second factor to remove (only with limma’s removebatcheffect()).
batch_step	From step 1-5, when should batch correction be applied?
low_to_zero	When log transforming, change low numbers (< 0) to 0 to avoid NaN?
thresh	Used by cbc_lowfilter().
min_samples	Also used by cbc_lowfilter().
p	Used by genefilter’s pofa().
A	Also used by genefilter’s pofa().
k	Used by genefilter’s kofa().
cv_min	Used by genefilter’s cv().
cv_max	Also used by genefilter’s cv().
na_to_zero	Sometimes rpkm gives some NA values for very low numbers.
adjust_method	Given a set of sv estimates, change the counts with this method.
verbose	Print what is happening while the normalization is performed? I am not sure why, but I think they should be 0.
...	more options

normalize_todo	<i>Simplified and ideally improved normalization function</i>
----------------	---

Description

This function is ideally should provide a simpler and more capable version of normalize_expt. I also want to move everything to using summarizedExperiments and this simpler method provides an opportunity.

Usage

```
normalize_todo(expt, todo = list())
```

Arguments

expt	Input data
todo	List of tasks to perform.

notes,expt-method	<i>A getter to pull the notes an expt.</i>
-------------------	--

Description

A getter to pull the notes an expt.

Usage

```
## S4 method for signature 'expt'  
notes(object)
```

Arguments

object	An expt.
--------	----------

orgdb_from_ah	<i>Get an orgdb from an AnnotationHub taxonID.</i>
---------------	--

Description

Ideally, annotationhub will one day provide a one-stop shopping source for a tremendous wealth of curated annotation databases, sort of like a non-obnoxious biomart. But for the moment, this function is more fragile than I would like.

Usage

```
orgdb_from_ah(ahid = NULL, title = NULL, species = NULL, type = "OrgDb")
```

Arguments

ahid	TaxonID from AnnotationHub
title	Title for the annotation hub instance
species	Species to download
type	Datatype to download

Value

An Orgdb instance

See Also

[AnnotationHub] [S4Vectors]

Examples

```
## Not run:  
org <- mytaxIdToOrgDb(species = "Leishmania", type = "TxDb")  
  
## End(Not run)
```

overlap_geneids	<i>Mostly as a reminder of how to get the gene IDs from a specific group in an upset plot.</i>
-----------------	--

Description

Given a set of groups from upsetr, extract the elements from one of them.

Usage

```
overlap_geneids(overlapping_groups, group)
```

Arguments

overlapping_groups	Result from overlap_groups, which just makes an indexed version of the genes by venn/upset group.
group	Name of the subset of interest, something like 'a:b' for the union of a:b.

overlap_groups	<i>Extract overlapping groups from an upset</i>
----------------	---

Description

Taken from: <https://github.com/hms-dbmi/UpSetR/issues/85> and lightly modified to match my style and so I could more easily understand what it is doing.

Usage

```
overlap_groups(input, sort = TRUE)
```

Arguments

input	upset data structure.
sort	Sort the result?

parse_msigdb	<i>Parse either xml or sqlite data from MSigDB. I think I will likely remove the xml version as I think the msigdb xml files are poorly formatted.</i>
--------------	--

Description

Parse either xml or sqlite data from MSigDB. I think I will likely remove the xml version as I think the msigdb xml files are poorly formatted.

Usage

```
parse_msigdb(filename)
```

Arguments

filename	Input file
----------	------------

parse_msigdb_sqlite	<i>Extract metadata from the msigdb sqlite data.</i>
---------------------	--

Description

Extract metadata from the msigdb sqlite data.

Usage

```
parse_msigdb_sqlite(filename)
```

Arguments

filename	db file.
----------	----------

parse_msigdb_xml	<i>Extract fun experimental metadata from a MSigDB xml file.</i>
------------------	--

Description

Extract fun experimental metadata from a MSigDB xml file.

Usage

```
parse_msigdb_xml(filename)
```

Arguments

filename	input file.
----------	-------------

pattern_count_genome *Find how many times a given pattern occurs in every gene of a genome.*

Description

There are times when knowing how many times a given string appears in a genome/CDS is helpful. This function provides that information and is primarily used by cp_seq_m().

Usage

```
pattern_count_genome(
  fasta,
  gff = NULL,
  pattern = "TA",
  type = "gene",
  id_col = "ID",
  key = NULL
)
```

Arguments

fasta	Genome sequence.
gff	Gff of annotation information from which to acquire CDS (if not provided it will just query the entire genome).
pattern	What to search for? This was used for tnseq and TA is the mariner insertion point.
type	Column to use in the gff file.
id_col	Column containing the gene IDs.
key	What type of entry of the gff file to key from?

Details

This is once again a place where mcols() usage might improve the overall quality of life.

Value

Data frame of gene names and number of times the pattern appears/gene.

See Also

[Biostrings] [Rsamtools::FaFile()] [Biostrings::PDict()]

Examples

```
pa_data <- get_paeruginosa_data()
pa_fasta <- pa_data[["fasta"]]
pa_gff <- pa_data[["gff"]]
ta_count <- pattern_count_genome(pa_fasta, pa_gff)
head(ta_count)
```

pc_fstatistics	<i>A sister function to sv_fstatistics()</i>
----------------	--

Description

TODO: Use this to yank a bunch of code out of pca_information and simplify.

Usage

```
pc_fstatistics(
  expt,
  pc_df = NULL,
  num_pcs = 10,
  queries = c("typeofcells", "visitnumber", "donor"),
  ...
)
```

Arguments

expt	Input expressionset, redo everything to use SE, stupid.
queries	List of metadata factors to query.
...	Parameters to plot_pca.

Details

Calculate f-statistics between metadata factors and principal components.

Random note to self: principle or principal? I can NEVER remember; also I am just pasting my docstring from the sv_fstatistics for the moment. I think the key observation: this might actually be Hector's idea to both Theresa and I in different contexts.

This is taken directly from Theresa's TMRC work and is her idea. I mainly want to be able to use it on a few datasets without risking typographical or logical errors. In addition, I would like to be able to play with things like the number of surrogates and/or other methods of estimating them. In addition, I have some f-statistics of PCs vs metadata in the function 'pca_information().' which I think is likely complementary to her work (which makes sense, Hector was her professor before she joined us, and Hector suggested the PC idea to me).

pca_highscores	<i>Get the highest/lowest scoring genes for every principle component.</i>
----------------	--

Description

This function uses princomp to acquire a principle component biplot for some data and extracts a dataframe of the top n genes for each component by score.

Usage

```
pca_highscores(expt, n = 20, cor = TRUE, vs = "means", logged = TRUE)
```

Arguments

expt	Experiment to poke.
n	Number of genes to extract.
cor	Perform correlations?
vs	Do a mean or median when getting ready to perform the pca?
logged	Check for the log state of the data and adjust as deemed necessary?

Value

a list including the princomp biplot, histogram, and tables of top/bottom n scored genes with their scores by component.

See Also

[stats] [stats::princomp]

Examples

```
## Not run:
information <- pca_highscores(df = df, conditions = cond, batches = bat)
information$pca_bitplot ## oo pretty

## End(Not run)
```

pca_information

Gather information about principle components.

Description

Calculate some information useful for generating PCA plots. `pca_information` seeks to gather together interesting information to make principle component analyses easier, including: the results from `(fast.)svd`, a table of the r^2 values, a table of the variances in the data, coordinates used to make a pca plot for an arbitrarily large set of PCs, correlations and fstats between experimental factors and the PCs, and heatmaps describing these relationships. Finally, it will provide a plot showing how much of the variance is provided by the top-n genes and (optionally) the set of all PCA plots with respect to one another. (PCx vs. PCy)

Usage

```
pca_information(
  expt,
  expt_design = NULL,
  expt_factors = c("condition", "batch"),
  colors_chosen = NULL,
  expt_state = NULL,
  num_components = NULL,
  plot_pcas = FALSE,
  ...
)
```

Arguments

expt	Data to analyze (usually <code>exprs(somedataset)</code>).
expt_design	Dataframe describing the experimental design, containing columns with useful information like the conditions, batches, number of cells, whatever...
expt_factors	Character list of experimental conditions to query for R^2 against the <code>fast.svd</code> of the data.
num_components	Number of principle components to compare the design factors against. If left null, it will query the same number of components as factors asked for.
plot_pcas	Plot the set of PCA plots for every pair of PCs queried.
...	Extra arguments for the <code>pca</code> plotter

Value

a list of fun `pca` information: `svd_u/d/v`: The `u/d/v` parameters from `fast.svd` `rsquared_table`: A table of the `rsquared` values between each factor and principle component `pca_variance`: A table of the `pca` variances `pca_data`: Coordinates for a `pca` plot `pca_cor`: A table of the correlations between the factors and principle components `anova_fstats`: the sum of the residuals with the factor vs without (manually calculated) `anova_f`: The result from performing `anova(withfactor, withoutfactor)`, the F slot `anova_p`: The p-value calculated from the `anova()` call `anova_sums`: The RSS value from the above `anova()` call `cor_heatmap`: A heatmap from `recordPlot()` describing `pca_cor`.

Warning

This function has gotten too damn big and needs to be split up.

See Also

`[corpcor]` `[plot_pca()]` `[plot_pcs()]` `[stats::lm()]`

Examples

```
## Not run:
pca_info = pca_information(exprs(some_expt), some_design, "all")
pca_info

## End(Not run)
```

pct_all_kegg	<i>Extract the percent differentially expressed genes for all KEGG pathways.</i>
--------------	--

Description

KEGGgraph provides some interesting functionality for mapping KEGGids and examining the pieces. This attempts to use that in order to evaluate how many 'significant' genes are in a given pathway.

Usage

```
pct_all_kegg(
  all_ids,
  sig_ids,
  organism = "dme",
  pathways = "all",
  pathdir = "kegg_pathways",
  verbose = FALSE,
  ...
)
```

Arguments

all_ids	Set of all gene IDs in a given analysis.
sig_ids	Set of significant gene IDs.
organism	KEGG organism identifier.
pathways	What pathways to look at?
pathdir	Directory into which to copy downloaded pathway files.
verbose	Talky talky?
...	Options I might pass from other functions are dropped into arglist.

Value

Dataframe including the filenames, percentages, nodes included, and differential nodes.

See Also

[KEGGgraph] [KEGGREST]

pct_kegg_diff	<i>Extract the percent differentially expressed genes in a given KEGG pathway.</i>
---------------	--

Description

KEGGgraph provides some interesting functionality for mapping KEGGids and examining the pieces. This attempts to use that in order to evaluate how many 'significant' genes are in a given pathway.

Usage

```
pct_kegg_diff(
  all_ids,
  sig_ids,
  pathway = "00500",
  organism = "dme",
  pathdir = "kegg_pathways",
  ...
)
```


Arguments

all_ids	Set of all gene IDs in a given analysis.
sig_ids	Set of significant gene IDs.
pathway	Numeric pathway identifier.
organism	KEGG organism identifier.
pathdir	Directory into which to copy downloaded pathway files.
...	Options I might pass from other functions are dropped into arglist.

Value

Percent genes/pathway deemed significant.

See Also

[KEGGgraph] [KEGGREST]

pData,expt-method	<i>A getter to pull the experimental metadata from an expt.</i>
-------------------	---

Description

A getter to pull the experimental metadata from an expt.

Usage

```
## S4 method for signature 'expt'
pData(object)
```

Arguments

object	An expt.
--------	----------

pData,SummarizedExperiment-method	<i>A getter to pull the experimental metadata from a SummarizedExperiment.</i>
-----------------------------------	--

Description

This is essentially synonymous with colData, except I cannot seem to remember that function when I am working; so I just added another signature to pData.

Usage

```
## S4 method for signature 'SummarizedExperiment'
pData(object)
```

Arguments

object	An expt.
--------	----------

`pData<-`, *expt*, *ANY*-method

A setter to put the experimental metadata into an expt.

Description

A setter to put the experimental metadata into an expt.

Usage

```
## S4 replacement method for signature 'expt,ANY'
pData(object) <- value
```

Arguments

`object` An expt.

`pData<-`, *SummarizedExperiment*, *ANY*-method

A setter to put the experimental metadata into a SummarizedExperiment.

Description

This is essentially synonymous with `colData`, except I cannot seem to remember that function when I am working; so I just added another signature to `pData`.

Usage

```
## S4 replacement method for signature 'SummarizedExperiment,ANY'
pData(object) <- value
```

Arguments

`object` An expt.

plot_3d_pca	<i>Something silly for Najib.</i>
-------------	-----------------------------------

Description

This will make him very happy, but I remain skeptical.

Usage

```
plot_3d_pca(pc_result, components = c(1, 2, 3), file = "3dpca.html")
```

Arguments

pc_result	The result from plot_pca()
components	List of three axes by component.
file	File to write the created plotly object.

Value

List containing the plotly data and filename for the html widget.

See Also

[plotly] [htmlwidgets]

plot_batchsv	<i>Make a dotplot of known batches vs. SVs.</i>
--------------	---

Description

This should make a quick df of the factors and surrogates and plot them. Maybe it should be folded into plot_svfactor? Hmm, I think first I will write this and see if it is better.

Usage

```
plot_batchsv(
  expt,
  sv,
  sv = 1,
  batch_column = "batch",
  condition_column = "condition",
  factor_type = "factor",
  id_column = "sampleid"
)
```

Arguments

expt	Experiment from which to acquire the design, counts, etc.
svs	Set of surrogate variable estimations from sva/svg or batch estimates.
sv	Which surrogate variable to show?
batch_column	Which experimental design column to use?
factor_type	This may be a factor or range, it is intended to plot a scatterplot if it is a range, a dotplot if a factor.
id_column	Use this column for the sample IDs.

Value

Plot of batch vs surrogate variables as per Leek's work.

See Also

[sva] [ggplot2]

Examples

```
## Not run:
estimate_vs_snps <- plot_batchsv(start, surrogate_estimate, "snpcategory")

## End(Not run)
```

plot_bcv

Steal edgeR's plotBCV() and make it a ggplot2.

Description

This was written primarily to understand what that function is doing in edgeR.

Usage

```
plot_bcv(data)
```

Arguments

data	Dataframe/expt/exprs with count data
------	--------------------------------------

Value

Plot of the BCV a la ggplot2.

See Also

[edgeR::plotBCV()] [ggplot2]

Examples

```
## Not run:
bcv <- plot_bcv(expt)
summary(bcv$data)
bcv$plot

## End(Not run)
```

plot_boxplot

*Make a ggplot boxplot of a set of samples.***Description**

Boxplots and density plots provide complementary views of data distributions. The general idea is that if the box for one sample is significantly shifted from the others, then it is likely an outlier in the same way a density plot shifted is an outlier.

Usage

```
plot_boxplot(
  data,
  colors = NULL,
  plot_title = NULL,
  order = NULL,
  violin = FALSE,
  scale = NULL,
  expt_names = NULL,
  label_chars = 10,
  ...
)
```

Arguments

data	Expt or data frame set of samples.
colors	Color scheme, if not provided will make its own.
plot_title	A title!
order	Set the order of boxen.
violin	Print this as a violin rather than a just box/whiskers?
scale	Whether to log scale the y-axis.
expt_names	Another version of the sample names for printing.
label_chars	Maximum number of characters for abbreviating sample names.
...	More parameters are more fun!

Value

Ggplot2 boxplot of the samples. Each boxplot contains the following information: a centered line describing the median value of counts of all genes in the sample, a box around the line describing the inner-quartiles around the median (quartiles 2 and 3 for those who are counting), a vertical line above/below the box which shows 1.5x the inner quartile range (a common metric of the non-outliers), and single dots for each gene which is outside that range. A single dot is transparent.

See Also

[ggplot2]

Examples

```
## Not run:
a_boxplot <- plot_boxplot(expt)
a_boxplot ## ooo pretty boxplot look at the lines

## End(Not run)
```

plot_cleaved	<i>Plot the average mass and expected intensity of a set of sequences given an enzyme.</i>
--------------	--

Description

This uses the cleaver package to generate a plot of expected intensities vs. weight for a list of protein sequences.

Usage

```
plot_cleaved(pep_sequences, enzyme = "trypsin", start = 600, end = 1500)
```

Arguments

pep_sequences	Set of protein sequences.
enzyme	One of the allowed enzymes for cleaver.
start	Limit the set of fragments from this point
end	to this point.

Value

List containing the distribution of weights and the associated plot.

plot_corheat	<i>Make a heatmap.3 description of the correlation between samples.</i>
--------------	---

Description

Given a set of count tables and design, this will calculate the pairwise correlations and plot them as a heatmap. It attempts to standardize the inputs and eventual output.

Usage

```
plot_corheat(
  expt_data,
  expt_colors = NULL,
  expt_design = NULL,
  method = "pearson",
  expt_names = NULL,
  batch_row = "batch",
  plot_title = NULL,
  label_chars = 10,
  ...
)
```

Arguments

expt_data	Dataframe, expt, or expressionset to work with.
expt_colors	Color scheme for the samples, not needed if this is an expt.
expt_design	Design matrix describing the experiment, not needed if this is an expt.
method	Correlation statistic to use. (pearson, spearman, kendall, robust).
expt_names	Alternate names to use for the samples.
batch_row	Name of the design row used for 'batch' column colors.
plot_title	Title for the plot.
label_chars	Limit on the number of label characters.
...	More options are wonderful!

Value

Gplots heatmap describing describing how the samples are clustering vis a vis pairwise correlation.

See Also

[grDevice] [gplot2::heatmap.2()]

Examples

```
## Not run:
corheat_plot <- hppl_corheat(expt = expt, method = "robust")

## End(Not run)
```

plot_de_pvals

Given a DE table with p-values, plot them.

Description

Plot a multi-histogram containing (adjusted)p-values.

Usage

```
plot_de_pvals(
  combined_data,
  type = "limma",
  p_type = "both",
  columns = NULL,
  ...
)
```

Arguments

combined_data	Table to extract the values from.
type	If provided, extract the type_p and type_adj columns.
p_type	Which type of pvalue to show (adjusted, raw, or all)?
columns	Otherwise, extract whatever columns are provided.
...	Arguments passed through to the histogram plotter

Details

The assumption of this plot is that the adjustment will significantly decrease the representation of genes in the 'highly significant' range of p-values. However, it is hoped that it will not utterly remove them.

Value

Multihistogram of the result.

See Also

[plot_histogram()]

plot_density	Create a density plot, showing the distribution of each column of data.
--------------	---

Description

Density plots and boxplots are cousins and provide very similar views of data distributions. Some people like one, some the other. I think they are both colorful and fun!

Usage

```
plot_density(
  data,
  colors = NULL,
  expt_names = NULL,
  position = "identity",
  direct = NULL,
  fill = NULL,
  plot_title = NULL,
  scale = NULL,
```



```

    colors_by = "condition",
    label_chars = 10,
    ...
)

```

Arguments

data	Expt, expressionset, or data frame.
colors	Color scheme to use.
expt_names	Names of the samples.
position	How to place the lines, either let them overlap (identity), or stack them.
direct	Use direct.labels for labeling the plot?
fill	Fill the distributions? This might make the plot unreasonably colorful.
plot_title	Title for the plot.
scale	Plot on the log scale?
colors_by	Factor for coloring the lines
label_chars	Maximum number of characters in sample names before abbreviation.
...	sometimes extra arguments might come from graph_metrics()

Value

ggplot2 density plot!

See Also

[ggplot2]

Examples

```

## Not run:
funkytown <- plot_density(data)

## End(Not run)

```

plot_disheat	<i>Make a heatmap.³ of the distances (euclidean by default) between samples.</i>
--------------	---

Description

Given a set of count tables and design, this will calculate the pairwise distances and plot them as a heatmap. It attempts to standardize the inputs and eventual output.

Usage

```
plot_disheat(
  expt_data,
  expt_colors = NULL,
  expt_design = NULL,
  method = "euclidean",
  expt_names = NULL,
  batch_row = "batch",
  plot_title = NULL,
  label_chars = 10,
  ...
)
```

Arguments

expt_data	Dataframe, expt, or expressionset to work with.
expt_colors	Color scheme (not needed if an expt is provided).
expt_design	Design matrix (not needed if an expt is provided).
method	Distance metric to use.
expt_names	Alternate names to use for the samples.
batch_row	Name of the design row used for 'batch' column colors.
plot_title	Title for the plot.
label_chars	Limit on the number of label characters.
...	More parameters!

Value

a recordPlot() heatmap describing the distance between samples.

See Also

[gplots::heatmap.2()]

Examples

```
## Not run:
disheat_plot = plot_disheat(expt = expt, method = "euclidean")

## End(Not run)
```

plot_dist_scatter	<i>Make a scatter plot between two sets of numbers with a cheesy distance metric and some statistics of the two sets.</i>
-------------------	---

Description

The distance metric should be codified and made more intelligent. Currently it creates a dataframe of distances which are absolute distances from each axis, multiplied by each other, summed by axis, then normalized against the maximum.

Usage

```
plot_dist_scatter(df, size = 2, xlab = NULL, ylab = NULL)
```

Arguments

df	Dataframe likely containing two columns.
size	Size of the dots.
xlab	x-axis label.
ylab	y-axis label.

Value

Ggplot2 scatter plot. This plot provides a "bird's eye" view of two data sets. This plot assumes the two data structures are not correlated, and so it calculates the median/mad of each axis and uses these to calculate a stupid, home-grown distance metric away from both medians. This distance metric is used to color dots which are presumed to be interesting because they are far from 'normal.' This will make a fun clicky googleVis graph if requested.

See Also

```
[ggplot2::geom_point()] [plot_linear_scatter()]
```

Examples

```
## Not run:
dist_scatter(lotsofnumbers_intwo_columns)

## End(Not run)
```

plot_enrichresult

Invoke the various fun plots created by Guangchuang Yu.

Description

I would like to replace all of my bad ontology plotting functions with the nicer versions from enrichplot. I therefore have a series of functions which recast my ontology results to enrichResults, which is suitable for those plots.

Usage

```
plot_enrichresult(enrichresult, ...)
```

Arguments

enrichresult	S4 object of type enrichResult.
--------------	---------------------------------

Details

For the moment this is just a skeleton with reminders to me for the various plots available. Also, when I looked up these plots it appears that clusterProfiler has some new functionality to make it easier to send results to it.

plot_epitrochoid	<i>Make epitrochoid plots!</i>
------------------	--------------------------------

Description

7, 2, 6, 7 should give a pretty result.

Usage

```
plot_epitrochoid(
  radius_a = 7,
  radius_b = 2,
  dist_b = 6,
  revolutions = 7,
  increments = 6480
)
```

Arguments

radius_a	Radius of the major circle
radius_b	And the smaller circle.
dist_b	between b and the drawing point.
revolutions	How many times to revolve through the spirograph.
increments	How many dots to lay down while writing.

plot_essentiality	<i>Plot the essentiality of a library as per DeJesus et al.</i>
-------------------	---

Description

This provides a plot of the essentiality metrics 'zbar' with respect to gene. In my pipeline, I use their stand alone mh_ess and tn_hmm packages. The result files produced are named mh_ess-sequence_prefix-mapping_parameters_gene_tas_m_parameter.csv where sequence_prefix is the base-name() of the input sequence file, mapping_parameters are a string describing the bowtie mapping used, and m_parameter is usually one of 1,2,4,8,16,32 and defines the lower limit of read depth to be considered useful by the mh_ess package. Thus, before using this, one may want to look at the result from tseq_saturation() to see if there is a most-appropriate m_parameter. I think I should figure out a heuristic to choose the m, but I am not sure what it would be, perhaps the median of the hits summary?

Usage

```
plot_essentiality(
  file,
  order_by = "posterior_zbar",
  keep_esses = FALSE,
  min_sig = 0.0371,
  max_sig = 0.9902
)
```

Arguments

file	Result from the DeJesus essentiality package. I think this has been effectively replaced by their TRANSIT package.
order_by	What column to use when ordering the data?
keep_esses	Keep entries in the data which are 'S' meaning insufficient evidence.
min_sig	Minimal value below which a gene is deemed non-essential and above which it is uncertain.
max_sig	Maximum value above which a gene is deemed essential and below which it is uncertain.

Value

A couple of plots

See Also

[ggplot2]

plot_exprs_by_chromosome

Create a plot showing relative expression with respect to each chromosome/contig.

Description

Create a plot showing relative expression with respect to each chromosome/contig.

Usage

```
plot_exprs_by_chromosome(
  expt,
  chromosome_column = "chromosome",
  scaffolds = TRUE,
  min_genes = 10
)
```

Arguments

expt	Input expressionset.
chromosome_column	Annotation column containing the chromosome ID.
scaffolds	Include scaffolds in addition to the actual chromosomes.
min_genes	The minimum number of genes which should be on the 'chromosome' before it is considered worth considering.

```
plot_forest_from_regression
```

Given the result from one of the regression testers, plot it!

Description

Given the result from one of the regression testers, plot it!

Usage

```
plot_forest_from_regression(
  plot_df,
  percent = 95,
  type = "logistic",
  iterate = TRUE,
  family = "binomial",
  intercept = FALSE,
  base_size = 18,
  title_size = 22,
  axis_size = 20,
  query = "condition"
)
```

Arguments

percent	Confidence interval chosen.
type	Either linear or logistic.
iterate	Was this a series of single-variable regressions, or all in one?
family	Only currently used for logistic.
intercept	Include the intercept in the plot?
df	The primary dataframe from one of the sister regression functions above.

```
plot_fun_venn
```

A quick wrapper around venneuler to help label stuff

Description

venneuler makes pretty venn diagrams, but no labels!

Usage

```
plot_fun_venn(
  ones = c(),
  twos = c(),
  threes = c(),
  fours = c(),
  fives = c(),
  factor = 0.9
)
```

Arguments

ones	Character list of singleton categories
twos	Character list of doubletone categories
threes	Character list of tripletone categories
fours	Character list of quad categories
fives	Character list of quint categories
factor	Currently unused, but intended to change the radial distance to the label from the center of each circle.

Value

Two element list containing the venneuler data and the plot.

See Also

[venneuler]

plot_goseq_pval	<i>Make a pvalue plot from goseq data.</i>
-----------------	--

Description

With minor changes, it is possible to push the goseq results into a clusterProfiler-ish pvalue plot. This handles those changes and returns the ggplot results.

Usage

```
plot_goseq_pval(
  goterms,
  wrapped_width = 30,
  cutoff = 0.1,
  x_column = "score",
  order_by = "score",
  decreasing = FALSE,
  n = 30,
  mincat = 5,
  level = NULL,
  ...
)
```

Arguments

goterms	Some data from goseq!
wrapped_width	Number of characters before wrapping to help legibility.
cutoff	Pvalue cutoff for the plot.
x_column	Choose the data column to put on the x-axis of the plot.
order_by	Choose the data column for ordering the bars.
decreasing	When ordering the bars, go up or down?

n	How many groups to include?
mincat	Minimum size of the category for inclusion.
level	Levels of the ontology tree to use.
...	Arguments passed from simple_goseq()

Value

Plots!

See Also

[ggplot2]

plot_gostats_pval	<i>Make a pvalue plot similar to that from clusterprofiler from gostats data.</i>
-------------------	---

Description

clusterprofiler provides beautiful plots describing significantly overrepresented categories. This function attempts to expand the repertoire of data available to them to include data from gostats. The pval_plot function upon which this is based now has a bunch of new helpers now that I understand how the ontology trees work better, this should take advantage of that, but currently does not.

Usage

```
plot_gostats_pval(
  gs_result,
  wrapped_width = 20,
  cutoff = 0.1,
  n = 30,
  group_minsize = 5
)
```

Arguments

gs_result	Ontology search results.
wrapped_width	Make the text large enough to read.
cutoff	What is the maximum pvalue allowed?
n	How many groups to include in the plot?
group_minsize	Minimum group size before inclusion.

Value

Plots!

See Also

[ggplot2]

plot_gprofiler_pval	<i>Make a pvalue plot from gprofiler data.</i>
---------------------	--

Description

The p-value plots from clusterProfiler are pretty, this sets the gprofiler data into a format suitable for plotting in that fashion and returns the resulting plots of significant ontologies.

Usage

```
plot_gprofiler_pval(  
  gp_result,  
  wrapped_width = 30,  
  cutoff = 0.1,  
  n = 30,  
  group_minsize = 5,  
  scorer = "recall",  
  ...  
)
```

Arguments

gp_result	Some data from gProfiler.
wrapped_width	Maximum width of the text names.
cutoff	P-value cutoff for the plots.
n	Maximum number of ontologies to include.
group_minsize	Minimum ontology group size to include.
scorer	Which column to use for scoring the data.
...	Options I might pass from other functions are dropped into arglist.

Value

List of MF/BP/CC pvalue plots.

See Also

[ggplot2]

plot_gprofiler2_pval	<i>Make a pvalue plot from gprofiler data.</i>
----------------------	--

Description

The p-value plots from clusterProfiler are pretty, this sets the gprofiler data into a format suitable for plotting in that fashion and returns the resulting plots of significant ontologies.

Usage

```
plot_gprofiler2_pval(
  gp_result,
  wrapped_width = 30,
  cutoff = 0.1,
  n = 30,
  group_minsize = 5,
  scorer = "recall",
  ...
)
```

Arguments

gp_result	Some data from gProfiler.
wrapped_width	Maximum width of the text names.
cutoff	P-value cutoff for the plots.
n	Maximum number of ontologies to include.
group_minsize	Minimum ontology group size to include.
scorer	Which column to use for scoring the data.
...	Options I might pass from other functions are dropped into arglist.

Value

List of MF/BP/CC pvalue plots.

See Also

[ggplot2]

plot_heatmap	<i>Make a heatmap.3 plot, does the work for plot_disheat and plot_corheat.</i>
--------------	--

Description

This does what is says on the tin. Sets the colors for correlation or distance heatmaps, handles the calculation of the relevant metrics, and plots the heatmap.

Usage

```
plot_heatmap(
  expt_data,
  expt_colors = NULL,
  expt_design = NULL,
  method = "pearson",
  expt_names = NULL,
  type = "correlation",
  batch_row = "batch",
  plot_title = NULL,
  label_chars = 10,
  ...
)
```

Arguments

expt_data	Dataframe, expt, or expressionset to work with.
expt_colors	Color scheme for the samples.
expt_design	Design matrix describing the experiment vis a vis conditions and batches.
method	Distance or correlation metric to use.
expt_names	Alternate names to use for the samples.
type	Defines the use of correlation, distance, or sample heatmap.
batch_row	Name of the design row used for 'batch' column colors.
plot_title	Title for the plot.
label_chars	Limit on the number of label characters.
...	I like ellipses!

Value

a recordPlot() heatmap describing the distance between samples.

See Also

[gplots::heatmap.2()]

plot_heatmap,data.frame-method

Run plot_heatmap with a dataframe as input.

Description

Run plot_heatmap with a dataframe as input.

Usage

```
## S4 method for signature 'data.frame'
plot_heatmap(
  expt_data,
  expt_colors = NULL,
  expt_design = NULL,
  method = "pearson",
  expt_names = NULL,
  type = "correlation",
  batch_row = "batch",
  plot_title = NULL,
  label_chars = 10,
  ...
)
```

plot_heatmap,ExpressionSet-method

Run plot_heatmap with an ExpressionSet as input.

Description

Run plot_heatmap with an ExpressionSet as input.

Usage

```
## S4 method for signature 'ExpressionSet'
plot_heatmap(
  expt_data,
  expt_colors = NULL,
  expt_design = NULL,
  method = "pearson",
  expt_names = NULL,
  type = "correlation",
  batch_row = "batch",
  plot_title = NULL,
  label_chars = 10,
  ...
)
```

plot_heatmap,expt-method

Run plot_heatmap with an expt as input.

Description

Run plot_heatmap with an expt as input.

Usage

```
## S4 method for signature 'expt'
plot_heatmap(
  expt_data,
  expt_colors = NULL,
  expt_design = NULL,
  method = "pearson",
  expt_names = NULL,
  type = "correlation",
  batch_row = "batch",
  plot_title = NULL,
  label_chars = 10,
  ...
)
```

plot_heatmap, SummarizedExperiment-method

Run plot_heatmap with a SummarizedExperiment as input.

Description

Run plot_heatmap with a SummarizedExperiment as input.

Usage

```
## S4 method for signature 'SummarizedExperiment'
plot_heatmap(
  expt_data,
  expt_colors = NULL,
  expt_design = NULL,
  method = "pearson",
  expt_names = NULL,
  type = "correlation",
  batch_row = "batch",
  plot_title = NULL,
  label_chars = 10,
  ...
)
```

plot_heatplus

Potential replacement for heatmap.2 based plots.

Description

Heatplus is an interesting tool, I have a few examples of using it and intend to include them here.

Usage

```
plot_heatplus(
  expt,
  type = "correlation",
  method = "pearson",
  annot_columns = "batch",
  annot_rows = "condition",
  cutoff = 1,
  cluster_colors = NULL,
  scale = "none",
  cluster_width = 2,
  cluster_function = NULL,
  heatmap_colors = NULL
)
```

Arguments

expt	Experiment to try plotting.
type	What comparison method to use on the data (distance or correlation)?
method	What distance/correlation method to perform?
annot_columns	Set of columns to include as terminal columns next to the heatmap.
annot_rows	Set of columns to include as terminal rows below the heatmap.
cutoff	Cutoff used to define color changes in the annotated clustering.
cluster_colors	Choose colors for the clustering?
scale	Scale the heatmap colors?
cluster_width	How much space to include between clustering?
cluster_function	Choose an alternate clustering function than hclust()?
heatmap_colors	Choose your own heatmap cluster palette?

Value

List containing the returned heatmap along with some parameters used to create it.

See Also

[Heatplus] [fastcluster]

plot_histogram	<i>Make a pretty histogram of something.</i>
----------------	--

Description

A shortcut to make a ggplot2 histogram which makes an attempt to set reasonable bin widths and set the scale to log if that seems a good idea.

Usage

```
plot_histogram(
  df,
  binwidth = NULL,
  log = FALSE,
  bins = 500,
  adjust = 1,
  fillcolor = "darkgrey",
  color = "black"
)
```

Arguments

df	Dataframe of lots of pretty numbers.
binwidth	Width of the bins for the histogram.
log	Replot on the log scale?
bins	Number of bins for the histogram.
adjust	The prettification parameter in the ggplot2 density.
fillcolor	Change the fill colors of the plotted elements?
color	Change the color of the lines of the plotted elements?

Value

Ggplot histogram.

See Also

[ggplot2]

Examples

```
## Not run:
kittytime = plot_histogram(df)

## End(Not run)
```

plot_hypotrochoid	<i>Make hypotrochoid plots!</i>
-------------------	---------------------------------

Description

3,7,1 should give the classic 7 leaf clover

Usage

```
plot_hypotrochoid(
  radius_a = 3,
  radius_b = 7,
  dist_b = 1,
  revolutions = 7,
  increments = 6480
)
```

Arguments

radius_a	Radius of the major circle
radius_b	And the smaller circle.
dist_b	between b and the drawing point.
revolutions	How many times to revolve through the spirograph.
increments	How many dots to lay down while writing.

plot_intensity_mz	<i>Plot mzXML peak intensities with respect to m/z.</i>
-------------------	---

Description

I want to have a pretty plot of peak intensities and m/z. The plot provided by this function is interesting, but suffers from some oddities; notably that it does not currently separate the MS1 and MS2 data.

Usage

```
plot_intensity_mz(  
  mzxml_data,  
  loess = FALSE,  
  alpha = 0.5,  
  ms1 = TRUE,  
  ms2 = TRUE,  
  x_scale = NULL,  
  y_scale = NULL,  
  ...  
)
```

Arguments

mzxml_data	The data structure from extract_mzxml or whatever it is.
loess	Do a loess smoothing from which to extract a function describing the data? This is terribly slow, and in the data I have examined so far, not very helpful, so it is FALSE by default.
alpha	Make the plotted dots opaque to this degree.
ms1	Include MS1 data in the plot?
ms2	Include MS2 data in the plot?
x_scale	Plot the x-axis on a non linear scale?
y_scale	Plot the y-axis on a non linear scale?
...	Extra arguments for the downstream functions.

Value

ggplot2 goodness.

plot_legend	<i>Scab the legend from a PCA plot and print it alone</i>
-------------	---

Description

This way I can have a legend object to move about.

Usage

```
plot_legend(stuff)
```

Arguments

stuff	This can take either a ggplot2 pca plot or some data from which to make one.
-------	--

Value

A legend!

plot_libsize	<i>Make a ggplot graph of library sizes.</i>
--------------	--

Description

It is often useful to have a quick view of which samples have more/fewer reads. This does that and maintains one's favorite color scheme and tries to make it pretty!

Usage

```
plot_libsize(
  data,
  condition = NULL,
  colors = NULL,
  text = TRUE,
  order = NULL,
  plot_title = NULL,
  yscale = NULL,
  expt_names = NULL,
  label_chars = 10,
  ...
)
```

Arguments

data	Expt, dataframe, or expressionset of samples.
condition	Vector of sample condition names.
colors	Color scheme if the data is not an expt.
text	Add the numeric values inside the top of the bars of the plot?
order	Explicitly set the order of samples in the plot?

<code>plot_title</code>	Title for the plot.
<code>yscale</code>	Whether or not to log10 the y-axis.
<code>expt_names</code>	Design column or manually selected names for printing sample names.
<code>label_chars</code>	Maximum number of characters before abbreviating sample names.
<code>...</code>	More parameters for your good time!

Value

a ggplot2 bar plot of every sample's size

See Also

[ggplot2] [prettyNum] [plot_sample_bars()]

Examples

```
## Not run:
  libsize_plot <- plot_libsize(expt = expt)
  libsize_plot ## ooo pretty bargraph

## End(Not run)
```

`plot_libsize,data.frame,factor,character-method`

Run plot_libsize() with a dataframe as input.

Description

Run plot_libsize() with a dataframe as input.

Usage

```
## S4 method for signature 'data.frame,factor,character'
plot_libsize(
  data,
  condition = NULL,
  colors = NULL,
  text = TRUE,
  order = NULL,
  plot_title = NULL,
  yscale = NULL,
  expt_names = NULL,
  label_chars = 10,
  ...
)
```

plot_libsize, ExpressionSet, ANY, ANY-method

Run plot_libsize() with an ExpressionSet as input.

Description

Run plot_libsize() with an ExpressionSet as input.

Usage

```
## S4 method for signature 'ExpressionSet,ANY,ANY'
plot_libsize(
  data,
  condition = NULL,
  colors = NULL,
  text = TRUE,
  order = NULL,
  plot_title = NULL,
  yscale = NULL,
  expt_names = NULL,
  label_chars = 10,
  ...
)
```

plot_libsize, expt, ANY, ANY-method

Run plot_libsize() with an expt as input.

Description

Run plot_libsize() with an expt as input.

Usage

```
## S4 method for signature 'expt,ANY,ANY'
plot_libsize(
  data,
  condition = NULL,
  colors = NULL,
  text = TRUE,
  order = NULL,
  plot_title = NULL,
  yscale = NULL,
  expt_names = NULL,
  label_chars = 10,
  ...
)
```

plot_libsize, SummarizedExperiment, ANY, ANY-method

Send a SummarizedExperiment to plot_libsize().

Description

Send a SummarizedExperiment to plot_libsize().

Usage

```
## S4 method for signature 'SummarizedExperiment,ANY,ANY'
plot_libsize(
  data,
  condition = NULL,
  colors = NULL,
  text = TRUE,
  order = NULL,
  plot_title = NULL,
  yscale = NULL,
  expt_names = NULL,
  label_chars = 10,
  ...
)
```

Arguments

data	SummarizedExperiment presumably created by create_se().
condition	Set of conditions observed in the metadata, overriding the metadata in the SE.
colors	Set of colors for the plot, overriding the SE metadata.
text	Print text with the counts/sample observed at the top of the bars?
order	Optionally redefine the order of the bars of the plot.
plot_title	Plot title!
yscale	Explicitly set the scale on the log or base10 scale.
expt_names	Optionally change the names of the bars.
label_chars	If the names of the bars are larger than this, abbreviate them.
...	Additional arbitrary arguments.

Value

Plot of library sizes and a couple tables describing the data.

plot_libsize_prepost *Visualize genes observed before/after filtering.*

Description

Thanks to Sandra Correia for this! This function attempts to represent the change in the number of genes which are well/poorly represented in the data before and after performing a low-count filter.

Usage

```
plot_libsize_prepost(
  expt,
  low_limit = 2,
  filter = TRUE,
  num_color = "black",
  num_size = 4,
  ...
)
```

Arguments

expt	Input expressionset.
low_limit	Threshold to define 'low-representation.'
filter	Method used to low-count filter the data.
...	Extra arbitrary arguments to pass to normalize_expt()

Value

Bar plot showing the number of genes below the low_limit before and after filtering the data.

See Also

[plot_libsize()] [filter_counts()]

plot_linear_scatter *Make a scatter plot between two groups with a linear model superimposed and some supporting statistics.*

Description

Make a scatter plot between two groups with a linear model superimposed and some supporting statistics.

Usage

```

plot_linear_scatter(
  df,
  cormethod = "pearson",
  size = 2,
  loess = FALSE,
  xcol = NULL,
  ycol = NULL,
  text_col = NULL,
  logfc = 2,
  identity = FALSE,
  z = 1.5,
  z_lines = FALSE,
  first = NULL,
  second = NULL,
  base_url = NULL,
  color_weights = TRUE,
  xlab = NULL,
  ylab = NULL,
  model_type = "robust",
  add_equation = TRUE,
  add_rsqa = TRUE,
  add_cor = TRUE,
  label_prefix = "Expression of",
  color_high = NULL,
  color_low = NULL,
  alpha = 0.4,
  ...
)

```

Arguments

<code>df</code>	Dataframe likely containing two columns.
<code>cormethod</code>	What type of correlation to check?
<code>size</code>	Size of the dots on the plot.
<code>loess</code>	Add a loess estimation?
<code>xcol</code>	Column name of x-values
<code>ycol</code>	Column name of y-values#'
<code>text_col</code>	Column containing text annotations.
<code>logfc</code>	Point out genes with a specific logfc.
<code>identity</code>	Add the identity line?
<code>z</code>	Use this z-score cutoff.
<code>z_lines</code>	Include lines defining the z-score boundaries.
<code>first</code>	First column to plot.
<code>second</code>	Second column to plot.
<code>base_url</code>	Base url to add to the plot.
<code>xlab</code>	Alternate x-axis label.
<code>ylab</code>	Alternate x-axis label.

color_high	Chosen color for points significantly above the mean.
color_low	Chosen color for points significantly below the mean.
alpha	Choose an alpha channel to define how see-through the dots are.
...	Extra args likely used for choosing significant genes.
pretty_colors	Colors!

Value

List including a ggplot2 scatter plot and some histograms. This plot provides a "bird's eye" view of two data sets. This plot assumes a (potential) linear correlation between the data, so it calculates the correlation between them. It then calculates and plots a robust linear model of the data using an 'SMDM' estimator (which I don't remember how to describe, just that the document I was reading said it is good). The median/mad of each axis is calculated and plotted as well. The distance from the linear model is finally used to color the dots on the plot. Histograms of each axis are plotted separately and then together under a single cdf to allow tests of distribution similarity. This will make a fun clicky googleVis graph if requested.

See Also

[robust] [stats] [ggplot2] [robust::lmRob] [stats::weights] [plot_histogram()]

Examples

```
## Not run:
plot_linear_scatter(lotsofnumbers_intwo_columns)

## End(Not run)
```

plot_ly

Plotly for interactive 3-D plotting in the Shiny App

Description

Plotly for interactive 3-D plotting in the Shiny App

plot_ma_condition_de

Create a MA plot with colors from the original expressionset.

Description

The logic for this is directly from its volcano plot sister, but I think that function is more complete.

Usage

```

plot_ma_condition_de(
  input,
  table_name,
  expr_col = "logCPM",
  fc_col = "logFC",
  p_col = "qvalue",
  color_high = "red",
  color_low = "blue",
  pval = 0.05,
  alpha = 0.4,
  logfc = 1,
  label_numbers = TRUE,
  size = 2,
  shapes = TRUE,
  invert = FALSE,
  outline = TRUE,
  stroke = 1,
  label = 10,
  label_column = "hgnc_symbol",
  ...
)

```

Arguments

<code>input</code>	Result from <code>all_pairwise()</code> and friends.
<code>table_name</code>	Name the table!
<code>expr_col</code>	Column name from the input containing expression data.
<code>fc_col</code>	Ibid but the fold change column.
<code>p_col</code>	Ibid but the p-value.
<code>color_high</code>	Color for the values above the identity line.
<code>color_low</code>	and the low side.
<code>pval</code>	Significance cutoff.
<code>alpha</code>	Degree of see-through-ness.
<code>logfc</code>	Fold-change cutoff.
<code>label_numbers</code>	Add a legend containing counts by significance.
<code>size</code>	Relative size of the dots.
<code>shapes</code>	Use fun shapes for categories?
<code>invert</code>	Invert the plot?
<code>label</code>	Add labels for this number of genes.
<code>label_column</code>	Use this column for the labels.
<code>...</code>	Arbitrary passthrough.

plot_ma_de

*Make a pretty MA plot from one of limma, deseq, edger, or basic.***Description**

Because I can never remember, the following from wikipedia: "An MA plot is an application of a Bland-Altman plot for visual representation of two channel DNA microarray gene expression data which has been transformed onto the M (log ratios) and A (mean average) scale."

Usage

```
plot_ma_de(
  table,
  expr_col = "logCPM",
  fc_col = "logFC",
  p_col = "qvalue",
  pval = 0.05,
  alpha = 0.4,
  logfc = 1,
  label_numbers = TRUE,
  size = 2,
  shapes = TRUE,
  invert = FALSE,
  label = NULL,
  label_column = "hgnc_symbol",
  ...
)
```

Arguments

table	Df of linear-modelling, normalized counts by sample-type,
expr_col	Column showing the average expression across genes.
fc_col	Column showing the logFC for each gene.
p_col	Column containing the relevant p values.
pval	Name of the pvalue column to use for cutoffs.
alpha	How transparent to make the dots.
logfc	Fold change cutoff.
label_numbers	Show how many genes were 'significant', 'up', and 'down'?
size	How big are the dots?
shapes	Provide different shapes for up/down/etc?
invert	Invert the ma plot?
label	Label the top/bottom n logFC values?
label_column	gene annotation column from which to extract labels.
...	More options for you

Value

ggplot2 MA scatter plot. This is defined as the rowmeans of the normalized counts by type across all sample types on the x axis, and the log fold change between conditions on the y-axis. Dots are colored depending on if they are 'significant.' This will make a fun clicky googleVis graph if requested.

See Also

[limma_pairwise()] [deseq_pairwise()] [edger_pairwise()] [basic_pairwise()]

Examples

```
## Not run:
plot_ma(voomed_data, table)
## Currently this assumes that a variant of toptable was used which
## gives adjusted p-values. This is not always the case and I should
## check for that, but I have not yet.

## End(Not run)
```

plot_meta_sankey	<i>Plot metadata factors as a sankey diagram.</i>
------------------	---

Description

This provides two implementations of a sankey plot, one interactive and one using ggplot2.

Usage

```
plot_meta_sankey(
  design,
  factors = c("condition", "batch"),
  fill = "node",
  font_size = 18,
  node_width = 30,
  color_choices = NULL,
  drill_down = TRUE
)
```

Arguments

design	Metadata from which to extract the categories/numbers.
factors	Factors/columns in the metadata to count and plot.
fill	Use either the current or next node for coloring the transitions.
font_size	Chosen font size, perhaps no longer needed?
node_width	Make nodes more or less rectangular with this.
color_choices	Either a named vector of states and colors, or NULL (in which case it will use viridis.)
drill_down	When true, this will end in the product of the factor levels number of final states. (e.g. if there are 2 sexes, 3 visits, and 4 genotypes, there will be 2, 6, 24 states going from right to left). If FALSE, there will be 2,3,4 states going from right to left.

Value

List containing a couple of plots, one interactive, one gg.

```
plot_meta_sankey,expt-method
```

Feed an expt to a sankey plot.

Description

Feed an expt to a sankey plot.

Usage

```
## S4 method for signature 'expt'
plot_meta_sankey(
  design,
  factors = c("condition", "batch"),
  color_choices = NULL
)
```

```
plot_metadata_factors
```

Produce plots of metadata factor(s) of interest.

Description

Produce plots of metadata factor(s) of interest.

Usage

```
plot_metadata_factors(
  expt,
  column = "hisatsinglemapped",
  second_column = NULL,
  norm_column = NULL,
  type = NULL,
  scale = "base10"
)
```

Arguments

expt	Input expressionset.
column	Currently a single, but soon multiple column(s) of metadata.
second_column	Or perhaps put other columns here.
norm_column	Normalize the data?
type	Assume a violin unless otherwise specified.
scale	Rescale the data?

Value

ggplot and maybe some form of useful table.

plot_multihistogram	<i>Make a pretty histogram of multiple datasets.</i>
---------------------	--

Description

If there are multiple data sets, it might be useful to plot them on a histogram together and look at the t.test results between distributions.

Usage

```
plot_multihistogram(  
  data,  
  log = FALSE,  
  binwidth = NULL,  
  bins = NULL,  
  colors = NULL  
)
```

Arguments

data	Dataframe of lots of pretty numbers, this also accepts lists.
log	Plot the data on the log scale?
binwidth	Set a static bin width with an unknown # of bins? If neither of these are provided, then bins is set to 500, if both are provided, then bins wins.
bins	Set a static # of bins of an unknown width?
colors	Change the default colors of the densities?

Value

List of the ggplot histogram and some statistics describing the distributions.

See Also

[stats::pairwise.t.test()] [ggplot2]

Examples

```
## Not run:  
kittytime = plot_multihistogram(df)  
  
## End(Not run)
```

plot_multiplot	<i>Make a grid of plots.</i>
----------------	------------------------------

Description

Make a grid of plots.

Usage

```
plot_multiplot(plots, file, cols = NULL, layout = NULL)
```

Arguments

plots	List of plots
file	File to write to
cols	Number of columns in the grid
layout	Set the layout specifically

Value

a multiplot!

plot_mzxml_boxplot	<i>Make a boxplot out of some of the various data available in the mzxml data.</i>
--------------------	--

Description

There are a few data within the mzXML raw data files which are likely candidates for simple summary via a boxplot/densityplot/whatever. For the moment I am just doing boxplots of a few of them. Since my metadata extractor dumps a couple of tables, one must choose a desired table and column from it to plot.

Usage

```
plot_mzxml_boxplot(  
  mzxml_data,  
  table = "precursors",  
  column = "precursorintensity",  
  violin = FALSE,  
  names = NULL,  
  plot_title = NULL,  
  scale = NULL,  
  ...  
)
```

Arguments

mzxml_data	Provide a list of mzxml data, one element for each sample.
table	One of precursors or scans
column	One of the columns from the table; if 'scans' is chosen, then likely choices include: 'peakcount', 'basepeakmz', 'basepeakintensity'; if 'precursors' is chosen, then the only likely choice for the moment is 'precursorintensity'.
violin	Print the samples as violins rather than only box/whiskers?
names	Names for the x-axis of the plot.
plot_title	Title the plot?
scale	Put the data on a specific scale?
...	Further arguments, presumably for colors or some such.

Value

Boxplot describing the requested column of data in the set of mzXML files.

plot_nonzero	<i>Make a ggplot graph of the number of non-zero genes by sample.</i>
--------------	---

Description

This puts the number of genes with > 0 hits on the y-axis and CPM on the x-axis. Made by Ramzi Temanni <temanni at umd dot edu>.

Usage

```
plot_nonzero(
  data,
  design = NULL,
  colors = NULL,
  plot_labels = "repel",
  expt_names = NULL,
  max_overlaps = 5,
  label_chars = 10,
  plot_legend = FALSE,
  plot_title = NULL,
  cutoff = 0.65,
  ...
)
```

Arguments

data	Expt, expressionset, or dataframe.
design	Eesign matrix.
colors	Color scheme.
plot_labels	How do you want to label the graph? 'fancy' will use directlabels() to try to match the labels with the positions without overlapping anything else will just stick them on a 45° offset next to the graphed point.

expt_names	Column or character list of preferred sample names.
max_overlaps	Permit this many labels to overlap before dropping some.
label_chars	How many characters for sample names before abbreviation.
plot_legend	Print a legend for this plot?
plot_title	Add a title?
cutoff	Minimum proportion (or number) of genes below which samples might be in trouble.
...	rawr!

Value

a ggplot2 plot of the number of non-zero genes with respect to each library's CPM.

See Also

[ggplot2]

Examples

```
## Not run:
nonzero_plot <- plot_nonzero(expt = expt)

## End(Not run)
```

plot_nonzero, ExpressionSet-method

Make a nonzero plot given an ExpressionSet

Description

Make a nonzero plot given an ExpressionSet

Usage

```
## S4 method for signature 'ExpressionSet'
plot_nonzero(
  data,
  design = NULL,
  colors = NULL,
  plot_labels = "repel",
  expt_names = NULL,
  max_overlaps = 5,
  label_chars = 10,
  plot_legend = FALSE,
  plot_title = NULL,
  cutoff = 0.65,
  ...
)
```

```
plot_nonzero, expt-method
```

Make a nonzero plot given an expt.

Description

Make a nonzero plot given an expt.

Usage

```
## S4 method for signature 'expt'
plot_nonzero(
  data,
  design = NULL,
  colors = NULL,
  plot_labels = "repel",
  expt_names = NULL,
  max_overlaps = 5,
  label_chars = 10,
  plot_legend = FALSE,
  plot_title = NULL,
  cutoff = 0.65,
  ...
)
```

```
plot_nonzero, SummarizedExperiment-method
```

Make a nonzero plot given a SummarizedExperiment

Description

Make a nonzero plot given a SummarizedExperiment

Usage

```
## S4 method for signature 'SummarizedExperiment'
plot_nonzero(
  data,
  design = NULL,
  colors = NULL,
  plot_labels = "repel",
  expt_names = NULL,
  max_overlaps = 5,
  label_chars = 10,
  plot_legend = FALSE,
  plot_title = NULL,
  cutoff = 0.65,
  ...
)
```

plot_num_siggenes	<i>Given a DE table with fold changes and p-values, show how 'significant' changes with changing cutoffs.</i>
-------------------	---

Description

Sometimes one might want to know how many genes are deemed significant while shifting the bars which define significant. This provides that metrics as a set of tables of numbers of significant up/down genes when p-value is held constant, as well as number when fold-change is held constant.

Usage

```
plot_num_siggenes(
  table,
  methods = c("limma", "edger", "deseq", "ebseq", "basic", "noiseq", "dream"),
  bins = 100,
  constant_p = 0.05,
  constant_fc = 0
)
```

Arguments

table	DE table to examine.
methods	List of methods to use when plotting.
bins	Number of incremental changes in p-value/FC to examine.
constant_p	When plotting changing FC, where should the p-value be held?
constant_fc	When plotting changing p, where should the FC be held?

Value

Plots and dataframes describing the changing definition of 'significant.'

See Also

[ggplot2]

Examples

```
## Not run:
pairwise_result <- all_pairwise(expt)
crazy_sigplots <- plot_num_siggenes(pairwise_result)

## End(Not run)
```

plot_ontpval	<i>Make a pvalue plot from a df of IDs, scores, and p-values.</i>
--------------	---

Description

This function seeks to make generating pretty pvalue plots as shown by clusterprofiler easier.

Usage

```
plot_ontpval(  
  df,  
  ontology = "MF",  
  fontsize = 14,  
  plot_title = NULL,  
  text_location = "right",  
  text_color = "black",  
  x_column = "score",  
  numerator = NULL,  
  denominator = NULL  
)
```

Arguments

df	Some data from topgo/goseq/clusterprofiler.
ontology	Ontology to plot (MF,BP,CC).
fontsize	Fiddling with the font size may make some plots more readable.
plot_title	Set an explicit plot title.
text_location	Choose where to put the text describing the number of genes in the category.
text_color	Choose the text color, I have a fun function for this now...
x_column	Use this column to arrange the x-axis.
numerator	Column used for printing a ratio of genes/category.
denominator	Column used for printing a ratio of genes/category.

Value

Ggplot2 plot of pvalues vs. ontology.

See Also

[ggplot2]

plot_pairwise_ma	<i>Plot all pairwise MA plots in an experiment.</i>
------------------	---

Description

Use affy's `ma.plot()` on every pair of columns in a data set to help diagnose problematic samples.

Usage

```
plot_pairwise_ma(data, log = NULL, ...)
```

Arguments

data	Expt expressionset or data frame.
log	Is the data in log format?
...	Options are good and passed to <code>arglist()</code> .

Value

List of `affy::maplots`

See Also

[`affy::ma.plot()`]

Examples

```
## Not run:
ma_plots = plot_pairwise_ma(expt = some_expt)

## End(Not run)
```

plot_pca	<i>Make a PCA plot describing the samples' clustering.</i>
----------	--

Description

Make a PCA plot describing the samples' clustering.

Usage

```
plot_pca(
  data,
  design = NULL,
  state = NULL,
  plot_colors = NULL,
  plot_title = TRUE,
  plot_size = 5,
  plot_alpha = NULL,
  plot_labels = FALSE,
```

```

    size_column = NULL,
    pc_method = "fast_svd",
    x_pc = 1,
    y_pc = 2,
    max_overlaps = 20,
    num_pc = NULL,
    expt_names = NULL,
    label_chars = 10,
    cond_column = "condition",
    batch_column = "batch",
    ...
)

```

Arguments

<code>data</code>	an expt set of samples.
<code>design</code>	a design matrix and.
<code>plot_colors</code>	a color scheme.
<code>plot_title</code>	a title for the plot.
<code>plot_size</code>	size for the glyphs on the plot.
<code>plot_alpha</code>	Add an alpha channel to the dots?
<code>plot_labels</code>	add labels? Also, what type? FALSE, "default", or "fancy".
<code>size_column</code>	use an experimental factor to size the glyphs of the plot
<code>pc_method</code>	how to extract the components? (svd
<code>x_pc</code>	Component to put on the x axis.
<code>y_pc</code>	Component to put on the y axis.
<code>max_overlaps</code>	Passed to ggrepel.
<code>num_pc</code>	How many components to calculate, default to the number of rows in the meta-data.
<code>expt_names</code>	Column or character list of preferred sample names.
<code>label_chars</code>	Maximum number of characters before abbreviating sample names.
<code>cond_column</code>	Column containing the color information.
<code>batch_column</code>	Column containing the shape information.
<code>...</code>	Arguments passed through to the pca implementations and plotter.

Value

a list containing the following (this is currently wrong)

1. `pca` = the result of `fast.svd()`
2. `plot` = `ggplot2` `pca_plot` describing the principle component analysis of the samples.
3. `table` = a table of the PCA plot data
4. `res` = a table of the PCA res data
5. `variance` = a table of the PCA plot variance

See Also

[corpcor] [Rtsne] [uwot] [fastICA] [pcaMethods] [plot_pcs()]

Examples

```
## Not run:
pca_plot <- plot_pca(expt = expt)
pca_plot

## End(Not run)
```

plot_pca_genes	<i>Make a PC plot describing the gene' clustering.</i>
----------------	--

Description

Make a PC plot describing the gene' clustering.

Usage

```
plot_pca_genes(
  data,
  design = NULL,
  plot_colors = NULL,
  plot_title = NULL,
  plot_size = 2,
  plot_alpha = 0.4,
  plot_labels = FALSE,
  size_column = NULL,
  pc_method = "fast_svd",
  x_pc = 1,
  y_pc = 2,
  label_column = "description",
  num_pc = 2,
  expt_names = NULL,
  label_chars = 10,
  ...
)
```

Arguments

data	an expt set of samples.
design	a design matrix and.
plot_colors	a color scheme.
plot_title	a title for the plot.
plot_size	size for the glyphs on the plot.
plot_alpha	Add an alpha channel to the dots?
plot_labels	add labels? Also, what type? FALSE, "default", or "fancy".
size_column	use an experimental factor to size the glyphs of the plot
pc_method	how to extract the components? (svd
x_pc	Component to put on the x axis.
y_pc	Component to put on the y axis.

label_column	Which metadata column to use for labels.
num_pc	How many components to calculate, default to the number of rows in the meta-data.
expt_names	Column or character list of preferred sample names.
label_chars	Maximum number of characters before abbreviating sample names.
...	Arguments passed through to the pca implementations and plotter.

Value

a list containing the following (this is currently wrong)

1. pca = the result of fast.svd()
2. plot = ggplot2 pca_plot describing the principle component analysis of the samples.
3. table = a table of the PCA plot data
4. res = a table of the PCA res data
5. variance = a table of the PCA plot variance

See Also

[plot_pcs()]

Examples

```
## Not run:
pca_plot <- plot_pca(expt = expt)
pca_plot

## End(Not run)
```

plot_pcfactor	<i>make a dotplot of some categorised factors and a set of principle components.</i>
---------------	--

Description

This should make a quick df of the factors and PCs and plot them.

Usage

```
plot_pcfactor(pc_df, expt, exp_factor = "condition", component = "PC1")
```

Arguments

pc_df	Df of principle components.
expt	Expt containing counts, metadata, etc.
exp_factor	Experimental factor to compare against.
component	Which principal component to compare against?

Value

Plot of principle component vs factors in the data

See Also

[ggplot2]

Examples

```
## Not run:
estimate_vs_pcs <- plot_pcfactor(pcs, times)

## End(Not run)
```

plot_pload	<i>Print a plot of the top-n most PC loaded genes.</i>
------------	--

Description

Sometimes it is nice to know what is happening with the genes which have the greatest effect on a given principal component. This function provides that.

Usage

```
plot_pload(expt, genes = 40, desired_pc = 1, which_scores = "high", ...)
```

Arguments

expt	Input expressionset.
genes	How many genes to observe?
desired_pc	Which component to examine?
which_scores	Perhaps one wishes to see the least-important genes, if so set this to low.
...	Extra arguments passed, currently to nothing.

Value

List containing an expressionset of the subset and a plot of their expression.

See Also

[plot_sample_heatmap()]

plot_pcs

Plot principle components and make them pretty.

Description

All the various dimension reduction methods share some of their end-results in common. Most notably a table of putative components which may be plotted against one another so that one may stare at the screen and look for clustering among the samples/genes/whatever. This function attempts to make that process as simple and pretty as possible.

Usage

```
plot_pcs(
  pca_data,
  first = "PC1",
  second = "PC2",
  variances = NULL,
  design = NULL,
  plot_title = TRUE,
  plot_labels = NULL,
  x_label = NULL,
  y_label = NULL,
  plot_size = 5,
  outlines = TRUE,
  plot_alpha = NULL,
  size_column = NULL,
  rug = TRUE,
  max_overlaps = 20,
  cis = c(0.95, 0.9),
  ellipse_type = "t",
  ellipse_geom = "polygon",
  label_size = 4,
  ...
)
```

Arguments

pca_data	Dataframe of principle components PC1 .. PCN with any other arbitrary information.
first	Principle component PCx to put on the x axis.
second	Principle component PCy to put on the y axis.
variances	List of the percent variance explained by each component.
design	Experimental design with condition batch factors.
plot_title	Title for the plot.
plot_labels	Parameter for the labels on the plot.
x_label	Label for the x-axis.
y_label	Label for the y-axis.
plot_size	Size of the dots on the plot

outlines	Add a black outline to the plotted shapes?
plot_alpha	Add an alpha channel to the dots?
size_column	Experimental factor to use for sizing the glyphs
rug	Include the rugs on the sides of the plot?
max_overlaps	Increase overlapping label tolerance.
cis	What (if any) confidence intervals to include.
ellipse_type	Choose the kernel for the ellipse.
ellipse_geom	Use this ggplot geometry.
label_size	The text size of the labels.
...	Extra arguments dropped into arglist

Value

gplot2 PCA plot

See Also

[directlabels] [ggplot2] [plot_pca] [pca_information]

Examples

```
## Not run:
pca_plot = plot_pcs(pca_data, first = "PC2", second = "PC4", design = expt$design)

## End(Not run)
```

plot_pct_kept	<i>Make a ggplot graph of the percentage/number of reads kept/removed.</i>
---------------	--

Description

The function `expt_exclude_genes()` removes some portion of the original reads. This function will make it possible to see what is left.

Usage

```
plot_pct_kept(
  data,
  row = "pct_kept",
  condition = NULL,
  colors = NULL,
  names = NULL,
  text = TRUE,
  plot_title = NULL,
  yscale = NULL,
  ...
)
```

Arguments

data	Dataframe of the material remaining, usually expt\$summary_table
row	Row name to plot.
condition	Vector of sample condition names.
colors	Color scheme if the data is not an expt.
names	Alternate names for the x-axis.
text	Add the numeric values inside the top of the bars of the plot?
plot_title	Title for the plot.
yscale	Whether or not to log10 the y-axis.
...	More parameters for your good time!

Value

a ggplot2 bar plot of every sample's size

See Also

[plot_sample_bars()]

Examples

```
## Not run:
kept_plot <- plot_pct_kept(expt_removed)
kept_plot ## ooo pretty bargraph

## End(Not run)
```

plot_peprophet_data	<i>Plot some data from the result of extract_peprophet_data()</i>
---------------------	---

Description

extract_peprophet_data() provides a ridiculously large data table of a comet result after processing by RefreshParser and xinteract/peptideProphet. This table has some 37-ish columns and I am not entirely certain which ones are useful as diagnostics of the data. I chose a few and made options to pull some/most of the rest. Lets play!

Usage

```
plot_peprophet_data(
  table,
  xaxis = "precursor_neutral_mass",
  xscale = NULL,
  yaxis = "num_matched_ions",
  yscale = NULL,
  size_column = "prophet_probability",
  ...
)
```

Arguments

table	Big honking data table from extract_peprophet_data()
xaxis	Column to plot on the x-axis
xscale	Change the scale of the x-axis?
yaxis	guess!
yscale	Change the scale of the y-axis?
size_column	Use a column for scaling the sizes of dots in the plot?
...	extra options which may be used for plotting.

Value

a plot!

plot_pyprophet_counts *Count some aspect(s) of the pyprophet data and plot them.*

Description

This function is mostly redundant with the plot_mzxml_boxplot above. Unfortunately, the two data types are subtly different enough that I felt it not worth while to generalize the functions.

Usage

```
plot_pyprophet_counts(
  pyprophet_data,
  type = "count",
  keep_real = TRUE,
  keep_decoys = TRUE,
  expt_names = NULL,
  label_chars = 10,
  plot_title = NULL,
  scale = NULL,
  ...
)
```

Arguments

pyprophet_data	List containing the pyprophet results.
type	What to count/plot?
keep_real	Do we keep the real data when plotting the data? (perhaps we only want the decoys)
keep_decoys	Do we keep the decoys when plotting the data?
expt_names	Names for the x-axis of the plot.
label_chars	Maximum number of characters before abbreviating sample names.
plot_title	Title the plot?
scale	Put the data on a specific scale?
...	Further arguments, presumably for colors or some such.

Value

Boxplot describing the desired column from the data.

```
plot_pyprophet_distribution
```

Make a boxplot out of some of the various data available in the pyprophet data.

Description

This function is mostly redundant with the plot_mzxml_boxplot above. Unfortunately, the two data types are subtly different enough that I felt it not worth while to generalize the functions.

Usage

```
plot_pyprophet_distribution(
    pyprophet_data,
    column = "delta_rt",
    keep_real = TRUE,
    keep_decoys = TRUE,
    expt_names = NULL,
    label_chars = 10,
    plot_title = NULL,
    scale = NULL,
    ...
)
```

Arguments

pyprophet_data	List containing the pyprophet results.
column	What column of the pyprophet scored data to plot?
keep_real	Do we keep the real data when plotting the data? (perhaps we only want the decoys)
keep_decoys	Do we keep the decoys when plotting the data?
expt_names	Names for the x-axis of the plot.
label_chars	Maximum number of characters before abbreviating sample names.
plot_title	Title the plot?
scale	Put the data on a specific scale?
...	Further arguments, presumably for colors or some such.

Value

Boxplot describing the desired column from the data.

plot_pyprophet_points *Plot some data from the result of extract_pyprophet_data()*

Description

extract_pyprophet_data() provides a ridiculously large data table of a scored openswath data after processing by pyprophet.

Usage

```
plot_pyprophet_points(
    pyprophet_data,
    xaxis = "mass",
    xscale = NULL,
    sample = NULL,
    yaxis = "leftwidth",
    yscale = NULL,
    alpha = 0.4,
    color_by = "sample",
    legend = TRUE,
    size_column = "mscore",
    rug = TRUE,
    ...
)
```

Arguments

pyprophet_data	List of pyprophet data, one element for each sample, taken from extract_pyprophet_data()
xaxis	Column to plot on the x-axis
xscale	Change the scale of the x-axis?
sample	Which sample(s) to include?
yaxis	guess!
yscale	Change the scale of the y-axis?
alpha	How see-through to make the dots?
color_by	Change the colors of the points either by sample or condition?
legend	Include a legend of samples?
size_column	Use a column for scaling the sizes of dots in the plot?
rug	Add a distribution rug to the axes?
...	extra options which may be used for plotting.

Value

a plot!

plot_pyprophet_protein

Read data from pyprophet and plot columns from it.

Description

More proteomics diagnostics! Now that I am looking more closely, I think this should be folded into plot_pyprophet_distribution().

Usage

```
plot_pyprophet_protein(
  pyprophet_data,
  column = "intensity",
  keep_real = TRUE,
  keep_decoys = FALSE,
  expt_names = NULL,
  label_chars = 10,
  protein = NULL,
  plot_title = NULL,
  scale = NULL,
  legend = NULL,
  order_by = "condition",
  show_all = TRUE,
  ...
)
```

Arguments

pyprophet_data	Data from extract_pyprophet_data()
column	Chosen column to plot.
keep_real	FIXME: This should be changed to something like 'data_type' here and in plot_pyprophet_distribution.
keep_decoys	Do we keep the decoys when plotting the data?
expt_names	Names for the x-axis of the plot.
label_chars	Maximum number of characters before abbreviating sample names.
protein	chosen protein(s) to plot.
plot_title	Title the plot?
scale	Put the data on a specific scale?
legend	Include the legend?
order_by	Reorder the samples by some factor, presumably condition.
show_all	Skip samples for which no observations were made.
...	Further arguments, presumably for colors or some such.

Value

Boxplot describing the desired column from the data.

plot_pyprophet_xy	<i>Invoked plot_pyprophet_counts() twice, once for the x-axis, and once for the y.</i>
-------------------	--

Description

Then plot the result, hopefully adding some new insights into the state of the post-pyprophet results. By default, this puts the number of identifications (number of rows) on the x-axis for each sample, and the sum of intensities on the y. Currently missing is the ability to change this from sum to mean/median/etc. That should trivially be possible via the addition of arguments for the various functions of interest.

Usage

```
plot_pyprophet_xy(
    pyprophet_data,
    keep_real = TRUE,
    size = 6,
    label_size = 4,
    keep_decoys = TRUE,
    expt_names = NULL,
    label_chars = 10,
    x_type = "count",
    y_type = "intensity",
    plot_title = NULL,
    scale = NULL,
    ...
)
```

Arguments

pyprophet_data	List of pyprophet matrices by sample.
keep_real	Use the real identifications (as opposed to the decoys)?
size	Size of the glyphs used in the plot.
label_size	Set the label sizes.
keep_decoys	Use the decoy identifications (vs. the real)?
expt_names	Manually change the labels to some other column than sample.
label_chars	Maximum number of characters in the label before shortening.
x_type	Column in the data to put on the x-axis.
y_type	Column in the data to put on the y-axis.
plot_title	Plot title.
scale	Put the data onto the log scale?
...	Extra arguments passed along.

plot_qq_all	<i>Quantile/quantile comparison of the mean of all samples vs. each sample.</i>
-------------	---

Description

This allows one to visualize all individual data columns against the mean of all columns of data in order to see if any one is significantly different than the cloud.

Usage

```
plot_qq_all(data, labels = "short", ...)
```

Arguments

data	Expressionset, expt, or dataframe of samples.
labels	What kind of labels to print?
...	Arguments passed presumably from graph_metrics().

Value

List containing: logs = a recordPlot() of the pairwise log qq plots. ratios = a recordPlot() of the pairwise ratio qq plots. means = a table of the median values of all the summaries of the qq plots.

See Also

[Biobase]

plot_rmats	<i>Given some psi and tpm data from rMATS, make a pretty plot!</i>
------------	--

Description

This should take either a dataframe or filename for the psi data from rMATS. This was mostly copy/pasted from plot_suppa().

Usage

```
plot_rmats(
  se = NULL,
  a5ss = NULL,
  a3ss = NULL,
  mxe = NULL,
  ri = NULL,
  sig_threshold = 0.05,
  dpsi_threshold = 0.7,
  label_type = NULL,
  alpha = 0.7
)
```


Arguments

se	Table of skipped exon data from rmats.
a5ss	Table of alternate 5p exons.
a3ss	Table of alternate 3p exons.
mxe	Table of alternate exons.
ri	Table of retained introns.
sig_threshold	Use this significance threshold.
dpsi_threshold	Use a delta threshold.
label_type	Choose a type of event to label.
alpha	How see-through should the points be in the plot?

Value

List containing the plot and some of the requisite data.

See Also

[plot_supps()]

Examples

```
## Not run:
rmats_plot <- plot_rmats(se_table, a5_table, a3_table)

## End(Not run)
```

plot_rpm

Make relatively pretty bar plots of coverage in a genome.

Description

This was written for ribosome profiling coverage / gene. It should however, work for any data with little or no modification, it was also written when I was first learning R and when I look at it now I see a few obvious places which can use improvement.

Usage

```
plot_rpm(
  input,
  workdir = "images",
  output = "01.svg",
  name = "LmjF.01.0010",
  start = 1000,
  end = 2000,
  strand = 1,
  padding = 100
)
```

Arguments

input	Coverage / position filename.
workdir	Where to put the resulting images.
output	Output image filename.
name	Gene name to print at the bottom of the plot.
start	Relative to 0, where is the gene's start codon.
end	Relative to 0, where is the gene's stop codon.
strand	Is this on the + or - strand? (+1/-1)
padding	How much space to provide on the sides?

Value

coverage plot surrounding the ORF of interest

See Also

[ggplot2]

plot_sampleBars	<i>The actual library size plotter.</i>
-----------------	---

Description

This makes a ggplot2 plot of library sizes.

Usage

```
plot_sampleBars(
  sample_df,
  condition = NULL,
  colors = NULL,
  integerp = FALSE,
  order = NULL,
  text = TRUE,
  plot_title = NULL,
  yscale = NULL,
  ...
)
```

Arguments

sample_df	Expt, dataframe, or expressionset of samples.
condition	Vector of sample condition names.
colors	Color scheme if the data is not an expt.
integerp	Is this comprised of integer values?
order	Explicitly set the order of samples in the plot?
text	Add the numeric values inside the top of the bars of the plot?

plot_title	Title for the plot.
yscale	Whether or not to log10 the y-axis.
...	Used to catch random arguments which are unused here.

plot_sample_cvheatmap *An experiment to see if I can visualize the genes with the highest variance.*

Description

An experiment to see if I can visualize the genes with the highest variance.

Usage

```
plot_sample_cvheatmap(
  expt,
  fun = "mean",
  fact = "condition",
  row_label = NA,
  plot_title = NULL,
  Rowv = TRUE,
  Colv = TRUE,
  label_chars = 10,
  dendrogram = "column",
  min_delta = 0.5,
  x_factor = 1,
  y_factor = 2,
  min_cvsd = NULL,
  cv_min = 1,
  cv_max = Inf,
  remove_equal = TRUE
)
```

Arguments

expt	ExpressionSet
fun	mean or median
fact	Which factor to slice/dice the data?
row_label	Label the rows?
plot_title	Title for the plot
Rowv	Row vs (yeah I forgot what this does.)
Colv	Col vs
label_chars	Maximum number of characters in the sample IDs.
dendrogram	Make a tree of the samples?
min_delta	Minimum delta value for filtering
x_factor	When plotting two factors against each other, which is x?
y_factor	When plotting two factors against each other, which is y?

min_cvsd	Include only those with a minimal CV?
cv_min	Minimum cv to examine (I think this should be slightly lower)
cv_max	Maximum cV to examine (I think this should be limited to ~ 0.7?)
remove_equal	Filter uninteresting genes.

plot_sample_heatmap	<i>Make a heatmap.³ description of the similarity of the genes among samples.</i>
---------------------	--

Description

Sometimes you just want to see how the genes of an experiment are related to each other. This can handle that. These heatmap functions should probably be replaced with neatmaps or heatplus or whatever it is, as the annotation dataframes in them are pretty awesome.

Usage

```
plot_sample_heatmap(
  data,
  colors = NULL,
  design = NULL,
  heatmap_colors = NULL,
  expt_names = NULL,
  dendrogram = "column",
  row_label = NA,
  plot_title = NULL,
  Rowv = TRUE,
  Colv = TRUE,
  label_chars = 10,
  filter = TRUE,
  ...
)
```

Arguments

data	Expt/expressionset/dataframe set of samples.
colors	Color scheme of the samples (not needed if input is an expt).
design	Design matrix describing the experiment (gotten for free if an expt).
heatmap_colors	Specify a colormap.
expt_names	Alternate samples names.
dendrogram	Where to put dendrograms?
row_label	Passed through to heatmap. ² .
plot_title	Title of the plot!
Rowv	Reorder the rows by expression?
Colv	Reorder the columns by expression?
label_chars	Maximum number of characters before abbreviating sample names.
filter	Filter the data before performing this plot?
...	More parameters for a good time!

Value

a recordPlot() heatmap describing the samples.

See Also

[gplots::heatmap.2()]

plot_sample_heatmap, ExpressionSet-method

Plot a sample heatmap of an ExpressionSet.

Description

Plot a sample heatmap of an ExpressionSet.

Usage

```
## S4 method for signature 'ExpressionSet'
plot_sample_heatmap(
  data,
  colors = NULL,
  design = NULL,
  heatmap_colors = NULL,
  expt_names = NULL,
  dendrogram = "column",
  row_label = NA,
  plot_title = NULL,
  Rowv = TRUE,
  Colv = TRUE,
  label_chars = 10,
  filter = TRUE,
  ...
)
```

plot_sample_heatmap, expt-method

Plot the sample heatmap of an expt.

Description

Plot the sample heatmap of an expt.

Usage

```
## S4 method for signature 'expt'
plot_sample_heatmap(
  data,
  colors = NULL,
  design = NULL,
  heatmap_colors = NULL,
  expt_names = NULL,
  dendrogram = "column",
  row_label = NA,
  plot_title = NULL,
  Rowv = TRUE,
  Colv = TRUE,
  label_chars = 10,
  filter = TRUE,
  ...
)
```

plot_sample_heatmap, SummarizedExperiment-method

Plot a sample heatmap with a SummarizedExperiment.

Description

Plot a sample heatmap with a SummarizedExperiment.

Usage

```
## S4 method for signature 'SummarizedExperiment'
plot_sample_heatmap(
  data,
  colors = NULL,
  design = NULL,
  heatmap_colors = NULL,
  expt_names = NULL,
  dendrogram = "column",
  row_label = NA,
  plot_title = NULL,
  Rowv = TRUE,
  Colv = TRUE,
  label_chars = 10,
  filter = TRUE,
  ...
)
```

plot_sankey_de	<i>Make a sankey plot showing how the number of genes deemed significant is constrained.</i>
----------------	--

Description

Ideally, this should show how adding various Fc/p-value constraints on the definition of 'significant' decreases the number of genes one is likely to look at.

Usage

```
plot_sankey_de(
  de_table,
  lfc = 1,
  p = 0.05,
  lfc_column = "deseq_logfc",
  p_column = "deseq_adj_p"
)
```

Arguments

de_table	The result from combine_de_tables()
lfc	FC constraint.
p	P-value constraint.
lfc_column	Dataframe column from which to acquire the FC values.
p_column	Dataframe column from which to acquire the p-values.

Value

A fun sankey plot!

plot_scatter	<i>Make a pretty scatter plot between two sets of numbers.</i>
--------------	--

Description

This function tries to supplement a normal scatterplot with some information describing the relationship between the columns of data plotted.

Usage

```
plot_scatter(
  df,
  color = "black",
  xlab = NULL,
  xcol = NULL,
  ycol = NULL,
  ylab = NULL,
  alpha = 0.6,
  size = 2
)
```

Arguments

df	Dataframe likely containing two columns.
color	Color of the dots on the graph.
xlab	Alternate x-axis label.
ylab	Alternate x-axis label.
alpha	Define how see-through the dots are.
size	Size of the dots on the graph.

Value

Ggplot2 scatter plot.

See Also

[plot_linear_scatter()] [all_pairwise()]

Examples

```
## Not run:
plot_scatter(lotsofnumbers_intwo_columns)

## End(Not run)
```

plot_seurat_scatter	<i>Make a few of the likely scatterplots provided by FeatureScatter.</i>
---------------------	--

Description

It seems I have used the same couple of scatter plots more often than others.

Usage

```
plot_seurat_scatter(scd, set = NULL)
```

Arguments

scd	SCD to plot.
set	List of plots, use my favorites when NULL.

Value

List of plots.

plot_significant_bar	<i>Plot significant genes by contrast with different colors for significance levels.</i>
----------------------	--

Description

This is my attempt to recapitulate some plots made in Laura and Najib's mbio paper. The goal of the plot is to show a few ranges of significance as differently colored and stacked bars. The colors are nice because Najib and Laura chose them.

Usage

```
plot_significant_bar(
  ups,
  downs,
  maximum = NULL,
  text = TRUE,
  color_list = c("lightcyan", "lightskyblue", "dodgerblue", "plum1", "orchid", "purple4"),
  color_names = c("a_up_inner", "b_up_middle", "c_up_outer", "a_down_inner",
    "b_down_middle", "c_down_outer")
)
```

Arguments

ups	Set of up-regulated genes.
downs	Set of down-regulated genes.
maximum	Maximum/minimum number of genes to display.
text	Add text at the ends of the bars describing the number of genes $>/< 0$ fc.
color_list	Set of colors to use for the bars.
color_names	Categories associated with aforementioned colors.

Value

weird significance bar plots

See Also

[ggplot2] [extract_significant_genes()]

plot_single_qq	<i>Perform a qqplot between two columns of a matrix.</i>
----------------	--

Description

Given two columns of data, how well do the distributions match one another? The answer to that question may be visualized through a qq plot!

Usage

```
plot_single_qq(data, x = 1, y = 2, labels = TRUE)
```

Arguments

<code>data</code>	Data frame/expt/expressionset.
<code>x</code>	First column to compare.
<code>y</code>	Second column to compare.
<code>labels</code>	Include the labels?

Value

a list of the logs, ratios, and mean between the plots as ggplots.

See Also

[Biobase]

plot_sm	<i>Make an R plot of the standard median correlation or distance among samples.</i>
---------	---

Description

This was written by a mix of Kwame Okrah <kokrah at gmail dot com>, Laura Dillon <dillonl at umd dot edu>, and Hector Corrada Bravo <hcorrada at umd dot edu> I reimplemented it using ggplot2 and tried to make it a little more flexible. The general idea is to take the pairwise correlations/distances of the samples, then take the medians, and plot them. This version of the plot is no longer actually a dotplot, but a point plot, but who is counting?

Usage

```
plot_sm(
  data,
  design = NULL,
  colors = NULL,
  method = "pearson",
  plot_legend = FALSE,
  expt_names = NULL,
  label_chars = 10,
  plot_title = NULL,
  dot_size = 5,
  ...
)
```

Arguments

data	Expt, expressionset, or data frame.
design	Specify metadata if desired.
colors	Color scheme if data is not an expt.
method	Correlation or distance method to use.
plot_legend	Include a legend on the side?
expt_names	Use pretty names for the samples?
label_chars	Maximum number of characters before abbreviating sample names.
plot_title	Title for the graph.
dot_size	How large should the glyphs be?
...	More parameters to make you happy!

Value

ggplot of the standard median something among the samples. This will also write to an open device. The resulting plot measures the median correlation of each sample among its peers. It notes 1.5* the interquartile range among the samples and makes a horizontal line at that correlation coefficient. Any sample which falls below this line is considered for removal because it is much less similar to all of its peers.

See Also

[matrixStats] [ggplot2]

Examples

```
## Not run:
smc_plot = hpgl_smc(expt = expt)

## End(Not run)
```

plot_sm,data.frame-method

Plot the standard median pairwise values of a dataframe.

Description

Plot the standard median pairwise values of a dataframe.

Usage

```
## S4 method for signature 'data.frame'
plot_sm(
  data,
  design = NULL,
  colors = NULL,
  method = "pearson",
  plot_legend = FALSE,
```

```

    expt_names = NULL,
    label_chars = 10,
    plot_title = NULL,
    dot_size = 5,
    ...
)

```

plot_sm,ExpressionSet-method

Plot the standard median pairwise values of an ExpressionSet.

Description

Plot the standard median pairwise values of an ExpressionSet.

Usage

```

## S4 method for signature 'ExpressionSet'
plot_sm(
  data,
  design = NULL,
  colors = NULL,
  method = "pearson",
  plot_legend = FALSE,
  expt_names = NULL,
  label_chars = 10,
  plot_title = NULL,
  dot_size = 5,
  ...
)

```

plot_sm,expt-method

Plot the standard median pairwise values of an expt.

Description

Plot the standard median pairwise values of an expt.

Usage

```

## S4 method for signature 'expt'
plot_sm(
  data,
  design = NULL,
  colors = NULL,
  method = "pearson",
  plot_legend = FALSE,
  expt_names = NULL,
  label_chars = 10,

```

```

    plot_title = NULL,
    dot_size = 5,
    ...
)

```

plot_sm, SummarizedExperiment-method

Plot the standard median pairwise values of a SummarizedExperiment.

Description

Plot the standard median pairwise values of a SummarizedExperiment.

Usage

```

## S4 method for signature 'SummarizedExperiment'
plot_sm(
  data,
  design = NULL,
  colors = NULL,
  method = "pearson",
  plot_legend = FALSE,
  expt_names = NULL,
  label_chars = 10,
  plot_title = NULL,
  dot_size = 5,
  ...
)

```

plot_spirograph

Make spirographs!

Description

Taken (with modifications) from: <http://menugget.blogspot.com/2012/12/spirograph-with-r.html#more>
 A positive value for 'B' will result in a epitrochoid, while a negative value will result in a hypotrochoid.

Usage

```

plot_spirograph(
  radius_a = 1,
  radius_b = -4,
  dist_bc = -2,
  revolutions = 158,
  increments = 3160,
  center_a = list(x = 0, y = 0)
)

```

Arguments

radius_a	The radius of the primary circle.
radius_b	The radius of the circle travelling around a.
dist_bc	A point relative to the center of 'b' which rotates with the turning of 'b'.
revolutions	How many revolutions to perform in the plot
increments	The number of radial increments to be calculated per revolution
center_a	The position of the center of 'a'.

Value

something which I don't yet know.

plot_suppa	<i>Given some psi and tpm data, make a pretty plot!</i>
------------	---

Description

This should take either a dataframe or filename for the psi data from suppa, along with the same for the average log tpm data (acquired from suppa diffSplice with `--save_tpm_events`)

Usage

```
plot_suppa(
  file_prefix,
  file_list = NULL,
  type = "type",
  annot = NULL,
  annot_column = NULL,
  sig_threshold = 0.05,
  label_type = NULL,
  alpha = 0.3,
  numerator = "infected",
  denominator = "uninfected"
)
```

Arguments

file_prefix	Directory containing the various requisite input files.
file_list	Vector of filenames.
type	Either transcript or 'type' referring to the type of DPSI analysis performed.
annot	Dataframe of annotations.
annot_column	Column in annot with the IDs to cross reference against.
sig_threshold	Use this significance threshold.
label_type	Choose a type of event to label.
alpha	How see-through should the points be in the plot?
numerator	Name of the desired comparison's numerator.
denominator	Name of the desired comparison's denominator.

Value

List containing the plot and some of the requisite data.

See Also

[plot_rmats()]

Examples

```
## Not run:
suppa_plot <- plot_suppa(dpsi_file, tmp_file)

## End(Not run)
```

plot_svfactor	<i>Make a dotplot of some categorised factors and a set of SVs (for other factors).</i>
---------------	---

Description

This should make a quick df of the factors and surrogates and plot them.

Usage

```
plot_svfactor(
  expt,
  svest,
  sv = 1,
  chosen_factor = "batch",
  factor_type = "factor"
)
```

Arguments

expt	Experiment from which to acquire the design, counts, etc.
svest	Set of surrogate variable estimations from sva/svg or batch estimates.
sv	Which surrogate to plot?
chosen_factor	Factor to compare against.
factor_type	This may be a factor or range, it is intended to plot a scatterplot if it is a range, a dotplot if a factor.

Value

surrogate variable plot as per Leek's work

See Also

[ggplot2]

Examples

```
## Not run:
  estimate_vs_snps <- plot_svfactor(start, surrogate_estimate, "snpcategory")

## End(Not run)
```

plot_topgo_densities *Plot the density of categories vs. the possibilities of all categories.*

Description

This can make a large number of plots.

Usage

```
plot_topgo_densities(godatum, table)
```

Arguments

table	Table of genes.
godata	Result from topgo.

Value

density plot as per topgo

See Also

[topGO]

plot_topgo_pval *Make a pvalue plot from topgo data.*

Description

The p-value plots from clusterProfiler are pretty, this sets the topgo data into a format suitable for plotting in that fashion and returns the resulting plots of significant ontologies.

Usage

```
plot_topgo_pval(
  topgo,
  wrapped_width = 20,
  cutoff = 0.1,
  n = 30,
  type = "fisher",
  ...
)
```


Arguments

topgo	Some data from topgo!
wrapped_width	Maximum width of the text names.
cutoff	P-value cutoff for the plots.
n	Maximum number of ontologies to include.
type	Type of score to use.
...	arguments passed through presumably from simple_topgo()

Value

List of MF/BP/CC pvalue plots.

See Also

[ggplot2]

plot_topn	<i>Plot the representation of the top-n genes in the total counts / sample.</i>
-----------	---

Description

One question we might ask is: how much do the most abundant genes in a samples comprise the entire sample? This plot attempts to provide a visual hint toward answering this question. It does so by rank-ordering all the genes in every sample and dividing their counts by the total number of reads in that sample. It then smooths the points to provide the resulting trend. The steeper the resulting line, the more over-represented these top-n genes are. I suspect, but haven't tried yet, that the inflection point of the resulting curve is also a useful diagnostic in this question.

Usage

```
plot_topn(
  data,
  plot_title = NULL,
  num = 100,
  expt_names = NULL,
  plot_labels = NULL,
  label_chars = 10,
  plot_legend = FALSE,
  ...
)
```

Arguments

data	Dataframe/matrix/whatever for performing topn-plot.
plot_title	A title for the plot.
num	The N in top-n genes, if null, do them all.
expt_names	Column or character list of sample names.
plot_labels	Method for labelling the lines.
label_chars	Maximum number of characters before abbreviating samples.
plot_legend	Add a legend to the plot?
...	Extra arguments, currently unused.

Value

List containing the ggplot2

plot_topn_gsea	<i>Iterate gseaplot2 over an arbitrary number of enrichments.</i>
----------------	---

Description

Iterate gseaplot2 over an arbitrary number of enrichments.

Usage

```
plot_topn_gsea(gse, topn = 20, id = NULL, add_score = TRUE)
```

Arguments

gse	clusterProfiler GSEA result.
topn	Number of enrichments to plot.

Value

List of plots.

plot_topn_gsea,all_cprofiler-method	<i>Plot topn GSEA results given the result from all_cprofiler</i>
-------------------------------------	---

Description

Plot topn GSEA results given the result from all_cprofiler

Usage

```
## S4 method for signature 'all_cprofiler'  
plot_topn_gsea(gse, topn = 20, id = NULL, add_score = TRUE)
```

plot_topn_gsea,clusterprofiler_result-method	<i>Plot topn GSEA results given the result from simple_clusterprofiler</i>
--	--

Description

Plot topn GSEA results given the result from simple_clusterprofiler

Usage

```
## S4 method for signature 'clusterprofiler_result'  
plot_topn_gsea(gse, topn = 20, id = NULL, add_score = TRUE)
```

plot_tsne	<i>Shortcut to plot_pca(pc_method = "tsne")</i>
-----------	---

Description

Shortcut to plot_pca(pc_method = "tsne")

Usage

```
plot_tsne(...)
```

Arguments

...	Arguments for plot_pca()
-----	--------------------------

plot_variance_coefficients	
----------------------------	--

Look at the (biological)coefficient of variation/quartile coefficient of dispersion with respect to an experimental factor.

Description

I want to look at the (B)CV of some data with respect to condition/batch/whatever. This function should make that possible, with some important caveats. The most appropriate metric is actually the biological coefficient of variation as calculated by DESeq2/EdgeR; but the metrics I am currently taking are the simpler and less appropriate CV(sd/mean) and QCD(q3-q1/q3+q1).

Usage

```
plot_variance_coefficients(
  data,
  design = NULL,
  x_axis = "condition",
  colors = NULL,
  plot_title = NULL,
  ...
)
```

Arguments

data	Expressionset/epxt to poke at.
design	Specify metadata if necessary.
x_axis	Factor in the experimental design we may use to group the data and calculate the dispersion metrics.
colors	Set of colors to use when making the violins
plot_title	Optional title to include with the plot.
...	Extra arguments to pass along.

Value

List of plots showing the coefficients vs. genes along with the data.

plot_variance_coefficients,ExpressionSet-method

Plot the coefficient of variance values of an ExpressionSet.

Description

Plot the coefficient of variance values of an ExpressionSet.

Usage

```
## S4 method for signature 'ExpressionSet'
plot_variance_coefficients(
  data,
  design = NULL,
  x_axis = "condition",
  colors = NULL,
  plot_title = NULL,
  ...
)
```

plot_variance_coefficients,expt-method

Plot the coefficient of variance values of a SummarizedExperiment.

Description

Plot the coefficient of variance values of a SummarizedExperiment.

Usage

```
## S4 method for signature 'expt'
plot_variance_coefficients(
  data,
  design = NULL,
  x_axis = "condition",
  colors = NULL,
  plot_title = NULL,
  ...
)
```

plot_variance_coefficients, SummarizedExperiment-method

Plot the coefficient of variance values of a SummarizedExperiment.

Description

Plot the coefficient of variance values of a SummarizedExperiment.

Usage

```
## S4 method for signature 'SummarizedExperiment'
plot_variance_coefficients(
  data,
  design = NULL,
  x_axis = "condition",
  colors = NULL,
  plot_title = NULL,
  ...
)
```

plot_volcano_condition_de

Theresa's volcano plots are objectively nicer because they are colored by condition.

Description

I therefore took a modified copy of her implementation and added it here.

Usage

```
plot_volcano_condition_de(
  input,
  table_name,
  alpha = 0.5,
  fc_col = "logFC",
  fc_name = "log2 fold change",
  line_color = "black",
  line_position = "bottom",
  logfc = 1,
  p_col = "adj.P.Val",
  p_name = "-log10 p-value",
  pval = 0.05,
  shapes_by_state = FALSE,
  stroke = TRUE,
  fill = TRUE,
  color_high = "darkred",
  color_low = "darkblue",
  size = 2,
```

```

    invert = FALSE,
    label = NULL,
    label_type = "text",
    label_column = "hgnc_symbol",
    label_size = 6,
    nudge_x = 0,
    nudge_y = 0,
    ...
)

```

Arguments

input	Table of DE values, likely from combine_de_tables().
table_name	Name the table!
alpha	Make see-through.
fc_col	Column containing the fold-change values.
fc_name	Axis label.
line_color	Color for the demarcation lines.
line_position	Put the lines above or below the dots.
logfc	Demarcation line for fold-change significance.
p_col	Column containing the significance information.
p_name	Axis label for the significance.
pval	Demarcation for (in)significance.
shapes_by_state	Change point shapes according to their states?
stroke	Include the geom_color to get the outline of the dots?
color_high	Color for the ups.
color_low	and the downs.
size	Point size
invert	Flip the plot?
label	Label some points?
label_column	Using this column in the data.
label_size	Use this font size for the labels on the plot.

plot_volcano_de

Make a pretty Volcano plot!

Description

Volcano plots and MA plots provide quick an easy methods to view the set of (in)significantly differentially expressed genes. In the case of a volcano plot, it places the $-\log_{10}$ of the p-value estimate on the y-axis and the fold-change between conditions on the x-axis. Here is a neat snippet from wikipedia: "The concept of volcano plot can be generalized to other applications, where the x-axis is related to a measure of the strength of a statistical signal, and y-axis is related to a measure of the statistical significance of the signal."

Usage

```

plot_volcano_de(
  table,
  alpha = 0.5,
  color_by = "p",
  color_list = c(`FALSE` = "darkblue", `TRUE` = "darkred"),
  fc_col = "logFC",
  fc_name = "log2 fold change",
  line_color = "black",
  line_position = "bottom",
  logfc = 1,
  p_col = "adj.P.Val",
  p_name = "-log10 p-value",
  p = 0.05,
  shapes_by_state = FALSE,
  minimum_p = NULL,
  size = 2,
  invert = FALSE,
  label = NULL,
  label_column = "hgnc_symbol",
  ...
)

```

Arguments

table	Dataframe from limma's toptable which includes log(fold change) and an adjusted p-value.
alpha	How transparent to make the dots.
color_by	By p-value something else?
color_list	List of colors for significance.
fc_col	Which column contains the fc data?
fc_name	Name of the fold-change to put on the plot.
line_color	What color for the significance lines?
line_position	Put the significance lines above or below the dots?
logfc	Cutoff defining the minimum/maximum fold change for interesting.
p_col	Which column contains the p-value data?
p_name	Name of the p-value to put on the plot.
p	Cutoff defining significant from not.
shapes_by_state	Add fun shapes for the various significance states?
minimum_p	If a pvalue is lower than this, then set it to this, thus artificially limiting the y-scale of a volcano plot. This is only valid if one thinks that the pvalues are artificially low and that is messing with the interpretation of the data.
size	How big are the dots?
invert	Flip the x-axis?
label	Label the top/bottom n logFC values?
label_column	Use this column of annotations for labels instead of rownames?
...	I love parameters!

Value

Ggplot2 volcano scatter plot. This is defined as the $-\log_{10}(\text{p-value})$ with respect to $\log(\text{fold change})$. The cutoff values are delineated with lines and mark the boundaries between 'significant' and not. This will make a fun clicky googleVis graph if requested.

See Also

[all_pairwise()]

Examples

```
## Not run:
plot_volcano_de(table)
## Currently this assumes that a variant of toptable was used which
## gives adjusted p-values. This is not always the case and I should
## check for that, but I have not yet.

## End(Not run)
```

plotly_pca

Plot a PC plot with options suitable for ggplotly.

Description

Plot a PC plot with options suitable for ggplotly.

Usage

```
plotly_pca(
  data,
  design = NULL,
  plot_colors = NULL,
  plot_title = NULL,
  plot_size = 5,
  plot_alpha = NULL,
  plot_labels = NULL,
  size_column = NULL,
  pc_method = "fast_svd",
  x_pc = 1,
  y_pc = 2,
  outlines = FALSE,
  num_pc = NULL,
  expt_names = NULL,
  label_chars = 10,
  tooltip = c("shape", "fill", "sampleid"),
  ...
)
```


Arguments

<code>data</code>	an expt set of samples.
<code>design</code>	a design matrix and.
<code>plot_colors</code>	a color scheme.
<code>plot_title</code>	a title for the plot.
<code>plot_size</code>	size for the glyphs on the plot.
<code>plot_alpha</code>	Add an alpha channel to the dots?
<code>plot_labels</code>	add labels? Also, what type? FALSE, "default", or "fancy".
<code>size_column</code>	use an experimental factor to size the glyphs of the plot
<code>pc_method</code>	how to extract the components? (svd
<code>x_pc</code>	Component to put on the x axis.
<code>y_pc</code>	Component to put on the y axis.
<code>outlines</code>	Include black outlines around glyphs?
<code>num_pc</code>	How many components to calculate, default to the number of rows in the meta-data.
<code>expt_names</code>	Column or character list of preferred sample names.
<code>label_chars</code>	Maximum number of characters before abbreviating sample names.
<code>tooltip</code>	Which columns to include in the tooltip.
<code>...</code>	Arguments passed through to the pca implementations and plotter.

Value

This passes directly to `plot_pca()`, so its returns should be applicable along with the result from `ggplotly`.

See Also

[plotly]

pp

Plot a picture, with hopefully useful options for most(any) format.

Description

This calls `svg/png/postscript/etc` according to the filename provided.

Usage

```
pp(file, image = NULL, width = 9, height = 9, res = 180, crop = TRUE, ...)
```

Arguments

<code>file</code>	Filename to write
<code>image</code>	Optionally, add the image you wish to plot and this will both print it to file and screen.
<code>width</code>	How wide?
<code>height</code>	How high?
<code>res</code>	The chosen resolution.
<code>...</code>	Arguments passed to the image plotters.

Value

a png/svg/eps/ps/pdf with height = width=9 inches and a high resolution

See Also

[png()] [svg()] [postscript()] [cairo_ps()] [cairo_pdf()] [tiff()] [devEMF::emf()] [jpg()] [bmp()]

primer_qc	<i>Perform a series of tests of a putative primer.</i>
-----------	--

Description

This function should probably replace the morass of code found in snp_density_primers(). It is current used by snp_cds_primers().

Usage

```
primer_qc(  
  entry,  
  genome,  
  variant_gr,  
  target_temp = 60,  
  direction = "fwd",  
  run_pattern = "AAAA",  
  min_gc_prop = 0.3,  
  seq_object = NULL  
)
```

Arguments

entry	Single row of the table of potential primers.
genome	bsgenome used to search against.
variant_gr	GRanges of variants to xref against.
target_temp	Desired Tm.
direction	Either fwd or rev.
run_pattern	Regex to look for bad runs of a single nt.
min_gc_prop	Minimum proportion of GC content.
seq_object	Used to hunt for multi-hit primers.

```
print.abundant_genes
```

Print a summary of a set of abundant genes.

Description

Print a summary of a set of abundant genes.

Usage

```
## S3 method for class 'abundant_genes'
print(x, ...)
```

Arguments

x	Abundant gene list comprising an element 'high' and 'low' for the most and least abundant genes observed.
...	Other args to match the generic.

```
print.all_gprofiler
```

Print the result of all_gprofiler()

Description

Print the result of all_gprofiler()

Usage

```
## S3 method for class 'all_gprofiler'
print(x, ...)
```

Arguments

x	List composed of simple_gprofiler() results for every up/down set provided by extract_significant_genes().
...	Other args to match the generic.

print.all_pairwise	<i>Print function for a pairwise differential expression result.</i>
--------------------	--

Description

Print function for a pairwise differential expression result.

Usage

```
## S3 method for class 'all_pairwise'  
print(x, ...)
```

Arguments

x	List containing basic, deseq, edger, ebseq, limma, and noiseseq pairwise comparisons as well as some information about the contrasts and models used.
...	Other args to match the generic.

print.annotations_biomart	<i>Print function for a set of annotations downloaded from biomart.</i>
---------------------------	---

Description

Print function for a set of annotations downloaded from biomart.

Usage

```
## S3 method for class 'annotations_biomart'  
print(x, ...)
```

Arguments

x	List containing the relevant information gathered from ensembl's biomart.
...	Other args to match the generic.

print.aucc_info	<i>Print the result from calculate_aucc().</i>
-----------------	--

Description

Print the result from calculate_aucc().

Usage

```
## S3 method for class 'aucc_info'  
print(x, ...)
```

Arguments

x	List containing the AUCC, correlation, and a plot describing the AUCC.
...	Other args to match the generic.

print.biomart_go	<i>Print the results of load_biomart_go().</i>
------------------	--

Description

Print the results of load_biomart_go().

Usage

```
## S3 method for class 'biomart_go'  
print(x, ...)
```

Arguments

x	List from load_biomart_go() containing the table of data, mart used, host used, name of the mart, and attributes.
...	Other args to match the generic.

```
print.cds_variant_primers
```

Print the results of snp_cds_primers().

Description

Print the results of snp_cds_primers().

Usage

```
## S3 method for class 'cds_variant_primers'  
print(x, ...)
```

Arguments

x	List currently only containing the dataframe of putative primers.
...	Other args to match the generic.

```
print.classified_mutations
```

Print the results of classify_snps().

Description

Print the results of classify_snps().

Usage

```
## S3 method for class 'classified_mutations'  
print(x, ...)
```

Arguments

x	List containing some fun stats of variants observed.
...	Other args to match the generic.

```
print.classifier_evaluation
```

Print the result from self_evaluate_model().

Description

Print the result from self_evaluate_model().

Usage

```
## S3 method for class 'classifier_evaluation'  
print(x, ...)
```

Arguments

x	List showing AUC/ROC curves of the test performed, summary thereof, the confusion matrix, and vector of incorrectly called samples.
...	Other args to match the generic.

```
print.clusterprofiler_result
```

Print a clusterprofiler over representation search.

Description

Print a clusterprofiler over representation search.

Usage

```
## S3 method for class 'clusterprofiler_result'  
print(x, ...)
```

Arguments

x	Monstrous list of the various results, including but not limited to plots, go-gene mappings, enrichmed, kegg, david, GO analyses.
...	Other args to match the generic.

print.combined_de	<i>Print a combined differential expression analysis.</i>
-------------------	---

Description

Print a combined differential expression analysis.

Usage

```
## S3 method for class 'combined_de'  
print(x, ...)
```

Arguments

x	List containing the dataframes for each contrast, the various plots, the set of wanted contrasts, models used, and summaries of the data.
...	Other args to match the generic.

print.combined_de_upset	<i>Print a summary from combine_de_upset</i>
-------------------------	--

Description

Print a summary from combine_de_upset

Usage

```
## S3 method for class 'combined_de_upset'  
print(x, ...)
```

Arguments

x	List produced by combined_de_upset
...	Other args for the generic.

```
print.combined_table
```

Print a single combined DE result.

Description

Print a single combined DE result.

Usage

```
## S3 method for class 'combined_table'  
print(x, ...)
```

Arguments

x	Data table of combined differential expression results.
...	Other args to match the generic.

```
print.correlation_heatmap
```

Print the result of plot_corheat().

Description

Print the result of plot_corheat().

Usage

```
## S3 method for class 'correlation_heatmap'  
print(x, ...)
```

Arguments

x	List containing the correlations observed and a recorded heatmap.3().
...	Other args to match the generic.

```
print.cross_table_comparison
```

Print a representation of compare_de_tables(). Note I think I want to have that function return slightly different types depending on how the function call was set up.

Description

Print a representation of compare_de_tables(). Note I think I want to have that function return slightly different types depending on how the function call was set up.

Usage

```
## S3 method for class 'cross_table_comparison'
print(x, ...)
```

Arguments

x	List provided by plot_linear_scatter() containing correlations, plots, linear model.
...	Other args to match the generic.

```
print.density_plot
```

Print the result from plot_density().

Description

Print the result from plot_density().

Usage

```
## S3 method for class 'density_plot'
print(x, ...)
```

Arguments

x	List containing the plot, summary of the conditions/batches/samples, and the melted table of reads/gene.
...	Other args to match the generic.

```
print.density_primers
```

Print a summary of putative PCR primers based on variant density.

Description

Print a summary of putative PCR primers based on variant density.

Usage

```
## S3 method for class 'density_primers'
print(x, ...)
```

Arguments

x	List from snp_density_primers()
...	Other args for the generic.

```
print.deseq_lrt
```

Print the result of running deseq_lrt().

Description

Print the result of running deseq_lrt().

Usage

```
## S3 method for class 'deseq_lrt'
print(x, ...)
```

Arguments

x	List containing the DESeq2 result, the associated table, clusters from degPatterns, list of associated genes, and dataframes of the most significant genes.
...	Other args to match the generic.

```
print.distance_heatmap
```

Print the result of plot_disheat().

Description

Print the result of plot_disheat().

Usage

```
## S3 method for class 'distance_heatmap'
print(x, ...)
```

Arguments

x	List containing the distances observed and a recorded heatmap.3().
...	Other args to match the generic.

```
print.dream_pairwise
```

Print a summary of the result from dream_pairwise().

Description

Print a summary of the result from dream_pairwise().

Usage

```
## S3 method for class 'dream_pairwise'
print(x, ...)
```

Arguments

x	List from dream_pairwise().
...	Other args for the generic.

print.expt	<i>Modified print function for an expt.</i>
------------	---

Description

I am trying to understand how R collates functions.

Usage

```
## S3 method for class 'expt'  
print(x, ...)
```

Arguments

x	List from create_expt containing the expressionSet, annotation data, batches, conditions, colors, libsizes, etc.
...	Other args to match the generic.

print.goseq_result	<i>Print a goseq over representation search.</i>
--------------------	--

Description

Print a goseq over representation search.

Usage

```
## S3 method for class 'goseq_result'  
print(x, ...)
```

Arguments

x	List containing the various goseq results, plots, significant subsets, enrichResult coercions, etc.
...	Other args to match the generic.

`print.gostats_result` *Print a gostats over representation search.*

Description

Print a gostats over representation search.

Usage

```
## S3 method for class 'gostats_result'  
print(x, ...)
```

Arguments

<code>x</code>	List containing the various gostats results, plots, significant subsets, enrichResult coercions, etc.
<code>...</code>	Other args to match the generic.

`print.gprofiler_result`
 Print a gprofiler over representation search.

Description

Print a gprofiler over representation search.

Usage

```
## S3 method for class 'gprofiler_result'  
print(x, ...)
```

Arguments

<code>x</code>	List from gProfiler2 containing its various plots, tables of significant categories for GO, reactome, KEGG, miRNA, transcription factors, CORUM, wiki pathways, etc; along with the coerced enrichResult versions.
<code>...</code>	Other args to match the generic.

```
print.graphed_metrics
```

Print a message about the results from graph_metrics().

Description

Print a message about the results from graph_metrics().

Usage

```
## S3 method for class 'graphed_metrics'
print(x, ...)
```

Arguments

x	List containing a large number of plots and some tables.
...	Other args to match the generic.

```
print.gsva_result
```

Print a gsva category search.

Description

Print a gsva category search.

Usage

```
## S3 method for class 'gsva_result'
print(x, ...)
```

Arguments

x	List containing signature annotations, the result from GSVA, a modified expressionset, the signatures used, and method.
...	Other args to match the generic.

```
print.gsva_sig          Print gsva categories deemed 'significant'.
```

Description

Print gsva categories deemed 'significant'.

Usage

```
## S3 method for class 'gsva_sig'
print(x, ...)
```

Arguments

x	List of scored GSVA results, including some plots, likelihood tables, subsets of significant categories, etc.
...	Other args to match the generic.

```
print.legend_plot      Print a legend of an expressionset.
```

Description

Print a legend of an expressionset.

Usage

```
## S3 method for class 'legend_plot'
print(x, ...)
```

Arguments

x	List containing the condition factor, colors used, and plot.
...	Other args to match the generic.

```
print.libsize_plot     Print the library sizes from an experiment.
```

Description

Print the library sizes from an experiment.

Usage

```
## S3 method for class 'libsize_plot'
print(x, ...)
```

Arguments

x	List containing a summary of the library sizes, the plot, and table.
...	Other args to match the generic.

```
print.linear_scatter
```

Print a linear scatter plot without all the fluff.

Description

Print a linear scatter plot without all the fluff.

Usage

```
## S3 method for class 'linear_scatter'  
print(x, ...)
```

Arguments

x	List containing the result of plot_linear_scatter()
...	Other args for the generic.

```
print.mapped_keepers
```

Print a set of mapped keepers from combine_de_tables()

Description

Print a set of mapped keepers from combine_de_tables()

Usage

```
## S3 method for class 'mapped_keepers'  
print(x, ...)
```

Arguments

x	List full of kept information.
...	Other args to match the generic.

```
print.meta_sankey
```

Print a metadata sankey plot.

Description

Print a metadata sankey plot.

Usage

```
## S3 method for class 'meta_sankey'  
print(x, ...)
```

Arguments

x	List containing the table of connected nodes and a ggplot2 sankey.
...	Other args to match the generic.

<code>print.nonzero_plot</code>	<i>Print a nonzero plot.</i>
---------------------------------	------------------------------

Description

Print a nonzero plot.

Usage

```
## S3 method for class 'nonzero_plot'  
print(x, ...)
```

Arguments

<code>x</code>	List containing the plot and table describing the data.
<code>...</code>	Other args to match the generic.

<code>print.partitioned_data</code>	<i>Print something useful about the result of create_partitions()</i>
-------------------------------------	---

Description

Print something useful about the result of create_partitions()

Usage

```
## S3 method for class 'partitioned_data'  
print(x, ...)
```

Arguments

<code>x</code>	List containing the n sets of partitioned data test/train.
<code>...</code>	Other args to match the generic.

print.pattern_counted *Print some information about a pattern counted genome*

Description

Print some information about a pattern counted genome

Usage

```
## S3 method for class 'pattern_counted'  
print(x, ...)
```

Arguments

x	Dataframe containing how many instances of the pattern were observed in every gene.
...	Other args to match the generic.

print.pca_result *Print the result from one of the various dimension reductions.*

Description

Print the result from one of the various dimension reductions.

Usage

```
## S3 method for class 'pca_result'  
print(x, ...)
```

Arguments

x	List comprised of the residuals, variance summary, tables, the PCA-esque plot, experimental design, etc.
...	Other args to match the generic.

```
print.prepost_filter
```

Print a representation of the pre vs. post filtered data.

Description

Print a representation of the pre vs. post filtered data.

Usage

```
## S3 method for class 'prepost_filter'  
print(x, ...)
```

Arguments

x	List containing the information before/after filtering, the plots, and summary information.
...	Other args to match the generic.

```
print.preprocessing_metadata
```

Print the result from gather_preprocessing_metadata().

Description

Print the result from gather_preprocessing_metadata().

Usage

```
## S3 method for class 'preprocessing_metadata'  
print(x, ...)
```

Arguments

x	List composed of the xlsx output file, new columns added to it, and copies of the metadata before/after modification.
...	Other args to match the generic.

print.proper_estimate *Print the result from simple_proper().*

Description

Print the result from simple_proper().

Usage

```
## S3 method for class 'proper_estimate'  
print(x, ...)
```

Arguments

x	List including the various plots from PROPER, the associated tables, simulation options, and example text for a paper/grant.
...	Other args to match the generic.

print.reordered_varpart
Print the result of a reordered variance partition analysis.

Description

Print the result of a reordered variance partition analysis.

Usage

```
## S3 method for class 'reordered_varpart'  
print(x, ...)
```

Arguments

x	List of a resorted variance partition analysis and its plot.
...	Other args to match the generic.

print.sig_genes	<i>Print some significantly differentially expressed genes.</i>
-----------------	---

Description

Print some significantly differentially expressed genes.

Usage

```
## S3 method for class 'sig_genes'  
print(x, ...)
```

Arguments

x	List containing the parameters used, gene subset tables, plots, xlsx output file, etc.
...	Other args to match the generic.

print.sig_intersect	<i>Print the intersection of significant genes from multiple analyses.</i>
---------------------	--

Description

Print the intersection of significant genes from multiple analyses.

Usage

```
## S3 method for class 'sig_intersect'  
print(x, ...)
```

Arguments

x	List containing some venn diagrams, summaries of intersections, subsets of the intersections, etc.
...	Other args to match the generic.

```
print.snp_intersections
```

Print some information about the result of snp_intersections().

Description

Print some information about the result of snp_intersections().

Usage

```
## S3 method for class 'snp_intersections'  
print(x, ...)
```

Arguments

x	List containing a datatable of intersections, summaries by chromosome and gene.
...	Other args to match the generic.

```
print.snp_sets
```

Print the result of get_snp_sets().

Description

Print the result of get_snp_sets().

Usage

```
## S3 method for class 'snp_sets'  
print(x, ...)
```

Arguments

x	List containing the cross references of variants by factor, the set of observed variants, the possible combinations of the factor, etc.
...	Other args to match the generic.

```
print.snps_genes      Print the result of snps_vs_genes().
```

Description

Print the result of snps_vs_genes().

Usage

```
## S3 method for class 'snps_genes'
print(x, ...)
```

Arguments

x	List containing granges of variants, variants observed by chromosome, gene, and summaries of the result.
...	Other args to match the generic.

```
print.standardmedian_plot
      Print the result of plot_sm()
```

Description

Print the result of plot_sm()

Usage

```
## S3 method for class 'standardmedian_plot'
print(x, ...)
```

Arguments

x	List containing the pairwise distances/correlations, median/mean values, quartiles, and the standard median plot.
...	Other args to match the generic.

print.topgo_result	<i>Print a topgo over representation search.</i>
--------------------	--

Description

Print a topgo over representation search.

Usage

```
## S3 method for class 'topgo_result'  
print(x, ...)
```

Arguments

x	List of the various over/under representation analyses provided by topGO, the associated plots, and coerced enrichResults.
...	Other args to match the generic.

print.topn_plot	<i>Print a result from plot_topn().</i>
-----------------	---

Description

Print a result from plot_topn().

Usage

```
## S3 method for class 'topn_plot'  
print(x, ...)
```

Arguments

x	List with the topn plot and summary table.
...	Other args to match the generic.

print.varcoef_plot	<i>Print a result from plot_variance_coefficients().</i>
--------------------	--

Description

Print a result from plot_variance_coefficients().

Usage

```
## S3 method for class 'varcoef_plot'  
print(x, ...)
```

Arguments

x	List containing the coefficient of variance plot and summary.
...	Other args to match the generic.

print.varpart	<i>Print variance partition results.</i>
---------------	--

Description

Print variance partition results.

Usage

```
## S3 method for class 'varpart'
print(x, ...)
```

Arguments

x	List of results from variancePartition including the model information, percent/partition plots, dataframes of the fitted/sorted data by variance, etc.
...	Other args to match the generic.

print.written_expt	<i>Print the result from write_expt.</i>
--------------------	--

Description

Print the result from write_expt.

Usage

```
## S3 method for class 'written_expt'
print(x, ...)
```

Arguments

x	List containing all the many plots, the dataframes, etc.
...	Other args to match the generic.

print.written_xlsx	<i>Print the result from write_xlsx.</i>
--------------------	--

Description

Print the result from write_xlsx.

Usage

```
## S3 method for class 'written_xlsx'
print(x, ...)
```

Arguments

x	List containing some information about the xlsx file.
...	Other args for the generic.

print_ups_downs	<i>Reprint the output from extract_significant_genes().</i>
-----------------	---

Description

I found myself needing to reprint these excel sheets because I added some new information. This shortcuts that process for me.

Usage

```
print_ups_downs(
  upsdowns,
  wb,
  excel_basename,
  according = "limma",
  summary_count = 1,
  ma = FALSE,
  fancy = FALSE
)
```

Arguments

upsdowns	Output from extract_significant_genes().
wb	Workbook object to use for writing, or start a new one.
excel_basename	Used when including plots in the xlsx sheet.
according	Use limma, deseq, or edger for defining 'significant'.
summary_count	For spacing sequential tables one after another.
ma	Include ma plots?
fancy	Print fancy plots with the xlsx file?x

Value

Return from write_xlsx.

See Also

[combine_de_tables](#)

proportions_by_factors	<i>Extract the proportions of each group/sample in a scd.</i>
------------------------	---

Description

Extract the proportions of each group/sample in a scd.

Usage

```
proportions_by_factors(
  scd,
  group_factor = "res0p1_clusters",
  sample_factor = "gexcells"
)
```

Arguments

scd Seurat single cell dataset.
 group_factor Set of groups to examine.
 sample_factor Column defining the samples.

prune_network	<i>Exclude nodes from a network which are not well connected.</i>
---------------	---

Description

Exclude nodes from a network which are not well connected.

Usage

```
prune_network(network, min_weight = 0.4, min_connectivity = 1)
```

Arguments

network input network to prune.
 min_weight Minimum acceptable weight.
 min_connectivity Minimum number of nodes to which to be connected.

Value

A hopefully smaller, but not too small network.

pull_git_commit	<i>Reset the chosen git repository to a chosen commit.</i>
-----------------	--

Description

Reset the chosen git repository to a chosen commit.

Usage

```
pull_git_commit(gitdir = "~/hpgltools", commit = NULL)
```

Arguments

gitdir Desired repository, defaulting to my hpgltools copy.
 commit commit ID to which to reset.

random_ontology	<i>Perform a simple_ontology() on some random data.</i>
-----------------	---

Description

At the very least, the result should be less significant than the actual data!

Usage

```
random_ontology(input, method = "goseq", n = 200, ...)
```

Arguments

input	Some input data
method	goseq, clusterp, topgo, gostats, gprofiler.
n	how many 'genes' to analyse?
...	Arguments passed to the method.

Value

An ontology result

See Also

[simple_goseq()] [simple_clusterprofiler()] [simple_topgo()] [simple_gostats()]

rank_order_scatter	<i>Plot the rank order of the data in two tables against each other.</i>
--------------------	--

Description

Steve Christensen has some neat plots showing the relationship between two tables. I thought they were cool, so I co-opted the idea in this function.

Usage

```
rank_order_scatter(
  first,
  second = NULL,
  first_type = "limma",
  second_type = "limma",
  first_table = NULL,
  alpha = 0.5,
  second_table = NULL,
  first_column = "logFC",
  second_column = "logFC",
  first_p_col = "adj.P.Val",
  second_p_col = "adj.P.Val",
  p_limit = 0.05,
```

```

    both_color = "red",
    first_color = "green",
    second_color = "blue",
    no_color = "black"
  )

```

Arguments

first	First table of values.
second	Second table of values, if null it will use the first.
first_type	Assuming this is from all_pairwise(), use this method.
second_type	Ibid.
first_table	Again, assuming all_pairwise(), use this to choose the table to extract.
alpha	How see-through to make the dots?
second_table	Ibid.
first_column	What column to use to rank-order from the first table?
second_column	What column to use to rank-order from the second table?
first_p_col	Use this column for pretty colors from the first table.
second_p_col	Use this column for pretty colors from the second table.
p_limit	A p-value limit for coloring dots.
both_color	If both columns are 'significant', use this color.
first_color	If only the first column is 'significant', this color.
second_color	If the second column is 'significant', this color.
no_color	If neither column is 'significant', then this color.

Value

a list with a plot and a couple summary statistics.

rbind_summary_rows	<i>Append rows containing summary() information.</i>
--------------------	--

Description

Append rows containing summary() information.

Usage

```
rbind_summary_rows(df)
```

Arguments

df	Starter df
----	------------

Value

the original df with a couple of new rows at the bottom.

read_counts	<i>Read a bunch of count tables and create a usable data frame from them.</i>
-------------	---

Description

It is worth noting that this function has some logic intended for the elsayed lab's data storage structure. It shouldn't interfere with other usages, but it attempts to take into account different ways the data might be stored.

Usage

```
read_counts(
  ids,
  files,
  header = FALSE,
  include_summary_rows = FALSE,
  all.x = TRUE,
  all.y = FALSE,
  merge_type = "merge",
  suffix = NULL,
  countdir = NULL,
  tx_gene_map = NULL,
  file_type = NULL,
  ignore_tx_version = TRUE,
  ...
)
```

Arguments

ids	List of experimental ids.
files	List of files to read.
header	Whether or not the count tables include a header row.
include_summary_rows	Whether HTSeq summary rows should be included.
all.x	When merging (as opposed to join), choose the x data column.
all.y	When merging (as opposed to join), choose the y data column.
merge_type	Choose one, merge or join.
suffix	Optional suffix to add to the filenames when reading them.
countdir	Optional count directory to read from.
tx_gene_map	Dataframe which provides a mapping between transcript IDs and gene IDs.
file_type	Short circuit the file format autodetection.
ignore_tx_version	Pass along TRUE to tximport's parameter ignoreTxIds to alleviate the headaches associated with salmon's stupid transcript ID .x suffix.
...	More options for happy time!

Details

Used primarily in `create_expt()` This is responsible for reading count tables given a list of filenames. It tries to take into account upper/lowercase filenames and uses `data.table` to speed things along.

Value

Data frame of count tables.

See Also

[`data.table`] [`create_expt()`] [`tximport`]

Examples

```
## Not run:
count_tables <- hpgl_read_files(as.character(sample_ids), as.character(count_filenames))

## End(Not run)
```

read_metadata	<i>Given a table of meta data, read it in for use by <code>create_expt()</code>.</i>
---------------	--

Description

Reads an experimental design in a few different formats in preparation for creating an `expt`.

Usage

```
read_metadata(
  file,
  sep = ",",
  header = TRUE,
  sheet = 1,
  comment = "#",
  sanitize = TRUE,
  sanitize_underscore = FALSE,
  ...
)
```

Arguments

<code>file</code>	Csv/xls file to read.
<code>sep</code>	Used by <code>read.csv</code> , the separator
<code>header</code>	Used by <code>read.csv</code> , is there a header?
<code>sheet</code>	Used for excel/etc, which sheet to read?
<code>comment</code>	Skip rows starting with this (in the first cell of the row if not a text file).
<code>...</code>	Arguments for <code>arglist</code> , used by <code>sep</code> , <code>header</code> and similar <code>read_csv/read.table</code> parameters.

Value

Df of metadata.

See Also

[openxlsx] [readODS]

read_snp_columns	<i>Read the output from bcfutils into a count-table-esque</i>
------------------	---

Description

Previously, I put all my bcfutils output files into one directory. This function would iterate through every file in that directory and add the contents as columns to this growing data table. Now it works by accepting a list of filenames (presumably kept in the metadata for the experiment) and reading them into the data table. It is worth noting that it can accept either a column name or index – which when you think about it is pretty much always true, but in this context is particularly interesting since I changed the names of all the columns when I rewrote this functionality.

Usage

```
read_snp_columns(  
  samples,  
  file_lst,  
  column = "diff_count",  
  verbose = FALSE,  
  reader = "readr"  
)
```

Arguments

samples	Sample names to read.
file_lst	Set of files to read.
column	Column from the bcf file to read.
verbose	Print information about the input data.

Value

A big honking data table.

See Also

[readr]

read_thermo_xlsx	<i>Parse the difficult thermo fisher xlsx file.</i>
------------------	---

Description

The Thermo(TM) workflow has as its default a fascinatingly horrible excel output. This function parses that into a series of data frames.

Usage

```
read_thermo_xlsx(xlsx_file, test_row = NULL)
```

Arguments

xlsx_file	The input xlsx file
test_row	A single row in the xlsx file to use for testing, as I have not yet seen two of these accursed files which had the same headers.

Value

List containing the protein names, group data, protein dataframe, and peptide dataframe.

recolor_points	<i>Quick point-recolorizer given an existing plot, df, list of rownames to recolor, and a color.</i>
----------------	--

Description

This function should make it easy to color a family of genes in any of the point plots.

Usage

```
recolor_points(plot, df, ids, color = "red", ...)
```

Arguments

plot	Geom_point based plot
df	Data frame used to create the plot
ids	Set of ids which must be in the rownames of df to recolor
color	Chosen color for the new points.
...	Extra arguments are passed to arglist.

Value

prettier plot.

record_seurat_samples	<i>Add into the miscellaneous SCD slot a dataframe with some summary stats.</i>
-----------------------	---

Description

There are some simple summaries which are nice to have on hand regarding the number of RNAs, cells, rProteins, rmito observed. This function collects them and drops them into a dataframe within the slot 'misc' of the SCD. I may also print to screen some pretty skims of the results.

Usage

```
record_seurat_samples(  
  scd,  
  type = "num_cells",  
  pattern = NULL,  
  column_name = NULL,  
  column_prefix = NULL,  
  verbose = FALSE,  
  group = "Idents",  
  assay = "RNA"  
)
```

Arguments

scd	Single Cell Dataset to query.
type	Type of column to add to the metadata df, named for the column in the Cell-annotation table to query.
pattern	Pattern used for regex-based queries.
column_name	Name for the new column.
column_prefix	Prefix added to the new column.
verbose	Print the summaries to screen?
group	Could up the data by this column.
assay	Use this assay. (might be useful if you have antibody data)

Value

Give back the SCD with some new information.

renderme	<i>Add a little logic to rmarkdown::render to date the final outputs as per a request from Najib.</i>
----------	---

Description

Add a little logic to rmarkdown::render to date the final outputs as per a request from Najib.

Usage

```
renderme(file, format = "html_document", overwrite = TRUE)
```

Arguments

file	Rmd file to render.
format	Chosen file format.
overwrite	Overwrite an existing file?

Value

Final filename including the prefix rundate.

See Also

[rmarkdown]

replot_varpart_percent	<i>A shortcut for replotting the percent plots from variancePartition.</i>
------------------------	--

Description

In case I wish to look at different numbers of genes from variancePartition and/or different columns to sort from.

Usage

```
replot_varpart_percent(
  varpart_output,
  n = 30,
  column = NULL,
  decreasing = TRUE
)
```

Arguments

varpart_output	List returned by varpart()
n	How many genes to plot.
column	The df column to use for sorting.
decreasing	high->low or vice versa?

Value

The percent variance bar plots from variancePartition!

See Also

[variancePartition]

 rex

Send the R plotter to the computer of your choice!

Description

Resets the display and xauthority variables to the new computer I am using so that plot() works.

Usage

```
rex(display = ":0")
```

Arguments

display DISPLAY variable to use, if NULL it looks in ~/.displays/\${host}.last

Value

Fresh plotting window to the display of your choice!

 rowData, ExpressionSet-method

A getter of the gene information from an ExpressionSet, synonymous with fData().

Description

A getter of the gene information from an ExpressionSet, synonymous with fData().

Usage

```
## S4 method for signature 'ExpressionSet'
rowData(x, withDimnames = TRUE, ...)
```

 rowData, expt-method

A getter of the gene information from an expt, synonymous with fData().

Description

A getter of the gene information from an expt, synonymous with fData().

Usage

```
## S4 method for signature 'expt'
rowData(x, withDimnames = TRUE, ...)
```

```
rowData<- ,expt-method
```

A setter to put the gene information into an expt.

Description

A setter to put the gene information into an expt.

Usage

```
## S4 replacement method for signature 'expt'
rowData(x, i, withDimnames = TRUE, ...) <- value
```

```
rowmax_filter_counts
```

Filter low-count genes from a data set only using a simple maximum-count threshold.

Description

Filter low-count genes from a data set only using a simple maximum-count threshold.

Usage

```
rowmax_filter_counts(count_table, threshold = 2)
```

Arguments

count_table	Data frame of (pseudo)counts by sample.
threshold	Lower threshold of counts for each gene.

Value

Dataframe of counts without the low-count genes.

See Also

[edgeR]

Examples

```
## Not run:
  filtered_table <- rowmax_filter_counts(count_table)

## End(Not run)
```

```
rowMeans
```

Make sure BiocGenerics' version of rowMeans is available.

Description

Make sure BiocGenerics' version of rowMeans is available.

s2s_all_filters

*Gather together the various SWATH2stats filters into one place.***Description**

There are quite a few filters available in SWATH2stats. Reading the documentation, it seems at least possible, if not appropriate, to use them together when filtering DIA data before passing it to MSstats/etc. This function attempts to formalize and simplify that process.

Usage

```
s2s_all_filters(
  s2s_exp,
  column = "proteinname",
  pep_column = "fullpeptidename",
  fft = 0.7,
  plot = FALSE,
  target_fdr = 0.02,
  upper_fdr = 0.05,
  mscore = 0.01,
  percentage = 0.75,
  remove_decoys = TRUE,
  max_peptides = 15,
  min_peptides = 2,
  do_mscore = TRUE,
  do_freqobs = TRUE,
  do_fdr = TRUE,
  do_proteotypic = TRUE,
  do_peptide = TRUE,
  do_max = TRUE,
  do_min = TRUE,
  ...
)
```

Arguments

s2s_exp	SWATH2stats result from the sample_annotation() function. (s2s_exp stands for: SWATH2stats experiment)
column	What column in the data contains the protein name?
pep_column	What column in the data contains the peptide name (not currently used, but it should be.)
fft	Ratio of false negatives to true positives, used by assess_by_fdr() and similar functions.
plot	Print plots of the various rates by sample?
target_fdr	When invoking mscore4assayfdr, choose an mscore which corresponds to this false discovery rate.
upper_fdr	Used by filter_mscore_fdr() to choose the minimum threshold of identification confidence.
mscore	Mscore cutoff for the mscore filter.

percentage	Cutoff for the mscore_freqobs filter.
remove_decoys	Get rid of decoys in the final filter, if they were not already removed.
max_peptides	A maximum number of peptides filter.
min_peptides	A minimum number of peptides filter.
do_mscore	Perform the mscore filter? SWATH2stats::filter_mscore()
do_freqobs	Perform the mscore_freqobs filter? SWATH2stats::filter_mscore_freqobs()
do_fdr	Perform the fdr filter? SWATH2stats::filter_mscore_fdr()
do_proteotypic	Perform the proteotypic filter? SWATH2stats::filter_proteotypic_peptides()
do_peptide	Perform the single-peptide filter? SWATH2stats::filter_all_peptides()
do_max	Perform the maximum peptide filter? SWATH2stats::filter_max_peptides()
do_min	Perform the minimum peptide filter? SWATH2stats::filter_min_peptides()
...	Other arguments passed down to the filters.

Value

Smaller SWATH2stats data set.

See Also

[SWATH2stats]

sampleNames, expt-method

A getter to get the samples names from an expt.

Description

A getter to get the samples names from an expt.

Usage

```
## S4 method for signature 'expt'
sampleNames(object)
```

sampleNames, SummarizedExperiment-method

A getter to get the samples names from a SummarizedExperiment.

Description

A getter to get the samples names from a SummarizedExperiment.

Usage

```
## S4 method for signature 'SummarizedExperiment'
sampleNames(object)
```

```
sampleNames<- , expt, ANY-method
```

A setter to put the samples names into an expt.

Description

A setter to put the samples names into an expt.

Usage

```
## S4 replacement method for signature 'expt,ANY'
sampleNames(object) <- value
```

```
sampleNames<- , SummarizedExperiment, character-method
```

A setter to put the samples names into a SummarizedExperiment.

Description

A setter to put the samples names into a SummarizedExperiment.

Usage

```
## S4 replacement method for signature 'SummarizedExperiment,character'
sampleNames(object) <- value
```

```
sanitize_expt
```

Get rid of characters which will mess up contrast making and such before playing with an expt.

Description

Get rid of characters which will mess up contrast making and such before playing with an expt.

Usage

```
sanitize_expt(expt, keep_underscore = TRUE, factors = c("condition", "batch"))
```

Arguments

```
expt
```

An expt object to clean.

```
keep_underscore
```

Sanitize underscores too?

sanitize_expt_fData	<i>Given an expressionset, sanitize the gene information data.</i>
---------------------	--

Description

Given an expressionset, sanitize the gene information data.

Usage

```
sanitize_expt_fData(
  expt,
  columns = NULL,
  na_value = "notapplicable",
  lower = TRUE,
  punct = TRUE,
  factorize = "heuristic",
  max_levels = NULL,
  spaces = FALSE,
  numbers = NULL,
  numeric = FALSE
)
```

Arguments

expt	Input expressionset.
columns	Set of columns to sanitize, otherwise all of them.
na_value	Fill in NA with this.
lower	sanitize capitalization.
punct	Remove punctuation?
factorize	Convert columns to factors? When set to 'heuristic' this tries out as.factor and sees if the number of levels is silly.
max_levels	The definition of 'silly' above.
spaces	Allow spaces in the data?
numbers	Sanitize number formats (e.g. 1.000.000,0 vs. 1,000,000.0)
numeric	Set columns to numeric when possible?

sanitize_expt_pData	<i>Adding an alias to sanitize_metadata until I decide how I want to name this.</i>
---------------------	---

Description

Adding an alias to sanitize_metadata until I decide how I want to name this.

Usage

```
sanitize_expt_pData(
  expt,
  columns = NULL,
  na_value = "notapplicable",
  lower = TRUE,
  punct = TRUE,
  factorize = "heuristic",
  max_levels = NULL,
  spaces = FALSE,
  numbers = NULL,
  numeric = FALSE
)
```

Arguments

expt	Input expressionset.
columns	Set of columns to sanitize, otherwise all of them.
na_value	Fill in NA with this.
lower	sanitize capitalization.
punct	Remove punctuation?
factorize	Convert columns to factors? When set to 'heuristic' this tries out as.factor and sees if the number of levels is silly.
max_levels	The definition of 'silly' above.
spaces	Allow spaces in the data?
numbers	Sanitize number formats (e.g. 1.000.000,0 vs. 1,000,000.0)
numeric	Set columns to numeric when possible?

sanitize_metadata	<i>Given an expressionset, sanitize pData columns of interest.</i>
-------------------	--

Description

I wrote this function after spending a couple of hours confused because one cell in my metadata said 'cure ' instead of 'cure' and I could not figure out why chaos reigned in my analyses. There is a sister to this somewhere else which checks that the expected levels of a metadata factor are consistent; this is because in another analysis we essentially had a cell which said 'cyre' and a similar data explosion occurred.

Usage

```
sanitize_metadata(
  meta,
  columns = NULL,
  na_value = "notapplicable",
  lower = TRUE,
  punct = TRUE,
  factorize = "heuristic",
```

```

    max_levels = NULL,
    spaces = FALSE,
    numbers = NULL,
    numeric = FALSE
  )

```

Arguments

meta	Input metadata
columns	Set of columns to check, if left NULL, all columns will be molested.
na_value	Fill NA values with a string.
lower	Set everything to lowercase?
punct	Remove punctuation?
factorize	Set some columns to factors? If set to a vector of length ≥ 1 , then set all of the provided columns to factors. When set to 'heuristic', set any columns with \leq max_levels different elements to factors.
max_levels	When heuristically setting factors, use this as the heuristic, when NULL it is the number of samples / 6
spaces	Remove any spaces in this column?
numbers	Sanitize numbers by adding a prefix character to them?
numeric	Recast the values as numeric when possible?

sanitize_model	<i>Ensure an experimental model is safe to use</i>
----------------	--

Description

Ensure an experimental model is safe to use

Usage

```

sanitize_model(
  model,
  keep_underscore = FALSE,
  exclude_strings = c("condition", "batch")
)

```

Arguments

model	input model
keep_underscore	I previously dropped all punctuation including underscores.
exclude_strings	simplify the strings for these factors a little.

`sanitize_number_encoding`*Re-encode South American numbers so they fit my preconceptions.*

Description

Ensure that we handle numbers encoded as '4.012.321,10' are properly (from the perspective of R using my encoding system) interpreted as 'four million twelve thousand three hundred twenty-one and one tenth.'

Usage

```
sanitize_number_encoding(numbers, df = NULL)
```

Arguments

<code>numbers</code>	Column of numbers.
<code>df</code>	optional df rather than just a vector.

`sanitize_percent`*Sanitize unreliable presentation of percent values from excel.*

Description

In a recent sample sheet, we had some percentage values which were '0.5', '5 should sanitize such shenanigans.

Usage

```
sanitize_percent(numbers, df = NULL)
```

Arguments

<code>numbers</code>	Either a vector of excel crap, or a column name/number.
<code>df</code>	When provided, a data frame from which to extract the numbers.

Value

Either the numbers or dataframe with the sanitized information.

`saveme`*Make a backup rdata file for future reference*

Description

I often use R over a sshfs connection, sometimes with significant latency, and I want to be able to save/load my R sessions relatively quickly. Thus this function uses `pxz` to compress the R session maximally and relatively fast. This assumes you have `pxz` installed and ≥ 4 CPUs.

Usage

```
saveme(  
  directory = "savefiles",  
  backups = 2,  
  cpus = 6,  
  filename = "Rdata.rda.xz"  
)
```

Arguments

<code>directory</code>	Directory to save the Rdata file.
<code>backups</code>	How many revisions?
<code>cpus</code>	How many cpus to use for the xz call
<code>filename</code>	Choose a filename.

Value

Command string used to save the global environment.

See Also

`[loadme()]`

Examples

```
## Not run:  
saveme()  
  
## End(Not run)
```

score_gsva_likeliheids

Score the results from simple_gsva().

Description

Yeah, this is a bit meta, but the scores from gsva seem a bit meaningless to me, so I decided to look at the distribution of observed scores in some of my data; I quickly realized that they follow a nicely normal distribution. Therefore, I thought to calculate some scores of gsva() using that information.

Usage

```
score_gsva_likeliheids(
  gsva_result,
  score = NULL,
  category = NULL,
  factor = NULL,
  sample = NULL,
  factor_column = "condition",
  method = "mean",
  label_size = NULL,
  col_margin = 6,
  row_margin = 12,
  cutoff = 0.95
)
```

Arguments

gsva_result	Input result from simple_gsva()
score	What type of scoring to perform, against a value, column, row?
category	What category to use as baseline?
factor	Which experimental factor to compare against?
sample	Which sample to compare against?
factor_column	When comparing against an experimental factor, which design column to use to find it?
method	mean or median when when bringing together values?
label_size	By default, enlarge the labels to readable at the cost of losing some.
col_margin	Attempt to make heatmaps fit better on the screen with this and...
row_margin	this parameter
cutoff	Highlight only the categories deemed more significant than this.

Details

The nicest thing in this, I think, is that it provides its scoring metric(s) according to a few different possibilities, including: * the mean of samples found in an experimental factor * All provided scores against the distribution of observed scores as z-scores. * A single score against all scores. * Rows (gene sets) against the set of all gene sets.

Value

The scores according to the provided category, factor, sample, or score(s).

See Also

[simple_gsva()]

score_mhess	<i>A scoring function for the mh_ess TNSeq method.</i>
-------------	--

Description

I dunno, I might delete this function, I am not sure if it will ever get use.

Usage

```
score_mhess(expt, ess_column = "essm1")
```

Arguments

expt	Input expressionset with a metadata column with the ess output files.
ess_column	Metadata column containing the mh_ess output files.

Value

List containing the scores along with the genes which have changed using it.

self_evaluate_model	<i>Create a confusion matrix and ROC of a model against its training data. (and test data if the annotations are known)</i>
---------------------	---

Description

This assumes a set of partitions from create_partitions() which keeps the training metadata alongside the matrix of model variables. When available, that function also keeps the known annotations of the testing data. Given those annotations and the model created/tested from them, this runs confusionMatrix and ROC, collects the results, and provides them as a list.

Usage

```
self_evaluate_model(predictions, datasets, which_partition = 1, type = "train")
```

Arguments

predictions	Model created by train()
datasets	Set of training/testing partitions along with associated metadata annotations.
which_partition	Choose a partition to evaluate
type	Use the training or testing data?

semantic_copynumber_extract

Extract multicopy genes from up/down gene expression lists.

Description

The function semantic_copynumber_filter() is the inverse of this.

Usage

```
semantic_copynumber_extract(...)
```

Arguments

... Arguments for semantic_copynumber_filter()

Details

Currently untested, used for Trypanosome analyses primarily, thus the default strings.

semantic_copynumber_filter

Remove multicopy genes from up/down gene expression lists.

Description

In our parasite data, there are a few gene types which are consistently obnoxious. Multi-gene families primarily where the coding sequences are divergent, but the UTRs nearly identical. For these genes, our sequence based removal methods fail and so this just excludes them by name.

Usage

```
semantic_copynumber_filter(
  input,
  max_copies = 2,
  use_files = FALSE,
  invert = TRUE,
  semantic = c("mucin", "sialidase", "RHS", "MASP", "DGF", "GP63"),
  semantic_column = "product"
)
```

Arguments

input	List of sets of genes deemed significantly up/down with a column expressing approximate count numbers.
max_copies	Keep only those genes with <= n putative copies.
use_files	Use a set of sequence alignments to define the copy numbers?
invert	Keep these genes rather than drop them?
semantic	Set of strings with gene names to exclude.
semantic_column	Column in the DE table used to find the semantic strings for removal.

Details

Currently untested, used for Trypanosome analyses primarily, thus the default strings.

Value

Smaller list of up/down genes.

See Also

[semantic_copynumber_extract()]

Examples

```
## Not run:
pruned <- semantic_copynumber_filter(table, semantic = c("ribosomal"))
## Get rid of all genes with 'ribosomal' in the annotations.

## End(Not run)
```

semantic_expt_filter	<i>Remove/keep specifically named genes from an expt.</i>
----------------------	---

Description

I find subsetting weirdly confusing. Hopefully this function will allow one to include/exclude specific genes/families based on string comparisons.

Usage

```
semantic_expt_filter(
  input,
  invert = FALSE,
  topn = NULL,
  semantic = c("mucin", "sialidase", "RHS", "MASP", "DGF", "GP63"),
  semantic_column = "description"
)
```

Arguments

input	Expt to filter.
invert	The default is to remove the genes with the semantic strings. Keep them when inverted.
topn	Take the topn most abundant genes rather than a text based heuristic.
semantic	Character list of strings to search for in the annotation data.
semantic_column	Column in the annotations to search.

Value

A presumably smaller expt.

See Also

[Biobase]

sequence_attributes *Gather some simple sequence attributes.*

Description

This extends the logic of the pattern searching in `pattern_count_genome()` to search on some other attributes.

Usage

```
sequence_attributes(fasta, gff = NULL, type = "gene", key = NULL)
```

Arguments

<code>fasta</code>	Genome encoded as a fasta file.
<code>gff</code>	Optional gff of annotations (if not provided it will just ask the whole genome).
<code>type</code>	Column of the gff file to use.
<code>key</code>	What type of entry of the gff file to key from?

Value

List of data frames containing `gc/at/gt/ac` contents.

See Also

[Biostrings] [Rsamtools]

Examples

```
pa_data <- get_paeruginosa_data()
pa_fasta <- pa_data[["fasta"]]
pa_gff <- pa_data[["gff"]]
pa_attrbs <- sequence_attributes(pa_fasta, gff = pa_gff)
head(pa_attrbs)
```

sequential_variants	<i>Search a set of variants for ones which are relatively sequential.</i>
---------------------	---

Description

One potential way to screen strains is to use PCR primers which should(not) anneal due to variants with respect to the genome. This function seeks to find variants which are clustered sufficiently close to each other that this is possible.

Usage

```
sequential_variants(
  snp_sets,
  conditions = NULL,
  minimum = 3,
  maximum_separation = 3,
  one_away_file = "one_away.csv",
  two_away_file = "two_away.csv",
  doubles_file = "doubles.csv",
  singles_file = "singles.csv"
)
```

Arguments

snp_sets	Result from get_snp_sets() containing the variants with respect to known conditions.
conditions	Set of conditions to search against.
minimum	Minimum number of variants required for a candidate.
maximum_separation	How far apart from each other are these \geq minimum variants allowed to be?
one_away_file	Location to write variants that are no more than 1 base apart.
two_away_file	Location for those which are no more than 2 apart.
doubles_file	Write out variants which are 2 in a row.
singles_file	Write out the individual variants here.

set_expt_batches	<i>Change the batches of an expt.</i>
------------------	---------------------------------------

Description

When exploring differential analyses, it might be useful to play with the conditions/batches of the experiment. Use this to make that easier.

Usage

```
set_expt_batches(expt, fact, ids = NULL, ...)
```

Arguments

expt	Expt to modify.
fact	Batches to replace using this factor.
ids	Specific samples to change.
...	Extra options are like spinach.

Value

The original expt with some new metadata.

See Also

[create_expt()] [set_expt_conditions()] [Biobase]

Examples

```
## Not run:
expt = set_expt_batches(big_expt, factor = c(some,stuff,here))

## End(Not run)
```

set_expt_colors	<i>Change the colors of an expt</i>
-----------------	-------------------------------------

Description

When exploring differential analyses, it might be useful to play with the conditions/batches of the experiment. Use this to make that easier.

Usage

```
set_expt_colors(
  expt,
  colors = TRUE,
  chosen_palette = "Dark2",
  change_by = "condition"
)
```

Arguments

expt	Expt to modify
colors	colors to replace
chosen_palette	I usually use Dark2 as the RColorBrewer palette.
change_by	Assuming a list is passed, cross reference by condition or sample?

Value

expt Send back the expt with some new metadata

See Also

[set_expt_conditions()] [set_expt_batches()] [RColorBrewer]

Examples

```
## Not run:
unique(esmer_expt$design$conditions)
chosen_colors <- list(
  "cl14_epi" = "#FF8D59",
  "clbr_epi" = "#962F00",
  "cl14_tryp" = "#D06D7F",
  "clbr_tryp" = "#A4011F",
  "cl14_late" = "#6BD35E",
  "clbr_late" = "#1E7712",
  "cl14_mid" = "#7280FF",
  "clbr_mid" = "#000D7E")
esmer_expt <- set_expt_colors(expt = esmer_expt, colors = chosen_colors)

## End(Not run)
```

set_expt_conditions	<i>Change the condition of an expt</i>
---------------------	--

Description

When exploring differential analyses, it might be useful to play with the conditions/batches of the experiment. Use this to make that easier.

Usage

```
set_expt_conditions(
  expt,
  fact = NULL,
  ids = NULL,
  prefix = NULL,
  null_cell = "null",
  colors = TRUE,
  ...
)
```

Arguments

expt	Expt to modify
fact	Conditions to replace
ids	Specific sample IDs to change.
prefix	Add a prefix to the samples?
null_cell	How to fill elements of the design which are null?
colors	While we are here, set the colors.
...	Extra arguments are given to arglist.

Value

expt Send back the expt with some new metadata

See Also

[set_expt_batches()] [create_expt()]

Examples

```
## Not run:
expt = set_expt_conditions(big_expt, factor = c(some,stuff,here))

## End(Not run)
```

set_expt_factors

Change the factors (condition and batch) of an expt

Description

When exploring differential analyses, it might be useful to play with the conditions/batches of the experiment. Use this to make that easier.

Usage

```
set_expt_factors(
  expt,
  condition = NULL,
  batch = NULL,
  ids = NULL,
  table = "metadata",
  class = "factor",
  columns = NULL,
  ...
)
```

Arguments

expt	Expt to modify
condition	New condition factor
batch	New batch factor
ids	Specific sample IDs to change.
table	When set to 'metadata', use pData, otherwise fData.
class	Set the data to this class by default.
columns	Change these columns.
...	Arguments passed along (likely colors)

Value

expt Send back the expt with some new metadata

See Also

[set_expt_conditions()] [set_expt_batches()]

Examples

```
## Not run:
expt = set_expt_factors(big_expt, condition = "column", batch = "another_column")

## End(Not run)
```

```
set_expt_genename_column
```

Switch the gene names of an expressionset using a column from fData.

Description

I am not sure if set_expt_genenames() is smart enough to check for missing values. It definitely handles duplicates.

Usage

```
set_expt_genename_column(expt, new_column)
```

Arguments

expt	Current expressionSet.
new_column	Column from the gene annotations containing the new gene IDs.

Value

The expressionset with swapped out IDs.

```
set_expt_genenames
```

Change the gene names of an expt.

Description

I want to change all the gene names of a big expressionset to the ortholog groups. But I want to also continue using my expts. Ergo this little function.

Usage

```
set_expt_genenames(expt, ids = NULL, ...)
```

Arguments

expt	Expt to modify
ids	Specific sample IDs to change.
...	Extra arguments are given to arglist.

Value

expt Send back the expt with some new metadata

See Also

[set_expt_conditions()] [create_expt()]

Examples

```
## Not run:
  expt = set_expt_conditions(big_expt, factor = c(some,stuff,here))

## End(Not run)
```

set_expt_samplenames *Change the sample names of an expt.*

Description

Sometimes one does not like the hpgl identifiers, so provide a way to change them on-the-fly.

Usage

```
set_expt_samplenames(expt, newnames)
```

Arguments

expt	Expt to modify
newnames	New names, currently only a character vector.

Value

expt Send back the expt with some new metadata

See Also

[set_expt_conditions()] [set_expt_batches()]

Examples

```
## Not run:
  expt = set_expt_samplenames(expt, c("a","b","c","d","e","f"))

## End(Not run)
```

shiny *Shiny App for interactively visualizing RNAseq data*

Description

Shiny App for interactively visualizing RNAseq data

sig_ontologies	<i>Take the result from extract_significant_genes() and perform ontology searches.</i>
----------------	--

Description

It can be annoying/confusing to extract individual sets of 'significant' genes from a differential expression analysis. This function should make that process easier.

Usage

```
sig_ontologies(
  significant_result,
  excel_prefix = "excel/sig_ontologies",
  search_by = "deseq",
  excel_suffix = ".xlsx",
  type = "gprofiler",
  ...
)
```

Arguments

significant_result	Result from extract_siggenes()
excel_prefix	How to start the output filenames?
search_by	Use the definition of 'significant' from which program?
excel_suffix	How to end the excel filenames?
type	Which specific ontology search to use?
...	Arguments passed to the various simple_ontology() function.

Value

A list of the up/down results of the ontology searches.

See Also

[openxlsx] [simple_goseq()] [simple_clusterprofiler()] [simple_topgo()] [simple_gprofiler()] [simple_topgo()] [simple_gostats()]

significant_barplots	<i>Given the set of significant genes from combine_de_tables(), provide a view of how many are significant up/down.</i>
----------------------	---

Description

These plots are pretty annoying, and I am certain that this function is not well written, but it provides a series of bar plots which show the number of genes/contrast which are up and down given a set of fold changes and p-value.

Usage

```
significant_barplots(
  combined,
  lfc_cutoffs = c(0, 1, 2),
  invert = FALSE,
  p = 0.05,
  z = NULL,
  p_type = "adj",
  according_to = "all",
  order = NULL,
  maximum = NULL,
  ...
)
```

Arguments

<code>combined</code>	Result from <code>combine_de_tables</code> and/or <code>extract_significant_genes()</code> .
<code>lfc_cutoffs</code>	Choose 3 fold changes to define the queries. 0, 1, 2 mean greater/less than 0 followed by 2 fold and 4 fold cutoffs.
<code>invert</code>	Reverse the order of contrasts for readability?
<code>p</code>	Chosen p-value cutoff.
<code>z</code>	Choose instead a z-score cutoff.
<code>p_type</code>	Adjusted or not?
<code>according_to</code>	limma, deseq, edger, basic, or all of the above.
<code>order</code>	Choose a specific order for the plots.
<code>maximum</code>	Set a specific limit on the number of genes on the x-axis.
<code>...</code>	More arguments are passed to <code>arglist</code> .

Value

list containing the significance bar plots and some information to hopefully help interpret them.

Examples

```
## Not run:
expt <- create_expt(metadata = "some_metadata.xlsx", gene_info = annotations)
pairwise_result <- all_pairwise(expt)
combined_result <- combine_de_tables(pairwise_result)
## Damn I wish I were smrt enough to make this elegant, but I cannot.
barplots <- significant_barplots(combined_result)

## End(Not run)
```

sillydist

Calculate a simplistic distance function of a point against two axes.

Description

Sillydist provides a distance of any point vs. the axes of a plot. This just takes the abs(distances) of each point to the axes, normalizes them against the largest point on the axes, multiplies the result, and normalizes against the max of all point.

Usage

```
sillydist(firstterm, secondterm, firstaxis = 0, secondaxis = 0)
```

Arguments

firstterm	X-values of the points.
secondterm	Y-values of the points.
firstaxis	X-value of the vertical axis.
secondaxis	Y-value of the second axis.

Value

Dataframe of the distances.

See Also

[ggplot2]

Examples

```
## Not run:
mydist <- sillydist(df[,1], df[,2], first_median, second_median)
first_vs_second <- ggplot(df, aes(x = .data[["first"]], y = .data[["second"]]),
                          environment = hpgl_env) +
  ggplot2::xlab(paste("Expression of", df_x_axis)) +
  ggplot2::ylab(paste("Expression of", df_y_axis)) +
  ggplot2::geom_vline(color = "grey", xintercept=(first_median - first_mad), size = line_size) +
  ggplot2::geom_vline(color = "grey", xintercept=(first_median + first_mad), size = line_size) +
  ggplot2::geom_vline(color = "darkgrey", xintercept = first_median, size = line_size) +
  ggplot2::geom_hline(color = "grey", yintercept=(second_median - second_mad), size = line_size) +
  ggplot2::geom_hline(color = "grey", yintercept=(second_median + second_mad), size = line_size) +
  ggplot2::geom_hline(color = "darkgrey", yintercept = second_median, size = line_size) +
  ggplot2::geom_point(colour = grDevices::hsv(mydist$dist, 1, mydist$dist),
                      alpha = 0.6, size = size) +
  ggplot2::theme(legend.position = "none")
first_vs_second ## dots get colored according to how far they are from the medians
## replace first_median, second_median with 0,0 for the axes

## End(Not run)
```

`simple_clusterprofiler`*Perform the array of analyses in the 2016-04 version of clusterProfiler*

Description

The new version of clusterProfiler has a bunch of new toys. However, it is more stringent in terms of input in that it now explicitly expects to receive annotation data in terms of a orgdb object. This is mostly advantageous, but will probably cause some changes in the other ontology functions in the near future. This function is an initial pass at making something similar to my previous 'simple_clusterprofiler()' but using these new toys.

Usage

```
simple_clusterprofiler(  
  sig_genes,  
  de_table = NULL,  
  orgdb = "org.Hs.eg.db",  
  orgdb_from = NULL,  
  orgdb_to = "ENTREZID",  
  go_level = 3,  
  pcutoff = 0.05,  
  organism = "human",  
  qcutoff = 0.2,  
  fc_column = "logFC",  
  second_fc_column = "deseq_logfc",  
  internal = FALSE,  
  updown = "up",  
  permutations = 1000,  
  min_groupsize = 5,  
  max_groupsize = 500,  
  kegg_prefix = NULL,  
  kegg_organism = NULL,  
  do_gsea = TRUE,  
  categories = 12,  
  excel = NULL,  
  do_david = FALSE,  
  do_kegg = TRUE,  
  david_id = "ENTREZ_GENE_ID",  
  padj_type = "BH",  
  david_user = "abelew@umd.edu",  
  do_reactome = TRUE,  
  do_dose = FALSE,  
  do_mesh = FALSE,  
  do_msigdb = FALSE,  
  mesh_category = "C",  
  mesh_dbname = "gendoo",  
  msigdb_category = "C2",  
  msigdb = NULL  
)
```

Arguments

sig_genes	Dataframe of genes deemed 'significant.'
de_table	Dataframe of all genes in the analysis, primarily for GSEA.
orgdb	Name of the orgDb used for gathering annotation data.
orgdb_from	Name of a key in the orgdb used to cross reference to entrez IDs.
orgdb_to	List of keys to grab from the orgdb for cross referencing ontologies.
go_level	How deep into the ontology tree should this dive for over expressed categories.
pcutoff	P-value cutoff for 'significant' analyses.
qcutoff	Q-value cutoff for 'significant' analyses.
fc_column	When extracting vectors of all genes, what column should be used?
second_fc_column	When extracting vectors of all genes, what column should be tried the second time around?
updown	Include the less than expected ontologies?
permutations	How many permutations for GSEA-ish analyses?
min_groupsize	Minimum size of an ontology before it is included.
kegg_prefix	Many KEGG ids need a prefix before they will cross reference.
kegg_organism	Choose the 3 letter KEGG organism name here.
do_gsea	Perform gsea searches?
categories	How many categories should be plotted in bar/dot plots?
excel	Print the results to an excel file?
do_david	Attempt to use the DAVID database for a search?
do_kegg	Perform kegg search?
david_id	Which column to use for cross-referencing to DAVID?
david_user	Default registered username to use.

Value

a list

See Also

[clusterProfiler] [AnnotationDbi] [KEGGREST]

Examples

```
## Not run:
  holyasscrackers <- simple_clusterprofiler(gene_list, all_genes, "org.Dm.eg.db")

## End(Not run)
```

simple_cp_enricher	<i>Generic enrichment using clusterProfiler.</i>
--------------------	--

Description

culsterProfiler::enricher provides a quick and easy enrichment analysis given a set of significant genes and a data frame which connects each gene to a category.

Usage

```
simple_cp_enricher(sig_genes, de_table, go_db = NULL)
```

Arguments

sig_genes	Set of 'significant' genes as a table.
de_table	All genes from the original analysis.
go_db	Dataframe of GO->ID matching the gene names of sig_genes to GO categories.

Value

Table of 'enriched' categories.

simple_cprofiler	<i>I cannot be trusted to type 'cluster'</i>
------------------	--

Description

I cannot be trusted to type 'cluster'

Usage

```
simple_cprofiler(...)
```

Arguments

...	Passed to simple_clusterprofiler()
-----	------------------------------------

simple_dorothea	<i>Invoke dorothea in an attempt to hunt down cool TFs.</i>
-----------------	---

Description

dorothea: <https://github.com/saezlab/dorothea> appears to provide experimentally verified mappings from genes->transcription factors as well as a set of functions which allow one to pass it an expressionset/matrix of counts(log scale) and get back scores by tf. This function is an attempt to smooth it out and prod it for usability.

Usage

```
simple_dorothea(
  expt,
  gene_column = "ensembl_gene_id",
  hgnc_column = "hgnc_symbol",
  transform = "log2",
  conf = c("A", "B", "C"),
  dorothea_options = NULL,
  lfc = 1,
  p = 0.05,
  species = "hsapiens"
)
```

Arguments

expt	Expressionset
gene_column	Column in fData containing the gene IDs.
hgnc_column	fData column containing the HGNC symbols as used by dorothea/viper
transform	Explicitly set the scale to log2 (TODO: improve this)
conf	Vector of confidence scores to filter the data.
dorothea_options	Optional configuration list.
lfc	Fold-change cutoff.
p	P-value cutoff.
species	Either human or mouse.

Value

list containing some information from dorothea and limma.

simple_filter_counts	<i>Filter low-count genes from a data set only using a simple threshold and number of samples.</i>
----------------------	--

Description

This was a function written by Kwame Okrah and perhaps also Laura Dillon to remove low-count genes. It drops genes based on a threshold and number of samples.

Usage

```
simple_filter_counts(count_table, threshold = 2)
```

Arguments

count_table	Data frame of (pseudo)counts by sample.
threshold	Lower threshold of counts for each gene.

Value

Dataframe of counts without the low-count genes.

See Also

[edgeR]

Examples

```
## Not run:
  filtered_table <- simple_filter_counts(count_table)

## End(Not run)
```

simple_gadem	<i>run the rGADEM suite</i>
--------------	-----------------------------

Description

This should provide a set of rGADEM results given an input file of sequences and a genome.

Usage

```
simple_gadem(
  inputfile,
  genome = "BSgenome.Hsapiens.UCSC.hs19",
  p = 0.1,
  e = 0,
  ...
)
```

Arguments

inputfile	Fasta or bed file containing sequences to search.
genome	BSgenome to read.
p	pvalue cutoff
e	evalute cutoff
...	Parameters for plotting the gadem result.

Value

A list containing slots for plots, the stdout output from gadem, the gadem result, set of occurrences of motif, and the returned set of motifs.

See Also

[IRanges] [Biostrings] [rGADEM]

simple_goseq	<i>Perform a simplified goseq analysis.</i>
--------------	---

Description

goseq can be pretty difficult to get set up for non-supported organisms. This attempts to make that process a bit simpler as well as give some standard outputs which should be similar to those returned by clusterprofiler/topgo/gostats/gprofiler.

Usage

```
simple_goseq(
  sig_genes,
  go_db = NULL,
  length_db = NULL,
  doplot = TRUE,
  adjust = 0.1,
  threshold = 0.1,
  plot_title = NULL,
  length_keytype = "transcripts",
  go_keytype = "entrezid",
  goseq_method = "Wallenius",
  padjust_method = "BH",
  expand_categories = TRUE,
  excel = NULL,
  enrich = TRUE,
  minimum_interesting = 2,
  min_xref = 40,
  ...
)
```

Arguments

sig_genes	Data frame of differentially expressed genes, containing IDs etc.
go_db	Database of go to gene mappings (OrgDb/OrganismDb)
length_db	Database of gene lengths (gff/TxDb)
doplot	Include pwf plots?
adjust	Minimum adjusted pvalue for 'significant.'
threshold	Look at sets with this significance or better.
plot_title	Set a title for the pvalue plots.
length_keytype	Keytype to provide to extract lengths
go_keytype	Keytype to provide to extract go IDs
goseq_method	Statistical test for goseq to use.
padjust_method	Which method to use to adjust the pvalues.
expand_categories	Expand the GO categories to make the results more readable?
excel	Print the results to an excel file?
enrich	Convert the goseq result to the clusterProfiler format?
minimum_interesting	Exclude categories with less than this number of genes.
min_xref	Stop everything if we get less than this intersection of genes/GO/lengths.
...	Extra parameters which I do not recall

Value

Big list including: the pwd:pwf function, alldata:the godata dataframe, pvalue_histogram:p-value histograms, godata_interesting:the ontology information of the enhanced groups, term_table:the goterms with some information about them, mf_subset:a plot of the MF enhanced groups, mfp_plot:the pvalues of the MF group, bp_subset:a plot of the BP enhanced groups, bpp_plot, cc_subset, and ccp_plot

See Also

[goseq] [GO.db] [GenomicFeatures] [stats::p.adjust()]

Examples

```
## Not run:
lotsotables <- simple_goseq(gene_list, godb, lengthdb)

## End(Not run)
```

simple_gostats

Simplification function for gostats, in the same vein as those written for clusterProfiler, goseq, and topGO.

Description

GOSTats has a couple interesting peculiarities: Chief among them: the gene IDs must be integers. As a result, I am going to have this function take a gff file in order to get the go ids and gene ids on the same page.

Usage

```
simple_gostats(
  sig_genes,
  go_db = NULL,
  gff = NULL,
  gff_df = NULL,
  universe_merge = "id",
  second_merge_try = "locus_tag",
  species = "fun",
  pcutoff = 0.1,
  conditional = FALSE,
  categorysize = NULL,
  gff_id = "ID",
  gff_type = "cds",
  excel = NULL,
  ...
)
```

Arguments

sig_genes	Input list of differentially expressed genes.
go_db	Set of GOids, as before in the format ID/GO.
gff	Annotation information for this genome.
gff_df	I do not remember what this is for.
universe_merge	Column from which to create the universe of genes.
second_merge_try	If the first universe merge fails, try this.
species	Genbank organism to use.
pcutoff	Pvalue cutoff for deciding significant.
conditional	Perform a conditional search?
categorysize	Category size below which to not include groups.
gff_id	key in the gff file containing the unique IDs.
gff_type	Gff column to use for creating the universe.
excel	Print the results to an excel file?
...	More parameters!

Value

List of returns from GSEABase, Category, etc.

See Also

[GSEABase] [Category] [load_gff_annotations()] [GOstats]

Examples

```
## Not run:
knickerbockers <- simple_gostats(sig_genes, gff_file, goids)

## End(Not run)
```

simple_gprofiler	<i>Redirect users to simple_gprofiler2</i>
------------------	--

Description

Redirect users to simple_gprofiler2

Usage

```
simple_gprofiler(...)
```

Arguments

... Arguments passed to simple_gprofiler2()

simple_gprofiler2	<i>Run searches against the web service g:Profiler.</i>
-------------------	---

Description

This is the beginning of a reimplementaion to use gprofiler2. However, AFAICT gprofiler2 does not yet actually work for anything other than their GO data.

Usage

```
simple_gprofiler2(
  sig_genes,
  species = "hsapiens",
  convert = TRUE,
  first_col = "deseq_logfc",
  second_col = "logfc",
  do_mf = TRUE,
  do_bp = TRUE,
  do_cc = TRUE,
  do_kegg = TRUE,
  do_reactome = TRUE,
```

```

do_mi = TRUE,
do_tf = TRUE,
do_corum = TRUE,
do_hp = TRUE,
do_hpa = TRUE,
do_wp = TRUE,
significant = TRUE,
exclude_iea = FALSE,
do_under = FALSE,
evcodes = TRUE,
threshold = 0.05,
adjp = "g_SCS",
domain_scope = "annotated",
bg = NULL,
min_genes = 10,
ordered = TRUE,
id_col = "row.names",
plot_type = "dotplot",
excel = NULL,
min_go_level = 3,
...
)

```

Arguments

<code>sig_genes</code>	Guess! The set of differentially expressed/interesting genes.
<code>species</code>	Organism supported by gprofiler.
<code>convert</code>	Use gProfileR's conversion utility?
<code>first_col</code>	First place used to define the order of 'significant'.
<code>second_col</code>	If that fails, try a second column.
<code>do_kegg</code>	Perform KEGG search?
<code>do_reactome</code>	Perform reactome search?
<code>do_mi</code>	Do miRNA search?
<code>do_tf</code>	Search for transcription factors?
<code>do_corum</code>	Do corum search?
<code>do_hp</code>	Do the hp search?
<code>do_hpa</code>	Do the hpa search?
<code>do_wp</code>	Do the wp search?
<code>significant</code>	Only return the statistically significant hits?
<code>exclude_iea</code>	Passed directly to gprofiler2.
<code>do_under</code>	Perform under-representation search?
<code>evcodes</code>	Get the set of evcodes in the data? This makes it take longer.
<code>threshold</code>	p-value 'significance' threshold.
<code>adjp</code>	Method to adjust p-values.
<code>domain_scope</code>	Passed to gprofiler2.
<code>bg</code>	Background genes.

ordered	Is the data in a ranked order by significance?
id_col	Which column in the table should be used for gene ID crossreferencing? gProfiler uses Ensembl ids. So if you have a table of entrez or whatever, translate it!
plot_type	Use this plot type for images.
excel	Print the results to an excel file?
...	Primarily for changing options when writing a xlsx output.
do_go	Perform GO search?
enrich_id_column	Column from which to extract more readable gene IDs when creating a clusterProfiler-compatible enrich object.

Value

a list of results for go, kegg, reactome, and a few more.

See Also

[gProfiler]

Examples

```
## Not run:
gprofiler_is_nice_and_easy <- simple_gprofiler(genes, species='mmusculus')

## End(Not run)
```

simple_gsva	<i>Provide some defaults and guidance when attempting to use gsva.</i>
-------------	--

Description

gsva seems to hold a tremendous amount of potential. Unfortunately, it is somewhat opaque and its requirements are difficult to pin down. This function will hopefully provide some of the requisite defaults and do some sanity checking to make it more likely that a gsva analysis will succeed.

Usage

```
simple_gsva(
  expt,
  signatures = "c2BroadSets",
  data_pkg = "GSVAdata",
  signature_category = "c2",
  cores = NULL,
  current_id = "ENSEMBL",
  required_id = "ENTREZID",
  id_source = "orgdb",
  min_catsize = 5,
  orgdb = "org.Hs.eg.db",
  method = "ssgsea",
```

```

    kcdf = NULL,
    ranking = FALSE,
    msig_db = NULL,
    wanted_meta = "all",
    mx_diff = TRUE,
    verbose = FALSE,
    id_type = "entrez"
)

```

Arguments

expt	Expt object to be analyzed.
signatures	Provide an alternate set of signatures (GeneSetCollections)
data_pkg	What package contains the requisite dataset?
signature_category	Specify a subset category to extract from the signatures database.
cores	How many CPUs to use?
current_id	Where did the IDs of the genes come from?
required_id	gsva (I assume) always requires ENTREZ IDs, but just in case this is a parameter.
min_catsize	Minimum category size to consider interesting (passed to gsva()).
orgdb	What is the data source for the rownames()?
method	Which gsva method to use? Changed this from gsva to ssgsea because it was throwing segmentation faults.
kcdf	Options for the gsva methods.
ranking	another gsva option.
msig_db	File containing msigdb annotations.
wanted_meta	Desired metadata elements from the mxig_xml file.
mx_diff	Passed to gsva(), I do not remember what it does.
verbose	Print some information while running?
id_type	Specify the ID type when loading the signature database.

Value

List containing three elements: first a modified expressionset using the result of gsva in place of the original expression data; second the result from gsva, and third a data frame of the annotation data for the gene sets in the expressionset. This seems a bit redundant, perhaps I should revisit it?

See Also

[GSEABase] [load_gmt_signatures()] [create_expt()] [GSVA]

simple_motifRG	<i>Run motifRG on a fasta file.</i>
----------------	-------------------------------------

Description

Run motifRG on a fasta file.

Usage

```
simple_motifRG(  
  input_fasta,  
  control_fasta,  
  maximum = 3,  
  title = "Motifs of XXX",  
  prefix = "motif",  
  genome = "BSgenome.Hsapiens.UCSC.hg19"  
)
```

Arguments

input_fasta	Input file.
control_fasta	control file.
maximum	3
title	Output image title.
prefix	Prefix for the output files.
genome	Package containing the full genome.

See Also

[motifRG]

simple_pathview	<i>Print some data onto KEGG pathways.</i>
-----------------	--

Description

KEGGREST and pathview provide neat functions for coloring molecular pathways with arbitrary data. Unfortunately they are somewhat evil to use. This attempts to alleviate that.

Usage

```
simple_pathview(  
  gene_input = NULL,  
  compound_input = NULL,  
  indir = "pathview_in",  
  outdir = "pathview",  
  pathway = "all",  
  species = "lma",
```

```

    from_list = NULL,
    to_list = NULL,
    suffix = "_colored",
    id_column = NULL,
    filenames = "id",
    fc_column = "limma_logfc",
    format = "png",
    verbose = TRUE
)

```

Arguments

gene_input	Some differentially expressed genes.
compound_input	Sets of compounds which have changed in the data of interest.
indir	Directory into which the unmodified kegg images will be downloaded (or already exist).
outdir	Directory which will contain the colored images.
pathway	Perform the coloring for a specific pathway?
species	Kegg identifier for the species of interest.
from_list	Regex to help in renaming KEGG categories/gene names from one format to another.
to_list	Regex to help in renaming KEGG categories/gene names from one format to another.
suffix	Add a suffix to the completed, colored files.
id_column	use this to handle the peculiar ways in which kegg handles IDs.
filenames	Name the final files by id or name?
fc_column	What is the name of the fold-change column to extract?
format	Format of the resulting images, I think only png really works well.
verbose	When on, this function is quite chatty.

Value

A list of some information for every KEGG pathway downloaded/examined. This information includes: a. The filename of the final image for each pathway. b. The number of genes which were found in each pathway image. c. The number of genes in the 'up' category d. The number of genes in the 'down' category

See Also

[pathview] [KEGGREST]

Examples

```

## Not run:
thy_el_comp2_path = hpgl_pathview(thy_el_comp2_kegg, species = "spz", indir = "pathview_in",
                                outdir = "kegg_thy_el_comp2", string_from = "_Spy",
                                string_to = "_Spy_", filenames = "pathname")

## End(Not run)

```

simple_proper

*Invoke PROPER and replace its default data set with data of interest.***Description**

Recent reviewers of Najib's grants have taken an increased interest in knowing the statistical power of the various experiments. He queried Dr. Corrada-Bravo who suggested PROPER. I spent some time looking through it and, with some reverervations, modified its workflow to (at least in theory) be able to examine any dataset. The workflow in question is particularly odd and warrants further discussion/analysis. This function is a modified version of 'default_proper()' above and invokes PROPER after re-formatting a given dataset in the way expected by PROPER.

Usage

```
simple_proper(
  de_tables,
  de = NULL,
  mtrx = NULL,
  p = 0.05,
  experiment = "cheung",
  nsims = 20,
  reps = c(3, 5, 7, 10),
  de_method = "edger",
  alpha_type = "fdr",
  alpha = 0.1,
  stratify = "expr",
  target = "lfc",
  mean_or_median = "mean",
  filter = "none",
  delta = 1,
  add_coverage = TRUE,
  target_power = 0.8,
  mean_gene_length = 2000,
  nt_per_read = 200,
  describe_samples = 5
)
```

Arguments

de_tables	A set of differential expression results, presumably from EdgeR or DESeq2.
p	Cutoff
experiment	The default data set in PROPER is entitled 'cheung'.
nsims	Number of simulations to perform.
reps	Simulate these number of experimental replicates.
de_method	There are a couple choices here for tools which are pretty old, my version of this only accepts deseq or edger.
alpha_type	I assume p-adjust type.
alpha	Accepted fdr rate.
stratify	There are a few options here, I don't fully understand them.

target	Cutoff.
mean_or_median	Use mean or median values?
filter	Apply a filter?
delta	Not epsilon! (E.g. I forget what this does).
add_coverage	When plotting, add a line showing the actual coverage?
target_power	When creating boilerplate text for a grant, specify power goal.
mean_gene_length	When making text, specify the mean gene length expected.
nt_per_read	Specify how many reads are in each read(pair).
describe_samples	Add a guestimate of the number of samples required for the power goal.

Value

List containin the various tables and plots returned by PROPER.

See Also

[PROPER] DOI:10.1093/bioinformatics/btu640

simple_topgo	<i>Perform a simplified topgo analysis.</i>
--------------	---

Description

This will attempt to make it easier to run topgo on a set of genes. The way I organized these data structures is completely stupid. I want to convert the data from topgo to clusterprofiler for ease of plotting, but because of the terrible way I organized everything that is likely to be difficult.

Usage

```
simple_topgo(
  sig_genes,
  goid_map = "id2go.map",
  go_db = NULL,
  pvals = NULL,
  limitby = "fisher",
  limit = 0.1,
  signodes = 100,
  sigforall = TRUE,
  numchar = 300,
  selector = "topDiffGenes",
  pval_column = "deseq_adj",
  overwrite = FALSE,
  densities = FALSE,
  pval_plots = TRUE,
  parallel = TRUE,
  excel = NULL,
  ...
)
```

Arguments

sig_genes	Data frame of differentially expressed genes, containing IDs any other columns.
goid_map	File containing mappings of genes to goids in the format expected by topgo.
go_db	Data frame of the goids which may be used to make the goid_map.
pvals	Set of pvalues in the DE data which may be used to improve the topgo results.
limitby	Test to index the results by.
limit	Ontology pvalue to use as the lower limit.
signodes	I don't remember right now.
sigforall	Provide the significance for all nodes?
numchar	Character limit for the table of results.
selector	Function name for choosing genes to include.
pval_column	Column from which to acquire scores.
overwrite	Yeah I do not remember this one either.
densities	Densities, yeah, the densities...
pval_plots	Include pvalue plots of the results a la clusterprofiler?
excel	Print the results to an excel file?
...	Other options which I do not remember right now!

Value

Big list including the various outputs from topgo

See Also

[topGO]

simple_topgo,character-method

Coerce simple_topgo to accept a vector of gene IDs instead of a real dataframe of significance.

Description

Doing this voids the topgo warantee.

Usage

```
## S4 method for signature 'character'
simple_topgo(
  sig_genes,
  goid_map = "id2go.map",
  go_db = NULL,
  pvals = NULL,
  limitby = "fisher",
  limit = 0.1,
  signodes = 100,
```

```

sigforall = TRUE,
numchar = 300,
selector = "topDiffGenes",
pval_column = "deseq_adj",
overwrite = FALSE,
densities = FALSE,
pval_plots = TRUE,
parallel = TRUE,
excel = NULL,
...
)

```

simple_varpart	<i>Use variancePartition to try and understand where the variance lies in a data set.</i>
----------------	---

Description

The arguments and usage of variancePartition are a bit opaque. This function attempts to fill in reasonable values and simplify its invocation.

Usage

```

simple_varpart(
  input,
  fstring = "~ condition + batch",
  do_fit = FALSE,
  cor_gene = 1,
  cpus = NULL,
  genes = 40,
  parallel = TRUE,
  strict_filter = TRUE,
  modify_input = TRUE
)

```

Arguments

do_fit	Perform a fitting using variancePartition?
cor_gene	Provide a set of genes to look at the correlations, defaults to the first gene.
cpus	Number cpus to use
genes	Number of genes to count.
parallel	Use doParallel?
strict_filter	Perform a strict filtering of the results via median_by_factor and dropping any genes with a 0.
expt	Some data
predictor	Non-categorical predictor factor with which to begin the model.
factors	Character list of columns in the experiment design to query
chosen_factor	When checking for sane 'batches', what column to extract from the design?
mixed	Used a mixed model?
modify_expt	Add annotation columns with the variance/factor?

Value

List of plots and variance data frames

See Also

[variancePartition] DOI:10.1186/s12859-016-1323-z.

simple_xcell

Invoke xCell and pretty-ify the result.

Description

I initially thought xCell might prove the best tool/method for exploring cell deconvolution. I slowly figured out its limitations, but still think it seems pretty nifty for its use case. Thus this function is intended to make invoking it easier/faster.

Usage

```
simple_xcell(
  expt,
  signatures = NULL,
  genes = NULL,
  spill = NULL,
  expected_types = NULL,
  label_size = NULL,
  col_margin = 6,
  row_margin = 12,
  sig_cutoff = 0.2,
  verbose = TRUE,
  cores = 4,
  ...
)
```

Arguments

expt	Expressionset to query.
signatures	Alternate set of signatures to use.
genes	Subset of genes to query.
spill	The xCell spill parameter.
expected_types	Set of assumed types in the data.
label_size	How large to make labels when printing the final heatmap.
col_margin	Used by par() when printing the final heatmap.
row_margin	Ibid.
sig_cutoff	Only keep celltypes with a significance better than this.
verbose	Print some extra information during runtime.
cores	How many CPUs to use?
...	Extra arguments when normalizing the data for use with xCell.

Value

Small list providing the output from xCell, the set of signatures, and heatmap.

See Also

[xCell]

single_topgo_tree	<i>Collapse the logic for collecting topgo trees into one little function.</i>
-------------------	--

Description

Collapse the logic for collecting topgo trees into one little function.

Usage

```
single_topgo_tree(
  tg,
  score_column = "fisher_mf",
  node_data = "fmmf_godata",
  score_limit = 0.1,
  sigforall = TRUE
)
```

Arguments

tg	TopGO result.
score_column	Use this column for the topgo scores.
node_data	and this column for the cateogyr names.
score_limit	The scores must be better than this.
sigforall	Calculate significance for all categories.

skim_seurat_metadata	<i>Use skimr to make pretty summaries of cell-data.</i>
----------------------	---

Description

I think I want to expand this to handle RNA summaries as well.

Usage

```
skim_seurat_metadata(
  sample_meta,
  obj_meta,
  meta_query = "nCount_RNA",
  group_column = NULL,
  summary_query = "numeric.mean",
  column_name = NULL,
  column_prefix = NULL,
  verbose = TRUE
)
```


Arguments

sample_meta	df of the known samples by name.
obj_meta	The 'meta.data' slot of a SCD
meta_query	Column to query.
group_column	Column used to group the cells.
summary_query	Which of the various data produced by skimr should be extracted?
column_name	Add the new column with this name.
column_prefix	And this prefix.
verbose	Print the pretty skimr table?

Value

df with some new meta(meta?)data.

slide_de_threshold	<i>make a slideable threshold for cutting off significant genes in a DE table.</i>
--------------------	--

Description

make a slideable threshold for cutting off significant genes in a DE table.

Usage

```
slide_de_threshold(  
  de_table,  
  contrast = 1,  
  lfc = 1,  
  p = 0.05,  
  according_to = "deseq"  
)
```

Arguments

de_table	Table of DE results.
contrast	Use this contrast for visualization.
lfc	LogFC starting cutoff.
p	Starting pvalue cutoff.
according_to	Which method to deem the arbiter of truth?

sm	<i>Silence</i>
----	----------------

Description

Some libraries/functions just won't shut up. Ergo, silence, peasant! This is a simpler silence peasant.

Usage

sm(...)

Arguments

... Some code to shut up.

Value

Whatever the code would have returned.

snp_by_chr	<i>The real worker. This extracts positions for a single chromosome and puts them into a parallelizable data structure.</i>
------------	---

Description

The real worker. This extracts positions for a single chromosome and puts them into a parallelizable data structure.

Usage

snp_by_chr(observations, chr_name = "01", limit = 1)

Arguments

observations A set of observations by position to look through
chr_name Chromosome name to search
limit Minimum number of median hits/position to count as a snp.

Value

A list of variant positions where each element is one chromosome.

See Also

[Vennerable]

snp_cds_primers	<i>Look for variants associated with CDS regions instead of high-density.</i>
-----------------	---

Description

The function `snp_density_primers` looks for regions with many variants. This flips the script and looks first to the set of CDS regions. It also makes heavy use of GRanges and so should prove useful as a reference when looking for range examples.

Usage

```
snp_cds_primers(
  cds_gr,
  variant_gr,
  bsgenome,
  amplicon_size = 600,
  min_overlap = 200,
  minvar_perbin = 10,
  super_len = 30,
  target_temp = 60,
  min_gc_prop = 0.3,
  max_nmer_run = 4,
  count_occurrences = TRUE,
  occurrence_mismatch = 0
)
```

Arguments

<code>cds_gr</code>	GRanges of CDS features. It does not have to be CDS, but probably should not be genes.
<code>variant_gr</code>	GRanges of observed variants. I get this by coercing my peculiar variant row-names into a GR.
<code>bsgenome</code>	Genome containing all the contigs mentioned above.
<code>amplicon_size</code>	Desired PCR amplicon for sequencing.
<code>min_overlap</code>	Desired overlap between every genome bin and CDS. Note I didn't say amplicon here because of the way I am making the primers.
<code>minvar_perbin</code>	Discard bins with less than this number of variants inside them.
<code>super_len</code>	I start out with a 'superprimer' which is assumed to be longer than needed for the target Tm. It is this long.
<code>target_temp</code>	Attempt to create primers with this Tm.
<code>min_gc_prop</code>	Warn or discard primers with less than this GC content.
<code>max_nmer_run</code>	Warn or discard primers with runs of a single base this long.
<code>count_occurrences</code>	Count up how many times the primer is found in the genome, hopefully this is always 1. Annoyingly, the <code>vcountDict</code> function does not allow mismatches.
<code>occurrence_mismatch</code>	I cannot use this, but I want to.

snp_density_primers *Create a density function given a variant output and some metadata*

Description

It is hoped that this will point out regions of a genome which might prove useful when designing PCR primers for a specific condition in a dataset of variants.

Usage

```
snp_density_primers(
  snp_count,
  pdata_column = "condition",
  condition = NULL,
  cutoff = 20,
  bin_width = 600,
  divide = FALSE,
  topn = 400,
  target_temp = 53,
  max_primer_length = 50,
  bsgenome = "BSGenome.Leishmania.panamensis.MHOMCOL81L13.v52",
  gff = "reference/lpanamensis_col_v46.gff",
  feature_type = "protein_coding_gene",
  feature_start = "start",
  feature_end = "end",
  feature_strand = "strand",
  feature_chr = "seqnames",
  feature_type_column = "type",
  feature_id = "ID",
  feature_name = "description",
  truncate = TRUE,
  xref_genes = TRUE,
  verbose = FALSE,
  min_contig_length = NULL,
  min_gc_prop = 0.25,
  max_nmer_run = 5
)
```

Arguments

snp_count	Result from count_expt_snps()
pdata_column	Metadata column containing the condition of interest.
condition	Chosen condition to search for variants.
cutoff	Minimum number of variants in a region.
bin_width	Bin size/region of genome to consider.
divide	Normalize by bin width?
topn	Keep only this number of candidates.
target_temp	Try to get primers with this Tm.

max_primer_length	Keep primers at or less than this length.
bsgenome	Genome package containing the sequence of interest.
gff	GFF to define regions of interest.
feature_type	GFF feature type to search against.
feature_start	GFF column with the starts (needed?)
feature_end	GFF column with the ends (needed?)
feature_strand	GFF column with strand information (needed?)
feature_chr	GFF column with chromosome information.
feature_type_column	GFF column with type information.
feature_id	GFF tag with the ID information.
feature_name	GFF tag with the names.
truncate	Truncate the results to just the columns I think are useful.
xref_genes	Cross reference the result against the nearest gene?
verbose	Talky talky?
min_contig_length	Skip any regions on small contigs?
min_gc_prop	Minimum GC content for a suitable primer.
max_nmer_run	Filter candidates on maximum nmer runs?

snp_subset_genes	<i>Look for only the variant positions in a subset of genes.</i>
------------------	--

Description

This was written in response to a query from Nancy and Maria Adelaida who wanted to look only at the variant positions in a few specific genes.

Usage

```
snp_subset_genes(
  expt,
  snp_expt,
  start_col = "start",
  end_col = "end",
  expt_name_col = "chromosome",
  snp_name_col = "chromosome",
  snp_start_col = "position",
  expt_gid_column = "gid",
  genes = c("LPAL13_120010900", "LPAL13_340013000", "LPAL13_000054100",
    "LPAL13_140006100", "LPAL13_180018500", "LPAL13_320022300")
)
```

Arguments

expt	Initial expressionset.
snp_expt	Variant position expressionset.
start_col	Metadata column with the start positions for each gene.
end_col	Metadata column with the end of the genes.
expt_name_col	Metadata column with the chromosome names.
snp_name_col	Ditto for the snp_expressionset.
snp_start_col	Metadata column containing the variant positions.
expt_gid_column	ID column for the genes.
genes	Set of genes to cross reference.

Value

New expressionset with only the variants for the genes of interest.

See Also

[GenomicRanges::makeGRangesFromDataFrame()] [IRanges::subsetByOverlaps()]

snpnames2gr	<i>Take a vector of my peculiarly named variants and turn them into a grange</i>
-------------	--

Description

Take a vector of my peculiarly named variants and turn them into a grange

Usage

snpnames2gr(names, gr = NULL)

Arguments

names	A set of things which look like: chr_x_pos_y_ref_a_alt_b
gr	Extant GRanges to modify?

snps_intersections	<i>Cross reference observed variants against the transcriptome annotation.</i>
--------------------	--

Description

This function should provide counts of how many variant positions were observed with respect to each chromosome and with respect to each annotated sequence (currently this is limited to CDS, but that is negotiable).

Usage

```
snps_intersections(
  expt,
  snp_result,
  start_column = "start",
  end_column = "end",
  chr_column = "seqnames"
)
```

Arguments

expt	The original expressionset. This provides the annotation data.
snp_result	The result from get_snp_sets or count_expt_snps.
start_column	Metadata column with the start position of each ORF.
end_column	Metadata column with the end position of each ORF.
chr_column	Column in the annotation with the chromosome names.

Value

List containing the set of intersections in the conditions contained in snp_result, the summary of numbers of variants per chromosome, and

See Also

[snps_vs_genes()] [GenomicRanges::makeGRangesFromDataFrame()] [IRanges::subsetByOverlaps()] [IRanges::countOverlaps()]

Examples

```
## Not run:
expt <- create_expt(metadata, gene_information)
snp_expt <- count_expt_snps(expt)
snp_result <- get_snp_sets(snp_expt)
intersections <- snps_vs_intersections(expt, snp_result)

## End(Not run)
```

snps_vs_genes

Make a summary of the observed snps by gene ID.

Description

Instead of cross referencing variant positions against experimental condition, one might be interested in seeing what variants are observed per gene. This function attempts to answer that question.

Usage

```
snps_vs_genes(
  expt,
  snp_result,
  start_col = "start",
  end_col = "end",
  snp_name_col = "seqnames",
  observed_in = NULL,
  expt_name_col = "chromosome",
  ignore_strand = TRUE
)
```

Arguments

expt	The original expressionset.
snp_result	The result from get_snp_sets().
start_col	Which column provides the start of each gene?
end_col	and the end column of each gene?
snp_name_col	Name of the column in the metadata with the sequence names.
observed_in	Minimum proportion of samples required before this is deemed real.
expt_name_col	Name of the metadata column with the chromosome names.
ignore_strand	Ignore strand information when returning?

Value

List with some information by gene.

See Also

[GenomicRanges::makeGRangesFromDataFrame()] [IRanges::subsetByOverlaps()] [IRanges::mergeByOverlaps()] [IRanges::countOverlaps()]

Examples

```
## Not run:
expt <- create_expt(metadata, gene_information)
snp_expt <- count_expt_snps(expt)
snp_result <- get_snp_sets(snp_expt)
gene_intersections <- snps_vs_genes(expt, snp_result)

## End(Not run)
```

snps_vs_genes_padded	<i>A copy of the above function with padding for species without defined UTRs</i>
----------------------	---

Description

A copy of the above function with padding for species without defined UTRs

Usage

```
snps_vs_genes_padded(
  expt,
  snp_result,
  start_col = "start",
  end_col = "end",
  strand_col = "strand",
  padding = 200,
  normalize = TRUE,
  snp_name_col = "seqnames",
  expt_name_col = "chromosome",
  observed_in = NULL,
  ignore_strand = TRUE
)
```

Arguments

expt	The original expressionset.
snp_result	The result from get_snp_sets().
start_col	Which column provides the start of each gene?
end_col	and the end column of each gene?
strand_col	Define strands.
padding	Add this amount to each CDS.
normalize	Normalize the returns to the length of the putative CDS.
snp_name_col	Name of the column in the metadata with the sequence names.
expt_name_col	Name of the metadata column with the chromosome names.
observed_in	Print some information about how many variants were observed.
ignore_strand	Ignore the strand information when returning?

Value

List with some information by gene.

See Also

[GenomicRanges::makeGRangesFromDataFrame()] [IRanges::subsetByOverlaps()] [IRanges::mergeByOverlaps()] [IRanges::countOverlaps()]

Examples

```
## Not run:
expt <- create_expt(metadata, gene_information)
snp_expt <- count_expt_snps(expt)
snp_result <- get_snp_sets(snp_expt)
gene_intersections <- snps_vs_genes(expt, snp_result)

## End(Not run)
```

state	<i>Get the state from an expt.</i>
-------	------------------------------------

Description

Get the state from an expt.
Get the state of the data in an expt.

Usage

```
state(expt)

state(expt)
```

Arguments

expt Experiment containing the state.

Value

List with the methods used to modify the data (if any).

state,expt-method	<i>Extract the state of an expt vis a vis normalization.</i>
-------------------	--

Description

Extract the state of an expt vis a vis normalization.

Usage

```
## S4 method for signature 'expt'
state(expt)
```

```
state, SummarizedExperiment-method
```

Get the state from a SummarizedExperiment.

Description

Get the state from a SummarizedExperiment.

Usage

```
## S4 method for signature 'SummarizedExperiment'
state(expt)
```

```
state<-
```

Set the state of the data in an expt.

Description

Set the state of the data in an expt.

Usage

```
state(expt) <- value
```

Arguments

expt	Experiment requiring a state update.
value	New state!

```
state<-, expt-method
```

Put the current state into an expt.

Description

Put the current state into an expt.

Usage

```
## S4 replacement method for signature 'expt'
state(expt) <- value
```

```
state<-, SummarizedExperiment-method
```

Put the state into a SummarizedExperiment.

Description

Put the state into a SummarizedExperiment.

Usage

```
## S4 replacement method for signature 'SummarizedExperiment'
state(expt) <- value
```

```
steal_salmon_tx_ids
```

Steal transcript IDs from the first count table.

Description

Steal transcript IDs from the first count table.

Usage

```
steal_salmon_tx_ids(
  meta,
  annotations,
  meta_column = "salmon_count_table",
  annot_gene_column = "ensembl_gene_id",
  annot_tx_column = "ensembl_transcript_id",
  keep_unique = TRUE
)
```

Arguments

<code>meta</code>	Input metadata containing the salmon count table names.
<code>annotations</code>	Extant set of gene annotations, likely from biomart.
<code>meta_column</code>	metadata column with the filenames.
<code>annot_gene_column</code>	Column of annotations with the gene IDs.
<code>annot_tx_column</code>	Column of annotations with the transcript IDs.
<code>keep_unique</code>	Drop the potential duplicate GIDs?

Value

List containing modified annotations for the genes, transcripts, and the map between them.

subset_expt	<i>Extract a subset of samples following some rule(s) from an experiment class.</i>
-------------	---

Description

Sometimes an experiment has too many parts to work with conveniently, this operation allows one to break it into smaller pieces.

Usage

```
subset_expt(
  expt,
  subset = NULL,
  ids = NULL,
  nonzero = NULL,
  coverage = NULL,
  print_excluded = FALSE
)
```

Arguments

expt	Expt chosen to extract a subset of data.
subset	Valid R expression which defines a subset of the design to keep.
ids	List of sample IDs to extract.
nonzero	Look for a minimal number of nonzero genes.
coverage	Request a minimum coverage/sample rather than text-based subset.
print_excluded	Print out the samples which are removed via this filter?

Value

metadata Expt class which contains the smaller set of data.

See Also

[Biobase] [pData()] [exprs()] [fData()]

Examples

```
## Not run:
smaller_expt <- expt_subset(big_expt, "condition=='control'")
all_expt <- expt_subset(expressionset, "") ## extracts everything

## End(Not run)
```

```
subset_expt, SummarizedExperiment-method
```

Subset a SummarizedExperiment with some extra syntax.

Description

Subset a SummarizedExperiment with some extra syntax.

Usage

```
## S4 method for signature 'SummarizedExperiment'
subset_expt(expt, subset = NULL, ids = NULL, nonzero = NULL, coverage = NULL)
```

```
subset_genes
```

Exclude some genes given a pattern match

Description

Because I am too lazy to remember that expressionsets use matrix subsets for gene and sample. Also those methods lead to shenanigans when I want to know what happened to the data over the course of the subset.

Usage

```
subset_genes(
  expt,
  column = "txtype",
  method = "remove",
  ids = NULL,
  warning_cutoff = 90,
  meta_column = NULL,
  patterns = c("snRNA", "tRNA", "rRNA"),
  ...
)
```

Arguments

expt	Expressionset containing expt object.
column	fData column to use for subsetting.
method	Either remove explicit rows, or keep them.
ids	Specific IDs to exclude.
warning_cutoff	Print the sample IDs for anything which has less than this percent left.
meta_column	Save the amount of data lost to this metadata column when not null.
patterns	Character list of patterns to remove/keep
...	Extra arguments are passed to arglist, currently unused.

Value

A smaller expt

See Also

[create_expt()] [Biobase]

Examples

```
## Not run:
all_expt <- create_expt(metadata)
## This assumes a column in the metadata named 'txtype' containing the
## information telling us what type of transcript each gene is.
no_ribosomes <- exclude_genes_expt(all_expt, column = "txtype",
                                   patterns = c("snRNA", "tRNA", "rRNA"))
i_hate_these_genes <- exclude_genes_expt(all_expt, ids = c("gene1", "gene2"))
only_ribosomes <- exclude_genes_expt(all_expt, method = "keep")

## End(Not run)
```

subset_ontology_search

Perform ontology searches on up/down subsets of differential expression data.

Description

In the same way all_pairwise() attempts to simplify using multiple DE tools, this function seeks to make it easier to extract subsets of differentially expressed data and pass them to goseq, clusterProfiler, topGO, GOstats, and gProfiler.

Usage

```
subset_ontology_search(
  changed_counts,
  doplot = TRUE,
  do_goseq = TRUE,
  do_cluster = TRUE,
  do_topgo = TRUE,
  do_gostats = TRUE,
  do_gprofiler = TRUE,
  according_to = "limma",
  ...
)
```

Arguments

changed_counts	List of changed counts as ups and downs.
doplot	Include plots in the results?
do_goseq	Perform goseq search?
do_cluster	Perform clusterprofiler search?

do_topgo	Perform topgo search?
do_gostats	Perform gostats search?
do_gprofiler	Do a gprofiler search?
according_to	If results from multiple DE tools were passed, which one defines 'significant'?
...	Extra arguments!

Value

List of ontology search results, up and down for each contrast.

See Also

[goseq] [clusterProfiler] [topGO] [goStats] [gProfiler]

subtract_expt	<i>Try a very literal subtraction</i>
---------------	---------------------------------------

Description

Try a very literal subtraction

Usage

```
subtract_expt(
  expt,
  new_meta,
  sample_column = "sample",
  convert_state = "cpm",
  transform_state = "raw",
  handle_negative = "zero",
  savefile = "subtracted.rda",
  ...
)
```

Arguments

expt	Input expressionset.
new_meta	dataframe containing the new metadata.
sample_column	Column in the sample sheet to use to acquire the sample IDs given the subtractions.
convert_state	Expected state of the input data vis a vis conversion (rpkm/cpm).
transform_state	Expected state of the input data vis a vis transformation (log/linear).
handle_negative	Set negative subtracted values to zero?
savefile	Save the new expt data to this file.
...	Parameters to pass to normalize_expt()

Value

New expt

`sum_eupath_exon_counts`

I want an easy way to sum counts in eupathdb-derived data sets. These have a few things which should make this relatively easy. Notably: The gene IDs look like: "exon_ID-1 exon_ID-2 exon_ID-3" Therefore we should be able to quickly merge these.

Description

I want an easy way to sum counts in eupathdb-derived data sets. These have a few things which should make this relatively easy. Notably: The gene IDs look like: "exon_ID-1 exon_ID-2 exon_ID-3" Therefore we should be able to quickly merge these.

Usage

```
sum_eupath_exon_counts(counts)
```

Arguments

counts Matrix/df/dt of count data.

Value

The same data type but with the exons summed.

`sum_exon_widths`

Given a data frame of exon counts and annotation information, sum the exons.

Description

This function will merge a count table to an annotation table by the child column. It will then sum all rows of exons by parent gene and sum the widths of the exons. Finally it will return a list containing a df of gene lengths and summed counts.

Usage

```
sum_exon_widths(  
  data = NULL,  
  gff = NULL,  
  annotdf = NULL,  
  parent = "Parent",  
  child = "row.names"  
)
```

Arguments

data	Count tables of exons.
gff	Gff filename.
annotdf	Dataframe of annotations (probably from load_gff_annotations).
parent	Column from the annotations with the gene names.
child	Column from the annotations with the exon names.

Value

List of 2 data frames, counts and lengths by summed exons.

Author(s)

Keith Hughitt with some modifications by atb.

See Also

[rtracklayer] [load_gff_annotations()]

Examples

```
## Not run:
summed <- sum_exon_widths(counts, gff = "reference/xenopus_laevis.gff.xz")

## End(Not run)
```

summarize_scd_clusters

Summarize scores across observed clusters in a scd.

Description

Currently this assumes the set of outputs produced by Seurat's AddModuleScore() for a gsc. It summarizes those scores for each cluster and gives back the mean, sd, and z.

Usage

```
summarize_scd_clusters(
  scd,
  fx = "mean",
  column_prefix = "descartes",
  column_range = NULL,
  cluster_column = "cluster_sample",
  real_column_names = NULL,
  abbreviate = TRUE,
  min_mean = NULL
)
```

Arguments

scd	Input dataset.
fx	Function to summarize, this may change.
column_prefix	Prefix for the scores of interest.
column_range	Explicitly set the range of interested columns.
cluster_column	The column containing the information about cluster occupancy.
real_column_names	The original columns get names like bob1 to bobn, this can be used to make them more informative.
abbreviate	When using mSigDB information, the category names are exceedingly long with often a consistent prefix.
min_mean	Currently unused, but intended to filter out gsc which are not observed to any significant degree.

summarize_ups_downs	<i>Create a summary table of the ranges of fold-change values of potential interest.</i>
---------------------	--

Description

The columns have names with explicit lfc values, but the numbers which get put in them may represent any arbitrary cutoff employed by the caller.

Usage

```
summarize_ups_downs(ups, downs)
```

Arguments

ups	The set of ups!
downs	and downs!

sv_fstatistics	<i>Calculate f-statistics between metadata factors and surrogate estimates.</i>
----------------	---

Description

This is taken directly from Theresa's TMRC work and is her idea. I mainly want to be able to use it on a few datasets without risking typographical or logical errors. In addition, I would like to be able to play with things like the number of surrogates and/or other methods of estimating them. In addition, I have some f-statistics of PCs vs metadata in the function 'pca_information()' which I think is likely complementary to her work (which makes sense, Hector was her professor before she joined us, and Hector suggested the PC idea to me).

Usage

```
sv_fstatistics(
  expt,
  num_surrogates = NULL,
  filter = TRUE,
  norm = "raw",
  convert = "cpm",
  transform = "log2",
  batch = "svaseq",
  sv_df = NULL,
  queries = c("typeofcells", "visitnumber", "donor"),
  ...
)
```

Arguments

expt	Input expressionset, redo everything to use SE, stupid.
num_surrogates	Specify the number of surrogates or let it choose.
filter	Pre-filter the data?
norm	Pre-normalize?
convert	Pre-convert?
transform	Pre-transform?
batch	Use this method
sv_df	Or provide your own set of SVs
queries	List of metadata factors to query.
...	Used to make compatible with pc_fstatistics and to pass stuff to normalize_expt().

sva_modify_pvalues	<i>Use sva's f.pvalue to adjust p-values for data adjusted by combat.</i>
--------------------	---

Description

This is from section 5 of the sva manual: "Adjusting for surrogate values using the f.pvalue function." The following chunk of code is longer and more complex than I would like. This is because f.pvalue() assumes a pairwise comparison of a data set containing only two experimental factors. As a way to provide an example of `_how_` to calculate appropriately corrected p-values for surrogate factor adjusted models, this is great; but when dealing with actual data, it falls a bit short.

Usage

```
sva_modify_pvalues(results)
```

Arguments

results	Table of differential expression results.
---------	---

See Also

[sva]

svpc_fstats	<i>Get the f-stats before/after messing with sva.</i>
-------------	---

Description

Get the f-stats before/after messing with sva.

Usage

svpc_fstats(expt, ...)

Arguments

expt	input
...	Args passed to everything else.

synchronize_expt	<i>Synchronize the extra elements of an expt with a new expressionset.</i>
------------------	--

Description

Synchronize the extra elements of an expt with a new expressionset.

Usage

synchronize_expt(expt, previous = NULL, ...)

Arguments

expt	Modified/new expt
previous	Optional previous state to use as a template.
...	Parameters used to fill in other optional slots.

table_style	<i>Set the xlsx table style</i>
-------------	---------------------------------

Description

Set the xlsx table style

Usage

table_style

Format

An object of class character of length 1.

tar_meta_column	<i>Make an archive using a column from the metadata.</i>
-----------------	--

Description

I am hoping this will be useful for either backing up count tables or making containerized versions of analyses.

Usage

```
tar_meta_column(
  meta,
  column = "hisatcounttable",
  output = NULL,
  compression = "xz"
)
```

Arguments

meta	dataframe of the good stuff.
column	Column containing filenames to archive.
output	Output prefix for the tarball's name.
compression	Actually, this might be a mistake, I think <code>utils::tar</code> takes 'gzip', not 'gz'?

tar_meta_column,character-method	<i>Make a tarball using a metadata column given an xlsx file.</i>
----------------------------------	---

Description

Make a tarball using a metadata column given an xlsx file.

Usage

```
## S4 method for signature 'character'
tar_meta_column(
  meta,
  column = "hisatcounttable",
  output = NULL,
  compression = "xz"
)
```

`tempfile`*A cheater redefinition of tempfile.*

Description

I found this at: <https://stackoverflow.com/questions/5262332/parallel-processing-and-temporary-files> and was intrigued. I did not think to overwrite the tempfile definition. Something in me says this is a terrible idea. The same page suggests creating all the tempfile names `_before_` beginning the parallel operations. I think this might be the way to go; however I do not know how that will affect the tempfile names produced by knitr when it is making its images.

Usage

```
tempfile(pattern = "file", tmpdir = tmpdir(), fileext = "")
```

Arguments

<code>pattern</code>	starting string of each tempfile.
<code>tmpdir</code>	Location to put the file.
<code>fileext</code>	suffix.

`test_design_model_rank`*Check on the rank of an experimental design*

Description

Check on the rank of an experimental design

Usage

```
test_design_model_rank(design, fstring = "~ condition + batch")
```

Arguments

<code>design</code>	Dataframe of metadata
<code>fstring</code>	Formula to test.

Value

List containing some information about degrees of freedom

```
test_design_model_rank, expt-method
```

Pass an expt to test_design_model_rank.

Description

Pass an expt to test_design_model_rank.

Usage

```
## S4 method for signature 'expt'
test_design_model_rank(design, fstring = "~ condition + batch")
```

Arguments

design	In this instance, an expressionset.
fstring	Formula string to query.

test_model_rank	<i>Make sure a given experimental factor and design will play together.</i>
-----------------	---

Description

Have you ever wanted to set up a differential expression analysis and after minutes of the computer churning away it errors out with some weird error about rank? Then this is the function for you!

Usage

```
test_model_rank(design, goal = "condition", factors = NULL, ...)
```

Arguments

design	Dataframe describing the design of the experiment.
goal	Experimental factor you actually want to learn about.
factors	Experimental factors you rather wish would just go away.
...	I might decide to add more options from other functions.

Value

List of booleans telling if the factors + goal will work.

See Also

[model.matrix()] [qr()]

tmpmd5file	<i>A hopefully more robust version of tempfile().</i>
------------	---

Description

A hopefully more robust version of tempfile().

Usage

```
tmpmd5file(pattern = "", suffix = "", digits = 6, body = NULL, fileext = "")
```

Arguments

pattern	Filename prefix.
suffix	Filename suffix.
digits	Currently I use Sys.time() with this number of digits.
body	No implemented, intended to use other sources of digest()
fileext	Filename extension as per tempfile().

Value

md5 based tempfilename.

tnseq_multi_saturation	<i>Plot the saturation of multiple libraries simultaneously.</i>
------------------------	--

Description

Plot the saturation of multiple libraries simultaneously.

Usage

```
tnseq_multi_saturation(
  meta,
  meta_column,
  ylimit = 100,
  column = "Reads",
  adjust = 1,
  ggstatsplot = FALSE
)
```

Arguments

meta	Experimental metadata
meta_column	Metadata column containing the filenames to query.
ylimit	Maximum y axis
column	Data file column to use for density calculation.
adjust	Density adjustment.
ggstatsplot	Include pretty ggstatsplot plot?

Value

a plot and table of the saturation for all samples.

tnseq_saturation	<i>Make a plot and some simple numbers about tnseq saturation</i>
------------------	---

Description

This function takes as input a tab separated file from essentiality_tas.pl This is a perl script written to read a bam alignment of tnseq reads against a genome and count how many hits were observed on every TA in the given genome. It furthermore has some logic to tell the difference between reads which were observed on the forward vs. reverse strand as well as reads which appear to be on both strands (eg. they start and end with 'TA').

Usage

```
tnseq_saturation(data, column = "Reads", ylimit = 100, adjust = 2)
```

Arguments

data	data to plot
column	which column to use for plotting
ylimit	Define the y axis?
adjust	Prettification parameter from ggplot2.

Value

A plot and some numbers:

1. maximum_reads = The maximum number of reads observed in a single position.
2. hits_by_position = The full table of hits / position
3. num_hit_table = A table of how many times every number of hits was observed.
4. eq_0 = How many times were 0 hits observed?
5. gt_1 = How many positions have > 1 hit?
6. gt_2 = How many positions have > 2 hits?
7. gt_4 = How many positions have > 4 hits?
8. gt_8 = How many positions have > 8 hits?
9. gt_16 = How many positions have > 16 hits?
10. gt_32 = How many positions have > 32 hits?
11. ratios = Character vector of the ratios of each number of hits vs. 0 hits.
12. hit_positions = 2 column data frame of positions and the number of observed hits.
13. hits_summary = summary(hit_positions)
14. plot = Histogram of the number of hits observed.

See Also

[ggplot2]

Examples

```
## Not run:
input <- "preprocessing/hpgl0837/essentiality/hpgl0837-trimmed_ca_ta-v0M1.wig"
saturation <- tseq_saturation(file = input)

## End(Not run)
```

topDiffGenes	<i>A very simple selector of strong scoring genes (by p-value)</i>
--------------	--

Description

This function was provided in the topGO documentation, but not defined. It was copied/pasted here. I have ideas for including up/down expression but have so far deemed them not needed because I am feeding topGO already explicit lists of genes which are up/down/whatever. But it still is likely to be useful to be able to further subset the data.

Usage

```
topDiffGenes(allScore)
```

Arguments

allScore	The scores of the genes
----------	-------------------------

topgo_tables	<i>Make pretty tables out of topGO data</i>
--------------	---

Description

The topgo function GenTable is neat, but it needs some simplification to not be obnoxious.

Usage

```
topgo_tables(
  result,
  godata,
  limit = 0.1,
  limitby = "fisher",
  numchar = 300,
  orderby = "fisher",
  ranksof = "fisher"
)
```

Arguments

result	Topgo result.
godata	The ontology database.
limit	Pvalue limit defining 'significant'.
limitby	Type of test to perform.
numchar	How many characters to allow in the description?
orderby	Which of the available columns to order the table by?
ranksof	Which of the available columns are used to rank the data?

Value

prettier tables

See Also

[topGO]

topgo_trees	<i>Print trees from topGO.</i>
-------------	--------------------------------

Description

The tree printing functionality of topGO is pretty cool, but difficult to get set correctly.

Usage

```
topgo_trees(  
  tg,  
  score_limit = 0.01,  
  sigforall = TRUE,  
  do_mf_fisher_tree = TRUE,  
  do_bp_fisher_tree = TRUE,  
  do_cc_fisher_tree = TRUE,  
  do_mf_ks_tree = FALSE,  
  do_bp_ks_tree = FALSE,  
  do_cc_ks_tree = FALSE,  
  do_mf_el_tree = FALSE,  
  do_bp_el_tree = FALSE,  
  do_cc_el_tree = FALSE,  
  do_mf_weight_tree = FALSE,  
  do_bp_weight_tree = FALSE,  
  do_cc_weight_tree = FALSE,  
  parallel = FALSE  
)
```

Arguments

tg	Data from simple_topgo().
score_limit	Score limit to decide whether to add to the tree.
sigforall	Add scores to the tree?
do_mf_fisher_tree	Add the fisher score molecular function tree?
do_bp_fisher_tree	Add the fisher biological process tree?
do_cc_fisher_tree	Add the fisher cellular component tree?
do_mf_ks_tree	Add the ks molecular function tree?
do_bp_ks_tree	Add the ks biological process tree?
do_cc_ks_tree	Add the ks cellular component tree?
do_mf_el_tree	Add the el molecular function tree?
do_bp_el_tree	Add the el biological process tree?
do_cc_el_tree	Add the el cellular component tree?
do_mf_weight_tree	Add the weight mf tree?
do_bp_weight_tree	Add the bp weighted tree?
do_cc_weight_tree	Add the guess
parallel	Perform operations in parallel to speed this up?

Value

Big list including the various outputs from topgo.

See Also

[topGO]

topgo2enrich	<i>Convert a simple_topgo() result to an enrichResult.</i>
--------------	--

Description

Same idea as goseq2enrich.

Usage

```
topgo2enrich(
  retlist,
  ontology = "mf",
  pval = 0.05,
  organism = NULL,
  column = "fisher",
  padjust_method = "BH"
)
```

Arguments

retlist	result from simple_topgo()
ontology	Ontology subtree to act upon.
pval	Cutoff, hmm I think I need to standardize these.
organism	org name/data.
column	Table column to export.
padjust_method	Use this method for the pvalues for the enrich result.

Value

enrichResult object ready to pass to things like dotplot.

transform_counts	<i>Perform a simple transformation of a count table (log2)</i>
------------------	--

Description

the add argument is only important if the data was previously cpm'd because that does a +1, thus this will avoid a double+1 on the data.

Usage

```
transform_counts(count_table, design = NULL, method = "raw", base = NULL, ...)
```

Arguments

count_table	Matrix of count data
design	Sometimes the experimental design is also required.
method	Type of transformation to perform: log2/log10/log.
base	Other log scales?
...	Options I might pass from other functions are dropped into arglist.

Value

dataframe of transformed counts.

See Also

[limma]

Examples

```
## Not run:
filtered_table = transform_counts(count_table, transform='log2', converted='cpm')

## End(Not run)
```

u_plot	<i>Plot the rank order svd\$u elements to get a view of how much the first genes contribute to the total variance by PC.</i>
--------	--

Description

Plot the rank order svd\$u elements to get a view of how much the first genes contribute to the total variance by PC.

Usage

```
u_plot(plotted_us)
```

Arguments

plotted_us a list of svd\$u elements

Value

a recordPlot() plot showing the first 3 PCs by rank-order svd\$u.

unAsIs	<i>Remove the AsIs attribute from some data structure.</i>
--------	--

Description

Notably, when using some gene ontology libraries, the returned data structures include information which is set to type 'AsIs' which turns out to be more than slightly difficult to work with.

Usage

```
unAsIs(stuff)
```

Arguments

stuff The data from which to remove the AsIs classification.

update.RNAseq.SimOptions.2grp	<i>Use my cheater infix ::: to handle some unexported stuff from PROPER.</i>
-------------------------------	--

Description

Use my cheater infix ::: to handle some unexported stuff from PROPER.

Usage

```
## S3 method for class 'RNAseq.SimOptions.2grp'
update(sim.opts)
```

upsetr_combined_de	<i>Make an upset plot of all up/down genes in a set of contrasts.</i>
--------------------	---

Description

This is intended to give a quick and dirty view of the genes observed in a series of de comparisons.

Usage

```
upsetr_combined_de(
  combined,
  according_to = "deseq",
  lfc = 1,
  adjp = 0.05,
  text_scale = 2,
  color_by = NULL,
  desired_contrasts = NULL,
  intersections = "all",
  num_sets = "all"
)
```

Arguments

combined	Result from combine_de_tables.
according_to	Choose the lfc column to use.
lfc	Choose the logFC
adjp	and the p-value.
desired_contrasts	Use factors from a few contrasts.

upsetr_sig	<i>Use UpSetR to compare significant gene lists.</i>
------------	--

Description

Use UpSetR to compare significant gene lists.

Usage

```
upsetr_sig(
  sig,
  according_to = "deseq",
  contrasts = NULL,
  up = TRUE,
  down = TRUE,
  both = TRUE,
  all = TRUE,
  scale = 2,
```



```

    intersections = "all",
    num_sets = "all",
    ...
)

```

Arguments

sig	datastructure of significantly DE genes.
according_to	Choose your favorite method.
contrasts	Choose a specific contrast(s)
up	Make a plot of the up genes?
down	Make a plot of the down genes?
both	Make a plot of the up+down genes?
scale	Make the numbers larger and easier to read?
...	Other parameters to pass to upset().

variance_expt	<i>Add some gene annotations based on the mean/variance in the data.</i>
---------------	--

Description

Why? Maria Adelaida is interested in pulling the least-variant genes in our data, this seems like it might be generally applicable. Note, I made this slightly redundant by doing a cpm on the data; as a result the proportion and mean values are effectively identical.

Usage

```
variance_expt(expt, convert = "cpm", transform = "raw", norm = "raw")
```

Arguments

expt	Expressionset to which to add this information.
convert	Use this conversion,
transform	and transformation,
norm	and normalization.

Value

Slightly modified gene annotations including the mean/variance.

varpart_summaries	<i>Attempt to use variancePartition's fitVarPartModel() function.</i>
-------------------	---

Description

Note the word 'attempt'. This function is so ungodly slow that it probably will never be used.

Usage

```
varpart_summaries(expt, factors = c("condition", "batch"), cpus = 6)
```

Arguments

expt	Input expressionset.
factors	Set of factors to query
cpus	Number of cpus to use in doParallel.

Value

Summaries of the new model, in theory this would be a nicely batch-corrected data set.

See Also

[variancePartition]

verbose	<i>Set a default verbosity, for now this just queries if this is an interactive session.</i>
---------	--

Description

Set a default verbosity, for now this just queries if this is an interactive session.

Usage

```
verbose
```

Format

An object of class logical of length 1.

wgcna_network	<i>Just putting down an example from Alejandro's work and https://bioinformaticsworkbook.org/tutorials/wgcna.html#gsc.tab=0 so that I have someplace to remember the general path wgcna takes and as a starting point to explore further.</i>
---------------	---

Description

Just putting down an example from Alejandro's work and <https://bioinformaticsworkbook.org/tutorials/wgcna.html#gsc.tab=0> so that I have someplace to remember the general path wgcna takes and as a starting point to explore further.

Usage

```
wgcna_network(expt)
```

Arguments

expt	Input expressionset.
------	----------------------

what_happened	<i>Print a string describing what happened to this data.</i>
---------------	--

Description

Sometimes it is nice to have a string like: `log2(cpm(data))` describing what happened to the data.

Usage

```
what_happened(
  expt = NULL,
  transform = "raw",
  convert = "raw",
  norm = "raw",
  filter = "raw",
  batch = "raw",
  impute = "raw"
)
```

Arguments

expt	The expressionset.
transform	How was it transformed?
convert	How was it converted?
norm	How was it normalized?
filter	How was it filtered?
batch	How was it batch-corrected?

Value

An expression describing what has been done to this data.

See Also

[create_expt()] [normalize_expt()]

write_basic	<i>Writes out the results of a basic search using write_de_table()</i>
-------------	--

Description

Looking to provide a single interface for writing tables from basic and friends.

Usage

```
write_basic(data, ...)
```

Arguments

data	Output from basic_pairwise()
...	Options for writing the xlsx file.

Details

Tested in test_26basic.R

See Also

[basic_pairwise()] [write_de_table()]

Examples

```
## Not run:
finished_comparison <- basic_pairwise(expressionset)
data_list <- write_basic(finished_comparison)

## End(Not run)
```

write_cds_entries	<i>Extract CDS sequences from a genome and set of annotations.</i>
-------------------	--

Description

Given a BSGenome and some annotations, write out the CDS entries.

Usage

```
write_cds_entries(
  genome,
  annot,
  ids = NULL,
  output = "all_cds.fasta",
  strand_column = "strand",
  chr_column = "chromosome",
  start_column = "start",
  end_column = "end",
  name_column = "rownames",
  name_prefix = "lpanamensis_mcol"
)
```

Arguments

genome	BSGenome containing the raw sequence.
annot	Annotation dataframe.
ids	Set of annotations to write, write them all if null.
output	Fasta file to write.
strand_column	Column name with the strand information.
chr_column	Column name with the chromosomes.
start_column	Column with the start positions.
end_column	Column with the end positions.
name_column	Names of the CDS
name_prefix	Prefix to add to the entries.

write_classifier_summary	<i>Write out the results of classify_n_times().</i>
--------------------------	---

Description

Write out the results of classify_n_times().

Usage

```
write_classifier_summary(result, excel = "ML_summary.xlsx", name = NULL)
```

Arguments

result	Ibid.
excel	Output excel file
name	Name of the sheet to write.

write_combined_legend *Write the legend of an excel file for combine_de_tables()*

Description

Write the legend of an excel file for combine_de_tables()

Usage

```
write_combined_legend(
  wb,
  excel_basename,
  plot_dim,
  apr,
  basic,
  deseq,
  dream,
  ebseq,
  edger,
  limma,
  noiseq,
  includes,
  padj_type,
  fancy = FALSE
)
```

Arguments

wb	Workbook to write
excel_basename	Where to write it
plot_dim	Default plot size.
apr	The all_pairwise() result.
basic	Basic data
deseq	The deseq result, which is redundant.
dream	The result from varpart::dream
ebseq	The ebseq result, which is redundant.
edger	The edger result, which is redundant.
limma	The limma result, which is redundant.
noiseq	Noiseq results.
includes	List of booleans defining which methods to examine.
padj_type	P-adjustment employed.
fancy	Write fancy plots with the xlsx file?

write_combined_summary

Internal function to write a summary of some combined data

Description

Internal function to write a summary of some combined data

Usage

```
write_combined_summary(
  wb,
  excel_basename,
  apr,
  extracted,
  compare_plots,
  lfc_cutoff = 1,
  p_cutoff = 0.05,
  fancy = FALSE
)
```

Arguments

wb	xlsx workbook to which to write.
excel_basename	basename for printing plots.
apr	a pairwise result
extracted	table extracted from the pairwise result
compare_plots	series of plots to print out.
lfc_cutoff	Used for volcano/MA plots.
p_cutoff	Used for volcano/MA plots.
fancy	Write fancy plots with the xlsx file?

write_cp_data

Make a pretty table of clusterprofiler data in excel.

Description

It is my intention to make a function like this for each ontology tool in my repertoire

Usage

```
write_cp_data(
  cp_result,
  excel = "excel/clusterprofiler.xlsx",
  add_trees = TRUE,
  order_by = "qvalue",
  pval = 0.1,
```

```

    add_plots = TRUE,
    height = 15,
    width = 10,
    decreasing = FALSE,
    primary_key = 1,
    new = "ORF",
    add_gsea = TRUE,
    pval_column = "deseq_adj_p",
    ...
)

```

Arguments

<code>cp_result</code>	A set of results from <code>simple_clusterprofiler()</code> .
<code>excel</code>	An excel file to which to write some pretty results.
<code>add_trees</code>	Include topgoish ontology trees?
<code>order_by</code>	What column to order the data by?
<code>pval</code>	Choose a cutoff for reporting by p-value.
<code>add_plots</code>	Include some pvalue plots in the excel output?
<code>height</code>	Height of included plots.
<code>width</code>	and their width.
<code>decreasing</code>	which direction?
<code>primary_key</code>	Use this annotation column to keep track of annotation IDs.
<code>...</code>	Extra arguments are passed to <code>arglist</code> .

Value

The result from `openxlsx` in a prettyfied xlsx file.

See Also

[`openxlsx`]

`write_de_table`

Writes out the results of a single pairwise comparison.

Description

However, this will do a couple of things to make one's life easier: 1. Make a list of the output, one element for each comparison of the contrast matrix. 2. Write out the `results()` output for them in separate sheets in excel. 3. Since I have been using qvalues a lot for other stuff, add a column.

Usage

```
write_de_table(
  data,
  type = "limma",
  coef = NULL,
  table_type = "contrasts",
  excel = "de_table.xlsx",
  n = 0,
  ...
)
```

Arguments

data	Output from results().
type	Which DE tool to write.
excel	Filename into which to save the excel data.
...	Parameters passed downstream, dumped into arglist and passed, notably the number of genes (n), the coefficient column (coef)

Details

Tested in test_24deseq.R Rewritten in 2016-12 looking to simplify combine_de_tables(). That function is far too big, this should become a template for that.

Value

List of data frames comprising the toptable output for each coefficient, I also added a qvalue entry to these toptable() outputs.

See Also

[write_excel](#)

Examples

```
## Not run:
finished_comparison <- eBayes(deseq_output)
data_list <- write_deseq(finished_comparison, workbook="excel/deseq_output.xls")

## End(Not run)
```

write_density_primers *Write out a set of primers for testing.*

Description

Write out a set of primers for testing.

Usage

```
write_density_primers(
  density_primers,
  prefix = "pf",
  column = "fwd_primer",
  fasta = "forward_primers.fasta"
)
```

Arguments

density_primers	List containing a series of putative sequencing/PCR primers.
prefix	Sequence name prefix, 'pf' meaning 'primer forward'.
column	Column from the dataframe of putative primers.
fasta	Output filename.

Value

DNAStrngSet of the primers with side effect of written fasta file.

write_deseq	<i>Writes out the results of a deseq search using write_de_table()</i>
-------------	--

Description

Looking to provide a single interface for writing tables from deseq and friends.

Usage

```
write_deseq(data, ...)
```

Arguments

data	Output from deseq_pairwise()
...	Options for writing the xlsx file.

Details

Tested in test_24deseq.R

See Also

[write_de_table()]

Examples

```
## Not run:
finished_comparison <- deseq2_pairwise(expressionset)
data_list <- write_deseq(finished_comparison)

## End(Not run)
```

write_edger	<i>Writes out the results of a edger search using write_de_table()</i>
-------------	--

Description

Looking to provide a single interface for writing tables from edger and friends.

Usage

```
write_edger(data, ...)
```

Arguments

data	Output from deseq_pairwise()
...	Options for writing the xlsx file.

Details

Tested in test_26edger.R

See Also

[write_de_Table()]

Examples

```
## Not run:
finished_comparison <- edger_pairwise(expressionset)
data_list <- write_edger(finished_comparison, excel = "edger_result.xlsx")

## End(Not run)
```

write_expt	<i>Make pretty xlsx files of count data.</i>
------------	--

Description

Some folks love excel for looking at this data. ok.

Usage

```
write_expt(
  expt,
  excel = "excel/pretty_counts.xlsx",
  norm = "quant",
  violin = TRUE,
  sample_heat = NULL,
  convert = "cpm",
  transform = "log2",
  batch = "svaseq",
```

```

    filter = TRUE,
    med_or_mean = "mean",
    color_na = "#DD0000",
    merge_order = "counts_first",
    ...
)

```

Arguments

expt	An expressionset to print.
excel	Filename to write.
norm	Normalization to perform.
violin	Include violin plots?
sample_heat	Include sample heatmaps?
convert	Conversion to perform.
transform	Transformation used.
batch	Batch correction applied.
filter	Filtering method used.
med_or_mean	When printing mean by condition, one may want median.
color_na	Color cells which were NA before imputation this color.
merge_order	Used to decide whether to put the counts or annotations first when printing count tables.
...	Parameters passed down to methods called here (graph_metrics, etc).

Details

Tested in test_03graph_metrics.R This performs the following: Writes the raw data, graphs the raw data, normalizes the data, writes it, graphs it, and does a median-by-condition and prints that. I replaced the openxlsx function which writes images into xlsx files with one which does not require an opening of a pre-existing plotter. Instead it (optionally) opens a pdf device, prints the plot to it, opens a png device, prints to that, and inserts the resulting png file. Thus it sacrifices some flexibility for a hopefully more consistent behavior. In addition, one may use the pdfs as a set of images importable into illustrator or whatever.

Value

A big honking excel file and a list including the dataframes and images created.

See Also

[openxlsx] [Biobase] [normalize_expt()] [graph_metrics()]

Examples

```

## Not run:
excel_sucks <- write_expt(expt)

## End(Not run)

```

write_go_xls*Write gene ontology tables for excel*

Description

Combine the results from goseq, cluster profiler, topgo, and gostats and drop them into excel. Hopefully with a relatively consistent look.

Usage

```
write_go_xls(  
  goseq,  
  cluster,  
  topgo,  
  gostats,  
  gprofiler,  
  file = "excel/merged_go",  
  dated = TRUE,  
  n = 30,  
  overwritefile = TRUE  
)
```

Arguments

goseq	The goseq result from simple_goseq()
cluster	The result from simple_clusterprofiler()
topgo	Guess
gostats	Yep, ditto
gprofiler	woo hoo!
file	the file to save the results.
dated	date the excel file
n	the number of ontology categories to include in each table.
overwritefile	overwrite an existing excel file

Value

the list of ontology information

See Also

[openxlsx] [simple_goseq()] [simple_clusterprofiler()] [simple_gostats()] [simple_topgo()] [simple_gprofiler()]

write_goseq_data	<i>Make a pretty table of goseq data in excel.</i>
------------------	--

Description

It is my intention to make a function like this for each ontology tool in my repertoire

Usage

```
write_goseq_data(
  goseq_result,
  excel = "excel/goseq.xlsx",
  wb = NULL,
  add_trees = TRUE,
  gather_genes = TRUE,
  order_by = "qvalue",
  pval = 0.1,
  add_plots = TRUE,
  height = 15,
  width = 10,
  decreasing = FALSE,
  ...
)
```

Arguments

goseq_result	A set of results from simple_goseq().
excel	An excel file to which to write some pretty results.
wb	Workbook object to write to.
add_trees	Include topgoish ontology trees?
gather_genes	Make a table of the genes in each category? (This may be slow)
order_by	What column to order the data by?
pval	Choose a cutoff for reporting by p-value.
add_plots	Include some pvalue plots in the excel output?
height	Height of included plots.
width	and their width.
decreasing	In forward or reverse order?
...	Extra arguments are passed to arglist.

Value

The result from openxlsx in a prettyified xlsx file.

See Also

[openxlsx] [simple_goseq()]

write_gostats_data	<i>Make a pretty table of gostats data in excel.</i>
--------------------	--

Description

It is my intention to make a function like this for each ontology tool in my repertoire

Usage

```
write_gostats_data(  
  gostats_result,  
  excel = "excel/gostats.xlsx",  
  add_trees = TRUE,  
  order_by = "qvalue",  
  pval = 0.1,  
  add_plots = TRUE,  
  height = 15,  
  width = 10,  
  decreasing = FALSE,  
  ...  
)
```

Arguments

<code>gostats_result</code>	A set of results from <code>simple_gostats()</code> .
<code>excel</code>	An excel file to which to write some pretty results.
<code>add_trees</code>	Include topgoish ontology trees?
<code>order_by</code>	Which column to order the data by?
<code>pval</code>	Choose a cutoff for reporting by p-value.
<code>add_plots</code>	Include some pvalue plots in the excel output?
<code>height</code>	Height of included plots.
<code>width</code>	and their width.
<code>decreasing</code>	Which order?
<code>...</code>	Extra arguments are passed to <code>arglist</code> .

Value

The result from `openxlsx` in a prettyfied xlsx file.

See Also

[`openxlsx`] [`simple_gostats()`]

`write_gprofiler_data` *Write some excel results from a gprofiler search.*

Description

Gprofiler is pretty awesome. This function will attempt to write its results to an excel file.

Usage

```
write_gprofiler_data(
  gprofiler_result,
  wb = NULL,
  excel = "excel/gprofiler_result.xlsx",
  order_by = "recall",
  add_plots = TRUE,
  height = 15,
  width = 10,
  decreasing = FALSE,
  ...
)
```

Arguments

<code>gprofiler_result</code>	The result from <code>simple_gprofiler()</code> .
<code>wb</code>	Optional workbook object, if you wish to append to an existing workbook.
<code>excel</code>	Excel file to which to write.
<code>order_by</code>	Which column to order the data by?
<code>add_plots</code>	Add some pvalue plots?
<code>height</code>	Height of included plots?
<code>width</code>	And their width.
<code>decreasing</code>	Which order?
<code>...</code>	More options, not currently used I think.

Value

A prettyfied table in an xlsx document.

See Also

[`openxlsx`] [`simple_gprofiler()`]

write_gsva	<i>Write out my various attempts at making sense of gsva.</i>
------------	---

Description

While I am trying to make sense of gsva, I will use this function to write out the results I get so I can pass them to Najib/Maria Adelaida/Theresa to see if I am making sense.

Usage

```
write_gsva(retlist, excel, plot_dim = 6)
```

Arguments

retlist	Result from running get_sig_gsva
excel	Excel file to write
plot_dim	Plot dimensions, likely needs adjustment.

See Also

[simple_gsva()] [score_gsva_likelihoods()] [get_sig_gsva_categories()]

write_limma	<i>Writes out the results of a limma search using write_de_table()</i>
-------------	--

Description

Looking to provide a single interface for writing tables from limma and friends.

Usage

```
write_limma(data, ...)
```

Arguments

data	Output from limma_pairwise()
...	Options for writing the xlsx file.

See Also

[write_de_table()]

Examples

```
## Not run:
finished_comparison = limma_pairwise(expressionset)
data_list = write_limma(finished_comparison)

## End(Not run)
```

write_sample_design	<i>Put the metadata at the end of combined_de_tables()</i>
---------------------	--

Description

For the moment this is a stupidly short function. I am betting we will elaborate on this over time.

Usage

```
write_sample_design(wb, apr)
```

Arguments

wb	workbook object.
apr	Pairwise result.

write_sig_legend	<i>Internal function to write a legend for significant gene tables.</i>
------------------	---

Description

Internal function to write a legend for significant gene tables.

Usage

```
write_sig_legend(wb)
```

Arguments

wb	xlsx workbook object from openxlsx.
----	-------------------------------------

write_snps	<i>Write a matrix of variants in an alignment-esque format.</i>
------------	---

Description

Write a matrix of variants in an alignment-esque format.

Usage

```
write_snps(expt, output_file = "funky.aln")
```

Arguments

expt	variant expressionset.
output_file	File to write, presumably to be passed to something like phyML.

write_subset_ontologies

Write gene ontology tables for data subsets

Description

Given a set of ontology results, this attempts to write them to an excel workbook in a consistent and relatively easy-to-read fashion.

Usage

```
write_subset_ontologies(
  kept_ontology,
  outfile = "excel/subset_go",
  dated = TRUE,
  n = NULL,
  overwritefile = TRUE,
  add_plots = TRUE,
  ...
)
```

Arguments

kept_ontology	A result from subset_ontology_search()
outfile	Workbook to which to write.
dated	Append the year-month-day-hour to the workbook.
n	How many ontology categories to write for each search
overwritefile	Overwrite an existing workbook?
add_plots	Add the various p-value plots to the end of each sheet?
...	some extra parameters

Value

a set of excel sheet/coordinates

See Also

[openxlsx]

Examples

```
## Not run:
all_contrasts <- all_pairwise(expt, model_batch = TRUE)
keepers <- list(bob = ('numerator','denominator'))
kept <- combine_de_tables(all_contrasts, keepers = keepers)
changed <- extract_significant_genes(kept)
kept_ontologies <- subset_ontology_search(changed, lengths = gene_lengths,
                                         goids = goids, gff = gff, gff_type='gene')
go_writer <- write_subset_ontologies(kept_ontologies)

## End(Not run)
```

write_suppa_table	<i>Take a set of results from suppa and attempt to write it to a pretty xlsx file.</i>
-------------------	--

Description

Suppa provides a tremendous amount of output, this attempts to standardize those results and print them to an excel sheet.

Usage

```
write_suppa_table(
  table,
  annotations = NULL,
  by_table = "gene_name",
  by_annot = "ensembl_gene_id",
  columns = "default",
  excel = "excel/suppa_table.xlsx"
)
```

Arguments

table	Result table from suppa.
annotations	Set of annotation data to include with the suppa result.
by_table	Use this column to merge the annotations and data tables from the perspective of the data table.
by_annot	Use this column to merge the annotations and data tables from the perspective of the annotations.
columns	Choose a subset of columns to include, or leave the defaults.
excel	Provide an excel file to write.

Value

Data frame of the merged data.

See Also

[write_xlsx()]

Examples

```
## Not run:
prettier_table <- write_suppa_table(suppa_result_file,
                                   annotations = gene_info,
                                   excel = "excel/pretty_suppa_table.xlsx")

## End(Not run)
```

write_svpc_fstats	<i>Write an xlsx file of SV/PC f-statistics</i>
-------------------	---

Description

Write an xlsx file of SV/PC f-statistics

Usage

```
write_svpc_fstats(input, excel = "excel/svpc_fstats.xlsx")
```

Arguments

input	Result from svpc_fstats()
excel	Output excel file.

write_topgo_data	<i>Make a pretty table of topgo data in excel.</i>
------------------	--

Description

It is my intention to make a function like this for each ontology tool in my repertoire

Usage

```
write_topgo_data(
  topgo_result,
  excel = "excel/topgo.xlsx",
  wb = NULL,
  order_by = "fisher",
  decreasing = FALSE,
  pval = 0.1,
  add_plots = TRUE,
  height = 15,
  width = 10,
  ...
)
```

Arguments

topgo_result	A set of results from simple_topgo().
excel	An excel file to which to write some pretty results.
wb	Workbook object to write to.
order_by	Which column to order the results by?
decreasing	In forward or reverse order?
pval	Choose a cutoff for reporting by p-value.
add_plots	Include some pvalue plots in the excel output?
height	Height of included plots.
width	and their width.
...	Extra arguments are passed to arglist.

Value

The result from openxlsx in a prettyfied xlsx file.

See Also

[openxlsx] [simple_topgo()]

write_xlsx

Write a dataframe to an excel spreadsheet sheet.

Description

I like to give folks data in any format they prefer, even though I sort of hate excel. Most people I work with use it, so therefore I do too. This function has been through many iterations, first using XLConnect, then xlsx, and now openxlsx. Hopefully this will not change again.

Usage

```
write_xlsx(
  data = NULL,
  wb = NULL,
  sheet = "first",
  excel = NULL,
  rownames = TRUE,
  start_row = 1,
  start_col = 1,
  title = NULL,
  float_format = "0.000",
  data_table = TRUE,
  freeze_first_row = TRUE,
  freeze_first_column = TRUE,
  date_format = "yyyy-mm-dd",
  column_width = "heuristic",
  ...
)
```

Arguments

data	Data frame to print.
wb	Workbook to which to write.
sheet	Name of the sheet to write.
excel	Filename of final excel workbook to write
rownames	Include row names in the output?
start_row	First row of the sheet to write. Useful if writing multiple tables.
start_col	First column to write.
title	Title for this xlsx table.
float_format	Revisit this, but it hard-sets the number of decimal points in floating point columns.

data_table	Write this as an excel data table instead of just a collection of cells.
freeze_first_row	Add a hint to make the first row always on screen?
freeze_first_column	Add a hint to make the first column always on screen?
date_format	Coerce date columns to this format.
column_width	Either a specific value, NULL, or 'heuristic' which guesses.
...	Set of extra arguments given to openxlsx.

Value

List containing the sheet and workbook written as well as the bottom-right coordinates of the last row/column written to the worksheet.

See Also

[openxlsx] [openxlsx::createWorkbook()] [openxlsx::writeData()] [openxlsx::writeDataTable()] [openxlsx::saveWorkbook()]

Examples

```
## Not run:
xls_coords <- write_xlsx(dataframe, sheet = "hpgl_data", excel = "testing.xlsx")
xls_coords <- write_xlsx(another_df, wb = xls_coords$workbook,
  sheet = "hpgl_data", start_row = xls_coords$end_col)

## End(Not run)
```

write_xlsx,ANY,ANY,ANY,written_xlsx-method

Write an xlsx file given the result of an existing xlsx write.

Description

Write an xlsx file given the result of an existing xlsx write.

Usage

```
## S4 method for signature 'ANY,ANY,ANY,written_xlsx'
write_xlsx(
  data = NULL,
  wb = NULL,
  sheet = NULL,
  excel,
  rownames = TRUE,
  start_row = 1,
  start_col = 1,
  title = NULL,
  number_format = "0.000",
  data_table = TRUE,
  freeze_first_row = TRUE,
  freeze_first_column = TRUE,
```

```

        column_width = "heuristic",
        ...
    )

```

xlsx_insert_png

An attempt to improve the behavior of openxlsx's plot inserter.

Description

The functions provided by openxlsx for adding plots to xlsx files are quite nice, but they can be a little annoying. This attempt to catch some corner cases and potentially save an extra svg-version of each plot inserted.

Usage

```

xlsx_insert_png(
  a_plot,
  wb = NULL,
  sheet = 1,
  width = 6,
  height = 6,
  res = 90,
  plotname = "plot",
  savedir = "saved_plots",
  fancy = FALSE,
  fancy_type = "pdf",
  start_row = 1,
  start_col = 1,
  file_type = "png",
  units = "in",
  ...
)

```

Arguments

a_plot	The plot provided
wb	Workbook to which to write.
sheet	Name or number of the sheet to which to add the plot.
width	Plot width in the sheet.
height	Plot height in the sheet.
res	Resolution of the png image inserted into the sheet.
plotname	Prefix of the pdf file created.
savedir	Directory to which to save pdf copies of the plots.
fancy	Plot fancy plots with the xlsx file?
fancy_type	Plot publication quality images in this format.
start_row	Row on which to place the plot in the sheet.
start_col	Column on which to place the plot in the sheet.

file_type	Currently this only does pngs, but perhaps I will parameterize this.
units	Units for the png plotter.
...	Extra arguments are passed to arglist (Primarily for vennerable plots which are odd)

Value

List containing the result of the tryCatch used to invoke the plot prints.

See Also

[openxlsx::insertImage()]

Examples

```
## Not run:
fun_plot <- plot_pca(stuff)$plot
df <- some_data_frame
wb <- write_xlsx(df, excel = "funkytown.xlsx")$workbook
try_results <- xlsx_insert_png(fun_plot, wb = wb)

## End(Not run)
```

xref_regions	<i>If I were smart I would use an I/GRanges for this.</i>
--------------	---

Description

But I was asked to get the closest feature if it is not inside one. I am not sure how to do that with a ranges. Sadly, I think it will be easier for me to just iterate over the sequence_df and query each feature on that chromosome/scaffold.

Usage

```
xref_regions(
  sequence_df,
  gff,
  bin_width = 600,
  feature_type = "protein_coding_gene",
  feature_start = "start",
  feature_end = "end",
  feature_strand = "strand",
  feature_chr = "seqnames",
  feature_type_column = "type",
  feature_id = "ID",
  feature_name = "description",
  name_type = NULL,
  desc_column = "description"
)
```

Arguments

sequence_df	dataframe of sequence regions of interest.
gff	gff annotations against which to hunt.
bin_width	size of the regions of interest (e.g. the amplicon size)
feature_type	What feature type to hunt for?
feature_start	Column containing the starts.
feature_end	Column containing the ends.
feature_strand	Column containing strand information.
feature_chr	Column containing the chromosome names.
feature_type_column	Column containing the feature types.
feature_id	Column with the IDs (coming from the gff tags).
feature_name	Column with the descriptive name.
name_type	I dont remember, I think this allows one to limit the search to a feature type.
desc_column	Use this column to extract full-text gene descriptions.

ymxb_print

Print a model as $y = mx + b$ just like in grade school!

Description

Because, why not!?

Usage

```
ymxb_print(lm_model, as = "glue")
```

Arguments

lm_model	Model to print from glm/lm/robustbase.
as	Type to return.

Value

a string representation of that model.

Index

- * **datasets**
 - base_size, [32](#)
 - table_style, [461](#)
 - verbose, [474](#)
- .data, [16](#)
- [.expt, [17](#)
- [[,expt,character,ANY-method, [17](#)
- %:::%, [18](#)

- add_binary_states, [18](#)
- add_clonotype_annotations, [19](#)
- add_conditional_nas, [19](#)
- adjuster_expt_svs, [20](#)
- all_adjusters, [21](#)
- all_cprofiler, [22](#)
- all_gprofiler, [23](#)
- all_ontology_searches, [24](#)
- all_pairwise, [25](#)
- annotate_network, [27](#)
- annotate_network_df, [28](#)
- annotation,expt-method, [28](#)
- annotation<-,expt,ANY-method, [29](#)
- assay,ExpressionSet,ANY-method, [29](#)
- assay,expt,ANY-method, [30](#)
- assay<-,ExpressionSet,ANY-method, [30](#)
- assay<-,expt,ANY-method, [31](#)

- backup_file, [31](#)
- base_size, [32](#)
- basic_pairwise, [32](#)
- batch_counts, [33](#)
- binary_pairwise, [35](#)
- bioc_all, [35](#)
- broom, [36](#)

- calculate_aucc, [36](#)
- cbcb_batch, [37](#)
- cbcb_combat, [38](#)
- cbcb_filter_counts, [39](#)
- cheap_tm, [40](#)
- check_circos, [40](#)
- check_includes, [41](#)
- check_metadata_year, [41](#)
- check_plot_scale, [42](#)

- check_xlsx_worksheet, [43](#)
- choose_basic_dataset, [43](#)
- choose_binom_dataset, [44](#)
- choose_dataset, [44](#)
- choose_limma_dataset, [45](#)
- choose_sequence_regions, [46](#)
- circos-class, [46](#)
- circos_arc, [47](#)
- circos_check_chromosomes, [48](#)
- circos_heatmap, [48](#)
- circos_hist, [50](#)
- circos_ideogram, [51](#)
- circos_karyotype, [52](#)
- circos_make, [53](#)
- circos_plus_minus, [53](#)
- circos_prefix, [55](#)
- circos_suffix, [57](#)
- circos_ticks, [57](#)
- circos_tile, [60](#)
- classify_n_times, [61](#)
- classify_variants, [62](#)
- clear_session, [62](#)
- cleavage_histogram, [63](#)
- cluster_trees, [64](#)
- colData,ExpressionSet-method, [65](#)
- colData,expt-method, [65](#)
- colData<-,ExpressionSet,ANY-method, [66](#)
- colData<-,expt,ANY-method, [66](#)
- color_int, [67](#)
- colors,expt-method, [67](#)
- colors,SummarizedExperiment-method, [67](#)
- colors<-,expt-method, [68](#)
- colors<-,SummarizedExperiment-method, [68](#)

- combine_de_tables, [69](#), [146](#), [387](#)
- combine_expts, [71](#)
- combine_extracted_plots, [72](#)
- combine_mapped_table, [73](#)
- combine_single_de_table, [74](#)
- compare_batches, [76](#)
- compare_de_results, [76](#)
- compare_de_tables, [77](#)
- compare_go_searches, [78](#)

- compare_logfc_plots, 79
- compare_pc_sv, 79
- compare_significant_contrasts, 80
- compare_surrogate_estimates, 81
- concatenate_runs, 82
- convert_counts, 83
- convert_gsc_ids, 83
- convert_ids, 84
- cordist, 85
- correlate_de_tables, 86
- count_clonotype_by_cluster, 87
- count_expt_snps, 87
- count_nmer, 88
- count_nmer, character-method, 89
- counts_from_surrogates, 89
- cp_options, 90
- create_expt, 91
- create_partitions, 93
- create_scd, 94
- create_se, 95
- de_venn, 96
- default_proper, 97
- deparse_go_value, 98
- deseq2_pairwise, 101
- deseq_lrt, 99
- deseq_pairwise, 99
- deseq_try_sv, 100
- disjunct_pvalues, 102
- dispatch_count_lines, 103
- dispatch_csv_search, 104
- dispatch_fasta_lengths, 105
- dispatch_filename_search, 105
- dispatch_gc, 106
- dispatch_metadata_extract, 106
- dispatch_metadata_ratio, 107
- dispatch_regex_search, 108
- dispatch_sum_column, 109
- divide_seq, 110
- do_batch, 110
- do_pairwise, 111
- do_topgo, 112
- download_gbk, 113
- download_microbesonline_files, 113
- dream_pairwise, 114
- ebseq_few, 116
- ebseq_pairwise, 116
- ebseq_pairwise_subset, 118
- ebseq_size_factors, 119
- ebseq_two, 120
- edger_pairwise, 121
- enrichResult-class, 122
- exclude_genes_expt, 123
- exprs, expt-method, 123
- exprs, SummarizedExperiment-method, 123
- exprs<-, ExpressionSet, data.frame-method, 124
- exprs<-, expt, ANY-method, 124
- exprs<-, SummarizedExperiment, ANY-method, 124
- expt, 125
- extract_abundant_genes, 126
- extract_coefficient_scatter, 127
- extract_de_plots, 128
- extract_eupath_orthologs, 130
- extract_go, 131
- extract_interesting_goseq, 132
- extract_keepers, 132
- extract_keepers, list, character-method (extract_keepers), 132
- extract_lengths, 134
- extract_linear_regression, 135
- extract_logistic_regression, 136
- extract_mayu_pps_fdr, 137
- extract_metadata, 137
- extract_msraw_data, 138
- extract_mzML_scans, 139
- extract_mzXML_scans, 140
- extract_peprophet_data, 141
- extract_pyprophet_data, 142
- extract_scan_data, 143
- extract_siggenes, 144
- extract_significant_genes, 144
- factor_rsquared, 146
- fData, expt-method, 146
- fData, SummarizedExperiment-method, 147
- fData<-, expt, ANY-method, 147
- fData<-, SummarizedExperiment, ANY-method, 147
- features_greater_than, 148
- features_in_single_condition, 149
- features_less_than, 150
- filter_counts, 150
- filter_scd, 151
- find_subseq_target_temp, 152
- find_working_dataset, 153
- find_working_mart, 153
- flanking_sequence, 154
- gather_cp_genes, 155
- gather_eupath_utrs_padding, 155
- gather_genes_orgdb, 156
- gather_masses, 156
- gather_ontology_genes, 157

- gather_preprocessing_metadata, 158
- gather_utrs_padding, 159
- gather_utrs_txdb, 160
- genefilter_cv_counts, 161
- genefilter_kofa_counts, 161
- genefilter_pofa_counts, 162
- generate_expt_colors, 163
- generate_nn_groups, 163
- genomic_kmer_dist, 164
- genoplot_chromosome, 165
- get_abundant_genes, 165
- get_degrees, 166
- get_expt_colors, 167
- get_formula_factors, 167
- get_formula_factors, formula-method, 168
- get_genesizes, 168
- get_git_commit, 169
- get_group_gsva_means, 169
- get_gsvadb_names, 170
- get_identifier, 170
- get_individual_snps, 171
- get_inter_txdb, 171
- get_kegg_compounds, 171
- get_kegg_genes, 172
- get_kegg_organ, 173
- get_kegg_sub, 173
- get_microbesonline_taxid, 174
- get_msigdb_metadata, 175
- get_pairwise_gene_abundances, 175
- get_plot_columns, 176
- get_proportion_snp_sets, 176
- get_res, 178
- get_sig_genes, 178
- get_sig_gsva_categories, 179
- get_snp_sets, 180
- get_yyyyymm_commit, 181
- getEdgeWeights, 182
- gff2gr, 182
- gff2irange, 183
- ggplotly_url, 184
- ggplt, 184
- godef, 185
- golev, 186
- golevel, 187
- golevel_df, 187
- goont, 188
- gosec, 189
- goseq2enrich, 192
- goseq_msigdb, 189
- goseq_table, 191
- goseq_trees, 192
- gostats2enrich, 195
- gostats_kegg, 193
- gostats_trees, 194
- gosyn, 195
- goterm, 196
- gotest, 197
- gprofiler2enrich, 197
- graph_metrics, 198
- group_mean_cds_length, 200
- guess_factors, 200
- guess_num_surrogates, 201
- guess_organism_keytype, 201
- heatmap.2, 205
- heatmap.3, 202
- hpgl_arescore, 205
- hpgl_cor, 206
- hpgl_dist, 207
- hpgl_filter_counts, 207
- hpgl_GOplot, 208
- hpgl_GroupDensity, 209
- hpgl_log2cpm, 209
- hpgl_norm, 210
- hpgl_padjust, 211
- hpgl_qshrink, 212
- hpgl_qstats, 213
- hpgl_rpkms, 214
- hpgl_voom, 214
- hpgl_voomweighted, 216
- hpgltools, 217
- hpgltools-package (hpgltools), 217
- iDA, 218
- iDA, matrix-method, 218
- ihw_adjust, 219
- import.gff, 183
- import_deseq, 220
- import_edger, 220
- impute_expt, 221
- init_xlsx, 221
- intersect_signatures, 222
- intersect_significant, 223
- iterate_linear_regression, 224
- iterate_logistic_regression, 224
- kegg_vector_to_df, 225
- libsize, 226
- libsize, SummarizedExperiment-method, 226
- libsize<-, 226
- limma_pairwise, 227
- load_annotations, 228

- load_biomart_annotations, 229
- load_biomart_go, 231
- load_biomart_orthologs, 232
- load_genbank_annotations, 234
- load_gff_annotations, 235
- load_gmt_signatures, 236
- load_kegg_annotations, 236
- load_microbesonline_annotations, 237
- load_microbesonline_go, 238
- load_orgdb_annotations, 239
- load_orgdb_go, 240
- load_trinotate_annotations, 241
- load_trinotate_go, 242
- load_uniprot_annotations, 243
- load_uniprot_go, 244
- loadme, 244
- local_get_value, 245

- make_assembly_spec, 245
- make_dnaseq_spec, 246
- make_gsc_from_abundant, 246
- make_gsc_from_ids, 247
- make_gsc_from_pairwise, 249
- make_id2gomap, 250
- make_kegg_df, 250
- make_limma_tables, 251
- make_ntile_factor, 252
- make_pairwise_contrasts, 252
- make_pombe_expt, 254
- make_pombe_se, 254
- make_quartile_factor, 255
- make_rnaseq_spec, 255
- make_simplified_contrast_matrix, 256
- make_tx_gene_map, 256
- make_varpart_tables, 257
- map_keepers, 258
- map_orgdb_ids, 259
- map_species_orgdb, 259
- mean_by_bioreplicate, 260
- mean_by_factor, 260
- median_by_factor, 261
- mesg, 261
- my_identifyAUBlocks, 262
- my_isva, 262
- my_runsims, 263
- mymakeContrasts, 264
- myretrieveKGML, 264

- network_from_matrix, 265
- noiseq_pairwise, 266
- normalize, 267
- normalize, expt-method, 267
- normalize_counts, 268
- normalize_expt, 269
- normalize_se, 271
- normalize_todo, 272
- notes, expt-method, 273

- orgdb_from_ah, 273
- overlap_geneids, 274
- overlap_groups, 274

- parse_msigdb, 275
- parse_msigdb_sqlite, 275
- parse_msigdb_xml, 275
- pattern_count_genome, 276
- pc_fstatistics, 277
- pca_highscores, 277
- pca_information, 278
- pct_all_kegg, 279
- pct_kegg_diff, 280
- pData, expt-method, 281
- pData, SummarizedExperiment-method, 281
- pData<-, expt, ANY-method, 282
- pData<-, SummarizedExperiment, ANY-method, 282
- plot_3d_pca, 283
- plot_batchsv, 283
- plot_bcv, 284
- plot_boxplot, 285
- plot_cleaved, 286
- plot_corheat, 286
- plot_de_pvals, 287
- plot_density, 288
- plot_disheat, 289
- plot_dist_scatter, 290
- plot_enrichresult, 291
- plot_epitrochoid, 292
- plot_essentiality, 292
- plot_exprs_by_chromosome, 293
- plot_forest_from_regression, 294
- plot_fun_venn, 294
- plot_goseq_pval, 295
- plot_gostats_pval, 296
- plot_gprofiler2_pval, 297
- plot_gprofiler_pval, 297
- plot_heatmap, 298
- plot_heatmap, data.frame-method, 299
- plot_heatmap, ExpressionSet-method, 300
- plot_heatmap, expt-method, 300
- plot_heatmap, SummarizedExperiment-method, 301
- plot_heatplus, 301

- plot_histogram, 302
- plot_hypotrochoid, 303
- plot_intensity_mz, 304
- plot_legend, 305
- plot_libsize, 305
- plot_libsize, data.frame, factor, character-method, 306
- plot_libsize, ExpressionSet, ANY, ANY-method, 307
- plot_libsize, expt, ANY, ANY-method, 307
- plot_libsize, SummarizedExperiment, ANY, ANY-method, 308
- plot_libsize_prepost, 309
- plot_linear_scatter, 309
- plot_ly, 311
- plot_ma_condition_de, 311
- plot_ma_de, 313
- plot_meta_sankey, 314
- plot_meta_sankey, expt-method, 315
- plot_metadata_factors, 315
- plot_mutihistogram, 316
- plot_multiplot, 317
- plot_mzxml_boxplot, 317
- plot_nonzero, 318
- plot_nonzero, ExpressionSet-method, 319
- plot_nonzero, expt-method, 320
- plot_nonzero, SummarizedExperiment-method, 320
- plot_num_siggenes, 321
- plot_ontpval, 322
- plot_pairwise_ma, 323
- plot_pca, 323
- plot_pca_genes, 325
- plot_pcfactor, 326
- plot_pclload, 327
- plot_pcs, 328
- plot_pct_kept, 329
- plot_peprophet_data, 330
- plot_pyprophet_counts, 331
- plot_pyprophet_distribution, 332
- plot_pyprophet_points, 333
- plot_pyprophet_protein, 334
- plot_pyprophet_xy, 335
- plot_qq_all, 336
- plot_rmats, 336
- plot_rpm, 337
- plot_sampleBars, 338
- plot_sample_cvheatmap, 339
- plot_sample_heatmap, 340
- plot_sample_heatmap, ExpressionSet-method, 341
- plot_sample_heatmap, expt-method, 341
- plot_sample_heatmap, SummarizedExperiment-method, 342
- plot_sankey_de, 343
- plot_scatter, 343
- plot_seurat_scatter, 344
- plot_significant_bar, 345
- plot_single_qq, 345
- plot_sm, 346
- plot_sm, data.frame-method, 347
- plot_sm, ExpressionSet-method, 348
- plot_sm, expt-method, 348
- plot_sm, SummarizedExperiment-method, 349
- plot_spirograph, 349
- plot_suppa, 350
- plot_svfactor, 351
- plot_topgo_densities, 352
- plot_topgo_pval, 352
- plot_topn, 353
- plot_topn_gsea, 354
- plot_topn_gsea, all_cprofiler-method, 354
- plot_topn_gsea, clusterprofiler_result-method, 354
- plot_tsne, 355
- plot_variance_coefficients, 355
- plot_variance_coefficients, ExpressionSet-method, 356
- plot_variance_coefficients, expt-method, 356
- plot_variance_coefficients, SummarizedExperiment-method, 357
- plot_volcano_condition_de, 357
- plot_volcano_de, 358
- plotly_pca, 360
- pp, 361
- primer_qc, 362
- print.abundant_genes, 363
- print.all_gprofiler, 363
- print.all_pairwise, 364
- print.annotations_biomart, 364
- print.aucc_info, 365
- print.biomart_go, 365
- print.cds_variant_primers, 366
- print.classified_mutations, 366
- print.classifier_evaluation, 367
- print.clusterprofiler_result, 367
- print.combined_de, 368
- print.combined_de_upset, 368
- print.combined_table, 369
- print.correlation_heatmap, 369
- print.cross_table_comparison, 370

- `print.density_plot`, 370
- `print.density_primers`, 371
- `print.deseq_lrt`, 371
- `print.distance_heatmap`, 372
- `print.dream_pairwise`, 372
- `print.expt`, 373
- `print.goseq_result`, 373
- `print.gostats_result`, 374
- `print.gprofiler_result`, 374
- `print.graphed_metrics`, 375
- `print.gsva_result`, 375
- `print.gsva_sig`, 376
- `print.legend_plot`, 376
- `print.libsize_plot`, 376
- `print.linear_scatter`, 377
- `print.mapped_keepers`, 377
- `print.meta_sankey`, 377
- `print.nonzero_plot`, 378
- `print.partitioned_data`, 378
- `print.pattern_counted`, 379
- `print.pca_result`, 379
- `print.prepost_filter`, 380
- `print.preprocessing_metadata`, 380
- `print.proper_estimate`, 381
- `print.reordered_varpart`, 381
- `print.sig_genes`, 382
- `print.sig_intersect`, 382
- `print.snp_intersections`, 383
- `print.snp_sets`, 383
- `print.snps_genes`, 384
- `print.standardmedian_plot`, 384
- `print.topgo_result`, 385
- `print.topn_plot`, 385
- `print.varcoef_plot`, 385
- `print.varpart`, 386
- `print.written_expt`, 386
- `print.written_xlsx`, 386
- `print_ups_downs`, 387
- `proportions_by_factors`, 387
- `prune_network`, 388
- `pull_git_commit`, 388
- `random_ontology`, 389
- `rank_order_scatter`, 389
- `rbind_summary_rows`, 390
- `read_counts`, 391
- `read_metadata`, 392
- `read_snp_columns`, 393
- `read_thermo_xlsx`, 394
- `recolor_points`, 394
- `record_seurat_samples`, 395
- `renderme`, 396
- `replot_varpart_percent`, 396
- `rex`, 397
- `rowData`, *ExpressionSet*-method, 397
- `rowData`, *expt*-method, 397
- `rowData<-`, *expt*-method, 398
- `rowmax_filter_counts`, 398
- `rowMeans`, 398
- `s2s_all_filters`, 399
- `sampleNames`, *expt*-method, 400
- `sampleNames`, *SummarizedExperiment*-method, 400
- `sampleNames<-`, *expt*, *ANY*-method, 401
- `sampleNames<-`, *SummarizedExperiment*, *character*-method, 401
- `sanitize_expt`, 401
- `sanitize_expt_fData`, 402
- `sanitize_expt_pData`, 402
- `sanitize_metadata`, 403
- `sanitize_model`, 404
- `sanitize_number_encoding`, 405
- `sanitize_percent`, 405
- `saveme`, 406
- `score_gsva_likelihooods`, 407
- `score_mhess`, 408
- `self_evaluate_model`, 408
- `semantic_copynumber_extract`, 409
- `semantic_copynumber_filter`, 409
- `semantic_expt_filter`, 410
- `sequence_attributes`, 411
- `sequential_variants`, 412
- `set_expt_batches`, 412
- `set_expt_colors`, 413
- `set_expt_conditions`, 414
- `set_expt_factors`, 415
- `set_expt_genename_column`, 416
- `set_expt_genenames`, 416
- `set_expt_samplenames`, 417
- `shiny`, 417
- `sig_ontologies`, 418
- `significant_barplots`, 418
- `sillydist`, 420
- `simple_clusterprofiler`, 421
- `simple_cp_enricher`, 423
- `simple_cprofiler`, 423
- `simple_dorothea`, 424
- `simple_filter_counts`, 425
- `simple_gadem`, 425
- `simple_goseq`, 426
- `simple_gostats`, 428
- `simple_gprofiler`, 429
- `simple_gprofiler2`, 429
- `simple_gsva`, 431
- `simple_motifRG`, 433

- simple_pathview, 433
- simple_proper, 435
- simple_topgo, 436
- simple_topgo, character-method, 437
- simple_varpart, 438
- simple_xcell, 439
- single_topgo_tree, 440
- skim_seurat_metadata, 440
- slide_de_threshold, 441
- sm, 442
- snp_by_chr, 442
- snp_cds_primers, 443
- snp_density_primers, 444
- snp_subset_genes, 445
- snpsnames2gr, 446
- snps_intersections, 447
- snps_vs_genes, 448
- snps_vs_genes_padded, 449
- state, 450
- state, expt-method, 450
- state, SummarizedExperiment-method, 451
- state<-, 451
- state<-, expt-method, 451
- state<-, SummarizedExperiment-method, 452
- steal_salmon_tx_ids, 452
- subset_expt, 453
- subset_expt, SummarizedExperiment-method, 454
- subset_genes, 454
- subset_ontology_search, 455
- subtract_expt, 456
- sum_eupath_exon_counts, 457
- sum_exon_widths, 457
- summarize_scd_clusters, 458
- summarize_ups_downs, 459
- sv_fstatistics, 459
- sva_modify_pvalues, 460
- svpc_fstats, 461
- synchronize_expt, 461
- table_style, 461
- tar_meta_column, 462
- tar_meta_column, character-method, 462
- tempfile, 463
- test_design_model_rank, 463
- test_design_model_rank, expt-method, 464
- test_model_rank, 464
- tmpmd5file, 465
- tnseq_multi_saturation, 465
- tnseq_saturation, 466
- topDiffGenes, 467
- topgo2enrich, 469
- topgo_tables, 467
- topgo_trees, 468
- transform_counts, 470
- u_plot, 471
- unAsIs, 471
- update.RNAseq.SimOptions.2grp, 471
- upsetr_combined_de, 472
- upsetr_sig, 472
- variance_expt, 473
- varpart_summaries, 474
- verbose, 474
- wgcna_network, 475
- what_happened, 475
- write_basic, 476
- write_cds_entries, 477
- write_classifier_summary, 477
- write_combined_legend, 478
- write_combined_summary, 479
- write_cp_data, 479
- write_de_table, 480
- write_density_primers, 481
- write_deseq, 482
- write_edger, 483
- write_expt, 483
- write_go_xls, 485
- write_goseq_data, 486
- write_gostats_data, 487
- write_gprofiler_data, 488
- write_gsva, 489
- write_limma, 489
- write_sample_design, 490
- write_sig_legend, 490
- write_snps, 490
- write_subset_ontologies, 491
- write_suppa_table, 492
- write_svpc_fstats, 493
- write_topgo_data, 493
- write_xlsx, 481, 494
- write_xlsx, ANY, ANY, ANY, written_xlsx-method, 495
- xlsx_insert_png, 496
- xref_regions, 497
- ymxb_print, 498