

Nodemailer

What is Nodemailer?

- Very simply put, it allows developers to send emails from their Node.js app
- Almost every site uses mailing:
 - Forgot password?
 - The contact section of a webpage
 - Account creation/verify account
- Can you think of more?
- Very simple to use and integrate into an existing app
- Read some docs on Nodemailer [here](#)

TCP/IP Protocols for Mail Delivery

- Sometimes when setting up older smartphones you might have seen SMTP, POP3, and IMAP before
- Each protocol has a specific set of communication rules between computers

SMTP

- Simple Mail Transfer Protocol is used when email is delivered from an email client, such as Outlook Express, to an email server or when email is delivered from one email server to another.
- The definition above is a little confusing, but remember, it is typically used for sending email messages
- SMTP uses port 25

POP3

- Post Office Protocol allows an email client to download an email from an email server
- This protocol is simply for download
- POP3 is typically port 110

IMAP

- Internet Message Access Protocol is designed to let users keep their email on the server
- IMAP requires more disk space on the server and more CPU resources than POP3 - since emails are stored on the server
- IMAP can also download, just like POP3
- Typically uses port 143

Stringing It All Together

- Let's say you want to send an email to jirani@towson.edu
 - You click send in your email client (Let's say it's Outlook Express)
 - Outlook Express delivers the email to your email server using SMTP
 - Your server delivers the email to (potentially mail.towson.edu) using SMTP
 - My email client downloads the email from mail.towson.edu to my laptop using POP3 (or maybe IMAP)

Install Nodemailer

- `npm install nodemailer`
 - Just as we have seen with other packages and libraries
- Then `require('nodemailer')`

To Send Emails You Need A Transporter Object

- From the Nodemailer website:

```
let transporter = nodemailer.createTransport(transport[, defaults])
```



Where

- **transporter** is going to be an object that is able to send mail
- **transport** is the transport configuration object, connection url or a transport plugin instance
- **defaults** is an object that defines default values for mail options

Building the Transporter Object

```
let transporter = nodeMailer.createTransport({  
  host: 'smtp.gmail.com',  
  port: 465,  
  secure: true,  
  auth: {  
    user: 'nodemailertowson@gmail.com',  
    pass: 'xxxxx'  
  }  
});
```

Mail Options as JSON

```
let mailOptions = {  
  // sender address  
  from: '"Jal Irani" <nodemailertowson@gmail.com>',  
  // list of receivers  
  to: 'test@gmail.com',  
  // Subject line  
  subject: 'Test Subject',  
  // plain text body  
  text: 'Hello There',  
  // html body  
  html: '<p> Hello There </p>'  
};
```

Call The Transporter Function

- Calling the transporter function and passing the mailoptions
- BOOM, you've sent an email, so simple

Transporter Function From The Docs

```
transporter.sendMail(data[, callback])
```



Where

- **data** defines the mail content (see [Message Configuration](#) for possible options)
- **callback** is an optional callback function to run once the message is delivered or it failed
 - **err** is the error object if message failed
 - **info** includes the result, the exact format depends on the transport mechanism used
 - **info.messageId** most transports *should* return the final Message-Id value used with this property
 - **info.envelope** includes the envelope object for the message
 - **info.accepted** is an array returned by SMTP transports (includes recipient addresses that were accepted by the server)
 - **info.rejected** is an array returned by SMTP transports (includes recipient addresses that were rejected by the server)
 - **info.pending** is an array returned by Direct SMTP transport. Includes recipient addresses that were temporarily rejected together with the server response
 - **response** is a string returned by SMTP transports and includes the last SMTP response from the server

For More

<https://www.youtube.com/watch?v=nF9g1825mwk>

Start Minute 5:45