TEST REPORT FOR ACCELEROMETER: MODEL NO PG503M9/PG045M0

Job No:
Customer Name:
Serial No:

Test 1: Axial Sensitivity
Linearity test
Frequency: 50Hz

Acceleration from Std A (g)	**Output of Test Accelerometer V mV (Pk-Pk)**	**Sensitivity of Test accelerometer $S = \frac{V}{A}$ (mV/g)**
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		

Mean: mV/g

Frequency test

Frequency (Hz)	**Acceleration from Standard A (g)**	**Output of Test Accelerometer V mV (Pk-Pk)**	**Sensitivity of test accelerometer $S = \frac{V}{A}$ (mV/g)**
50	1		
200	1		
300	1		
50	10		
200	10		
300	10		

Mean: mV/g

Test 2. Post Sealing Axial Sensitivity

Linearity test

Frequency: 50Hz

Acceleration from Std A (g)	**Output of test accelerometer V mV (pk-pk)**	**Sensitivity of test accelerometer $S = \frac{V}{A}$ (mV/g)**
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		

Mean: mV/g

A) CHARGE SENSITIVITY :

B) CAPACITANCE :

C) INSULATION RESISTANCE :

TESTED BY : **APPROVED BY:**

DATE : **HOD-PDN**