

## **ROUTINE TEST RECORD FOR BELT SCALE**

JOB No. : BS-FIELD-ALIAS-TEST  
CAPACITY : 1200 TPH  
BC-05

CUSTOMER NAME:  
CONVEYOR NO:

| BELT SCALE                                                                                          | LOAD CELL                                                                               | SPEED SENSOR            | JUNCTION BOX                |
|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-------------------------|-----------------------------|
| Model No: BS-1200<br>Serial No: BS-SN-999<br>S/W Version:<br><br>REMOTE:<br>Model No:<br>Serial No: | Model No:<br><br>Serial No:<br>1) LC-750-1<br>2) LC-750-2<br>3) LC-750-3<br>4) LC-750-4 | Model No:<br>Serial No: | Model No. :<br>Serial No. : |
|                                                                                                     |                                                                                         | ANGLE SENSOR            | Model No. :<br>Serial No. : |
|                                                                                                     |                                                                                         | Model No:<br>Serial No: | Model No. :<br>Serial No. : |

Check for short between Line & Neutral, Neutral & Earth, Line & Earth :

| SL. No. | Test Performed                         | Specified  | Actual     |
|---------|----------------------------------------|------------|------------|
| 1.      | Input Supply Voltage (+/-10%)          | 230V       | 230V       |
| 2.      | Derived DC Voltages (+/-5%)            | 24V        | 24V        |
| 3.      | Display and Keypad Functionality       | Display OK | Display OK |
| 4.      | Belt Load as specified in G.A. or MPL  | 27.78      | 27.78 Kg/m |
| 5.      | Belt Speed as specified in G.A. or MPL | 2.50       | 2.50 m/s   |
| 6.      | Number of PF Contacts                  | 4          | 4          |
| 7.      | Communication Output (Specify)         | RS-485     | RS-485     |
| 8.      | Analog Output (Specify number)         | 4-20mA     | 4-20mA     |
| 9.      | Wiring, TB and Component Layout        | Wiring OK  | Wiring OK  |

Resolution: L: 0.1 kg/m      S: 0.01 m/s      r: 1 tph      t: 0.1 tonnes

Measurement to be done from 0 to 110% of the Belt Scale capacity.

| Load on Load cell Kg/Mv | Belt load Kg/m | Speed in m/s | Rate in tph | Totalizer in Tones (6 min) | O/p current mA |
|-------------------------|----------------|--------------|-------------|----------------------------|----------------|
| 10                      | 2.5            | 2.50         | 10          | 1.5                        | 2.00           |
| 20                      | 5.0            | 2.50         | 20          | 3.0                        | 4.00           |
| 30                      | 7.5            | 2.50         | 30          | 4.5                        | 6.00           |
| 40                      | 10.0           | 2.50         | 40          | 6.0                        | 8.00           |
| 50                      | 12.5           | 2.50         | 50          | 7.5                        | 10.00          |
| 60                      | 15.0           | 2.50         | 60          | 9.0                        | 12.00          |
| 70                      | 17.5           | 2.50         | 70          | 10.5                       | 14.00          |
| 80                      | 20.0           | 2.50         | 80          | 12.0                       | 16.00          |
| 90                      | 22.5           | 2.50         | 90          | 13.5                       | 18.00          |
| 100                     | 25.0           | 2.50         | 100         | 15.0                       | 20.00          |
| 110                     | 27.5           | 2.50         | 110         | 16.5                       | 22.00          |

Instrument Used: Fluke Multimeter

