

TEST REPORT FOR ACCELEROMETER: MODEL NO PG503M9/PG045M0

Job No:

Customer Name:

Serial No:

Test 1: Axial Sensitivity

Linearity test

Frequency: 50Hz

Acceleration from Std A (g)	Output of Test Accelerometer V mV (Pk-Pk)	Sensitivity of Test accelerometer $S = \frac{V}{A}$ (mV/g)
1	{{cal_in_1}}	{{cal_out_1}}
2	{{cal_in_2}}	{{cal_out_2}}
3	{{cal_in_3}}	{{cal_out_3}}
4	{{cal_in_4}}	{{cal_out_4}}
5	{{cal_in_5}}	{{cal_out_5}}
6	{{cal_in_6}}	{{cal_out_6}}
7	{{cal_in_7}}	{{cal_out_7}}
8	{{cal_in_8}}	{{cal_out_8}}
9	{{cal_in_9}}	{{cal_out_9}}
10	{{cal_in_10}}	{{cal_out_10}}

Mean: **mV/g**

Frequency test

Frequency (Hz)	Acceleration from Standard A (g)	Output of Test Accelerometer V mV (Pk-Pk)	Sensitivity of test accelerometer $S = \frac{V}{A}$ (mV/g)
50	1	{{spec_1}}	{{act_1}}
200	1	{{spec_2}}	{{act_2}}
300	1	{{spec_3}}	{{act_3}}

50	10	{{spec_4}}	{{act_4}}
200	10	{{spec_5}}	{{act_5}}
300	10	{{spec_6}}	{{act_6}}

Mean: mV/g

Test 2. Post Sealing Axial Sensitivity

Linearity test

Frequency: 50Hz

Acceleration from Std A (g)	Output of test accelerometer V mV (pk-pk)	Sensitivity of test accelerometer $S = \frac{V}{A}$ (mV/g)
1	{{cal_in_1}}	{{cal_out_1}}
2	{{cal_in_2}}	{{cal_out_2}}
3	{{cal_in_3}}	{{cal_out_3}}
4	{{cal_in_4}}	{{cal_out_4}}
5	{{cal_in_5}}	{{cal_out_5}}
6	{{cal_in_6}}	{{cal_out_6}}
7	{{cal_in_7}}	{{cal_out_7}}
8	{{cal_in_8}}	{{cal_out_8}}
9	{{cal_in_9}}	{{cal_out_9}}
10	{{cal_in_10}}	{{cal_out_10}}

Mean: mV/g

A) CHARGE SENSITIVITY :

B) CAPACITANCE :

C) INSULATION RESISTANCE :

TESTED BY :

DATE {{cal_in_1}}

APPROVED BY:

 {{cal_out_1}}