

ROUTINE TEST RECORD FOR LOSS IN WEIGHT FEEDER

JOB No. : JOB-LIW-021
Process Plant
CAPACITY : 25 TPH TPH

CUSTOMER: Pharma
MATERIAL: API Powder

LOSS IN WEIGHT FEEDER	CONTROLLER	LOADCELL	JUNCTION BOX
Model No.: {{liw_model}} Serial No.: {{liw_serial}} LOCAL PANEL / PUSH BUTTON: Model No.: {{lp_model}} Serial No.: {{lp_serial}}	Model No.: {{ctrl_model}} Serial No.: {{ctrl_serial}} SW Version: {{ctrl_sw}}	Model No.: {{lc_model}} Serial No.: 1) {{lc_serial_1}} 2) {{lc_serial_2}} 3) {{lc_serial_3}} 4) {{lc_serial_4}}	1) Model: {{jbox_1_model}} / Sl: {{jbox_1_serial}} 2) Model: {{jbox_2_model}} / Sl: {{jbox_2_serial}} 3) Model: {{jbox_3_model}} / Sl: {{jbox_3_serial}}

AC/DC DRIVE Details	Screw		Agitator	
	Motor	Gearbox	Motor	Gearbox
Make: {{drive_make}} Model: {{drive_model}} Serial No.: {{drive_serial}} Capacity: {{drive_kw}} kW	Make: {{screw_motor_make}} Model No.: {{screw_motor_model}} Serial No.: {{screw_motor_serial}} Rating: {{screw_motor_kw}} kW	Make: {{screw_gb_make}} Model No.: {{screw_gb_model}} Serial No.: {{screw_gb_serial}} Ratio: {{screw_gb_ratio}}	Make: {{agit_motor_make}} Model No.: {{agit_motor_model}} Serial No.: {{agit_motor_serial}} Rating: {{agit_motor_kw}} kW	Make: {{agit_gb_make}} Model No.: {{agit_gb_model}} Serial No.: {{agit_gb_serial}} Ratio: {{agit_gb_ratio}}

SL. No.	Test Performed	Specified Values	Actual Values
1.	Input Supply Voltage (+/-10%)	{{spec_1}}	{{act_1}}
2.	SMPS Output (+/-5%)	{{spec_2}}	{{act_2}}
3.	Check for the Display, Touchpad/Keypad functionality	{{spec_3}}	{{act_3}}
4.	Accuracy of the System	{{spec_4}}	{{act_4}}
5.	Bulk Density of the Material	{{spec_5}}	{{act_5}}

Resolution: Load: {{res_load}} kg/m Rate: {{res_rate}} tph Totalizer: {{res_tot}} tonnes

Measurement to be done from 10% to 100% of the capacity.

Span Rate: {{span_rate}} tph / kg/hr

P Value: {{p_val}} I Value: {{i_val}} D Value: {{d_val}}

Feed Forward time: {{feed_fwd_time}}

Rate Interval Time:

{{rate_interval_time}}

Set Rate tph / kg/hr or mV	Achieved rate tph / kg/hr	Error in %	Current output mA
{{set_rate_1}}	{{achieved_rate_1}}	{{pct_err_1}}	{{ma_out_1}}

{{set_rate_2}}	{{achieved_rate_2}}	{{pct_err_2}}	{{ma_out_2}}
{{set_rate_3}}	{{achieved_rate_3}}	{{pct_err_3}}	{{ma_out_3}}
{{set_rate_4}}	{{achieved_rate_4}}	{{pct_err_4}}	{{ma_out_4}}
{{set_rate_5}}	{{achieved_rate_5}}	{{pct_err_5}}	{{ma_out_5}}
{{set_rate_6}}	{{achieved_rate_6}}	{{pct_err_6}}	{{ma_out_6}}

ROUTINE TEST RECORD FOR LOSS IN WEIGHT FEEDER

Functionality Check a) Control Panel Mode b) Local Mode c) Remote Mode	{{func_mode}}
Check Digital Input functions	{{func_di}}
Check the function for PF Contacts from/to Customer	{{func_pf}}
Check for the function Analog Input and outputs	{{func_aio}}
Check Communication Specify the Slave Address, Baud Rate and other Communication Parameters	{{func_comm}}

Remarks: {{remarks}}

Instrument Used: {{instrument_used}}

Tested by: Cal Engineer
Date: 2026-08-22

Approved by: HOD-PDN
(HOD - PDN)