

ROUTINE TEST RECORD FOR WEIGH FEEDER/SCREW FEEDER

JOB No. : JOB-WF-005
Power Station
CAPACITY : 150 TPH TPH

CUSTOMER: Thermal

MATERIAL : {{material}}

WEIGH FEEDER	CONTROLLER	LOADCELL	TACHO / PROXIMITY	JUNCTION BOX
Model No.: {{wf_model}} Serial No.: {{wf_serial}} LOCAL PANEL / PUSH BUTTON: Model No.: {{lp_model}} Serial No.: {{lp_serial}}	Model No.: {{ctrl_model}} Serial No.: {{ctrl_serial}} SW Version: {{ctrl_sw}}	Model No.: {{lc_model}} Serial No.: 1) {{lc_serial_1}} 2) {{lc_serial_2}} 3) {{lc_serial_3}} 4) {{lc_serial_4}}	AC / Pulse Model No.: {{tacho_model}} } Serial No.: {{tacho_serial}}	1) Model: {{jbox_1_model}} / Sl: {{jbox_1_serial}} 2) Model: {{jbox_2_model}} / Sl: {{jbox_2_serial}} 3) Model: {{jbox_3_model}} / Sl: {{jbox_3_serial}}

AC/DC DRIVE Details	Motor	Gearbox	RAL details
Make: {{drive_make}} Model: {{drive_model}} Serial No.: {{drive_serial}} Capacity: {{drive_kw}} kW	Make: {{motor_make}} Model No.: {{motor_model}} Serial No.: {{motor_serial}} Rating: {{motor_kw}} kW	Make: {{gb_make}} Ratio: {{gb_ratio}} Model No.: {{gb_model}} Serial No.: {{gb_serial}}	Make: {{ral_make}} Model No.: {{ral_model}} Serial No.: {{ral_serial}}
NOTE: Check for short between Line & Neutral, Neutral & Earth, Line & Earth before powering ON the system			

SL. No.	Test Performed	Specified Values	Actual Values
1.	Input Supply Voltage (+/-10%)	{{spec_1}}	{{act_1}}
2.	SMPS Output (+/-5%)	{{spec_2}}	{{act_2}}
3.	Check for the Display, Touchpad/Keypad functionality	{{spec_3}}	{{act_3}}
4.	Belt/Screw Load as specified in G.A. or MPL	{{spec_4}}	{{act_4}}
5.	Belt Speed as specified in G.A. or MPL	{{spec_5}}	{{act_5}}

Resolution: Load: {{res_load}} kg/m Speed: {{res_speed}} m/s Rate: {{res_rate}} tph Totalizer:
{{res_tot}} tonnes

I) Measurement to be done from 10 to 100% of the Feeder capacity unless specified in Design Document.

Belt Length /width	{{belt_len_width}} mm
Actual speed (Measured with stop clock)	{{act_speed_measured}} m/s

II). *Speed calibration:* Calibrate the speed by entering the actual belt speed when the Drive output is 100%.

Drive output in %	Calculated Speed m/s	Measured Speed m/s
10	{{calc_speed_10}}	{{meas_speed_10}}
25	{{calc_speed_25}}	{{meas_speed_25}}
50	{{calc_speed_50}}	{{meas_speed_50}}
75	{{calc_speed_75}}	{{meas_speed_75}}

100	{{calc_speed_100}}	{{meas_speed_100}}
-----	--------------------	--------------------

ROUTINE TEST RECORD FOR WEIGH FEEDER/SCREW FEEDER

III). Load Calibration: Weight of Calibration Chain: {{cal_chain_wt}} Kg/m

IV). VOLUMETRIC MODE: {{vol_mode}}

V). GRAVIMETRIC MODE: Operating Range: {{grav_mode}}

Set rate tph		Actual rate tph Min Max Avg			Load in Kg/m	Totalizer (6 min)		% Error	Current O/p mA
						Act.	Meas.		
10%	{{set_tph_10}}	{{act_avg_10}}			{{load_kgm_10}}	{{tot_act_10}}	{{tot_meas_10}}	{{pct_err_10}}	{{ma_out_10}}
25%	{{set_tph_25}}	{{act_avg_25}}			{{load_kgm_25}}	{{tot_act_25}}	{{tot_meas_25}}	{{pct_err_25}}	{{ma_out_25}}
50%	{{set_tph_50}}	{{act_avg_50}}			{{load_kgm_50}}	{{tot_act_50}}	{{tot_meas_50}}	{{pct_err_50}}	{{ma_out_50}}
75%	{{set_tph_75}}	{{act_avg_75}}			{{load_kgm_75}}	{{tot_act_75}}	{{tot_meas_75}}	{{pct_err_75}}	{{ma_out_75}}
100%	{{set_tph_100}}	{{act_avg_100}}			{{load_kgm_100}}	{{tot_act_100}}	{{tot_meas_100}}	{{pct_err_100}}	{{ma_out_100}}

Functionality Check a) Control Panel Mode b) Local Mode c) Remote Mode	{{func_mode}}
Check Digital Input functions	{{func_di}}
Check the function for PF Contacts from/to Customer	{{func_pf}}
Check for the function Analog Input and outputs	{{func_aio}}
Check Communication Specify the Slave Address, Baud Rate and other Communication Parameters	{{func_comm}}

Remarks: {{remarks}}

Instrument Used: {{instrument_used}}

Tested by: Lead Inspector
Date: 2026-08-22

Approved by: HOD-PDN
(HOD - PDN)