

Package ‘hiR’

January 31, 2013

Title Harmony Institute’s toolkit for R

Description Various helper tools for R maintained by HI data lab

Version 0.2

Author HI Data Lab <info@harmony-institute.org>

Maintainer Burton Dewilde <burton@harmony-institute.org>

License MIT

Depends R (>= 2.15.2), tm, lattice, makeR, classInt, scales, RColorBrewer, plyr, Matrix, glm-net, Rstem, lda, rjson, RCurl, stringr, chron, grid

Suggests maps, XML, sentiment

LazyLoad yes

Collate

‘classify_sentiment.R’ ‘gen_var_names.R’ ‘geocode.R’ ‘get_klout_scores.R’ ‘lda.R’ ‘leading_zeros.R’ ‘word_stemmer.R’

R topics documented:

calendar	2
classify_sentiment	2
color_assign	3
csv_stack	4
gen_ctm_data	5
gen_var_names	5
geocode	6
get_klout_scores	7
lda	8
leading_zeros	9
pretty_coefs	9
word_stemmer	10

Index	11
--------------	-----------

calendar	<i>Create a calendar heat map with a set number of breaks</i>
----------	---

Description

This function creates a calendar heat map with custom break values, allowing for comparisons between multiple time series.

Usage

```
calendar(dates, values, breaks, ncolors = 9,
         pal = "Spectral", varname = "Values",
         date_form = "%Y-%m-%d")
```

Arguments

dates	Vector of dates.
values	Numeric vector of values per day.
breaks	Vector specifying values to breaks colors at (optional).
ncolors	Number of colors to use.
pal	Palette from RColorBrewer
varname	Name of variable for plot title.
date_form	Date format. Defaults to "%Y-%m-%d"

Examples

```
date <- seq(from=as.Date("2010-01-01"),
           to=as.Date("2012-12-31"),
           by='day')
value <- rnorm(length(date), mean = 10, sd=1)
library("hiR")
calendar(dates=date, values=value)
```

classify_sentiment	<i>Classify the sentiment of text documents</i>
--------------------	---

Description

This function takes a character vector of documents as an input and returns probabilistic sentiment classification. This function is a slight adjustment to "classify_polarity" in the "sentiment" package. **WARNING:** This still needs to be tweaked to return meaningful classifications. Use the pos/neg ratio as a better metric for now.

Usage

```
classify_sentiment(text, algorithm = "bayes",
                  pstrong = 1, pweak = 0.75, prior = 1,
                  neutral_range = c(1, 1.5), verbose = FALSE, ...)
```

Arguments

text	A character vector of text blobs.
algorithm	A string indicating whether to use the naive bayes algorithm or a simple voter algorithm.
pstrong	A numeric specifying the probability that a strongly subjective term appears in the given text.
pweak	A numeric specifying the probability that a weakly subjective term appears in the given text.
prior	A numeric specifying the prior probability to use for the naive Bayes classifier.
neutral_range	# A numeric vector specifying the low and high value of pos/neg ratio to classify as "neutral."
verbose	A logical specifying whether to print detailed output regarding the classification process.
...	Additional arguments to pass to create_matrix in the sentiment package

Examples

```
documents <- c("I am very happy, excited, and optimistic.",
               "I am very scared, annoyed, and irritated.",
               "Iraq's political crisis entered its second
               week one step closer to the potential
               dissolution of the government, with a call
               for elections by a vital coalition partner
               and a suicide attack that extended the spate
               of violence that has followed the withdrawal
               of U.S. troops.",
               "With nightfall approaching, Los Angeles
               authorities are urging residents to keep their
               outdoor lights on as police and fire officials
               try to catch the person or people responsible
               for nearly 40 arson fires in the last three days.")

library("hiR")
classify_sentiment(documents, algorithm="bayes", verbose=TRUE)
```

color_assign

Partition a numeric vector into a set of breaks and assign colors

Description

This function takes an input numeric vector and partitions it into a set number of breaks. It then assigns a color to each break via RColorBrewer

Usage

```
color_assign(var, n = 9, style = "jenks",
             pal = "Spectral", rev = FALSE, na_color = "#787878",
             na_omit = FALSE, alph = 1, include_var = TRUE)
```

Arguments

var	Numeric vector to partition. Alternatively, if "style" argument is a clustering algorithm, you can supply a matrix.
n	Number of colors / breaks
style	Breaks algorithm from "classIntervals" in the "classInt" package. These include: "fixed", "sd", "equal", "pretty", "quantile", "kmeans", "hclust", "bclust", "fisher", or "jenks"
pal	Palette from RColorBrewer. Alternatively a character vector of hexcodes representing your palette. If your variable is continuous, these colors should be ramped upwards or downwards.
rev	Logical; should the function reverse the ordering of the palette
na_color	Hexcode to assign NA values
na_omit	Logical; should the function remove NAs. 'na_color' will be irrelevant if this is TRUE.
alph	Opacity level (0=transparent, 1=opaque)
include_var	Logical; should the function return the input variable(s)

Value

A data.frame with the variable, break assignments, and color assignments

Examples

```
var <- rnorm(1000)
library("hiR")
var_cols <- color_assign(var)
par(family="HersheySans")
plot(var_cols$var,
      pch=20,
      col=var_cols$col,
      xlab="index",
      ylab="value",
      main="color_assign example")
```

 csv_stack

Stack up a directory of csvs or list of data.frames

Description

This functions makes data stacks

Usage

```
csv_stack(csvs = NULL, pattern = NULL)
```

Arguments

csvs a directory full of csv files or a list of data.frames

Value

A data.frame with inconsistent columns filled in

gen_ctm_data	<i>output .dat document term format for ctm algorithm</i>
--------------	---

Description

output .dat document term format for ctm algorithm

Usage

```
gen_ctm_data(corpus, file = "ctm.dat")
```

Arguments

corpus a corpus / character vector of text documents

Examples

```
#gen_ctm_data(corpus, "ctm.dat")
```

gen_var_names	<i>Automatically generate variable names for subsetted dataframes.</i>
---------------	--

Description

Say you were building a dataset and wanted to automatically generate variable names by some pattern. For instance, you might want to do this with population counts within 100 census tracts by race IE: `tracts <- paste("c", rep(1:100), sep=""); race - c("black", "white", "hispanic");` In this case you would want to generate 300 unique variable names This function will generate these variable names automatically when provided with: 1. the "roots" - in the example above, the unique census tracts 2. the "vars" - in the example above, the unique races

Usage

```
gen_var_names(roots, vars, delim = "_")
```

Arguments

roots A set of names that serve as the root variable
vars A set of names that represent the subsets of each root variable
delim Character to separate roots and vars by. Defaults to "_"

Examples

```
tracts <- paste("ct", rep(1:100), sep="")
race <- c("black", "white", "hispanic")
library("hiR")
gen_var_names(roots=tracts, vars=race)
```

geocode

*Geocode strings of text via the Google API***Description**

The function hits the google maps API and tries to geocode strings of text

Usage

```
geocode(uid_location, service = "google",
        yahoo_appid = "")
```

Arguments

uid_location	A data.frame with one column named "uid" - a vector unique ids and another column named "location" - a vector of strings of text to geocode
service	either yahoo or google, you can programmatically alternate to avoid rate limits
yahoo_appid	Your yahoo_appid from https://developer.apps.yahoo.com/dashboard/createKey.html

Value

A data.frame with the uid, location, lat, lng, and type indicating the geocoding precision

Examples

```
# Generate the data
uid <- paste0("city", 1:5)
location <- c("Boston, MA",
              "New York, NY",
              "Washington D.C.",
              "Philadelphia, PA",
              "Baltimore, MD"
            )
uid_location <- data.frame(uid, location)

# Run geocoding function
library("plyr")
library("hiR")
geocoded_data <- ddply(uid_location, .(uid), geocode)
summary(geocoded_data)

# Plot results
#params
par(family="HersheySans")

#map
library("maps")
regions <- c("new hampshire",
             "massachusetts",
             "rhode island",
             "penn",
             "connecticut",
             "washington d.c",
```

```

        "new york",
        "new jersey",
        "delaware",
        "maryland"
    )
map("state", region=regions, col="grey80")

#points + labels
points(geocoded_data$lng,
       geocoded_data$lat,
       pch=20,
       cex=2,
       col="steelblue")
text(geocoded_data$lng-0.5,
     geocoded_data$lat+0.3,
     labels=geocoded_data$location,
     cex=1,
     col="darkred")
title("Major Cities on the Eastern Seaboard")

```

get_klout_scores

*Retrieve klout scores for a vector of twitter handles***Description**

Retrieve klout scores for a vector of twitter handles

Usage

```
get_klout_scores/twitter_handles, api_key,
na_omit = TRUE)
```

Arguments

twitter_handles	A character vector of twitter handles - with or without "@"
api_key	Your api key from http://klout.com/s/developers/
na_omit	Logical; should the function remove handles that don't have klout scores

Value

A data.frame of twitter handles, klout ids, and klout scores

Examples

```

# simply get a couple of klout scores
# you can use my apikey for now but it will eventually break
library("hiR")
get_klout_scores/twitter_handles = c("brianabelson", "hinstitute"), api_key="8yng356gnjg37cvn4esbtewy")
# see inst/docs/get_klout_scores_ex.R for a more detailed use case

```

lda	<i>An easy-to-use and comprehensive implementation of topic modeling in R</i>
-----	---

Description

lda is a wrapper for `lda.collapsed.gibbs.sampler` in the "lda" package. It fits topic models using latent dirichlet allocation. It provides arguments for cleaning the input text and tuning the parameters of the model. It also returns a lot of useful information about the topics/documents in a format that you can easily join back to your original data. This allows you to easily model outcomes based on the distribution of topics within a collection of texts.

Usage

```
lda(text, ids = NULL, lower_case = TRUE,
    remove_stop_words = TRUE, stop_words_to_add = NULL,
    remove_numbers = TRUE, remove_punctuation = TRUE,
    remove_non_ascii = TRUE, stem_words = FALSE,
    char_range = c(3, 50), min_word_count = 5,
    n_topics = 10, n_topic_words = 20, n_iter = 1000,
    burnin = 100, alpha = 0.1, eta = 0.1,
    n_assignments = 2, doc_stats = TRUE)
```

Arguments

text	A character vector of text documents
ids	A vector of ids (to allow joining results to other variables). default is 1:length(text)
lower_case	Logical; should the function make the text lower case?
remove_stop_words	Logical; should the function remove stop words? NOTE: this will also make the text lower case
stop_words_to_add	A character vector of stopwords to add
remove_numbers	Logical; should the function remove numbers?
remove_punctuation	Logical; should the function remove punctuation?
remove_non_ascii	Logical; should the function remove non-ASCII characters?
stem_words	Logical; should the function stem the words?
char_range	A numeric vector of length two with low and high value of characters per word (inclusive!) - e.g: c(3,50)
min_word_count	The number of times a word/feature must occur in a text to be considered
n_topics	The number of topics to fit
n_topic_words	The number of top topic words to return
n_iter	The number of iterations
burnin	The number of initial iterations to ignore. the function adds burnin to n_iter
alpha	The scalar value of the dirichlet hyperparameter for topic proportions
eta	The scalar value of the dirichlet hyperparameter for topic multinomials
n_assignments	The number of assignments to return (returned as topic_a, topic_b etc.)

Value

A list of: \$topic_words: A table of the top n words per topic, n = n_topic_words
 \$document_stats: A data.frame of stats about topics in each document
 \$topic_words: A table of top topic words in each document

 leading_zeros

Automatically add leading zeros to id columns

Description

This function quickly and painlessly adds leading zeros to id variables

Usage

```
leading_zeros(ids = NULL, n_digits = NULL)
```

Arguments

ids	A vector of ids to add zeros to.
n_digits	The desired length of each id. if NULL, this will be the maximum number of characters of a single id.

Examples

```
ids <- c("1", "12470192401" , "30479103", "42u1p9241", "532", "3153")
library("hiR")
leading_zeros(ids)
```

 pretty_coefs

Create Pretty Coefficient Plots

Description

Create Pretty Coefficient Plots

Usage

```
pretty_coefs(m, title = "", pval = 0.05, null = 0)
```

Arguments

m	A model from glm, lm, etc.
title	The title for the plot
pval	the p-value at which to color significant coefficients blue
null	the value at which a coefficient is null (0 or 1, usually)

Value

A pretty coefficient plot

Examples

```
y = rnorm(100)
x1 = rnorm(100)
x2 = rnorm(100)
x3 = rnorm(100)
x4 = rnorm(100)
m <- glm(y ~ x1 + x2 + x3 + x4)
pretty_coefs(m)
```

word_stemmer

Stem each feature in a blob of text

Description

A vecotrizable wrapper for wordStem in the Rstem package

Usage

```
word_stemmer(document)
```

Arguments

document A blob of text

Examples

```
documents <- c("running runner run", "jumping jump jumped")
library("tm")
corpus <- Corpus(VectorSource(documents))
library("hiR")
as.character(tm_map(corpus, word_stemmer))
```

Index

calendar, [2](#)
classify_sentiment, [2](#)
color_assign, [3](#)
csv_stack, [4](#)

gen_ctm_data, [5](#)
gen_var_names, [5](#)
geocode, [6](#)
get_klout_scores, [7](#)

lda, [8](#)
leading_zeros, [9](#)

pretty_coefs, [9](#)

word_stemmer, [10](#)