

WEEK 3 UNIT 2


DEFINING A RESPONSIVE TABLE

Please perform the exercises below in your app project as shown in the video.

Table of Contents

1	Responsive Table Behavior	2
2	Update the Products Table and Header	3
3	Add A Column for the Supplier	6
4	Add A Column for the Supplier Web Address	8
5	Testing the Responsiveness with Chrome	10
6	Testing the Responsiveness with SAP Web IDE	13

Preview



Manage Products


Products (115)

Product	Supplier	Web Address	Price
HT-1000 Notebook Basic 15	SAP	http://www.sap.com	957.00 EUR >
HT-1001 Notebook Basic 17	Becker Berlin	http://www.beckerberlin.de	1249.00 EUR >
HT-1002 Notebook Basic 18	DelBont Industries	http://www.delbont.com	1570.00 USD >
HT-1003 Notebook Basic 19	Talpa	http://www.talpa-hannover.de	1650.00 EUR >
HT-1007 ITelO Vault	Panorama Studios	http://www.panorama-studios.biz	299.00 USD >
HT-1010 Notebook Professional 15	TECUM	http://www.tecum-ag.de	1999.00 EUR >
HT-1011 Notebook Professional 17	Asia High tech	http://www.asia-ht.com	229900.00 JPY >
HT-1020 ITelO Vault Net	Laurent	http://www.laurent-paris.com	459.00 EUR >
HT-1021 ITelO Vault SAT	AVANTEL	http://www.avantel.com	149.00 MXN >
HT-1022 Comfort Easy	Telecomunicaciones Star	http://www.telecomunicacionesstar.com	1679.00 ARS >
HT-1023 Comfort Senior	Pear Computing Services	http://www.pear-computing.com	512.00 USD >
HT-1030 Ergo Screen E-I	Alpine Systems	http://www.alp-systems.at	230.00 EUR >

Figure 1 - Preview of the app after doing this unit's exercises

1 RESPONSIVE TABLE BEHAVIOR


At first you will enhance the display of products with the product name and include additional information about the product's supplier:



Product	Supplier	Web Address	Price
HT-1000 Notebook Basic 15	SAP	http://www.sap.com	956.00 EUR >
HT-1001 Notebook Basic 17	Becker Berlin	http://www.beckerberlin.de	1249.00 EUR >
HT-1002 Notebook Basic 18	DelBont Industries	http://www.delbont.com	1570.00 USD >

Figure 2 – The table on a desktop device

You will test the responsive behaviour on devices with small screens by simulating this environment in Chrome and Web IDE:




Product	Price
HT-1000 Notebook Basic 15 Supplier: SAP	956.00 EUR >
HT-1001 Notebook Basic 17 Supplier: Becker Berlin	1249.00 EUR >
HT-1002 Notebook Basic 18 Supplier: DelBont Industries	1570.00 USD >

Figure 3 – The table on a phone device in portrait mode

2 UPDATE THE PRODUCTS TABLE AND HEADER

At first you improve the generated code for properly displaying products and their name.

Preview




Manage Products	
Products (115)	Suchen
Product	Price
HT-1000 Notebook Basic 15	956.00 EUR >
HT-1001 Notebook Basic 17	1249.00 EUR >
HT-1002 Notebook Basic 18	1570.00 USD >

Figure 4 – Adjustments on the worklist view

Worklist View

- Update the table title
- Update the first column title
- Show in addition the product's name



Product	
HT-1000	956.00 EUR
Notebook Basic 15	

Figure 5 – Adjustments on the object view

Object View

- Update the page title
- Show the name as attribute

webapp/view/Worklist.view.xml

```

<Table ...>
  ...
  <items>
    <ColumnListItem
      type="Navigation"
      press="onPress">
      <cells>
        <ObjectIdentifier
          title="{ProductID}"
          text="{Name}"/>
        <ObjectNumber
          number="{
            path: 'Price',
            formatter: '.formatter.numberUnit'
          }"
          unit="{CurrencyCode}"/>
      </cells>
    </ColumnListItem>
  </items>
</Table>

```

Find the `ColumnListItem` which represents a row of the table. The `cells` aggregation contains the controls that display the content for the different columns. Extend the first control – an `ObjectIdentifier` – with a text that is bound to the product name.

webapp/view/Object.view.xml

```

<ObjectHeader
  id="objectHeader"
  title="{ProductID}"
  number="{
    path: 'Price',
    formatter: '.formatter.numberUnit'
  }"
  numberUnit="{CurrencyCode}">
  <attributes>
    <ObjectAttribute text="{Name}"/>
  </attributes>
</ObjectHeader>

```

Add an `ObjectAttribute` control to the `attributes` aggregation of the `ObjectHeader` and bind it to the `Name` property.

webapp/i18n/i18n.properties

```

...

#~~~ Worklist View ~~~~~

#XTIT: Table view title
worklistViewTitle=Manage Products

#XTIT: Table view title
worklistTableTitle=Products

```

```
#XTOL: Tooltip for the search field
worklistSearchTooltip=Enter a product name or a part of it.

#XBLI: text for a table with no data with filter or search
worklistNoDataWithSearchText=No matching products found

#XTIT: Table view title with placeholder for the number of items
worklistTableTitleCount=Products ({0})

#XTIT: The title of the column containing the ProductID of ProductSet
tableNameColumnTitle=Product

#XTIT: The title of the column containing the Price and the unit of
measure
tableUnitNumberColumnTitle=Price

#XBLI: text for a table with no data
tableNoDataText=No products are currently available

...

#~~~ Object View ~~~~~

#XTIT: Object view title
objectTitle=Product

...

#~~~ Not Found View ~~~~~

#YMSG: The ProductSet not found text is displayed when there is no
ProductSet with this id
noObjectFoundText=This Product is not available


#YMSG: The ProductSet not available text is displayed when there is no
data when starting the app
noObjectsAvailableText=No Products are currently available
```

Update the existing i18n properties that have been generated by the template based on the service metadata with these more readable values.

3 ADD A COLUMN FOR THE SUPPLIER

Add a new column showing the product's supplier.

Preview



Product	Supplier	Price
HT-1000 Notebook Basic 15	SAP	956.00 EUR >
HT-1001 Notebook Basic 17	Becker Berlin	1249.00 EUR >
HT-1002 Notebook Basic 18	DelBont Industries	1570.00 USD >

Figure 6 – Adding a “Supplier” column

webapp/view/Worklist.view.xml

```

<Table ... >
  ...
  <columns>
    <Column id="nameColumn">
      <Text text="{i18n>tableNameColumnTitle}" id="..." />
    </Column>
    <Column
      id="supplierNameColumn"
      demandPopin="true"
      minScreenWidth="Tablet">
      <Text text="{i18n>tableSupplierColumnTitle}" />
    </Column>
    <Column id="unitNumberColumn" hAlign="End">
      <Text text="{i18n>tableUnitNumberColumnTitle}" id="..." />
    </Column>
  </columns>

  <items>
    <ColumnListItem
      type="Navigation"
      press="onPress">
      <cells>
        <ObjectIdentifier
          title="{ProductID}"
          text="{Name}" />
        <Text text="{SupplierName}" />
        <ObjectNumber
          number="{
            path: 'Price',
            formatter: '.formatter.numberUnit'
          }"
          unit="{CurrencyCode}" />
      </cells>
    </ColumnListItem>
  </items>
</Table>

```

- Add a new `Column` between the existing two columns.
 - The column control has an aggregation to the `Text` control that is used to render the column header.
 - Setting the `minScreenWidth` to `Tablet` indicates that the column is only shown on tablets or larger screen.
 - `demandPopin` will show the cell in-place if the column is not shown.
 - Add a new `Text` control between the existing two cells and bind it to the `SupplierName`.

webapp/i18n/ i18n.properties

```
...  
  
#~~~ Worklist View ~~~~~  
  
...  
  
#XTIT: The title of the column containing the ProductID of ProductSet  
tableNameColumnTitle=Product  
  
#XTIT: The title of the column containing the product's supplier name  
tableSupplierColumnTitle=Supplier  
  
...
```

Add a new `i18n` property for the supplier column title.

4 ADD A COLUMN FOR THE SUPPLIER WEB ADDRESS

You now add a second column that displays the supplier's web address as a link.

Preview

Product	Supplier	Web Address	Price
HT-1000 Notebook Basic 15	SAP	http://www.sap.com	956.00 EUR >
HT-1001 Notebook Basic 17	Becker Berlin	http://www.beckerberlin.de	1249.00 EUR >
HT-1002 Notebook Basic 18	DelBont Industries	http://www.delbont.com	1570.00 USD >

Figure 7 –Adding a “Web Address” Column

webapp/view/Worklist.view.xml

```
<Table ... >
  ...
  <columns>
    <Column id="nameColumn">
      <Text text="{i18n>tableNameColumnTitle}" id="..."/>
    </Column>
    <Column
      id="supplierNameColumn"
      demandPopin="true"
      minScreenWidth="Small">
      <Text text="{i18n>tableSupplierColumnTitle}"/>
    </Column>
    <Column id="webAddressColumn"
      demandPopin="false"
      minScreenWidth="Tablet">
      <Text text="{i18n>tableSupplierWebAddressColumnTitle}"/>
    </Column>
    <Column id="unitNumberColumn" hAlign="End">
      <Text text="{i18n>tableUnitNumberColumnTitle}" id="..."/>
    </Column>
  </columns>

  <items>
    <ColumnListItem
      type="Navigation"
      press="onPress">
      <cells>
        <ObjectIdentifier
          title="{ProductID}"
          text="{Name}"/>
        <Text text="{SupplierName}"/>
        <Link
          text="{ToSupplier/WebAddress}"
          href="{ToSupplier/WebAddress}"
          target="_blank"/>
        <ObjectNumber
          number="{
            path: 'Price',
            formatter: '.formatter.numberUnit'
          }"
        </ObjectNumber>
      </cells>
    </ColumnListItem>
  </items>
</Table>
```



```

        unit="{CurrencyCode}"/>
    </cells>
</ColumnListItem>
</items>
</Table>

```

- Add the additional Column to the columns aggregation of the Table
- Add a Link control to the cells aggregation of the ObjectListItem. Bind the text and href to the path ToSupplier/WebAddress. The ToSupplier/ prefix represents a navigation to a different object in the OData metamodel.

```

<Table
  id="table"
  width="auto"
  class="sapUiResponsiveMargin"
  items="{
    path: '/ProductSet',
    sorter: {
      path: 'ProductID',
      descending: false
    },
    parameters: {
      expand: 'ToSupplier'
    }
  }"
  noDataText="{worklistView>/tableNoDataText}"
  ... >

```

We extend the items aggregation of the table with an expand parameter for the ToSupplier navigation property. With this the supplier data will be already included in the first service request for the products and no additional requests are required.

webapp/i18n/i18n.properties

```

...

#~~~ Worklist View ~~~~~

...

#XTIT: The title of the column containing the ProductID of ProductSet
tableNameColumnTitle=Product

#XTIT: The title of the column containing the product's supplier name
tableSupplierColumnTitle=Supplier

#XTIT: The title of the column containing the product's supplier web
address
tableSupplierWebAddressColumnTitle=Web Address



...

```




Add a new property for the supplier web address column title.



5 TESTING THE RESPONSIVENESS WITH CHROME

The responsiveness of `sap.m.Table` can most easily be tested by changing the width of the browser window:

Explanation	Screenshot
<ol style="list-style-type: none"> Run the application in the Chrome browser and maximize the window. Observe that all columns are shown and that the UI does not grow beyond a certain width. The rest of the space is filled with a darker background color. 	
<ol style="list-style-type: none"> Gradually reduce the width of the browser window. Observe that at a certain threshold 2 columns disappear. The Supplier is now shown as a “popin”. The Web Address is hidden. 	





Other controls than `sap.m.Table` and potentially your application logic might react on other factors than the screen size. Thus for proper testing you should really simulate the device with the Chrome developer tools:




Explanation	Screenshot
<p>5. Run the application in the Chrome browser and press the F12 key to open the developer tools</p> <p>6. Press the small icon in the left upper corner of the toolbar to Toggle the device mode.</p>	
<p>7. Set the device to Apple iPhone 5</p>	
<p>8. Observe that the Supplier column is shown in each row as a “popin”.</p> <p>9. Observe that the Web Address column is hidden.</p>	

Explanation	Screenshot
10. Refresh the application's browser tab.	
11. End the device mode by pressing on the Toggle device model icon again.	

6 TESTING THE RESPONSIVENESS WITH SAP WEB IDE

We will test the responsiveness of our application with SAP Web IDE's testing tool that can simulate different screen resolutions and even the device orientation.

Explanation	Screenshot
12. Select the folder ManageProducts	 A screenshot of the SAP Web IDE interface. The Explorer view on the left shows a folder named 'ManageProducts' which is highlighted with a blue selection bar. A red rectangle is drawn around this folder name.
13. Open the Run menu 14. Choose Run Configurations ...	 A screenshot of the 'Run' menu in SAP Web IDE. The 'Run' menu item is highlighted with a red rectangle. The dropdown menu is open, and 'Run Configurations ...' is highlighted with a red rectangle.
15. Select the configuration App	 A screenshot of the 'Run Configurations for project Manag' dialog. Under the 'Web Application' category, the 'App' configuration is highlighted with a blue selection bar and a red rectangle.
16. In the General tab set the Preview Mode to With Frame	 A screenshot of the 'General' tab in the 'Run Configurations' dialog. Under the 'Preview Mode' section, the 'With Frame' option is selected, indicated by a blue button and a red rectangle.

Explanation	Screenshot
17. Press the Save and Run button	
18. Check that “Small” screen size is selected at the top of the page	
19. Observe that the Supplier column is shown in each row as a “popin”. 20. Observe that the Web Address column is hidden.	
Optional: 21. Click on the QR-Code icon in the right upper corner. 22. Scan the shown QR code with your smart phone and run the application with a web browser	

Coding Samples

Any software coding or code lines/strings (“Code”) provided in this documentation are only examples and are not intended for use in a productive system environment. The Code is only intended to better explain and visualize the syntax and phrasing rules for certain SAP coding. SAP does not warrant the correctness or completeness of the Code provided herein and SAP shall not be liable for errors or damages caused by use of the Code, except where such damages were caused by SAP with intent or with gross negligence.