



Exercises session 6

Reductions

1 Definitions

Definition 1.1 (Computable functions) A function $f : \Sigma^* \rightarrow \Sigma^*$ is a **polynomial time computable function** if some polynomial time Turing machine exists that halts with just $f(w)$ on its tape, when started with the input $w \in \Sigma^*$.

Definition 1.2 (Karp reductions) Language A is **polynomial time Karp reducible** to language B , written $A \leq_P B$, if there is a polynomial time computable function $f : \Sigma^* \rightarrow \Sigma^*$ such that:

$$w \in A \iff f(w) \in B.$$

2 Session exercises

1. Sudoku and Latin Square

A **Sudoku** puzzle is a $n^2 \times n^2$ grid that is partially filled with integers, where each integer from 1 to n^2 must appear exactly once in every row, every column, and every $n \times n$ sub-grid. A **Latin Square** of order n is an $n \times n$ grid filled with n different symbols such that each symbol appears exactly once in each row and exactly once in each column. A Latin Square is a special case of a Sudoku grid, where the only constraints are row and column uniqueness, without the additional sub-grid constraints found in Sudoku.

Task: Reduce Latin Square to Sudoku.

2. Course scheduling

Consider a university that needs to schedule courses for a set of students. The goal is to assign each course to a time slot, while ensuring that no student has more than one course scheduled in the same time slot.

Task: Show how to reduce this problem to a graph colouring problem.

3. Word Ladder

A word ladder involves transforming one word into another by changing one letter at a time, where each intermediate word must also be a valid word in the dictionary. For example, transforming "cat" to "dog" could proceed as follows: "cat" $\rightarrow$ "cot" $\rightarrow$ "dot" $\rightarrow$ "dog".

Task: Show that this problem can be reduced to the path finding problem on a graph.

Describe the reduction and how finding the shortest path could solve the word ladder problem.

4. **Debate tournament**

A university is organizing a debate tournament with teams of three debaters. Each debater has a list of topics they refuse to argue. The goal is to assign debaters to teams so that every team can argue all the topics in the competition. Specifically, each team should have at least one debater who is willing to argue each of the required topics.

Task: Prove that this problem of forming valid debate teams can be reduced to a SAT problem. Show how to encode the debater-topic refusal constraints as a Boolean formula, where satisfying the formula corresponds to finding valid teams for the debate.