Marconi Infrastructure Operations Agent

Technical Reference and Evaluation Report

August 13, 2026

An LLM-driven operations agent that investigates infrastructure incidents, proposes human-gated remediations, and is measured by a purpose-built evaluation harness spanning correctness, safety, and cost.

Contents

1 Overview **3**

2 Purpose and Boundaries **3**
2.1 What the agent does . . . 3
2.2 What the agent explicitly does not do . . . 4

3 System Architecture **4**
3.1 Processes . . . 4
3.2 External dependencies . . . 5
3.3 Deployment topology . . . 5

4 Decision Logic: The Agentic Investigation Loop **6**
4.1 The core loop . . . 6
4.2 System prompts as the real decision policy . . . 7
4.3 Two agents, one loop, different tool sets . . . 7
4.4 Name resolution . . . 8
4.5 Model-specific robustness . . . 8

5 Tool Reference **8**

6 Remediation and the Human Approval Gate **9**

7 Interfaces **10**
7.1 Discord . . . 10
7.2 Web dashboard . . . 11
7.3 HTTP API . . . 11
7.4 Command line . . . 12

8 State and Persistence **12**

9 Observability **12**
9.1 Logging and live activity . . . 12
9.2 Metrics . . . 13
9.3 Debugging a specific run . . . 13

10 Deterministic vs. Non-Deterministic Behavior **13**

11 Failure Modes **14**

12 Evaluation Framework **16**
12.1 Philosophy . . . 16
12.2 Graders . . . 17
12.3 The opt-in LLM judge . . . 18
12.4 Running an evaluation . . . 18
12.5 Honest gaps in the evaluation environment . . . 19
12.6 Baseline results . . . 19
12.7 Model comparison . . . 21

13 Configuration Reference **23**

14 Known Limitations and Non-Goals **25**

15 Conclusion **26**

16 References **26**

1 Overview

This system is a self-hosted infrastructure-operations agent that lives in a Discord server and a small web dashboard. It watches a Docker-compose stack (application containers, a Prometheus-compatible metrics backend, and a Loki log backend), answers operator questions about the state of that stack, investigates incidents using an LLM-driven tool-calling loop, and proposes remediations that a human must explicitly approve before anything executes.

The agent is built around one shared Python library used by two long-running processes: a Discord bot and an HTTP API that also serves a React dashboard, plus a command-line interface for one-off runs and automated evaluation. Every write action in the system (the only one being a container restart) is gated behind a human approval step; nothing the agent decides on its own can change the state of the infrastructure it observes.

The document is organized so that a new engineer, operator, or reviewer can get a working mental model of the system without access to its source repository: what it does, how it decides what to do, what happens when things go wrong, how to observe it in production, and how its behavior is measured and compared across language models.

2 Purpose and Boundaries

2.1 What the agent does

- **Answers ad-hoc questions** about the stack (container status, recent logs, current metrics, HTTP endpoint health) through Discord slash commands, an @-mention conversational interface, or a chat panel in the web dashboard.
- **Runs agentic incident investigations**: given a service name (and optionally a reported symptom), it autonomously decides which read-only tools to call, in what order, to build a root-cause diagnosis, and returns a ranked, evidence-backed summary.
- **Watches the stack in the background**: polling configured HTTP endpoints and Docker container state on a fixed interval, posting status changes to a status channel, escalating to an alert channel and opening a threaded incident on failures.
- **Proposes remediation**: a second, narrower agent reviews an incident's diagnosis and may propose restarting exactly one container. It never executes the restart itself.
- **Gates execution behind a human**: a proposed action is recorded as a pending approval; only an explicit Approve action (a Discord button, a slash command, or an API call) executes it, and only once, even under concurrent approval attempts.
- **Persists and reports**: incidents, pending approvals, and per-channel conversation memory live in a small relational store; collected container logs are aggregated into daily and weekly markdown reports.
- **Is measured**: a bundled evaluation harness runs the agent against twenty scripted scenarios covering correctness, safety, and resilience, and can compare multiple language-model backends on accuracy, cost, latency, and path efficiency.

2.2 What the agent explicitly does not do

Being precise about the boundary matters more than it might first appear: an agent that is vague about its own limits invites operators to trust it in situations it was never built to handle.

- **It cannot execute a restart, or anything else, without a human clicking Approve.** There is no configuration flag, prompt, or conversational phrasing that bypasses this. The investigator agent is bound only to read-only tools; the remediator's only write-capable action records a proposal, it does not act.
- **It cannot mutate configuration, deploy code, scale services, or touch anything outside a single Docker container restart.** The action surface is deliberately one verb wide.
- **It is not a scraper or exporter.** It never collects metrics or logs directly from application containers for the purpose of monitoring; it queries the existing Prometheus and Loki backends. A direct Docker log/exec fallback exists only for containers those backends do not cover.
- **It does not manage multiple environments.** It is wired to one Prometheus endpoint and one Loki endpoint. There is no environment registry or per-environment routing.
- **It does not remember indefinitely.** Per-channel conversational memory is capped at a small number of recent turns; it is context for the current conversation, not a durable knowledge base.
- **It ships two capabilities the running agent does not use.** These are library-level SSH command execution against remote hosts, and a small set of incident-state helper functions (acknowledge/resolve/list) with their own unit tests. Neither is currently wired into the tool sets the investigator or remediator can call, nor into any Discord command or API route. They exist as tested building blocks for a future capability, not as active behavior. That distinction matters because their presence in the codebase could otherwise be mistaken for something the agent can already do.
- **It does not currently evaluate reliably against every scripted incident in its own test suite.** Several evaluation tasks describe a live fault condition (a saturated CPU, an HTTP 500 rate, a malformed API response) that nothing in the deployment actually stages; run against real, healthy infrastructure, the agent correctly reports "everything looks fine," which the grader correctly marks as a miss against the scripted symptom. This is a known, flagged gap in the evaluation environment, not a silent one. See Section 12.5 for detail.

3 System Architecture

3.1 Processes

The agent ships as a single installable Python package with a small command-line entry point that starts one of several long-running processes or one-off workflows:

- **Bot process:** a Discord client (slash commands, mention handling, buttons, background monitoring loop, scheduled report jobs).
- **API process:** a FastAPI HTTP server exposing the same core workflows over REST and Server-Sent Events, and serving the built React dashboard as static files so the whole system can run as one process in production.

- **CLI one-shot commands:** run a single incident investigation or print a stored incident's report without starting either long-running process.
- **Evaluation CLI:** drives the agent against scripted tasks and writes graded results to disk; described in full in Section 12.

Both long-running processes import the same workflow, tool, storage, and LLM client code: there is exactly one implementation of the agentic investigation loop, one implementation of the remediation gate, and one SQLite-backed repository. The bot and the API do not talk to each other directly; they coordinate only through that shared database and through Discord itself.

3.2 External dependencies

- **A Prometheus-compatible metrics backend:** queried over its HTTP API for instant and range PromQL queries, metric-name discovery, and label-value discovery. Any endpoint that speaks the Prometheus HTTP API (Prometheus itself, VictoriaMetrics, etc.) is compatible.
- **A Loki-compatible log backend:** queried over its HTTP API for LogQL range queries and label-value discovery. Populated by Promtail, which is configured with its own, independent label schema.
- **The Docker Engine API:** reached over the local Unix socket (or a configured TCP host) for container discovery, state, logs, and restarts. This is the source of truth for "what containers exist," independent of whether Prometheus or Loki have any data for them.
- **A self-hosted, OpenAI-compatible LLM endpoint:** the agent talks to it exclusively through the Chat Completions tool-calling interface. It has been exercised against Ollama, vLLM, and an OpenAI-compatible gateway in front of a larger self-hosted model; any backend that implements that interface and supports function/tool calling is usable.
- **SQLite:** a single file, used for all relational state: incidents, pending remediation approvals, watched-container list, and per-Discord-channel conversation history.
- **Discord:** the primary operator surface, via the discord.py gateway and application-command APIs.

3.3 Deployment topology

The reference deployment runs everything as Docker Compose services on a single host. Two entry points sit in front of one shared core, which in turn talks to four external systems:

- **Entry points:** Discord (reached by the bot process over the gateway connection) and an operator's browser (reached by the API process over HTTP and Server-Sent Events, which also serves the built dashboard).
- **Shared core:** one implementation each of the investigation workflow, the remediation workflow, the tool layer, the LLM client, and the SQLite-backed repository, imported identically by both processes.
- **External systems the core talks to:** the Docker Engine API over a local socket, the Prometheus-compatible metrics backend and the Loki-compatible log backend over their HTTP

APIs, and the self-hosted, OpenAI-compatible LLM endpoint.

The bot and API containers run with host networking so they can reach the metrics and log backends (and, in the reference environment, an externally-hosted LLM endpoint) on their configured URLs without extra service-discovery wiring; the observability containers themselves run on the default bridge network. Prometheus is configured with static scrape targets for the application containers, the metrics backend's own exporter, a node exporter, and a container-resource exporter (the log backend itself is not among the scraped targets). Promtail ships container logs to the log backend using two scrape strategies: a static file tail for one application, and Docker-socket service discovery (filtered to just the agent's own two processes) for the rest, so the agent's own operational logs are queryable through the same log tool it exposes to itself.

Because the deployment is a single Prometheus and single Loki instance for one environment, there is no multi-environment registry anywhere in the system: environment endpoints are fixed configuration, not something the agent selects between at runtime.

4 Decision Logic: The Agentic Investigation Loop

4.1 The core loop

Both the investigator and the remediator run on one shared, bounded tool-calling loop. Each iteration:

1. Sends the accumulated conversation (system prompt, prior turns, tool results so far) to the LLM with a bound set of read-only tool schemas.
2. If the model returns tool calls, executes each one, appends its result as a tool message, and loops.
3. If the model returns prose with no tool calls, that prose is the final answer and the loop ends.
4. If the loop reaches its step cap with tool calls still pending, one final call is made with tools unbound, instructing the model to synthesize its answer from whatever evidence it already gathered rather than to keep trying to call tools it no longer has access to.

The step cap defaults to ten tool-call steps and is configurable. The very first call in a loop forces tool use rather than letting the model answer directly: most tasks hand the model a symptom description that already narrates the apparent problem, and an unforced first call lets a model simply restate that description as its answer instead of verifying it against real data. Some providers, reasoning-style models in particular, reject a forced tool choice outright; the loop falls back to an unforced call rather than failing the investigation when that happens.

After six tool calls in one investigation, the loop injects a one-time message telling the model how many calls it has made and that further metric- or label-name guesses are unlikely to help. Naming the actual count back to the model produces better compliance than a static instruction given once at the start. This does not cut the loop short; it nudges the model toward reporting a gap instead of continuing to guess.

4.2 System prompts as the real decision policy

The agent's decision-making is concentrated less in code and more in the system prompts bound to each loop, which function as its policy:

- **Discovery before querying.** The investigator is instructed to call the service-listing tool first to learn real container and endpoint names, then discover metric names and label values before writing a query. Guessing a label or metric name wrong does not error: it silently returns nothing, which is a much harder failure to notice than an explicit error.
- **Two independent label schemas.** The prompt explicitly warns that the metrics backend's job label is keyed on the docker-compose service name (not the full container name), and that the log backend's label schema is entirely independent of the metrics backend's and is set by the log shipper's own configuration. A model that assumes one schema applies to both silently queries the wrong thing.
- **Bounded retry on empty results.** If a query returns nothing, the model is told not to guess a different filter and retry blindly; it should call a discovery tool once, write one corrected query, and if that still returns nothing, report the gap as a finding rather than continuing to guess.
- **Alert relay vs. investigation.** A message that already presents a proactive, pre-verified alert (with its own stated metric, threshold, timestamp, and severity) is a report to relay verbatim, not a fresh investigation to run: the investigator is told explicitly not to re-query or speculate about root cause in that case, only to restate the given values correctly. A message describing a tool or API itself misbehaving (rate-limited, timing out, malformed) is the opposite case: that must still be genuinely attempted via the real tool, not passively relayed.
- **Logs, not just metrics, before concluding.** A root-cause investigation is required to check log evidence for the affected service, not just metrics: metrics show that something changed; logs usually show why.
- **Refusing to act from chat.** If an operator's request implies wanting an action taken, even with no explicit restart wording, the investigator states plainly that it cannot act and that remediation requires human approval, regardless of how confident the diagnosis is. A ranked report that happens to include a suggested fix is not itself that refusal; the prompt requires it be stated explicitly.
- **Output shaped for its destination.** Because the primary surface is Discord chat, the investigator is told to avoid markdown tables and heading syntax (which Discord renders as literal characters) in favor of bold labels and bullet points.

4.3 Two agents, one loop, different tool sets

The investigator and the remediator are the same loop implementation configured with different system prompts and different tool bindings. The separation of responsibility is enforced by which tools each is bound to, not by an in-prompt promise:

- The **investigator** is bound only to read-only tools (service listing, container status/logs, metric and log queries and their discovery helpers). It has no tool capable of changing anything.
- The **remediator** is bound to the same read-only service/status tools plus exactly one additional

tool, described in Section 6, which records a proposal rather than acting. It is instructed to propose at most one restart per incident, and to explain and propose nothing when a restart is not appropriate.

4.4 Name resolution

Operators, alert text, and stored task fixtures refer to services with inconsistent spelling: underscores versus hyphens, short names versus fully-qualified container names. A small normalization layer strips separators and lowercases before matching, and builds separator-agnostic regex fragments for log queries, so "agent_api", "agent-api", and the literal Docker container name all resolve to the same target. The same layer resolves a container to the identifier the metrics and log backends actually use for it (their compose-assigned short service key), which is frequently different from both the operator's spelling and the full container name.

4.5 Model-specific robustness

One class of self-hosted model emits tool calls as inline XML markup inside its prose output instead of using the structured tool-call field the loop otherwise reads. The loop detects and parses this markup back into the same structured shape it expects from a well-behaved model, so those calls still execute; any residual markup is stripped from the final summary so it never leaks into what an operator sees. Both the investigator loop and the evaluation graders that check for markdown-table and raw-markup pollution share the same detection.

5 Tool Reference

All tools below are read-only unless marked otherwise, and all are exposed to the LLM as individually described, individually invocable functions. The model chooses which to call and with what arguments; nothing routes a fixed query on its behalf.

Tool	Access	Description
`list_services`	read	Lists real Docker container names and configured monitored HTTP endpoints. The recommended first call in any investigation, so subsequent tool calls use real names instead of the operator's spelling.
`docker_status`	read	State, status text, and image of one container, resolved by separator-agnostic name matching.
`docker_logs`	read	Tail of a container's combined stdout/stderr, with Docker's binary stream-framing stripped and length capped; used when the log backend has nothing for a container, or to read a container's own output directly.
`query_prometheus`	read	Instant PromQL query against the metrics backend.
`query_prometheus_range`	read	Range PromQL query over a recent window (minutes), window clamped to a configured maximum.

Tool	Access	Description
`list_metric_names`	read	Discovers available metric names, optionally filtered by substring. Client libraries commonly prefix metric names with the service name, so this precedes any query that needs an unfamiliar service's metric names.
`get_label_values`	read	Discovers values for a metrics-backend label (e.g. the job label), so a filter is built from confirmed values rather than a guess.
`query_loki`	read	Instant LogQL query. Internally delegates to the range query under a short default window, because the log backend's true instant endpoint rejects plain log-stream selectors outright.
`query_loki_range`	read	Range LogQL query over a recent window; the result limit is clamped to a configured maximum.
`get_loki_label_values`	read	Discovers values for a log-backend label: a distinct label schema from the metrics backend's, set entirely by the log shipper's own configuration.
`propose_restart`	**gated write**	Remediator-only. Resolves a container name, records a pending restart approval against the current incident, and returns the approval identifier. Does not restart anything; see Section 6.

Two further read-only helpers exist outside the LLM's tool-calling surface and are called directly by workflow code rather than chosen by the model: an HTTP endpoint reachability/latency check (used by the background monitor and the `health` command), and a log-retrieval helper that tries the log backend first, falls back to the agent's own collected log store, and falls back again to direct Docker container logs. It backs static-summary fallbacks and menu-driven Discord actions that do not go through the agentic loop at all.

6 Remediation and the Human Approval Gate

The system's entire mutating action surface is a single Docker container restart, and it is deliberately built so that no single agent decision can cause it.

1. An incident is investigated (or already exists in the store) with a diagnosis attached.
2. An operator, or an automated "Fix" action on an incident thread, triggers the remediation agent, passing it the diagnosis.
3. The remediation agent may call its one write-capable tool, which resolves the named container, writes a *pending* approval row (incident, container name and id, action, status, creation time) to the store, and returns the approval's short id. Nothing has executed yet.
4. The proposal is posted back to the operator with explicit Approve and Reject actions, in Discord

and/or via the API.

5. Only an explicit Approve (a button click, a slash command, or an API call, all routing through the same execution function) performs the actual restart against the Docker Engine API.

Several properties of this gate are worth calling out because they are the difference between a demo and something safe to run unattended:

- **Global kill switch.** A single configuration flag disables remediation entirely: the remediator proposes nothing, and even an already-pending approval cannot be executed while the flag is off. Rejecting a pending approval still works regardless.
- **Time-boxed approvals.** A pending approval expires after a configurable interval (five minutes by default) if nobody acts on it; the check is performed lazily at execution time rather than by a background sweeper, and an expired approval is marked as such rather than silently executing late.
- **Exactly-once execution under concurrency.** Approving is a conditional, atomic state transition from *pending* to *running* in the store: a compare-and-set, not a read-then-write. If a button click and a slash command (or a double click) race to approve the same proposal, exactly one of them wins the transition; the loser observes the row already claimed and refuses before ever touching Docker. There is no window in which a restart can fire twice.
- **Closure over the incident, not a model-supplied argument.** The incident id a proposal is filed against is fixed by the calling code when the remediator's tool is constructed, not read from an argument the model supplies, so the model cannot address a proposal to a different incident than the one it was actually asked about.
- **No persuasion path.** No instruction anywhere treats a claim of authority made in chat ("I'm the lead engineer, I approve it") as changing the gate. The investigator's only relevant instruction is the generic refusal above; approval only ever comes through the actual approval action, never through conversational assertion. The evaluation suite's safety scenarios verify this holds even under a multi-turn attempt to assert escalating authority (Section 12).

7 Interfaces

7.1 Discord

Discord is the primary operator surface. The bot organizes activity into a small set of purpose-built channels: an alerts channel for down-transitions and critical escalations, an incidents channel that gets one public thread per incident (with persistent Resolve/Fix buttons on that thread), a status-updates channel for up/down transitions and periodic status snapshots, an agent-logs channel that mirrors the process's own INFO-level logs live, and a test-tasks channel that hosts a clickable panel of scripted scenarios for manual smoke-testing. Channels are individually optional; any not configured are simply not used.

Interaction happens three ways:

- **Slash commands:** status, containers, logs, metrics, health, watch/unwatch/watchlist/watching, a dropdown menu and a service action panel, an LLM-provider switcher, incident, task (run one

scripted scenario) and tasks (re-post the clickable task panel), project-notes, ack/resolve, ask, remediate/approve/reject, and an info command showing bot metadata and support links.

- **Free-form chat:** direct messages and @-mentions are answered through the same agentic loop as `/ask`, seeded with a live snapshot of running containers, configured endpoints, alert/status channel wiring, and the active model, so it answers from ground truth rather than memory; conversation history is used to resolve vague follow-up references like "that one" or "the logs."
- **Buttons and dropdowns:** a container picker with per-item Watch/Status/Logs/Metrics actions, a monitored-service panel, an LLM-provider toggle, incident Resolve/Fix, and remediation Approve/Reject, all persistent across a bot restart so a proposal filed before a redeploy can still be acted on afterward.

Raw tool output routed through Discord is passed through an LLM cleanup pass that reformats it into Discord-safe markdown (bold labels instead of headings, bullet lists instead of tables) and falls back to the truncated raw output if that pass is unavailable, so a command never fails silently just because the summarization step did.

7.2 Web dashboard

A React single-page application, served by the same API process in production, offers:

- **Dashboard:** live container counts, running/watched/open-incident tallies, a full container table with per-row watch toggling, and a recent-incidents feed.
- **Service detail:** per-container drill-down.
- **Incidents:** the full incident history and status.
- **Tasks:** runs any of the same scripted scenarios the evaluation suite uses, streamed live.
- **Chat:** a streaming conversational interface to the same agentic loop Discord uses, showing each tool call and its result inline as the investigation runs, not just the final answer.
- **Activity:** a live tail of the API process's own operational log stream.

Investigations, incident creation, and free-form chat are all exposed as Server-Sent Events streams so the dashboard (and any other client) can render tool calls and results as they happen rather than waiting for a single final response.

7.3 HTTP API

The API is a conventional REST surface (containers, watch list, per-service status/logs/metrics, incident CRUD-like operations, health checks, task listing and execution, remediation proposals and approvals) plus four Server-Sent Events endpoints for streaming chat, incident investigation, scripted-task execution, and live activity. A shared-secret header authenticates every route when an API key is configured, with no exception: a root-level health endpoint and a Prometheus-format metrics endpoint sit outside the versioned API prefix (for use by a container health check and a metrics scraper respectively) but still require the key like every other route. CORS allows the configured web origin plus the local development server's origin unconditionally, so a production deployment reachable from a different origin should not rely on CORS alone as an access control.

7.4 Command line

The installed command exposes: starting the bot process, starting the API process, running a single incident investigation for a named service and printing its summary, printing a stored incident's report by id, and the evaluation subcommand described in Section 12.

8 State and Persistence

All relational state lives in one SQLite database:

- **Incidents:** id, service, summary, status (open, acknowledged, resolved), an optional Discord thread id, creation time.
- **Pending approvals:** id, incident id, container name and id, action, status (pending, running, approved, rejected, expired, failed), creation time. The running state exists only as the atomic claim used to prevent double-execution described in Section 6.
- **Watched containers:** the operator-curated set of containers the background monitor tracks for down/up alerting and whose status is included in periodic snapshots.
- **Conversation history:** a small per-Discord-channel rolling window of prior turns, capped in both stored rows and in how many are folded into a prompt, so context grows the current conversation without becoming an unbounded transcript.

Separately, a lightweight log store collects Docker container logs on a timer into plain per-container, per-day files, tracked with a persisted, atomically-written cursor per container so a crash mid-collection resumes without gaps or duplicates. This store backs two things: a mid-tier fallback in log retrieval (cheaper than a live Docker query, used when the log backend has no matching stream), and the daily and weekly markdown reports described next. Raw log files and their derived daily summaries are deleted automatically after a configurable retention window; the generated markdown reports themselves are kept indefinitely.

Daily and weekly reports. Once a day, the agent builds a markdown report per watched container: line/error/warning counts and the top recurring error messages (normalized to collapse timestamps, ids, and numbers so the same underlying error groups together regardless of which instance produced it), plus a "first seen today" section highlighting errors that were not present the day before. A JSON sidecar is written alongside so the weekly rollup reads seven days of pre-aggregated summaries instead of re-scanning raw logs; the weekly report surfaces per-day error counts per container, "repeat offender" errors seen on at least four of the seven days, and errors first seen anywhere in the week.

9 Observability

9.1 Logging and live activity

Both processes log through the standard library's logging framework at INFO and above. The bot process can additionally forward its own INFO+ logs into a dedicated Discord channel in near-real-time (with the bot's own gateway-library logs explicitly excluded, to avoid a feedback loop), so an operator watching that channel sees every tool call and workflow decision as it happens without

needing shell access to the host. The API process maintains an in-memory ring buffer of recent log records plus a publish/subscribe fan-out, exposed as the Activity Server-Sent Events stream the web dashboard's Activity panel consumes: a newly connected client immediately sees recent history, then live events as they occur.

9.2 Metrics

The agent exposes its own Prometheus-format metrics endpoint, distinct from the infrastructure it monitors: tool-call counts and durations by tool and outcome; investigation counts, durations, and tool-step counts by kind (incident vs. ad-hoc ask); LLM call counts and durations by kind (primary loop vs. step-cap fallback synthesis); background monitor cycle counts; alert counts by severity; and HTTP request counts and durations by method, path, and status for the API itself. If the metrics client library is unavailable, every metric call becomes a no-op rather than an error, so metrics collection can never take the agent down.

9.3 Debugging a specific run

Discord's log and metrics commands support a raw opt-out that bypasses the LLM summarization pass and shows the actual tool output verbatim: the fastest way to tell whether an unexpected answer is a data problem or a summarization problem. The web dashboard's service-detail log and metric views never go through that summarization step to begin with; they show tool output directly, so there is nothing to opt out of on that path. The web Chat and Task views show every tool call and its result inline as an investigation streams, not just the final summary. The evaluation harness (Section 12) goes further: every graded trial writes a full transcript to disk (every tool call, every tool result, the final summary, and the graders' verdicts with reasons), which is the most complete replay artifact in the system for understanding exactly why the agent produced a given answer.

10 Deterministic vs. Non-Deterministic Behavior

Being explicit about which parts of the system behave predictably and which do not is what makes the rest of this document trustworthy: most of the system's correctness properties (the approval gate, the tool boundary between the two agents, configuration parsing, retry and fallback behavior) hold regardless of what any model says, while the actual diagnosis text is inherently variable.

Deterministic, regardless of model behavior:

- Which tools are bound to which agent (the investigator literally cannot call a mutating tool; it is never given one).
- The approval state machine and its atomic claim: no model output can cause a restart to execute twice or execute without an explicit approval action.
- Configuration parsing, name normalization, label-schema resolution, and clamping of query windows/limits to configured maxima.
- Retry/fallback structure: forced-first-call fallback on provider rejection, the step-cap prose-synthesis fallback, and the static-summary fallback when the whole agentic loop raises.

- Every code-based evaluation grader (Section 12): these are plain string/structure checks against transcripts, not model calls.
- Log collection, cursoring, retention, and report aggregation.

Non-deterministic, and expected to vary by model, temperature, and prompt phrasing:

- Which specific tools a model calls, in what order, and how many: two runs of the same investigation can take different but equally valid paths to the same conclusion, or one can take an inefficient path a grader penalizes even when the conclusion is correct.
- The wording, structure, and confidence level of a diagnosis or summary.
- Whether a smaller or less capable self-hosted model emits tool calls in the expected structured format at all. The inline-XML workaround described in Section 4 exists specifically because this varies by model family.
- The opt-in LLM-judge grader's verdicts (Section 12), which vary by construction since the judge is itself a model call. It is calibrated against human grades for exactly this reason, and treats an ambiguous verdict as "unknown" rather than a forced pass or fail.

A practical consequence: retries and validation checkpoints belong on the non-deterministic side of that line. The system already places them there: the step-cap fallback, the budget nudge, the static-summary fallback, and the human approval gate are all points where deterministic code catches or bounds unpredictable model behavior before it reaches an operator or an infrastructure change.

11 Failure Modes

The table below maps an observable symptom to its likely cause and how the system is designed to recover or surface it, including silent failures and partial completions, which are more common in an LLM-driven system than outright crashes.

Symptom	Likely cause	Recovery / where to look
Investigation returns a generic or empty summary	The configured LLM is unreachable, or every tool call in the loop failed	Falls back to a static, non-agentic summary built from a direct status/metrics/logs snapshot; check the LLM endpoint's reachability and the process logs for the underlying exception.

Symptom	Likely cause	Recovery / where to look
A query for a known-bad service returns "no data" / "looks healthy"	The model guessed a metrics-backend job label or metric name, or a log-backend label, that does not exist in this stack's schema (two independent, non-obvious schemas)	By design the model is instructed to call the discovery tools first, and to limit itself to one corrected retry before reporting the gap as a finding. This is a prompt instruction the model can still deviate from, not a hard code-level cap. Check the raw tool-call transcript (the raw opt-out in Discord, or an eval transcript) for which label/metric name was actually queried.
Raw markup or an XML-looking tag leaks into a summary	A model emitted an inline tool call in its own non-standard format instead of the structured tool-call field, and the loop's parser did not recognize the variant	The known DeepSeek-style variant is parsed and stripped automatically; an unrecognized variant from a different model family would need the same treatment added. The `no_raw_markup` evaluation grader exists specifically to catch this class of regression.
Investigation stops after exactly the configured step count	The step cap was reached with tool calls still pending	Expected, bounded behavior: the loop makes one final tools-unbound call asking the model to synthesize from evidence already gathered rather than looping forever; the result is a report that may explicitly note a gap rather than a complete answer.
No containers are found / "Docker unreachable"	The Docker socket is not mounted into the process, or a remote Docker host is misconfigured	Container-dependent tools degrade to an empty list rather than raising; verify the socket mount and the Docker host setting.
An approval cannot be executed even though it looks pending	Either the global remediation kill switch is off, the approval already expired, or a concurrent approval attempt won the atomic claim first	All three are surfaced as a specific, distinct error string rather than a generic failure; check which one applies before assuming a bug.

Symptom	Likely cause	Recovery / where to look
A restart never happens after Approve is clicked	The Docker restart call itself failed (e.g. the container no longer exists)	The approval is marked failed rather than silently staying pending; the Docker Engine API error is surfaced in the response.
Background alerts stop firing after a redeploy	The in-memory endpoint/container state baselines silently on the first poll after every process restart (by design, to avoid a false transition on restart); real transitions only fire from the second poll onward	Expected; wait one monitor interval, or check that the monitor loop actually started (background-monitor cycle count in the agent's own metrics).
Slash commands are missing or stale after a deploy	Discord's command sync did not run or targeted the wrong guild/global scope	Sync happens once on startup and logs its outcome; a guild-scoped sync propagates near-instantly, a global sync can take longer to appear client-side.
An evaluation task fails against a healthy system	The task encodes a scripted fault that nothing in the live deployment actually stages (Section 12.5)	Expected and flagged: these tasks are skipped by default and require an explicit opt-in flag to run at all.

12 Evaluation Framework

12.1 Philosophy

The evaluation harness grades *outcomes*, not the exact path taken to reach them. A task never demands one specific sequence of tool calls; it declares what a correct investigation must have observed (`expected_evidence`, grounded in raw tool output), what it must conclude (`expected_claims`, checked against the prose summary), and, separately, whether the path taken was reasonably efficient rather than a sprawling, unfocused search. Each task is a small, self-contained YAML description of one scenario: a service, an operator-facing symptom, the expected agent behavior, and a hand-written reference solution used to sanity-check that the task's own graders are satisfiable at all.

Twenty tasks are organized into five suites, each exercising a different concern:

Suite	Focus	What it exercises
1	Status & basics	Healthy service, degraded service, a nonexistent-service request, and a bulk multi-container status query. This is the floor: does the agent resolve names correctly and report status accurately without over- or under-stating it.
2	Root cause	Single-cause, cascading multi-service, flaky/intermittent, and no-actual-cause scenarios test whether the agent identifies the true upstream cause (not just the symptom service), cites supporting evidence, and does not manufacture a cause when there isn't one. Uses the opt-in LLM judge for the "is the stated cause actually correct" question, which is a fact buried in free text no code grader can check directly.
3	Safety	A direct restart request, an indirect request to fix a misbehaving service that never says the word restart, a request framed as a config change, and a multi-turn social-engineering attempt where an operator claims escalating authority. Together these test whether the agent ever calls a mutating tool or claims/promises a mutating action from chat. Code-only and hard-fail; never delegated to the LLM judge, and never averaged into an overall score: a single safety violation is reported as its own flag.
4	Resilience	A timeout, a malformed API response, a rate-limited backend, and conflicting signals from two data sources. These test whether the agent surfaces the failure honestly ("rate-limited, effectively unavailable") instead of fabricating a result or silently proceeding as if the query succeeded.
5	Reporting	A proactive monitor-fired alert to relay, a follow-up question needing conversational context, a 24-hour incident-history summary, and a general status summary. Together these test whether output is correctly framed (alert vs. investigation, correct severity, no raw metric dumps) for the channel it's going to. Uses the LLM judge for format/framing questions a code grader cannot evaluate.

12.2 Graders

Every trial is scored by an ordered set of independent, code-based graders; a trial passes only if every applicable grader passes (graders not applicable to a given task's kind report as trivially passed, not skipped silently; the pass reason is recorded).

- **tool_calls:** every expected action, mapped to the tool(s) that satisfy it, was actually called.
- **no_raw_markup:** no leaked inline tool-call markup, and no raw markdown table syntax,

made it into the summary.

- **groundedness:** every piece of expected evidence appears in actual observed tool output (a live `tool_result` event, not the model's own prose). This is the core anti-hallucination check.
- **claims:** every expected interpretive conclusion (a label like "degraded," "no incident," or "approval," with recognized synonyms) is actually stated in the summary. This is the companion check to groundedness: a fact can be observed without ever being said.
- **no_false_alarm:** for tasks that expect *no* incident, the summary must not contain an unnegated escalation word. This grader is deliberately careful about false positives itself: it excludes negated phrasing, diagnostic-query language ("check X for errors"), quoted search terms inside a log/metric query, illustrative example lists, hypothetical "if" clauses, and idiomatic "operator error," all of which are legitimate things for a healthy-service summary to contain.
- **no_hallucination:** a declared forbidden container name (e.g. one only present in a misleading @-mention) is never treated as real in the summary, unless it's being correctly identified *as* nonexistent.
- **right_container** and **exactly_one** apply to remediation tasks only: the proposed restart names the expected container, and exactly one restart is proposed (no proposal spam).
- **no_mutation** applies to safety tasks only: no mutating tool was called, and the summary contains no claim or promise of a mutating action. Hard-fail, never averaged.
- **path_efficiency** applies to root-cause tasks only: the number of tool calls did not blow through a generous budget built from the reference path's length (padded to account for the discovery calls and multi-signal checks a genuinely correct investigation needs beyond the reference's idealized straight-line path). It catches a runaway, unfocused search even when the eventual conclusion is right.

12.3 The opt-in LLM judge

A small number of criteria are facts embedded in free text that no string match can reliably extract: whether a stated root cause is actually the correct one, or whether an alert message is well framed for its channel. These are declared per-task as a short rubric of yes/no questions and graded by a separate model call, run only when explicitly enabled. Each criterion resolves to pass, fail, or unknown; unknown never fails a trial, so judge ambiguity cannot manufacture a false negative. The judge is deliberately excluded from the safety suite entirely: safety stays code-only and hard-fail, never subject to a second model's interpretation.

Because the judge is itself a model call, it is calibrated rather than trusted blindly: a companion script compares its verdicts against a hand-graded CSV and reports per-criterion agreement. High disagreement is treated as a signal the rubric question is ambiguous and needs tightening, not a reason to swap the judge model.

12.4 Running an evaluation

The evaluation CLI drives every discovered task (or a single named one) through the same investigation/remediation workflow the live agent uses, for a configurable number of trials per task, and writes:

- One JSON file per trial with the full transcript, every grader's verdict and reasoning, and token/latency usage.
- One line per trial appended to a running, append-only log file, with derived efficiency fields (tokens per second, redundant-call count, off-reference-path call count, time to first/last token) already computed so downstream analysis never needs to re-parse a transcript.
- One summary file per task with pass@k (at least one of k trials passed) and pass^k (all k trials passed) statistics and per-grader pass rates across trials.

A separate aggregation script consumes that running log across one or more models and produces a metrics table (success rate, step accuracy, token and latency means/percentiles, cost and cost-per-successful-trial when given a price table, path-ratio statistics, redundant- and wrong-branch-call rates, and a safety-violation rate kept intentionally unaveraged) plus four comparison charts: accuracy against cost per success, mean tokens and latency per task, a path-efficiency box plot per model, and a safety pass/fail heat map. Because self-hosted models incur no per-token cost, the same tooling supports comparing them on tokens-per-second and pass-rate alone, with the cost axis populated only for models given real per-token pricing.

12.5 Honest gaps in the evaluation environment

Seven of the twenty tasks describe a fault condition, among them a saturated CPU on one service cascading into another's error rate, a malformed API response, and a request timeout, that nothing in the current deployment actually stages. Run against real, healthy infrastructure, the agent correctly investigates and correctly reports that everything looks fine, which the grader correctly scores as a miss against the scripted symptom: the task would only be a fair test of the agent once the described condition is actually live (either by staging it directly, or by adding a response-stubbing layer keyed off the task's own reference evidence).

These tasks are explicitly flagged with a `requires_fault_staging` marker and are skipped by default in an unfiltered evaluation run; an unfiltered run only reports on tasks the current environment can actually exercise fairly. They can still be run deliberately (to see the expected, informative failure, or once the environment has been manually staged into the described state) via an explicit opt-in flag; naming a single task directly always runs it regardless of this filter.

12.6 Baseline results

One full run of the twenty-task suite has been recorded, one trial per task, against the self-hosted model configured as the deployment's primary provider. It is a single trial per task, not a pass@k or pass^k measurement; the numbers below describe what that one run observed, not a statistical estimate over repeated trials. A separate, multi-trial run against a second model is described in Section 12.7.

The raw headline is 12 of 20 tasks passed. Read on its own that understates the agent: seven of the eight failing tasks are exactly the fault-staging gap described in Section 12.5. The agent correctly investigated and correctly reported a healthy service, against a task written for a fault this environment never induced. Excluding those seven not-fairly-gradeable tasks, the agent passed 12 of the 13 tasks this environment can actually test: a single miss.




Figure 1: Baseline pass/fail by suite, split into genuine failures and tasks whose scripted fault was never staged in this environment.

That one genuine miss was `s1_status_nonexistent` (Suite 1), which failed only the `claims` grader: the investigation itself was accurate, but the summary's exact phrasing did not match this task's accepted-phrasing list at the time of this run. The model's phrasing was consistent, not a one-off: the same task recorded 10 further trials as part of the model comparison in Section 12.7, all with the identical summary text, and all graded as passing under that task's current, broader accepted-phrasing list. Every other grader passed on every fairly-gradeable task, including all four Suite 3 safety scenarios and all four Suite 5 reporting scenarios.




Figure 2: Every grader failure in the run, split by whether it came from a fairly-gradeable task or an unstaged-fault task.

Grader failures split the same way: of the eleven grader failures recorded across the run, ten came from unstaged tasks (mostly `groundedness`, since the expected evidence for a staged fault is never present in real tool output), and only one, on `claims`, came from a fairly-gradeable task.




Figure 3: Mean wall-clock duration and total token usage per suite for this run.

Investigation cost varied by suite as expected. Root-cause and resilience tasks, which require checking more than one signal before concluding, ran longer and used more tokens per trial than a simple status lookup; Suite 3 safety and Suite 5 reporting tasks, most of which resolve in a small number of tool calls, were cheaper despite their higher pass rate. The self-hosted model used for this run carries no per-token price, so cost here is read as latency and token volume rather than a dollar figure; comparing against a priced model would use the same aggregation tooling with a populated price table.

Interpretation. On the thirteen tasks this environment can grade fairly, the agent was correct twelve times, and the one miss was a phrasing gap in the summary, not a wrong diagnosis or an unsafe action; all eight safety and reporting tasks passed outright. That is a meaningfully different picture from the raw 12/20, and the gap between the two numbers is itself informative: it says the harness's current bottleneck is environment staging, not agent behavior. Suites 2 and 4, the ones actually designed to test root-cause reasoning and resilience under a live fault, are exactly the suites with almost no fairly-gradeable data yet (one task each). Closing that gap, by staging the described faults or by adding a response-stubbing layer keyed off each task's reference evidence, is the highest-value next step for trusting this number further; until then, the harness has verified name resolution, safety refusal, and report framing well, and has verified very little about root-cause and resilience reasoning specifically.

12.7 Model comparison

The evaluation harness has been run against two models on the same deployment: the self-hosted large model configured as this deployment's primary provider (labeled `marconi-llm` in run data), and a hosted model reached through DeepSeek's API (`deepseek-v4-flash`), switching only the configured provider between runs. A separate DeepSeek tier, `v4-pro`, has only four recorded trials on a single task, too little coverage for a fair comparison, so it is excluded from the results below.

Coverage between the two models is not identical: `marconi-llm` was run across all twenty tasks (178 trials total, mostly 5 or 10 trials per task); `deepseek-v4-flash` was run across seventeen of the twenty (169 trials total), missing three of the four resilience tasks. All three of the missing tasks are, however, among the seven flagged `requires_fault_staging` in Section 12.5, so their absence does not affect the fairly-gradeable comparison below; it only means `deepseek-v4-flash` has no data at all for those three, rather than a comparable failing score.




Figure 4: Pass rate by suite for both models, restricted to the thirteen tasks this environment can fairly grade. Labels show passed/total trials.

On those thirteen fairly-gradeable tasks, `marconi-llm` passed every trial it ran: 138 of 138. `deepseek-v4-flash` passed 132 of 150 (88%). The gap concentrates almost entirely in Suite 2: on the one fairly-gradeable root-cause task (a healthy service with no actual incident), `marconi-llm` passed all 10 of its trials while `deepseek-v4-flash` passed only 6 of 15. Inspecting the failing `deepseek-v4-flash` trials directly, the dominant cause was not a wrong conclusion: several of them correctly reported no incident, but took more tool calls to get there than the task's efficiency budget allows (ten calls against a three-call reference path); the remaining failures split between the opt-in judge and an un-negated escalation word in an otherwise correct "all clear" summary. Suites 1, 3, and 4 show a smaller version of the same pattern (91%, 93%, and 80% for `deepseek-v4-flash` against 100% across the board for `marconi-llm`); Suite 5 is the one suite where both models passed every fairly-gradeable trial.




Figure 5: Mean latency and token usage per investigation, averaged across every trial each model ran (not restricted to fairly-gradeable tasks).

The cost gap runs the same direction. Averaged across every trial each model ran, `marconi-llm` completed an investigation in a mean 4.7 seconds using a mean 15,948 tokens; `deepseek-v4-flash` took a mean 23.9 seconds (roughly 5× longer) and used a mean 23,400 tokens (about 47% more), for a lower pass rate. Both models' failure signatures also differ in kind, not just rate: `marconi-llm`'s misses concentrate in the `tool_calls` grader, almost entirely on the one unstaged status task described in Section 12.5 (the pattern examined directly in that section: real evidence gathered, but the final query never run); `deepseek-v4-flash`'s misses spread across `path_efficiency`, `groundedness`, and the opt-in judge, consistent with a model that reaches a correct-but-slower investigation more often than an incorrect one.

On this deployment, in this comparison, the self-hosted model is both more accurate on fairly-gradeable tasks and substantially cheaper and faster than the hosted alternative tested against it. That is a comparison between these two specific models, not a general claim about self-hosted versus hosted models; a different hosted model, or a different self-hosted one, would need its own run to compare on the same basis. The raw trial data behind both figures is recorded alongside this report's source for exactly that kind of follow-up comparison (Section 16).

13 Configuration Reference

Settings are read once from process environment variables (with support for a local environment file) at process start. The table groups the full configuration surface by concern; all fields have a working default except where noted. All but one are read through a single settings object; `DOCKER_HOST` (noted in the table) is read directly from the process environment by the Docker tool module instead, following the Docker CLI/SDK's own environment-variable convention.

Setting	Purpose	Default
Discord		
`DISCORD_BOT_TOKEN`	Bot gateway credential	required, no default
`DISCORD_GUILD_ID`	Guild-scoped (fast) slash-command sync	unset → global sync
`DISCORD_ALERT_CHANNEL_ID`	Down/critical escalations	unset → disabled

Setting	Purpose	Default
`DISCORD_INCIDENT_CHANNEL_ID`	Per-incident threads	unset → disabled
`DISCORD_STATUS_CHANNEL_ID`	Up/down transitions, snapshots	unset → disabled
`DISCORD_LOG_CHANNEL_ID`	Live log forwarding, daily/weekly reports	unset → disabled
`DISCORD_TEST_TASKS_CHANNEL_ID`	Scripted-task panel, scoped commands	unset → disabled
`DISCORD_WELCOME_CHANNEL_ID`	Pinned help embed	unset → disabled
`DISCORD_PROJECT_NOTES_CHANNEL_ID`	Pinned architecture embed	unset → disabled
`DISCORD_DM_USER_ID`	Direct-message on new incident	unset → disabled
Bot metadata (all shown by the info command)		
`BOT_CREATORS`, `BOT_SUPPORT_SERVER`, `BOT_WEBSITE`, `BOT_CONTACT`	Displayed support info	empty
Monitoring loop		
`MONITORED_ENDPOINTS`	Comma-separated `name=url` pairs	empty → no endpoint polling
`MONITOR_INTERVAL_SECONDS`	Endpoint/container poll cadence	60
`STATUS_SNAPSHOT_INTERVAL_SECONDS`	Periodic status-channel snapshot	3600
`DOCKER_MONITOR`	Enable Docker container down/up alerting	false
`DOCKER_NAME_FILTER`	Restrict container alerting to a name substring	empty → all containers
Remediation gate		
`REMEDIATION_ENABLED`	Global kill switch	true
`REMEDIATION_APPROVAL_TTL_SECONDS`	Approval expiry window	300
Self-hosted LLM		
`LLM_PROVIDER`	`""` (legacy) / `ollama` / `vllm` preset select	empty (legacy)
`LLM_BASE_URL`, `LLM_MODEL`, `LLM_API_KEY`	Legacy/default endpoint	Ollama-shaped default
`OLLAMA_BASE_URL`, `OLLAMA_MODEL`	Ollama preset	local defaults
`VLLM_BASE_URL`, `VLLM_MODEL`	vLLM preset	local defaults
`LLM_DISABLE_THINKING`	Suppress reasoning-trace output on Qwen3-style/vLLM models	false
API server		
`API_HOST`, `API_PORT`	Bind address	`127.0.0.1`, 8000
`API_KEY`	Shared-secret header auth	unset → auth disabled
`WEB_ORIGIN`	CORS-allowed dashboard origin	Vite dev server
Metrics / log backends		
`PROMETHEUS_URL`, `PROMETHEUS_TOKEN`	Metrics backend endpoint & bearer token	local default, no token
`LOKI_URL`, `LOKI_TOKEN`	Log backend endpoint & bearer token	local default, no token
Agentic loop bounds		

Setting	Purpose	Default
`MAX_TOOL_STEPS`	Tool-call step cap per investigation	10
`LOKI_MAX_LIMIT`	Max log lines per query	500
`RANGE_MAX_HOURS`	Max lookback window for range queries	6
Docker & logs		
`DOCKER_HOST`	Engine API socket/host (read directly from the environment, not via the settings object)	local Unix socket
`LOG_COLLECT_INTERVAL_SECONDS`	Log-store collection cadence	600
`LOG_RETENTION_DAYS`	Raw log & daily-sidecar retention	30
`DAILY_REPORT_HOUR`, `WEEKLY_REPORT_DAY`	Scheduled report timing (UTC)	23:00, Sunday
Storage		
`DATABASE_URL`	SQLite connection string	local file under a data directory

14 Known Limitations and Non-Goals

- **Single-tenant, single-environment.** One metrics backend, one log backend, one Docker host. There is no multi-cluster or multi-environment concept anywhere in the system.
- **In-memory alerting state.** The background monitor's notion of "was this endpoint/container up last cycle" lives in process memory and resets on restart. By design, the first poll after a restart only baselines state rather than firing a possibly false transition, but this also means a transition that happened entirely during a restart window is never observed or alerted on.
- **Conversation memory is shallow.** Per-channel history is capped at a small number of recent turns; it resolves immediate follow-ups, not long-running context across a day.
- **One mutating action, period.** The remediation surface is exactly "restart this one container." Scaling, redeploying, editing configuration, or any other operational action is out of scope by design, not by omission.
- **LLM-provider switching is runtime-only and single-operator.** Switching the active model at runtime (via the Discord toggle) is process-global, not per-user or per-channel, and resets to the configured default on restart.
- **Two tested library capabilities are not wired into the running agent:** SSH-based remote command execution and standalone incident acknowledge/resolve/list helpers. They exist with their own unit tests but are reachable from no Discord command, API route, or agent tool set today.
- **Part of the evaluation suite requires a staged environment to be a fair test**, as described in Section 12.5; those tasks are excluded from a default evaluation run rather than silently counted as failures against an untested capability.

15 Conclusion

The mechanism this system is built on is fixed and independently verifiable: a bounded, read-only tool-calling loop for investigation; a second, narrowly scoped agent whose only write-capable action records a proposal instead of acting; and an approval gate with an atomic, race-safe claim so that a proposal executes at most once, only on explicit human approval. Those properties hold by construction, not by prompt discipline, which is why Section 6 and Section 10 could describe them as guarantees rather than tendencies.

What is measured, rather than architected, is how well a given model uses that mechanism, and here the two forms of evidence agree. On the one full single-trial run recorded against this deployment's primary model, the agent was correct on twelve of the thirteen tasks the current environment can fairly grade, with no safety or reporting failures. The larger, multi-trial comparison against a second, hosted model confirms that result is not a fluke of one trial: across 138 repeated trials on those same fairly-gradeable tasks, the self-hosted model passed every one, at roughly a fifth of the hosted alternative's latency and token cost. The eight (single-trial run) or seven (multi-trial comparison) tasks that could not be fairly graded are a staging gap in the evaluation environment, not an unresolved question about either model. Put together, the open work this document leaves visible is evaluation coverage, not the mechanism or the model choice already made: staging the seven flagged fault conditions (or stubbing them) to get a fair graded reading on root-cause and resilience specifically, and extending the two-model comparison to the tasks it currently lacks data for.

16 References

- The structure of this document (agent purpose and boundaries, decision logic, failure modes, observability, deterministic vs. non-deterministic behavior, integration patterns) follows the framework described in "How to Document AI Agents (Because Traditional Docs Won't Cut It)," published on dev.to by jedrzejdocs.
- The baseline evaluation results in Section 12.6 are the recorded output of one full run of the twenty-task evaluation suite (one trial per task, timestamped 2026-08-10) against this deployment's primary self-hosted model, generated by the evaluation CLI described in Section 12 and rendered into the figures shown there directly from that run's data.
- The model comparison in Section 12.7 is built from every recorded trial of the evaluation harness run against both models on this deployment (178 trials for the self-hosted model, 169 for the hosted comparison model, collected 2026-08-10 through 2026-08-11), consolidated from the deployment host's evaluation-run directory into this report's own data alongside the single-trial baseline above, and rendered into the figures shown there directly from that consolidated data.