Tuesday, May 7, 2024 12:18 PM

special cases

Number	Sign	Exponent	Fraction
0	Any	00000000	0000000000000000000000
00	0	11111111	0000000000000000000000
- 00	1	11111111	0000000000000000000000
NaN	Any	11111111	non-zero
denormals	Any	00000000	F ≠ 0 (-1)°x 2 ⁻¹²⁶ x 0.F

Denormals - have a smaller magnitude than the smallest normalized number

We don't implicitly assume the leading bit to be 1.

$$(-1)^{s} \times 2^{(126)} \times 0.F$$

- have an exponent part which is 0 and Mantisa different from zero
- the range of numbers that can be represented [2**-149, (1-2**-23) * 2**-126]

ISEE 754 to base 10

$$(-1)^{s} \times 2^{(E-127)} \times 1.F$$

Double and Half precision Floating points

Precision	Num. Bits	Num. Sign Bits	Num. Exponent Bits	Num. Fraction Bits	Bias	Minimum Positive Normal Value	Maximum Value	Minimum Positive Subnormal Value
Single	32	1	8	23	127	2-126	(2-2 ⁻²³) x 2 ¹²⁷	2.149
Double	64	1	11	52	1023	2 ⁻¹⁰²²	(2-2 ⁻⁵²) x 2 ¹⁰²³	2-1074
Half	16	1	5	10	15	2-14	(2-2 ⁻¹⁰) x 2 ¹⁵	2-24

Rounding

round 1.100101 (1.578125) to only 3 fraction bits

Down (floor)

1.100 Up (ceiling) # Up: 1.101

Toward zero (truncation)

1.100

To nearest (default) - If equidistant, round towards the one with 0 in the least significant position of the fraction

1.101 (1.625 is closer to 1.578125 than 1.5

Addition

1. write them in the formula that we use to convert them to decimal format

$$(-1)^{s} \times 2^{(126)} \times G.F$$

- 2. adjust the decimal points using the exponents to make them easy to add
 - · it's better to adjet the one with smallest exponent o that we don't lose the most significant bit in the process

3. add like terms

To subtract use the same technique making sure the sign of the second number is right

Multiplication

 follow the addition step except instead of addition use multiplication Use same method for division

xlemark-we only take one exponent as

7 eg- 1011 x 1017 100001

a common factor after adjustment:
- Multiply the mantisas > 1. F x 1. F'
- Consider the sign.

- Binary coded decimal (BCD) system 4 bits are used to represent a decimal digit from 0 to 9**.**
 - **-**example, 37 is written as 0011 0111