

Index

Symbols

? (question mark) command, [101](#)

Numbers

2-way states, [550](#)

10/100 ports, autonegotiation, [161](#), [162](#)

10/100/1000 ports, autonegotiation, [161](#), [162](#), [163](#)

10BASE-T

pin pairs, [48](#)

UTP pinouts, [46–47](#)

100BASE-T

pin pairs, [48](#)

UTP pinouts, [46–47](#)

802.1Q trunking, [194–195](#), [454](#), [457–464](#)

802.3 10-Gbps fiber standards, [52](#)

802.3 Ethernet header and trailer fields, [53–54](#)

A

AAA servers. *See* [authentication servers](#)

abbreviating IPv6 addresses, [647](#), [648–649](#)

ABR (Area Border Routers), [556](#)

access interfaces, VLAN, 197–198

access switches, 259

accessing

 Cisco IOS XE CLI, 91–101

in privileged (enable) mode, 96–98

with SSH, 96

with Telnet, 96

in user mode, 96–98

 CLI

from Cisco Catalyst switches, 90

Cisco IOS XE CLI, 91–101

password security, 98–99

from WebUI, 99–101

 router CLI, 414–415

 user mode, switches

external authentication servers, 141–142

remote access, IPv4, 146–147

remote access, SSH, 142–145

acknowledgement messages, 489

AD (Administrative Distance)

 default distances, 623

 IPv6 routing

connected routes, 727

static routes, 739–741

additional content (exams), 751

address masks, 496

addressing

 Ethernet addressing, 54–55

 MAC addresses, 54–55

addressing, IPv4

- address exhaustion timeline, IPv4, [641–642](#)
- APIPA IP addresses (169.254.x.x), [490](#)
- ARP, [80–81](#)
- classes, [328–330](#)
- classful addressing, [348](#)
- classless addressing, [348](#)
- configuring, connected routes, [435–439](#)
- default masks, [330](#)
- dividing with subnet masks, [346–348](#)
- formats, [330](#)
- hosts
 - DHCP*, [488–497](#)
 - Linux settings*, [504–506](#)
 - macOS settings*, [502–504](#)
 - settings*, [497–499](#)
 - troubleshooting settings*, [506–509](#)
 - Windows IP settings*, [499–502](#)
- LLA, [680–684](#)
- network broadcast addresses, [331](#), [333–334](#)
- router interfaces, [418–419](#)
- routing, [76–77](#)
 - grouping addresses*, [76](#)
 - header fields*, [76–77](#)
 - subnetting*, [76](#)
- subnetting, [76](#), [308](#)
 - broadcast addresses*, [358](#), [359](#), [361](#)
 - ID/addresses*, [308](#), [360](#)
 - ID/addresses, binary math analysis*, [362–366](#)
 - ID/addresses, finding in difficult subnet masks*, [369–371](#)
 - range of usable addresses*, [361](#), [367](#)
- troubleshooting, [522–524](#)
- unicast IP addresses, [358](#)

addressing, IPv6

- abbreviating addresses, [647](#), [648–649](#)
- address formats/conventions, [646](#)
- address prefix lengths, [649](#)
- anycast addresses, [672–689](#)
- configuration summary, [690–691](#)
- DAD, [705](#)
- DHCP, [706–710](#)
- dual stacks, [671](#)
- expanding addresses, [648–649](#)
- full (unabbreviated) addresses, [646–647](#)
- GUA, [655–664](#)
- hexadecimal/binary conversion chart, [647](#)
- on-link prefixes, [703–704](#)
- LLA, [680–684](#)
- loopback addresses, [689](#)
- modified EUI-64, [674–679](#), [682–683](#)
- multicast addresses, [684–688](#)
- NA, [699–702](#), [705](#)
- NDP, [698–699](#)
 - NA*, [699–702](#), [705](#)
 - NS*, [699–702](#), [705](#)
 - RA*, [702–704](#)
 - RS*, [702–704](#)
 - summary*, [705–706](#)
- next-hop addresses, static network routes, [730–735](#)
- NS, [699–702](#), [705](#)
- permanent IPv6 addresses, [712](#)
- prefix discovery, [699](#)
- private addresses, [655–664](#)
- public addresses, [656–657](#)
- RA, [702–704](#)

- RS, [702–704](#)
- scopes, [686–687](#)
- SLAAC, [710–714](#)
- solicited-node multicast addresses, [684](#), [687–688](#)
- special addresses, [680](#)
- subnet prefixes, [649–652](#)
- temporary IPv6 addresses, [712–714](#)
- testing connectivity, [716–718](#)
- troubleshooting, [714–718](#)
- ULA, [656](#), [664–666](#)
- unicast IP addresses, [670–671](#)
 - dynamic*, [679–680](#)
 - static*, [671–679](#)
- unspecified addresses, [689](#)
- verifying host connectivity, [718–719](#)

adjacencies, OSPF neighbor, [612–617](#)

adjacent neighbors, [553](#)

adjacent-layer interaction, TCP/IP networking models, [25–26](#)

advanced distance vector (hybrid) algorithms, [543](#)

advertisements (network), IP routing, [78](#)

aging MAC addresses, clearing, [126–127](#)

alternate ports, RSTP, [241–243](#)

anycast IPv6 addresses, IPv6 routing, [672–689](#)

APIPA IP addresses (169.254.x.x), [490](#)

application layer, TCP/IP networking models, [23](#)

- HTTP, [23–24](#)

- web pages, accessing, [23](#)

areas, OSPF, [555–557](#)

- multi-area OSPF, [555–557](#), [574–575](#)

- single-area OSPF*, [555–557](#), [565–566](#)

ARP (Address Resolution Protocol)

- network layer, [80–81](#)
- proxy, static routes, [443](#)
- tables, routers, [439–440](#)

ASN (AS Numbers), [541](#)

assigning

- subnets to different locations, [320–321](#)
- VLAN to interfaces, [197–201](#), [213](#)

authentication servers, switch security, [141–142](#)

auto-MDIX (Automatic Medium-Dependent Interface Crossover), [49](#), [170–172](#)

autonegotiation

- 10/100 ports, [161](#), [162](#)
- 10/100/1000 ports, [161](#), [162](#), [163](#)
- full duplex transmissions, [161](#)
- half duplex transmissions, [161](#)
- LAN hubs, [165](#)
- parallel detection logic, [163–164](#)
- routers, Ethernet interface autonegotiation, [420–422](#)
- switches, [161–169](#)

AS (Autonomous Systems), [542–543](#)

autostate setting, SVI, [467–469](#)

Aux ports, [423](#)

B

backbone areas, [556](#)

backbone routers, [556](#)

backup ports, RSTP, [241](#), [244](#)

backups, BDR, [552–553](#)

bandwidth

- interface bandwidth, [599](#), [600](#)
- reference bandwidth, [599](#), [600–601](#)
- router serial interfaces, [423](#)

basic passwords, configuring, [137–138](#)

BDR (Backup Designated Routers), [552–553](#)

BDR/DR elections, OSPF, [590–592](#)

Bellman-Ford (distance vector) algorithms, [543](#)

BID (Bridge ID), [229–231](#), [261–262](#)

binary/hexadecimal conversion chart, [647](#)

binary masks, [340](#)

- DDN mask conversions, [342–344](#)
- prefix mask conversions, [341–342](#)

binary math analysis, subnet ID/address, [362–366](#)

blocking state

- STP, [120–121](#), [238–239](#)
- STP/RSTP, [225](#), [229](#)

Boolean AND/OR operations, subnet masks, [367](#)

BPDU (Bridge Protocol Data Units)

- STP/RSTP, [230–231](#), [236–237](#)
- superior BPDU, [251](#)
- tunneling, [266](#)

BPDU Filter, [248–250](#), [274–278](#)

BPDU Guard, [248](#), [269–274](#)

bridging tables. *See* [MAC addresses](#)

broadcast addresses, subnet, [358](#), [359](#), [361](#)

broadcast domains, [191–192](#)

broadcast flags, [489](#)

broadcast frames, flooding, [119–120](#)

broadcast networks, 586–592

broadcast storms, 225–227

broken state, STP, 251

building Ethernet LAN

data-link layer protocols, 53–57

fiber builds, 50–53

UTP builds, 43–49

C

cabling

auto-MDIX, 49

Cisco IOS XE CLI connections, 93–94

crossover cabling, 48–49

Ethernet cabling

auto-MDIX, 49

pinouts, 48

fiber cabling

802.3 10-Gbps fiber standards, 52

cladding, 50–51

components of, 50–51

Ethernet LAN builds, 50–53

multimode fiber, 51–53

optical transmitters, 50–51

single-mode fiber, 51–53

pinouts, choosing, 48–49

rollover cabling, console connections, 93–94

straight-through cabling, pinouts, 47

UTP

10BASE-T pinouts, 46–47

100BASE-T pinouts, 46–47

1000BASE-T pinouts, 49
cabling comparisons, 52–53
data transmission, 43–44
Ethernet LAN builds, 43–49
Ethernet links, 44–46

CAM tables. *See* **MAC addresses**

campus LAN, 114

Catalyst Edge Platform, 411

certification exams

additional content, 751
Cisco Certification Roadmap, 751–752
release dates/information, 751–752, 754
study plans, 753–754
updates, 751–752

changing interface states with STP, 238–239

channel-group configuration command, 281–284

choosing

cabling pinouts, 48–49
designated ports for LAN segments, 234–235
dynamic ranges for subnetting, 321–322
IP networks, subnetting, 314
masks, subnetting, 314–318
root ports, 232–234
static ranges for subnetting, 321–322
subnet masks, to meet requirements, 380–386

CIDR blocks

classful networks, 326–328
subnet masks and, 351–352

CIDR masks. *See* **prefix masks**

Cisco Catalyst switches, 90

9200 model switches, [91](#), [94](#)

CLI, accessing, [90](#)

Cisco Certification Roadmap, [751–752](#)

Cisco IOS

enterprise routers, [409–410](#)

help features, [101–102](#)

software configuration, [103–104](#)

Cisco IOS XE

CLI

accessing, [91–101](#)

accessing in privileged (enable) mode, [96–98](#)

accessing in user mode, [96–98](#)

accessing with SSH, [96](#)

accessing with Telnet, [96](#)

cabling console connections, [93–94](#)

enterprise routers, [409–410](#)

terminal emulator configurations, [95](#)

Cisco Meraki switches, [90](#)

Cisco Nexus switches, [90](#)

cladding, [50–51](#)

classes, IPv4 networks, [328–330](#)

classful addressing, [348](#)

classful networks

CIDR blocks, [326–328](#)

classes, [328–330](#)

network broadcast addresses, [331](#), [333–334](#)

network ID, [331–334](#)

number of hosts, determining, [331](#)

practicing with, [334–335](#)

public IP networks, setting context of, [326–328](#)

- subnetting, [311–314](#)
- WHOIS records, [328](#)

classless addressing, [348](#)

clearing aging MAC addresses, [126–127](#)

CLI (Command-Line Interface), [88](#)

- accessing

 - from Cisco Catalyst switches, [90](#)*

 - password security, [98–99](#)*

 - from WebUI, [99–101](#)*

- Cisco IOS XE CLI

 - accessing, [91–101](#)*

 - accessing in privileged (enable) mode, [96–98](#)*

 - accessing in user mode, [96–98](#)*

 - accessing with SSH, [96](#)*

 - accessing with Telnet, [96](#)*

 - cabling console connections, [93–94](#)*

 - terminal emulator configurations, [95](#)*

- configuration mode, [103–104](#)

 - common configuration modes, [105–106](#)*

 - contexts, [104–106](#)*

 - interface command, [104–105](#)*

 - navigating between modes, [105–106](#)*

 - submodes, [104–106](#)*

- EXEC commands, [98](#)

- EXEC mode, [103–104](#)

- exec-timeout command, [152–153](#)

- help features, [101–102](#)

- history buffer commands, [151–152](#)

- logging synchronous command, [152–153](#)

- no ip domain-lookup command, [152–153](#)

- router CLI, accessing, [414–415](#)

- security, [134–135](#)
- software configuration, [103–104](#)

clock rates, router serial interfaces, [423](#)

collisions

- Ethernet hubs, [58–59](#)
- frame transmissions, [58–59](#)

commands

- channel-group configuration command, [281–284](#)
- com? command, [101](#)
- command ? command, [101](#)
- command parm <Tab> command, [102](#)
- command parm? command, [101](#)
- command parm1? command, [102](#)
- context-setting commands, [104–106](#)
- copy running-config startup-config command, [109](#)
- debug command, [103](#)
- description command, [172–173](#)
- editing, [102](#)
- EXEC commands, [98](#)
- exec-timeout command, [152–153](#)
- help commands, CLI, [101–102](#)
- history buffer commands, [151–152](#)
- hostname command, [109](#)
- interface command, [104–105](#)
- interface range command, [172–173](#)
- ip address command, [436–439](#)
- logging synchronous command, [152–153](#)
- network commands, OSPFv2, [564–565](#)
 - single-area OSPF configuration*, [565–566](#)
 - wildcard matching*, [566–568](#)
- no ip domain-lookup command, [152–153](#)

ping command

basics, 513–514

extended ping, testing LAN neighbors, 520–521

extended ping, testing reverse routes, 517–519

IP addresses, 522–524

IPv4 routing, 512, 513–524

IPv6 connectivity, 716–718

name resolution, 522–524

problem isolation, 513

strategies/results, 514–521

testing LAN neighbors, 519–520

testing longer routes, 514–517

testing reverse routes, 517–519

testing WAN neighbors, 521

productivity commands, 153

question mark (?) command, 101

recalling, 102

rejected commands example, enable (privileged) mode, 97–98

reload command, switch configurations, 109

show command, 103

show interfaces command, 124

shutdown command, 172–173

tracert command

IPv4 routing, 512, 524–527

IPv6 connectivity, 716–718

tracert command

basics, 524–525

extended traceroute, 526–527

operation of, 525–526

problem isolation, 524

verification commands, OSPFv2, 568–573

configuration mode, CLI, 103–104

- common configuration modes, [105–106](#)
- contexts, [104–106](#)
- interface command, [104–105](#)
- navigating between modes, [105–106](#)
- submodes, [103–106](#)

configuring

- Cisco IOS software, [103–104](#)
- data VLAN, [209–212](#)
- DHCP, [493–494](#)
 - client configurations*, [496–497](#)
 - switches, client configurations*, [495–496](#)
- DHCP Relay, [494](#)
- embedded switch ports, [478–480](#)
- EtherChannel
 - dynamic EtherChannels*, [284–287](#)
 - interface configuration consistency*, [287–289](#)
 - Layer 2 EtherChannel*, [281–284](#)
- IPv4
 - addressing, connected routes*, [435–439](#)
 - switches*, [149–151](#)
- Layer 3 Switch SVI, [464–466](#)
- OSPF
 - interface configurations*, [575–578](#)
 - RID*, [573–574](#)
 - single-area OSPF configuration*, [565–566](#)
- passwords, basic, [137–138](#)
- RID, OSPF, [573–574](#)
- ROAS, [458–461](#)
- RSTP, [259](#)
- static routes, [440–443](#)
- switches
 - autonegotiation*, [161–169](#)

- common configuration modes, 105–106*
- copying switch configurations, 109*
- duplex, manually setting, 169–170*
- erasing switch configurations, 109*
- interface configurations, 172–180*
- IPv4 configurations, 149–151*
- removing interface configurations, 174–176*
- speed, manually setting, 169–170*
- storing switch configurations, 106–108*

terminal emulators, 95

VLAN, 197–201

- data VLAN, 209–212*

- voice VLAN, 209–212*

connected routes

- IPv4, 426–427

- IPv6, 724–727

connectivity, high-speed Internet, 18–19

console passwords, 135–139

context-setting commands, 104–106

contexts, CLI configuration, 104–106

convergence

- dynamic routing protocols, 541, 542

- STP, convergence management, 237–238

converting subnet masks, 340–345

copy running-config startup-config command, 109

copying switch configurations, 109

costs

- default port costs, 235–236

- OSPFv2 metrics, 599–601

- port costs, STP, 266–268

root costs, STP, [266–268](#)
crossover cabling, [48–49](#)

D

DAD (Duplicate Address Detection), [705](#)

data center LAN, [114](#)

data encapsulation

steps of, [31–32](#)

terminology, [31–32](#)

data transmission

single-mode fiber cabling, [51](#)

UTP, [43–44](#)

data VLAN

configuring, [209–212](#)

verifying, [209–212](#)

data-link layer

encapsulation, [74](#)

Ethernet LAN

consistency, [42–43](#)

protocols, [53–57](#)

TCP/IP networking models, [29–31](#)

data-only messages, HTTP, [24](#)

DDN (Dotted-Decimal Notation), [367](#)

binary mask conversions, [342–344](#)

magic numbers, [370](#)

prefix mask conversions, [344](#)

subnet masks, [318, 341](#)

Dead intervals, [602–604, 614–615](#)

debug command, [103](#)

default gateways

- DHCP, [496](#)

- hosts, [148–149](#)

- switches, [148–149](#)

default masks, IP addresses, [330](#)**default port costs, [235–236](#)****default routers, [73](#)****default routes**

- OSPFv2, [597–599](#)

- static routes, [443–445](#)

description command, switch interface configuration, [172–173](#)**design view, subnetting, [303–304](#)****designated ports, choosing LAN segments, [234–235](#)****designated switches, STP/RSTP, [229](#)****detecting errors, Ethernet, [56–57](#)****DHCP (Dynamic Host Configuration Protocol), [488](#)**

- acknowledgement messages, [489](#)

- address masks, [496](#)

- APIPA IP addresses (169.254.x.x), [490](#)

- broadcast flags, [489](#)

- concepts, [488–490](#)

- configuring, [493–494](#)

 - client configurations*, [496–497](#)

 - DHCP Relay*, [494](#)

 - switches, client configurations*, [495–496](#)

- default gateways, [496](#)

- discover messages, [489–490](#)

- IPv6 hosts, [706–710](#)

- offer messages, [489–490](#)

- request messages, [489](#)

servers

preconfiguration, 493

stored information, 492–493

stateful DHCPv6, 706–710

stateless DHCPv6, 707, 710, 711–712

subnetting, 321–322

switches, learning IP addresses, 150

DHCP Relay, 490–492, 494

difficult subnet masks, 368, 369–371

Dijkstra SPF algorithm

LSDB, 547–548

route calculation, 553–555

disabled state, STP, 239

disabled/undefined VLAN, 213–215

discarding state, RSTP, 243

discover messages, 489–490

distance vector (Bellman-Ford) algorithms, 543

distribution switches as root switches, 259

dividing IP addresses with subnet masks, 346–348

DNS (Domain Name System)

name resolution requests, 79–80, 152–153

network layer, 79–80

server lists, 500

switches, 149, 152–153

DP (Designated Ports), STP/RSTP, 229

DR/BDR elections, OSPF, 590–592

dual stacks, IPv6 addressing, 671

duplex mismatches, switch interface configurations, 177–178

duplex of switches, manually setting, 169–170

duplex transmissions, autonegotiation, [161](#)
dynamic auto mode, trunking, [203–204](#)
dynamic desirable mode, trunking, [203](#)
dynamic EtherChannels, configuring, [284–287](#)
dynamic ranges, choosing for subnetting, [321–322](#)

dynamic routing protocols

- convergence, [541](#), [542](#)
- EIGRP, [543–545](#)
- features, [540](#)
- functions, [541–542](#)
- ICMPv6, [642](#)
- IGP, [542–545](#)
- IGRP, [543](#)
- NDP, [642](#)
- OSPF, [543–545](#)
 - AD*, [623](#)
 - areas*, [555–557](#)
 - BDR*, [552–553](#)
 - broadcast networks*, [586–592](#)
 - concepts*, [546](#)
 - design terminology*, [556](#)
 - Dijkstra SPF algorithm*, [553–555](#)
 - DR/BDR elections*, [590–592](#)
 - ECMP routing*, [621–622](#)
 - equal-cost routes*, [621–622](#)
 - Hello packets*, [548–549](#)
 - interface configurations*, [575–578](#)
 - IP forwarding*, [625–628](#)
 - IP routing table*, [628–630](#)
 - longest prefix matching*, [625–630](#)
 - LSA*, [546–548](#), [557–560](#)

- LSDB, 546, 547–548, 550–553*
- MTU, troubleshooting, 618*
- multi-area OSPF, 574–575*
- neighbors, 546, 548–553*
- neighbors, requirements, 611–612*
- neighbors, troubleshooting adjacencies, 612–617*
- neighbors, troubleshooting missing routes, 619–621*
- neighbors, troubleshooting priority 0, 618–619*
- network types, troubleshooting, 618*
- operation of, 546*
- point-to-point networks, 586, 592–594*
- priority, 590–592*
- RID, 548*
- route calculation, 553–555*
- route selection, 621–630*
- routing, troubleshooting, 618–621*
- shutting down, 615–617*
- topologies, 546–547*

OSPFv2

- Dead intervals, 602–604, 614–615*
- default routes, 597–599*
- Hello intervals, 602–604, 614–615*
- implementing with interface subcommands, 576*
- interface bandwidth, 599, 600*
- metrics (cost), 599–601*
- network commands, 564–568*
- passive interfaces, 594–597*
- reference bandwidth, 599, 600–601*
- verification commands, 568–573*

OSPFv3, 642

- path selection, 540*

RIPv2, 543–545

dynamic unicast IP addresses, IPv6 routing, [679–680](#)

E

easy subnet masks, [367–369](#)

echo requests, ICMP, [81–82](#)

ECMP routing, OSPF, [621–622](#)

edge ports, RSTP, [245](#)

editing, commands, [102](#)

EGP (Exterior Gateway Protocols), [542–543](#)

EIGRP (Enhanced Interior Gateway Routing Protocol), [543–545](#)

EIGRPv6 (EIGRP version 6), [645–646](#)

election process, root switches, [231](#)

embedded switch ports

- configuring, [478–480](#)

- identifying, [481–482](#)

- verifying routing, [480–481](#)

EMI (Electromagnetic Interference), [43–44](#)

emulators (terminal), configuring, [95](#)

enable (privileged) mode

- Cisco IOS XE CLI access, [96–98](#)

- rejected commands example, [97–98](#)

enable passwords, [135–139](#)

enable secret passwords, [137](#)

encapsulating

- data

 - steps of*, [31–32](#)

 - terminology*, [31–32](#)

- data-link layer, [74](#)

IP packets, [68–69](#)

network layer, [74](#)

end-users, high-speed Internet connections, [18–19](#)

enterprise LAN, [40–41](#)

enterprise networks (internetworks), [19](#), [304](#)

enterprise routers, installing, [408–409](#), [412](#)

Catalyst Edge Platform, [411](#)

IOS, [409–410](#)

IOS XE, [409–410](#)

ISR, [410–411](#)

OS, [409–410](#)

equal-cost routes, [621–622](#)

erasing switch configurations, [109](#)

error detection, Ethernet, [56–57](#)

error recovery, TCP/IP networking models, [25](#)

EtherChannel

dynamic EtherChannels, configuring, [284–287](#)

interface configuration consistency, [287–289](#)

Layer 2 EtherChannel, configuring, [281–284](#)

load distribution, [289–291](#)

STP, [246](#)

Ethernet

10BASE-T, UTP pinouts, [46–47](#)

100BASE-T, UTP pinouts, [46–47](#)

1000BASE-T pinouts, UTP pinouts, [49](#)

addressing, [54–55](#)

cabling, auto-MDIX, [49](#)

crossover cabling, pinouts, [48](#)

error detection, [56–57](#)

Ethernet Type (EtherType) fields, [56](#)

FCS fields, [56–57](#)

fiber cabling, [52–53](#)

frame format, [53–54](#)

frame transmissions

collisions, [58–59](#)

full duplex transmissions, [57–58](#), [59](#)

half duplex transmissions, [58–60](#)

hubs, [57–60](#)

switches, [57–60](#)

frames, [30](#)

header fields, [53–54](#), [67](#)

hubs

collisions, [58–59](#)

frame transmissions, [57–60](#)

half duplex transmissions, [58–60](#)

LAN, [36](#)

data-link layer consistency, [42–43](#)

data-link layer protocols, [53–57](#)

fiber builds, [50–53](#)

frame transmissions, [57–60](#)

physical layer standards, [41–42](#)

UTP builds, [43–49](#)

LAN, switching

analyzing, [121–122](#)

finding MAC addresses in tables, [124–126](#)

flooding unknown unicast/broadcast frames, [119–120](#)

forwarding known unicast frames, [116–118](#)

forward-versus filter decisions, [118](#)

interfaces, [123–124](#)

learning MAC addresses, [118–119](#), [122–123](#)

loop prevention, [120–121](#)

MAC address tables, [116–118](#)

MAC addresses with multiple switches, 127–128

managing MAC address tables, 126–127

summary, 121

verifying, 121–123

Layer 3 EtherChannels, Layer 3 Switch Routed Ports, 473–477

network layer protocols, identifying, 56

NIC, 47

OUI, 54–55

point-to-point, 60

routers, Ethernet interface autonegotiation, 420–422

shared media, 60

static routes, Ethernet outgoing interfaces, 443

switches, frame transmissions, 57–60

transceivers, 45

types of, 41–42

unicast addressing, 54–55

UTP, Ethernet links, 44–46

VLAN, 188

access interfaces, 197–198

assigning to interfaces, 197–201, 213

broadcast domains, 191–192

configuring, 197–201

creating, 197–201

data VLAN, 209–212

disabled/undefined VLAN, 212–218

forwarding data between VLAN, 195–197

native VLAN, 195

phone connections, 207–212

routing between VLAN, 195–197

static access interfaces, 197–198

troubleshooting, 212–218

trunking, 192–195, 201–207, 215–218

undefined/disabled VLAN, 213–215

voice VLAN, 209–212

VTP, 194, 201–202

WAN, 64, 69

IP routing, 70–71

Layer 2 services, 70

EUI-64 (modified), IPv6 addressing, 674–679, 682–683

exams

additional content, 751

Cisco Certification Roadmap, 751–752

release dates/information, 751–752, 754

study plans, 753–754

updates, 751–752

EXEC commands, 98

EXEC mode, CLI, 103–104

exec-timeout command, 152–153

existing subnets

difficult subnet masks, 369–373

easy subnet masks, 367–369

practicing with, 373

expanding IPv6 addresses, 648–649

extended ping, testing

LAN neighbors, 520–521

reverse routes, 517–519

extended traceroute, 526–527

external authentication servers, switch security, 141–142

F

FCS (Frame Check Sequence) fields, 56–57

fiber cabling

- 802.3 10-Gbps fiber standards, [52](#)
- cladding, [50–51](#)
- components of, [50–51](#)
- Ethernet, [52–53](#)
- Ethernet LAN builds, [50–53](#)
- multimode fiber, [51–53](#)
- optical transmitters, [50–51](#)
- single-mode fiber, [51–53](#)

filtering, forward-versus filter decisions, [118](#)**finding**

- MAC addresses in tables, [124–126](#)
- range of usable subnet addresses, [367](#)
- subnet ID/addresses, [369–371](#), [386–396](#)

floating static routes

- IPv4 routing [447–448](#)
- IPv6 network routing, [739–741](#)

flooding

- routers, [546](#)
- switches, [119–120](#)
- unknown broadcast/unicast frames, [119–120](#)

formatting IP addresses, [330](#)**forwarding**

- data between VLAN, [195–197](#)
- unicast frames, Ethernet LAN switching, [116–118](#)

forwarding state

- RSTP, [225](#), [229](#)
- STP, [120–121](#), [225](#), [229](#), [238–239](#)

forward-versus filter decisions, Ethernet LAN switching, [118](#)**frames, [30](#), [31–32](#)**

- collisions, [58–59](#)
- Ethernet frame format, [53–54](#)
- FCS fields, [56–57](#)
- full duplex transmissions, [57–58](#), [59](#)
- half duplex transmissions, [58–60](#)
- hub transmissions, [57–60](#)
- looping frames, [225–227](#)
- multiple frame transmissions, STP, [227](#)
- switch transmissions, [57–60](#)

full (unabbreviated) IPv6 addresses, [646–647](#)

full duplex transmissions

- autonegotiation, [161](#)
- Ethernet frame transmissions, [57–58](#), [59](#)

fully-adjacent neighbors, [553](#)

G

gateways, default. *See* [default routers](#)

GET requests, HTTP, [24](#)

global ID, ULA, [665–666](#)

grouping, [73](#)

- hosts in subnets, [304–305](#)
- IP addressing, [76](#)

GUA (Global Unicast Addresses), [655–664](#)

H

half duplex transmissions

- autonegotiation, [161](#)
- frame transmissions, [58–60](#)

HDLC (High-level Data Link Control)

framing, [65–67](#)

header fields, [65–67](#)

leased-line WAN, [66–67](#)

header fields

Ethernet frames, [53–54](#), [67](#)

HDLC, [65–67](#)

IP, [77](#)

headers, IPv6, [643](#)

Hello BPDUs, STP/RSTP, [230–231](#), [236–237](#)

Hello, inferior, [231](#)

Hello intervals, [602–604](#), [614–615](#)

help features, CLI, [101–102](#)

hexadecimal/binary conversion chart, [647](#)

high-speed Internet connections, end-user perspectives, [18–19](#)

history buffer commands, [151–152](#)

host routes, static, [445–447](#)

hostname command, [109](#)

hostnames, [79](#)

hosts

classful networks, determining number of hosts, [331](#)

default gateways, [148–149](#)

IPv4 addressing

DHCP, [488–497](#)

Linux settings, [504–506](#)

macOS settings, [502–504](#)

settings, [497–499](#)

troubleshooting settings, [506–509](#)

Windows IP settings, [499–502](#)

IPv6 addressing

- DAD*, [705](#)
- DHCP*, [706–710](#)
- on-link prefixes*, [703–704](#)
- NA*, [699–702](#), [705](#)
- NDP*, [698–699](#)
- NDP*, *NA*, [699–702](#), [705](#)
- NDP*, *NS*, [699–702](#), [705](#)
- NDP*, *RA*, [702–704](#)
- NDP*, *RS*, [702–704](#)
- NDP*, *summary*, [705–706](#)
- NS*, [699–702](#), [705](#)
- permanent IPv6 addresses*, [712](#)
- prefix discovery*, [699](#)
- RA*, [702–704](#)
- RS*, [702–704](#)
- SLAAC*, [710–714](#)
- static host routes*, [737–739](#)
- temporary IPv6 addresses*, [712–714](#)
- testing connectivity*, [716–718](#)
- troubleshooting*, [714–718](#)
- verifying host connectivity*, [718–719](#)
- network layer routing (forwarding) logic, [72](#)
- routing logic (summary), [429](#)
- stateful DHCPv6, [706–710](#)
- stateless DHCPv6, [707](#), [710](#), [711–712](#)
- subnetting
 - determining number of hosts*, [307](#)
 - grouping in*, [304–305](#)
- verifying connectivity, IPv6 addressing, [718–719](#)

HTTP (HyperText Transfer Protocol)

- data-only messages, [24](#)
- GET requests, [24](#)

- overview of, [23](#)
- protocol mechanisms, [23–24](#)
- replies, [24](#)
- web pages, [24](#)

hubs

- collisions, [58–59](#)
- Ethernet frame transmissions, [57–60](#)

hybrid (advanced distance vector) algorithms, [543](#)

I

ICMP (Internet Control Message Protocol)

- echo replies, [513](#)
- echo requests, [81–82, 513](#)

ICMPv6 (Internet Control Message Protocol version 6), [642](#)

ID/addresses, subnetting, [308, 360](#)

- binary math analysis, [362–366](#)
- finding, [386–396](#)

identifying

- embedded switch ports, [481–482](#)
- network layer protocols, with EtherType fields, [56](#)
- port costs, [266–268](#)
- roles, [266–268](#)
- root switches, [263–266](#)
- states, [266–268](#)
- switch priority, [263–266](#)

IEEE (Institute of Electrical and Electronics Engineers)

- 802.3 10-Gbps fiber standards, [52](#)
- 802.3 Ethernet header and trailer fields, [53–54](#)
- autonegotiation, [161–169](#)
- default port costs, [235–236](#)

IGP (Interior Gateway Protocols), 542–545

advanced distance vector (hybrid) algorithms, 543

distance vector (Bellman-Ford) algorithms, 543

EIGRP, 543–544

ICMPv6, 642

IGRP, 543

link-state, 543

NDP, 642

OSPF, 543–545

AD, 623

areas, 555–557

BDR, 552–553

broadcast networks, 586–592

concepts, 546

design terminology, 556

Dijkstra SPF algorithm, 553–555

DR/BDR elections, 590–592

ECMP routing, 621–622

equal-cost routes, 621–622

Hello packets, 548–549

interface configurations, 575–578

IP forwarding, 625–628

IP routing table, 628–630

longest prefix matching, 625–630

LSA, 546–548, 557–560

LSDB, 546, 547–548, 550–553

MTU, troubleshooting, 618

multi-area OSPF, 574–575

neighbors, 546, 548–553

neighbors, requirements, 611–612

neighbors, troubleshooting adjacencies, 612–617

neighbors, troubleshooting missing routes, 619–621

- neighbors, troubleshooting priority 0, 618–619*
- network types, troubleshooting, 618*
- operation of, 546*
- point-to-point networks, 586, 592–594*
- priority, 590–592*
- RID, 548*
- route calculation, 553–555*
- route selection, 621–630*
- routing, troubleshooting, 618–621*
- shutting down, 615–617*
- topologies, 546–547*

OSPFv2

- Dead intervals, 602–604, 614–615*
- default routes, 597–599*
- Hello intervals, 602–604, 614–615*
- implementing with interface subcommands, 576*
- interface bandwidth, 599, 600*
- metrics (cost), 599–601*
- network commands, 564–568*
- passive interfaces, 594–597*
- reference bandwidth, 599, 600–601*
- verification commands, 568–573*

OSPFv3, 642

RIPv2, 543–545

IGRP (Interior Gateway Routing Protocol), 543

inferior Hello, 231

installing

- enterprise routers, 408–409, 412*
 - Catalyst Edge Platform, 411*
 - IOS, 409–410*
 - IOS XE, 409–410*

ISR, 410–411

OS, 409–410

SOHO routers, [412–413](#)

interarea routes, [556](#)

interesting octets (subnet masks), predictability in, [368–369](#)

interface command, [104–105](#)

interface ID, LAN switches, [91](#)

interface range command, switch interface configuration, [172–173](#)

interface subcommands, OSPFv2 implementation, [576](#)

interfaces

bandwidth, [599](#), [600](#)

configuring

EtherChannel, [287–289](#)

OSPF, [575–578](#)

routed interfaces, switches, [470–473](#)

routers

bandwidth, serial interfaces, [423](#)

clock rates, serial interfaces, [423](#)

Ethernet interface autonegotiation, [420–422](#)

IPv4 addressing, [418–419](#)

listing interfaces, [416–417](#)

serial interfaces, [423](#)

status codes, [417–418](#)

show interfaces command, [124](#)

states, changing with STP, [238–239](#)

switches, [123–124](#), [172](#)

administratively controlling interface state, [172–173](#)

description command, [172–173](#)

duplex mismatches, [177–178](#)

interface range command, [172–173](#)

late collisions, [163](#)

- layer 1 problems, 178–180*
- removing, 174–176*
- routed interfaces, 470–473*
- shutdown command, 172–173*
- states, 234–235*
- status codes, 176–177*
- VLAN assignments, 197–201, 213*

VLAN interfaces, 464–466

internal routers, 556

Internet, high-speed connections, 18–19

Internet layer. See network layer, TCP/IP networking models

internetworks (enterprise networks), 19, 304

intra-area routes, 556

IOS

- enterprise routers, 409–410
- help features, 101–102
- software configuration, 103–104

IOS XE

CLI

- accessing, 91–101*
- accessing in privileged (enable) mode, 96–98*
- accessing in user mode, 96–98*
- accessing with SSH, 96*
- accessing with Telnet, 96*
- cabling console connections, 93–94*
- enterprise routers, 409–410
- terminal emulator configurations, 95

IP (Internet Protocol). See also IPv4; IPv6

addressing

- APIPA IP addresses (169.254.x.x), 490*

- ARP*, [80–81](#)
- basics*, [27–28](#)
- configuring, connected routes*, [435–439](#)
- IP routing*, [76–77](#)
- troubleshooting, ping command*, [522–524](#)
- forwarding, OSPF, [625–628](#)
- groupings, [73](#)
- ip address command, [436–439](#)
- network broadcast addresses, [331](#), [333–334](#)
- networks, [73](#)
- no ip domain-lookup command, [152–153](#)
- packets, encapsulating/de-encapsulating, routing, [68–69](#)
- postal service analogy, [26–27](#)
- public IP networks
 - setting context of*, [326–328](#)
 - subnetting*, [311–313](#)
- routing, [71–72](#), [428](#)
 - AD*, [623](#)
 - basics*, [28–29](#)
 - default routers*, [73](#)
 - dynamic routing protocols*. *See separate entry*
 - ECMP routing*, [621–622](#)
 - encapsulating/de-encapsulating IP packets*, [68–69](#)
 - equal-cost routes*, [621–622](#)
 - Ethernet WAN*, [70–71](#)
 - IP addressing*, [76–77](#)
 - LAN*, [67–69](#), [73–75](#)
 - network advertisements*, [78](#)
 - network layer routing (forwarding), logic*, [72–73](#)
 - OSPF, AD*, [623](#)
 - protocols*, [77–78](#)
 - route selection, OSPF*, [621–630](#)

- tables, 73, table, 628–630*
- troubleshooting, IP addresses, 522–524*
- troubleshooting, name resolution, 522–524*
- troubleshooting, ping command, 512, 513–527*
- troubleshooting, SSH, 527–530*
- troubleshooting, Telnet, 527–530*
- troubleshooting, testing LAN neighbors, 519–521*
- troubleshooting, testing longer routes, 514–517*
- troubleshooting, testing reverse routes, 517–519*
- troubleshooting, testing WAN neighbors, 521*
- troubleshooting, traceroute command, 512, 524–527*
- WAN, 67–69, 73–75*

- subnetting, 73, 76, 314

- switches, 147–149, 150

- telephony ports, 208, 212

- unicast IP addresses, CIDR blocks, 327

ip address command, 436–439

IPv4 (Internet Protocol version 4)

- addresses

- APIPA IP addresses (169.254.x.x), 490*

- classes, 328–330*

- default masks, 330*

- exhaustion timeline, 641–642*

- formats, 330*

- hosts, DHCP, 488–497*

- hosts, Linux settings, 504–506*

- hosts, macOS settings, 502–504*

- hosts, settings, 497–499*

- hosts, troubleshooting settings, 506–509*

- hosts, Windows IP settings, 499–502*

- router interfaces, 418–419*

troubleshooting, ping command, 522–524

classful networks

CIDR blocks, 326–328

classes, 328–330

determining number of hosts, 331

network broadcast addresses, 331, 333–334

network ID, 331–334

practicing with, 334–335

public IP networks, setting context of, 326–328

subnetting, 311–314

WHOIS records, 328

hosts, addressing

DHCP, 488–497

Linux settings, 504–506

macOS settings, 502–504

settings, 497–499

troubleshooting settings, 506–509

Windows IP settings, 499–502

ip address command, 436–439

routers, support for, 413–423

routing

ARP tables, 439–440

connected routes, 426–427

example of, 431–435

host routing logic (summary), 429

ip address command, 436–439

IP addressing, configuring with connected routes, 435–439

process reference, 429–431

routing logic (summary), 430–431

static routes, 426–427

static routes, configuring, 440–443

- static routes, Ethernet outgoing interfaces, 443*
- static routes, floating static routes, 447–448*
- static routes, proxy ARP, 443*
- static routes, static default routes, 443–445*
- static routes, static host routes, 445–447*
- static routes, static network routes, 441–442*
- static routes, troubleshooting, 443–445*
- tables, 426–427*
- troubleshooting, IP addresses, 522–524*
- troubleshooting, name resolution, 522–524*
- troubleshooting, ping command, 512, 513–524*
- troubleshooting, SSH, 527–530*
- troubleshooting, Telnet, 527–530*
- troubleshooting, testing LAN neighbors, 519–521*
- troubleshooting, testing longer routes, 514–517*
- troubleshooting, testing reverse routes, 517–519*
- troubleshooting, testing WAN neighbors, 521*
- troubleshooting, traceroute command, 512, 524–527*
- VLAN, Layer 3 Switch Routed Ports, 455, 469–477*
- VLAN, Layer 3 Switch SVI, 455, 464–469*
- VLAN, ROAS, 457–464*
- VLAN, Router 802.1Q Trunks, 454, 457–464*
- VLAN, Router LAN Switch Ports, 455, 477–482*

subnetting, 302

- assigning to different locations, 320–321*
- broadcast addresses, 358, 359, 361*
- calculating based on IPv4 format, 349–350*
- choosing dynamic ranges, 321–322*
- choosing IP networks, 314*
- choosing static ranges, 321–322*
- classful addressing, 348*
- classful networks, 311–314*

- classless addressing, 348*
- DDN masks, 367, 370*
- defined, 302–303*
- defining, 358*
- defining size of subnets, 308–310*
- design choices, 309–311*
- design view, 303–304*
- determining number of hosts, 307*
- determining number of subnets, 305–307*
- DHCP, 320–321*
- difficult subnet masks, 368*
- difficult subnet masks, finding subnet ID/addresses, 369–371*
- dividing IP addresses, 346–348*
- easy subnet masks, 367–369*
- existing subnets, difficult subnet masks, 369–373*
- existing subnets, easy subnet masks, 367–369*
- existing subnets, practicing with, 373*
- grouping hosts, 304–305*
- ID/addresses, 308, 360*
- ID/addresses, binary math analysis, 362–366*
- ID/addresses, finding in difficult subnet masks, 369–371*
- identifying design choices, 345–346*
- listing subnets, 318–320*
- magic numbers, 370, 373–374, 388–389*
- masks, 314–318, 387–388*
- masks, binary masks, 340, 341–344*
- masks, Boolean AND/OR operations, 367*
- masks, choosing to meet requirements, 380–386*
- masks, CIDR blocks, 351–352*
- masks, conversions, 340–345*
- masks, DDN, 318, 341*

- masks, DDN masks, 342–344*
- masks, finding ID addresses, 386–396*
- masks, formats of (overview), 340–341*
- masks, magic numbers, 370, 373–374, 388–389*
- masks, octet values, 342–343*
- masks, practicing with, 350–351*
- masks, prefix masks, 341–342, 344*
- operational view, 303–304*
- planning implementations, 320*
- predictability in interesting octets, 368–369*
- private IP networks, 313–314*
- public IP networks, 311–313*
- range of usable addresses, 361, 367*
- resident subnets, 358–359*
- unicast IP addresses, 358*
- VLSM, 309–311*

switches

- configuring, 149–150*
- security, remote access, 146–147*
- verifying configurations, 150–151*

unicast IP addresses, CIDR blocks, 327

VLAN routing

- Layer 3 Switch Routed Ports, 455, 469–477*
- Layer 3 Switch SVI, 455, 464–469*
- ROAS, 457–464*
- Router 802.1Q Trunks, 454, 457–464*
- routing, Router LAN Switch Ports, 455, 477–482*

IPv6 (Internet Protocol version 6), 640

addressing

- anycast addresses, 672–689*
- configuration summary, 690–691*
- DAD, 705*

DHCP, [706–710](#)
dual stacks, [671](#)
on-link prefixes, [703–704](#)
LLA, [680–684](#)
loopback addresses, [689](#)
modified EUI-64, [674–679](#), [682–683](#)
multicast addresses, [684–688](#)
NA, [699–702](#), [705](#)
NDP, [698–699](#)
NDP, NA, [699–702](#), [705](#)
NDP, NS, [699–702](#), [705](#)
NDP, RA, [702–704](#)
NDP, RS, [702–704](#)
NDP, summary, [705–706](#)
next-hop addresses, static network routes, [730–735](#)
NS, [699–702](#), [705](#)
permanent IPv6 addresses, [712](#)
prefix discovery, [699](#)
RA, [702–704](#)
RS, [702–704](#)
scopes, [686–687](#)
SLAAC, [710–714](#)
solicited-node multicast addresses, [684](#), [687–688](#)
special addresses, [680](#)
static host routes, [737–739](#)
temporary IPv6 addresses, [712–714](#)
testing connectivity, [716–718](#)
troubleshooting, [714–718](#)
unicast IP addresses, [670–671](#)
unicast IP addresses, dynamic, [679–680](#)
unicast IP addresses, static, [671–679](#)
unspecified addresses, [689](#)

- verifying host connectivity, 718–719*
- GUA, [655–664](#)
- headers, [643](#)
- historical reasons for, [640–642](#)
- hosts
 - DAD, 705*
 - DHCP, 706–710*
 - NA, 699–702, 705*
 - NDP, 698–699*
 - NDP, NA, 699–702, 705*
 - NDP, NS, 699–702, 705*
 - NDP, RA, 702–704*
 - NDP, RS, 702–704*
 - NDP, summary, 705–706*
 - NS, 699–702, 705*
 - RA, 702–704*
 - RS, 702–704*
 - SLAAC, 710–714*
 - static host routes, 737–739*
 - troubleshooting, 714–718*
 - verifying host connectivity, 718–719*
- ICMPv6, [642](#)
- NDP, [642](#)
 - NA, 699–702, 705*
 - NS, 699–702, 705*
 - RA, 702–704*
 - RS, 702–704*
 - summary, 705–706*
- private addresses, [655–664](#)
- public addresses, [656–657](#)
- routing, [643–645](#)
 - abbreviating addresses, 647, 648–649*

AD, [727](#), [739–741](#)
address formats/conventions, [646](#)
address prefix lengths, [649](#)
anycast addresses, [672–689](#)
configuration summary, [690–691](#)
connected routes, [724–727](#)
dual stacks, [671](#)
EIGRPv6, [645–646](#)
expanding addresses, [648–649](#)
floating static routes, [739–741](#)
full (unabbreviated) addresses, [646–647](#)
hexadecimal/binary conversion chart, [647](#)
LLA, [680–684](#)
local routes, [724–725](#), [727–728](#)
loopback addresses, [689](#)
modified EUI-64, [674–679](#), [682–683](#)
MP BGP-4, [645–646](#)
multicast addresses, [684–688](#)
OSPFv3, [642](#), [645](#)
RIPng, [645](#)
scopes, [686–687](#)
solicited-node multicast addresses, [684](#), [687–688](#)
special addresses, [680](#)
static default routes, [735–737](#)
static host routes, [737–739](#)
static network routes, [728–735](#)
subnet prefixes, [649–652](#)
troubleshooting, [741–743](#)
unicast IP addresses, [670–671](#)
unicast IP addresses, dynamic, [679–680](#)
unicast IP addresses, static, [671–679](#)
unspecified addresses, [689](#)

ULA, [656](#), [664–666](#)
ISL VLAN trunking, [194–195](#)
ISR (Integrated Services Routers), [410–411](#)

L

LACP (Link Aggregation Control Protocol), [284](#)

LAN (Local Area Networks). *See also* [VLAN](#); [WLAN](#)

campus LAN, [114](#)

data center LAN, [114](#)

designated ports, choosing, [234–235](#)

enterprise LAN, [40–41](#)

Ethernet LAN, [36](#)

data-link layer consistency, [42–43](#)

data-link layer protocols, [53–57](#)

fiber builds, [50–53](#)

frame transmissions, [57–60](#)

physical layer standards, [41–42](#)

UTP builds, [43–49](#)

Ethernet LAN, switching

analyzing, [121–122](#)

finding MAC addresses in tables, [124–126](#)

flooding unknown unicast/broadcast frames, [119–120](#)

forward-versus filter decisions, [118](#)

forwarding known unicast frames, [116–118](#)

interfaces, [123–124](#)

learning MAC addresses, [118–119](#), [122–123](#)

loop prevention, [120–121](#)

MAC addresses with multiple switches, [127–128](#)

MAC address tables, [116–118](#), [126–127](#)

summary, [121](#)

- verifying, 121–123*
- hubs, autonegotiation, 165
- IP routing, 67–69
- neighbors, testing, 519–520
- network layer routing (forwarding), 73–75
- overview of, 38
- SOHO LAN, 39
- switches. *See also* Ethernet LAN, switching
 - concepts, 114*
 - interface ID, 91*
 - logic, 115–116*
- wired LAN. *See* Ethernet LAN
- WLAN, 18–19

late collisions, switch interface configurations, 163

layer 1 problems, switch interface configurations, 178–180

Layer 2 EtherChannel, configuring, 281–284

Layer 2 services, Ethernet WAN, 70

Layer 3 Switch Routed Ports

- Layer 3 EtherChannels, 473–477
- routed interfaces, 470–473
- VLAN routing, 455, 469–477

Layer 3 Switch SVI

- autostate setting, 467–469
- configuring, 464–466
- troubleshooting, 467–469
- verifying configurations, 466
- VLAN routing, 455, 464–469

learning

- learning state, STP, 239
- MAC addresses, 118–119, 122–123
- switch learning, 118–119

leased-line WAN, [64–65](#)

- conceptual view, [65](#)
- data-link details, [66–69](#)
- different names for, [65–66](#)
- HDLC, [66–67](#)
- IP routing, [67–69](#)
- physical details, [65–66](#)
- PPP, [66–67](#)
- routers, [67–69](#)
- telcos, [65–66](#)

link types, RSTP, [245](#)

link-state, [543](#)

Linux host settings, [504–506](#)

listening state, STP, [239](#)

listing

- router interfaces, [416–417](#)
- subnets, [318–320](#)

LLA (Link Local Addresses), IPv6 routing, [680–684](#)

load balancing, VLAN, [260](#)

local IPv6 routes, [724–725](#), [727–728](#)

local usernames/passwords, switch security, [139–141](#)

log messages, switches, [141](#)

logging synchronous command, [152–153](#)

longest prefix matching, IP forwarding, [625–630](#)

Loop Guard, STP, [251–253](#), [279–280](#)

loop prevention, Ethernet LAN switching, [120–121](#)

loopback IPv6 addresses, IPv6 routing, [689](#)

looping frames, [225–227](#)

LSA (Link State Advertisements), [546–548](#), [557–560](#)

LSDB (Link State Databases), 546, 550–553

Dijkstra SPF algorithm, 547–548

neighbors, 550–553

M

MAC addresses, 54–55

aging MAC addresses, clearing, 126–127

Ethernet LAN, switching, 116–118

finding in tables, 124–126

learning, 118–119, 122–123

managing tables, 126–127

STP/RSTP, 227

tables, routers, 481

tables, switches, 103, 127–128

macOS host settings, 502–504

magic numbers, 370, 373–374, 388–389

managing

convergence, STP, 237–238

MAC address tables, 126–127

masks, subnetting, 314–318, 545

binary masks, 340

DDN mask conversions, 342–344

prefix mask conversions, 341–342

Boolean AND/OR operations, 367

choosing to meet requirements, 380–386

conversions, 340–345

DDN masks, 318, 341

binary mask conversions, 342–344

DDN masks, 367

prefix mask conversions, 344

- design choices, identifying, [345–346](#)
- dividing IP addresses, [346–348](#)
- easy subnet masks, [367–369](#)
- finding ID/addresses, [386–396](#)
- formats of (overview), [340–341](#)
- magic numbers, [370](#), [373–374](#), [388–389](#)
- octet values, [342–343](#)
- predictability in interesting octets, [368–369](#)
- prefix masks, [341–342](#), [344](#)
- zero subnet, [387–388](#)

MaxAge timers, STP, [237](#), [238](#), [241](#)

metrics (cost), OSPFv2, [599–601](#)

modified EUI-64, IPv6 addressing, [674–679](#), [682–683](#)

moving between configuration modes, [105–106](#)

MP BGP-4 (Multiprotocol BGP version 4), [645–646](#)

MSTP (Multiple Spanning Tree Protocol), [260](#), [261](#)

MTU (Maximum Transmission Units)

- Ethernet frames, [54](#)

- OSPF, troubleshooting, [618](#)

multi-area OSPF, [555](#), [574–575](#)

multicast IPv6 addresses

- IPv6 routing, [684–688](#)

- scopes, [686–687](#)

- solicited-node multicast addresses, [684](#), [687–688](#)

multilayer switches. *See* [Layer 3 Switch SVI](#)

multimode fiber, [51–53](#)

multiple frame transmissions, STP, [227](#)

multiple spanning trees, need for, [260](#)

N

NA (Neighbor Advertisements), [699–702](#), [705](#)

name resolution

IPv4 routing, troubleshooting, [522–524](#)

requests, DNS, [79–80](#), [152–153](#)

native VLAN, [195](#)

navigating between configuration modes, [105–106](#)

NDP (Neighbor Discovery Protocol), [642](#), [698–699](#)

NA, [699–702](#), [705](#)

NS, [699–702](#), [705](#)

RA, [702–704](#)

RS, [702–704](#)

summary, [705–706](#)

neighbors

adjacencies, [553](#), [612–617](#)

fully-adjacent neighbors, [553](#)

LSDB, [550–553](#)

missing routes, troubleshooting, [619–621](#)

NA, [699–702](#), [705](#)

NDP, [642](#), [698–699](#)

NA, [699–702](#), [705](#)

NS, [699–702](#), [705](#)

RA, [702–704](#)

RS, [702–704](#)

summary, [705–706](#)

NS, [699–702](#), [705](#)

OSPF, [546](#)

priority 0, troubleshooting, [618–619](#)

RA, [702–704](#)

relationships, [553](#)

requirements, [611–612](#)

RS, [702–704](#)

network commands, OSPFv2, [564–565](#)

single-area OSPF configuration, [565–566](#)

wildcard matching, [566–568](#)

network layer, [79](#)

ARP, [80–81](#)

DNS, [79–80](#)

encapsulation, [74](#)

EtherType fields, identifying layers with, [56](#)

ICMP echo requests, [81–82](#)

IP routing, [76–77](#)

grouping addresses, [76](#)

header fields, [76–77](#)

LAN, [73–75](#)

protocols, [77–78](#)

subnets, [76](#)

WAN, [73–75](#)

ping command, [81–82](#)

routing (forwarding), logic, [72–73](#)

TCP/IP networking model, [22, 26](#)

addressing, basics, [27–28](#)

postal service analogy, [26–27](#)

outing, basics, [28–29](#)

network types (OSPF), troubleshooting, [618](#)

networking models

defined, [19–20](#)

OSI, [20–21](#)

TCP/IP

development of, [20–21](#)

history of, [20–21](#)

network layer, 22
overview of, 21–23
protocols, 22–23
RFC, 21

networks

advertisements, IP routing, 78
AS, 542–543
broadcast addresses, classful networks, 331, 333–334
broadcast networks, 586–592
classful networks
 broadcast addresses, 331, 333–334
 CIDR blocks, 326–328
 classes, 328–330
 determining number of hosts, 331
 network broadcast addresses, 331, 333–334
 network ID, 331–334
 practicing with, 334–335
 public IP networks, setting context of, 326–328
 subnetting, 311–314
 WHOIS records, 328
enterprise LAN, 40–41
enterprise networks (internetworks), example of, 19
Ethernet LAN, 36
 data-link layer consistency, 42–43
 data-link layer protocols, 53–57
 fiber builds, 50–53
 frame transmissions, 57–60
 physical layer standards, 41–42
 UTP builds, 43–49
ID, classful networks, 331–334
IP, 73
LAN, 36

- campus LAN, 114*
- data center LAN, 114*
- designated ports, choosing, 234–235*
- hubs, autonegotiation, 165*
- IP routing, 67–69*
- network layer routing (forwarding), 73–75*
- overview of, 38*
- SOHO LAN, 39*
- switches, interface ID, 91*
- switching, concepts, 114*
- switching, logic, 115–116*
- testing neighbors, 519–521*
- WLAN, 18–19*

LSA, 558

perspectives on, 18–19

point-to-point networks, 586, 592–594

private IP networks, subnetting, 313–314

public IP networks

- setting context of, 326–328*

- subnetting, 311–313*

VLAN, 188

- access interfaces, 197–198*

- assigning to interfaces, 197–201, 213*

- broadcast domains, 191–192*

- configuring, 197–201*

- creating, 197–201*

- data VLAN, 209–212*

- disabled/undefined VLAN, 212–218*

- forwarding data between VLAN, 195–197*

- load balancing with STP, 260*

- native VLAN, 195*

- phone connections, 207–212*

PVST+ [260](#), [261](#)

ROAS, [454](#)

ROAS, configuring, [458–461](#)

ROAS, troubleshooting, [463–464](#)

ROAS, verifying configurations, [461–463](#)

routing, Layer 3 Switch Routed Ports, [455](#), [469–477](#)

routing, Layer 3 Switch SVI, [455](#), [464–469](#)

routing, Router 802.1Q Trunks, [454](#), [457–464](#)

routing, Router LAN Switch Ports, [455](#), [477–482](#)

routing between VLAN, [195–197](#)

RPVST+ [260](#), [261](#)

static access interfaces, [197–198](#)

switches, IP settings, [147–149](#)

troubleshooting, [212–218](#)

trunking, [192–195](#), [201–207](#), [215–218](#)

undefined/disabled VLAN, [213–215](#)

voice VLAN, [209–212](#)

VTP, [194](#), [201–202](#)

WAN, [36](#), [64](#)

Ethernet WAN, [64](#), [69–71](#)

leased-line WAN, [64–69](#)

network layer routing (forwarding), [73–75](#)

testing neighbors, [521](#)

wired LAN. *See* [Ethernet LAN](#)

WLAN, [18–19](#)

next-hop IPv6 addresses, static network routes, [730–735](#)

next-hop routers, [434](#), [441](#), [442–443](#)

NIC (Network Interface Cards), Ethernet, [47](#)

no ip domain-lookup command, [152–153](#)

NS (Neighbor Solicitations), [699–702](#), [705](#)

O

octet values

- IPv4 address classes, [328–330](#)

- subnet masks, [342–343](#)

offer messages, [489–490](#)

on-link prefixes, [703–704](#)

operational view, subnetting, [303–304](#)

optical transmitters, [50–51](#)

OS (Operating Systems), routers, [409–410](#)

OSI networking models, [20–21](#), [32–34](#)

OSPF (Open Shortest Path First), [543–545](#)

- AD, [623](#)

- areas, [555–557](#)

 - multi-area OSPF*, [555](#), [574–575](#)

 - single-area OSPF*, [555–557](#), [565–566](#)

- BDR, [552–553](#)

- broadcast networks, [586–592](#)

- concepts, [546](#)

- configuring

 - interface configurations*, [575–578](#)

 - RID*, [573–574](#)

 - single-area OSPF*, [565–566](#)

- design terminology, [556](#)

- Dijkstra SPF algorithm

 - LSDB*, [547–548](#)

 - route calculation*, [553–555](#)

- DR/BDR elections, [590–592](#)

- ECMP routing, [621–622](#)

- equal-cost routes, [621–622](#)

- Hello packets, [548–549](#)
- interface configurations, [575–578](#)
- IP
 - forwarding*, [625–628](#)
 - routing table*, [628–630](#)
- longest prefix matching, [625–630](#)
- LSA, [546–548](#), [557–560](#)
- LSDB, [546](#), [547–548](#), [550–553](#)
- MTU, troubleshooting, [618](#)
- neighbors, [546](#), [548–553](#)
 - requirements*, [611–612](#)
 - troubleshooting*, *priority 0*, [618–619](#)
 - troubleshooting adjacencies*, [612–617](#)
 - troubleshooting missing routes*, [619–621](#)
- network types, troubleshooting, [618](#)
- operation of, [546](#)
- point-to-point networks, [586](#), [592–594](#)
- priority, [590–592](#)
- RID, [548](#), [573–574](#)
- routing
 - route selection*, [621–630](#)
 - troubleshooting*, [618–621](#)
- shutting down, [615–617](#)
- topologies, [546–547](#)
- wildcard matching, [566–568](#)

OSPFv2 (Open Shortest Path First version 2)

- Dead intervals, [602–604](#), [614–615](#)
- default routes, [597–599](#)
- Hello intervals, [602–604](#), [614–615](#)
- implementing with interface subcommands, [576](#)
- interface bandwidth, [599](#), [600](#)
- metrics (cost), [599–601](#)

- network commands, [564–565](#)
 - single-area OSPF configuration*, [565–566](#)
 - wildcard matching*, [566–568](#)
- passive interfaces, [594–597](#)
- reference bandwidth, [599](#), [600–601](#)
- verification commands, [568–573](#)

OSPFv3 (Open Shortest Path First version 3), [642](#), [645](#)

OUI (Organizationally Unique Identifiers), Ethernet addressing, [54–55](#)

P

packets, [27](#), [28–32](#)

PAGP (Port Aggregation Protocol), [284](#)

parallel detection logic, autonegotiation, [163–164](#)

passive interfaces, OSPFv2, [594–597](#)

passwords

- basic password configurations, [137–138](#)
- CLI access, [98–99](#)
- console passwords, [135–139](#)
- enable passwords, [135–139](#)
- enable secret passwords, [137](#)
- privileged mode, switches, [135–139](#)
- shared passwords, [135–139](#)
- simple security concepts, [135](#)
- switch security, user mode, [139–141](#)
- Telnet, [135–139](#)
- user mode, switches, [135–139](#)
- vty passwords, [135](#), [137](#)

path selection. *See* [routing](#), [IP](#)

permanent IPv6 addresses, [712](#)

phone connections, VLAN, [207–212](#)

physical layer

Ethernet LAN, standards, [41–42](#)

TCP/IP networking models, [29–31](#)

pin pairs

10BASE-T, [48](#)

100BASE-T, [48](#)

ping command

basics, [513–514](#)

extended ping

testing LAN neighbors, [520–521](#)

testing reverse routes, [517–519](#)

IP addresses, [522–524](#)

IPv4 routing, [512](#), [513–524](#)

IPv6 connectivity, [716–718](#)

name resolution, [522–524](#)

network layer, [81–82](#)

problem isolation, [513](#)

strategies/results, [514–521](#)

testing

LAN neighbors, [519–520](#)

longer routes, [514–517](#)

reverse routes, [517–519](#)

WAN neighbors, [521](#)

pinouts

choosing, [48–49](#)

crossover cabling, Ethernet cabling pinouts, [48](#)

straight-through cabling, [47](#)

UTP

10BASE-T pinouts, [46–47](#)

100BASE-T pinouts, [46–47](#)

1000BASE-T pinouts, 49

planning subnet implementations, 320

point-to-point, Ethernet, 60

point-to-point links/lines. *See* leased-line WAN

point-to-point networks, 586, 592–594

point-to-point ports, RSTP, 245

PortFast, STP, 247–248, 269–274

ports

10/100 ports, autonegotiation, 161, 162

10/100/1000 ports, autonegotiation, 161, 162, 163

Aux ports, 423

costs, STP, 266–268

default costs, 235–236

DP, 229

embedded switch ports

configuring, 478–480

identifying, 481–482

verifying routing, 480–481

IP telephony ports, 208, 212

Layer 3 Switch Routed Ports

Layer 3 EtherChannels, 473–477

routed interfaces, 470–473

VLAN routing, 455, 469–477

root ports, choosing, 232–234

Router LAN Switch Ports

embedded switch ports, 478–482

VLAN routing, 455, 477–482

RSTP

alternate ports, 241–243

backup ports, 241, 244

edge ports, 245

point-to-point ports, 245

port roles, 241

states, 243–244

types of ports, 245–246

STP, states, 243–244

postal service, IP analogy, 26–27

PPP (Point-to-Point Protocol), leased-line WAN, 66–67

predictability in interesting octets, subnet masks, 368–369

preferred lifetimes, SLAAC, 712–714

prefixes

discovery, 699

lengths, IPv6 addresses, 649

on-link prefixes, 703–704

longest prefix matching, OSPF, 625–630

masks, 341

binary mask conversions, 341–342

DDN mask conversions, 342–344

priority

OSPF, 590–592

switches, identifying, 263–266

values, STP/RSTP, 262

priority 0, troubleshooting OSPF neighbors, 618–619

private IP networks, subnetting, 313–314

private IPv6 addresses, 656–657

private lines. *See* leased-line WAN

privileged (enable) mode

Cisco IOS XE CLI access, 96–98

rejected commands example, 97–98

switches, security, simple passwords, 135–139

problem isolation

ping command, [513](#)
tracert command, [524](#)

productivity commands, [153](#)

protocols

ARP, network layer, [80–81](#)

dynamic routing protocols

convergence, [541](#), [542](#)

EIGRP, [543–544](#), [545](#)

features, [540](#)

functions, [541–542](#)

ICMPv6, [642](#)

IGP, [542–545](#)

IGRP, [543](#)

NDP, [642](#)

OSPF, [543–545](#)

OSPF, AD, [623](#)

OSPF, areas, [555–557](#)

OSPF, BDR, [552–553](#)

OSPF, broadcast networks, [586–592](#)

OSPF, concepts, [546](#)

OSPF, design terminology, [556](#)

OSPF, Dijkstra SPF algorithm, [553–555](#)

OSPF, DR/BDR elections, [590–592](#)

OSPF, ECMP routing, [621–622](#)

OSPF, equal-cost routes, [621–622](#)

OSPF, Hello packets, [548–549](#)

OSPF, implementing with interface subcommands, [576](#)

OSPF, interface configurations, [575–578](#)

OSPF, IP forwarding, [625–628](#)

OSPF, IP routing table, [628–630](#)

OSPF, longest prefix matching, [625–630](#)

- OSPF, LSA, 546–548, 557–560*
- OSPF, LSDB, 546, 547–548, 550–553*
- OSPF, MTU, 618*
- OSPF, multi-area OSPF, 574–575*
- OSPF, neighbor adjacencies, 612–617*
- OSPF, neighbor priorities, 618–619*
- OSPF, neighbor requirements, 611–612*
- OSPF, neighbors, 546, 548–553*
- OSPF, neighbors with missing routes, 619–621*
- OSPF, network types, 618*
- OSPF, operation of, 546*
- OSPF, point-to-point networks, 586, 592–594*
- OSPF, priority, 590–592*
- OSPF, RID, 548*
- OSPF, route calculation, 553–555*
- OSPF, route selection, 621–630*
- OSPF, shutting down, 615–617*
- OSPF, topologies, 546–547*
- OSPF, troubleshooting routing, 618–621*
- OSPFv2, Dead intervals, 602–604, 614–615*
- OSPFv2, default routes, 597–599*
- OSPFv2, Hello intervals, 602–604, 614–615*
- OSPFv2, interface bandwidth, 599, 600*
- OSPFv2, metrics (cost), 599–601*
- OSPFv2, network commands, 564–568*
- OSPFv2, passive interfaces, 594–597*
- OSPFv2, reference bandwidth, 599, 600–601*
- OSPFv2, verification commands, 568–573*
- OSPFv3, 642*
- path selection, 540*
- RIPv2, 543–545*

EIGRP, 543–545

EIGRPv6, [645–646](#)

HTTP

data-only messages, [24](#)

GET requests, [24](#)

overview of, [23](#)

replies, [24](#)

web pages, [24](#)

ICMP, echo requests, [81–82](#)

ICMPv6, [642](#)

IGP, [542–545](#)

IGRP, [543](#)

IP routing, [77–78](#)

LACP, [284](#)

MP BGP-4, [645–646](#)

NDP, [642](#), [698–699](#)

NA, [699–702](#), [705](#)

NS, [699–702](#), [705](#)

RA, [702–704](#)

RS, [702–704](#)

summary, [705–706](#)

network layer protocols, identifying with EtherType fields, [56](#)

OSPF, [543–545](#)

AD, [623](#)

areas, [555–557](#)

BDR, [552–553](#)

concepts, [546](#)

design terminology, [556](#)

Dijkstra SPF algorithm, [553–555](#)

DR/BDR elections, [590–592](#)

ECMP routing, [621–622](#)

equal-cost routes, [621–622](#)

Hello packets, [548–549](#)

- interface configurations, 575–578*
- IP forwarding, 625–628*
- IP routing table, 628–630*
- longest prefix matching, 625–630*
- LSA, 546–548, 557–560*
- LSDB, 546, 547–548, 550–553*
- MTU, troubleshooting, 618*
- multi-area OSPF, 574–575*
- neighbors, 546, 548–553*
- neighbors, requirements, 611–612*
- neighbors, troubleshooting adjacencies, 612–617*
- neighbors, troubleshooting missing routes, 619–621*
- neighbors, troubleshooting priority 0, 618–619*
- network types, troubleshooting, 618*
- operation of, 546*
- OSPF, broadcast networks, 586–592*
- point-to-point networks, 586, 592–594*
- priority, 590–592*
- RID, 548*
- route calculation, 553–555*
- route selection, 621–630*
- routing, troubleshooting, 618–621*
- shutting down, 615–617*
- topologies, 546–547*

OSPFv2

- Dead intervals, 602–604, 614–615*
- default routes, 597–599*
- Hello intervals, 602–604, 614–615*
- implementing with interface subcommands, 576*
- interface bandwidth, 599*
- metrics (cost), 599–601*
- network commands, 564–568*

- passive interfaces*, [594–597](#)
 - reference bandwidth*, [599](#), [600–601](#)
 - verification commands*, [568–573](#)
- OSPFv3, [642](#), [645](#)
- PAgP, [284](#)
- RIPng, [645](#)
- RIPv2, [543–545](#)
- TCP/IP networking models, [22–23](#)
- VTP, [194](#), [201–202](#)
- proxy ARP, static routes**, [443](#)
- public IP networks**
 - setting context of, [326–328](#)
 - subnetting, [311–313](#)
- public IPv6 addresses**, [656–657](#)
- PVST+ (Per VLAN Spanning Tree Plus)**, [260](#), [261](#)

Q

- quartets, [646–647](#)
- question mark (?) command, [101](#)

R

- RA (Neighbor Advertisements)**, [702–704](#)
- range of usable subnet addresses**, [361](#), [367](#)
- recalling commands**, [102](#)
- reference bandwidth**, [599](#), [600–601](#)
- rejected commands example, enable (privileged) mode**, [97–98](#)
- relationships, neighbors**, [553](#)
- reload command, switch configurations**, [109](#)

remote access, switches

IPv4, [146–147](#)

SSH, [142–145](#)

remote subnets, DHCP Relay, [490–492](#)

removing, interface configurations from switches, [174–176](#)

replies, HTTP, [24](#)

request messages, [489](#)

resident subnets, [358–359](#)

reverse routes, testing, [517–519](#)

RFC (Requests for Comments), [21](#)

RID (Router ID), OSPF, [548](#), [573–574](#)

RIPng (RIP next generation), [645](#)

RIPv2 (Routing Information Protocol version 2), [543–545](#)

ROAS (Router-On-A-Stick)

configuring, [458–461](#)

verifying configurations, [461–463](#)

VLAN routing, 802.1Q trunking, [457–464](#)

roles

identifying, [266–268](#)

STP, [238](#)

rollover cabling, console connections, [93–94](#)

root costs, STP, [266–268](#)

root election, STP/RSTP, [231](#)

Root Guard, STP, [250–251](#), [278–279](#)

root ports, choosing, [232–234](#)

root switches

designated ports, choosing for LAN segments, [234–235](#)

distribution switches as, [259](#)

election process, [231](#)

- identifying, [263–266](#)
- root ports, choosing, [232–234](#)
- STP/RSTP, [229](#)

routers

- 802.1Q trunking, VLAN routing, [454](#), [457–464](#)
- ABR, [556](#)
- Aux ports, [423](#)
- backbone routers, [556](#)
- CLI, accessing, [414–415](#)
- default routers, [73](#)
- DHCP, client configurations, [496–497](#)
- encapsulating/de-encapsulating IP packets, [68–69](#)
- enterprise routers, installing, [408–409](#), [412](#)
 - Catalyst Edge Platform*, [411](#)
 - IOS*, [409–410](#)
 - IOS XE*, [409–410](#)
 - ISR*, [410–411](#)
 - OS*, [409–410](#)
- interfaces, [415](#)
 - bandwidth, serial interfaces*, [423](#)
 - clock rates, serial interfaces*, [423](#)
 - Ethernet interface autonegotiation*, [420–422](#)
 - IPv4 addressing*, [418–419](#)
 - listing*, [416–417](#)
 - serial interfaces*, [423](#)
 - status codes*, [417–418](#)
- internal routers, [556](#)
- IPv4 support, [413–423](#)
- IPv6 addressing
 - anycast addresses*, [672–689](#)
 - configuration summary*, [690–691](#)
 - dual stacks*, [671](#)

LLA, 680–684

loopback addresses, 689

modified EUI-64, 674–679, 682–683

multicast addresses, 684–688

scopes, 686–687

solicited-node multicast addresses, 684, 687–688

special addresses, 680

unicast IP addresses, 670–671

unicast IP addresses, dynamic, 679–680

unicast IP addresses, static, 671–679

unspecified addresses, 689

ISR, 410–411

Layer 3 Switch Routed Ports

Layer 3 EtherChannels, 473–477

routed interfaces, 470–473

VLAN routing, 455, 469–477

LSA, 558

MAC address tables, 481

next-hop routers, 434, 441, 442–443

ROAS, 454

configuring, 458–461

troubleshooting, 463–464

verifying configurations, 461–463

Router LAN Switch Ports

embedded switch ports, 478–482

VLAN routing, 455, 477–482

RS, 702–704

SOHO routers, installing, 412–413

WAN data links, 67–69

routing, IPv4, 71–72, 428

addressing, 76–77

configuring with connected routes, 435–439

- grouping addresses, 76*
 - header fields, 76–77*
 - ip address command, 436–439*
 - network advertisements, 78*
 - subnetting, 76*
- ARP tables, 439–440
- basics, 28–29
- BDR, 552–553
- connected routes, 426–427
- default routers, 73
- Dijkstra SPF algorithm, 547–548, 553–555
- dynamic routing protocols
 - convergence, 541, 542*
 - EIGRP, 543–545*
 - features, 540*
 - functions, 541–542*
 - ICMPv6, 642*
 - IGP, 542–545*
 - IGRP, 543*
 - NDP, 642*
 - OSPF, 543–545*
 - OSPF, AD, 623*
 - OSPF, areas, 555–557*
 - OSPF, BDR, 552–553*
 - OSPF, broadcast networks, 586–592*
 - OSPF, concepts, 546*
 - OSPF, design terminology, 556*
 - OSPF, Dijkstra SPF algorithm, 553–555*
 - OSPF, DR/BDR elections, 590–592*
 - OSPF, ECMP routing, 621–622*
 - OSPF, equal-cost routes, 621–622*
 - OSPF, Hello packets, 548–549*

OSPF, implementing with interface subcommands, 576
OSPF, interface configurations, 575–578
OSPF, IP forwarding, 625–628
OSPF, IP routing table, 628–630
OSPF, longest prefix matching, 625–630
OSPF, LSA, 546–548, 557–560
OSPF, LSDB, 546, 547–548, 550–553
OSPF, MTU, 618
OSPF, multi-area OSPF, 574–575
OSPF, neighbor adjacencies, 612–617
OSPF, neighbor priorities, 618–619
OSPF, neighbor requirements, 611–612
OSPF, neighbors, 546, 548–553
OSPF, neighbors with missing routes, 619–621
OSPF, network types, 618
OSPF, operation of, 546
OSPF, point-to-point networks, 586, 592–594
OSPF, priority, 590–592
OSPF, RID, 548
OSPF, route calculation, 553–555
OSPF, route selection, 621–630
OSPF, shutting down, 615–617
OSPF, topologies, 546–547
OSPF, troubleshooting routing, 618–621
OSPFv2, Dead intervals, 602–604, 614–615
OSPFv2, default routes, 597–599
OSPFv2, Hello intervals, 602–604, 614–615
OSPFv2, interface bandwidth, 599, 600
OSPFv2, metrics (cost), 599–601
OSPFv2, network commands, 564–568
OSPFv2, passive interfaces, 594–597
OSPFv2, reference bandwidth, 599, 600–601

- OSPFv2, verification commands, 568–573*
 - OSPFv3, 642*
 - path selection, 540*
 - RIPv2, 543–545*
- ECMP routing, 621–622
- encapsulating/de-encapsulating IP packets, 68–69
- equal-cost routes, 621–622
- Ethernet WAN, 70–71
- example of, 431–435
- flooding, 546
- host routing logic (summary), 429
- interarea routes, 556
- intra-area routes, 556
- ip address command, 436–439
- LAN, 67–69, 73–75
- logic, 72–73
- OSPF, troubleshooting, 618–621
- OSPFv2, default routes, 597–599
- process reference, 429–431
- protocols, 77–78
- route selection, OSPF, 621–630
- routing logic (summary), 430–431
- static routes, 426–427
 - configuring, 440–443*
 - Ethernet outgoing interfaces, 443*
 - floating static routes, 447–448*
 - proxy ARP, 443*
 - static default routes, 443–445*
 - static host routes, 445–447*
 - static network routes, 441–442*
 - troubleshooting, 443–445*
- tables, 73

troubleshooting

IP addresses, 522–524

name resolution, 522–524

ping command, 512, 513–524

SSH, 527–530

Telnet, 527–530

testing LAN neighbors, 519–521

testing longer routes, 514–517

testing reverse routes, 517–519

testing WAN neighbors, 521

traceroute command, 512, 524–527

VLAN, 195–197

Layer 3 Switch Routed Ports, 455, 469–477

Layer 3 Switch SVI, 455, 464–469

ROAS, 454

ROAS, configuring, 458–461

ROAS, troubleshooting, 463–464

ROAS, verifying configurations, 461–463

Router 802.1Q Trunks, 454, 457–464

Router LAN Switch Ports, 455, 477–482

WAN, 73–75

routing, IPv6, 643–645

abbreviating addresses, 647, 648–649

AD

connected routes, 727

static routes, 739–741

address formats/conventions, 646

address prefix lengths, 649

connected routes, 724–727

EIGRPv6, 645–646

expanding addresses, 648–649

floating static routes, 739–741

- full (unabbreviated) addresses, [646–647](#)
- hexadecimal/binary conversion chart, [647](#)
- local routes, [724–725](#), [727–728](#)
- MP BGP-4, [645–646](#)
- OSPFv3, [645](#)
- RIPng, [645](#)
- static default routes, [735–737](#)
- static host routes, [737–739](#)
- static network routes, [728](#)
 - logic*, [728–729](#)
 - next-hop addresses*, [730–735](#)
 - outgoing interfaces*, [729–730](#)
 - troubleshooting*, [741–743](#)
- subnet prefixes, [649–652](#)

RPVST+ (Rapid Per VLAN Spanning Tree Plus), [260](#), [261](#), [266](#)

RS (Router Solicitations), [702–704](#)

RSTP (Rapid Spanning Tree Protocol), [222](#), [236](#), [239–240](#), [260](#), [261](#), [266](#)

- alternate ports, [241–243](#)
- basics, [224–225](#)
- BID, [229–231](#)
- blocking state, [225](#), [229](#)
- broadcast storms, [225–227](#)
- configurable priority values, [262](#)
- configuring, [259](#)
- designated switches, [229](#)
- discarding state, [243](#)
- DP, [229](#)
- forwarding state, [225](#), [229](#)
- frames, multiple frame transmissions, [227](#)
- Hello BPDU, [230–231](#)

- link types, [245](#)
- looping frames, [225–227](#)
- MAC tables, [227](#)
- need for, [225–227](#)
- operation of, [228–235](#)
- ports
 - alternate ports*, [241](#)
 - backup ports*, [241](#), [244](#)
 - edge ports*, [245](#)
 - point-to-point ports*, [245](#)
 - roles*, [241](#)
 - states*, [243–244](#)
 - types of ports*, [245–246](#)
- role of, [227–228](#)
- root switches, [229](#)
 - designated ports, choosing for LAN segments*, [234–235](#)
 - election process*, [231](#)
 - root ports, choosing*, [232–234](#)
- STA, [228](#)
- STP comparisons, [240–241](#), [243–244](#)
- topological influence, configuring, [235–236](#)

RSTP (Rapid Spanning Tree Protocol). *See also* **STP**

running-config files, [107–108](#)

S

- same-layer interaction, TCP/IP networking models**, [25–26](#)
- scopes, multicast IPv6 addresses**, [686–687](#)
- security**
 - CLI, [98–99](#), [134–135](#)
 - passwords

basic password configurations, 137–138

CLI, 98–99

console passwords, 135–139

enable passwords, 135–139

enable secret passwords, 137

privileged mode, switches, 135–139

shared passwords, 135–139

simple security concepts, 135

switch security, user mode, 139–141

Telnet, 135–139

user mode, switches, 135–139

vty passwords, 135, 137

switches

CLI, 134–135

privileged mode, simple passwords, 135–139

user mode, external authentication servers, 141–142

user mode, local usernames/passwords, 139–141

user mode, simple passwords, 135–139

segments, 25–26, 31, 32

selecting paths. See [routing, IPv4](#)

serial interfaces, routers, 423

serial links/lines. See [leased-line WAN](#)

servers

authentication servers, switch security, user mode, [141–142](#)

DHCP servers

preconfiguration, 493

stored information, 492–493

DNS server lists, [500](#)

services (Layer 2), Ethernet WAN, 70

shared media, Ethernet, 60

- shared passwords, [135–139](#)**
- show command, [103](#)**
- show interfaces command, [124](#)**
- shutdown command, switch interface configuration, [172–173](#)**
- shutting down, OSPF, [615–617](#)**
- single switch topologies, learning MAC addresses, [122–123](#)**
- single-area OSPF, [555](#), [565–566](#)**
- single-mode fiber, [51–53](#)**
- SLAAC (Stateless Address Autoconfiguration), [710–714](#)**
- slash masks. *See* prefix masks**
- software configuration, Cisco IOS, [103–104](#)**
- SOHO (Small Office/Home Office)**
 - LAN, [39](#)
 - routers, installing, [412–413](#)
- solicited-node multicast addresses, [684](#), [687–688](#)**
- spanning trees (multiple), need for, [260](#)**
- special IPv6 addresses, IPv6 routing, [680](#)**
- speed of switches, manually setting, [169–170](#)**
- SPF algorithm**
 - LSDB, [547–548](#)
 - route calculation, [553–555](#)
- SSH (Secure Shell)**
 - Cisco IOS XE CLI access, [96](#)
 - IPv4 routing, [527–530](#)
 - status, displaying, [145](#)
 - switch security, remote access, [142–145](#)
- STA (Spanning Tree Algorithm), [228](#)**
- startup-config files, [108–109](#)**
- stateful DHCPv6, [706–710](#)**

stateless DHCPv6, 707, 710, 711–712

states, identifying, 266–268

static access interfaces, 197–198

static ranges, choosing for subnetting, 321–322

static routes, 426–427

configuring, 440–443

Ethernet outgoing interfaces, 443

floating static routes, 447–448, 739–741

IPv6 network routing

floating static routes, 739–741

logic, 728–729

next-hop addresses, 730–735

outgoing interfaces, 729–730

static default routes, 735–737

static host routes, 737–739

static network routes, 728–735

troubleshooting, 741–743

proxy ARP, 443

static default routes, 443–445

static host routes, 445–447

static network routes, 441–442

troubleshooting, 448–450

static unicast IP addresses, IPv6 routing, 671–679

status codes

router interfaces, 417–418

switch interface configurations, 176–177

storing switch configurations, 106–108

STP (Spanning Tree Protocol), 222, 236, 261

basics, 224–225

BID, 229–231, 261–262

- blocking state, [120–121](#), [225](#), [229](#), [238–239](#)
- BPDU Filter, [248–250](#), [274–278](#)
- BPDU Guard, [248](#), [269–274](#)
- broadcast storms, [225–227](#)
- broken state, [251](#)
- channel-group configuration command, [281–284](#)
- configurable priority values, [262](#)
- convergence management, [237–238](#)
- designated switches, [229](#)
- disabled state, [239](#)
- DP, [229](#)
- EtherChannel, [246](#)
 - load distribution*, [289–291](#)
- EtherChannel configurations
 - dynamic EtherChannels*, [284–287](#)
 - interface configuration consistency*, [287–289](#)
 - Layer 2 EtherChannel*, [281–284](#)
- forwarding state, [120–121](#), [225](#), [229](#), [238–239](#)
- frames
 - looping frames*, [225–227](#)
 - multiple frame transmissions*, [227](#)
- Hello BPDUs, [230–231](#), [236–237](#)
- interface states, changing, [238–239](#)
- learning state, [239](#)
- listening state, [239](#)
- Loop Guard, [251–253](#), [279–280](#)
- loop prevention, [120–121](#)
- MAC tables, [227](#)
- MaxAge timers, [237](#), [238](#), [241](#)
- modes, [260–261](#)
- MSTP, [261](#)
- need for, [225](#)

- operation of, 228–235
- port costs, 266–268
- PortFast, 247–248, 269–274
- ports, states, 243–244
- PVST+260, 261
- role of, 227–228
- roles, 238
- roles, identifying, 266–268
- root costs, 266–268
- Root Guard, 250–251, 278–279
- root switches, 229
 - designated ports, choosing for LAN segments, 234–235*
 - election process, 231*
 - root ports, choosing, 232–234*
- RPVST+260, 261, 266
- RSTP, 260, 261, 240–241, 243–244
- STA, 228
- stable network activity, 236–237
- standards, 260–261
- states, identifying, 266–268
- superior BPDU, 251
- system ID extensions, 261–262
- timers, convergence management, 237–238
- topological influence, configuring, 235–236
- unidirectional links, 252
- VLAN, load balancing, 260

STP (Spanning Tree Protocol). *See also* **RSTP**

straight-through cabling, pinouts, 47

study plans (exams), 753–754

submodes, CLI configuration, 104–106

subnetting

- broadcast addresses, [358](#), [359](#), [361](#)
- calculating based on IPv4 format, [349–350](#)
- classful addressing, [348](#)
- classless addressing, [348](#)
- defining, [358](#)
- DHCP Relay, [490–492](#)
- difficult subnet masks, [368](#), [369–371](#)
- existing subnets
 - difficult subnet masks*, [369–373](#)
 - easy subnet masks*, [367–369](#)
 - practicing with*, [373](#)
- GUA, [659–664](#)
- ID/addresses, [308](#), [360](#)
 - binary math analysis*, [362–366](#)
 - finding in difficult subnet masks*, [369–371](#)
- IPv4, [73](#), [76](#), [302](#)
 - assigning to different locations*, [320–321](#)
 - choosing dynamic ranges*, [321–322](#)
 - choosing IP networks*, [314](#)
 - choosing static ranges*, [321–322](#)
 - classful networks*, [311–314](#)
 - defined*, [302–303](#)
 - defining size of subnets*, [308–310](#)
 - design choices*, [309–311](#)
 - design view*, [303–304](#)
 - determining number of hosts*, [307](#)
 - determining number of subnets*, [305–307](#)
 - forwarding*, [626–628](#)
 - DHCP*, [321–322](#)
 - grouping hosts*, [304–305](#)
 - listing subnets*, [318–320](#)
 - masks*, [314–318](#)

- operational view, 303–304*
 - planning implementations, 320*
 - private IP networks, 313–314*
 - public IP networks, 311–313*
- IPv6 prefixes, 649–652
- magic numbers, 370, 373–374
- masks, 314–318
 - binary masks, 340*
 - binary masks, DDN mask conversions, 342–344*
 - binary masks, prefix mask conversions, 341–342*
 - Boolean AND/OR operations, 367*
 - choosing to meet requirements, 380–386*
 - CIDR blocks, 351–352*
 - conversions, 340–345*
 - DDN, 318, 341*
 - DDN masks, 341, 342–344, 367, 370*
 - dividing IP addresses, 346–348*
 - finding ID/addresses, 386–396*
 - formats of (overview), 340–341*
 - identifying design choices, 345–346*
 - magic numbers, 370, 373–374, 388–389*
 - octet values, 342–343*
 - practicing with, 350–351*
 - predictability in interesting octets, 368–369*
 - prefix masks, 341–344*
 - zero subnet, 387–388*
- masks, easy subnet masks, 367–369
- range of usable addresses, 361, 367
- resident subnets, 358–359
- ULA, 665–666
- unicast IP addresses, 358
- VLSM, 309–311, 545

summary LSA, 558

superior BPDU, 251

SVI (Switch Virtual Interfaces), 147

autostate setting, 467–469

Layer 3 Switch SVI

configuring, 464–466

troubleshooting, 467–469

verifying configurations, 466

VLAN routing, 455, 464–469

switches

10/100 ports, autonegotiation, 161, 162

10/100/1000 ports, autonegotiation, 161, 162, 163

access switches, 259

auto-MDIX, 170–172

autonegotiation, 161–169

BID, 261–262

broadcast domains, 191–192

Cisco Catalyst switches, 90

9200 model switches, 91, 94

CLI, accessing, 90

Cisco Meraki switches, 90

Cisco Nexus switches, 90

configuring

common configuration modes, 105–106

copying switch configurations, 109

erasing switch configurations, 109

storing switch configurations, 106–108

default gateways, 148–149

designated switches, 229

DHCP, learning IP addresses, 150

DHCP client configurations, 495–496

- distribution switches, as root switches, [259](#)
- DNS, [149](#), [152–153](#)
- duplex, manually setting, [169–170](#)
- embedded switch ports
 - configuring*, [478–480](#)
 - identifying*, [481–482](#)
 - verifying routing*, [480–481](#)
- erasing configurations, [109](#)
- Ethernet frame transmissions, [57–60](#)
- Ethernet LAN
 - analyzing*, [121–122](#)
 - finding MAC addresses in tables*, [124–126](#)
 - flooding unknown unicast/broadcast frames*, [119–120](#)
 - forwarding known unicast frames*, [116–118](#)
 - forward-versus filter decisions*, [118](#)
 - interfaces*, [123–124](#)
 - learning MAC addresses*, [118–119](#), [122–123](#)
 - loop prevention*, [120–121](#)
 - MAC address tables*, [116–118](#)
 - MAC addresses with multiple switches*, [127–128](#)
 - managing MAC address tables*, [126–127](#)
 - summary*, [121](#)
 - verifying*, [121–123](#)
- exec-timeout command, [152–153](#)
- flooding, [119–120](#)
- history buffer commands, [151–152](#)
- interface configurations, [123–124](#), [172](#)
 - administratively controlling interface state*, [172–173](#)
 - description command*, [172–173](#)
 - duplex mismatches*, [177–178](#)
 - interface range command*, [172–173](#)
 - late collisions*, [163](#)

- layer 1 problems, 178–180*
 - removing, 174–176*
 - shutdown command, 172–173*
 - status codes, 176–177*
 - VLAN assignments, 197–201*
- interface states, 234–235
- IP settings, 147–149
- IP telephony ports, 208, 212
- IPv4 configurations, 149–151
- LAN switches
 - concepts, 114*
 - interface ID, 91*
 - logic, 115–116*
- Layer 3 Switch SVI
 - autostate setting, 467–469*
 - configuring, 464–466*
 - troubleshooting, 467–469*
 - verifying configurations, 466*
 - VLAN routing, 455, 464–469*
- learning, 118–119
- log messages, 141
- logging synchronous command, 152–153
- MAC addresses
 - with multiple switches, 127–128*
 - tables, 103*
- no ip domain-lookup command, 152–153
- port costs, 266–268
- priority, identifying, 263–266
- remote access
 - IPv4, 146–147*
 - SSH, 142–145*
- roles, identifying, 266–268

root costs, [266–268](#)

root switches

designated ports, choosing for LAN segments, [234–235](#)

distribution switches as, [259](#)

election process, [231](#)

identifying, [263–266](#)

root ports, choosing, [232–234](#)

STP/RSTP, [229](#)

routed interfaces, [470–473](#)

Router LAN Switch Ports

embedded switch ports, [478–482](#)

VLAN routing, [455](#), [477–482](#)

security

CLI, [134–135](#)

privileged mode, simple passwords, [135–139](#)

user mode, simple passwords, [135–139](#)

single switch topologies, learning MAC addresses, [122–123](#)

speed, manually setting, [169–170](#)

states, identifying, [266–268](#)

storing configurations, [106–108](#), [109](#)

SVI, [147](#)

syslog messages, [149–150](#), [152](#)

user mode

external authentication servers, [141–142](#)

local usernames/passwords, [139–141](#)

VLAN

access interfaces, [197–198](#)

assigning to interfaces, [213](#)

broadcast domains, [191–192](#)

data VLAN, [209–212](#)

disabled/undefined VLAN, [212–218](#)

IP settings, [147–149](#)

- native VLAN*, [195](#)
 - static access interfaces*, [197–198](#)
 - troubleshooting*, [212–218](#)
 - trunking*, [192–195](#), [201–207](#), [215–218](#)
 - undefined/disabled VLAN*, [213–215](#)
 - voice VLAN*, [209–212](#)
 - VTP*, [194](#), [201–202](#)
- WebUI, security, [145–146](#)
- switching tables**. *See* [MAC addresses](#)
- syslog messages, switches**, [149–150](#), [152](#)
- system ID extensions**, [261–262](#)

T

T1. *See* [leased-line WAN](#)

TCP/IP networking models

- adjacent-layer interaction, [25–26](#)
- application layer, [23](#)
 - accessing web pages*, [23](#)
 - HTTP*, [23–24](#)
- data encapsulation, [31–32](#)
- data-link layer, [29–31](#)
- development of, [20–21](#)
- error recovery, [25](#)
- history of, [20–21](#)
- hostnames, [79](#)
- messages, names of, [31–32](#)
- network layer, [22](#), [26](#)
 - IP, postal service analogy*, [26–27](#)
 - IP addressing, basics*, [27–28](#)
 - IP routing, basics*, [28–29](#)

- OSIv comparisons, [33–34](#)
- overview of, [21–23](#)
- physical layer, [29–31](#)
- protocols, [22–23](#)
- RFC, [21](#)
- same-layer interaction, [25–26](#)
- transport layer, [24](#)
 - adjacent-layer interaction*, [25–26](#)
 - error recovery*, [25](#)
 - same-layer interaction*, [25–26](#)

technical content (exams), additional content, [751](#)

telcos, leased-line WAN, [65–66](#)

Telnet

- Cisco IOS XE CLI access, [96](#)
- IPv4 routing, [527–530](#)
- passwords, [135–139](#)

temporary IPv6 addresses, [712–714](#)

terminal emulators, configuring, [95](#)

testing

- IPv6 connectivity, [716–718](#)
- LAN neighbors, [519–521](#)
- longer routes, [514–517](#)
- reverse routes, [517–519](#)
- WAN neighbors, [521](#)

timers, STP convergence management, [237–238](#)

topologies

- OSPF, [546–547](#)
- single switch topologies, learning MAC addresses, [122–123](#)
- STP/RSTP configuration, [235–236](#)

traceroute command

IPv4 routing, [512](#), [524–527](#)

IPv6 connectivity, [716–718](#)

tracert command

basics, [524–525](#)

extended traceroute, [526–527](#)

operation of, [525–526](#)

problem isolation, [524](#)

trailer fields, Ethernet frames, [53–54](#)

transceivers, Ethernet, [45](#)

transmitting data

optical transmitters, [50–51](#)

single-mode fiber cabling, [51](#)

UTP, [43–44](#)

transport layer, TCP/IP networking models, [24](#)

adjacent-layer interaction, [25–26](#)

error recovery, [25](#)

same-layer interaction, [25–26](#)

troubleshooting

host settings, IPv4 addressing, [506–509](#)

IPv4 routing

IP addresses, [522–524](#)

name resolution, [522–524](#)

ping command, [512](#), [513–524](#)

SSH, [527–530](#)

Telnet, [527–530](#)

testing LAN neighbors, [519–521](#)

testing longer routes, [514–517](#)

testing reverse routes, [517–519](#)

testing WAN neighbors, [521](#)

traceroute command, [512](#), [524–527](#)

IPv6 addressing, [714–718](#)

Layer 3 Switch SVI, [467–469](#)

OSPF

MTU, [618](#)

neighbor adjacencies, [612–617](#)

neighbor priorities, [618–619](#)

neighbors with missing routes, [619–621](#)

network types, [618](#)

routing, [618–621](#)

priority 0, OSPF neighbors, [618–619](#)

ROAS, [463–464](#)

static routes

IPv4 routing, [443–445](#)

IPv6 routing, [741–743](#)

trunking, [212–218](#)

VLAN, [212–218](#)

trunking

802.1Q trunking, [194–195](#), [454](#), [457–464](#)

administrative mode options, [203](#)

dynamic auto mode, [203–204](#)

dynamic desirable mode, [203](#)

ISL VLAN trunking, [194–195](#)

operational mode options, [203](#), [207](#)

troubleshooting, [212–218](#)

VLAN, [192–195](#), [201–207](#), [215–218](#)

tunneling, BPDU, [266](#)

U

ULA (Unique Local Addresses), [656](#), [664–666](#)

unabbreviated (full) IPv6 addresses, [646–647](#)

undefined/disabled VLAN, [213–215](#)

unicast Ethernet addresses, [54–55](#)

unicast frames

flooding unknown unicast frames, [119–120](#)

forwarding, Ethernet LAN switching, [116–118](#)

unicast IP addresses, [358](#)

CIDR blocks, [327](#)

GUA, [655–664](#)

IPv6 routing, [670–671](#)

unidirectional links, STP, [252](#)

unknown broadcast/unicast frames, flooding, [119–120](#)

unspecified IPv6 addresses, IPv6 routing, [689](#)

updates, exams, [751–752](#)

user interface. *See* [WebUI](#)

user mode

Cisco IOS XE CLI access, [96–98](#)

rejected commands example, [97–98](#)

switch security

external authentication servers, [141–142](#)

local usernames/passwords, [139–141](#)

remote access, IPv4, [146–147](#)

remote access, SSH, [142–145](#)

simple passwords, [135–139](#)

usernames, switch security, [139–141](#)

UTP (Unshielded Twisted-Pair) cabling

10BASE-T pinouts, [46–47](#)

100BASE-T pinouts, [46–47](#)

1000BASE-T pinouts, [49](#)

cabling comparisons, [52–53](#)

data transmission, [43–44](#)

Ethernet LAN builds, [43–49](#)

Ethernet links, [44–46](#)

V

valid lifetimes, SLAAC, [712–713](#)

verifying

broadcast network operations, [588–590](#)

data VLAN, [209–212](#)

embedded switch port routing, [480–481](#)

Ethernet LAN switching, [121–123](#)

host connectivity, IPv6 addressing, [718–719](#)

IPv4 configurations, switches, [150–151](#)

Layer 3 Switch SVI configurations, [466](#)

OSPFv2 verification commands, [568–573](#)

ROAS configurations, [461–463](#)

static network routes, [442](#)

VLAN

data VLAN, [209–212](#)

voice VLAN, [209–212](#)

voice VLAN, [209–212](#)

VLAN (Virtual LAN), [188](#). *See also* LAN; WLAN

access interfaces, [197–198](#)

assigning to interfaces, [197–201](#), [213](#)

broadcast domains, [191–192](#)

configuring, [197–201](#)

creating, [197–201](#)

data VLAN

configuring, [209–212](#)

verifying, [209–212](#)

disabled/undefined VLAN, [212–218](#)

forwarding data between VLAN, [195–197](#)

interfaces, [464–466](#)

load balancing with STP, [260](#)

native VLAN, [195](#)

phone connections, [207–212](#)

PVST+[260](#), [261](#)

routing

Layer 3 Switch Routed Ports, [455](#), [469–477](#)

Layer 3 Switch SVI, [455](#), [464–469](#)

ROAS, [454](#)

ROAS, configuring, [458–461](#)

ROAS, troubleshooting, [463–464](#)

ROAS, verifying configurations, [461–463](#)

Router 802.1Q Trunks, [454](#), [457–464](#)

Router LAN Switch Ports, [455](#), [477–482](#)

routing between VLAN, [195–197](#)

RPVST+[260](#), [261](#)

static access interfaces, [197–198](#)

switches, IP settings, [147–149](#)

troubleshooting, [212–218](#)

trunking, [192–195](#), [201–207](#), [215–218](#)

undefined/disabled VLAN, [213–215](#)

voice VLAN

configuring, [209–212](#)

verifying, [209–212](#)

VTP, [194](#), [201–202](#)

VLSM (Variable-Length Subnet Masks), [309–311](#), [545](#)

voice VLAN

configuring, [209–212](#)

verifying, [209–212](#)

VTP (VLAN Trunking Protocol), [194](#), [201–202](#)

vty passwords, [135](#), [137](#)

WAN (Wide Area Networks), 36, 64

Ethernet WAN, 64, 69

IP routing, 70–71

Layer 2 services, 70

leased-line WAN, 64–65

conceptual view, 65

data-link details, 66–69

different names for, 65–66

HDLC, 66–67

IP routing, 67–69

physical details, 65–66

PPP, 66–67

routers, 67–69

telcos, 65–66

neighbors, testing, 521

network layer routing (forwarding), 73–75

web pages

accessing from, application layer, TCP/IP networking models, 23

HTTP, 24

WebUI (User Interface)

CLI access, 99–101

security, 145–146

WHOIS records, 328

wildcard characters, matching with OSPFv2 network commands, 566–568

Windows IP host settings, 499–502

wired LAN. *See* Ethernet LAN

WLAN (Wireless LAN), 18–19

X - Y - Z

zero subnet, [387–388](#)



Register your product at **ciscopress.com/register** to unlock additional benefits:

- Save 35%* on your next purchase with an exclusive discount code
- Find companion files, errata, and product updates if available
- Sign up to receive special offers on new editions and related titles

Get more when you shop at **ciscopress.com**:

- Everyday discounts on books, eBooks, video courses, and more
- Free U.S. shipping on all orders
- Multi-format eBooks to read on your preferred device
- Print and eBook Best Value Packs

*Discount code valid for 30 days; may not be combined with any other offer and is not redeemable for cash. Offer subject to change.

Cisco Press