

Package ‘metabolighteR’

November 19, 2019

Type Package

Title R Interface to the Metabolights RESTful API

Version 0.1.0

Date 2019-11-19

Description Access to the Metabolights RESTful API <<https://www.ebi.ac.uk:443/metabolights/ws>>.

Depends magrittr

Imports httr, dplyr, purrr

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.0.0

Suggests covr, testthat, tibble

NeedsCompilation no

Author Tom Wilson [aut, cre] (<<https://orcid.org/0000-0003-3112-4682>>)

Maintainer Tom Wilson <tpw2@aber.ac.uk>

R topics documented:

get_isa_investigation	2
get_private_studies	2
get_studies	2
get_study_contacts	3
get_study_desc	3
get_study_descriptors	4
get_study_factors	4
get_study_files	5
get_study_meta	5
get_study_protocols	6
get_study_pubs	6
get_study_title	7
get_webservice	7
mtbls_key	8

Index**9**

`get_isa_investigation` *Get ISA Investigation File*

Description

Get ISA Investigation File

Usage

```
get_isa_investigation(study_id, outpath)
```

Arguments

<code>study_id</code>	A character string of a valid MTBLS study id
<code>outpath</code>	A character string of a filepath where the ISA Investigation '.txt' file will be saved to

`get_private_studies` *Get Private Studies*

Description

Get Private Studies

Usage

```
get_private_studies()
```

Value

a 'tibble' of your private Study IDs

`get_studies` *Get Studies*

Description

Retrieve a list of all available MTBLS Study ID's

Usage

```
get_studies()
```

Value

a 'tibble' of Study IDs

<code>get_study_contacts</code>	<i>Get Study Contacts</i>
---------------------------------	---------------------------

Description

Get Study Contacts

Usage

```
get_study_contacts(study_id)
```

Arguments

`study_id` a character string of a valid MTBLS study id

Value

a ‘tibble’ of study contacts

<code>get_study_desc</code>	<i>Get Study Description</i>
-----------------------------	------------------------------

Description

Get Study Description

Usage

```
get_study_desc(study_id)
```

Arguments

`study_id` A character string of a valid MTBLS study id

Value

a character string of the study description

get_study_descriptors *Get Study Descriptors*

Description

Get Study Descriptors

Usage

```
get_study_descriptors(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a 'tibble' of study descriptors

get_study_factors *Get Study Factors*

Description

Get Study Factors

Usage

```
get_study_factors(study_id)
```

Arguments

study_id A character string of a valid MTBLS study id

Value

a 'tibble' of study factors

get_study_files	<i>Get Study Files</i>
-----------------	------------------------

Description

Get Study Files

Usage

```
get_study_files(study_id, raw_data = FALSE)
```

Arguments

study_id	A character string of a valid MTBLS study id
raw_data	logical; if 'TRUE' then raw data file info is also returned. (Default is 'FALSE')

Value

a 'tibble' of file info

get_study_meta	<i>Get Study Meta</i>
----------------	-----------------------

Description

Get Study Meta

Usage

```
get_study_meta(study_id)
```

Arguments

study_id	A character string of a valid MTBLS study id
----------	--

Value

a 'tibble' of study meta data

get_study_protocols	<i>Get Study Protocols</i>
---------------------	----------------------------

Description

Get Study Protocols

Usage

```
get_study_protocols(study_id)
```

Arguments

study_id	A character string of a valid MTBLS study id
----------	--

Value

a 'tibble' of study protocols

get_study_pubs	<i>Get Study Publications</i>
----------------	-------------------------------

Description

Get Study Publications

Usage

```
get_study_pubs(study_id)
```

Arguments

study_id	A character string of a valid MTBLS study id
----------	--

Value

a 'tibble' of study publicatons

get_study_title	<i>Get Study Title</i>
-----------------	------------------------

Description

Get Study Title

Usage

```
get_study_title(study_id)
```

Arguments

study_id	A character string of a valid MTBLS study id
----------	--

Value

a character string of the study title

get_webservice	<i>Get Web-service details</i>
----------------	--------------------------------

Description

Get Web-service details

Usage

```
get_webservice()
```

Value

a list of the MTBLS webservice information

`mtbls_key`*Set API Token*

Description

Set your Metabolights API Token as global option. If 'MTBLS_API_KEY' is set in '.Renviron' then this variable will be passed directly to the 'MTBLS_API_KEY' option. If no 'MTBLS_API_KEY' is set in '.Renviron', then the API Token must be passed as an input in the 'set_api_token' function

Usage

```
mtbls_key(API_KEY = NULL)
```

Arguments

API_KEY a character string of your Metabolights API Token (Default is 'NULL')

Examples

```
## Not run:

# If API Token is set in `.Renviron`

mtbls_key()

# If API Token is not set in `.Renviron`

mtbls_key('XXXX-0000-XXXX-0000')

## End(Not run)
```


Index

`get_isa_investigation`, [2](#)
`get_private_studies`, [2](#)
`get_studies`, [2](#)
`get_study_contacts`, [3](#)
`get_study_desc`, [3](#)
`get_study_descriptors`, [4](#)
`get_study_factors`, [4](#)
`get_study_files`, [5](#)
`get_study_meta`, [5](#)
`get_study_protocols`, [6](#)
`get_study_pubs`, [6](#)
`get_study_title`, [7](#)
`get_webservice`, [7](#)

`mtbls_key`, [8](#)