

OFF-ROAD electric pallet truck (all working conditions)



① Four-Proof Accelerator Switch

Dustproof, waterproof, shockproof, and burn-resistant design. More durable and worry-free.

② Heavy-Duty Hydraulic Cylinder Assembly

Integrated high-strength cylinder with a reinforced 50mm diameter piston rod. Lifting force up to 4t with higher safety factor.

③ Permanent Magnet Brushless Motor

48V maintenance-free, high-torque motor. Strong power to climb slopes, cross uneven ground, and handle complex terrains.

④ Solid Rubber Drive Wheel

350×100mm heavy-duty solid rubber drive wheel with high durability and strong traction. 100mm ground clearance ensures superior passability.

⑤ Sealed Gearbox

Fully sealed, high gear ratio, large module, high torque gearbox. Stable, reliable, and long-lasting.

⑥ Premium Battery Options

Equipped with branded power batteries. Flexible selection of lead-acid or lithium batteries with extended endurance to meet customer needs.



Technical Parameters

Features	1	Model		TYA30 (lead-acid battery)	TYA30 (lithium battery)
	2	Power form		Electrical	Electrical
	3	Operation		Pedestrian	Pedestrian
	4	Load	kg	3000	3000
	5	Load center distance	mm	600	600
	6	Wheelbase	mm	1230/1300	1230/1300
Weight	7	Self weight with battery	kg	230	207
Wheel	8	Wheel Type		Front rubber, rear PU/nylon	Front rubber, rear PU/nylon
	9	Driving wheel size (diameter×width)	mm	φ350×100	φ350×100
	10	Load-bearing wheel size (diameter×width)	mm	φ80×60	φ80×60
	11	Number of wheels Drive side / Load side		1/4	1/4
Basic size	12	Maximum height of fork	mm	200	200
	13	Lifting stroke	mm	115	115
	14	Minimum height of fork (±2mm)	mm	85	85
	15	Fork outer distance (±3mm)	mm	550/685	550/685
	16	Fork inner distance (±3mm)	mm	250/385	250/385
	17	Length of forks	mm	1150/1220	1150/1220
	18	Width of forks	mm	150	150
	19	Thickness of forks	mm	60	60
	20	Overall width	mm	595/685	595/685
	22	Overall height without handle	mm	800	800
	22	Overall length	mm	1780/1850	1780/1850
	23	Overall height with handle	mm	1260	1260
Capability	24	Turning Radius	mm	1550/1620	1550/1620
	25	Travel speed (laden/unladen)	km/h	4/4.5	4/4.5
	26	Lifting speed (laden/unladen)	mm/s	15/19	15/19
	27	Maximum climbing grade (laden/unladen)	%	8/16	8/16
Motor / Battery	28	Brake type		Electronic brake /electromagnetic brake	Electronic brake /electromagnetic brake
	29	Rated power of driving motor	kw	1.0	1.0
	30	Rated power of lifting motor	kw	0.8	0.8
	31	Battery	V/Ah	48/32	51.2/30
Motor / Battery	32	Battery weight	kg	36	12.5

All pictures and information in this document are for reference only. Tianyu Company reserves the right to modify the corresponding parameters and configurations. If there are any changes, no further notice will be given.

Application Scenarios

The TIANYULUX All-Terrain Champion Edition is specially designed to solve tough challenges in construction sites and harsh outdoor working conditions, such as difficult maneuverability, poor ground clearance, and frequent breakdowns.

With its powerful drive system, strong motor, high-voltage configuration, long endurance, true load capacity, and outstanding reliability, it has gained high recognition from domestic and overseas distribution partners.



Outdoor construction material handling



Factory material transfer



Warehouse goods turnover

OFF-ROAD electric pallet truck (Factory Edition)



① Four-Proof Accelerator Switch

Dustproof, waterproof, shockproof, burn-resistant. Durable and reliable.



② Heavy-Duty Drive Wheel Guard

Integrated thickened steel guard. Strong anti-collision and anti-foot-crush design for operator safety.




③ Electromagnetic Brake

Standard electromagnetic braking for safer parking. Aluminum brake housing provides dust, water, and impact resistance.



④ Dual-Mode Function

Soft-start mode for smooth operation; efficiency mode for faster response. Adaptable to different working conditions.



⑤ Heavy-Duty Frame

5mm thickened integrated forks with precision-welded reinforced steel frame. Higher strength and safety factor.



⑥ Battery Options

Compatible with multiple lead-acid and lithium batteries. Long endurance to meet customer needs.



Technical Parameters

Features	1	Model		TYA30PS (lead-acid battery)	TYA30PS (lithium battery)
	2	Power form		Electrical	Electrical
	3	Operation		Pedestrian	Pedestrian
	4	Load	kg	3000	3000
	5	Load center distance	mm	600	600
	6	Wheelbase	mm	1320/1380	1320/1380
Weight	7	Self weight with battery	kg	262/280	239
Wheel	8	Wheel Type		Front rubber, rear PU/nylon	Front rubber, rear PU/nylon
	9	Driving wheel size (diameter×width)	mm	Φ350×100	Φ350×100
	10	Load-bearing wheel size (diameter×width)	mm	Φ80×70	Φ80×70
	11	Number of wheels Drive side / Load side		1/4	1/4
Basic size	12	Maximum height of fork	mm	200	200
	13	Lifting stroke	mm	115	115
	14	Minimum height of fork (±2mm)	mm	85	85
	15	Fork outer distance (±3mm)	mm	550/685	550/685
	16	Fork inner distance (±3mm)	mm	230/365	230/365
	17	Length of forks	mm	1150/1220	1150/1220
	18	Width of forks	mm	160	160
	19	Thickness of forks	mm	60	60
	20	Overall width	mm	685	685
	22	Overall height without handle	mm	800	800
	22	Overall length	mm	1880/1950	1880/1950
	23	Overall height with handle	mm	1320	1320
Capability	24	Turning Radius	mm	1530/1600	1530/1600
	25	Travel speed (laden/unladen)	km/h	4/4.5	4/4.5
	26	Lifting speed (laden/unladen)	mm/s	15/19	15/19
	27	Maximum climbing grade (laden/unladen)	%	8/16	8/16
Motor / Battery	28	Brake type		Electromagnetic brake	Electromagnetic brake
	29	Rated power of driving motor	kw	1	1
	30	Rated power of lifting motor	kw	0.8	0.8
	31	Battery	V/Ah	lead-acid battery 48/32 , 48/52	lithium battery 51.2/30
	32	Battery weight	kg	36/54	12.5

All pictures and information in this document are for reference only. Tianyu Company reserves the right to modify the corresponding parameters and configurations. If there are any changes, no further notice will be given.

Stand-On Kit (Optional)

Operator-friendly kit for long-distance, high-frequency handling. Foldable pedal saves space, improves comfort, and enhances efficiency.

