

# Team Contest Reference

## Ballmer Peak

Universität zu Lübeck

19. November 2013

### Inhaltsverzeichnis

<b>1</b>	<b>Mathematische Algorithmen</b>	<b>1</b>
1.1	Primzahlen . . . . .	1
1.1.1	Sieb des Eratosthenes . . . . .	1
1.1.2	Primzahlentest . . . . .	2
1.2	Binomial Koeffizient . . . . .	2
1.3	Modulare Arithmetik . . . . .	2
1.3.1	Erweiterter Euklidischer Algorithmus . . . . .	2
1.4	Matrixmultiplikation . . . . .	2
<b>2</b>	<b>Datenstrukturen</b>	<b>2</b>
2.1	Fenwick Tree (Binary Indexed Tree) . . . . .	2
<b>3</b>	<b>Graphenalgorithmen</b>	<b>2</b>
3.1	Topologische Sortierung . . . . .	2
3.2	Minimum Spanning Tree . . . . .	2
3.2.1	Prim's Algorithm . . . . .	2
3.2.2	Union and Find: Kruskal's Algorithm . . . . .	3
3.3	Maximaler Fluss (Ford-Fulkerson) . . . . .	3
3.4	Floyd-Warshall . . . . .	4
3.5	Dijkstra . . . . .	4
3.6	Bellmann-Ford . . . . .	5
3.7	Starke Zusammenhangskomponenten (Kosaraju) . . . . .	5
<b>4</b>	<b>Geometrische Algorithmen</b>	<b>5</b>
4.1	Rotate a Point . . . . .	5
4.2	Graham Scan (Convex Hull) . . . . .	5
4.3	Maximum Distance in a Point Set . . . . .	6
4.4	Area of a Polygon . . . . .	6
4.5	Punkt in Polygon . . . . .	6
<b>5</b>	<b>Verschiedenes</b>	<b>6</b>
5.1	Potenzmenge . . . . .	6
5.2	Longest Common Subsequence . . . . .	6
5.3	Longest Increasing Subsequence . . . . .	7
<b>6</b>	<b>Eine kleine C-Referenz</b>	<b>7</b>

## 1 Mathematische Algorithmen

### 1.1 Primzahlen

Für Primzahlen gilt immer (aber nicht nur für Primzahlen)

$$a^p \equiv a \pmod{p} \quad \text{bzw.} \quad a^{p-1} \equiv 1 \pmod{p}.$$

Ein paar Primzahlen für den Hausgebrauch:  
1000003, 2147483647( $2^{31}$ ), 4294967291( $2^{32}$ )

#### 1.1.1 Sieb des Eratosthenes

```

1 static boolean[] sieve(int until) {
2     boolean[] a = new boolean[until + 1];
3     Arrays.fill(a, true);
4     for (int i = 2; i < Math.sqrt(a.length); i++) {
5         if (a[i]) {
6             for (int j = i * i; j < a.length; j += i) a[j] = false;
7         }
8     }

```

```

9  return a; // a[i] == true, iff. i is prime. a[0] ▼
    is ignored
10 }

```

### 1.1.2 Primzahlentest

```

1  static boolean isPrim(int p) {
2  if (p < 2 || p > 2 && p % 2 == 0) return false;
3  for (int i = 3; i <= Math.sqrt(p); i += 2)
4  if (p % i == 0) return false;
5  return true;
6  }

```

## 1.2 Binomial Koeffizient

```

1  static int[][] mem = new int[MAX_N][(MAX_N + 1) / ▼
    2];
2  static int binoCo(int n, int k) {
3  if (k < 0 || k > n) return 0;
4  if (2 * k > n) binoCo(n, n - k);
5  if (mem[n][k] > 0) return mem[n][k];
6  int ret = 1;
7  for (int i = 1; i <= k; i++) {
8  ret *= n - k + i;
9  ret /= i;
10 mem[n][i] = ret;
11 }
12 return ret;
13 }

```

## 1.3 Modulare Arithmetik

Bedeutung der größten gemeinsamen Teiler:

$$d = \text{ggT}(a, b) = as + bt$$

Verwendung zu Berechnung des inversen Elements  $b$  zu  $a$  bezüglich einer Restklassengruppe  $n$  ( $a$  und  $n$  müssen teilerfremd sein):

$$ab \equiv 1 \pmod{n} \Leftrightarrow s \equiv b \pmod{n} \text{ für } 1 = \text{ggT}(a, n)$$

### 1.3.1 Erweiterter Euklidischer Algorithmus

```

1  static int[] eea(int a, int b) {
2  int[] dst = new int[3];
3  if (b == 0) {
4  dst[0] = a;
5  dst[1] = 1;
6  return dst; // a, 1, 0
7  }
8  dst = eea(b, a % b);
9  int tmp = dst[2];
10 dst[2] = dst[1] - ((a / b) * dst[2]);
11 dst[1] = tmp;
12 return dst;
13 }

```

Zur Berechnung des Inversen von  $n$  im Restklassenring  $p$  gilt:  $d = \text{eea}(p, n)$ .

## 1.4 Matrixmultiplikation

Strassen-Algorithmus:  $C = AB$   $A, B, C \in R^{2^n \times 2^n}$

$$\begin{aligned}
C_{1,1} &= A_{1,1}B_{1,1} + A_{1,2}B_{2,1} \\
C_{1,2} &= A_{1,1}B_{1,2} + A_{1,2}B_{2,2} \\
C_{2,1} &= A_{2,1}B_{1,1} + A_{2,2}B_{2,1} \\
C_{2,2} &= A_{2,1}B_{1,2} + A_{2,2}B_{2,2}
\end{aligned}$$

## 2 Datenstrukturen

### 2.1 Fenwick Tree (Binary Indexed Tree)

```

1  class FenwickTree {
2  private int[] values;
3  private int n;
4  public FenwickTree(int n) {
5  this.n = n;
6  values = new int[n];
7  }
8  public int get(int i) { //get value of i
9  int x = values[0];
10 while (i > 0) {
11 x += values[i];
12 i -= i & -i; }
13 return x;
14 }
15 public void add(int i, int x) { // add x to ▼
    interval [i,n]
16 if (i == 0) values[0] += x;
17 else {
18 while (i < n) {
19 values[i] += x;
20 i += i & -i; }
21 }
22 }
23 }

```

## 3 Graphenalgorithmen

### 3.1 Topologische Sortierung

```

1  static List<Integer> topoSort(Map<Integer, List<▼
    Integer>> edges,
2  Map<Integer, List<Integer>> revedges) {
3  Queue<Integer> q = new LinkedList<Integer>();
4  List<Integer> ret = new LinkedList<Integer>();
5  Map<Integer, Integer> indeg = new HashMap<Integer▼
    , Integer>();
6  for (int v : revedges.keySet()) {
7  indeg.put(v, revedges.get(v).size());
8  if (revedges.get(v).size() == 0)
9  q.add(v);
10 }
11 while (!q.isEmpty()) {
12 int tmp = q.poll();
13 ret.add(tmp);
14 for (int dest : edges.get(tmp)) {
15 indeg.put(dest, indeg.get(dest) - 1);
16 if (indeg.get(dest) == 0)
17 q.add(dest);
18 }
19 }
20 return ret;
21 }

```

### 3.2 Minimum Spanning Tree

#### 3.2.1 Prim's Algorithm

```

1  #define WHITE 0
2  #define BLACK 1
3  #define INF INT_MAX
4
5  int baum( int **matrix, int N){
6  int i, sum = 0;
7
8  int color[N];
9  int dist[N];
10
11 // markiere alle Knoten ausser 0 als unbesucht
12 color[0] = BLACK;
13 for( i=1; i<N; i++){

```

```

14     color[i] = WHITE;
15     dist[i] = INF;
16 }
17
18 // berechne den Rand
19 for( i=1; i<N; i++){
20     if( dist[i] > matrix[i][nextIndex]){
21         dist[i] = matrix[i][nextIndex];
22     }
23 }
24
25 while( 1){
26     int nextDist = INF, nextIndex = -1;
27
28     /* Den naechsten Knoten waehlen */
29     for(i=0; i<N; i++){
30         if( color[i] != WHITE) continue;
31
32         if( dist[i] < nextDist){
33             nextDist = dist[i];
34             nextIndex = i;
35         }
36     }
37
38     /* Abbruchbedingung*/
39     if( nextIndex == -1) break;
40
41     /* Knoten in MST aufnehmen */
42     color[nextIndex] = RED;
43     sum += nextDist;
44
45     /* naechste kuerzeste Distanzen berechnen */
46     for( i=0; i<N; i++){
47         if( i == nextIndex || color[i] == BLACK )▼
48             continue;
49
50         if( dist[i] > matrix[i][nextIndex]){
51             dist[i] = matrix[i][nextIndex];
52         }
53     }
54
55     return sum;
56 }

```

### 3.2.2 Union and Find: Kruskal's Algorithm

Amortized time per operation is  $O(\alpha(n))$ .

```

1 // Only the tree root is stored. The edges must be ▼
   stored separately.
2 // Path compression and union by rank
3
4 int *par = (int *) malloc(n * sizeof(int));
5 int *rank = (int *) malloc(n * sizeof(int));
6
7 // Create new forest of n vertices
8 void init(int n, int *par, int *rank) {
9     int i;
10    for (i = 1; i <= n; i++) {
11        par[i] = i; // every vertex is its on root
12        rank[i] = 0;
13    }
14 }
15
16 // Union two trees which contain x and y ▼
   respectively, returns new root
17 int union(int n, int *par, int *rank, int x, int y)▼
   {
18     y = find(n, par, y);
19     x = find(n, par, x);
20     if (rank[x] > rank[y]) return par[y] = x;
21     if (rank[x] < rank[y]) return par[x] = y;
22     rank[x]++; // rank[x] == rank[y]
23     return par[y] = x;
24 }
25

```

```

26 // Find the tree root of x
27 int find(int n, int *par, int x) {
28     // if parent is not a tree root
29     if (par[x] != par[par[x]]) par[x] = find(n, par, ▼
        par[x]);
30     return par[x];
31 }

```

### 3.3 Maximaler Fluss (Ford-Fulkerson)

```

1 /* die folgende Zeile anpassen! */
2
3 #define N_MAX 30*30+30
4
5 /* hier drunter nichts anfassen! */
6 /* ----- */
7 #define SIZE_MAX (N_MAX+2)
8 #define SIZE (N+2)
9 #define QUELLE (N)
10 #define SENKE (N+1)
11 extern int capacity[SIZE_MAX][SIZE_MAX];
12 extern int N;
13
14 int maxFlow();
15 void reset();
16
17 #include <stdio.h>
18 #include <limits.h>
19 #include <string.h>
20 #include "flow.h"
21
22 #define NONE -1
23 #define INF INT_MAX/2
24
25 int N;
26 int capacity[SIZE_MAX][SIZE_MAX];
27 int flow[SIZE_MAX][SIZE_MAX];
28 int queue[SIZE_MAX], *head, *tail;
29 int state[SIZE_MAX];
30 int pred[SIZE_MAX];
31
32 enum { UNVISITED, WAITING, PROCESSED };
33
34 void enqueue( int x){
35     *tail++ = x;
36     state[x] = WAITING;
37 }
38
39 int dequeue(){
40     int x = *head++;
41     state[x] = PROCESSED;
42     return x;
43 }
44
45 void reset(){
46     int i, j;
47     for(i=0; i<SIZE;i++){
48         memset( capacity[i], 0, sizeof(int)*SIZE );
49     }
50 }
51
52 int bfs( int start, int target){
53     int u, v;
54     for( u=0; u< SIZE; u++){
55         state[u] = UNVISITED;
56     }
57     head = tail = queue;
58     pred[start] = NONE;
59
60     enqueue(start);
61
62     while( head < tail){
63         u = dequeue();
64
65         for( v= 0; v< SIZE; v++){

```

```

50         if( state[v] == UNVISITED &&
51             capacity[u][v] - flow[u][v] > 0){
52
53             enqueue(v);
54             pred[v] = u;
55         }
56     }
57 }
58
59 return state[target] == PROCESSED;
60 }
61
62 int maxFlow(){
63     int max_flow = 0;
64     int u;
65
66     int i, j;
67     for(i=0; i<SIZE;i++){
68         memset( flow[i], 0, sizeof(int)*SIZE );
69     }
70
71     while( bfs( QUELLE, SENKE)){
72         int increment = INF, temp;
73
74         for( u= SENKE; pred[u] != NONE; u = pred[u])▼
75             {
76                 temp = capacity[pred[u]][u] - flow[pred[u]
77 ][u];
78                 if( temp < increment){
79                     increment = temp;
80                 }
81             }
82
83         for( u= SENKE; pred[u] != NONE; u = pred[u])▼
84             {
85                 flow[pred[u]][u] += increment;
86                 flow[u][pred[u]] -= increment;
87             }
88
89         max_flow += increment;
90     }
91
92     /**
93     * Ford Fulkerson
94     * @param s source
95     * @param d destination
96     * @param c capacity
97     * @param f flow, init with 0
98     * @return
99     */
100    static int ff(int s, int d, int[][] c, int[][] f) {
101        List<Integer> path = dfs(s, d, c, f, new boolean[▼
102            c.length]); // find path
103        if (path.size() < 2) {
104            int flow = 0;
105            for (int i = 0; i < f[s].length; i++) { // ▼
106                leaving flow of source
107                flow += f[s][i];
108            }
109            return flow;
110        }
111        int cap = Integer.MAX_VALUE; // capacity of ▼
112        current path
113        for (int i = 0; i < path.size() - 1; i++) {
114            int a = path.get(i), b = path.get(i + 1);
115            cap = Math.min(cap, c[a][b] - f[a][b]);
116        }
117        for (int i = 0; i < path.size() - 1; i++) { //▼
118            update flow
119            int a = path.get(i), b = path.get(i + 1);
120            f[a][b] += cap;
121            f[b][a] -= cap;
122        }
123        return ff(s, d, c, f); // tail recursion

```

```

29 }
30
31 /**
32  * depth first search in flow network
33  * @param s source
34  * @param d destination
35  * @param c capacity
36  * @param f flow
37  * @param v visited, init with false
38  * @return
39  */
40 static List<Integer> dfs(int s, int d, int[][] c, ▼
41     int[][] f, boolean[] v) {
42     v[s] = true;
43     if (s == d) { // destination found
44         LinkedList<Integer> path = new LinkedList<▼
45             Integer>();
46         path.add(d);
47         return path;
48     }
49     for (int i = 0; i < c[s].length; i++) {
50         if (!v[i] && c[s][i] - f[s][i] > 0) {
51             List<Integer> path = dfs(i, d, c, f, v);
52             if (path.size() > 0) {
53                 ((LinkedList<Integer>) path).addFirst(s);
54                 return path;
55             }
56         }
57     }
58     return ((List<Integer>) Collections.EMPTY_LIST);
59 }

```

### 3.4 Floyd-Warshall

```

1 static int n;
2 static int[][] path = new int[n][n];
3 static int[][] next = new int[n][n];
4 static void floyd(int[][] ad) {
5     for (int i = 0; i < n; i++)
6         path[i] = Arrays.copyOf(ad[i], n);
7     for (int i = 0; i < n; i++)
8         for (int j = 0; j < n; j++)
9             for (int k = 0; k < n; k++)
10                 if (path[i][k] + path[k][j] < path[i][j]) {
11                     path[i][j] = path[i][k] + path[k][j];
12                     next[i][j] = k;
13                 }
14     // there is a negative circle iff. there is a i ▼
15     such that path[i][i] < 0
16 }

```

### 3.5 Dijkstra

```

1 HashMap<Integer, List<Edge>> graph = new HashMap<▼
2     Integer, List<Edge>>();
3 for (int i = 0; i < n; i++) graph.put(i, new ▼
4     ArrayList<Edge>());
5 int dist[] = new int[n];
6 Arrays.fill(dist, Integer.MAX_VALUE);
7 int shortest = dijkstra(source, dest, graph, dist);
8
9 static int dijkstra(int s, int d, HashMap<Integer, ▼
10     List<Edge>> graph, final int[] dist) {
11     dist[s] = 0;
12     TreeSet<Integer> queue = new TreeSet<Integer>(
13         new Comparator<Integer>() {
14             public int compare(Integer o1, Integer o2) {
15                 if (dist[o1] == dist[o2]) return o1.▼
16                 compareTo(o2);
17                 return ((Integer) o1).compareTo(o2);
18             }
19         });
20     queue.add(s);
21     while (queue.size() > 0) { // || queue.first() !=▼
22         d) {
23             int c = queue.pollFirst();
24             for (Edge e : graph.get(c)) {

```

```

19     if (dist[e.to] > dist[c] + e.val) {
20         queue.remove(e.to);
21         dist[e.to] = dist[c] + e.val;
22         queue.add(e.to);
23     } } }
24     return dist[d];
25 }
26
27 class Edge {
28     int from, to, val;
29     public Edge(int from, int to, int val) {
30         this.from = from;
31         this.to = to;
32         this.val = val;
33     } }

```

### 3.6 Bellmann-Ford

Single source all paths, negative weights.

```

1 // returns true iff negative-weight cycle reachable
2 private static boolean bellmannford(Node start, int n, List<Edge> edges) {
3     start.dist = 0; // others: dist = Integer.MAX_VALUE
4     while (n-- > 0) { // number of nodes --> for all vertices
5         for (Edge edge : edges) { // --> for all edges
6             if (edge.from.dist < Integer.MAX_VALUE
7                 && edge.from.dist + edge.w < edge.to.dist)
8                 edge.to.dist = edge.from.dist + edge.w; // update predecessor
9         } }
10        for (Edge edge : edges) {
11            if (edge.from.dist < Integer.MAX_VALUE
12                && edge.from.dist + edge.w < edge.to.dist)
13                return true;
14        }
15        return false;
16    }
17    class Node {}
18    class Edge {
19        Node from, to;
20        int w;
21        public Edge(Node from, Node to, int w) {
22            this.from = from; this.to = to; this.w = w;
23        }
24    }

```

### 3.7 Starke Zusammenhangskomponenten (Kosaraju)

```

1 #define POS(X,Y) ((X)+size*(Y))
2 #define M(X,Y) (M[POS((X),(Y))])
3
4 int *top;
5 int *color;
6
7 void Kosaraju( int *M, int size);
8 void DFS( int *M, int u, int size);
9 void RDFS( int *M, int u, int size, int colorN);
10
11 void Kosaraju( int *M, int size){
12     int i;
13     int *stack = malloc( size * sizeof(int));
14     top = stack;
15
16     for(i=0;i<size;i++){
17         color[i] = 0;
18     }
19     for(i=0;i<size;i++){
20         if(color[i] != 0) continue;
21
22         DFS(M,i,size);
23     }

```

```

24
25     for(i=0;i<size;i++){
26         color[i] = 0;
27     }
28     int colorN = 1;
29
30     while( top > stack ){
31         int v = *(--top);
32         if( color[v] != 0 ) continue;
33         RDFS( M, v, size, colorN++);
34     }
35
36     free( stack);
37 }
38
39 void DFS( int *M, int u, int size){
40     int v;
41     color[u] = 1;
42     for(v=0;v<size;v++){
43         if( M(u,v) && color[v] == 0){
44             DFS( M, v, size);
45         }
46     }
47
48     *top++ = u;
49 }
50
51 void RDFS( int *M, int u, int size, int colorN){
52     int v;
53     color[u] = colorN;
54     for(v=0;v<size;v++){
55         if( M(u,v) && color[v] == 0){
56             RDFS( M, v, size, colorN);
57         }
58     }
59 }

```

## 4 Geometrische Algorithmen

### 4.1 Rotate a Point

```

1 static P rotate(P origin, P p, double ccw) {
2     double x = (p.x - origin.x) * Math.cos(ccw) - (p.y - origin.y) * Math.sin(ccw);
3     double y = (p.x - origin.x) * Math.sin(ccw) + (p.y - origin.y) * Math.cos(ccw);
4     return new P(x, y);
5 }

```

### 4.2 Graham Scan (Convex Hull)

```

1 class P {
2     double x, y;
3
4     P(double x, double y) {
5         this.x = x;
6         this.y = y;
7     }
8     // polar coordinates (not used in graham scan)
9     double r() { return Math.sqrt(x * x + y * y); }
10    double d() { return Math.atan2(y, x); }
11 }
12
13 // turn is counter-clockwise if > 0; collinear if = 0; clockwise else
14 static double ccw(P p1, P p2, P p3) {
15     return (p2.x - p1.x) * (p3.y - p1.y) - (p2.y - p1.y) * (p3.x - p1.x);
16 }
17
18 static List<P> graham(List<P> l) {
19     if (l.size() < 3)
20         return l;
21     P temp = l.get(0);
22     for (P p : l)

```

```

23     if (temp.y > p.y || temp.y == p.y && temp.x > p.x)
24         temp = p;
25     final P start = temp; // min y (then leftmost)
26
27     Collections.sort(l, new Comparator<P>() {
28         public int compare(P o1, P o2) {
29             if (new Double(Math.atan2(o1.y - start.y, o1.x -
30                 start.x)) // same angle
31                 .compareTo(Math.atan2(o2.y - start.y, o2.x -
32                     start.x)) == 0)
33                     return new Double((o1.x - start.x) * (o1.x -
34                         start.x)
35                         + (o1.y - start.y) * (o1.y - start.y))
36                         .compareTo((o2.x - start.x) * (o2.x -
37                             start.x)
38                             + (o2.y - start.y) * (o2.y - start.y));
39                     // use distance
40             return new Double(Math.atan2(o1.y - start.y,
41                 o1.x - start.x))
42                 .compareTo(Math.atan2(o2.y - start.y, o2.x -
43                     start.x));
44         }
45     });
46     Stack<P> s = new Stack<P>();
47     s.add(start);
48     s.add(l.get(1));
49     for (int i = 2; i < l.size(); i++) {
50         while (s.size() >= 2
51             && ccw(s.get(s.size() - 2), s.get(s.size() - 1),
52                 l.get(i)) <= 0)
53             s.pop();
54         s.push(l.get(i));
55     }
56     return s;
57 }

```

### 4.3 Maximum Distance in a Point Set

```

1 List<P> hull = graham(list);
2 maxDist(hull);
3
4 static double dist(P p1, P p2) {
5     return Math.sqrt((p1.x - p2.x) * (p1.x - p2.x)
6         + (p1.y - p2.y) * (p1.y - p2.y));
7 }
8
9 static double maxDist(List<P> hull) {
10     double max = 0, tmp = 0;
11     int j = 0, n = hull.size();
12     for (P p : hull) {
13         for (P q : hull) {
14             if (p == q) continue;
15             tmp = dist(p, q);
16             max = Math.max(max, tmp);
17         }
18     }
19     return max;
20 }

```

### 4.4 Area of a Polygon

```

1 // area of a polygon, e.g. area(gham(list))
2 static double area(List<P> l) {
3     double sum = 0;
4     // points must be in ccw order, otherwise
5     // negative area returned
6     for (int i = 0; i < l.size(); i++) {
7         sum += l.get(i).x * l.get((i + 1) % l.size()).y;
8         sum -= l.get(i).y * l.get((i + 1) % l.size()).x;
9     }
10    return sum / 2;
11 }

```

### 4.5 Punkt in Polygon

```

1 /**
2  * -1: A liegt links von BC (ausser unterer
3  * Endpunkt)
4  * 0: A auf BC
5  * +1: sonst
6  */
7 public static int KreuzProdTest(double ax, double ay,
8     double bx, double by,
9     double cx, double cy) {
10     if (ay == by && by == cy) {
11         if ((bx <= ax && ax <= cx) || (cx <= ax && ax <=
12             bx)) return 0;
13         else return +1;
14     }
15     if (by > cy) {
16         double tmpx = bx, tmpy = by;
17         bx = cx;
18         by = cy;
19         cx = tmpx;
20         cy = tmpy;
21     }
22     if (ay == by && ax == bx) return 0;
23     if (ay <= by || ay > cy) return +1;
24     double delta = (bx - ax) * (cy - ay) - (by - ay) *
25         (cx - ax);
26     if (delta > 0) return -1;
27     else if (delta < 0) return +1;
28     else return 0;
29 }
30
31 /**
32  * Input: P[i] (x[i],y[i]); P[0]:=P[n]
33  * -1: Q ausserhalb Polygon
34  * 0: Q auf Polygon
35  * +1: Q innerhalb des Polygons
36  */
37 public static int PunktInPoly(double[] x, double[] y,
38     double qx, double qy) {
39     int t = -1;
40     for (int i = 0; i < x.length - 1; i++)
41         t = t * KreuzProdTest(qx, qy, x[i], y[i], x[i + 1],
42             y[i + 1]);
43     return t;
44 }

```

## 5 Verschiedenes

### 5.1 Potenzmenge

```

1 static <T> Iterator<List<T>> powerSet(final List<T> l) {
2     return new Iterator<List<T>>() {
3         int i; // careful: i becomes 2^l.size()
4         public boolean hasNext() {
5             return i < (1 << l.size());
6         }
7         public List<T> next() {
8             Vector<T> temp = new Vector<T>();
9             for (int j = 0; j < l.size(); j++)
10                 if (((i >> j) & 1) == 1)
11                     temp.add(l.get(j));
12             i++;
13             return temp;
14         }
15         public void remove() {}
16     };
17 }

```

### 5.2 Longest Common Subsequence

```

1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <string.h>
4
5

```

```

6 int lcs( char *a, char *b){
7     int len = strlen( a);
8     int lenb =strlen(b);
9
10    int *zeile = malloc( (len+1) * sizeof(int)), *▼
        temp,
11        *neue = malloc( (len+1) * sizeof(int)), i, j▼
        ;
12
13    for(i=0; i<len+1; i++){
14        zeile[i] = neue[i] = 0;
15    }
16
17    for(j=0; j<lenb; j++){
18        for(i=0; i<len; i++){
19            if( a[i] == b[j]){
20                neue[i+1] = zeile[i] + 1;
21            } else {
22                neue[i+1] = neue[i] > zeile[i+1] ? ▼
                    neue[i] : zeile[i+1];
23            }
24        }
25        temp = zeile;
26        zeile = neue;
27        neue = temp;
28    }
29
30    int res = zeile[len];
31    free( zeile);
32    free( neue);
33    return res;
34 }

```

### 5.3 Longest Increasing Subsequence

```

1 #include <stdio.h>
2 #include <stdlib.h>
3
4 int lis( int *list, int n){
5     int *sorted = malloc( n*sizeof(int)), sorted_n;

```

```

6     int i, *lower, *upper, *mid, *pos;
7
8     if( n == 0) return 0;
9
10    sorted[0] = list[0];
11    sorted_n = 1;
12
13    for( i=1; i<n; i++){
14        /* binaere Suche */
15        lower = list;
16        upper = list + sorted_n;
17        mid = list + sorted_n / 2;
18
19
20        while( lower < upper-1){
21            if( list[i] < *mid){
22                upper = mid;
23            } else {
24                lower = mid;
25            }
26
27            mid = lower + (upper-lower) / 2;
28        }
29
30        if( mid == list + sorted_n -1 && *mid < list[i]){
31            *mid = list[i];
32            sorted_n++;
33        }
34
35        if( list[i] < *mid){
36            *mid = list[i];
37        }
38    }
39
40    free( sorted);
41
42    return sorted_n;
43 }

```

## 6 Eine kleine C-Referenz

C Reference Card (ANSI)

Program Structure/Functions

function declarations  
external variable declarations  
main routine  
local variable declarations  
function definition  
local variable declarations  
declarations  
statements  
return value;  
/\* \*/  
main(int argc, char \*argv[])  
exit(arg)

C Preprocessor

include library file  
include user file  
replacement text  
replacement macro  
Example. #define max(A,B) ((A)>(B) ? (A) : (B))  
#undef name  
#  
##  
#if, #else, #elif, #endif  
#ifdef, #ifndef  
defined(name)  
\  
quoted string in replace  
concatenate args and rescan  
conditional execution  
is name defined, not defined?  
line continuation char

Data Types/Declarations

character (1 byte)  
integer  
float (single precision)  
float (double precision)  
short (16 bit integer)  
long (32 bit integer)  
positive and negative  
only positive  
pointer to int, float,...  
enumeration constant  
constant (unchanging) value  
declare external variable  
register variable  
local to source file  
no value  
structure  
create name by data type  
size of an object (type is size\_t)  
size of a data type (type is size\_t)  
char  
int  
float  
double  
short  
long  
signed  
unsigned  
\*int, \*float,...  
enum  
const  
extern  
register  
static  
void  
struct  
typedef type name  
sizeof object  
sizeof (type name)

Initialization

initialize variable  
initialize array  
initialize char string  
type name=value  
type name[]={value1,...}  
char name[]="string"

Constants

long (suffix)  
float (suffix)  
exponential form  
octal (prefix zero)  
hexadecimal (prefix zero-ex)  
character constant (char, octal, hex)  
newline, cr, tab, backspace  
special characters  
string constant (ends with '\0')  
L or l  
F or f  
e  
0  
0x or 0X  
'a', '\ooo', '\xhh',  
n, r, t, b  
\\, \?, \', \", \  
"abc...de"

Pointers, Arrays & Structures

declare pointer to type  
declare function returning pointer to type type \*f()  
declare pointer to function returning type type (\*pf)()  
generic pointer type  
void \*  
NULL  
object pointed to by pointer  
address of object name  
array  
multi-dim array  
name[dim]  
name[dim1][dim2]...  
structure template  
declaration of members  
struct tag {  
declarations  
};  
create structure  
member of structure from template  
member of pointed to structure  
pointer -> member  
Example. (\*p).x and p->x are the same  
single value, multiple type structure  
union  
member : b

Structures

struct tag {  
declarations  
};  
create structure  
member of structure from template  
member of pointed to structure  
pointer -> member  
Example. (\*p).x and p->x are the same  
single value, multiple type structure  
union  
member : b

Operators (grouped by precedence)

structure member operator  
structure pointer  
increment, decrement  
plus, minus, logical not, bitwise not  
indirection via pointer, address of object  
cast expression to type  
size of an object  
multiply, divide, modulus (remainder)  
\*, /, %  
add, subtract  
+, -  
left, right shift [bit ops]  
<<, >>  
comparisons  
>, >=, <, <=  
comparisons  
==, !=  
bitwise and  
&  
bitwise exclusive or  
^  
bitwise or (incl)  
|  
logical and  
&&  
logical or  
||  
conditional expression  
expr1 ? expr2 : expr3  
assignment operators  
+=, -=, \*=, ...  
expression evaluation separator  
,

Unary operators, conditional expression and assignment operators group right to left; all others group left to right.

Flow of Control

statement terminator  
block delimiters  
exit from switch, while, do, for  
next iteration of while, do, for  
go to  
label  
return value from function  
Flow Constructions  
if statement  
if (expr) statement  
else if (expr) statement  
else statement  
while (expr) statement  
for (expr1; expr2; expr3) statement  
do statement  
while(expr);  
switch statement  
switch (expr) {  
case const1: statement1 break;  
case const2: statement2 break;  
default: statement  
}  
statement terminator  
{ }  
break  
continue  
goto label  
return expr

ANSI Standard Libraries

<assert.h> <ctype.h> <errno.h> <float.h> <limits.h>  
<locale.h> <math.h> <setjmp.h> <signal.h> <stdarg.h>  
<stddef.h> <stdio.h> <stdlib.h> <string.h> <time.h>

Character Class Tests <ctype.h>

alphanumeric?  
alphabetic?  
control character?  
decimal digit?  
lower case letter?  
printing character (not incl space)?  
printing character (incl space)?  
printing char except space, letter, digit?  
space, formfeed, newline, cr, tab, vtab?  
upper case letter?  
hexadecimal digit?  
convert to lower case?  
convert to upper case?  
isalnum(c)  
isalpha(c)  
iscntrl(c)  
isdigit(c)  
isgraph(c)  
islower(c)  
isprint(c)  
ispunct(c)  
isspace(c)  
isupper(c)  
isxdigit(c)  
tolower(c)  
toupper(c)

String Operations <string.h>

s, t are strings, cs, ct are constant strings  
length of s  
strcpy(s, ct)  
strncpy(s, ct, n)  
strcat(s, ct)  
strncat(s, ct, n)  
strcmp(cs, ct)  
strncmp(cs, ct, n)  
strchr(cs, c)  
strrchr(cs, c)  
memcpy(s, ct, n)  
memmove(s, ct, n)  
memcmp(cs, ct, n)  
memchr(cs, c, n)  
memset(s, c, n)



## C Reference Card (ANSI)

### Input/Output <stdio.h>

#### Standard I/O

standard input stream  
standard output stream  
standard error stream  
end of file  
get a character  
print a character  
print formatted data  
print to string *s*  
read formatted data  
read from string *s*  
read line to string *s* (< max chars)  
print string *s*  
**File I/O**  
declare file pointer  
pointer to named file  
modes: *r* (read), *w* (write), *a* (append)  
get a character  
write a character  
write to file  
read from file  
close file  
non-zero if error  
non-zero if EOF  
read line to string *s* (< max chars)  
write string *s*  
**Codes for Formatted I/O: "%-+ 0w.pmic"**  
- left justify  
+ print with sign  
*space* print space if no sign  
0 pad with leading zeros  
*w* min field width  
*p* precision  
*m* conversion character:  
  *h* short, *l* long, *L* long double  
*c* conversion character:  
  *d,i* integer  
  *u* unsigned  
  *c* single char  
  *s* char string  
  *f* double  
  *e,E* exponential  
  *o* octal  
  *x,X* hexadecimal  
  *p* pointer  
  *n* number of chars written  
*g,G* same as *f* or *e,E* depending on exponent

### Variable Argument Lists <stdarg.h>

declaration of pointer to arguments *va\_list name*;  
initialization of argument pointer *va\_start(name, lastarg)*  
*lastarg* is last named parameter of the function  
access next unnamed arg, update pointer *va\_arg(name, type)*  
call before exiting function *va\_end(name)*

### Standard Utility Functions <stdlib.h>

absolute value of int *n*  
absolute value of long *n*  
quotient and remainder of ints *n,d*  
return structure with *div\_t.quot* and *div\_t.rem*  
quotient and remainder of longs *n,d*  
returns structure with *ldiv\_t.quot* and *ldiv\_t.rem*  
pseudo-random integer [0, RAND\_MAX]  
rand()  
set random seed to *n*  
terminate program execution  
pass string *s* to system for execution  
**Conversions**  
convert string *s* to double  
convert string *s* to integer  
convert string *s* to long  
convert string *s* to long  
convert prefix of *s* to double  
convert prefix of *s* (base *b*) to long  
same, but unsigned long  
strtoul(*s*, endp, *b*)

**Storage Allocation**  
allocate storage  
change size of object  
deallocate space  
**Array Functions**  
search array for key  
sort array ascending order  
bsearch(*key*, array, *n*, size, cmp())  
qsort(array, *n*, size, cmp())

### Time and Date Functions <time.h>

processor time used by program  
Example: clock()/CLOCKS\_PER\_SEC is time in seconds  
current calendar time  
time2-time<sub>1</sub> in seconds (double)  
arithmetic types representing times  
structure type for calendar time comps  
tm\_sec seconds after minute  
tm\_min minutes after hour  
tm\_hour hours since midnight  
tm\_mday day of month  
tm\_mon months since January  
tm\_year years since 1900  
tm\_wday days since Sunday  
tm\_yday days since January 1  
tm\_isdst Daylight Savings Time flag  
convert local time to calendar time  
convert time in *tp* to string  
convert calendar time in *tp* to local time  
convert calendar time to GMT  
convert calendar time to local time  
format date and time info  
*tp* is a pointer to a structure of type tm  
strftime(*s*, smax, "format", *tp*)

### Mathematical Functions <math.h>

Arguments and returned values are double  
trig functions  
inverse trig functions  
arctan(*y/x*)  
hyperbolic trig functions  
exponentials & logs  
exponentials & logs (2 power)  
division & remainder  
powers  
rounding  
sin(*x*), cos(*x*), tan(*x*)  
asin(*x*), acos(*x*), atan(*x*)  
atan2(*y,x*)  
sinh(*x*), cosh(*x*), tanh(*x*)  
exp(*x*), log(*x*), log10(*x*)  
ldexp(*x,n*), frexp(*x,\*e*)  
modf(*x,\*ip*), fmod(*x,y*)  
pow(*x,y*), sqrt(*x*)  
ceil(*x*), floor(*x*), fabs(*x*)

### Integer Type Limits <limits.h>

The numbers given in parentheses are typical values for the constants on a 32-bit Unix system.

CHAR\_BIT bits in char (8)  
CHAR\_MAX max value of char (127 or 255)  
CHAR\_MIN min value of char (-128 or 0)  
INT\_MAX max value of int (+32,767)  
INT\_MIN min value of int (-32,768)  
LONG\_MAX max value of long (+2,147,483,647)  
LONG\_MIN min value of long (-2,147,483,648)  
SCHAR\_MAX max value of signed char (+127)  
SCHAR\_MIN min value of signed char (-128)  
SHRT\_MAX max value of short (+32,767)  
SHRT\_MIN min value of short (-32,768)  
UCHAR\_MAX max value of unsigned char (255)  
UINT\_MAX max value of unsigned int (65,535)  
ULONG\_MAX max value of unsigned long (4,294,967,295)  
USHRT\_MAX max value of unsigned short (65,536)

### Float Type Limits <float.h>

FLT\_RADIX radix of exponent rep (2)  
FLT\_ROUNDS floating point rounding mode (6)  
FLT\_DIG decimal digits of precision (10-5)  
FLT\_EPSILON smallest *x* so  $1.0 + x \neq 1.0$   
FLT\_MANT\_DIG number of digits in mantissa (10<sup>37</sup>)  
FLT\_MAX maximum floating point number  
FLT\_MAX\_EXP maximum exponent (10-37)  
FLT\_MIN minimum floating point number  
FLT\_MIN\_EXP minimum exponent (10)  
DBL\_DIG decimal digits of precision (10-9)  
DBL\_EPSILON smallest *x* so  $1.0 + x \neq 1.0$   
DBL\_MANT\_DIG number of digits in mantissa (10<sup>37</sup>)  
DBL\_MAX max double floating point number  
DBL\_MAX\_EXP maximum exponent (10-37)  
DBL\_MIN min double floating point number  
DBL\_MIN\_EXP minimum exponent

May 1999 v1.3. Copyright © 1999 Joseph H. Silverman

Permission is granted to make and distribute copies of this card provided the copyright notice and this permission notice are preserved on all copies.

Send comments and corrections to J.H. Silverman, Math. Dept., Brown Univ., Providence, RI 02912 USA. (jhs@math.brown.edu)



## Theoretical Computer Science Cheat Sheet

Definitions		Series	
$f(n) = O(g(n))$	iff $\exists$ positive $c, n_0$ such that $0 \leq f(n) \leq cg(n) \forall n \geq n_0$ .	$\sum_{i=1}^n i = \frac{n(n+1)}{2}, \quad \sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}, \quad \sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4}.$	
$f(n) = \Omega(g(n))$	iff $\exists$ positive $c, n_0$ such that $f(n) \geq cg(n) \geq 0 \forall n \geq n_0$ .	In general:	
$f(n) = \Theta(g(n))$	iff $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$ .	$\sum_{i=1}^n i^m = \frac{1}{m+1} \left[ (n+1)^{m+1} - 1 - \sum_{i=1}^n ((i+1)^{m+1} - i^{m+1} - (m+1)i^m) \right]$	
$f(n) = o(g(n))$	iff $\lim_{n \rightarrow \infty} f(n)/g(n) = 0$ .	$\sum_{i=1}^{n-1} i^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k n^{m+1-k}.$	
$\lim_{n \rightarrow \infty} a_n = a$	iff $\forall \epsilon > 0, \exists n_0$ such that $ a_n - a  < \epsilon, \forall n \geq n_0$ .	Geometric series:	
$\sup S$	least $b \in \mathbb{R}$ such that $b \geq s, \forall s \in S$ .	$\sum_{i=0}^n c^i = \frac{c^{n+1} - 1}{c - 1}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} c^i = \frac{1}{1 - c}, \quad \sum_{i=1}^{\infty} c^i = \frac{c}{1 - c}, \quad  c  < 1,$	
$\inf S$	greatest $b \in \mathbb{R}$ such that $b \leq s, \forall s \in S$ .	$\sum_{i=0}^n ic^i = \frac{nc^{n+2} - (n+1)c^{n+1} + c}{(c-1)^2}, \quad c \neq 1, \quad \sum_{i=0}^{\infty} ic^i = \frac{c}{(1-c)^2}, \quad  c  < 1.$	
$\liminf_{n \rightarrow \infty} a_n$	$\lim_{n \rightarrow \infty} \inf \{a_i \mid i \geq n, i \in \mathbb{N}\}.$	Harmonic series:	
$\limsup_{n \rightarrow \infty} a_n$	$\lim_{n \rightarrow \infty} \sup \{a_i \mid i \geq n, i \in \mathbb{N}\}.$	$H_n = \sum_{i=1}^n \frac{1}{i}, \quad \sum_{i=1}^n iH_i = \frac{n(n+1)}{2} H_n - \frac{n(n-1)}{4}.$	
$\binom{n}{k}$	Combinations: Size $k$ sub-sets of a size $n$ set.	$\sum_{i=1}^n H_i = (n+1)H_n - n, \quad \sum_{i=1}^n \binom{i}{m} H_i = \binom{n+1}{m+1} \left( H_{n+1} - \frac{1}{m+1} \right).$	
$[n_k]$	Stirling numbers (1st kind): Arrangements of an $n$ element set into $k$ cycles.	1. $\binom{n}{k} = \frac{n!}{(n-k)!k!}, \quad 2. \sum_{k=0}^n \binom{n}{k} = 2^n, \quad 3. \binom{n}{k} = \binom{n}{n-k},$	
$\{n_k\}$	Stirling numbers (2nd kind): Partitions of an $n$ element set into $k$ non-empty sets.	4. $\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}, \quad 5. \binom{n}{k} = \binom{n-1}{k} + \binom{n-1}{k-1},$	
$\langle n_k \rangle$	1st order Eulerian numbers: Permutations $\pi_1 \pi_2 \dots \pi_n$ on $\{1, 2, \dots, n\}$ with $k$ ascents.	6. $\binom{n}{m} \binom{m}{k} = \binom{n}{k} \binom{n-k}{m-k}, \quad 7. \sum_{k=0}^n \binom{r+k}{k} = \binom{r+n+1}{n},$	
$\langle\langle n_k \rangle\rangle$	2nd order Eulerian numbers.	8. $\sum_{k=0}^n \binom{k}{m} = \binom{n+1}{m+1}, \quad 9. \sum_{k=0}^n \binom{r}{k} \binom{s}{n-k} = \binom{r+s}{n},$	
$C_n$	Catalan Numbers: Binary trees with $n+1$ vertices.	10. $\binom{n}{k} = (-1)^k \binom{k-n-1}{k}, \quad 11. \left\{ \begin{matrix} n \\ 1 \end{matrix} \right\} = \left\{ \begin{matrix} n \\ n \end{matrix} \right\} = 1,$	
14. $\begin{bmatrix} n \\ 1 \end{bmatrix} = (n-1)!,$	15. $\begin{bmatrix} n \\ 2 \end{bmatrix} = (n-1)!H_{n-1},$	16. $\begin{bmatrix} n \\ n \end{bmatrix} = 1,$	17. $\begin{bmatrix} n \\ k \end{bmatrix} \geq \left\{ \begin{matrix} n \\ k \end{matrix} \right\},$
18. $\begin{bmatrix} n \\ k \end{bmatrix} = (n-1) \begin{bmatrix} n-1 \\ k \end{bmatrix} + \begin{bmatrix} n-1 \\ k-1 \end{bmatrix},$	19. $\left\{ \begin{matrix} n \\ n-1 \end{matrix} \right\} = \begin{bmatrix} n \\ n-1 \end{bmatrix} = \binom{n}{2},$	20. $\sum_{k=0}^n \begin{bmatrix} n \\ k \end{bmatrix} = n!,$	21. $C_n = \frac{1}{n+1} \binom{2n}{n},$
22. $\langle n_0 \rangle = \langle n_{n-1} \rangle = 1,$	23. $\langle n_k \rangle = \langle n_{n-1-k} \rangle,$	24. $\langle n_k \rangle = (k+1) \langle n_{k-1} \rangle + (n-k) \langle n_{k-1} \rangle,$	
25. $\langle k_0 \rangle = \begin{cases} 1 & \text{if } k=0, \\ 0 & \text{otherwise} \end{cases}$	26. $\langle n_1 \rangle = 2^n - n - 1,$	27. $\langle n_2 \rangle = 3^n - (n+1)2^n + \binom{n+1}{2},$	
28. $x^n = \sum_{k=0}^n \langle n_k \rangle \binom{x+k}{n},$	29. $\langle n_m \rangle = \sum_{k=0}^m \binom{n+1}{k} (m+1-k)^n (-1)^k,$	30. $m! \left\{ \begin{matrix} n \\ m \end{matrix} \right\} = \sum_{k=0}^n \langle n_k \rangle \binom{k}{n-m},$	
31. $\langle n_m \rangle = \sum_{k=0}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\} \binom{n-k}{m} (-1)^{n-k-m} k!,$	32. $\langle\langle n_0 \rangle\rangle = 1,$	33. $\langle\langle n_n \rangle\rangle = 0 \quad \text{for } n \neq 0,$	
34. $\langle\langle n_k \rangle\rangle = (k+1) \langle\langle n_{k-1} \rangle\rangle + (2n-1-k) \langle\langle n_{k-1} \rangle\rangle,$		35. $\sum_{k=0}^n \langle\langle n_k \rangle\rangle = \frac{(2n)^n}{2^n},$	
36. $\left\{ \begin{matrix} x \\ x-n \end{matrix} \right\} = \sum_{k=0}^n \langle\langle n_k \rangle\rangle \binom{x+n-1-k}{2n},$		37. $\left\{ \begin{matrix} n+1 \\ m+1 \end{matrix} \right\} = \sum_k \binom{n}{k} \left\{ \begin{matrix} k \\ m \end{matrix} \right\} = \sum_{k=0}^n \left\{ \begin{matrix} k \\ m \end{matrix} \right\} (m+1)^{n-k},$	


## Theoretical Computer Science Cheat Sheet

Identities Cont.		Trees
<p>38. <math>\begin{bmatrix} n+1 \\ m+1 \end{bmatrix} = \sum_k \begin{bmatrix} n \\ k \end{bmatrix} \begin{bmatrix} k \\ m \end{bmatrix} = \sum_{k=0}^n \begin{bmatrix} k \\ m \end{bmatrix} n^{\overline{n-k}} = n! \sum_{k=0}^n \frac{1}{k!} \begin{bmatrix} k \\ m \end{bmatrix},</math></p> <p>40. <math>\left\{ \begin{matrix} n \\ m \end{matrix} \right\} = \sum_k \binom{n}{k} \left\{ \begin{matrix} k+1 \\ m+1 \end{matrix} \right\} (-1)^{n-k},</math></p> <p>42. <math>\left\{ \begin{matrix} m+n+1 \\ m \end{matrix} \right\} = \sum_{k=0}^m k \left\{ \begin{matrix} n+k \\ k \end{matrix} \right\},</math></p> <p>44. <math>\binom{n}{m} = \sum_k \left\{ \begin{matrix} n+1 \\ k+1 \end{matrix} \right\} \begin{bmatrix} k \\ m \end{bmatrix} (-1)^{m-k},</math></p> <p>46. <math>\left\{ \begin{matrix} n \\ n-m \end{matrix} \right\} = \sum_k \binom{m-n}{m+k} \binom{m+n}{n+k} \begin{bmatrix} m+k \\ k \end{bmatrix},</math></p> <p>48. <math>\left\{ \begin{matrix} n \\ \ell+m \end{matrix} \right\} \binom{\ell+m}{\ell} = \sum_k \left\{ \begin{matrix} k \\ \ell \end{matrix} \right\} \left\{ \begin{matrix} n-k \\ m \end{matrix} \right\} \binom{n}{k},</math></p>	<p>39. <math>\begin{bmatrix} x \\ x-n \end{bmatrix} = \sum_{k=0}^n \left\langle \begin{matrix} n \\ k \end{matrix} \right\rangle \binom{x+k}{2n},</math></p> <p>41. <math>\begin{bmatrix} n \\ m \end{bmatrix} = \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \binom{k}{m} (-1)^{m-k},</math></p> <p>43. <math>\begin{bmatrix} m+n+1 \\ m \end{bmatrix} = \sum_{k=0}^m k(n+k) \begin{bmatrix} n+k \\ k \end{bmatrix},</math></p> <p>45. <math>(n-m)! \binom{n}{m} = \sum_k \begin{bmatrix} n+1 \\ k+1 \end{bmatrix} \left\{ \begin{matrix} k \\ m \end{matrix} \right\} (-1)^{m-k}, \text{ for } n \geq m,</math></p> <p>47. <math>\begin{bmatrix} n \\ n-m \end{bmatrix} = \sum_k \binom{m-n}{m+k} \binom{m+n}{n+k} \left\{ \begin{matrix} m+k \\ k \end{matrix} \right\},</math></p> <p>49. <math>\begin{bmatrix} n \\ \ell+m \end{bmatrix} \binom{\ell+m}{\ell} = \sum_k \begin{bmatrix} k \\ \ell \end{bmatrix} \begin{bmatrix} n-k \\ m \end{bmatrix} \binom{n}{k}.</math></p>	<p>Every tree with <math>n</math> vertices has <math>n-1</math> edges.</p> <p>Kraft inequality: If the depths of the leaves of a binary tree are <math>d_1, \dots, d_n</math>:</p> $\sum_{i=1}^n 2^{-d_i} \leq 1,$ <p>and equality holds only if every internal node has 2 sons.</p>
Recurrences		
<p>Master method:</p> $T(n) = aT(n/b) + f(n), \quad a \geq 1, b > 1$ <p>If <math>\exists \epsilon &gt; 0</math> such that <math>f(n) = O(n^{\log_b a - \epsilon})</math> then</p> $T(n) = \Theta(n^{\log_b a}).$ <p>If <math>f(n) = \Theta(n^{\log_b a})</math> then</p> $T(n) = \Theta(n^{\log_b a} \log_2 n).$ <p>If <math>\exists \epsilon &gt; 0</math> such that <math>f(n) = \Omega(n^{\log_b a + \epsilon})</math>, and <math>\exists c &lt; 1</math> such that <math>af(n/b) \leq cf(n)</math> for large <math>n</math>, then</p> $T(n) = \Theta(f(n)).$ <p>Substitution (example): Consider the following recurrence</p> $T_{i+1} = 2^{2^i} \cdot T_i^2, \quad T_1 = 2.$ <p>Note that <math>T_i</math> is always a power of two. Let <math>t_i = \log_2 T_i</math>. Then we have</p> $t_{i+1} = 2^i + 2t_i, \quad t_1 = 1.$ <p>Let <math>u_i = t_i/2^i</math>. Dividing both sides of the previous equation by <math>2^{i+1}</math> we get</p> $\frac{t_{i+1}}{2^{i+1}} = \frac{2^i}{2^{i+1}} + \frac{t_i}{2^i}.$ <p>Substituting we find</p> $u_{i+1} = \frac{1}{2} + u_i, \quad u_1 = \frac{1}{2},$ <p>which is simply <math>u_i = i/2</math>. So we find that <math>T_i</math> has the closed form <math>T_i = 2^{i2^{i-1}}</math>.</p> <p>Summing factors (example): Consider the following recurrence</p> $T(n) = 3T(n/2) + n, \quad T(1) = 1.$ <p>Rewrite so that all terms involving <math>T</math> are on the left side</p> $T(n) - 3T(n/2) = n.$ <p>Now expand the recurrence, and choose a factor which makes the left side "telescope"</p>	<p>1(<math>T(n) - 3T(n/2) = n</math>)</p> $3(T(n/2) - 3T(n/4) = n/2)$ $\vdots$ $3^{\log_2 n - 1} (T(2) - 3T(1) = 2)$ <p>Let <math>m = \log_2 n</math>. Summing the left side we get <math>T(n) - 3^m T(1) = T(n) - 3^m = T(n) - n^k</math> where <math>k = \log_2 3 \approx 1.58496</math>. Summing the right side we get</p> $\sum_{i=0}^{m-1} \frac{n}{2^i} 3^i = n \sum_{i=0}^{m-1} \left(\frac{3}{2}\right)^i.$ <p>Let <math>c = \frac{3}{2}</math>. Then we have</p> $n \sum_{i=0}^{m-1} c^i = n \left( \frac{c^m - 1}{c - 1} \right)$ $= 2n(c^{\log_2 n} - 1)$ $= 2n(c^{(\log_2 n) \log_2 c} - 1)$ $= 2n^k - 2n,$ <p>and so <math>T(n) = 3n^k - 2n</math>. Full history recurrences can often be changed to limited history ones (example): Consider</p> $T_i = 1 + \sum_{j=0}^{i-1} T_j, \quad T_0 = 1.$ <p>Note that</p> $T_{i+1} = 1 + \sum_{j=0}^i T_j.$ <p>Subtracting we find</p> $T_{i+1} - T_i = 1 + \sum_{j=0}^i T_j - 1 - \sum_{j=0}^{i-1} T_j$ $= T_i.$ <p>And so <math>T_{i+1} = 2T_i = 2^{i+1}</math>.</p>	<p>Generating functions:</p> <ol style="list-style-type: none"> <li>1. Multiply both sides of the equation by <math>x^i</math>.</li> <li>2. Sum both sides over all <math>i</math> for which the equation is valid.</li> <li>3. Choose a generating function <math>G(x)</math>. Usually <math>G(x) = \sum_{i=0}^{\infty} x^i g_i</math>.</li> <li>3. Rewrite the equation in terms of the generating function <math>G(x)</math>.</li> <li>4. Solve for <math>G(x)</math>.</li> <li>5. The coefficient of <math>x^i</math> in <math>G(x)</math> is <math>g_i</math>.</li> </ol> <p>Example:</p> $g_{i+1} = 2g_i + 1, \quad g_0 = 0.$ <p>Multiply and sum:</p> $\sum_{i \geq 0} g_{i+1} x^i = \sum_{i \geq 0} 2g_i x^i + \sum_{i \geq 0} x^i.$ <p>We choose <math>G(x) = \sum_{i \geq 0} x^i g_i</math>. Rewrite in terms of <math>G(x)</math>:</p> $\frac{G(x) - g_0}{x} = 2G(x) + \sum_{i \geq 0} x^i.$ <p>Simplify:</p> $\frac{G(x)}{x} = 2G(x) + \frac{1}{1-x}.$ <p>Solve for <math>G(x)</math>:</p> $G(x) = \frac{x}{(1-x)(1-2x)}.$ <p>Expand this using partial fractions:</p> $G(x) = x \left( \frac{2}{1-2x} - \frac{1}{1-x} \right)$ $= x \left( 2 \sum_{i \geq 0} 2^i x^i - \sum_{i \geq 0} x^i \right)$ $= \sum_{i \geq 0} (2^{i+1} - 1) x^{i+1}.$ <p>So <math>g_i = 2^i - 1</math>.</p>

Theoretical Computer Science Cheat Sheet				
$\pi \approx 3.14159,$ $e \approx 2.71828,$ $\gamma \approx 0.57721,$ $\phi = \frac{1+\sqrt{5}}{2} \approx 1.61803,$ $\hat{\phi} = \frac{1-\sqrt{5}}{2} \approx -0.61803$				
$i$	$2^i$	$p_i$	General	Probability
1	2	2	Bernoulli Numbers ( $B_i = 0$ , odd $i \neq 1$ ):	Continuous distributions: If
2	4	3	$B_0 = 1, B_1 = -\frac{1}{2}, B_2 = \frac{1}{6}, B_4 = -\frac{1}{30},$	$\Pr[a < X < b] = \int_a^b p(x) dx,$
3	8	5	$B_6 = \frac{1}{42}, B_8 = -\frac{1}{30}, B_{10} = \frac{5}{66}.$	then $p$ is the probability density function of $X$ . If
4	16	7	Change of base, quadratic formula:	$\Pr[X < a] = P(a),$
5	32	11	$\log_b x = \frac{\log_a x}{\log_a b}, \quad \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}.$	then $P$ is the distribution function of $X$ . If $P$ and $p$ both exist then
6	64	13	Euler's number $e$ :	$P(a) = \int_{-\infty}^a p(x) dx.$
7	128	17	$e = 1 + \frac{1}{2} + \frac{1}{6} + \frac{1}{24} + \frac{1}{120} + \dots$	Expectation: If $X$ is discrete
8	256	19	$\lim_{n \rightarrow \infty} \left(1 + \frac{x}{n}\right)^n = e^x.$	$E[g(X)] = \sum_x g(x) \Pr[X = x].$
9	512	23	$\left(1 + \frac{1}{n}\right)^n < e < \left(1 + \frac{1}{n}\right)^{n+1}.$	If $X$ continuous then
10	1,024	29	$\left(1 + \frac{1}{n}\right)^n = e - \frac{e}{2n} + \frac{11e}{24n^2} - O\left(\frac{1}{n^3}\right).$	$E[g(X)] = \int_{-\infty}^{\infty} g(x)p(x) dx = \int_{-\infty}^{\infty} g(x) dP(x).$
11	2,048	31	Harmonic numbers:	Variance, standard deviation:
12	4,096	37	$1, \frac{3}{2}, \frac{11}{6}, \frac{25}{12}, \frac{137}{60}, \frac{49}{20}, \frac{363}{140}, \frac{761}{280}, \frac{7129}{2520}, \dots$	$\text{VAR}[X] = E[X^2] - E[X]^2,$
13	8,192	41	$\ln n < H_n < \ln n + 1,$	$\sigma = \sqrt{\text{VAR}[X]}.$
14	16,384	43	$H_n = \ln n + \gamma + O\left(\frac{1}{n}\right).$	For events $A$ and $B$ :
15	32,768	47	Factorial, Stirling's approximation:	$\Pr[A \vee B] = \Pr[A] + \Pr[B] - \Pr[A \wedge B]$
16	65,536	53	$1, 2, 6, 24, 120, 720, 5040, 40320, 362880, \dots$	$\Pr[A \wedge B] = \Pr[A] \cdot \Pr[B],$
17	131,072	59	$n! = \sqrt{2\pi n} \left(\frac{n}{e}\right)^n \left(1 + \Theta\left(\frac{1}{n}\right)\right).$	iff $A$ and $B$ are independent.
18	262,144	61	Ackermann's function and inverse:	$\Pr[A B] = \frac{\Pr[A \wedge B]}{\Pr[B]}$
19	524,288	67	$a(i, j) = \begin{cases} 2^j & i = 1 \\ a(i-1, 2) & j = 1 \\ a(i-1, a(i, j-1)) & i, j \geq 2 \end{cases}$	For random variables $X$ and $Y$ :
20	1,048,576	71	$\alpha(i) = \min\{j \mid a(j, j) \geq i\}.$	$E[X \cdot Y] = E[X] \cdot E[Y],$
21	2,097,152	73		if $X$ and $Y$ are independent.
22	4,194,304	79		$E[X + Y] = E[X] + E[Y],$
23	8,388,608	83		$E[cX] = cE[X].$
24	16,777,216	89	Binomial distribution:	Bayes' theorem:
25	33,554,432	97	$\Pr[X = k] = \binom{n}{k} p^k q^{n-k}, \quad q = 1 - p,$	$\Pr[A_i B] = \frac{\Pr[B A_i] \Pr[A_i]}{\sum_{j=1}^n \Pr[A_j] \Pr[B A_j]}.$
26	67,108,864	101	$E[X] = \sum_{k=1}^n k \binom{n}{k} p^k q^{n-k} = np.$	Inclusion-exclusion:
27	134,217,728	103	Poisson distribution:	$\Pr\left[\bigvee_{i=1}^n X_i\right] = \sum_{i=1}^n \Pr[X_i] +$
28	268,435,456	107	$\Pr[X = k] = \frac{e^{-\lambda} \lambda^k}{k!}, \quad E[X] = \lambda.$	$\sum_{k=2}^n (-1)^{k+1} \sum_{i_1 < \dots < i_k} \Pr\left[\bigwedge_{j=1}^k X_{i_j}\right].$
29	536,870,912	109	Normal (Gaussian) distribution:	Moment inequalities:
30	1,073,741,824	113	$p(x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-(x-\mu)^2/2\sigma^2}, \quad E[X] = \mu.$	$\Pr[ X  \geq \lambda E[X]] \leq \frac{1}{\lambda},$
31	2,147,483,648	127	The "coupon collector": We are given a random coupon each day, and there are $n$ different types of coupons. The distribution of coupons is uniform. The expected number of days to pass before we to collect all $n$ types is	$\Pr[ X - E[X]  \geq \lambda \cdot \sigma] \leq \frac{1}{\lambda^2}.$
32	4,294,967,296	131	$nH_n.$	Geometric distribution:
Pascal's Triangle				$\Pr[X = k] = pq^{k-1}, \quad q = 1 - p,$
1				$E[X] = \sum_{k=1}^{\infty} kpq^{k-1} = \frac{1}{p}.$
1 1				
1 2 1				
1 3 3 1				
1 4 6 4 1				
1 5 10 10 5 1				
1 6 15 20 15 6 1				
1 7 21 35 35 21 7 1				
1 8 28 56 70 56 28 8 1				
1 9 36 84 126 126 84 36 9 1				
1 10 45 120 210 252 210 120 45 10 1				

Theoretical Computer Science Cheat Sheet																										
Trigonometry	Matrices	More Trig.																								
<div></div> <p>Pythagorean theorem: <math>C^2 = A^2 + B^2</math>.</p> <p>Definitions: <math>\sin a = A/C, \quad \cos a = B/C,</math> <math>\csc a = C/A, \quad \sec a = C/B,</math> <math>\tan a = \frac{\sin a}{\cos a} = \frac{A}{B}, \quad \cot a = \frac{\cos a}{\sin a} = \frac{B}{A}.</math></p> <p>Area, radius of inscribed circle: <math>\frac{1}{2}AB, \quad \frac{AB}{A+B+C}.</math></p> <p>Identities: <math>\sin x = \frac{1}{\csc x}, \quad \cos x = \frac{1}{\sec x},</math> <math>\tan x = \frac{1}{\cot x}, \quad \sin^2 x + \cos^2 x = 1,</math> <math>1 + \tan^2 x = \sec^2 x, \quad 1 + \cot^2 x = \csc^2 x,</math> <math>\sin x = \cos(\frac{\pi}{2} - x), \quad \sin x = \sin(\pi - x),</math> <math>\cos x = -\cos(\pi - x), \quad \tan x = \cot(\frac{\pi}{2} - x),</math> <math>\cot x = -\cot(\pi - x), \quad \csc x = \cot \frac{\pi}{2} - \cot x,</math> <math>\sin(x \pm y) = \sin x \cos y \pm \cos x \sin y,</math> <math>\cos(x \pm y) = \cos x \cos y \mp \sin x \sin y,</math> <math>\tan(x \pm y) = \frac{\tan x \pm \tan y}{1 \mp \tan x \tan y},</math> <math>\cot(x \pm y) = \frac{\cot x \cot y \mp 1}{\cot x \pm \cot y},</math> <math>\sin 2x = 2 \sin x \cos x, \quad \sin 2x = \frac{2 \tan x}{1 + \tan^2 x},</math> <math>\cos 2x = \cos^2 x - \sin^2 x, \quad \cos 2x = 2 \cos^2 x - 1,</math> <math>\cos 2x = 1 - 2 \sin^2 x, \quad \cos 2x = \frac{1 - \tan^2 x}{1 + \tan^2 x},</math> <math>\tan 2x = \frac{2 \tan x}{1 - \tan^2 x}, \quad \cot 2x = \frac{\cot^2 x - 1}{2 \cot x},</math> <math>\sin(x+y) \sin(x-y) = \sin^2 x - \sin^2 y,</math> <math>\cos(x+y) \cos(x-y) = \cos^2 x - \sin^2 y.</math></p> <p>Euler's equation: <math>e^{ix} = \cos x + i \sin x, \quad e^{i\pi} = -1.</math></p>	<p>Multiplication: <math>C = A \cdot B, \quad c_{i,j} = \sum_{k=1}^n a_{i,k} b_{k,j}.</math></p> <p>Determinants: <math>\det A \neq 0</math> iff <math>A</math> is non-singular. <math>\det A \cdot B = \det A \cdot \det B,</math> <math>\det A = \sum_{\pi} \prod_{i=1}^n \text{sign}(\pi) a_{i,\pi(i)}.</math></p> <p><math>2 \times 2</math> and <math>3 \times 3</math> determinant: <math>\begin{vmatrix} a &amp; b \\ c &amp; d \end{vmatrix} = ad - bc,</math> <math>\begin{vmatrix} a &amp; b &amp; c \\ d &amp; e &amp; f \\ g &amp; h &amp; i \end{vmatrix} = g \begin{vmatrix} b &amp; c \\ e &amp; f \end{vmatrix} - h \begin{vmatrix} a &amp; c \\ d &amp; f \end{vmatrix} + i \begin{vmatrix} a &amp; b \\ d &amp; e \end{vmatrix}</math> <math>= aei + bfg + cdh - ceg - fha - ibd.</math></p> <p>Permanents: <math>\text{perm } A = \sum_{\pi} \prod_{i=1}^n a_{i,\pi(i)}.</math></p>	<div></div> <p>Law of cosines: <math>c^2 = a^2 + b^2 - 2ab \cos C.</math></p> <p>Area: <math>A = \frac{1}{2}hc,</math> <math>= \frac{1}{2}ab \sin C,</math> <math>= \frac{c^2 \sin A \sin B}{2 \sin C}.</math></p> <p>Heron's formula: <math>A = \sqrt{s \cdot s_a \cdot s_b \cdot s_c},</math> <math>s = \frac{1}{2}(a + b + c),</math> <math>s_a = s - a,</math> <math>s_b = s - b,</math> <math>s_c = s - c.</math></p> <p>More identities: <math>\sin \frac{x}{2} = \sqrt{\frac{1 - \cos x}{2}},</math> <math>\cos \frac{x}{2} = \sqrt{\frac{1 + \cos x}{2}},</math> <math>\tan \frac{x}{2} = \sqrt{\frac{1 - \cos x}{1 + \cos x}},</math> <math>= \frac{1 - \cos x}{\sin x},</math> <math>= \frac{\sin x}{1 + \cos x},</math> <math>\cot \frac{x}{2} = \sqrt{\frac{1 + \cos x}{1 - \cos x}},</math> <math>= \frac{1 + \cos x}{\sin x},</math> <math>= \frac{\sin x}{1 - \cos x},</math> <math>\sin x = \frac{e^{ix} - e^{-ix}}{2i},</math> <math>\cos x = \frac{e^{ix} + e^{-ix}}{2},</math> <math>\tan x = -i \frac{e^{ix} - e^{-ix}}{e^{ix} + e^{-ix}},</math> <math>= -i \frac{e^{2ix} - 1}{e^{2ix} + 1},</math> <math>\sin x = \frac{\sinh ix}{i},</math> <math>\cos x = \cosh ix,</math> <math>\tan x = \frac{\tanh ix}{i}.</math></p>																								
Hyperbolic Functions																										
<p>Definitions: <math>\sinh x = \frac{e^x - e^{-x}}{2}, \quad \cosh x = \frac{e^x + e^{-x}}{2},</math> <math>\tanh x = \frac{e^x - e^{-x}}{e^x + e^{-x}}, \quad \text{csch } x = \frac{1}{\sinh x},</math> <math>\text{sech } x = \frac{1}{\cosh x}, \quad \coth x = \frac{1}{\tanh x}.</math></p> <p>Identities: <math>\cosh^2 x - \sinh^2 x = 1, \quad \tanh^2 x + \text{sech}^2 x = 1,</math> <math>\coth^2 x - \text{csch}^2 x = 1, \quad \sinh(-x) = -\sinh x,</math> <math>\cosh(-x) = \cosh x, \quad \tanh(-x) = -\tanh x,</math> <math>\sinh(x+y) = \sinh x \cosh y + \cosh x \sinh y,</math> <math>\cosh(x+y) = \cosh x \cosh y + \sinh x \sinh y,</math> <math>\sinh 2x = 2 \sinh x \cosh x,</math> <math>\cosh 2x = \cosh^2 x + \sinh^2 x,</math> <math>\cosh x + \sinh x = e^x, \quad \cosh x - \sinh x = e^{-x},</math> <math>(\cosh x + \sinh x)^n = \cosh nx + \sinh nx, \quad n \in \mathbb{Z},</math> <math>2 \sinh^2 \frac{x}{2} = \cosh x - 1, \quad 2 \cosh^2 \frac{x}{2} = \cosh x + 1.</math></p>																										
<table><tr><th><math>\theta</math></th><th><math>\sin \theta</math></th><th><math>\cos \theta</math></th><th><math>\tan \theta</math></th></tr><tr><td>0</td><td>0</td><td>1</td><td>0</td></tr><tr><td><math>\frac{\pi}{6}</math></td><td><math>\frac{1}{2}</math></td><td><math>\frac{\sqrt{3}}{2}</math></td><td><math>\frac{\sqrt{3}}{3}</math></td></tr><tr><td><math>\frac{\pi}{4}</math></td><td><math>\frac{\sqrt{2}}{2}</math></td><td><math>\frac{\sqrt{2}}{2}</math></td><td>1</td></tr><tr><td><math>\frac{\pi}{3}</math></td><td><math>\frac{\sqrt{3}}{2}</math></td><td><math>\frac{1}{2}</math></td><td><math>\sqrt{3}</math></td></tr><tr><td><math>\frac{\pi}{2}</math></td><td>1</td><td>0</td><td><math>\infty</math></td></tr></table>		$\theta$	$\sin \theta$	$\cos \theta$	$\tan \theta$	0	0	1	0	$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$	$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1	$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$	$\frac{\pi}{2}$	1	0	$\infty$	<p>... in mathematics you don't understand things, you just get used to them. - J. von Neumann</p>
$\theta$	$\sin \theta$	$\cos \theta$	$\tan \theta$																							
0	0	1	0																							
$\frac{\pi}{6}$	$\frac{1}{2}$	$\frac{\sqrt{3}}{2}$	$\frac{\sqrt{3}}{3}$																							
$\frac{\pi}{4}$	$\frac{\sqrt{2}}{2}$	$\frac{\sqrt{2}}{2}$	1																							
$\frac{\pi}{3}$	$\frac{\sqrt{3}}{2}$	$\frac{1}{2}$	$\sqrt{3}$																							
$\frac{\pi}{2}$	1	0	$\infty$																							
v2.02 ©1994 by Steve Seiden sseiden@acm.org <a href="http://www.csc.lsu.edu/~seiden">http://www.csc.lsu.edu/~seiden</a>																										

## Theoretical Computer Science Cheat Sheet

Number Theory	Graph Theory	
<p>The Chinese remainder theorem: There exists a number <math>C</math> such that:</p> $C \equiv r_1 \pmod{m_1}$ $\vdots$ $C \equiv r_n \pmod{m_n}$ <p>if <math>m_i</math> and <math>m_j</math> are relatively prime for <math>i \neq j</math>.  Euler's function: <math>\phi(x)</math> is the number of positive integers less than <math>x</math> relatively prime to <math>x</math>. If <math>\prod_{i=1}^n p_i^{e_i}</math> is the prime factorization of <math>x</math> then</p> $\phi(x) = \prod_{i=1}^n p_i^{e_i-1} (p_i - 1).$ <p>Euler's theorem: If <math>a</math> and <math>b</math> are relatively prime then</p> $1 \equiv a^{\phi(b)} \pmod{b}.$ <p>Fermat's theorem:</p> $1 \equiv a^{p-1} \pmod{p}.$ <p>The Euclidean algorithm: if <math>a &gt; b</math> are integers then</p> $\gcd(a, b) = \gcd(a \bmod b, b).$ <p>If <math>\prod_{i=1}^n p_i^{e_i}</math> is the prime factorization of <math>x</math> then</p> $S(x) = \sum_{d x} d = \prod_{i=1}^n \frac{p_i^{e_i+1} - 1}{p_i - 1}.$ <p>Perfect Numbers: <math>x</math> is an even perfect number iff <math>x = 2^{n-1}(2^n - 1)</math> and <math>2^n - 1</math> is prime.  Wilson's theorem: <math>n</math> is a prime iff</p> $(n-1)! \equiv -1 \pmod{n}.$ <p>Möbius inversion:</p> $\mu(i) = \begin{cases} 1 & \text{if } i = 1. \\ 0 & \text{if } i \text{ is not square-free.} \\ (-1)^r & \text{if } i \text{ is the product of } r \text{ distinct primes.} \end{cases}$ <p>If</p> $G(a) = \sum_{d a} F(d),$ <p>then</p> $F(a) = \sum_{d a} \mu(d) G\left(\frac{a}{d}\right).$ <p>Prime numbers:</p> $p_n = n \ln n + n \ln \ln n - n + n \frac{\ln \ln n}{\ln n} + O\left(\frac{n}{\ln n}\right),$ $\pi(n) = \frac{n}{\ln n} + \frac{n}{(\ln n)^2} + \frac{2!n}{(\ln n)^3} + O\left(\frac{n}{(\ln n)^4}\right).$	<p><b>Definitions:</b></p> <p><i>Loop</i> An edge connecting a vertex to itself.</p> <p><i>Directed</i> Each edge has a direction.</p> <p><i>Simple</i> Graph with no loops or multi-edges.</p> <p><i>Walk</i> A sequence <math>v_0 e_1 v_1 \dots e_\ell v_\ell</math>.</p> <p><i>Trail</i> A walk with distinct edges.</p> <p><i>Path</i> A trail with distinct vertices.</p> <p><i>Connected</i> A graph where there exists a path between any two vertices.</p> <p><i>Component</i> A maximal connected subgraph.</p> <p><i>Tree</i> A connected acyclic graph.</p> <p><i>Free tree</i> A tree with no root.</p> <p><i>DAG</i> Directed acyclic graph.</p> <p><i>Eulerian</i> Graph with a trail visiting each edge exactly once.</p> <p><i>Hamiltonian</i> Graph with a cycle visiting each vertex exactly once.</p> <p><i>Cut</i> A set of edges whose removal increases the number of components.</p> <p><i>Cut-set</i> A minimal cut.</p> <p><i>Cut edge</i> A size 1 cut.</p> <p><i>k-Connected</i> A graph connected with the removal of any <math>k-1</math> vertices.</p> <p><i>k-Tough</i> <math>\forall S \subseteq V, S \neq \emptyset</math> we have <math>k \cdot c(G-S) \leq  S </math>.</p> <p><i>k-Regular</i> A graph where all vertices have degree <math>k</math>.</p> <p><i>k-Factor</i> A <math>k</math>-regular spanning subgraph.</p> <p><i>Matching</i> A set of edges, no two of which are adjacent.</p> <p><i>Clique</i> A set of vertices, all of which are adjacent.</p> <p><i>Ind. set</i> A set of vertices, none of which are adjacent.</p> <p><i>Vertex cover</i> A set of vertices which cover all edges.</p> <p><i>Planar graph</i> A graph which can be embedded in the plane.</p> <p><i>Plane graph</i> An embedding of a planar graph.</p> <hr/> $\sum_{v \in V} \deg(v) = 2m.$ <p>If <math>G</math> is planar then <math>n - m + f = 2</math>, so</p> $f \leq 2n - 4, \quad m \leq 3n - 6.$ <p>Any planar graph has a vertex with degree <math>\leq 5</math>.</p>	<p><b>Notation:</b></p> <p><math>E(G)</math> Edge set</p> <p><math>V(G)</math> Vertex set</p> <p><math>c(G)</math> Number of components</p> <p><math>G[S]</math> Induced subgraph</p> <p><math>\deg(v)</math> Degree of <math>v</math></p> <p><math>\Delta(G)</math> Maximum degree</p> <p><math>\delta(G)</math> Minimum degree</p> <p><math>\chi(G)</math> Chromatic number</p> <p><math>\chi_E(G)</math> Edge chromatic number</p> <p><math>G^c</math> Complement graph</p> <p><math>K_n</math> Complete graph</p> <p><math>K_{n_1, n_2}</math> Complete bipartite graph</p> <p><math>r(k, \ell)</math> Ramsey number</p> <hr/> <p><b>Geometry</b></p> <p>Projective coordinates: triples <math>(x, y, z)</math>, not all <math>x, y</math> and <math>z</math> zero.</p> $(x, y, z) = (cx, cy, cz) \quad \forall c \neq 0.$ <p>Cartesian Projective</p> $(x, y) \quad (x, y, 1)$ $y = mx + b \quad (m, -1, b)$ $x = c \quad (1, 0, -c)$ <p>Distance formula, <math>L_p</math> and <math>L_\infty</math> metric:</p> $\sqrt{(x_1 - x_0)^2 + (y_1 - y_0)^2},$ $[ x_1 - x_0 ^p +  y_1 - y_0 ^p]^{1/p},$ $\lim_{p \rightarrow \infty} [ x_1 - x_0 ^p +  y_1 - y_0 ^p]^{1/p}.$ <p>Area of triangle <math>(x_0, y_0), (x_1, y_1)</math> and <math>(x_2, y_2)</math>:</p> $\frac{1}{2} \text{abs} \begin{vmatrix} x_1 - x_0 & y_1 - y_0 \\ x_2 - x_0 & y_2 - y_0 \end{vmatrix}.$ <p>Angle formed by three points:</p>  $\cos \theta = \frac{(x_1, y_1) \cdot (x_2, y_2)}{\ell_1 \ell_2}.$ <p>Line through two points <math>(x_0, y_0)</math> and <math>(x_1, y_1)</math>:</p> $\begin{vmatrix} x & y & 1 \\ x_0 & y_0 & 1 \\ x_1 & y_1 & 1 \end{vmatrix} = 0.$ <p>Area of circle, volume of sphere:</p> $A = \pi r^2, \quad V = \frac{4}{3} \pi r^3.$ <hr/> <p>If I have seen farther than others, it is because I have stood on the shoulders of giants.  – Issac Newton</p>

## Theoretical Computer Science Cheat Sheet

$\pi$	Calculus
<p>Wallis' identity:</p> $\pi = 2 \cdot \frac{2 \cdot 2 \cdot 4 \cdot 4 \cdot 6 \cdot 6 \cdots}{1 \cdot 3 \cdot 3 \cdot 5 \cdot 5 \cdot 7 \cdots}$ <p>Brouncker's continued fraction expansion:</p> $\frac{\pi}{4} = 1 + \frac{1^2}{2 + \frac{3^2}{2 + \frac{5^2}{2 + \frac{7^2}{2 + \cdots}}}}$ <p>Gregory's series:</p> $\frac{\pi}{4} = 1 - \frac{1}{3} + \frac{1}{5} - \frac{1}{7} + \frac{1}{9} - \cdots$ <p>Newton's series:</p> $\frac{\pi}{6} = \frac{1}{2} + \frac{1}{2 \cdot 3 \cdot 2^3} + \frac{1 \cdot 3}{2 \cdot 4 \cdot 5 \cdot 2^5} + \cdots$ <p>Sharp's series:</p> $\frac{\pi}{6} = \frac{1}{\sqrt{3}} \left( 1 - \frac{1}{3 \cdot 3} + \frac{1}{3^2 \cdot 5} - \frac{1}{3^3 \cdot 7} + \cdots \right)$ <p>Euler's series:</p> $\frac{\pi^2}{6} = \frac{1}{1^2} + \frac{1}{2^2} + \frac{1}{3^2} + \frac{1}{4^2} + \frac{1}{5^2} + \cdots$ $\frac{\pi^2}{8} = \frac{1}{1^2} + \frac{1}{3^2} + \frac{1}{5^2} + \frac{1}{7^2} + \frac{1}{9^2} + \cdots$ $\frac{\pi^2}{12} = \frac{1}{1^2} - \frac{1}{2^2} + \frac{1}{3^2} - \frac{1}{4^2} + \frac{1}{5^2} - \cdots$	<p>Derivatives:</p> <ol style="list-style-type: none"> <li><math>\frac{d(cu)}{dx} = c \frac{du}{dx},</math></li> <li><math>\frac{d(u+v)}{dx} = \frac{du}{dx} + \frac{dv}{dx},</math></li> <li><math>\frac{d(uv)}{dx} = u \frac{dv}{dx} + v \frac{du}{dx},</math></li> <li><math>\frac{d(u^n)}{dx} = nu^{n-1} \frac{du}{dx},</math></li> <li><math>\frac{d(u/v)}{dx} = \frac{v(\frac{du}{dx}) - u(\frac{dv}{dx})}{v^2},</math></li> <li><math>\frac{d(e^{cu})}{dx} = ce^{cu} \frac{du}{dx},</math></li> <li><math>\frac{d(c^u)}{dx} = (\ln c)c^u \frac{du}{dx},</math></li> <li><math>\frac{d(\ln u)}{dx} = \frac{1}{u} \frac{du}{dx},</math></li> <li><math>\frac{d(\sin u)}{dx} = \cos u \frac{du}{dx},</math></li> <li><math>\frac{d(\cos u)}{dx} = -\sin u \frac{du}{dx},</math></li> <li><math>\frac{d(\tan u)}{dx} = \sec^2 u \frac{du}{dx},</math></li> <li><math>\frac{d(\cot u)}{dx} = -\csc^2 u \frac{du}{dx},</math></li> <li><math>\frac{d(\sec u)}{dx} = \tan u \sec u \frac{du}{dx},</math></li> <li><math>\frac{d(\csc u)}{dx} = -\cot u \csc u \frac{du}{dx},</math></li> <li><math>\frac{d(\arcsin u)}{dx} = \frac{1}{\sqrt{1-u^2}} \frac{du}{dx},</math></li> <li><math>\frac{d(\arccos u)}{dx} = \frac{-1}{\sqrt{1-u^2}} \frac{du}{dx},</math></li> <li><math>\frac{d(\arctan u)}{dx} = \frac{1}{1+u^2} \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{arccot} u)}{dx} = \frac{-1}{1+u^2} \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{arcsec} u)}{dx} = \frac{1}{u\sqrt{1-u^2}} \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{arccsc} u)}{dx} = \frac{-1}{u\sqrt{1-u^2}} \frac{du}{dx},</math></li> <li><math>\frac{d(\sinh u)}{dx} = \cosh u \frac{du}{dx},</math></li> <li><math>\frac{d(\cosh u)}{dx} = \sinh u \frac{du}{dx},</math></li> <li><math>\frac{d(\tanh u)}{dx} = \operatorname{sech}^2 u \frac{du}{dx},</math></li> <li><math>\frac{d(\coth u)}{dx} = -\operatorname{csch}^2 u \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{sech} u)}{dx} = -\operatorname{sech} u \tanh u \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{csch} u)}{dx} = -\operatorname{csch} u \coth u \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{arcsinh} u)}{dx} = \frac{1}{\sqrt{1+u^2}} \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{arccosh} u)}{dx} = \frac{1}{\sqrt{u^2-1}} \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{arctanh} u)}{dx} = \frac{1}{1-u^2} \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{arcoth} u)}{dx} = \frac{1}{u^2-1} \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{arcsech} u)}{dx} = \frac{-1}{u\sqrt{1-u^2}} \frac{du}{dx},</math></li> <li><math>\frac{d(\operatorname{arccsch} u)}{dx} = \frac{-1}{ u \sqrt{1+u^2}} \frac{du}{dx}.</math></li> </ol> <p>Integrals:</p> <ol style="list-style-type: none"> <li><math>\int cu \, dx = c \int u \, dx,</math></li> <li><math>\int (u+v) \, dx = \int u \, dx + \int v \, dx,</math></li> <li><math>\int x^n \, dx = \frac{1}{n+1} x^{n+1}, \quad n \neq -1,</math></li> <li><math>\int \frac{1}{x} \, dx = \ln x,</math></li> <li><math>\int e^x \, dx = e^x,</math></li> <li><math>\int \frac{dx}{1+x^2} = \arctan x,</math></li> <li><math>\int u \frac{dv}{dx} \, dx = uv - \int v \frac{du}{dx} \, dx,</math></li> <li><math>\int \sin x \, dx = -\cos x,</math></li> <li><math>\int \cos x \, dx = \sin x,</math></li> <li><math>\int \tan x \, dx = -\ln  \cos x ,</math></li> <li><math>\int \cot x \, dx = \ln  \cos x ,</math></li> <li><math>\int \sec x \, dx = \ln  \sec x + \tan x ,</math></li> <li><math>\int \csc x \, dx = \ln  \csc x + \cot x ,</math></li> <li><math>\int \arcsin \frac{x}{a} \, dx = \arcsin \frac{x}{a} + \sqrt{a^2 - x^2}, \quad a &gt; 0,</math></li> </ol>
<p>Partial Fractions</p> <p>Let <math>N(x)</math> and <math>D(x)</math> be polynomial functions of <math>x</math>. We can break down <math>N(x)/D(x)</math> using partial fraction expansion. First, if the degree of <math>N</math> is greater than or equal to the degree of <math>D</math>, divide <math>N</math> by <math>D</math>, obtaining</p> $\frac{N(x)}{D(x)} = Q(x) + \frac{N'(x)}{D(x)},$ <p>where the degree of <math>N'</math> is less than that of <math>D</math>. Second, factor <math>D(x)</math>. Use the following rules: For a non-repeated factor:</p> $\frac{N(x)}{(x-a)D(x)} = \frac{A}{x-a} + \frac{N'(x)}{D(x)},$ <p>where</p> $A = \left[ \frac{N(x)}{D(x)} \right]_{x=a}.$ <p>For a repeated factor:</p> $\frac{N(x)}{(x-a)^m D(x)} = \sum_{k=0}^{m-1} \frac{A_k}{(x-a)^{m-k}} + \frac{N'(x)}{D(x)},$ <p>where</p> $A_k = \frac{1}{k!} \left[ \frac{d^k}{dx^k} \left( \frac{N(x)}{D(x)} \right) \right]_{x=a}.$	
<p>The reasonable man adapts himself to the world; the unreasonable persists in trying to adapt the world to himself. Therefore all progress depends on the unreasonable.</p> <p>– George Bernard Shaw</p>	

## Theoretical Computer Science Cheat Sheet

## Calculus Cont.

15.  $\int \arccos \frac{x}{a} dx = \arccos \frac{x}{a} - \sqrt{a^2 - x^2}, \quad a > 0,$
16.  $\int \arctan \frac{x}{a} dx = x \arctan \frac{x}{a} - \frac{a}{2} \ln(a^2 + x^2), \quad a > 0,$
17.  $\int \sin^2(ax) dx = \frac{1}{2a} (ax - \sin(ax) \cos(ax)),$
18.  $\int \cos^2(ax) dx = \frac{1}{2a} (ax + \sin(ax) \cos(ax)),$
19.  $\int \sec^2 x dx = \tan x,$
20.  $\int \csc^2 x dx = -\cot x,$
21.  $\int \sin^n x dx = -\frac{\sin^{n-1} x \cos x}{n} + \frac{n-1}{n} \int \sin^{n-2} x dx,$
22.  $\int \cos^n x dx = \frac{\cos^{n-1} x \sin x}{n} + \frac{n-1}{n} \int \cos^{n-2} x dx,$
23.  $\int \tan^n x dx = \frac{\tan^{n-1} x}{n-1} - \int \tan^{n-2} x dx, \quad n \neq 1,$
24.  $\int \cot^n x dx = -\frac{\cot^{n-1} x}{n-1} - \int \cot^{n-2} x dx, \quad n \neq 1,$
25.  $\int \sec^n x dx = \frac{\tan x \sec^{n-1} x}{n-1} + \frac{n-2}{n-1} \int \sec^{n-2} x dx, \quad n \neq 1,$
26.  $\int \csc^n x dx = -\frac{\cot x \csc^{n-1} x}{n-1} + \frac{n-2}{n-1} \int \csc^{n-2} x dx, \quad n \neq 1,$
27.  $\int \sinh x dx = \cosh x,$
28.  $\int \cosh x dx = \sinh x,$
29.  $\int \tanh x dx = \ln |\cosh x|,$
30.  $\int \coth x dx = \ln |\sinh x|,$
31.  $\int \operatorname{sech} x dx = \arctan \sinh x,$
32.  $\int \operatorname{csch} x dx = \ln \left| \tanh \frac{x}{2} \right|,$
33.  $\int \sinh^2 x dx = \frac{1}{4} \sinh(2x) - \frac{1}{2} x,$
34.  $\int \cosh^2 x dx = \frac{1}{4} \sinh(2x) + \frac{1}{2} x,$
35.  $\int \operatorname{sech}^2 x dx = \tanh x,$
36.  $\int \operatorname{arcsinh} \frac{x}{a} dx = x \operatorname{arcsinh} \frac{x}{a} - \sqrt{x^2 + a^2}, \quad a > 0,$
37.  $\int \operatorname{arctanh} \frac{x}{a} dx = x \operatorname{arctanh} \frac{x}{a} + \frac{a}{2} \ln |a^2 - x^2|,$
38.  $\int \operatorname{arccosh} \frac{x}{a} dx = \begin{cases} x \operatorname{arccosh} \frac{x}{a} - \sqrt{x^2 + a^2}, & \text{if } \operatorname{arccosh} \frac{x}{a} > 0 \text{ and } a > 0, \\ x \operatorname{arccosh} \frac{x}{a} + \sqrt{x^2 + a^2}, & \text{if } \operatorname{arccosh} \frac{x}{a} < 0 \text{ and } a > 0, \end{cases}$
39.  $\int \frac{dx}{\sqrt{a^2 + x^2}} = \ln \left( x + \sqrt{a^2 + x^2} \right), \quad a > 0,$
40.  $\int \frac{dx}{a^2 + x^2} = \frac{1}{a} \arctan \frac{x}{a}, \quad a > 0,$
41.  $\int \sqrt{a^2 - x^2} dx = \frac{x}{2} \sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a}, \quad a > 0,$
42.  $\int (a^2 - x^2)^{3/2} dx = \frac{x}{8} (5a^2 - 2x^2) \sqrt{a^2 - x^2} + \frac{3a^4}{8} \arcsin \frac{x}{a}, \quad a > 0,$
43.  $\int \frac{dx}{\sqrt{a^2 - x^2}} = \arcsin \frac{x}{a}, \quad a > 0,$
44.  $\int \frac{dx}{a^2 - x^2} = \frac{1}{2a} \ln \left| \frac{a+x}{a-x} \right|,$
45.  $\int \frac{dx}{(a^2 - x^2)^{3/2}} = \frac{x}{a^2 \sqrt{a^2 - x^2}},$
46.  $\int \sqrt{a^2 \pm x^2} dx = \frac{x}{2} \sqrt{a^2 \pm x^2} \pm \frac{a^2}{2} \ln \left| x + \sqrt{a^2 \pm x^2} \right|,$
47.  $\int \frac{dx}{\sqrt{x^2 - a^2}} = \ln \left| x + \sqrt{x^2 - a^2} \right|, \quad a > 0,$
48.  $\int \frac{dx}{ax^2 + bx} = \frac{1}{a} \ln \left| \frac{x}{a+bx} \right|,$
49.  $\int x \sqrt{a+bx} dx = \frac{2(3bx-2a)(a+bx)^{3/2}}{15b^2},$
50.  $\int \frac{\sqrt{a+bx}}{x} dx = 2\sqrt{a+bx} + a \int \frac{1}{x\sqrt{a+bx}} dx,$
51.  $\int \frac{x}{\sqrt{a+bx}} dx = \frac{1}{\sqrt{2}} \ln \left| \frac{\sqrt{a+bx} - \sqrt{a}}{\sqrt{a+bx} + \sqrt{a}} \right|, \quad a > 0,$
52.  $\int \frac{\sqrt{a^2 - x^2}}{x} dx = \sqrt{a^2 - x^2} - a \ln \left| \frac{a + \sqrt{a^2 - x^2}}{x} \right|,$
53.  $\int x \sqrt{a^2 - x^2} dx = -\frac{1}{3} (a^2 - x^2)^{3/2},$
54.  $\int x^2 \sqrt{a^2 - x^2} dx = \frac{x}{8} (2x^2 - a^2) \sqrt{a^2 - x^2} + \frac{a^4}{8} \arcsin \frac{x}{a}, \quad a > 0,$
55.  $\int \frac{dx}{\sqrt{a^2 - x^2}} = -\frac{1}{a} \ln \left| \frac{a + \sqrt{a^2 - x^2}}{x} \right|,$
56.  $\int \frac{x dx}{\sqrt{a^2 - x^2}} = -\sqrt{a^2 - x^2},$
57.  $\int \frac{x^2 dx}{\sqrt{a^2 - x^2}} = -\frac{x}{2} \sqrt{a^2 - x^2} + \frac{a^2}{2} \arcsin \frac{x}{a}, \quad a > 0,$
58.  $\int \frac{\sqrt{a^2 + x^2}}{x} dx = \sqrt{a^2 + x^2} - a \ln \left| \frac{a + \sqrt{a^2 + x^2}}{x} \right|,$
59.  $\int \frac{\sqrt{x^2 - a^2}}{x} dx = \sqrt{x^2 - a^2} - a \arccos \frac{a}{|x|}, \quad a > 0,$
60.  $\int x \sqrt{x^2 \pm a^2} dx = \frac{1}{3} (x^2 \pm a^2)^{3/2},$
61.  $\int \frac{dx}{x \sqrt{x^2 + a^2}} = \frac{1}{a} \ln \left| \frac{x}{a + \sqrt{a^2 + x^2}} \right|,$



## Theoretical Computer Science Cheat Sheet

## Calculus Cont.

$$\begin{aligned}
 62. \int \frac{dx}{x\sqrt{x^2-a^2}} &= \frac{1}{a} \arccos \frac{a}{|x|}, \quad a > 0, & 63. \int \frac{dx}{x^2\sqrt{x^2 \pm a^2}} &= \mp \frac{\sqrt{x^2 \pm a^2}}{a^2 x}, \\
 64. \int \frac{x dx}{\sqrt{x^2 \pm a^2}} &= \sqrt{x^2 \pm a^2}, & 65. \int \frac{\sqrt{x^2 \pm a^2}}{x^4} dx &= \mp \frac{(x^2 + a^2)^{3/2}}{3a^2 x^3}, \\
 66. \int \frac{dx}{ax^2 + bx + c} &= \begin{cases} \frac{1}{\sqrt{b^2 - 4ac}} \ln \left| \frac{2ax + b - \sqrt{b^2 - 4ac}}{2ax + b + \sqrt{b^2 - 4ac}} \right|, & \text{if } b^2 > 4ac, \\ \frac{2}{\sqrt{4ac - b^2}} \arctan \frac{2ax + b}{\sqrt{4ac - b^2}}, & \text{if } b^2 < 4ac, \end{cases} \\
 67. \int \frac{dx}{\sqrt{ax^2 + bx + c}} &= \begin{cases} \frac{1}{\sqrt{a}} \ln \left| 2ax + b + 2\sqrt{a}\sqrt{ax^2 + bx + c} \right|, & \text{if } a > 0, \\ \frac{1}{\sqrt{-a}} \arcsin \frac{-2ax - b}{\sqrt{b^2 - 4ac}}, & \text{if } a < 0, \end{cases} \\
 68. \int \sqrt{ax^2 + bx + c} dx &= \frac{2ax + b}{4a} \sqrt{ax^2 + bx + c} + \frac{4ac - b^2}{8a} \int \frac{dx}{\sqrt{ax^2 + bx + c}}, \\
 69. \int \frac{x dx}{\sqrt{ax^2 + bx + c}} &= \frac{\sqrt{ax^2 + bx + c}}{a} - \frac{b}{2a} \int \frac{dx}{\sqrt{ax^2 + bx + c}}, \\
 70. \int \frac{dx}{x\sqrt{ax^2 + bx + c}} &= \begin{cases} \frac{-1}{\sqrt{c}} \ln \left| \frac{2\sqrt{c}\sqrt{ax^2 + bx + c} + bx + 2c}{x} \right|, & \text{if } c > 0, \\ \frac{1}{\sqrt{-c}} \arcsin \frac{bx + 2c}{|x|\sqrt{b^2 - 4ac}}, & \text{if } c < 0, \end{cases} \\
 71. \int x^3 \sqrt{x^2 + a^2} dx &= \left(\frac{1}{3}x^2 - \frac{2}{15}a^2\right)(x^2 + a^2)^{3/2}, \\
 72. \int x^n \sin(ax) dx &= -\frac{1}{a}x^n \cos(ax) + \frac{n}{a} \int x^{n-1} \cos(ax) dx, \\
 73. \int x^n \cos(ax) dx &= \frac{1}{a}x^n \sin(ax) - \frac{n}{a} \int x^{n-1} \sin(ax) dx, \\
 74. \int x^n e^{ax} dx &= \frac{x^n e^{ax}}{a} - \frac{n}{a} \int x^{n-1} e^{ax} dx, \\
 75. \int x^n \ln(ax) dx &= x^{n+1} \left( \frac{\ln(ax)}{n+1} - \frac{1}{(n+1)^2} \right), \\
 76. \int x^n (\ln ax)^m dx &= \frac{x^{n+1}}{n+1} (\ln ax)^m - \frac{m}{n+1} \int x^n (\ln ax)^{m-1} dx.
 \end{aligned}$$

## Finite Calculus

Difference, shift operators:

$$\Delta f(x) = f(x+1) - f(x),$$

$$\mathbb{E} f(x) = f(x+1).$$

Fundamental Theorem:

$$f(x) = \Delta F(x) \Leftrightarrow \sum f(x) \delta x = F(x) + C.$$

$$\sum_a^b f(x) \delta x = \sum_{i=a}^{b-1} f(i).$$

Differences:

$$\Delta(cu) = c\Delta u, \quad \Delta(u+v) = \Delta u + \Delta v,$$

$$\Delta(uv) = u\Delta v + \mathbb{E} v \Delta u,$$

$$\Delta(x^n) = nx^{n-1},$$

$$\Delta(H_x) = x^{-1}, \quad \Delta(2^x) = 2^x,$$

$$\Delta(c^x) = (c-1)c^x, \quad \Delta\binom{x}{m} = \binom{x}{m-1}.$$

Sums:

$$\sum cu \delta x = c \sum u \delta x,$$

$$\sum(u+v) \delta x = \sum u \delta x + \sum v \delta x,$$

$$\sum u \Delta v \delta x = uv - \sum \mathbb{E} v \Delta u \delta x,$$

$$\sum x^n \delta x = \frac{x^{n+1}}{n+1}, \quad \sum x^{-1} \delta x = H_x,$$

$$\sum c^x \delta x = \frac{c^x}{c-1}, \quad \sum \binom{x}{m} \delta x = \binom{x}{m+1}.$$

Falling Factorial Powers:

$$x^{\overline{n}} = x(x-1) \cdots (x-n+1), \quad n > 0,$$

$$x^{\overline{0}} = 1,$$

$$x^{\overline{n}} = \frac{1}{(x+1) \cdots (x+|n|)}, \quad n < 0,$$

$$x^{\overline{n+m}} = x^{\overline{m}}(x-m)^{\overline{n}}.$$

Rising Factorial Powers:

$$x^{\overline{n}} = x(x+1) \cdots (x+n-1), \quad n > 0,$$

$$x^{\overline{0}} = 1,$$

$$x^{\overline{n}} = \frac{1}{(x-1) \cdots (x-|n|)}, \quad n < 0,$$

$$x^{\overline{n+m}} = x^{\overline{m}}(x+m)^{\overline{n}}.$$

Conversion:

$$x^{\overline{n}} = (-1)^n (-x)^{\overline{n}} = (x-n+1)^{\overline{n}}$$

$$= 1/(x+1)^{\overline{-n}},$$

$$x^{\overline{n}} = (-1)^n (-x)^{\overline{n}} = (x+n-1)^{\overline{n}}$$

$$= 1/(x-1)^{\overline{-n}},$$

$$x^{\overline{n}} = \sum_{k=1}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\} x^k = \sum_{k=1}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\} (-1)^{n-k} x^{\overline{k}},$$

$$x^{\overline{n}} = \sum_{k=1}^n \left[ \begin{matrix} n \\ k \end{matrix} \right] (-1)^{n-k} x^k,$$

$$x^{\overline{n}} = \sum_{k=1}^n \left[ \begin{matrix} n \\ k \end{matrix} \right] x^k.$$

$$\begin{aligned}
 x^1 &= x^1 & x^{\overline{1}} &= x^{\overline{1}} \\
 x^2 &= x^2 + x^1 & x^{\overline{2}} &= x^{\overline{2}} - x^{\overline{1}} \\
 x^3 &= x^3 + 3x^2 + x^1 & x^{\overline{3}} &= x^{\overline{3}} - 3x^{\overline{2}} + x^{\overline{1}} \\
 x^4 &= x^4 + 6x^3 + 7x^2 + x^1 & x^{\overline{4}} &= x^{\overline{4}} - 6x^{\overline{3}} + 7x^{\overline{2}} - x^{\overline{1}} \\
 x^5 &= x^5 + 15x^4 + 25x^3 + 10x^2 + x^1 & x^{\overline{5}} &= x^{\overline{5}} - 15x^{\overline{4}} + 25x^{\overline{3}} - 10x^{\overline{2}} + x^{\overline{1}} \\
 x^{\overline{1}} &= x^1 & x^1 &= x^1 \\
 x^{\overline{2}} &= x^2 + x^1 & x^2 &= x^2 - x^1 \\
 x^{\overline{3}} &= x^3 + 3x^2 + 2x^1 & x^3 &= x^3 - 3x^2 + 2x^1 \\
 x^{\overline{4}} &= x^4 + 6x^3 + 11x^2 + 6x^1 & x^4 &= x^4 - 6x^3 + 11x^2 - 6x^1 \\
 x^{\overline{5}} &= x^5 + 10x^4 + 35x^3 + 50x^2 + 24x^1 & x^5 &= x^5 - 10x^4 + 35x^3 - 50x^2 + 24x^1
 \end{aligned}$$

## Theoretical Computer Science Cheat Sheet

## Series

Taylor's series:

$$f(x) = f(a) + (x-a)f'(a) + \frac{(x-a)^2}{2}f''(a) + \dots = \sum_{i=0}^{\infty} \frac{(x-a)^i}{i!} f^{(i)}(a).$$

Expansions:

$$\begin{aligned} \frac{1}{1-x} &= 1 + x + x^2 + x^3 + x^4 + \dots = \sum_{i=0}^{\infty} x^i, \\ \frac{1}{1-cx} &= 1 + cx + c^2x^2 + c^3x^3 + \dots = \sum_{i=0}^{\infty} c^i x^i, \\ \frac{1}{1-x^n} &= 1 + x^n + x^{2n} + x^{3n} + \dots = \sum_{i=0}^{\infty} x^{ni}, \\ \frac{x}{(1-x)^2} &= x + 2x^2 + 3x^3 + 4x^4 + \dots = \sum_{i=0}^{\infty} i x^i, \\ \sum_{k=0}^n \left\{ \begin{matrix} n \\ k \end{matrix} \right\} \frac{k! z^k}{(1-z)^{k+1}} &= x + 2^n x^2 + 3^n x^3 + 4^n x^4 + \dots = \sum_{i=0}^{\infty} i^n x^i, \\ e^x &= 1 + x + \frac{1}{2}x^2 + \frac{1}{6}x^3 + \dots = \sum_{i=0}^{\infty} \frac{x^i}{i!}, \\ \ln(1+x) &= x - \frac{1}{2}x^2 + \frac{1}{3}x^3 - \frac{1}{4}x^4 + \dots = \sum_{i=1}^{\infty} (-1)^{i+1} \frac{x^i}{i}, \\ \ln \frac{1}{1-x} &= x + \frac{1}{2}x^2 + \frac{1}{3}x^3 + \frac{1}{4}x^4 + \dots = \sum_{i=1}^{\infty} \frac{x^i}{i}, \\ \sin x &= x - \frac{1}{3!}x^3 + \frac{1}{5!}x^5 - \frac{1}{7!}x^7 + \dots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i+1}}{(2i+1)!}, \\ \cos x &= 1 - \frac{1}{2!}x^2 + \frac{1}{4!}x^4 - \frac{1}{6!}x^6 + \dots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i}}{(2i)!}, \\ \tan^{-1} x &= x - \frac{1}{3}x^3 + \frac{1}{5}x^5 - \frac{1}{7}x^7 + \dots = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i+1}}{(2i+1)}, \\ (1+x)^n &= 1 + nx + \frac{n(n-1)}{2}x^2 + \dots = \sum_{i=0}^{\infty} \binom{n}{i} x^i, \\ \frac{1}{(1-x)^{n+1}} &= 1 + (n+1)x + \binom{n+1}{2}x^2 + \dots = \sum_{i=0}^{\infty} \binom{i+n}{i} x^i, \\ \frac{x}{e^x - 1} &= 1 - \frac{1}{2}x + \frac{1}{12}x^2 - \frac{1}{720}x^4 + \dots = \sum_{i=0}^{\infty} \frac{B_i x^i}{i!}, \\ \frac{1}{2x}(1 - \sqrt{1-4x}) &= 1 + x + 2x^2 + 5x^3 + \dots = \sum_{i=0}^{\infty} \frac{1}{i+1} \binom{2i}{i} x^i, \\ \frac{1}{\sqrt{1-4x}} &= 1 + 2x + 6x^2 + 20x^3 + \dots = \sum_{i=0}^{\infty} \binom{2i}{i} x^i, \\ \frac{1}{\sqrt{1-4x}} \left( \frac{1 - \sqrt{1-4x}}{2x} \right)^n &= 1 + (2+n)x + \binom{4+n}{2}x^2 + \dots = \sum_{i=0}^{\infty} \binom{2i+n}{i} x^i, \\ \frac{1}{1-x} \ln \frac{1}{1-x} &= x + \frac{3}{2}x^2 + \frac{11}{6}x^3 + \frac{25}{12}x^4 + \dots = \sum_{i=1}^{\infty} H_i x^i, \\ \frac{1}{2} \left( \ln \frac{1}{1-x} \right)^2 &= \frac{1}{2}x^2 + \frac{3}{4}x^3 + \frac{11}{24}x^4 + \dots = \sum_{i=2}^{\infty} \frac{H_{i-1} x^i}{i}, \\ \frac{x}{1-x-x^2} &= x + x^2 + 2x^3 + 3x^4 + \dots = \sum_{i=0}^{\infty} F_i x^i, \\ \frac{F_n x}{1 - (F_{n-1} + F_{n+1})x - (-1)^n x^2} &= F_n x + F_{2n} x^2 + F_{3n} x^3 + \dots = \sum_{i=0}^{\infty} F_{ni} x^i. \end{aligned}$$

Ordinary power series:

$$A(x) = \sum_{i=0}^{\infty} a_i x^i.$$

Exponential power series:

$$A(x) = \sum_{i=0}^{\infty} a_i \frac{x^i}{i!}.$$

Dirichlet power series:

$$A(x) = \sum_{i=1}^{\infty} \frac{a_i}{i^x}.$$

Binomial theorem:

$$(x+y)^n = \sum_{k=0}^n \binom{n}{k} x^{n-k} y^k.$$

Difference of like powers:

$$x^n - y^n = (x-y) \sum_{k=0}^{n-1} x^{n-1-k} y^k.$$

For ordinary power series:

$$\alpha A(x) + \beta B(x) = \sum_{i=0}^{\infty} (\alpha a_i + \beta b_i) x^i,$$

$$x^k A(x) = \sum_{i=k}^{\infty} a_{i-k} x^i,$$

$$\frac{A(x) - \sum_{i=0}^{k-1} a_i x^i}{x^k} = \sum_{i=0}^{\infty} a_{i+k} x^i,$$

$$A(cx) = \sum_{i=0}^{\infty} c^i a_i x^i,$$

$$A'(x) = \sum_{i=0}^{\infty} (i+1) a_{i+1} x^i,$$

$$xA'(x) = \sum_{i=1}^{\infty} i a_i x^i,$$

$$\int A(x) dx = \sum_{i=1}^{\infty} \frac{a_{i-1}}{i} x^i,$$

$$\frac{A(x) + A(-x)}{2} = \sum_{i=0}^{\infty} a_{2i} x^{2i},$$

$$\frac{A(x) - A(-x)}{2} = \sum_{i=0}^{\infty} a_{2i+1} x^{2i+1}.$$

Summation: If  $b_i = \sum_{j=0}^i a_j$  then

$$B(x) = \frac{1}{1-x} A(x).$$

Convolution:

$$A(x)B(x) = \sum_{i=0}^{\infty} \left( \sum_{j=0}^i a_j b_{i-j} \right) x^i.$$

God made the natural numbers;  
all the rest is the work of man.  
– Leopold Kronecker

Theoretical Computer Science Cheat Sheet																																																																																																						
Series		Escher's Knot																																																																																																				
<p>Expansions:</p> $\frac{1}{(1-x)^{n+1}} \ln \frac{1}{1-x} = \sum_{i=0}^{\infty} (H_{n+i} - H_n) \binom{n+i}{i} x^i, \quad \left(\frac{1}{x}\right)^{-n} = \sum_{i=0}^{\infty} \left\{ \begin{matrix} i \\ n \end{matrix} \right\} x^i,$ $x^{\overline{n}} = \sum_{i=0}^{\infty} \left[ \begin{matrix} n \\ i \end{matrix} \right] x^i, \quad (e^x - 1)^n = \sum_{i=0}^{\infty} \left\{ \begin{matrix} i \\ n \end{matrix} \right\} \frac{n! x^i}{i!},$ $\left(\ln \frac{1}{1-x}\right)^n = \sum_{i=0}^{\infty} \left[ \begin{matrix} i \\ n \end{matrix} \right] \frac{n! x^i}{i!}, \quad x \cot x = \sum_{i=0}^{\infty} \frac{(-4)^i B_{2i} x^{2i}}{(2i)!},$ $\tan x = \sum_{i=1}^{\infty} (-1)^{i-1} \frac{2^{2i} (2^{2i} - 1) B_{2i} x^{2i-1}}{(2i)!}, \quad \zeta(x) = \sum_{i=1}^{\infty} \frac{1}{i^x},$ $\frac{1}{\zeta(x)} = \sum_{i=1}^{\infty} \frac{\mu(i)}{i^x}, \quad \frac{\zeta(x-1)}{\zeta(x)} = \sum_{i=1}^{\infty} \frac{\phi(i)}{i^x},$ $\zeta(x) = \prod_p \frac{1}{1 - p^{-x}},$ $\zeta^2(x) = \sum_{i=1}^{\infty} \frac{d(i)}{x^i} \quad \text{where } d(n) = \sum_{d n} 1,$ $\zeta(x)\zeta(x-1) = \sum_{i=1}^{\infty} \frac{S(i)}{x^i} \quad \text{where } S(n) = \sum_{d n} d,$ $\zeta(2n) = \frac{2^{2n-1}  B_{2n} }{(2n)!} \pi^{2n}, \quad n \in \mathbb{N},$ $\frac{x}{\sin x} = \sum_{i=0}^{\infty} (-1)^{i-1} \frac{(4^i - 2) B_{2i} x^{2i}}{(2i)!},$ $\left(\frac{1 - \sqrt{1-4x}}{2x}\right)^n = \sum_{i=0}^{\infty} \frac{n(2i+n-1)!}{i!(n+i)!} x^i,$ $e^x \sin x = \sum_{i=1}^{\infty} \frac{2^{i/2} \sin \frac{i\pi}{4}}{i!} x^i,$ $\sqrt{\frac{1 - \sqrt{1-x}}{x}} = \sum_{i=0}^{\infty} \frac{(4i)!}{16^i \sqrt{2} (2i)!(2i+1)!} x^i,$ $\left(\frac{\arcsin x}{x}\right)^2 = \sum_{i=0}^{\infty} \frac{4^i i!^2}{(i+1)(2i+1)!} x^{2i}.$																																																																																																						
		<p>Stieltjes Integration</p> <p>If <math>G</math> is continuous in the interval <math>[a, b]</math> and <math>F</math> is nondecreasing then</p> $\int_a^b G(x) dF(x)$ <p>exists. If <math>a \leq b \leq c</math> then</p> $\int_a^c G(x) dF(x) = \int_a^b G(x) dF(x) + \int_b^c G(x) dF(x).$ <p>If the integrals involved exist</p> $\int_a^b (G(x) + H(x)) dF(x) = \int_a^b G(x) dF(x) + \int_a^b H(x) dF(x),$ $\int_a^b G(x) d(F(x) + H(x)) = \int_a^b G(x) dF(x) + \int_a^b G(x) dH(x),$ $\int_a^b c \cdot G(x) dF(x) = \int_a^b G(x) d(c \cdot F(x)) = c \int_a^b G(x) dF(x),$ $\int_a^b G(x) dF(x) = G(b)F(b) - G(a)F(a) - \int_a^b F(x) dG(x).$ <p>If the integrals involved exist, and <math>F</math> possesses a derivative <math>F'</math> at every point in <math>[a, b]</math> then</p> $\int_a^b G(x) dF(x) = \int_a^b G(x) F'(x) dx.$																																																																																																				
<p>Cramer's Rule</p> <p>If we have equations:</p> $\begin{aligned} a_{1,1}x_1 + a_{1,2}x_2 + \dots + a_{1,n}x_n &= b_1 \\ a_{2,1}x_1 + a_{2,2}x_2 + \dots + a_{2,n}x_n &= b_2 \\ \vdots &\quad \quad \quad \vdots \\ a_{n,1}x_1 + a_{n,2}x_2 + \dots + a_{n,n}x_n &= b_n \end{aligned}$ <p>Let <math>A = (a_{i,j})</math> and <math>B</math> be the column matrix <math>(b_i)</math>. Then there is a unique solution iff <math>\det A \neq 0</math>. Let <math>A_i</math> be <math>A</math> with column <math>i</math> replaced by <math>B</math>. Then</p> $x_i = \frac{\det A_i}{\det A}.$		<table><tr><td>00</td><td>47</td><td>18</td><td>76</td><td>29</td><td>93</td><td>85</td><td>34</td><td>61</td><td>52</td></tr><tr><td>86</td><td>11</td><td>57</td><td>28</td><td>70</td><td>39</td><td>94</td><td>45</td><td>02</td><td>63</td></tr><tr><td>95</td><td>80</td><td>22</td><td>67</td><td>38</td><td>71</td><td>49</td><td>56</td><td>13</td><td>04</td></tr><tr><td>59</td><td>96</td><td>81</td><td>33</td><td>07</td><td>48</td><td>72</td><td>60</td><td>24</td><td>15</td></tr><tr><td>73</td><td>69</td><td>90</td><td>82</td><td>44</td><td>17</td><td>58</td><td>01</td><td>35</td><td>26</td></tr><tr><td>68</td><td>74</td><td>09</td><td>91</td><td>83</td><td>55</td><td>27</td><td>12</td><td>46</td><td>30</td></tr><tr><td>37</td><td>08</td><td>75</td><td>19</td><td>92</td><td>84</td><td>66</td><td>23</td><td>50</td><td>41</td></tr><tr><td>14</td><td>25</td><td>36</td><td>40</td><td>51</td><td>62</td><td>03</td><td>77</td><td>88</td><td>99</td></tr><tr><td>21</td><td>32</td><td>43</td><td>54</td><td>65</td><td>06</td><td>10</td><td>89</td><td>97</td><td>78</td></tr><tr><td>42</td><td>53</td><td>64</td><td>05</td><td>16</td><td>20</td><td>31</td><td>98</td><td>79</td><td>87</td></tr></table> <p>The Fibonacci number system: Every integer <math>n</math> has a unique representation</p> $n = F_{k_1} + F_{k_2} + \dots + F_{k_m},$ <p>where <math>k_i \geq k_{i+1} + 2</math> for all <math>i</math>, <math>1 \leq i &lt; m</math> and <math>k_m \geq 2</math>.</p>	00	47	18	76	29	93	85	34	61	52	86	11	57	28	70	39	94	45	02	63	95	80	22	67	38	71	49	56	13	04	59	96	81	33	07	48	72	60	24	15	73	69	90	82	44	17	58	01	35	26	68	74	09	91	83	55	27	12	46	30	37	08	75	19	92	84	66	23	50	41	14	25	36	40	51	62	03	77	88	99	21	32	43	54	65	06	10	89	97	78	42	53	64	05	16	20	31	98	79	87
00	47	18	76	29	93	85	34	61	52																																																																																													
86	11	57	28	70	39	94	45	02	63																																																																																													
95	80	22	67	38	71	49	56	13	04																																																																																													
59	96	81	33	07	48	72	60	24	15																																																																																													
73	69	90	82	44	17	58	01	35	26																																																																																													
68	74	09	91	83	55	27	12	46	30																																																																																													
37	08	75	19	92	84	66	23	50	41																																																																																													
14	25	36	40	51	62	03	77	88	99																																																																																													
21	32	43	54	65	06	10	89	97	78																																																																																													
42	53	64	05	16	20	31	98	79	87																																																																																													
<p>Improvement makes strait roads, but the crooked roads without Improvement, are roads of Genius. – William Blake (The Marriage of Heaven and Hell)</p>		<p>Fibonacci Numbers</p> <p>1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, ...</p> <p>Definitions:</p> $F_i = F_{i-1} + F_{i-2}, \quad F_0 = F_1 = 1,$ $F_{-i} = (-1)^{i-1} F_i,$ $F_i = \frac{1}{\sqrt{5}} \left( \phi^i - \hat{\phi}^i \right),$ <p>Cassini's identity: for <math>i &gt; 0</math>:</p> $F_{i+1}F_{i-1} - F_i^2 = (-1)^i.$ <p>Additive rule:</p> $F_{n+k} = F_k F_{n+1} + F_{k-1} F_n,$ $F_{2n} = F_n F_{n+1} + F_{n-1} F_n.$ <p>Calculation by matrices:</p> $\begin{pmatrix} F_{n-2} & F_{n-1} \\ F_{n-1} & F_n \end{pmatrix} = \begin{pmatrix} 0 & 1 \\ 1 & 1 \end{pmatrix}^n.$																																																																																																				