Sprites API v1

Examples: HTTP

Checkpoints

SPRITE-ENV v0.0.1-rc43

Checkpoints capture your Sprite's complete filesystem state for instant rollback. They're live snapshots—creation takes milliseconds with no interruption to running processes.

Use checkpoints before risky operations, to create reproducible environments, or to share known-good states across a team. Copy-on-write storage keeps incremental checkpoints small; you only store what changed.

Create Checkpoint

POST /v1/sprites/{name}/checkpoint

Create a new checkpoint of the current sprite state. Returns streaming NDJSON progress.

REQUEST BODY application/json

comment string

RESPONSE application/x-ndjson

StreamInfoEvent

type* "info"

data* String
Status message

time* DateTime
Timestamp

Sprites API v1

Examples:

type* "error"

error* String
Error description

time* DateTime
Timestamp

StreamCompleteEvent

type* "complete"

data* String
Completion message

time* DateTime
Timestamp

RESPONSE CODES

200 Success - Streaming NDJSON response

404 Not Found - Resource not found

500 Internal Server Error

bash HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites/{name}/checkpoint" \
  -H "Authorization: Bearer $SPRITES_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"comment":"Before deploying v2.0"}'
```

200 Response

```
[
  {
    "data": "Creating checkpoint...",
```

Sprites API v1

Examples:


```
  },
  {
    "data": "Stopping services...",
    "time": "2026-01-05T10:30:00Z",
    "type": "info"
  },
  {
    "data": "Saving filesystem state...",
    "time": "2026-01-05T10:30:00Z",
    "type": "info"
  },
  {
    "data": "Checkpoint v8 created",
    "time": "2026-01-05T10:30:00Z",
    "type": "complete"
  }
]
```


List Checkpoints

GET /v1/sprites/{name}/checkpoints

List all checkpoints.

RESPONSE application/json

id* string

Checkpoint identifier (e.g., v7)

create_time* string

When the checkpoint was created

source_id string

Parent checkpoint ID

Sprites API v1

Examples:

`health` string

Health status (empty = healthy, “mount_failed” = unhealthy)

RESPONSE CODES

200	Success
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites/{name}/checkpoints" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

```
[
  {
    "comment": "Before database migration",
    "create_time": "2026-01-05T10:30:00Z",
    "id": "v7"
  },
  {
    "comment": "Stable state",
    "create_time": "2026-01-04T15:00:00Z",
    "id": "v6"
  },
  {
    "comment": "",
    "create_time": "2026-01-04T09:00:00Z",
    "id": "v5"
  }
]
```

Sprites API v1

Examples:

GET /v1/sprites/{name}/checkpoints/{checkpoint_id}

Get details of a specific checkpoint.

RESPONSE application/json

id* string
Checkpoint identifier (e.g., v7)

create_time* string
When the checkpoint was created

source_id string
Parent checkpoint ID

comment string
User-provided description

health string
Health status (empty = healthy, “mount_failed” = unhealthy)

RESPONSE CODES

200	Success
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites/{name}/checkpoints/{checkpoint_id}"
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

Sprites API v1

Examples:

```
  "create_time": "2026-01-05T10:30:00Z",
  "id": "v7"
}
```

Restore Checkpoint

POST /v1/sprites/{name}/checkpoints/{checkpoint_id}/restore

Restore to a specific checkpoint. Returns streaming NDJSON progress.

RESPONSE application/x-ndjson

StreamInfoEvent

type* "info"

data* String
Status message

time* DateTime
Timestamp

StreamErrorEvent

type* "error"

error* String
Error description

time* DateTime
Timestamp

Sprites API v1

Examples:

type* "complete"

data* String

Completion message

time* DateTime

Timestamp

RESPONSE CODES

200 Success - Streaming NDJSON response

404 Not Found - Resource not found

500 Internal Server Error

bash HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites/{name}/checkpoints/{checkpoint_id}/
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response


```
[
  {
    "data": "Restoring to checkpoint v5...",
    "time": "2026-01-05T10:30:00Z",
    "type": "info"
  },
  {
    "data": "Stopping services...",
    "time": "2026-01-05T10:30:00Z",
    "type": "info"
  },
  {
    "data": "Restoring filesystem...",
    "time": "2026-01-05T10:30:00Z",
    "type": "info"
```

Sprites API v1

Examples:


```
    "data": "Restored to v5",
    "time": "2026-01-05T10:30:00Z",
    "type": "complete"
  }
]
```