Sprites API v1

Examples: HTTP

Filesystem

SPRITE-ENV v0.0.1-rc43

Read, write, and manage files within your Sprite environment.

Read File

GET /v1/sprites/{name}/fs/read

Read file contents from the sprite filesystem. Returns raw file bytes.

QUERY PARAMETERS

path* string

Path to the file to read

workingDir* string

Working directory for resolving relative paths

RESPONSE application/json

RESPONSE CODES

200	Success
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites/{name}/fs/read" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

Sprites API v1

Examples:

Write File

PUT /v1/sprites/{name}/fs/write

Write file contents to the sprite filesystem. Request body contains raw file bytes.

QUERY PARAMETERS

path* string
Path to the file to write

workingDir* string
Working directory for resolving relative paths

mode string
File permissions in octal (e.g., '0644')

mkdir bool
Create parent directories if they don't exist

RESPONSE application/json

path* string

size* number

mode* string

RESPONSE CODES

200	Success
400	Bad Request - Invalid request body
404	Not Found - Resource not found
500	Internal Server Error

Sprites API v1

Examples:

```
curl -X PUT \
  "https://api.sprites.dev/v1/sprites/{name}/fs/write" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

```
{
  "size": 1,
  "mode": "example",
  "path": "example"
}
```

List Directory

GET /v1/sprites/{name}/fs/list

List directory contents.

QUERY PARAMETERS

path* string
Path to the directory to list

workingDir* string
Working directory for resolving relative paths

RESPONSE application/json

path* string

entries* Entry[]

Sprites API v1

Examples:

RESPONSE CODES

200	Success
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites/{name}/fs/list" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

```json
{
  "count": 1,
  "path": "example",
  "entries": []
}
```

Delete File or Directory

DELETE /v1/sprites/{name}/fs/delete

Delete a file or directory.

RESPONSE application/json

deleted* string

count* number

Sprites API v1

Examples:

400 Bad Request - Invalid request body

404 Not Found - Resource not found

500 Internal Server Error

bash HTTP

```bash
curl -X DELETE \
  "https://api.sprites.dev/v1/sprites/{name}/fs/delete" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

```
{
  "count": 1,
  "deleted": "example"
}
```

Rename File or Directory

POST /v1/sprites/{name}/fs/rename

Rename or move a file or directory.

REQUEST BODY application/json

source* string

dest* string

workingDir* string

asRoot* boolean

Sprites API v1

Examples:

source* string

dest* string

RESPONSE CODES

200 Success

400 Bad Request - Invalid request body

404 Not Found - Resource not found

500 Internal Server Error

bash HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites/{name}/fs/rename" \
  -H "Authorization: Bearer $SPRITES_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"asRoot":false,"dest":"example","source":"example","workingDir":"e
```

200 Response

```
{
  "source": "example",
  "dest": "example"
}
```

Copy File or Directory

POST /v1/sprites/{name}/fs/copy

Sprites API v1

Examples:

REQUEST BODY application/json

source* string

dest* string

workingDir* string

recursive* boolean

preserveAttrs* boolean

asRoot* boolean

RESPONSE application/json

copied* CopyResult[]

count* number

totalBytes* number

RESPONSE CODES

200	Success
400	Bad Request - Invalid request body
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites/{name}/fs/copy" \
  -H "Authorization: Bearer $SPRITES_TOKEN" \
```

Sprites API v1

Examples:

200 Response

```
{
  "count": 1,
  "copied": [],
  "totalBytes": 1
}
```

Change File Mode

POST /v1/sprites/{name}/fs/chmod

Change file or directory permissions.

REQUEST BODY application/json

- path* string
- workingDir* string
- mode* string
- recursive* boolean
- asRoot* boolean

RESPONSE application/json

- affected* ChmodResult[]

Sprites API v1

Examples:

RESPONSE CODES

200	Success
400	Bad Request - Invalid request body
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites/{name}/fs/chmod" \
  -H "Authorization: Bearer $SPRITES_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"asRoot":false,"mode":"example","path":"example","recursive":false
```

200 Response

```
{
  "count": 1,
  "affected": []
}
```

Change File Owner

POST /v1/sprites/{name}/fs/chown

Change file or directory ownership.

REQUEST BODY application/json

path* string

Sprites API v1

Examples:

uid* interface{}

gid* interface{}

recursive* boolean

asRoot* boolean

RESPONSE application/json

affected* ChownResult[]

count* number

RESPONSE CODES

200	Success
400	Bad Request - Invalid request body
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites/{name}/fs/chown" \
  -H "Authorization: Bearer $SPRITES_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"asRoot":false,"gid":null,"path":"example","recursive":false,"uid"
```

200 Response

```json
{
  "count": 1,
  "affected": []
}
```

Watch Filesystem

WSS /v1/sprites/{name}/fs/watch

Watch for filesystem changes via WebSocket.

JSON MESSAGES

WatchMessage Client → Server

- type* String
- paths [String]
- recursive boolean
- workingDir String
- path String
- event String
- timestamp String
- size integer
- isDir boolean
- message String

WatchMessage Server → Client

- type* String
- paths [String]

Sprites API v1

Examples:

workingDir String

path String

event String

timestamp String

size integer

isDir boolean

message String

BINARY PROTOCOL

In non-PTY mode, binary messages are prefixed with a stream identifier byte. In PTY mode, binary data is sent raw without prefixes.

```
Binary Frame Format (non-PTY):
Stream ID (1 byte) + Payload (N bytes)
```

STREAM ID	NAME	DIRECTION	DESCRIPTION
0	stdin	client → server	Standard input data
1	stdout	server → client	Standard output data
2	stderr	server → client	Standard error data
3	exit	server → client	Exit code (payload is exit code as byte)
4	stdin_eof	client → server	End of stdin stream

RESPONSE CODES

101 Switching Protocols - WebSocket connection established

400 Bad Request - Invalid WebSocket upgrade or missing parameters

404 Not Found - Resource not found

Sprites API v1

Examples:

```
websocat \
  "wss://api.sprites.dev/v1/sprites/{name}/fs/watch?path=/bin/bash&tty=tr
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

Binary Streams

→ stdin (0x00 + data)

← stdout (0x01 + data)

← stderr (0x02 + data)

JSON Messages

Resize terminal (client → server):

```
{"type": "resize", "cols": 120, "rows": 40}
```

Port opened (server → client):

```
{"type": "port_opened", "port": 8080, "address": "0.0.0.0", "pid": 1234}
```