Sprites API v1

Examples: HTTP

Sprite Management

Sprites are persistent environments that hibernate when idle and wake automatically on demand. You only pay for compute while actively using them—storage persists indefinitely.

Create Sprites for development environments, CI runners, code execution sandboxes, or any workload that benefits from fast startup with preserved state. Each Sprite gets a unique URL for HTTP access, configurable as public or authenticated.

Create Sprite

POST `/v1/sprites`

Create a new sprite with a unique name in your organization

REQUEST BODY `application/json`

- `name*` `string`
  Unique name for the sprite within the organization
- `url_settings`
  URL access configuration
  - `auth` `"sprite" | "public"`
    Authentication type (default: sprite)

RESPONSE `application/json`

- `id*` `string`
  Unique sprite identifier (UUID)
- `name*` `string`
  Sprite name within the organization
- `organization*` `string`

Sprites API v1

Examples:

`url*` string

Sprite HTTP endpoint URL

`url_settings`

URL access configuration

`auth*` "sprite" | "public"

Authentication type

`status*` "cold" | "warm" | "running"

Runtime status

`created_at*` string

Creation timestamp (ISO 8601)

`updated_at*` string

Last update timestamp (ISO 8601)

`last_started_at` string

When the sprite machine last started (ISO 8601), null if not tracked

`last_active_at` string

When the sprite was last active/running (ISO 8601), null if not tracked

RESPONSE CODES

201	Created
400	Invalid request parameters
401	Missing or invalid authentication

bash HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites" \
  -H "Authorization: Bearer $SPRITES_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"name":"my-sprite","url_settings":{"auth":"public"}}'
```

200 Response

Sprites API v1

Examples:

```
  "name": "my-dev-sprite",
  "status": "cold",
  "url": "https://name-random-alphanumeric.sprites.app",
  "url_settings": {
    "auth": "sprite"
  },
  "created_at": "2024-01-15T10:30:00Z",
  "organization": "my-org",
  "updated_at": "2024-01-15T14:22:00Z",
  "last_active_at": "2024-01-15T14:22:00Z",
  "last_started_at": "2024-01-15T14:20:00Z"
}
```

List Sprites

GET /v1/sprites

List all sprites for the authenticated organization

QUERY PARAMETERS

`prefix` string

Filter sprites by name prefix

`max_results` number

Maximum number of results (1-50, default: 50)

`continuation_token` string

Token from previous response for pagination

RESPONSE application/json

`sprites*` SpriteEntry[]

Sprites API v1

Examples:

Sprite name

`org_slug*` string

Organization slug

`updated_at` string

Last update timestamp (ISO 8601)

`has_more*` boolean

Whether more results are available

`next_continuation_token` string

Token for fetching the next page of results

RESPONSE CODES

200	Success
401	Missing or invalid authentication

bash HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

```json
{
  "sprites": [
    {
      "name": "my-dev-sprite",
      "org_slug": "my-org",
      "updated_at": "2024-01-15T14:22:00Z"
    }
  ],
  "next_continuation_token": "eyJsYXN0IjoibXktZGV2LXNwcml0ZSJ9",
  "has_more": true
}
```

Sprites API v1

Examples:

Get Sprite

GET /v1/sprites/{name}

Get details for a specific sprite

PATH PARAMETERS

name* string

Unique sprite name

RESPONSE application/json

id* string

Unique sprite identifier (UUID)

name* string

Sprite name within the organization

organization* string

Organization slug

url* string

Sprite HTTP endpoint URL

url_settings

URL access configuration

auth* "sprite" | "public"

Authentication type

status* "cold" | "warm" | "running"

Runtime status

created_at* string

Creation timestamp (ISO 8601)

Sprites API v1

Examples:

`last_started_at` string

When the sprite machine last started (ISO 8601), null if not tracked

`last_active_at` string

When the sprite was last active/running (ISO 8601), null if not tracked

RESPONSE CODES

200	Success
401	Missing or invalid authentication
404	Sprite not found

bash HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites/{name}" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

```json
{
  "id": "01234567-89ab-cdef-0123-456789abcdef",
  "name": "my-dev-sprite",
  "status": "cold",
  "url": "https://name-random-alphanumeric.sprites.app",
  "url_settings": {
    "auth": "sprite"
  },
  "created_at": "2024-01-15T10:30:00Z",
  "organization": "my-org",
  "updated_at": "2024-01-15T14:22:00Z",
  "last_active_at": "2024-01-15T14:22:00Z",
  "last_started_at": "2024-01-15T14:20:00Z"
}
```

Sprites API v1

Examples:

DELETE /v1/sprites/{name}

Delete a sprite and all associated resources

PATH PARAMETERS

name* string

Unique sprite name

RESPONSE application/json

RESPONSE CODES

204 No content

401 Missing or invalid authentication

404 Sprite not found

bash HTTP

```bash
curl -X DELETE \
  "https://api.sprites.dev/v1/sprites/{name}" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

Update Sprite

PUT /v1/sprites/{name}

Update sprite settings such as URL authentication

PATH PARAMETERS

name* string

Sprites API v1

Examples:

REQUEST BODY `application/json`

`url_settings*`

URL access configuration to update

`auth` `"sprite" | "public"`

Authentication type (default: sprite)

RESPONSE `application/json`

`id*` `string`

Unique sprite identifier (UUID)

`name*` `string`

Sprite name within the organization

`organization*` `string`

Organization slug

`url*` `string`

Sprite HTTP endpoint URL

`url_settings`

URL access configuration

`auth*` `"sprite" | "public"`

Authentication type

`status*` `"cold" | "warm" | "running"`

Runtime status

`created_at*` `string`

Creation timestamp (ISO 8601)

`updated_at*` `string`

Last update timestamp (ISO 8601)

`last_started_at` `string`

When the sprite machine last started (ISO 8601), null if not tracked

Sprites API v1

Examples:

RESPONSE CODES

200	Success
400	Invalid request parameters
401	Missing or invalid authentication
404	Sprite not found

bash HTTP

```bash
curl -X PUT \
  "https://api.sprites.dev/v1/sprites/{name}" \
  -H "Authorization: Bearer $SPRITES_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"url_settings":{"auth":"public"}}'
```

200 Response

```json
{
  "id": "01234567-89ab-cdef-0123-456789abcdef",
  "name": "my-dev-sprite",
  "status": "cold",
  "url": "https://name-random-alphanumeric.sprites.app",
  "url_settings": {
    "auth": "sprite"
  },
  "created_at": "2024-01-15T10:30:00Z",
  "organization": "my-org",
  "updated_at": "2024-01-15T14:22:00Z",
  "last_active_at": "2024-01-15T14:22:00Z",
  "last_started_at": "2024-01-15T14:20:00Z"
}
```