Sprites API v1

Examples: HTTP

Services

SPRITE-ENV v0.0.1-rc43

Manage background services running in your Sprite environment.

List Services

GET /v1/sprites/{name}/services

List all configured services and their current state.

RESPONSE application/json

- name* string
  Service name
- cmd* string
  Command to execute
- args* string
  Command arguments
- needs* string
  Service dependencies
- http_port number
  HTTP port for proxy routing
- state
  Current runtime state
  - name* string
    Service name
  - status* string

Sprites API v1

Examples:

pid number

Process ID when running

started_at string

ISO 8601 timestamp

error string

Error message if failed

RESPONSE CODES

200 Success

404 Not Found - Resource not found

500 Internal Server Error

bash HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites/{name}/services" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response


```json
[
  {
    "args": [
      "-D",
      "/var/lib/postgresql/data"
    ],
    "cmd": "postgres",
    "http_port": null,
    "name": "postgres",
    "needs": [],
    "state": {
      "name": "postgres",
      "pid": 1234,
      "started_at": "2026-01-05T08:00:00Z",
      "status": "running"
    }
```

Sprites API v1

Examples:


```
      "args": [
        "-m",
        "http.server",
        "8000"
      ],
      "cmd": "python",
      "http_port": 8000,
      "name": "webapp",
      "needs": [
        "postgres"
      ],
      "state": {
        "name": "webapp",
        "pid": 1567,
        "started_at": "2026-01-05T08:01:00Z",
        "status": "running"
      }
    }
  ]
```


Get Service

GET /v1/sprites/{name}/services/{service_name}

Get details of a specific service.

RESPONSE application/json

name* string

Service name

cmd* string

Command to execute

args* string

Sprites API v1

Examples:

needs* string

Service dependencies

http_port number

HTTP port for proxy routing

state

Current runtime state

name* string

Service name

status* string

stopped, starting, running, stopping, or failed

pid number

Process ID when running

started_at string

ISO 8601 timestamp

error string

Error message if failed

RESPONSE CODES

200	Success
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites/{name}/services/{service_name}" \
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

Sprites API v1

Examples:


```
      "-m",
      "http.server",
      "8000"
    ],
    "cmd": "python",
    "http_port": 8000,
    "name": "webapp",
    "needs": [
      "postgres"
    ],
    "state": {
      "name": "webapp",
      "pid": 1567,
      "started_at": "2026-01-05T08:01:00Z",
      "status": "running"
    }
  }
```


Create Service

PUT /v1/sprites/{name}/services/{service_name}

Create or update a service definition.

QUERY PARAMETERS

duration duration

Time to monitor logs after starting (default: 5s)

REQUEST BODY application/json

cmd* string

Command to execute

Sprites API v1

Examples:

`env` map

Environment variables to add to the base service environment

`dir` string

Working directory for the service

`needs*` string

Service dependencies (started first)

`http_port` number

HTTP port for proxy routing

RESPONSE application/json

`name*` string

Service name

`cmd*` string

Command to execute

`args*` string

Command arguments

`needs*` string

Service dependencies

`http_port` number

HTTP port for proxy routing

`state`

Current runtime state

`name*` string

Service name

`status*` string

`stopped`, `starting`, `running`, `stopping`, or `failed`

Sprites API v1

Examples:

`started_at` string

ISO 8601 timestamp

`error` string

Error message if failed

RESPONSE CODES

200	Success
400	Bad Request - Invalid request body
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

```bash
curl -X PUT \
  "https://api.sprites.dev/v1/sprites/{name}/services/{service_name}" \
  -H "Authorization: Bearer $SPRITES_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"args":["-m","http.server","8000"],"cmd":"python","http_port":8000
```

200 Response

```json
{
  "args": [
    "-m",
    "http.server",
    "8000"
  ],
  "cmd": "python",
  "http_port": 8000,
  "name": "webapp",
  "needs": [
    "postgres"
  ],
  "state": {
    "name": "webapp",
```

Sprites API v1

Examples:

```
  }
}
```

Start Service

POST `/v1/sprites/{name}/services/{service_name}/start`

Start a service. Returns streaming NDJSON with stdout/stderr.

QUERY PARAMETERS

`duration` duration

Time to monitor logs after starting (default: `5s`)

RESPONSE application/x-ndjson

`ServiceLogStdoutEvent`

`type*` "stdout"

`data*` String

Log line content

`timestamp*` integer

Unix milliseconds

`ServiceLogStderrEvent`

`type*` "stderr"

`data*` String

Log line content

Sprites API v1

Examples:

ServiceLogExitEvent

type* "exit"

exit_code* integer
Process exit code

timestamp* integer
Unix milliseconds

ServiceLogErrorEvent

type* "error"

data* String
Error message

timestamp* integer
Unix milliseconds

ServiceLogCompleteEvent

type* "complete"

timestamp* integer
Unix milliseconds

ServiceLogStartedEvent

type* "started"

timestamp* integer
Unix milliseconds

RESPONSE CODES

Sprites API v1

Examples:

500 Internal Server Error

bash HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites/{name}/services/{service_name}/star
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response


```
[
  {
    "timestamp": 1735988400000,
    "type": "started"
  },
  {
    "data": "Starting server...\n",
    "timestamp": 1735988400000,
    "type": "stdout"
  },
  {
    "data": "Listening on port 8000\n",
    "timestamp": 1735988401000,
    "type": "stdout"
  },
  {
    "log_files": {
      "stdout": "/.sprite/logs/services/webapp.log"
    },
    "timestamp": 1735988402000,
    "type": "complete"
  }
]
```

Sprites API v1

Examples:

POST /v1/sprites/{name}/services/{service_name}/stop

Stop a running service. Returns streaming NDJSON with service stop progress.

QUERY PARAMETERS

timeout duration

Timeout waiting for service to stop (default: 10s)

RESPONSE application/x-ndjson

ServiceLogStoppingEvent

type* "stopping"

timestamp* integer

Unix milliseconds

ServiceLogStdoutEvent

type* "stdout"

data* String

Log line content

timestamp* integer

Unix milliseconds

ServiceLogStderrEvent

type* "stderr"

data* String

Log line content

timestamp* integer

Sprites API v1

Examples:

ServiceLogErrorEvent

type* "error"

data* String

Error message

timestamp* integer

Unix milliseconds

ServiceLogStoppedEvent

type* "stopped"

exit_code* integer

Process exit code

timestamp* integer

Unix milliseconds

ServiceLogCompleteEvent

type* "complete"

timestamp* integer

Unix milliseconds

RESPONSE CODES

200	Success - Streaming NDJSON response
404	Not Found - Resource not found
500	Internal Server Error

bash HTTP

Sprites API v1

Examples:

```
-H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response


```
[
  {
    "timestamp": 1735988400000,
    "type": "stopping"
  },
  {
    "exit_code": 0,
    "timestamp": 1735988401000,
    "type": "stopped"
  },
  {
    "log_files": {
      "stdout": "/.sprite/logs/services/webapp.log"
    },
    "timestamp": 1735988402000,
    "type": "complete"
  }
]
```


Restart Service

POST `/v1/sprites/{name}/services/{service_name}/restart`

Restart a service (stop if running, then start). Returns streaming NDJSON with stop and start progress.

QUERY PARAMETERS

`duration` duration

Sprites API v1

Examples:

RESPONSE application/x-ndjson

ServiceLogStoppingEvent

type* "stopping"

timestamp* integer
Unix milliseconds

ServiceLogStoppedEvent

type* "stopped"

exit_code* integer
Process exit code

timestamp* integer
Unix milliseconds

ServiceLogStdoutEvent

type* "stdout"

data* String
Log line content

timestamp* integer
Unix milliseconds

ServiceLogStderrEvent

type* "stderr"

data* String
Log line content

timestamp* integer

Sprites API v1

Examples:

ServiceLogExitEvent

type* "exit"

exit_code* integer

Process exit code

timestamp* integer

Unix milliseconds

ServiceLogErrorEvent

type* "error"

data* String

Error message

timestamp* integer

Unix milliseconds

ServiceLogCompleteEvent

type* "complete"

timestamp* integer

Unix milliseconds

ServiceLogStartedEvent

type* "started"

timestamp* integer

Unix milliseconds

RESPONSE CODES

Sprites API v1

Examples:

500 Internal Server Error

bash HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites/{name}/services/{service_name}/rest
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

Get Service Logs

GET `/v1/sprites/{name}/services/{service_name}/logs`

Stream logs for a service.

QUERY PARAMETERS

`lines` `int`

Number of lines to return from log buffer (default: all)

`duration` `duration`

Time to follow new logs (default: `0`, no follow)

RESPONSE `application/x-ndjson`

`ServiceLogStdoutEvent`

`type*` `"stdout"`

`data*` `String`

Sprites API v1

Examples:

timestamp* integer

Unix milliseconds

ServiceLogStderrEvent

type* "stderr"

data* String

Log line content

timestamp* integer

Unix milliseconds

ServiceLogExitEvent

type* "exit"

exit_code* integer

Process exit code

timestamp* integer

Unix milliseconds

ServiceLogErrorEvent

type* "error"

data* String

Error message

timestamp* integer

Unix milliseconds

ServiceLogCompleteEvent

type* "complete"

Sprites API v1

Examples:

RESPONSE CODES

200 Success - Streaming NDJSON response

404 Not Found - Resource not found

500 Internal Server Error

bash HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites/{name}/services/{service_name}/logs
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response


```
[
  {
    "data": "Server started\n",
    "timestamp": 1735988400000,
    "type": "stdout"
  },
  {
    "data": "Handling request from 127.0.0.1\n",
    "timestamp": 1735988450000,
    "type": "stdout"
  },
  {
    "data": "Warning: slow query detected\n",
    "timestamp": 1735988455000,
    "type": "stderr"
  },
  {
    "log_files": {
      "stdout": "/.sprite/logs/services/webapp.log"
    },
    "timestamp": 1735988460000,
    "type": "complete"
```

Sprites API v1

Examples: