Sprites API v1

Examples: Python

Checkpoints

SPRITE-ENV v0.0.1-rc43

Checkpoints capture your Sprite's complete filesystem state for instant rollback. They're live snapshots—creation takes milliseconds with no interruption to running processes.

Use checkpoints before risky operations, to create reproducible environments, or to share known-good states across a team. Copy-on-write storage keeps incremental checkpoints small; you only store what changed.

Create Checkpoint

POST `/v1/sprites/{name}/checkpoint`

Create a new checkpoint of the current sprite state. Returns streaming NDJSON progress.

REQUEST BODY `application/json`

`comment` string

RESPONSE `application/x-ndjson`

`StreamInfoEvent`

`type*` "info"

`data*` String
Status message

`time*` DateTime
Timestamp

Sprites API v1

Examples:

`type*` `"error"`

`error*` `String`
Error description

`time*` `DateTime`
Timestamp

`StreamCompleteEvent`

`type*` `"complete"`

`data*` `String`
Completion message

`time*` `DateTime`
Timestamp

RESPONSE CODES

200	Success - Streaming NDJSON response
404	Not Found - Resource not found
500	Internal Server Error

example.py Python

```python
import json
import os

from sprites import SpritesClient

token = os.environ["SPRITE_TOKEN"]
sprite_name = os.environ["SPRITE_NAME"]

client = SpritesClient(token)
sprite = client.sprite(sprite_name)

stream = sprite.create_checkpoint("my-checkpoint")
```

Sprites API v1

Examples:

```
print(json.dumps({"type": msg.type, "data": msg.data}))
```

stdout

List Checkpoints

GET /v1/sprites/{name}/checkpoints

List all checkpoints.

RESPONSE application/json

id* string
Checkpoint identifier (e.g., v7)

create_time* string
When the checkpoint was created

source_id string
Parent checkpoint ID

comment string
User-provided description

health string
Health status (empty = healthy, “mount_failed” = unhealthy)

RESPONSE CODES

200 Success

404 Not Found - Resource not found

500 Internal Server Error

Sprites API v1

Examples:

```
import json
import os

from sprites import SpritesClient

token = os.environ["SPRITE_TOKEN"]
sprite_name = os.environ["SPRITE_NAME"]

client = SpritesClient(token)
sprite = client.sprite(sprite_name)

checkpoints = sprite.list_checkpoints()

result = []
for cp in checkpoints:
    item = {"id": cp.id, "create_time": cp.create_time.isoformat().replac
    if cp.comment:
        item["comment"] = cp.comment
    result.append(item)

print(json.dumps(result, indent=2))
```

stdout

Get Checkpoint

GET /v1/sprites/{name}/checkpoints/{checkpoint_id}

Get details of a specific checkpoint.

RESPONSE application/json

Sprites API v1

Examples:

Checkpoint identifier (e.g., `v7`)

`create_time*` string

When the checkpoint was created

`source_id` string

Parent checkpoint ID

`comment` string

User-provided description

`health` string

Health status (empty = healthy, "mount_failed" = unhealthy)

RESPONSE CODES

200	Success
404	Not Found - Resource not found
500	Internal Server Error

example.py Python

```python
import json
import os

from sprites import SpritesClient

token = os.environ["SPRITE_TOKEN"]
sprite_name = os.environ["SPRITE_NAME"]
checkpoint_id = os.environ.get("CHECKPOINT_ID", "v1")

client = SpritesClient(token)
sprite = client.sprite(sprite_name)

checkpoint = sprite.get_checkpoint(checkpoint_id)

result = {
    "id": checkpoint.id,
    "create_time": checkpoint.create_time.isoformat().replace("+00:00", "
}
```

Sprites API v1

Examples:

```
print(json.dumps(result, indent=2))
```

stdout

Restore Checkpoint

POST /v1/sprites/{name}/checkpoints/{checkpoint_id}/restore

Restore to a specific checkpoint. Returns streaming NDJSON progress.

RESPONSE application/x-ndjson

StreamInfoEvent

type* "info"

data* String
Status message

time* DateTime
Timestamp

StreamErrorEvent

type* "error"

error* String
Error description

time* DateTime

Sprites API v1

Examples:

StreamCompleteEvent

type* "complete"

data* String

Completion message

time* DateTime

Timestamp

RESPONSE CODES

200	Success - Streaming NDJSON response
404	Not Found - Resource not found
500	Internal Server Error

example.py Python

```python
import json
import os

from sprites import SpritesClient

token = os.environ["SPRITE_TOKEN"]
sprite_name = os.environ["SPRITE_NAME"]
checkpoint_id = os.environ.get("CHECKPOINT_ID", "v1")

client = SpritesClient(token)
sprite = client.sprite(sprite_name)

stream = sprite.restore_checkpoint(checkpoint_id)

for msg in stream:
    print(json.dumps({"type": msg.type, "data": msg.data}))
```

stdout

Sprites API v1

Examples: