Sprites API v1

Examples: Python

Services

SPRITE-ENV v0.0.1-rc43

Manage background services running in your Sprite environment.

List Services

GET /v1/sprites/{name}/services

List all configured services and their current state.

RESPONSE application/json

- name* string
  Service name
- cmd* string
  Command to execute
- args* string
  Command arguments
- needs* string
  Service dependencies
- http_port number
  HTTP port for proxy routing
- state
  Current runtime state
  - name* string
    Service name
  - status* string

Sprites API v1

Examples:

`pid` number

Process ID when running

`started_at` string

ISO 8601 timestamp

`error` string

Error message if failed

RESPONSE CODES

200	Success
404	Not Found - Resource not found
500	Internal Server Error

example.py Python

```python
import json
import os

from sprites import SpritesClient

token = os.environ["SPRITE_TOKEN"]
sprite_name = os.environ["SPRITE_NAME"]

client = SpritesClient(token)
sprite = client.sprite(sprite_name)

services = sprite.list_services()

result = []
for svc in services:
    item = {"name": svc.name, "cmd": svc.cmd}
    if svc.state:
        item["status"] = svc.state.status
    result.append(item)

print(json.dumps(result, indent=2))
```

Sprites API v1

Examples:

Get Service

GET /v1/sprites/{name}/services/{service_name}

Get details of a specific service.

RESPONSE application/json

- name* string
  Service name
- cmd* string
  Command to execute
- args* string
  Command arguments
- needs* string
  Service dependencies
- http_port number
  HTTP port for proxy routing
- state
  Current runtime state
  - name* string
    Service name
  - status* string
    stopped, starting, running, stopping, or failed
  - pid number

Sprites API v1

Examples:

started_at string

ISO 8601 timestamp

error string

Error message if failed

RESPONSE CODES

200	Success
404	Not Found - Resource not found
500	Internal Server Error

example.py

Python

```python
import json
import os

from sprites import SpritesClient

token = os.environ["SPRITE_TOKEN"]
sprite_name = os.environ["SPRITE_NAME"]
service_name = os.environ["SERVICE_NAME"]

client = SpritesClient(token)
sprite = client.sprite(sprite_name)

svc = sprite.get_service(service_name)

result = {"name": svc.name, "cmd": svc.cmd}
if svc.state:
    result["status"] = svc.state.status

print(json.dumps(result, indent=2))
```

stdout

Sprites API v1

Examples:

PUT /v1/sprites/{name}/services/{service_name}

Create or update a service definition.

QUERY PARAMETERS

duration duration

Time to monitor logs after starting (default: 5s)

REQUEST BODY application/json

cmd* string

Command to execute

args* string

Command arguments

env map

Environment variables to add to the base service environment

dir string

Working directory for the service

needs* string

Service dependencies (started first)

http_port number

HTTP port for proxy routing

RESPONSE application/json

name* string

Service name

cmd* string

Command to execute

Sprites API v1

Examples:

needs* string

Service dependencies

http_port number

HTTP port for proxy routing

state

Current runtime state

name* string

Service name

status* string

stopped, starting, running, stopping, or failed

pid number

Process ID when running

started_at string

ISO 8601 timestamp

error string

Error message if failed

RESPONSE CODES

200	Success
400	Bad Request - Invalid request body
404	Not Found - Resource not found
500	Internal Server Error

example.py

Python

```python
import json
import os

from sprites import SpritesClient
from sprites.services import create_service
```

Sprites API v1

Examples:

```
sprite_name = os.environ["SPRITE_NAME"]
service_name = os.environ["SERVICE_NAME"]

client = SpritesClient(token)
sprite = client.sprite(sprite_name)

stream = create_service(
    sprite,
    name=service_name,
    cmd="python",
    args=["-m", "http.server", "8000"],
    http_port=8000,
)

for event in stream:
    print(json.dumps({"type": event.type, "timestamp": event.timestamp}))
```

stdout

Start Service

POST `/v1/sprites/{name}/services/{service_name}/start`

Start a service. Returns streaming NDJSON with stdout/stderr.

QUERY PARAMETERS

`duration` duration

Time to monitor logs after starting (default: `5s`)

RESPONSE application/x-ndjson

Sprites API v1

Examples:

type* "stdout"

data* String
Log line content

timestamp* integer
Unix milliseconds

ServiceLogStderrEvent

type* "stderr"

data* String
Log line content

timestamp* integer
Unix milliseconds

ServiceLogExitEvent

type* "exit"

exit_code* integer
Process exit code

timestamp* integer
Unix milliseconds

ServiceLogErrorEvent

type* "error"

data* String
Error message

timestamp* integer

Sprites API v1

Examples:

ServiceLogCompleteEvent

type* "complete"

timestamp* integer
Unix milliseconds

ServiceLogStartedEvent

type* "started"

timestamp* integer
Unix milliseconds

RESPONSE CODES

200	Success - Streaming NDJSON response
404	Not Found - Resource not found
500	Internal Server Error

example.py Python

```python
import json
import os

from sprites import SpritesClient
from sprites.services import start_service

token = os.environ["SPRITE_TOKEN"]
sprite_name = os.environ["SPRITE_NAME"]
service_name = os.environ["SERVICE_NAME"]

client = SpritesClient(token)
sprite = client.sprite(sprite_name)

stream = start_service(sprite, name=service_name)
```

Sprites API v1

Examples:

stdout

Stop Service

POST `/v1/sprites/{name}/services/{service_name}/stop`

Stop a running service. Returns streaming NDJSON with service stop progress.

QUERY PARAMETERS

`timeout` `duration`

Timeout waiting for service to stop (default: `10s`)

RESPONSE `application/x-ndjson`

`ServiceLogStoppingEvent`

`type*` `"stopping"`

`timestamp*` `integer`

Unix milliseconds

`ServiceLogStdoutEvent`

`type*` `"stdout"`

`data*` `String`

Log line content

`timestamp*` `integer`

Sprites API v1

Examples:

ServiceLogStderrEvent

type* "stderr"

data* String

Log line content

timestamp* integer

Unix milliseconds

ServiceLogErrorEvent

type* "error"

data* String

Error message

timestamp* integer

Unix milliseconds

ServiceLogStoppedEvent

type* "stopped"

exit_code* integer

Process exit code

timestamp* integer

Unix milliseconds

ServiceLogCompleteEvent

type* "complete"

timestamp* integer

Unix milliseconds

Sprites API v1

Examples:

404 Not Found - Resource not found

500 Internal Server Error

example.py Python

```python
import json
import os

from sprites import SpritesClient
from sprites.services import stop_service

token = os.environ["SPRITE_TOKEN"]
sprite_name = os.environ["SPRITE_NAME"]
service_name = os.environ["SERVICE_NAME"]

client = SpritesClient(token)
sprite = client.sprite(sprite_name)

stream = stop_service(sprite, name=service_name)

for event in stream:
    print(json.dumps({"type": event.type, "timestamp": event.timestamp}))
```

stdout

Restart Service

POST `/v1/sprites/{name}/services/{service_name}/restart`

Restart a service (stop if running, then start). Returns streaming NDJSON with stop and start progress.

QUERY PARAMETERS

Sprites API v1

Examples:

Time to monitor logs after starting (default: 0s)

RESPONSE application/x-ndjson

ServiceLogStoppingEvent

type* "stopping"

timestamp* integer

Unix milliseconds

ServiceLogStoppedEvent

type* "stopped"

exit_code* integer

Process exit code

timestamp* integer

Unix milliseconds

ServiceLogStdoutEvent

type* "stdout"

data* String

Log line content

timestamp* integer

Unix milliseconds

ServiceLogStderrEvent

type* "stderr"

data* String

Sprites API v1

Examples:

timestamp* integer

Unix milliseconds

ServiceLogExitEvent

type* "exit"

exit_code* integer

Process exit code

timestamp* integer

Unix milliseconds

ServiceLogErrorEvent

type* "error"

data* String

Error message

timestamp* integer

Unix milliseconds

ServiceLogCompleteEvent

type* "complete"

timestamp* integer

Unix milliseconds

ServiceLogStartedEvent

type* "started"

timestamp* integer

Unix milliseconds

Sprites API v1

Examples:

404 Not Found - Resource not found

500 Internal Server Error

bash

Python example unavailable HTTP

```bash
curl -X POST \
  "https://api.sprites.dev/v1/sprites/{name}/services/{service_name}/rest
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response

Get Service Logs

GET `/v1/sprites/{name}/services/{service_name}/logs`

Stream logs for a service.

QUERY PARAMETERS

`lines` `int`

Number of lines to return from log buffer (default: all)

`duration` `duration`

Time to follow new logs (default: `0`, no follow)

RESPONSE `application/x-ndjson`

`ServiceLogStdoutEvent`

`type*` `"stdout"`

Sprites API v1

Examples:

`timestamp*` `integer`

Unix milliseconds

`ServiceLogStderrEvent`

`type*` `"stderr"`

`data*` `String`

Log line content

`timestamp*` `integer`

Unix milliseconds

`ServiceLogExitEvent`

`type*` `"exit"`

`exit_code*` `integer`

Process exit code

`timestamp*` `integer`

Unix milliseconds

`ServiceLogErrorEvent`

`type*` `"error"`

`data*` `String`

Error message

`timestamp*` `integer`

Unix milliseconds

`ServiceLogCompleteEvent`

Sprites API v1

Examples:

timestamp* integer

Unix milliseconds

RESPONSE CODES

200 Success - Streaming NDJSON response

404 Not Found - Resource not found

500 Internal Server Error

bash

Python example unavailable HTTP

```bash
curl -X GET \
  "https://api.sprites.dev/v1/sprites/{name}/services/{service_name}/logs
  -H "Authorization: Bearer $SPRITES_TOKEN"
```

200 Response


```
[
  {
    "data": "Server started\n",
    "timestamp": 1735988400000,
    "type": "stdout"
  },
  {
    "data": "Handling request from 127.0.0.1\n",
    "timestamp": 1735988450000,
    "type": "stdout"
  },
  {
    "data": "Warning: slow query detected\n",
    "timestamp": 1735988455000,
    "type": "stderr"
  },
  {
    "log_files": {
      "stdout": "/.sprite/logs/services/webapp.log"
    },
```

Sprites API v1

Examples:

```
  ]
```